

Bass Management



Users Guide

Bass Management

🛎 M Audio Delta Control Pan	el								
Monitor Mixer Patchbay / Router	Hardware Settings	S/PDIF	Bas	s Man	ageme	nt 🛆	bout		
General Settings	Speaker freq. Resp	onse							Save
🔘 On Volume 🎴	Crossover Freq. (in Hz)	Off	40	60	80	90	100	120	Delete
⊙ Off -6.0 dB	Front	0	0	0	\odot	0	0	0	Load
PCM Limit 🔲 Mute 📃	Center	0	0	0	۲	0	0	0	
Sub Channel	Surrounds	0	0	0	۲	\bigcirc	0	0	H/W mistalied
Boost	Rear Surrounds	0	0	0	۲	0	0	0	● #1 1010
LFE +10dB 🗸 +180°	0 +12 Ciip Sub Mode (LFE + Main) Virtual 6.1 Virtual 7.1 0 #2								
- Speaker Placement									○ #3
Channel LF F	F C Sul	b L	6	RS	L	.RS	RF	is	O #4
Distance (1ft = 30 cm)	f 🔽 Off 🔽 Off	V Off	*	Off	v 0	lff 💊	 Off 	*	
Mute / Reroute									
									(AUDIO)
		D	one	٦					
		D	one						

About Bass Management:

Bass Management is a tool that is used to help surround speaker systems (i.e., systems featuring multiple "satellite" speakers paired with a subwoofer) reproduce the full spectrum of sound from surround-encoded material. This is done by taking your multi-channel source and re-routing the low frequency sounds from each of the satellite channels to the subwoofer. Doing so ensures that low-frequency sounds are heard even if they were originally routed to smaller satellite speakers that are not capable of reproducing low frequency sounds.

You will only need to take advantage of the Bass Management functions when using smaller satellite speakers that cannot reproduce low bass frequencies; If your main speakers are large enough to properly output low frequencies, Bass Management is not required and should remain off.

The M-Audio Bass Management system also includes several additional features that many users will find handy. These features include subwoofer loudness limiting (when adding rerouted main signal to the LFE, subwoofer phase inversion, and time-alignment on all channels.

Each section of the Bass Management system is covered in detail below.

Bass Management

The "General Settings" section sets global parameters for the Bass Management system.

- On/Off Bass Management is only active when the "On" radio button is selected. If the "Off" radio button is selected, all parameters of the Bass Management system will be deactivated.
- Volume This vertical slider adjusts the overall output level of all speakers at once. The output level of your interface is listed in "dB relative to full-scale" next

to the fader. This means that the loudest possible output level (i.e., when the fader is at the top) is referred to as "0dB" and a signal that is, for example, 12dB lower than the maximum loudness is referred to as "-12dB."

- PCM Limit When re-routing low frequency sounds from all of the satellite speakers to the subwoofer, it becomes possible to exceed the available headroom of the subwoofer channel. This will result in digital clipping (distortion). When the "PCM Limit" box is checked, the Bass Management system momentarily attenuates (reduces) the output volume when the signal exceeds the available digital headroom to prevent clipping.
- Mute This box mutes the output of all the speakers when checked.

The "Sub Channel" section contains volume and phase controls for the subwoofer channel.

- Boost (dB) This horizontal slider can be used to increase or decrease the subwoofer loudness by up to 12 dB in relation to the main channels. This is used to fine-tune the subwoofer level in relation to the rest of your speakers.
- LFE +10dB The subwoofer output is increased by an additional 10dB when this box is checked. The LFE output is left unaffected when the box is unchecked.
- Clip The Clip indicator is located next to the Boost slider and turns red when output to the subwoofer is too loud and is "clipping" or distorting.
- +180° This option inverts the phase of the signal sent to the subwoofer. Check the box to invert the subwoofer's signal; leave the box unchecked to let the signal pass unaffected.

• To set the +180° checkbox:

First, leave the box unchecked and listen to your sound system. Next, check the box and continue listening. If you notice that the bass level increases when you check the box, leave the box checked. If the bass level decreases, then leave this box unchecked. If you hear no difference between the two settings, your speakers are placed in a way in which the setting of this box will not affect your monitoring system.

TIP: When making any

no longer clips.

adjustments to the Boost controls,

it turns red, adjust the Boost slider

setting until the subwoofer output

keep an eye on the Clip indicator. If

monitoring of Dolby Digital soundtracks. Leave the box unchecked while monitoring DTS encoded material, or if subwoofer output has been boosted at another point in the subwoofer's signal path.

TIP: Check this box for correct



General Se	ettings	
🔿 On	Volume	7
📀 Off	-6.0 dB	
PCM Limit	Mute	

The "Speaker freq. Response" section allows you to configure crossover points and routing options for your sound system.

- Crossover Freq (in Hz) The Bass Management system re-routes low frequency sounds from main speaker channels to the subwoofer. These radio buttons allow you to set the "crossover" frequency at which the signal is split and sent to either the main channels (for use with satellite speakers) or subwoofer. For example, if "80" is selected (as shown in the picture), your interface will output frequencies above 80Hz to the specified main channels (where a smaller satellite speaker may be connected) while frequencies below 80Hz will be sent to the subwoofer. If the frequency is set to "Off," no bass re-routing will occur and the entire sound spectrum will be sent to the main channels.
- Sub Mode (LFE+Main) When checked, the bass management system routes frequencies below your Crossover Freq (in Hz) selection to both the main channels and the subwoofer. In other words, frequencies below the crossover points are not removed from the main speakers before being sent to the subwoofer. This increases the bass output of your sound system since bass will be duplicated at the main speakers and the subwoofer.

TIP: If you check this box and notice a reduction in bass levels or other phase-related issues (such as comb filtering), try changing the +180° setting in the Sub Channel section to see if the problem resolves.

nse							
Off	40	60	80	90	100	120	
0	0	0	\odot	0	0	0	
0	0	0	۲	0	0	0	
0	0	0	۲	0	0	0	
0	0	0	۲	0	0	0	
+ Main)	Virt	ual 6.1		Virtual	7.1	
	Off Off O O + Main	0 ff 40 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0ff 40 60 ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ ○ · + Main) □ Virt	Off 40 60 80 O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O O	Off 40 60 80 90 Image: Optimized state Image	Off 40 60 80 90 100 Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state Image: Optimized state	Off 40 60 80 90 100 120 Image: Optimized state Image

TIP: Consult your speaker's documentation to see if an optimum crossover point is specified for bass managed systems. If the documentation does not include this information, locate the speaker's frequency response rating (most documentation will list this information in a "Technical Specifications" section) and set your crossover point just above the speaker's low frequency limit.

For example, if the speaker's frequency response rating is "65 Hz – 20 kHz +/- 3 dB" this means that the lowest frequency that the speaker is designed to produce is 65 Hz. Therefore, select the next highest radio button above 65 Hz, which is 80 Hz in the Bass Management tab.

Virtual 6.1 and Virtual 7.1 – These two "virtual surround" checkboxes are for use when playing back 5.1 encoded surround material only. If you have a standard surround speaker set (consisting of 5 speakers and a subwoofer), leave these checkboxes empty. However, if your system has six or seven speakers and a sub (i.e., it is "6.1" or "7.1"), checking "Virtual 6.1" or "Virtual 7.1" will expand the original 5.1 source material to make use of all of your speakers.

NOTE: These checkboxes should be left unchecked if you are playing back true 6.1 or 7.1 sources such as Dolby Digital EX or DTS-ES encoded materials.

The "Speaker Placement" section allows you to fine-tune your surround monitoring system by setting the distance from each speaker to your listening position.

Speaker Placemer	nt							
Channel	LF	RF	С	Sub	LS	RS	LRS	RRS
Distance (1ft = 30 cm)	Off 🗸							
Mute / Reroute								

Distance (1ft = 30 cm) - In an ideal surround listening situation, all of the speakers should be equally distant from the listening position. If some of your speakers (such as the surround channels), are farther away from you than the remaining speakers (the front satellites, for example), sounds produced from the surround speakers will not reach your ears at the same time as sounds from the front speakers.

By selecting the speaker distances from the drop-down menus, the Bass Management system calculates the correct amount of delay compensation to add to each channel. This ensures that sounds from all speakers arrive at your ears at the same time. Λ

TIP: You can also use this feature if your video display timing lags behind the audio. By increasing the speaker distance setting for all speakers, you should be able to re-align video and audio synchronization to your satisfaction.

■ Mute / Reroute – Checking these boxes will mute the associated speaker channel.

If the center or subwoofer channels are muted, their audio signals will be re-routed to the left and right front speakers. This is a useful feature for mix engineers that would like to audition how a mix will sound on a system without a center channel or subwoofer.

NOTE: If the subwoofer channel is routed to the front speakers, the "Crossover Freq." for the front speakers must be set to "Off" for you to hear the low frequency sounds.



© 2007 Avid Technology, Inc. All rights reserved. Product features, specifications, system requirements and availability are subject to change without notice. Avid, M-Audio and Bass Management are either trademarks or registered trademarks of Avid Technology, Inc. All other trademarks contained herein are the property of their respective owners.

M-Audio USA 5795 Martin Rd., Irwindale, CA 91706		
Technical Support		
web:	www.m-audio.com/tech	
tel (pro products):	(626) 633-9055	
tel (consumer products):	(626) 633-9066	
fax (shipping):	(626) 633-9032	
Sales		
e-mail:	sales@m-audio.com	
tel:	I-866-657-6434	
fax:	(626) 633-9070	
Web	www.m-audio.com	

M-Audio U.K.

Floor 6, Gresham House, 53 Clarenden Road, Watford WD17 ILA, United Kingdom

Technical Support	
e-mail:	support@maudio.co.uk
tel:(Mac support):	+44 (0)1765 650072
tel: (PC support):	+44 (0)1309 671301
Sales	
tel:	+44 (0)1923 204010
fax:	+44 (0)1923 204039
Web	www.maudio.co.uk

M-Audio France			
Floor 6, Gresham House, 53 Clarenden Road, Watford WD17 ILA, United Kingdom			
Renseignements Commerciaux			
tel :	0 810 001 105		
e-mail :	info@m-audio.fr		
Assistance Technique			
PC :	0 820 000 731		
MAC :	0 820 391 191		
Assistance Technique			
e-mail :	support@m-audio.fr mac@m-audio.fr		
fax :	+33 (0)1 72 72 90 52		
Site Web	www.m-audio.fr		

M-Audio Germany Kuhallmand 34, D-74613 Ohringen, Germany **Technical Support** e-mail: support@m-audio.de +49 (0)7941 - 9870030 tel +49 (0)7941 98 70070 fax: Sales e-mail: info@m-audio.de tel: +49 (0)7941 98 7000 fax: +49 (0)7941 98 70070 Web www.m-audio.de

M-Audio Canada

1400 St-Jean Baptiste Ave.#150, Quebec City, Quebec G2E 5B7, Canada

Technical Support	
e-mail:	techcanada@m-audio.com
phone:	(418) 872-0444
fax:	(418) 872-0034
Sales	
e-mail:	infocanada@m-audio.com
phone:	(866) 872-0444
fax:	(418) 872-0034
Web:	www.m-audio.ca

M-Audio Japan アビッドテクノロジー株式会社 | エムオーディオ事業部:〒460-0002 愛知県名古屋市中区丸の内2-18-10 Avid Technology K.K.: 2-18-10 Marunouchi, Naka-Ku, Nagoya, Japan 460-0002 カスタマーサポート(Technical Support) e-mail : win-support@m-audio.jp e-mail (Macintosh 環境専用): mac-support@m-audio.jp 052-218-0859 (10:00~12:00/13:00~17:00) tel : セールスに関するお問い合わせ(Sales) info@m-audio.jp e-mail: tel: 052-218-3375 052-218-0875 fax: Web: www.m-audio.jp