



77.76MHz VCXO

DS4077

General Description

The DS4077 is an integrated voltage-controlled crystal oscillator (VCXO) module designed to provide reference clock generation in base stations, telecom/datacom, and wireless applications. The DS4077 is developed using a fundamental quartz crystal plus a unique integrated circuit design. The internal fundamental quartz crystal determines the frequency of operation. Custom frequencies are available. Contact the factory for availability.

The DS4077 is designed for use with applications requiring low phase noise and jitter. Jitter performance of better than 1ps RMS is achieved over the 12kHz to 80MHz range. Phase noise performance of better than -130dBc/Hz at 1kHz is achieved with this design.

Applications

- Clock-Data Recovery in Telecom/Datacom Applications
- Data Retiming
- Reference Clock Generation in Base Stations and Wireless Applications

Features


- 77.76MHz (fNOM) Frequency
- 3.135V to 3.465V Operation
- Low Jitter: < 1ps RMS
- ±69ppm Absolute Pull Range (APR)
- Output Options:
  - LVC MOS Output Buffer
  - LVDS Complementary Output Buffer
- Minimum ±110ppm Tuning Range (+25°C)
- 14mm x 9mm x 3.06mm Plastic LGA Package

Ordering Information


PART	TEMP RANGE	OUTPUT TYPE	FREQUENCY (fNOM) (MHz)	PIN-PACKAGE	TOP MARK*
DS4077L-0CN	-40°C to +85°C	LVC MOS	77.76	9 LGA	DS4077L-0CN
DS4077L-0DN	-40°C to +85°C	LVDS	77.76	9 LGA	DS4077L-0DN

\*The top mark includes an "N" for industrial temperature grade devices.

Pin Configuration



Block Diagram



# 77.76MHz VCXO

## ABSOLUTE MAXIMUM RATINGS

VC, V<sub>DD</sub>, LVCMOS, LVDSO+, LVDSO- Output .....-0.3V, +3.6V  
 Operating Temperature Range  
 (noncondensing) .....-40°C to +85°C  
 Junction Temperature .....+150°C  
 Thermal Resistance  
 Junction to Ambient .....91.06°C/W  
 Junction to Case .....44.51°C/W

Storage Temperature Range .....-55°C to +125°C  
 Soldering Temperature  
 (reflow, 2 passes max)....See IPC/JEDEC STD-020 Specification

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## ELECTRICAL CHARACTERISTICS

(V<sub>DD</sub> = 3.135V to 3.465V, T<sub>A</sub> = -40°C to +85°C, unless otherwise noted.) (Typical values at +25°C, V<sub>DD</sub> = 3.3V, unless otherwise noted.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
V <sub>DD</sub> Operating Supply Range	V <sub>DD</sub>		3.135	3.3	3.465	V
V <sub>DD</sub> Supply Current	I <sub>DD</sub>	Output open		20	30	mA
Frequency	f <sub>OUT</sub>	VC = 1.6V, V <sub>DD</sub> = 3.3V, T <sub>A</sub> = +25°C (Note 2)	f <sub>NOM</sub> -8ppm	f <sub>NOM</sub>	f <sub>NOM</sub> +8ppm	MHz
Frequency vs. V <sub>DD</sub> Sensitivity	V <sub>DD</sub> ppm	V <sub>DD</sub> = 3.3V ±5%	-3.5		+11.5	ppm/pF
Frequency vs. Load Sensitivity	LOADpmm	10pF to 20pF (Note 3)		-1		ppm
Frequency vs. Temperature	TEMPppm	From +25°C	-20		+20	ppm
VC Voltage Range	VC <sub>RANGE</sub>		0.3	1.60	2.8	V
Frequency Tuning Sensitivity	VC <sub>SEN</sub>		41		164	ppm/V
Tuning Voltage Bandwidth	VC <sub>BW</sub>	(Note 3)	10			kHz
Absolute Pull Range	f <sub>TUNE</sub>	VC = 0.3V to 2.8V (Note 2)	-69		+69	ppm
VC Input Leakage	I <sub>LCV</sub>	VC = 0V to V <sub>DD</sub>	-500		+500	nA
Aging, First Year	AGEppm		-5		+5	ppm
Aging, Years 0-10	t <sub>AGE</sub>	Total aging	-10		+10	ppm
<b>LVDS OUTPUT</b>						
Output High Voltage	VOHLVDSO	(Note 4)			1.475	V
Output Low Voltage	VOLLVDSO	(Note 4)	0.925			V
Differential Output Voltage	VODLVDSO	(Note 4)	250		400	mV
Output Common-Mode Variation	VLVDSOCOM	(Note 4)			150	mV
Offset Output Voltage	VOFFLVDSO	(Note 4)	1.125		1.275	V
Differential Output Impedance	ROLVDSO	(Note 3)	80		140	Ω
Output Current	IvSSLVDSO	Short ground			40	mA
Output Current	ILVDSO	Short together (Note 3)			12	mA
Output Rise Time (Differential)	t <sub>RLVDSO</sub>	20% to 80% (Note 3)	150			ps
Output Fall Time (Differential)	t <sub>FLVDSO</sub>	80% to 20% (Note 3)	150			ps

# 77.76MHz VCXO

## ELECTRICAL CHARACTERISTICS (continued)

( $V_{DD} = 3.135V$  to  $3.465V$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ , unless otherwise noted.) (Typical values at  $+25^{\circ}C$ ,  $V_{DD} = 3.3V$ , unless otherwise noted.) (Note 1)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>LVC MOS OUTPUT</b>						
Output Logic 0	$V_{OL}$	Output Current $-450\mu A$	0		0.4	V
Output Logic 1	$V_{OH}$	Output Current $+450\mu A$	$V_{DD} - 0.8V$		$V_{DD}$	V
Output Rise Time	$t_R$	Load condition: 10pF to ground; 10% to 90% $V_{DD}$ (Note 3)			2	ns
Output Fall Time	$t_F$	Load condition: 10pF to ground; 90% to 10% $V_{DD}$ (Note 3)			2	ns
Duty Cycle	DCYC	Load condition: 10pF, $V_{DD} / 2$ (Note 3)	40		60	%
Harmonics	H	$V_{DD} = 3.3V$ , $T_A = +25^{\circ}C$ (Note 3)		-18	-8	dBc/Hz
<b>SSB PHASE NOISE AND JITTER, <math>V_{DD} = 3.3</math>, <math>T_A = +25^{\circ}C</math> (Note 3)</b>						
10Hz Offset		LVC MOS		-74		dBc/Hz
100Hz Offset				-105		
1kHz Offset				-130		
10kHz Offset				-147		
100kHz Offset				-150		
Jitter (12kHz to 80MHz)				1		psRMS

**Note 1:** Limits at  $-40^{\circ}C$  are guaranteed by design and not production tested.

**Note 2:** 10pF, LVC MOS.

**Note 3:** Guaranteed by design and not production tested.

**Note 4:** 100 $\Omega$  differential load.




## Pin Description

PIN		NAME	FUNCTION
LVC MOS	LVDS		
1	1	VC	VCXO Control Voltage
2, 5, 7, 8, 9	2, 7, 8, 9	N.C.	No Connection
3	3	$V_{SS}$	Ground
4	—	LVC MOS	LVC MOS Output
6	6	$V_{DD}$	DC Power
—	4, 5	LVDSO+/LVDSO-	LVDS Positive and Negative Outputs

# 77.76MHz VCXO

## Typical Operating Characteristics

( $V_{CC} = +3.3V$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



## Package Information

(For the latest package information, go to [www.maxim-ic.com/DallasPackInfo](http://www.maxim-ic.com/DallasPackInfo) and click on package drawing 56-G6034-001.)

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

4 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 2005 Maxim Integrated Products

Printed USA

**MAXIM**

is a registered trademark of Maxim Integrated Products, Inc.

**DALLAS** SEMICONDUCTOR is a registered trademark of Dallas Semiconductor Corporation.