

TD62164BP, TD62164BF

4ch HIGH-CURRENT DARLINGTON SINK DRIVER

The TD62164BP and TD62164BF are high-voltage, high-current darlington drivers comprised of four NPN darlington pairs.

All units feature integral clamp diodes for switching inductive loads.


Applications include relay, hammer, lamp and stepping moter drivers.

FEATURES


- Two V_{CC} Terminals (Separated)
- Package Type BP : DIP16 pin
BF : PFP16 pin
- High Sustaining Voltage output : $V_{CE(SUS)} = 80V$ (Min.)
- Output Current (Single Output) : $I_{OUT} = 700mA / ch$ (Max.)
- Output Clamp Diodes
- Input Compatible with TTL and 5V CMOS
- GND and SUB Terminal Heat Sink

PIN CONNECTION (TOP VIEW)


TD62164BP



TD62164BF




TD62164BP



DIP16-P-300-2.54A

TD62164BF




HSOP16-P-300-1.00

Weight

DIP16-P-300-2.54A : 1.11g (Typ.)
HSOP16-P-300-1.00 : 0.50g (Typ.)

SCHEMATICS (EACH DRIVER)



Note: The input and output parasitic diodes cannot be used as clamp diodes.

961001EBA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V _{CC}	− 0.5~17	V
Output Sustaining Voltage	V _{CE (SUS)}	− 0.5~80	V
Output Current	I _{OUT}	700	mA/ch
Input Current	I _{IN}	50	mA
Input Voltage	V _{IN}	17	V
Clamp Diode Reverse Voltage	V _R	80	V
Clamp Diode Forward Current	I _F	700	mA
Power Dissipation	BP	1.47 / 2.7 *1	W
	BF	0.9 / 1.4 *2	
Operating Temperature	T _{opr}	− 40~85	°C
Storage Temperature	T _{stg}	− 55~150	°C

*1 On Glass Epoxy PCB (50×50×1.6mm Cu 50%)

*2 On Glass Epoxy PCB (60×30×1.6mm Cu 30%)

RECOMMENDED OPERATING (Ta = − 40~85°C)








CHARACTERISTIC	SYMBOL	CONDITION	MIN.	TYP.	MAX	UNIT
Supply Voltage	V _{CC}		4.5	—	5.5	V
Output Sustaining Voltage	V _{CE (SUS)}		0	—	80	V
Output Current	I _{OUT}	DC1 Circuit, Ta = 25°C	0	—	570	mA/ch
		T _{pw} = 25ms	0	—	570	
		4 Circuits	0	—	520	
		Ta = 85°C	0	—	570	
		T _j = 120°C	0	—	270	
Input Voltage	V _{IN}		0	—	15	V
	Output On	I _{OUT} = 500mA	10.0	—	15	V
	Output Off		0	—	0.4	
			0	—	0.4	
Input Current	I _{IN}		0	—	20	mA
Clamp Diode Reverse Voltage	V _R		—	—	80	V
Clamp Diode Forward Voltage	I _F		—	—	700	mA
Power Dissipation	BP	Ta = 85°C *1	—	—	1.4	W
	BF	Ta = 85°C *2	—	—	0.7	

*1 On Glass Epoxy PCB (50×50×1.6mm Cu 50%)

*2 On Glass Epoxy PCB (60×30×1.6mm Cu 30%)

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CIR-CUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Leakage Current		I_{CEX}	1	$V_{CE} = 80V, T_a = 25^\circ C$	—	—	50	μA
				$V_{CE} = 80V, T_a = 85^\circ C$	—	—	100	
Output Saturation Voltage		$V_{CE(sat)}$	2	$I_{OUT} = 500mA, V_{CC} = 5V$	—	—	0.8	V
				$I_{OUT} = 200mA, V_{CC} = 5V$	—	—	0.45	
DC Current Transfer Ratio		h_{FE}	2	$V_{CE} = 2V, I_{OUT} = 500mA$	2000	—	—	
Input Voltage (Output On)		$V_{IN(ON)}$	3	$I_{OUT} = 500mA, h_{FE} = 150$	7.0	—	10.0	V
				$I_{OUT} = 500mA, h_{FE} = 2000$	1.8	—	2.4	
Clamp Diode Leakage Current		I_R	4	$V_R = 80V, T_a = 25^\circ C$	—	—	50	μA
				$V_R = 80V, T_a = 85^\circ C$	—	—	100	
Clamp Diode Forward Voltage		V_F	5	$I_F = 500mA$	—	—	2.0	V
Supply Current	Output On	$I_{CC(ON)}$	3	$V_{CC} = 5.5V, V_{IN} = 2.4V$	—	35	40	mA/ch
	Output Off	$I_{CC(OFF)}$		$V_{CC} = 5.5V, V_{IN} = 0.4V$	—	—	10	μA
Input Capacitance		C_{IN}	6	$V_{IN} = 0, f = 1MHz$	—	15	—	pF
Turn-On Delay		t_{ON}	7	$V_{OUT} = 80V, R_L = 125\Omega$	—	0.2	0.4	μs
Turn-Off Delay		t_{OFF}		$T_a = 60^\circ C, V_{CC} = 5.0V, C_L = 15pF$	—	4.0	8.0	






TEST CIRCUIT
1. I_{CEX}

2. h_{FE} , $V_{CE(sat)}$

3. $I_{IN(ON)}$

4. I_R

5. V_F

6. $I_{CC(ON)}$, $I_{CC(OFF)}$

7. t_{ON} , t_{OFF}






(Note 1) Pulse Width $50\mu s$, Duty Cycle 10%
Output Impedance 50Ω , $t_r \leq 5ns$, $t_f \leq 10ns$

(Note 2) C_L includes probe and jig capacitance

PRECAUTIONS for USING


Utmost care is necessary in the design of the output line, V_{CC} , COMMON and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.





OUTLINE DRAWING
DIP16-P-300-2.54A

Unit : mm





Weight : 1.11g (Typ.)

OUTLINE DRAWING

HSOP16-P-300-1.00

Unit : mm



Weight : 0.50g (Typ.)