

PARALLEL PRINTER CABLES

- All printer cables have a minimum of 25 conductors
- Heavy duty mylar foil shielding
- Molded connectors with built in strain relief
- Cables use 28 AWG stranded cable
- Maximum run length is 50'



CEN36 (F)

Parallel Extension Cables

- All 36 pin wired straight through
- Heavy duty mylar foil shield
- Molded connectors

Parallel Extension Cable CEN36 (M)
CEN36 (M) 6'

Cat. No. 45-0700-0000

Parallel Extension Cable CEN36 (M)
CEN36 (M) 10'


Cat. No. 45-0705-0000

Parallel Extension Cable CEN36 (M)
CEN36 (F) 6'

Cat. No. 45-0710-0000

Parallel Extension Cable CEN36 (M)
CEN36 (F) 10'

Cat. No. 45-0715-0000



IDC25 (M)

Lap-Top Parallel Printer Cable

- 28 AWG flat ribbon cable
- Lightweight for use with PC portables

DB25 (M)/CEN36 (M)

Cat. No. 45-0250-0000

Package of 1

Cat. No. 45-0250-00BU



IDC CEN36 (M)

Print Adapters

DB25 (F)/CEN36 (F)

Cat. No. 45-0595-0000

Cat. No. 45-0595-00BU

DB25 (M)/CEN36 (F)

Cat. No. 45-0597-0000

Cat. No. 45-0597-00BU

DB25 (F)/CEN36 (M)

Cat. No. 45-0598-0000

Cat. No. 45-0598-00BU



45-0597-0000



45-0598-0000



DB25 (M)

Standard Parallel Printer Cables

- All cables fully wired with 25 conductors
- Premium quality cables have double shielding & lifetime warranty
- All high quality computer cables have a 5 year warranty

Premium Quality

Parallel Printer Cables DB25 (M)/
CEN36 (M) 7'

Cat. No. 45-4424-0000

High Quality

Parallel Printer Cables DB25 (M)/
CEN36 (M) 2'

Cat. No. 45-0202-0000

Parallel Printer Cables DB25 (M)/
CEN36 (M) 6'

Cat. No. 45-0201-0000

Parallel Printer Cables DB25 (M)/
CEN36 (M) 10'

Cat. No. 45-0204-0000

Parallel Printer Cables DB25 (M)/
CEN36 (M) 25'

Cat. No. 45-0206-0000

90° Parallel Printer Cables DB25 (M)/
CEN36 (M) 6'

Cat. No. 45-0210-0000

90° Parallel Printer Cables DB25 (M)/
CEN36 (M) 10'

Cat. No. 45-0213-0000

U/L Listed Parallel Printer Cables
DB25 (M)/CEN36 (M) 6'

Cat. No. 45-0231-0000

U/L Listed Parallel Printer Cables
DB25 (M)/CEN36 (M) 10'

Cat. No. 45-0234-0000

Parallel Printer Cables DB25 (M)/
CEN36 (M) 15'

Cat. No. 45-0381-0000



CEN36 (M)



90° CEN36 (M)