PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (<u>http://www.projector.com</u>) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.

proxima

In Focus Corporation: 27700B SW Parkway Avenue • Wilsonville , Oregon 97070-9215 Phone: 503-685-8888 • 1-800-294-6400 • Fax: 503-685-8887

In Europe: Olympia I • NL-1213 NS Hilversum, The Netherlands Phone: (31) 35 6474000 • Fax: (31) 35 6423999 Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: 238A Thomson Road • #18-01/04 Novena Square Singapore 307684 • Telephone: (65) 334-9005 • Fax: (65) 334-4525

User's Guide 010-0298-00



Part No.010-0298-00 DP6860 User's Manual.qxd Printed in Japan

QR50271



Liquid Crystal Projector USER'S GUIDE

Thank you for purchasing this liquid crystal projector.

MARNING • Please read the accompanying manual "SAFETY INSTRUCTIONS" and this "USER'S GUIDE" thoroughly to ensure correct usage through understanding. After reading, store this instruction manual in a safe place for future reference.

NOTE • The information in this manual is subject to change without notice.

- The manufacturer assumes no responsibility for any errors that may appear in this manual
- The reproduction, transmission or use of this document or contents is not permitted without express written authority.

TRADEMARK ACKNOWLEDGMENT : PS/2, VGA and XGA are registered trademarks of International Business Machines Corporation. Apple, Mac and ADB are registered trademarks of Apple Computer, Inc. VESA and SVGA are trademarks of the Video Electronics Standard Association. Windows is a registered trademark of Microsoft Corporation. Carefully observe the trademarks and registered trademarks of all companies, even when not mentioned.

CONTENTS

EEATUDES	raye
REFORE USE	ے 2
Contents of Package	2
Part Names	3
Loading the Batteries	5
INSTALLATION	6
Installation of the Projector and Screen	6
Angle Adjustment	6
Cabling	7
Power Connection	8
Example of System Setup	8
Plug & Play	8
OPERATIONS	9
Power On	9
Power Off	∩
	9
Basic Operation	9
Basic Operation Setup Menu	9 10 12
Basic Operation Setup Menu Input Menu	10 12 13
Basic Operation Setup Menu Input Menu Image Menu	10 12 13 14
Basic Operation Setup Menu Input Menu Image Menu Options Menu	10 12 13 14 15
Basic Operation Setup Menu Input Menu Image Menu Options Menu No Signal Menu	10 12 13 14 15 16
Basic Operation Setup Menu Input Menu Image Menu Options Menu No Signal Menu MAINTENANCE	10 12 13 14 15 16 17
Basic Operation Setup Menu Input Menu Image Menu Options Menu No Signal Menu MAINTENANCE Lamp Air Filter	10 12 13 14 15 16 17 17
Basic Operation Setup Menu Input Menu Image Menu Options Menu No Signal Menu MAINTENANCE Lamp Air Filter Other Maintenance	

	Page
TROUBLESHOOTING	20
OSD Message	20
Indicators Message	21
Symptom	22
SPECIFICATIONS	23
WARRANTY AND AFTER-SERVICE	24

TABLES

TADLLO	
Table 1. Installation Reference	6
Table 2. Cabling	7
Table 3. Basic Operations	10
Table 4. Setup Menu	12
Table 5. Input Menu	13
Table 6. Image Menu	14
Table 7. Options Menu	15
Table 8. No Signal Menu	16
Table 9. OSD Message	20
Table 10. Indicator Message	21
Table 11. Symptom	22
Table 12. Specifications	23

For "TECHNICAL" and "REGULATORY NOTICE", see the end of this manual.

FEATURES

This liquid crystal projector is used to project various computer signals as well as NTSC / PAL / SECAM video signals onto a screen. Little space is required for installation and large images can easily be realized.

Outstanding Brightness

The UHB lamp and high-efficiency optical system assure a high level of brightness.

Partial Magnification Function

Interesting parts of images can be magnified for closer viewing.

Distortion Correction Function

Distortion-free images are quickly available.

BEFORE USE

Contents of package

Make sure all of the following items are included in the package. If anything is missing, please contact your dealer.

NOTE • Keep the original packing material for future reshipment.



Before USE ([continued])

Part Names



ENGLISH

Before USE (continued))

Part Names (continued)



REMOTE CONTROL TRANSMITTER

(Refer to P.9 "OPERATIONS")

These functions works when the mouse control function is activated. Remember, the POSITION, BLANK ON and MENU ON functions disable the mouse control function.

▲ WARNING • The laser pointer of the remote control transmitter is used in place of a finger or rod. Never look directly into the laser beam outlet or point the laser beam at other people. The laser beam can cause vision problems.



NOTE To prevent any malfunction;

- Do not give the remote control transmitter any physical impact. Take care not to drop.
- Do not place the heavy objects on the remote control transmitter.
- Do not wet the remote control transmitter or place it on any wet object.
- Do not place the remote control transmitter close to the cooling fan of the projector.

• Do not disassemble the remote control transmitter in case of malfunction. Please bring it to the service station.

Loading the Batteries

Install the AA batteries into the remote control transmitter.

- 1. Remove the battery cover.
 - Push the knob while lifting up the battery cover.
- Load the batteries. Make sure the plus and minus poles are correctly oriented.
- 3. Close the battery cover.



▲ <u>CAUTION</u> • Use only the specified batteries with this remote control transmitter. Also, do not mix new and old batteries. This could cause battery cracking or leakage, which could result in fire or personal injury.

• When loading the batteries, make sure the plus and minus terminals are correctly oriented as indicated in the remote control transmitter. Incorrect orientation could cause battery cracking or leakage, which could result in personal injury or pollution of the surrounding environment.

• When you dispose the battery, you obey the law in the relative area or country.

• Keep the battery away from children and pets.

• When not to be used for an extended period, remove the batteries from the remote control transmitter.

NOTE Replace the batteries when remote control transmitter operation becomes difficult.

INSTALLATION

Installation of the Projector and Screen

Refer to the drawing and table below for determining of the screen size and projection distance.

Screen

The projection distances shown in the table below are for full size $(1024 \times 768 \text{ dots})$.

- **a**: Distance from the projector to the screen. $(\pm 10\%)$
- **b**: Distance from the lens center to the bottom of the screen. (±10%)

Table 1. Installation Reference



▲ <u>CAUTION</u> • Install the projector in a suitable environment according to instructions of the accompanying manual "SAFETY INSTRUCTIONS" and this manual.

• Please basically use liquid crystal projector at the horizontal position. If you use liquid crystal projector by the lens up position, the lens down position and the side up position, this may cause the heat inside to build up and become the cause of damage. Be especially careful not to install it with ventilation holes blocked.

• Do not install LCD projector in smoke effected environment. Smoke residue may buildup on critical parts (i.e.LCD panel, Lens Assy etc.).

Angle Adjustment

Use the foot adjusters on the bottom of the projector to adjust the projection angle. It is variable within 0° to 9° approximately.

- 1. Lift up the front side of the projector, and pressing the foot adjuster button, adjust the projection angle.
- 2. Release the button to lock at the angle to be fixed.
- 3. Make the foot adjusters screw for fine adjustment. Do not force the adjusters to make screw. This could damage the adjusters or cause the lock to fail.



Top View

Side View

Variable within the range of approximately 0° - 9°

▲ <u>CAUTION</u> • Do not release the foot adjuster button unless the projector is being held; otherwise, the projector could overturn or the fingers could get caught and cause personal injury.

Cabling

Refer to the table below for connecting each terminal of the projector to each device. **Table 2. Cabling**

Function	Terminal	Cable	
Analag DCD input	RGB IN 1	Accessony BGB cable or optional BGB	
Апаюд КСВ прис	RGB IN 2	cable with D-sub 15-pin shrink jack and	
Analog RGB output	RGB OUT	inch thread screws	
Digital RGB input	DIGITAL	Optional digital RGB cable with inch thread screws	
Audio input	AUDIO IN [RGB 1] / [DIGITAL] (interlocked with RGB IN 1 or DIGITAL)	Optional audio cable with stereo mini jack	
(from the computer)	AUDIO IN [RGB 2] (interlocked with RGB IN 2)		
PS/2 mouse control		Accessory PS/2 mouse cable	
ADB mouse control		Optional ADB mouse cable	
Serial mouse control	CONTROL	Optional Serial mouse cable	
RS-232C communication	_	Optional RS-232C cable	
USB mouse control	USB	Optional USB cable	
S-video input	S-VIDEO	Optional S-video cable with mini DIN 4-pin jack	
Video input	VIDEO	Accessory video/audio cable	
	COMPONENT VIDEO Y		
Component video input	COMPONENT VIDEO CB/PB	Accessory component video cable	
	COMPONENT VIDEO CR/PR		
Audio input	AUDIO (MONO)/L	Accessory video/audio cable or optional	
(from video equipment)	AUDIO R	audio cable with RCA jack	
Audio output	AUDIO OUT	Optional audio cable with stereo mini jack	

▲ <u>CAUTION</u> • Incorrect connecting could result in fire or electrical shock. Please read this manual and the separate "SAFETY INSTRUCTIONS". • Before connecting, turn off to all devices to be connected, except for the USB cable.

• The cables may have to be used with the core set to the projector side. Use the cables which are included with the projector or specified.

NOTE • Before connecting, read instruction manuals of the devices to be connected, and make sure that the projector is compatible with the device.

• Secure the screws on the connectors and tighten.

• For some RGB input modes, the optional Mac adapter is necessary.

• To select the digital RGB input, the computer may need some settings. See the manuals of the computer for details.

• Some computers may have multiple display screen modes. Use of some of these modes will not be possible with this projector.

• Refer to the "TECHNICAL" section for the pin assign of connectors and RS-232C communication data.

• When the DIGITAL terminal is used, the RGB OUT terminal may not function.

INSTALLATION (continued)

Power Connection

Use the correct one of the enclosed power cords depending on the power outlet to be used. Connect the AC inlet of the projector to the power outlet firmly by the power cord.



NOTE • When connecting with notebook computer, set to valid the RGB external image output (setting CRT display or simultaneous display of LCD and CRT). Please read instruction manual of the notebook for more information.

Plug & Play

This projector is VESA DDC 1/2B compatible. Plug & play is possible by connecting to a computer that is VESA DDC (Display Data Channel) compatible.

Please use this function by connecting the accessory RGB cable with RGB IN 1 terminal (DDC 1/2B compatible), or by connecting an optional digital RGB cable with DIGITAL terminal (DDC 2B compatible). Plug & play may not operate by other connecting.

NOTE • Plug & play is a system configured with peripheral equipment including a computer and display, and an operating system.

• This projector is recognized as a plug & play monitor. Use the standard display drivers.

• Plug & play may not operate by the computer to connect. Plug & play will not operate in the connection with Apple computer.

OPERATIONS



Power ON

- 1. Check that the power cord is connected correctly.
- 2. Set the power switch to [1]. The standby mode is selected, and the POWER indicator is turned to orange.
- 3. Press the STANDBY/ON button (1) on the control panel or the remote control transmitter. Warm-up begins and the POWER indicator blinks in green.
- 4. The POWER indicator ceases blinking and turns to green when power is on. Remove the lens cap.
- 5. Adjust picture size using the ZOOM button.
- 6. Adjust focus using the FOCUS button .

Power OFF

- 1. Press the STANDBY/ON button () on the control panel or the remote control transmitter for approximately 2 seconds. The projector lamp is extinguished and lamp cooling begins. The POWER indicator blinks orange during lamp cooling. Pressing the STANDBY/ON button () has no effect while the POWER indicator is blinking.
- 2. The system assumes the Standby mode when cooling is complete, and the POWER indicator ceases blinking and changes to orange. Check that the indicator is orange and set the Power switch to [O].
- 3. The POWER indicator is extinguished when power is off. Attach the lens cap.

$\underbrace{ \mbox{WARNING}}_{\mbox{INSTRUCTIONS"}} \bullet \mbox{Please read this manual, and the separate "SAFETY INSTRUCTIONS" thoroughly before using the equipment. Always ensure that the equipment is used safely. }$

NOTE • Except in emergencies, do not turn off unless the POWER indicator is orange as it will reduce the life of the projector lamp.

• To prevent any troble, turn on/off the projector when the computer or video tape recorder is OFF. Providing a RS-232C cable is connected, turn on the computer before the projector.

Basic Operation

The basic operations shown in Table 3 is performed from the supplied remote control transmitter or the projector control panel. Items indicated by (*) may be used from the control panel.

Table 3 . Basic Operation

Item	Description
INPUT SELECT	Select Input Signal (*) : Press the INPUT button.RGB IN 1 → RGB IN 2 → DIGITAL→ VIDEO → S-VIDEO → COMPONENT VIDEO (→ RGB IN 1)Select RGB Input : Press the RGB button.VIDEO/S-VIDEO/COMPONENT VIDEO → RGB IN 1/RGB IN 2/DIGITALRGB IN 1 → RGB IN 2 → DIGITAL (→ RGB IN 1)Select Video Input : Press the VIDEO button.RGB IN 1/RGB IN 2/DIGITAL → VIDEO/S-VIDEO/COMPONENT VIDEOVIDEO → S-VIDEO → COMPONENT VIDEO (→ VIDEO/COMPONENT VIDEOVIDEO → S-VIDEO → COMPONENT VIDEO (→ VIDEO)• The selected signal name is displayed for approximately 3 seconds when the input signal is changed.
POSITION	 Set/Clear Position Adjustment Mode : Press the POSITION button. The [□] icon is displayed in the POSITION mode. Image Position Adjustment: Press the , , and buttons in the POSITION mode. Valid only in the MAGNIFY mode with a video signal is input. After approximately 10 seconds of inactivity the [□] icon is extinguished and the POSITION mode is cleared automatically. , , and , buttons may operate as the mouse control button. Refer to page 4.
RESET (*)	 Initialise Each Item : Select an item and press the RESET button. Initialise Position Adjustment : Press the RESET button and the POSITION mode. This function is valid only when RGB signal is input. Valid except for the VOLUME, LANGUAGE and H PHASE. The RESET button may operate as the mouse control button. Refer to page 4.
MAGNIFY	 Set MAGNIFY Mode : Press the MAGNIFY ⊕ button. Move Magnified Area : Run the POSITION in the MAGNIFY mode. Adjust Magnification : Press the MAGNIFY ⊕ /
FREEZE	 Set/Clear FREEZE Mode : Press the FREEZE button. The [11] icon is displayed, and the image frozen, in the FREEZE mode. The FREEZE mode is cleared by running or setting POSITION, VOLUME, MUTE, Automatic Adjustment, BLANK ON/OFF, or MENU ON/OFF, or by changing the input signal. Do not forget to clear frozen static images.

NOTE • Use the remote control transmitter at a distance of approximately 5m from the sensor on the front of the projector, and within a range of 30° left-right. Strong light and obstacles will interfere with operation of the remote control transmitter.

Items indicated by (*) may be used from the control panel.

Table 3. Basic Operation (continued)

Item	Description		
VOLUME	Volume Adjustment : Press the VOLUME \odot / \odot button.		
MUTE (*)	Set/Clear Mute Mode : Press the MUTE button. No sound is heard in the MUTE mode.		
AUTO	Automatic Adjustment at RGB Input : Press the AUTO button. Horizontal position(H.POSIT), vertical position (V.POSIT), clock phase (H.PHASE), and horizontal size(H.SIZE) are automatically adjusted. Use with the window at maximum size in the application display. Automatic Adjustment at Video Input : Press the AUTO button. A signal type appropriate for the input signal is selected automatically. Valid only when AUTO is set for VIDEO on the menu. • This operation requires approximately ten seconds. It may not function correctly with some input signals.		
BLANK ON/OFF	Set/Clear Blank Mode: Press the BLANK button. No image is displayed in the Blank mode. The screen color is as set in BLANK on the Image menu.		
MENU ON/OFF (*)	Menu Display Start/Stop: Press the MENU button. • The menu display is terminated automatically after approximately ten seconds of inactivity.		
MENU SELECT	 Select Menu Type: Press the MENU SELECT button. Allows the user to select the normal menu or the single menu. Only the selected item is displayed on the single menu, and other items are displayed with the and buttons as with the normal menu. Valid only when the Setup menu is used. Push the MENU SELECT button after selecting items such as "BRIGHTNESS". The MENU SELECT button may operate as the mouse control button. Refer to page 4. Mormal menu (MENU SELECT) 		
P.IN P. MODE	Select Mode of P.IN P. Display : Press the PinP button. Small → Large → P.IN P. off (→ Small) • Valid only at RGB IN 1, RGB IN 2 or DIGITAL input.		
ZOOM	Adjust Screen Size : Press the ZOOM \oplus / \oplus button.		
FOCUS	Adjust Focus : Press the FOCUS \oplus / \oplus button.		

operations (continued)

Setup Menu

The following adjustments and settings are possible when SETUP is selected at the top of the menu. Part of the Setup menu differs between RGB input and video input. Select an item with the and buttons, and start operation. Use the Single menu to reduce menu size (see Table 3, MENU SELECT).

Table 4. Setup Menu





RGB IN 1 **RGB IN 2** DIGITAL



Item	Description	RGB IN 1 RGB IN 2	DIGTAL	VIDEO S-VIDEO COMPONENT
BRIGHT	Adjustment: Dark	~	~	~
CONTRAST	Adjustment: Weak $ \leftrightarrow $ Strong	~	~	~
V POSIT	Adjustment: Down	~	-	-
H POSIT	Adjustment: Left	~	-	-
H PHASE	Adjustment: Left	~	-	-
H SIZE	Adjustment: Small → Large • The image may not be displayed correctly if the horizontal size is excessive. In such cases, press the RESET button, and initialize the horizontal size.	~	-	-
SHARPNESS	Adjustment: Soft	-	-	~
COLOR	Adjustment: Light	-	-	~
TINT	Adjustment: Red	-	-	V
COLOR BAL R	Adjustment: Light	~	~	~
COLOR BAL B	Adjustment: Light	~	~	~
ASPECT	Select Image Aspect Ratio : $4:3[\begin{aligned} \begin{aligned} \label{eq:select} 16:9[\begin{aligned} \label{eq:select} \label{eq:select} 16:9[\begin{aligned} \label{eq:select} \label{eq:select} \end{aligned} \end{aligned} \end{aligned} \end{aligned} \end{aligned} \end{aligned} \begin{aligned} \label{eq:select} Select Position of Image: \\ \begin{aligned} \label{eq:select} \label{eq:select} \end{aligned} aligned$	r	v	-
	Select Image Aspect Ratio: $4:3[\] @ \leftrightarrow @ 16:9[\] @ \leftrightarrow @ 4:3 small[\]]$ Select Position of Image : Press the $@$ button while $16:9[\] @] / 4:3 small[\]]$ is selected. Center $\rightarrow @$ Down $\rightarrow @$ Up (\rightarrow Center $@$) • 4:3 small may not be displayed correctly with some input signals.	-	-	v

Input Menu

The following functions are available when INPUT is selected on the menu. Select an item with the (\square) and (\bigcirc) buttons, and start or stop operation with the (\bigcirc) and (\bigcirc) buttons. The functions indicated (**) are effective on video input mode only, not on RGB input mode, except in the P.IN P. window on RGB input mode.

SETUP , INPUT	, IMAGE , OPT.
AUTO RGB VIDEO VIDEO NR Progressive BLACK	EXECUTE CANCEL

Table 5. Input Menu

Item	Description		
AUTO	Automatic Adjustment at RGB Input: Select the EXECUTE with the button. Horizontal position (H.POSIT), vertical position (V.POSIT), clock phase (H.PHASE), and horizontal size (H.SIZE) are automatically adjusted. Use with the window at maximum size in the application display. Automatic Adjustment at Video Input: Select the EXECUTE with the button. A signal type appropriate for the input signal is selected automatically when EXECUTE is selected automatically. Valid only when AUTO is set for VIDEO on the menu. • This operation requires approximately 10 seconds. It may not function correctly with some input signals. Pressing the AUTO button in this case may correct this problem. • This function is the same as for the AUTO function in Basic operation.		
RGB	Displays RGB Input Frequency: Displays the horizontal and vertical sync signal frequencies for RGB input. • Valid only at RGB input.		
VIDEO (**)	 Select Video Signal Type: Select the signal type with the and buttons. Select NTSC, PAL, SECAM, NTSC4.43, M-PAL, or N-PAL as appropriate for the input signal. The selection of AUTO enables and executes the function AUTO (Automatic Adjustment at Video Input), except for the N-PAL input. Use this function when the image becomes unstable (eg. the image becomes irregular, or lacks color) at VIDEO/S-VIDEO input. Automatic Adjustment requires approximately ten seconds. It may not function correctly with some input signals. Pressing the AUTO button in this case may correct this problem except for the N-PAL input. For the COMPONENT VIDEO input, this function is not effective and the signal type is distinguished automatically. Refer to the item HDTV of the OPT. Menu for the signal of HDTV. 		
VIDEO NR (**)	Set/Clear Noise Reduction Mode: Select the TURN ON / TURN OFF with the $/$ button. When the TURN ON is selected, the NR mode is active and the noise on screen of the video input will be reduced.		
Progressive (**)	 Select Progressive Mode: Select the mode suitable for the input signal with the and buttons. The TV mode and the CINEMA mode convert the interlaced video signal into the progressive signal. The CINEMA mode is adptable for 2-3 Pull-Down system. Use this function to raise resolution, at the interlaced video input except HDTV signals. 		
BLACK(**)	Set/Clear Black Enhancement Mode: Select the TURN ON / TURN OFF with the (1)() button. When the TURN ON is selected, the black enhancement mode is active and the contrast ratio of the screen for the video input will be raised by making black level darker.		

Image Menu

The following adjustments and settings are available when IMAGE is selected on the menu. Select an item with the and buttons, and start operation.

Table 6. Image Menu

Item	Description
KEYSTONE	Keystone Adjustment: Reduce size of bottom of image → Reduce size of top of image • • When this function is activated, the image may not be displayed correctly with some input signals.
BLANK	Select Blank Screen Color: Select color with the and buttons. • The image is cleared when the BLANK mode is set with BLANK ON, or when there is no signal, and the entire screen is displayed in the selected color.
MIRROR	Operation Start/Stop: Press the e or e button. Select Mirror Status: Select mirror status with
START UP	Operation Start/Stop: Press the or button. Setup Initial Screen Display: Select TURN ON with the button. Clear Initial Screen Display: Select TURN OFF with the button. • Note that if TURN OFF is selected the blank screen is displayed in blue when there is no signal.
P. IN P.	Operation Start/Stop: Press the ● or ● button. Select Position of P. in P. Display : Press the ④ or ● button. ● ④ ↔ ● ● ④ ↔ ● ● ④ ↔ ● ● (④ ↔ ● ●) • Valid only at RGB IN 1, RGB IN 2 or DIGITAL input.

Options Menu

The following adjustments and settings are available when OPT. is selected on the menu. Select an item with the and buttons, and start operation. The function indicated (**) is effective on video input mode only, not on RGB input mode, except in the P.IN P. window on RGB input mode.

SETUP (, INPUT	, IMAGE ,	, OPT.
VOLUME		16
MENU COLOR+)		
LANGUAGE >		
AUTO OFF >		
SYNC ON G >		
HDTV 🕨		

Table 7. Options Menu

Item	Description		
VOLUME	Volume Adjustment: Reduce VOLUME		
MENU COLOR	Select Menu Background Color: Select with the and buttons. 		
LANGUAGE	Operation Start/Stop: Press the		
AUTO OFF	Operation Start/Stop: Press the or button. Set AUTO OFF: Set 1~99 minutes with the and buttons. The system automatically enters the standby mode when a signal is not received for the set time. Clear AUTO OFF: Select STOP (0 min.) with the button. When STOP is selected the system does not enter the standby mode even if no signal is received.		
SYNC ON G	Operation Start/Stop: Press the or button. SYNC ON G Valid: Select TURN ON with the button. SYNC ON G Invalid: Select TURN OFF with the button. • May not be displayed correctly with some input signals when SYNC ON G is valid. In such cases, remove the signal connector so that no signal is received, set SYNC ON G to invalid, and reconnect the signal.		
HDTV (**)	Select HDTV mode: Select the 1035i mode or 1080i mode suitable for the input signal with the I / button.		

No Signal Menu

The same adjustments and settings are available as with the Image and Options menus when the MENU button is pressed during display of the "NO INPUT IS DETECTED ON ***" or "SYNC IS OUT OF RANGE ON ***" message while no signal is received.

KEVSTONE +1 BLANK • MIRROR • MIRROR • MIRROR • MENU COLOR• MIRU • LANGUAGE • ALITO OFF •	SYNC ON G >
--	-------------

Table 8. No Signal Menu

Item	Description		
VOLUME	 Volume Adjustment: Reduce VOLUME → Increase VOLUME When this function is used, audio input is automatically switched to video. The audio input can be switched by moving the DISK PAD left and right during the display of the volume adjustment bar. The volume adjustment bar is displayed by pressing VOLUME or VOLUME button. 		
KEYSTONE	Keystone Adjustment: Reduce the size of bottom of image ↔ Reduce the size of top of image •		
	Select Blank Screen Color: Select the color with the () and ()		
BLANK	buttons. • When the blank mode is set with BLANK ON, by absence of a signal, or by input of a non-standard signal, the image is cleared and the complete screen is displayed in the selected color.		
MIRROR	Operation Start/Stop: Press the		
START UP	Operation Start/Stop: Press the		
MENU COLOR	Select Menu Background Color: Select the color with the and buttons.		
LANGUAGE	Operation Start/Stop: Press the		
AUTO OFF	Operation start/stop: Press the or button. Set AUTO OFF: Set 1~99 minutes with the and buttons. The system automatically enters the standby mode when a signal is not received for the set time. Clear AUTO OFF: Select the STOP (0 min.) with the button. When the STOP is selected the system does not enter the standby mode even if no signal is received.		
SYNC ON G	Operation Start/Stop: Press the or button. SYNC ON G Valid: Select the TURN ON with the button. SYNC ON G Invalid: Select the TURN OFF with the button. • May not be displayed correctly with some input signals when the SYNC ON G is valid. In such cases, remove the signal connector so that no signal is received, set the SYNC ON G to invalid, and reconnect the signal.		

MAINTENANCE

Lamp

HIGH VOLTAGE HIGH TEMPERATURE HIGH PRESSURE

Contact your dealer before replacing the lamp.

For the optional lamp, see the item "Option Parts" of the Table 12.

Before replacing the lamp, switch power OFF, remove the power cord from the power outlet, and wait approximately 45 minutes until the lamp has cooled. The lamp may explode if handled at high temperatures.

WARNING • For disposal of used lamp, treat according to the instruction of community authorities. • Since the lamp is made of glass, do not apply shock Lamp to it and do not scratch it. • Also, do not use old lamp. This could also cause explosion of the lamp. • If it is probable that the lamp has exploded (explosive sound is heard), disconnect the power plug from the power outlet and ask your dealer to replace lamp. The lamp is covered by front glass, but, in rare cases, the Reflector Front reflector and the inside of the projector may be alasss damaged by scattered broken pieces of glass, and broken pieces could cause injury when being handled. • Do not use the projector with the lamp cover removed.

Lamp Life

Projector lamps have a finite life. The image will become darker, and hues will become weaker, after a lamp has been used for a long period of time.

Replace the lamp if the LAMP indicator is red, or the CHANGE THE LAMP message appears when the projector is switched ON. See Table 9 of P.20 and Table 10 of P.21.

NOTE • The LAMP indicator is also red when the lamp unit reaches high temperature. Before replacing the lamp, switch power OFF, wait approximately 20 minutes, and switch power ON again. If the LAMP indicator is still red, replace the lamp.

Maintenance (continued)

Replacing the Lamp

- 1. Switch the projector OFF, remove the power cord from the power outlet, and wait at least 45 minutes for the unit to cool.
- 2. Prepare a new lamp.
- 3. Check that the projector has cooled sufficiently, and gently turn it upside down.
- 4. Loosen the screw as shown in the diagram, and remove the lamp cover.
- 5. Loosen the two screws, and gently remove the lamp while holding the grips. Touching the inside of the lamp case may result in uneven coloring.
- 6. Install the new lamp and tighten the two screws firmly. Also steadily push the opposite side of the screwed lamp into the unit.
- 7. Replace the lamp cover in position and tighten the screw firmly.
- 8. Gently turn the projector right-side up.





- ▲ <u>CAUTION</u> Ensure that screws are tightened properly. Screws not tightened fully may result in injury or accidents.
- Do not use the projector with the lamp cover removed.

Resetting the Lamp Timer

Reset the lamp timer after replacing the lamp. When the lamp has been replaced after the LAMP indicator is red, or the CHANGE THE LAMP message is displayed, complete the following operation within ten minutes of switching power ON. The power will be turned off automatically in over 10 minutes.

- 1. Switch power ON, and press the RESET button, for approximately three seconds. The 'LAMP xxxx hr' message will appear on the lamp timer on the bottom of the screen.
- 2. Press the MENU button on the remote control transmitter, or the RESET button on the control panel, while the lamp timer is displayed. The 'LAMP xxxx $\Box \rightarrow 0 \blacksquare$ CANCEL' message will then appear.
- 3. Press the \bigcirc and select 0, and wait until the timer display is cleared.

NOTE • Do not reset the lamp timer without replacing the lamp. Reset the lamp timer always when replacing the lamp. The message functions will not operate properly if the lamp timer is not reset correctly.

Air Filter Maintenance

The air filter should be cleaned as described below at intervals of approximately 100 hours.

1. Switch the projector power supply OFF, and remove the power cord from the power outlet. 2. Clean the air filter with a vacuum cleaner.

<u>CAUTION</u> • Switch power OFF and remove the power cord from the power outlet before beginning maintenance work. Please read the separate "SAFETY INSTRUCTIONS" thoroughly to ensure that maintenance is performed correctly. • Replace the air filter if contamination cannot be removed, or if it is damaged. Contact your dealer in such case. For the optional air filter, see the item "Option Parts" of the Table 12.

• Do not use the equipment with the air filter removed.

• When the air filter is clogged with dust etc. the power supply is switched OFF automatically to prevent the temperature rising inside the projector.

Other Maintenance

Maintenance Inside the Equipment

For safety reasons, ensure that the equipment is cleaned and checked by the dealer once every two years. Maintaining the equipment by yourself is dangerous.

Cleaning the Lens

Gently wipe the lens with lens cleaning paper. Do not touch the lens with your hands.

Cleaning the Cabinet and Remote control transmitter

Gently wipe with a soft cloth. If dirt and stains etc. are not easily removed, use a soft cloth dampened with water, or water and a neutral detergent, and wipe dry with a soft, dry cloth.

▲ <u>CAUTION</u> • Switch power OFF and remove the power cord from the power outlet before beginning maintenance work. Please read the separate "SAFETY INSTRUCTIONS" thoroughly to ensure that maintenance is performed correctly. • Do not use detergents or chemicals other than those noted above (e.g. benzene or thinners).

- Do not use cleaning sprays.
- Do not rub with hard materials, or tap the equipment.

TROUBLESHOOTING

OSD Message

The messages as described below may appear on the screen at power ON. Take the appropriate measures when such a message appears.

Table 9. OSD Messages

Message	Contents
CHANGE THE LAMP AFTER REPLACING LAMP, RESET THE LAMP TIME. *1)	The message shown at left appears after the lamp has been used for more than 1700 hours. The lamp is approaching the end of its life. Power is switched OFF automatically when the lamp reaches the end of its life. Prepare a new lamp for installation. Always reset the lamp timer after replacing the lamp.
CHANGE THE LAMP AFTER REPLACING LAMP, RESET THE LAMP TIME. THE POWER WILL TURN OFF AFTER ** hr. *1)	The lamp will reach the end of its life in ** hours. Power will be switched OFF automatically in ** hours. Replace the lamp as shown in P.17~18 "Lamp". Always reset the lamp timer after replacing the lamp.
CHANGE THE LAMP AFTER REPLACING LAMP, RESET THE LAMP TIME. THE POWER WILL TURN OFF AFTER 0 hr.	The lamp has reached the end of its life. Power will be switched OFF in a few minutes. Switch power OFF immediately and replace the lamp as shown in P.17~18 "Lamp". Always reset the lamp timer after replacing the lamp.
NO INPUT IS DETECTED ON ***	No input signal found. Check signal input connections and signal sources.
SYNC IS OUT OF RANGE ON ***	The horizontal or vertical frequency of the input signal is not within the specified range. Check the specifications of the equipment and the signal source.

NOTE *1) This message is cleared automatically after approximately three minutes, and appears every time power is switched ON.

Indicators Message

The POWER indicator, LAMP indicator, and TEMP indicator are lit and blank as follows. Take the appropriate measures.

Table	10.	Indicators	Message
-------	-----	------------	---------

POWER indicator	LAMP indicator	TEMP indicator	Contents
Lights orange	Turns off	Turns off	The Standby mode has been set.
Blinks green	Turns off	Turns off	Warming up. Please wait.
Lights green	Turns off	Turns off	ON. Normal operation possible.
Blinks orange	Turns off	Turns off	Cooling. Please wait.
Lights red	Lights red	Turns off	Lamp is not lit. The interior of the equipment may be too hot. Switch power OFF, wait 20 minutes until the equipment cools, and check whether the ventilation openings are blocked, whether the air filter is dirty, or whether the ambient temperature exceeds 35 °C. And switch power ON again. Replace the lamp if the same problem occurs.
Lights red	Blinks red	Turns off	Lamp or lamp cover is not found, or hasn't been fitted in correctly. Switch power OFF, and wait for 45 minutes until the equipment cools. Check fitting of the lamp and lamp cover, and switch power ON again. Contact your dealer if the same problem occurs again.
Lights red	Turns off	Blinks red	The cooling fan is not operating. Switch power OFF, and wait for 20 minutes until the equipment cools. Check for foreign matters in the fan, and switch power ON again. Contact your dealer if the same problem occurs again.

NOTE *1) When the internal temperature becomes excessive power is switched OFF automatically for safety reasons, and the indicator is extinguished. Set the power switch to [O] and wait for 20 minutes until the equipment has cooled sufficiently.

Symptom

Before requesting repair, check in accordance with the following chart. If the situation cannot be corrected, then contact your dealer.

Table 11. Symptom

Symptom	Possible cause	Remedy	Page
The power is not	The main power switch is not turned on.		
turned on.	The power cord is disconnected.	Plug the power cord into an AC power outlet.	0,9
No video or audio.	The input is not correctly set.	Use the projector or remote control transmitter to set.	10
	No signal input. Connect correctly.		7,8
	The projector is not correctly connected.	Connect correctly.	7,8
Video is present but no audio.	The volume is set to minimum.	Press VOLUME \bigcirc on the remote control or display the menu screen and adjust the volume.	11,15
	Mute is turned on.	Press the MUTE 🛞 button.	11
	The projector is not correctly connected.	Connect correctly.	7,8
Audio is present but no video.	The brightness is set to minimun.	Select BRIGHT with the MENU button and the press the	12
	The lens cap is still attached.	Remove the lens cap.	9
Colors are pale and color matching is poor.	Color density and color matching are not correctly adjusted.	Adjust the video.	12
Images are dark.	Brightness and contrast are not correctly adjusted.	Adjust the video.	12
	The lamp is nearing the end of its service life.	Replace with a new lamp.	17
Images are blurred.	Focus or H PHASE is out of adjustment.	Adjust the focus or H PHASE.	9,12

SPECIFICATIONS

Table 12. Specifications

Item			Specification
Product name			Liquid crystal projector
Liquid	Panel size		3.3 cm (1.3 type)
crystal	Drive system		TFT active matrix
panel	Pixels		786,432 pixels (1024 horizontal x 768 vertical)
Lens	1		Zoom lens F=1.7 ~ 2.3 f=49.0 ~ 64.0 mm
Lamp			250 W UHB
Speaker			1.2 W + 1.2W (Stereo)
Power supp	oly		AC100 ~ 120V, 4.5A / AC220 ~ 240V, 2.2A
Power cons	sumption		400W
Temperatu	re range		0 ~ 35°C (Operating)
Size			289 (W) x 124 (H) x 350 (D) mm
Weight (ma	ISS)		6.4 kg
		1	Video: Analog 0.7Vp-p, 75Ω terminator (positive)
RGB signal input	RGB IN		H/V. sync.: I I L level (positive/negative) Composite sync.: TTL level
		2	D-sub 15-pin shrink jack
	DIGITAL		TMDS, DC: 150~1200 mV / AC: 1.56 Vp-p TTL Level (Positive/Negative)
	AUDIO IN DIGITAL RGB2		200mVrms, 50 kΩ (max. 3.0Vp-p) Stereo mini jack
VIDEO			1.0Vp-p, 75Ω terminator RCA jack
Video signal input	S-VIDEO		Brightness signal: 1.0Vp-p, 75Ω terminator Color signal: 0.286Vp-p (burst signal), 75Ω terminator Mini DIN 4-pin jack
		Y	1.0 Vp-p, 75 Ω Terminator (Positive)
	VIDEO	CB/CR	0.7 Vp-p, 75 Ω Terminator (Positive)
		Pb/Pr	1.0 Vp-p, 75 Ω Terminator (Positive)
	AUDIO	L R	200mVrms, 50 kΩ (max. 3.0Vp-p) RCA jack
Signal RGB OUT			Video: Analog 0.7Vp-p, 75Ω output impedance (positive) H/V. sync.: TTL level (positive/negative) Composite sync.: TTL level D-sub 15-pin shrink jack
	AUDIO OUT		200mVrms, output impedance 1 k Ω (max. 3.0Vp-p) Stereo mini jack
Control	CONTROL		D-sub 15-pin shrink plug
functions	USB		USB jack (B type)
Optional Parts			Lamp: LAMP-030 Air Filter: MU00832 * For others, consult your dealer.

NOTE • This specifications are subject to change without notice.

WARRANTY AND AFTER-SERVICE

If a problem occurs with the equipment, first refer to the P.20 "TROUBLESHOOTING" section and run through the suggested checks. If this does not resolve the problem contact your dealer or service company.

PLEASE READ

This manual is provided as a free service by Projector.com.

We are in no way responsible for the contents of the manual. We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners.

ABOUT PROJECTOR.COM

Projector.com (<u>http://www.projector.com</u>) is your review and buying guide resource for DLP and LCD video projectors.

Visit the site to read the latest projector news and reviews, read and comment on projector specifications, download user manuals and much more.