

## **Product Data Sheet**

Updated : March 1996 Supersedes : October 1993

## **Product Description**

A flexible polythene coated woven cloth tape, coated with an aggressive rubber adhesive. The cloth backing is strong but exhibits easy tear properties. An extremely versatile tape for a multitude of uses.

## Physical Properties Not for specification purposes

Adhesive Type	Rubber resin.	
Backing	Polyethylene treated cloth.	
Thickness (ASTM D-3652)	320 µm	
Tape Colour	White, Green, Red, Silver, Black, Light Blue, Olive drab	
Shelf Life	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

## Performance Characteristics

Not for specification purposes

Adhesion to Stainless Steel ASTM D-3330	5.0 N/10mm	
Tensile Strength ASTM D-3759	70.0 N/10mm	
Elongation at Break ASTM D-3759	25.0 %	
Temperature Range Maximum	50 °C	
Moisture Vapour Transmission	20 g/m²/24hr	

Date: March 1996

3998 Waterproof Cloth Tape

**Application Techniques** 

Best results are attained when applied to a clean, dry and non dusty surface

above 0°C.

To improve adhesion ensure firm and even application pressure is applied.

**Applications** 

Ammunition container

sealing.

Duct sealing.

Colour coding.

General splicing, Packaging.

Patching and repairing.

**FEATURES** 

backing.

Polyethylene treated cloth

High strength.

**ADVANTAGES** 

Excellent water/humidity resistance.
Conformable.

Easy tear.

Good handling properties.

High tack adhesive. Adheres to a variety of

BENEFITS

Provides a strong versatile easy-to-use tape for general

industrial use.

surfaces.

**Specifications** 

3M waterproof cloth tape conforms to Def. Stan. Spec. 81-25/2.

Rubber resin adhesive.

3M is a trademark of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



**Specialty Tapes & Adhesives** 

© 3M United Kingdom PLC 1996

3M United Kingdom PLC 3M House, 28 Great Jackson Street, Manchester, M15 4PA Customer Service :

Tel 0161 236 8500 Fax 0161 237 1105 3M Ireland 3M House, Adelphi Centre, Upper Georges Street, Dun Laoghaire,Co. Dublin, Ireland Customer Service :

Tel (01) 280 3555 Fax (01) 280 3509