VA1912wb-4

19" 16:10 MULTIMEDIA LCD DISPLAY

High-definition, wide-screen LCD.

The ViewSonic VA1912wb-4 19" LCD will impress you with its generous feature set and its budget friendly price. The 16:10 WIDE-SCREEN ASPECT RATIO PROVIDES MORE PRODUCTIVE SPACE for multiple windows. ViewSonic's innovative Dynamic Structure™ technology ACCELERATES VIDEO RESPONSE FOR BROADCAST-QUALITY, seamless video. The ClearMotiv™II fast 5ms video response, 280 nits of brightness (typ), 700:1 contrast ratio (typ), and 1440x900 optimum resolution deliver crystal-clear images, crisp text and intense graphics. OSD lock and AutoTune® functions ensure your view is always optimal. Furnish your workplace in style with the feature-rich, wall-mountable, value-priced VA1912wb-4.



> ClearMotiv™ II technology

Human vision allows images shown at 24 frames per second (fps) to be perceived as smooth motion video. ClearMotiv fast video-response technology allows frame rate up to 200 fps for true broadcast quality full-motion video.

> Ultra-Slim Bezel

The ultra-slim bezel makes more productive use of the screen area while minimizing the image gap in multidisplay applications for continuous data display which enhances the visual experience with clean, minimalist borders around the active image area.

> sRGB Color Management

The sRGB color management chip technology ensures color accuracy from screen to print when used with other sRGB-compliant peripherals.

> OnView® controls Including

ViewMatch Technology

Screen adjustments are made via an on-screen menu using simple controls. This user-friendly control system easily adjusts image quality, size, position and geometry for optimal viewing.

> AutoTune™ Function

Provides the best image by monitoring signals from the computer and automatically optimizing the monitor settings.

> OSD/Power Lock Function

When activated, the user-controlled OSD/Power lock function prevents changes to monitor settings, maintaining an optimized image.





VA1912wb-4

19" 16:10 MULTIMEDIA LCD DISPLAY



| | | Model No. VS10866 |
|---------------|--------------------|--|
| LCD | Display Area | 19" diagonal wide screen" |
| | Optimum Resolution | 1440 X 900@60Hz |
| | Brightness | 280 cd/m ² (Typ.) |
| | Contrast Ratio | 700:1 (Typ.) |
| | Viewing Angles | 150° (Horizontal),130° (Vertical) (CR>10) |
| | Response Time | 5ms |
| | Pixel Pitch | 0.285mm X 0.285mm |
| | Panel Surface | Anti-glare |
| INPUT | Analog | RGB Analog |
| | Sync | H/V Separated |
| | Frequency | FH:30-82kHz, Fv:50-85Hz |
| COMPATIBILITY | PC | VGA up to 1440 X 900 Non Interlaced |
| | Mac | Power Mac, up to 1440 X 900 |
| CONNECTOR | Analog | 15 pin mini D-sub X 1 |
| | Audio-in | 3.5mm audio lin-in |
| | Power | Built-in power Adapter, 3-pin plug |
| AUDIO | Speaker | 2.5W X 2 |
| ERGONOMICS | Tilt | -5° 20°Degrees |
| POWER | Voltage | 100-240VAC; 50/60 Hz (Switch) |
| | Consumption | 35W (Max.) / 32W (Typ.) |
| CONTROLS | Basic | Mute [1], [Down], [Up], [2], power button |
| | OnView® | Auto Image Adjust Contrast/Brightness Input Select Analog / |
| | | Digital Audio Adjust Volume, Mute Color Adjust sRGB, 9300K, |
| | | 6500K(default), 5400, 5000, User Color [R, G, B] Information H |
| | | Frequency, V Frequency, Resolution, Pixel Clock, Serial |
| | | Number, Model Number, www.ViewSonic.com Manual Image |
| | | Adjust H. Size, H./V. Position, Fine Tune, Sharpness Setup |
| | | Menu Language [English, French, German, Spanish, Italian, |
| | | Finnish, Japanese, Traditional Chinese, Simplified Chinese], |
| | | Resolution Notice, OSD Position, OSD Timeout, OSD |
| | | Background Memory Recall |
| OPERATING | Temperature | 5°C - 35°C |
| CONDITIONS | Humidity | 20-80% (Non condensed) |
| DIMENSIONS | Physical (mm) | 451mm X 391mm X 197mm (With Base) |
| (WXHXD) | , , , | , |
| WEIGHT | Net | 4.5 kgs |
| REGULATIONS | | CB / TCO 03 / UL/cUL / FCC-B / ICES 003 / Argentina-TUV/S / |
| | | NOM / EPA Energy Star / TUV/Ergo / ISO134062 / TUV/GS / CE |
| | | / GOST-R / SASO / BSMI / PSB / C-Tick / Korea (MIC) / CCC / |
| | | WEEE / RoHS |
| Wall Mount | | Meet VESA (75mm X 75mm) standards |
| | | Pour 1h |









ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Headquarters:

381 Brea Canyon Road, Walnut, CA 91789-0708 www.viewsonic.com

ViewSonic Korea

#907, 9F, Hyundai HYEL, 2-36, Hangangro 2-ga, Yongsan-gu, Seoul, Korea 140-871 kr.viewsonic.com

9F, No. 192, Lien Chen Road, Chung Ho, 235 Taipei, Taiwan, R.O.C www.viewsonic.com.tw/

ViewSonic Singapore 221 Henderson Road. #04-08 Henderson Building, Singapore 159557 www.viewsonic.com.sg/

ViewSonic Australia Unit 4, 44 Dickson Ave, Artarmon, NSW 2064, Australia www.viewsonic.com.au/

M-28. Commercial Complex (M-Block Market). 3rd floor, Greater Kailash-II, N Delhi - 110 048, India in.viewsonic.com

ViewSonic Middle East LOB 13 Office 8, PO Box 17625. Jebel Ali, Dubai, U.A.E.

