

# VX2835wm

**28" WIDE (27.5" VIEWABLE)  
MULTIFUNCTION LCD  
WITH HDMI FOR HD QUALITY VIDEO**

## Desktop experience amplified

ViewSonic's 28" VX2835wm widescreen (27.5" viewable) LCD amplifies your desktop experience. With ultra-fast 3ms response and integrated speakers and amp, the VX2835wm offers high-performance features that elevate your message to a whole new level. Work more productively on the EXPANSIVE 27.5" WIDESCREEN DISPLAY. Play more intensely with HD games, movies and videos in their native format. MULTIPLE VIDEO CONNECTIONS including HDMI let you SELECT THE BEST INPUT SOURCE for your digital entertainment. The high 800:1 contrast ratio (typ.) and high 500cd/m<sup>2</sup> brightness (typ.) produce remarkably bright and rich colours. Integrated digital speakers and VESA wall-mount compliance save space and reduce desktop clutter. The VX2835wm is perfect for the serious gamer and movie aficionado who want a complete digital entertainment experience on the desktop.

**IT'S NOT JUST THE ULTIMATE LARGE SCREEN GAMING DISPLAY.  
IT'S A VIEWSONIC.**



### WORK FASTER, PLAY SMARTER

- > Full 27.5" viewable widescreen with 1920 x 1200 resolution
- > True 1080p with HDMI for HD quality video
- > ClearMotiv® 3ms video response time  
Fast 3ms video response enables digital, HD broadcast-quality video.
- > Stylish slim-bezel design with glossy, piano-black finish  
The thin bezel lets you see more without taking up valuable wall space.
- > Multifunction LCD with OptiSync® digital/analogue inputs  
Digital HDMI input gives you the best possible connection to HD signals for movies, video and Digital Signage applications. Multi-mode input technology supports both digital (HDMI or DVI) and analogue (VGA) signals.
- > Ultra-high brightness and contrast  
500cd/m<sup>2</sup> brightness (typ.) and 800:1 contrast ratio (typ.) for rich, detailed images, videos, and advertising content.
- > Multimedia enhanced  
Save desk and workspace and enjoy rich stereo sound with built-in stereo speakers.
- > OnView® controls for superior screen adjustability  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Windows Vista approved
- > ENERGY STAR® qualified

**HDMI™**  
HIGH DEFINITION MULTIMEDIA INTERFACE



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# VX2835wm

**ViewSonic®**  
See the difference™ 

**28" WIDE (27.5" VIEWABLE) MULTIFUNCTION LCD  
WITH HDMI FOR HD QUALITY VIDEO AND 1920 X 1200 RESOLUTION**



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	27.5" TN colour TFT active matrix WUXGA LCD
	Display Area	59.3cm horizontal x 37.1cm vertical, 69.9cm diagonal
	Pixel Pitch	0.309mm
	Optimum Resolution	1920 x 1200@60Hz
	Pixel Clock	165MHz (digital), 205MHz (analogue)
	Contrast Ratio	800:1 (typ.)
	Viewing Angles	160° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)
	Response Time	3ms (grey-to-grey typ.), 5ms (off-on-off typ.)
	Colour Support	16.7M colours (6-bit+2-bit FRC)
	Light Source	Long life, 50000 hrs. (typ.)
	Brightness	500cd/m² (typ.)
	Aspect Ratio	16:10 native (1:1, 4:3, 16:9, full screen switchable)
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7 Vp-p, 75 ohm), PAL, SECAM, NTSC, SDTV/EDTV (480i/p, 576i/p), HDTV (720p, 1080i)
	Digital	HDMI (HDCP enabled; TMDS, 100 ohm)
	Frequency	F <sub>H</sub> : 24~82kHz, F <sub>V</sub> : 50~85Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
<b>COMPATIBILITY</b>	PC	VGA up to 1920 x 1200 non-interlaced
	Mac®	Power Mac™ up to 1920 x 1200 non-interlaced
<b>CONNECTOR</b>	Analogue	1 x 15-pin mini D-Sub VGA (detachable cable)
	Digital	1 x 19-pin HDMI (HDCP enabled; detachable cable)
	Component	3 x RCA (YPbPr/YCbCr)
	S-Video	1 x 4-pin mini DIN jack (Y/C)
	Composite	1 x RCA (CVBS)
	Audio	1 x 3.5mm mini stereo jack
	Power	2 x L/R RCA sets (for YPbPr and for CVBS/S-video)
		3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	2 x 3 watt integrated stereo speakers
<b>POWER</b>	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply
	Consumption	64 watt (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2]
	OSD <sup>1</sup>	Auto image adjust, contrast, brightness, input select (D-sub, HDMI, component, S-video, composite), audio menu (volume, mute, bass, treble, balance), View-Match® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, video format, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness, tint, colour, OptiColor mode [standard, text, cinema, game, portrait, scenery, vivid], OptiColor skin [nature, reddish, yellowish], aspect ratio [1:1, 4:3, 16:9, full screen], PIP [position, size, source], PBP [source], setup menu (language [10 options], resolution notice, OSD position, OSD timeout, OSD background, sleep timer), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	5°C–35°C
	Humidity	20%–80% (non-condensation)
<b>DIMENSIONS</b>	W x H x D mm	662 x 578 x 306 (with stand)
		662 x 489 x 87 (without stand)
<b>WEIGHT</b>	Net	12.0kg (with stand)
	Gross	8.5kg (without stand) 14.3kg
<b>REGULATIONS</b>		CE, CB, TCO'06, NEMKO/ERGO <sup>2</sup> , ISO13406-2 (pixel failure class II), GOST-R + hygienic, UL, cUL, FCC-B, ENERGY STAR, ENERGY, NOM, MPR II, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, IRAM, UkrSEPRO, MIC, Green Mark, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'06 and ENERGY STAR standards
<b>SECURITY</b>		Kensington® security port
<b>WALL MOUNT</b>		VESA FDMI 200mm x 100mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, 15-pin VGA video cable, HDMI to DVI cable adapter, audio cable, component cable, S-video cable, composite cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

## ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

## ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

## ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

## ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

## ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)20 7120 860  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> Some features may not be available on all inputs. <sup>2</sup> Equivalent to TÜV/ERGO.

Copyright © 2008, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX2835wm g/e 01/08-UK

For more product information, visit us on the web at [www.ViewSonicEurope.com](http://www.ViewSonicEurope.com)