

CS5213AN Datasheet

HDMI to VGA Convertor with Audio Support

Contents

1	Introduction.....	5
2	Features.....	6
3	Pin Definition.....	7
3.1	Pin Assignments.....	7
3.2	Pin Description.....	7
4	Interfaces and Capability.....	9
4.1	HDMI Input	9
4.2	HDCP(Optional).....	9
4.3	Analog VGA output	9
5	Electrical Specifications	11
5.1	Absolute Maximum Conditions	11
5.2	Operating Conditions.....	11
5.3	Electrical Specification	11
5.4	CS5213AN Power Consumption	13
6	Package Specification	14
7	Ordering Information	15
8	Revision History	16

List of Figures

Figure 1-1 CS5213AN Block Diagram	5
Figure 3-1 CS5213AN Pin Layout	7
Figure 6-1 CS5213AN Package Outline (QFN32 Leads 4x4mm)	14

Confidential for 鼎唯 Only

List of Tables

Table 3-1 CS5213AN Pin Definitions	7
Table 4-1 Supported Popular Timing/ Resolution	10
Table 5-1 Absolute Maximum Conditions	11
Table 5-2 Normal Operating Conditions	11
Table 5-3 DC Electrical Specification	11
Table 5-4 AC Electrical Specification	12
Table 5-5 Audio Electrical Characteristics	12
Table 5-6 CS5213AN Typical Power Consumption	13
Table 6-1 Package Dimension	14
Table 7-1 CS5213AN Ordering Information	15
Table 8-1 Document Revision History	16

1 Introduction

The Capstone CS5213AN HDMI to VGA converter combines a HDMI input interface and an analog RGB DAC output. With support and on-chip Audio DAC, it saves cost and optimizes board space. The embedded MCU is based on an industrial standard 8051 core.

The CS5213AN is suitable for multiple market segments and display applications, such as laptop, motherboard, desktop, dongle, and docking system.




Figure 1-1 CS5213AN Block Diagram

2 Features

General

- HDMI 1.4 compliant receiver
- VGA output interface, DAC speed up to ~200-MHz Pixel rate, 8-bit
- Video resolution support up to 1920x1200@60 and 1920X1080@60Hz
- Embedded oscillator and there's no need for external crystal
- Embedded linear dropout regulator (LDO)
- Embedded MCU
- On-chip HDCP Engine Which is compliant with HDCP 1.4 Specification (Optional)
- Integrated on-chip HDCP 1.4 Keys (Optional)
- Embedded EDID (CS5213AN will response EDID if terminal device doesn't have it)
- Support EEPROM Free mode by using the internal pre-blew ROM
- Support Auto Power Saving mode
- VGA Connection detection supported
- Internal power-on-reset (POR)
- Dual Channel 16-bit resolution sigma-delta DAC
- Support Audio Sampling Frequently (Fs): up to 48KHz
- I2C Slave interface and HDMI DDC interface are available for debug and firmware update.
- QFN32 4x4 package

HDMI Digital Input

- HDMI 1.4 compliant
- Built-in high-performance adaptive equalizer
- Support Hot Plug Detection

VGA Output Interface

- Triple 8-bit DAC (Digital-to-Analog Converter) with clock up to 200-MHz
- Video resolution support up to 1920x1200@60 and 1920X1080@60Hz
- Embedded V-sync/ H-sync 5V buffer
- HBM 4-KV for VGA connector pins
- VESA VSIS v1r2 compliant

Embedded MCU

- Industrial standard 8051 core
- Support I2C Master and Slave up to 400-KHz.

Power & Technology

- Single 5V power supply
- Ultralow standby power < 100uW

3 Pin Definition

3.1 Pin Assignments




Figure 3-1 CS5213AN Pin Layout

3.2 Pin Description

Table 3-1 CS5213AN Pin Definitions

Pin #	Description	Type	PU/PD	Note
1	HDMI_CKN	I	-	HDMI clock differential pair N input
2	HDMI_CKP	I	-	HDMI clock differential pair P input
3	HDMI_D0N	I	-	HDMI data channel 0 different pair N input
4	HDMI_D0P	I	-	HDMI data channel 0 different pair P input
5	HDMI_D1N	I	-	HDMI data channel 1 different pair N input

Pin #	Description	Type	PU/PD	Note
6	HDMI_D1P	I	-	HDMI data channel 1 different pair P input
7	HDMI_D2N	I	-	HDMI data channel 2 different pair N input
8	HDMI_D2P	I	-	HDMI data channel 2 different pair P input
9	VDD33_OUT	P	-	3.3V power output
10	VDD5_IN	P	-	5V power input
11	VGA_VS	O	-	VGA vertical sync output
12	VGA_HS	O	-	VGA horizontal sync output
13	VGA_SCL	I/O	-	VGA DDC clock
14	VGA_SDA	I/O	-	VGA DDC data
15	VDD33	P	-	3.3V power input
16	GPIO	I	-	General GPIO
17	VGA_B	O	-	VGA Blue channel output
18	VGA_G	O	-	VGA Green channel output
19	VGA_R	O	-	VGA Red channel output
20	VDD33_VDAC	P	-	3.3V Video DAC power input, connect with VDD33_OUT
21	AVD_ADAC	P	-	3.3V Audio DAC power input, connect with VDD33_OUT
22	AUD_R	O	-	Audio DAC right channel headphone output
23	AUD_VREF	O	-	Audio DAC Internal voltage reference, tie 10uF in parallel with a 0.1uF ceramic capacitor to analog ground.
24	AUD_L	O	-	Audio DAC left channel headphone output
25	HDMI_HPD	I/O	PD	HDMI Hot Plug detect output
26	CFG_SDA	I/O	-	I2C slave DATA pin
27	CFG_SCL	I/O	-	I2C slave CLOCK pin
28	HDMI_SDA	I/O	-	HDMI DDC data
29	HDMI_SCL	I/O	PU	HDMI DDC clock
30	TEST_EN	I	PD	1: Test mode. 0: Normal mode
31	MODE	I	PU	1: Flash mode. 0: Reserved (Don't pull down)
32	VDD33	P	-	3.3V power input

4 Interfaces and Capability

4.1 HDMI Input

The HDMI input is compliant with the HDMI 1.4b standard. It supports HDCP(Optional) 1.4 content protection standard.

The DDC_SCL and DDC_SDA signals are used to access EDID. Because of pull-up resistors on these signals has been integrated into Chip, so there is no need external pull-up resistor anymore.

4.2 HDCP(Optional)

The CS5213AN supports HDCP 1.4 on the output video link with an embedded HDCP key. The Digital Rights Management (DRM) policy of the operating system running on the source application processor decides whether or not to enable HDCP on the link, depending on the content.

The HDCP(Optional) authentication is performed before the audio-video transmission. The HDCP authentication and encryption can be performed by the hardware HDCP module. Pre-programmed HDCP keys and Key Selector Value (KSV) stored in the internal memory are used in the HDCP process.

4.3 Analog VGA output

CS5213AN integrates triple 8bit-250MHz-DAC (Digital-to-Analog Converters), with each DAC assigned for each color, R (red), G (green), and B (blue). The Analog VGA interface of CS5213AN is compliant with the VESA VSIS v1r2. Real-time Hot plug detection mechanism is also integrated into CS5213AN.

The most popular video formats supported by CS5213AN are shown in the following Table 4 1. However, the formats supported by CS5213AN are not limited to this table. Those formats with (a) the data transmission bandwidth lower than the maximal bandwidth, the pixel frequency slower than the maximal DAC speed 200-MHz can also be supported by CS5213AN.

Table 4-1 Supported Popular Timing/ Resolution

Resolution	Refresh Rate (Hz)	Horizontal Freq. (kHz)	Pixel Freq. (MHz)	Standard Type	Ori. Document	Date
640 x 350	85	37.9	31.500	VESA Standard	VDMTPROP	3/1/96
640 x 400	85	37.9	31.500	VESA Standard	VDMTPROP	3/1/96
720 x 400	85	37.9	31.500	VESA Standard	VDMTPROP	3/1/96
640 x 480	60	31.5	25.175	Industry Standard		
	72	37.9	31.500	VESA Standard	VS901101	12/2/92
	75	37.5	31.500	VESA Standard	VDMT75HZ	10/4/93
	85	43.3	36.000	VESA Standard	VDMTPROP	3/1/96
800 x 600	60	37.9	40.000	VESA Guidelines	VG900602	8/6/90
	72	48.1	50.000	VESA Standard	VS900603A	8/6/90
	75	46.9	49.500	VESA Standard	VDMT75HZ	10/4/93
	85	53.7	56.250	VESA Standard	VDMTPROP	3/1/96
848 x 480	60	31.0	33.750	VESA Standard	AddDMT	3/4/03
1024 x 768	43	35.5	44.900	Industry Standard		
	60	48.4	65.000	VESA Guidelines	VG901101A	9/10/91
	70	56.5	75.000	VESA Standard	VS910801-2	8/9/91
	75	60.0	78.750	VESA Standard	VDMT75HZ	10/4/93
	85	68.7	94.500	VESA Standard	VDMTPROP	3/1/96
1152 x 864	75	67.5	108.000	VESA Standard	VDMTPROP	3/1/96
1280 x 720	60	45.0	74.250	CEA Standard	CEA -861	
1280 x 768	60	47.4	68.250	CVT Red. Blanking	AddDMT	3/4/03
	60	47.8	79.500	CVT	AddDMT	3/4/03
	75	60.3	102.250	CVT	AddDMT	3/4/03
	85	68.6	117.500	CVT	AddDMT	3/4/03
1280 x 800	60	49.3	71.000	CVT Red. Blanking	CVT1.0 2MA-R	5/1/07
	60	49.7	83.500	CVT	CVT 1.02MA	5/1/07
	75	62.8	106.500	CVT	CVT 1.02MA	5/1/07
	85	71.6	122.500	CVT	CVT 1.02MA	5/1/07
1280 x 960	60	60.0	108.000	VESA Standard	VDMTPROP	3/1/96
	85	85.9	148.500	VESA Standard	VDMTPROP	3/1/96
1280 x 1024	60	64.0	108.000	VESA Standard	VDMTREV	12/18/96
	75	80.0	135.000	VESA Standard	VDMT75HZ	10/4/93
	85	91.1	157.500	VESA Standard	VDMTPROP	3/1/96
1360x768	60	48.0	72.000	VESA Standard	DMT Update	11/30/07
	60	47.7	85.500	VESA Standard	AddDMT	3/4/03
	60	47.7	85.500	VESA Standard	DMT Update	11/30/07
1400 x 1050	60	64.7	101.000	CVT Red. Blanking	AddDMT	5/13/03
	60	65.3	121.750	CVT	AddDMT	3/4/03
	75	82.3	156.000	CVT	AddDMT	3/4/03
	85	93.9	179.500	CVT	AddDMT	3/4/03
1440 x 900	60	55.5	88.750	CVT Red. Blanking	CVT1.30MA-R	7/14/04
	60	55.9	106.500	CVT	CVT1.30MA-R	7/14/04
	75	70.6	136.750	CVT	CVT1.30MA-R	7/14/04
	85	80.4	157.000	CVT	CVT1.30MA-R	7/14/04
1600 x 900	60	60.0	108.000	VESA Standard	VDMTREV	11/17/08
1600 x 1200	60	75.0	162.000	VESA Standard	VDMTREV	12/18/96
	65	81.3	175.500	VESA Standard	VDMTREV	12/18/96
	70	87.5	189.000	VESA Standard	VDMTREV	12/18/96
	75	93.75	202.5	VESA Standard	VDMTREV	12/18/96
1680 x 1050	60	64.7	119.000	CVT Red. Blanking	CVT1.76MA-R	7/14 /04
	60	65.3	146.250	CVT	CVT1.76MA-R	7/14 /04
	75	82.3	187.000	CVT	CVT1.76MA-R	7/14 /04
1920 x 1080	60	67.5	148.500	CEA Standard	CEA -861	-
1920 x 1200	60	74.0	154.000	CVT Red. Blanking	AddDMT	3/4/03
	60	74.6	193.250	CVT	AddDMT	3/4/03
1920 x 1440	60	88.822	184.750	CVT Red. Blanking	CVT2.76M3-R	-
2048 x 1152	60	70.992	156.750	CVT Red. Blanking	VDMT REV	11/17 /08
2048 x 1536	60	94.769	209.250	CVT Red. Blanking	CVT3.15M3-R	-
2560 x 1080	60	66.636	181.250	Cinema 21:9 Aspect Ratio	N/A	N/A

5 Electrical Specifications

5.1 Absolute Maximum Conditions

Permanent damage may occur if absolute maximum conditions are violated. Refer to Section 5.2 for functional operating limits.

Table 5-1 Absolute Maximum Conditions

Symbol	Parameter	Min	Typ	Max	Unit
VDD5_IN	5V Power Input	-0.3	—	6	V
VDD33	3.3V power input	-0.3	—	3.96	V
VDD33_VDAC	3.3V Video DAC power input	-0.3	—	3.96	V
AVD_ADAC	3.3V Audio DAC power input	-0.3	—	3.96	V
T _A	Junction temperature	-40	—	125	°C
Q _{JA}	Storage temperature ¹	-65	—	150	°C
ESD _{HBM}	ESD protection (Human body model)	—	—	±4	KV
ESD _{CDM}	ESD protection (Charge Device model)	—	—	700	V

1. Max 260°C can be guaranteed with max 8 sec soldering time.

5.2 Operating Conditions

Table 5-2 Normal Operating Conditions

Symbol	Parameter	Min	Typ	Max	Unit
VDD33_OUT	3.3V LDO output	3.0	3.3	3.6	V
VDD5_IN	5V Power Input	4.75	5	5.25	V
VDD33	3.3V power input	3.0	3.3	3.6	V
VDD33_VDAC	3.3V Video DAC power input	3.0	3.3	3.6	V
AVD_ADAC	3.3V Audio DAC power input	3.0	3.3	3.6	V
T _A	Ambient temperature	-10	—	70	°C
Q _{JA}	Package thermal resistance, no air flow	—	39.3	—	°C/W

5.3 Electrical Specification

Table 5-3 DC Electrical Specification

Symbol	Parameter	For 3.3V I/O		
		Min	Typ	Max
V _{il} (V)	Input low voltage	—	—	0.8
V _{ih} (V)	Input high Voltage	2.0	—	—

Symbol	Parameter	For 3.3V I/O		
		Min	Typ	Max
V_{ol} (V)	Output low voltage	0	—	0.4
V_{oh} (V)	Output high voltage ¹	2.4	—	—
I_{in} (uA)	Input leakage current	-10	—	+10
I_{hiz} (uA)	Output tri-state leakage current	-10	—	+10

Table 5-4 AC Electrical Specification

Symbol	Description	Min	Typ	Max	Unit
T_{DPS}	Intra-Pair Differential Input Skew			0.4	T _{bit}
T_{CCS}	Channel to Channel Differential Input Skew			1.0	T _{pixel}
T_{IJIT}	Differential Input Clock Jitter Tolerance			0.3	T _{bit}
F_{RXC}	TMDS Clock Frequency	25		200	MHz

Table 5-5 Audio Electrical Characteristics

Symbol	Description	Load(Ω)	Min	Typ	Max	Unit
SNR	Signal to Noise Ratio	1K	--	-73	--	dB
DR	Dynamic Range	1K	--	-73	--	dB
THD+N	Total Harmonic Distortion	1K	--	-60	--	dB
ICI	Inter-channel isolation	1K	--	-75	--	dB

5.4 CS5213AN Power Consumption

Different applications would result in different power consumptions of CS5213AN. For example, whether to adopt the embedded oscillator, and how fast of the video clock frequency are all definitely the key factors of the power consumption of CS5213AN. The following tables show the reference power consumption of CS5213AN in several different application conditions.

Table 5-6 CS5213AN Typical Power Consumption

Active Resolution / Standby	Min	Typ	Max	Unit
800x600x60 (74.25-MHz)	-	803.4	-	mW
1024x768x60 (103-MHz)	-	871.8	-	mW
1920x1080x60 (148-MHz)	-	902.5	-	mW

Note: In practice, the measured power consumption might be slightly different from the tables above due to the different video content and the different measurement equipment

6 Package Specification




Figure 6-1 CS5213AN Package Outline (QFN32 Leads 4x4mm)

Table 6-1 Package Dimension

Symbol	Dimension in mm			Dimension in inch		
	Min	Normal	Max	Min	Normal	Max
A	0.80	0.85	0.90	0.031	0.033	0.035
A1	0.00	0.02	0.05	0.000	0.001	0.002
A2	—	0.65	0.70	—	0.026	0.028
A3		0.20 REF			0.008 REF	
b	0.15	0.20	0.25	0.006	0.080	0.010
D/E		4.00 BSC			0.157 BSC	
D2/E2	2.55	2.70	2.85	0.096	0.106	0.116
e		0.40 BSC			0.016 BSC	
L	0.30	0.40	0.50	0.012	0.016	0.020
L1	0.282	0.382	0.482	0.011	0.015	0.019

7 Ordering Information

The CS5213AN can be ordered using the part numbers in Table 7-1. Please consult sales for further details.

Table 7-1 CS5213AN Ordering Information

Part No.	Description	Temperature Range	Packing Type
CS5213AN	32 Pin (QFN) Lead-free package	Commercial: 0 to 70 degree C	5K / T &R

8 Revision History

Table 8-1 Document Revision History

Revision	Date	Changes
V0.1	April 2020	Initial version
V0.2	May 2020	Update
V0.3	June 2020	Update Pin Assignments and Pin Description
V1.0	Oct. 2020	Update Pin Assignments and Pin Description
V1.1	May. 2021	Update Power Consumption table
V1.2	Jun. 2021	Update doc template