

Draper Projector Lift Manual



File Name: Draper Projector Lift Manual.pdf

Size: 3796 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 22 May 2019, 19:11 PM

Rating: 4.6/5 from 808 votes.

Status: AVAILABLE

Last checked: 5 Minutes ago!

In order to read or download Draper Projector Lift Manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[❑ Register a free 1 month Trial Account.](#)

[❑ Download as many books as you like \(Personal use\)](#)

[❑ Cancel the membership at any time if not satisfied.](#)

[❑ Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Draper Projector Lift Manual . To get started finding Draper Projector Lift Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Draper Projector Lift Manual

Its use is restricted to individuals and organizations with a Draper account number. Register now! Send a message to Contact Draper if you should have access to this file. Its use is restricted to individuals and organizations with a Draper account number. Register now! Send a message to It features a maximum 35 pound lifting capacity and requires only a minimal amount of overhead ceiling space for installation. Kit includes ceiling trim ring and closure panel. Serious injury or damage could result. Scissor Lift is designed to accommodate ceiling suspended equipment. Equipment should not be allowed to rest on optional ceiling closure during operation refer to section titled "Installing Projector". Entire bottom of unit must be unobstructed to permit proper operation. Sufficient clearance must be allowed below projector or optional ceiling closure 4 for Model SL4, 5 for Model SL5, etc.; 11 for Model SLX11, 12 for Model SLX12, etc. Unit must be installed level use a carpenter's level. Unit operates on 110/120V AC 60 Hz. current. Note Unit has been thoroughly inspected and tested at factory and found to be operating properly prior to shipment. Minimum clearance above ceiling level varies according to Scissor Lift model, plus height of projector, optional mounting bracket, optional ceiling closure, and optional plenum rated housing. Arrange to provide service access to the unit. As Soon As Scissor Lift Arrives. Open carton and inspect for damage. Locate the following parts A. The unit itself B. Controls C. Any optional equipment plenum housing, closure panel, ceiling finish kit or decorative cover all ship in separate cartons. Test lift prior to installation. The threaded rods should pass through the corner mounting flanges and be secured by nuts above and below. The unit should then be guy wired or blocked to prevent swinging. All installations should observe the following guidelines. <http://pilot-market.ru/new/files/cooking-mama-wii-manual.xml>

- **draper projector lift manual, draper conceal reveal projector lift manual, draper projector lift manual free, draper projector lift manual download, draper projector lift manual 2017, draper projector lift manual instructions, draper projector lift manual 2016, draper projector lift manual online, draper projector lift manual youtube, draper projector lift manual video.**

Access from above the unit, with enough clearance to remove the top cover, should be provided in case service is required. If installing above a hard ceiling, optional Draper Access Panels are available to allow access to the unit. Installer must ensure that all fasteners and supports are of adequate strength to securely support Scissor Lift and projector. Fastening methods must be suitable for mounting surface, and securely anchored so that vibration or abusive pulling on unit will not weaken installation. Unit should be level, with weight shared more or less equally by all four threaded mounting rods. Bottom of unit must be unobstructed after installation. Sufficient clearance Electrical Connections Unit operates on 110/120V AC, 60 Hz. current. Removing the top cover of the unit and opening the electrical box exposes terminals for field connections. Unit is shipped with internal wiring complete. Wire to connect unit to power supply should be furnished by installer. Connections should be made in accordance with wiring diagram, and wiring should comply with national and local electrical codes. All operating switches should be "off" before power is connected. Standard switch shown below comes with 75' of cable and should be plugged in to box on front of top panel of lift to control lift. If you encounter any difficulties installing or servicing your Scissor Lift, call your dealer or Draper, Inc. Operation When unit is first operated, be cautious. If unit fails to operate when the toggle switch is flipped "down", return switch to "off" and recheck electrical connections before proceeding. Cycle unit down and up several times to confirm satisfactory

fac to ry operation. Standard Single Station Control— One 12V toggle switch mov ing 3po si tion toggle switch to “down” po si tion will start lift down. Moving toggle switch to “up” will start lift up.<http://angkortaxiservice.com/userfiles/cooker-hood-installation-manual.xml>

When lift is in “show” position, travel will au to mat i cal ly be stopped by factory set limit switch es. When ev er switch is placed in center “off” position, operation will stop. One, 12V key switch will lower lift from “show” to “service” position. Video Interface Control— This optional 12V control device allows the Scissor Lift switch to control the operation of a Draper motorized projec tion screen via a relay. Multiple Station Control —Optional, moves lift from “stored” to “show” positions only. Each switch ing station has a threebutton switch with “up”, “down”, and “off” buttons. Lift starts up or down when ap pro pri ate button is pressed, and may be stopped by pressing “off” button. Factory set limit switch es stop lift automatically when projec tor is in “show” position. Multiple Station Control re quired for this option. Moves lift from “stored” to “show” positions only. Infrared or Radio Frequency Remote Control— If ordered, a threebutton transmitter is provided, with “up”, “down”, and “stop” buttons. Unit starts up or down when appropriate button is pressed, and may be stopped by pressing “off” button. Factory set limit switches stop unit au to mat i cal ly when projector is in “show” po si tion. UP DOWN OFF OFF Next Page 2 Scissor Lift by Draper page 2 of 6Page 3 Scissor Lift by Draper page 3 of 6. You will find the current user manual for Draper projector lifts in the details of individual products. We also recommend looking through our discussion forum which serves to answer questions and solve problems with draper products. When concealed, your projector is pro. This projector lift off. Select a model based on the maximum lowering distance needed for easy access for servicing. A simple switch or wireless transmitter optional allows it to be shown as an. While other. Using a wireless transmitter or via switch and a precision actuator with preset limits, it ea.

The Revelation permanently conceals the projector and its noise above the ceiling at all times. While other products t. The Orbiter is designed to fit in small ceiling cavities and in angled ceilings making it versatile. The Orbiter is designed to fit in small ceiling cavities and in angled ceilings making it versatile. The builtin flexibility allows. The Revelation permanently conceals the projector and its noise above the ceiling at all times. While other products. The Draper Revelation permanently conceals the projector and its noise above the ceiling at all times. While other p. Try Google Search! Operation Simmons LRF600 4x20 Rangefinder 801408C Posted by Terry wheeler 20200922 010205 I depress button unit on depress again for range no range appears just dashes. User manual protest 6x20 Simmons LRF600 4x20 Rangefinder 801408C Posted by Terry wheeler 20200922 005936 I need used manual for item in subject. Blown fuse Wildgame Innovations Quik Set 225 Poly Barrel Feeder W225D Posted by Kasey 20200921 023059 My feeder is not turning on. I replaced the Battery in it and it will not turn on with a fully charged new battery I believe it's the fuse but I'm not sure. I need the manual to see what size fuse I need to replace it. Owners Manual Wildgame Innovations Illusion 8 Lights Out Trail Camera I8B20 Posted by Jeff 20200921 012318 I need a owners manual for the Illusion 8 Lights Out. PR, AK, HI and Military Boxes, please contact our sales specialists for freight quotes. We will still offer other expedited shipping methods, such as 3day, 2day and overnight delivery for an additional charge. Truck shipments will be tailgate delivery; inside delivery and other special arrangements may incur additional charges. Regardless of the shipping method selected, each item has a lead time prior to shipment, which is generally stated on the product page.

<http://gbb.global/blog/dreamweaver-cs4-missing-manual-pdf>

Regardless of the shipping method selected, each item has a lead time prior to shipment PR, AK, HI and Military Boxes, please contact our sales specialists for freight quotes. on every item in our network of websites. We will still offer other expedited shipping methods, such as 3day, 2day and overnight delivery for an additional charge. Truck shipments will be tailgate delivery; inside delivery

and other special arrangements may incur additional charges. Regardless of the shipping method selected, each item has a lead time prior to shipment, which is generally stated on the product details page. It can be installed in an existing 2 x 2 ceiling opening without disturbing the ceiling framework. The projector's "show" position can be set at any point with infinite adjustability, up to 48" extension. 35 pound lifting capacity. The Micro Projector Lift utilizes the same exclusive 3 scissor design as Draper's popular Scissor Lift but features a compact sidefolding scissor. Safety belt provides extra protection. Closed height of lifting unit is only 5" tall not including projector, mounting mechanism or closure, so a minimal amount of overhead ceiling space is required. Factory Installed Cables Draper will factory install cables for RGBHV with BNC or 15pin HD connectors, SVideo, Composite and Component Video with BNC or RCA connectors, Serial Communication for projector control with DB9 connectors, CAT 5e, CAT 6, and HDMI. This option is available on the LCD lift, Micro Projector Lift, and Scissor Lifts. This option save installation time in the field since installer does not have to attach cables to the lift. Can be independently operated using Drapers motorized lift controls. Warranted for one year against defects in materials and workmanship. Please use live chat or leave a message for a quick callback from our team. This projector lift offers three positions store, show and service.

The Scissor Lift stabilizes projector both laterally and front—to—back with 3 sets of scissors. SLX Series range with sizes at 10 305cm, 14 427cm, 17 518cm, 21 640cm, 24 731cm, and 28 853cm. 350 lbs. 159kg lifting capacity. This option is available on the LCD lift, Micro Projector Lift, and Scissor Lifts. This option save installation time in the field since installer does not have to attach cables to the lift. The SLX includes low voltage control for easy interface with secondary systems. Optional current sensor available. Call 8882480675 for the best deal. Terms of Use. Privacy Policy. Do Not Sell My Personal Information. All other company or product names mentioned herein are trademarks or registered trademarks of their respective companies. The Micro Projector Lift MPL is small and convenient, just like the projectors it is designed to accommodate. Weighing only 35 pounds, it can be installed in an existing ceiling opening without disturbing the ceiling framework. The projector's "show" position can be set at any point with infinite adjustability, up to extension. The Micro Projector Lift utilizes the same exclusive 3 scissor design as Draper's popular Scissor Lift see page 6, but features a compact sidefolding scissor. Safety belt provides extra protection. Closed height of lifting unit is only tall not including projector, mounting mechanism or closure, so a minimal amount of overhead ceiling space is required. Overall height of plenum is adjustable. Includes ceiling trim ring. Projector may also be mounted. Overall lift dimensions W x L 21. Closure panel weighs 10 lbs. 5 Does not include any load placed on MPL's prewired power cable. Ball joint adjusters in. Photograph by Wayne Williams, Indianapolis, IN. U. S. Patent Nos. D395,909 and 6,637,711. Other patents pending. Download an official Draper user manual in which you will find instructions on how to install, use, maintain and service your product.

The panel closes up the hole in the ceiling into which the projector is installed. In the Box Draper 300583 Ceiling Closure Panel for Scissor Lift SL412 B Sided, Black Limited 1Year Warranty Table of Contents Please send it to us and help us expand our library of instruction manuals. And what about you This product has already been rated by 83 owners. Add your rating and experience with the product. Let us know and we will try to add the missing manual Hercules dj starter kit dj cintrol starlight HDP DJ m 40.2 dj monitor 32. Hi. I would like to get a manuals for. Google Home Personal Assistant. Google Nest Mini 2nd Generation with Google Assistant. Thank you. Quik Pod Quick Pod Deluxe Extendable. Cursor jumps around. Name John Dyer Logitech M720 Triathlon Mouse I recently bought the keyboard mouse combo. Help the key board is working fine but the mouse cursor has a mind of its own and when I use the wheel to move the cursor up or down. When I stop the cursor it will move it up or down by itself. It happens when I am on the internet shop. JBL 600 BTNC Headphones Name Tara Evans JBL TUNE 600 BTNC Wireless OnEar Headphones Hello, the

right side of my headphones isn't working. I've tried all of the troubleshooting steps and nothing has worked.. instructions to charge my pelican 2450 Name Mae Joseph Pelican Stealthlite 2450 Light Hello I have the flashlight but cannot seem to charge it. I have no instructions.. Korg MA2 Name David Ginn Korg MA2 Digital Metronome I am a beginner learning guitar and purchased MA2 metronome to improve my scales. I required it for just basic timing starting at 60 bpm. I had it set at this basic metronome mode and began practicing everything was working well until unfortunately I dropped the metronome f. Bose T8S; help with vocal settings and effects. Name Chris Bose T8S ToneMatch Mixer Can someone provide me with step by step instruction for vocal settings. Nice warm vocal with effects.

All of the delay and reverb settings I've messed with seem to my ears to be very metallic and harsh. Im sure it's my error not Bose. I'm just finding it difficult to achi. Our instructions database is constantly updated and supplemented with new products. Looking for instruction manuals Ask us. Installation contrary to instructions inv alidates warranty. Do not obstruct operation of Scissor Lift with.Serious injur y or damage could result. Scissor Lift is designed to accommodate ceiling suspended equip ment. Equipment should not be allowed to rest on optional ceiling closure during operation refer to section titled "Installing Pro jec tor". Entire bottom of unit must be unobstructed to per mit proper op er a tion. Suf cient clearance must be allo wed belo w projector or op tion al ceiling closure 4 for Model SL4, 5 f or Model SL5, etc.; 11 for Model SLX11, 12 f or Model SLX12, etc. Unit must be installed le v el use a carpenter's le vel. Unit operates on 110/120V A C 60 Hz. current. Note Unit has been thoroughly inspected and tested at f actor y and f ound to be operating properly prior to shipment. Planning Based on screen location and projector speci.Minimum clear ance abov e ceiling le v el v aries according to Scissor Lift model, plus height of projector, optional mounting bracket, optional ceiling closure, and optional plenum r ated housing. Arrange to provide service access to the unit. As Soon As Scissor Lift Arrives. Open car ton and inspect f or damage. Locate the f ollowing parts A. The unit itself B. Controls C. Any optional equipment plenum housing, closure panel, ceiling.The threaded rods should pass through the cor ner mount ing.The unit should then be guy wired or bloc k ed to pre vent s wing ing. All installations should obser v e the f ollowing guidelines. Access from abov e the unit, with enough clearance to remo v e the top cov er, should be pro vid ed in case ser vice is re quired.

If installing abov e a hard ceiling, optional Draper Access P anels are availab le to allow access to the unit. Installer must ensure that all f asteners and suppor ts are of ad e quate strength to securely suppor t Scissor Lift and projector. F astening methods must be suitable f or mounting surf ace, and se cure ly anchored so that vibration or ab usive pulling on unit will not w eaken installation. Unit should be le vel, with w eight shared more or less equally by all f our threaded mount ing rods. Bottom of unit must be unobstructed after installation. Suf cient clear ance Electrical Connections Unit operates on 110/120V A C, 60 Hz. current. Removing the top co ver of the unit and opening the electrical bo x e x poses ter mi nals for.Wire to connect unit to power supply should be furnished by in stall er. Con nec tions should be made in accordance with wiring di a gram, and wiring should com ply with na tion al and local elec tri cal codes. All op er at ing switches should be "off " bef ore power is con nect ed. Standard s witch shown belo w comes with 75 of cable and should be plugged in to bo x on front of top pan of lift to control lift. If you encounter an y dif.Operation When unit is.If unit f ails to operate when the toggle s witch is.Cycle unit down and up se ver al times to con.Standard Single Station Contr ol— One 12V toggle s witch mov ing 3po si tion toggle s witch to "down" po si tion will star t lift down. Moving toggle s witch to "up" will star t lift up. When lift is in "show" position, trav el will au to mat i cal ly be stopped by f actor y set limit switch es. When ev er switch is placed in center "off " position, operation will stop. One, 12V k ey s witch will lower lift from "show" to "ser vice" position. Video Interface Control— This optional 12V control de vice allows the Scissor Lift s witch to control the operation of a Draper motorized pro jec tion screen via a rela y.

Multiple Station Control —Optional, moves lift from “stored” to “show” positions only. Each switching station has a threebutton switch with “up”, “down”, and “off” buttons. Lift starts up or down when appropriate button is pressed, and may be stopped by pressing “off” button. Factory set limit switches stop lift automatically when projector is in “show” position. Multiple Station Control required for this option. Moves lift from “stored” to “show” positions only. Infrared or Radio Frequency Remote Control— If ordered, a threebutton transmitter is provided, with “up”, “down”, and “stop” buttons. Unit starts up or down when appropriate button is pressed, and may be stopped by pressing “off” button. Factory set limit switches stop unit automatically when projector is in “show” position. Read instructions completely before proceeding. Test lift prior to installation. Follow instructions carefully. Installation contrary to instructions invalidates warranty. Do not obstruct operation of Scissor Lift with fingers or any object. Serious injury or damage could result. Scissor Lift is designed to accommodate ceiling suspended equipment. Page 2 Scissor Lift by Draper page 2 of 6 Installing Optional Plenum Housing Installing Projector Depending on job conditions and projector, it may be easier to remove optional ceiling closure panel before installing projector. Generally, the video projector should be suspended from the bottom pan according to projector manufacturer’s instructions and recommended standard ceiling mounting hardware. For projectors 26 lbs. Place tile into trim frame. Find the empty slot in the bottom of the top pan of lift the only empty slot. Use the openend wrench provided. Find the threaded coupling long nut just inside the top pan through the slot. Push wrench toward rear of unit to lower. Pull wrench toward front of unit to raise.

Find the Draper screen or accessory you need easier by selecting from one of the products below. If you do not see what you are looking for, call 800.784.1998 to speak with one of our lighting specialists. In most cases, we can find the Draper projector screen or equipment you need at a competitive price. Please check your inbox, and if you can’t find it, check your spam folder to make sure it didn’t end up there. Please also check your spam folder. Can specify at time of order Overall height of projector, plus optional mounting bracket, plus optional ceiling closure, plus optional plenum housing adds to overall height of equipment installed above ceiling. For other switching options, please select from below Scissor Lift equipped with 3 sets of stabilizing scissors, positioned on the left, right, and rear sides. Also equipped with failsafe inertial safety belt system and Cable Management System with projector power cord. Factory set limit switches to automatically stop travel at store, show, and service positions. Single Station Control, standard, consists of one 12V toggle switch to lower lift from “stored” to “show” positions, and one 12V momentary key switch to lower lift from “show” to “service” position. Optional LVCIH for operation from “stored” to “show” positions only; required for use with Key Operated Switch. Optional ceiling closure panel. Choose a model based on number of feet needed 1117 to put projector within easy reach for servicing. Installer shall provide mounting hardware appropriate to ceiling conditions. Steel ball joint attaches to Universal Projector Bracket with twistlock engagement. Min. overall height of assembled unit shall. Two setscrews lock ball joint in position. Max. load 26 lbs. Ceiling Access Door Provides access to projector and lift when unit is installed above hard ceiling. Finished by ceiling contractor to match ceiling.

As attractive as it is durable, this economical screen should be a frontrunner when it comes to buying your screen. The screen is housed within a hard steel shell which features matching end caps. As attractive as it is durable, this economical screen should be a frontrunner when it comes to buying your screen. Let us know YOUR RECENTLY VIEWED ITEMS Browsing History ON Clear History Not responsible for typographical or illustrative errors. Download PDF Access Fit E Electric Projection Screen Engineered with compact housing less than 6” tall, the ceilingrecessed Access FIT E electric projection screen fits tighter ceiling spaces. Download PDF Ultimate Access V Electric Projection Screen Complete concealment and smooth clean design makes the ceilingrecessed Ultimate Access V ideal for boardrooms, midsize training rooms, universities, or home theaters.

Download PDF Premier XL Electric Projection Screen Ideal for conference rooms, classrooms, or home theaters, the economical Premier XL wall or ceilingmounted electric projection screen features a tabtensioned viewing surface. Download PDF Silhouette V Electric Projection Screen With slender dimensions, the electric, tabtensioned, wall or ceilingmounted Silhouette V projection screen features a contemporary design. Download PDF Artisan V Electric Projection Screen The Artisan V electric, wall or ceilingmounted, tabtensioned projection screen offers quality engineering with style. This screen features either a solid, handrubbed hardwood or plastic laminate case with an array of colors, finishes, or custom color matching to the existing interior decor. Download PDF Envoy Electric Projection Screen This lowcost, ceilingrecessed, electric projection screen provides a clean appearance when fully retracted making the Envoy perfect for meeting rooms, executive facilities, or conference and training centers.

Download PDF Cineperm Fixed Projection Screen Designed to be wallmounted, suspended from a ceiling, or flown, Cineperm features an economical, fixed screen that is versatile. Download PDF Clarion Fixed Projection Screen With a truly flat viewing surface, the fixed frame Clarion projection screen features better image quality. The value of a fixed frame is the method used to attach the screen to the frame. Download PDF Onyx Fixed Projection Screen Sharper image quality makes the fixed frame Onyx projection screen ideal for control centers, boardrooms, training centers, home theaters, or any application that requires better image quality. Download PDF RoadWarrior Portable Projection Screen The rugged portable RoadWarrior projection screen features pneumatic cylinders for easy setup. Simply put it on the floor, open the case, and lift with one finger to the desired height. Download PDF Traveller Portable Projection Screen This lightweight, portable projection screen offers a clean, simple design with a black “rise” below the image area. An infinitely adjustable telescoping mast provides fast, easy setup by locking with a twist to position the screen at the desired height. Download PDF Luma Manual Projection Screen The choice for classrooms or boardrooms, the Luma wall or ceilingmounted, freehanging, manual springroller projection screen features an attractive scratchresistant pentagonal case. Download PDF Premier C Manual Projection Screen The crankoperated Premier C wallor ceilingmounted, tabtensioned projection screen features a crank handle for enhanced screen security. Download PDF Silhouette M Manual Projection Screen The wall or ceilingmounted Silhouette M manual, springroller projection screen features complete retraction of the screen and dowel inside the case for a clean, streamlined exterior. Download PDF Paragon V Electric Projection Screen The wall or ceilingmounted Paragon V electric projection screen is Draper’s largest tabtensioned screen.

Its size makes it ideal for auditoriums or lecture halls. Tabtensioned screens provide a perfectly flat viewing surface with better image quality. Download PDF Cinefold Portable Folding TrussStyle A portable folding projection screen, the TrussStyle Cinefold features an extra rigid trussstyle frame that accommodates large audience presentations. Engineered with special frame stiffeners, heavyduty leg stabilizers, and antisway stabilizers to provide extra reinforcement and durability. Download PDF Access FIT V CeilingRecessed, TabTensioned, Electric The slim case design of the Access FIT V ceilingrecessed, tabtensioned, electric projection screen provides easy installation above the ceiling—perfect for small conference or multipurpose rooms and home theaters. Download PDF Access V Motorized, CeilingRecessed, TabTensioned The Access V is a motorized, ceilingrecessed projection screen with a steel white case that installs above the ceiling. A trim flange finishes the ceiling opening for a clean appearance. Download PDF StageScreen FreeStanding or Flown The freestanding or flown StageScreen features interchangeable frame pieces. All available sizes utilize combinations of the same frame sections; these interchangeable parts make it easy to reuse frame pieces to create different size viewing formats. All Rights Reserved. Privacy Policy Terms and Conditions Cookie Policy Site Map Get a Quote Today Fill out your information below and we will get in touch with you about providing the perfect Pro AV solution for your needs. Phone This field is for validation purposes and should be left unchanged. Using stampedeglobal.com means you

agree to our use of cookies. We have published a new cookies policy, which you should read to find out more about the cookies we use. [Ok View Cookies Policy](#). Shop ShopMessage Stylish designs to discover daily. Shop ShopMessage Classic home. Comfortable cost. Shop ShopMessage The best of modern, priced for real life.

Unlock insider pricing Enter Your Email Address Notify Me Send me exclusive sales Save Product Overview Description Click to close Designed specifically with todays smaller, lighter projectors in mind, Drapers Micro Projector Lift MPL is small, convenient, and fits within an existing ceiling grid. The closed height of the lifting unit requires just a minimal amount of overhead ceiling space. All components can be serviced from below the unit, so the ceiling need never be opened. Projectors show position can be set at any point, with infinite adjustability, up to 4 1.2 meter extension. Three sets of scissors left, rear, and front stabilize the projector laterally and fronttoback. Please Note All MPL orders require a completed planning sheet. Please call for information. Features Ceiling closure panel Universal steel ceiling closure with white baked enamel can also accept ceiling tile Factory installed cables for RGB, video and control Access door A hinged access door in the ceiling for when access to the projector from above the ceiling is not convenient Can be independently operated using Drapers motorized lift controls Ceiling finish kit Ceiling closure panel and ceiling trim ring to finish ceiling opening Product Details Weight Capacity 35 lb. Mount Type Lift More About This Product When you buy a Draper Micro Projector Lift online from Wayfair, we make it as easy as possible for you to find out when your product will be delivered. If you have any questions about your purchase or any other product for sale, our customer service representatives are available to help. Whether you just want to buy a Draper Micro Projector Lift or shop for your entire home, Wayfair has a zillion things home. Audio Visual, Window And Athletic Equipment CONTACT INFO CONTENT DISTRIBUTION Audio Visual Equipment Manual Projection Screens The detachable crank handle provides an added benefit of limiting screen access within educational or businessrelated environments.

<https://ayurvedia.ch/dreamweaver-cs4-missing-manual>