



U.S. Environmental

DEVICE & DATA EXPERTISE

usenvironmental.com

(888) 550-8100

PRODUCT GUIDE

RENTALS • SALES • SERVICE



Introducing envizor

A giant leap in perimeter air monitoring data acquisition

See page 5 for more details.



THE BEST RENTAL EXPERIENCE POSSIBLE

What do we mean by that? It starts with the Quality Standards. These are the expectations that we have established for every area of our operation. We expect each and every associate to display a commitment to these standards.

PRODUCTS

The presentation of a first class, superior product is the foundation of providing the best rental experience possible. Our products will be 1st rate in cleanliness, condition, and functionality.

EMPLOYEE DEVELOPMENT

Each employee will be knowledgeable, team-oriented, and committed to continuously improving.

OFFICE & WORKSPACE CONDITION

Our workspaces will be organized and welcoming. The quality of our entire operation begins with a safe, clean, well-maintained, and organized workspace. Attention to small things make big things possible.

INVENTORY MANAGEMENT

In order to quickly meet the demands of our clients, we will maintain and improve our ability to track the physical location and status of each and every asset in our inventory in real-time.

ACCOUNTING

Our invoices will be prepared and submitted accurately and in a timely manner.

CUSTOMER SERVICE

We will meet or exceed the expectations of every client. By focusing on friendliness, professionalism, timeliness, accuracy, and technical knowledge, our people will be more than just another vendor, rather a partner/resource for each and every client.

Section	Page	Section	Page	Section	Page
Photo Ionization Detectors.....	1, 2, 3	Sound.....	18	Bladder Pumps.....	34, 35
Perimeter Air Monitoring.....	4, 5	Leak Detection.....	19	Compressors & Controllers.....	36, 37
Combustible Gas Monitors.....	6, 7	Thermal Imaging.....	19	Automatic Water Sampling.....	38
Flame Ionization Detectors.....	8	Water Level Indicators.....	20, 21	Discreet Water Sampling.....	39
Landfill Gas Monitors.....	9	Interface Probes.....	22	XRF.....	40
Mercury Vapor Analyzers.....	10	Pressure Transducers.....	23	Hammer Drills.....	41
Radiation.....	11	Flow Probes.....	24	Soil Sampling & Analysis.....	42, 43
Air Sampling.....	12, 13	MultiParameter Devices.....	25, 26, 27	Auto & Laser Levels.....	44
Air Pressure.....	14	Turbidimeters.....	28	GPS & Total Stations.....	45
Anemometers.....	15	Handheld Devices.....	29	Metal & Pipe Locators.....	46
Dust Monitors—Personal.....	16	Well Development.....	30	Generators.....	47
Indoor Air Quality.....	16	Peristaltic Pumps.....	31	Supplies.....	48-55
Gas Detection Tubes/Chips.....	17	Submersible Motor Pumps.....	32, 33		

PHOTO IONIZATION DETECTORS



ION SCIENCE Tiger

Ref # 1000

The Tiger is a PID VOC detector for the rapid, accurate detection of volatile organic compounds within the harshest of environments with a dynamic detection range. The Tiger incorporates Ion Science patented fence PID sensor technology with ultimate resistance to humidity and contamination.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	10.6 or 11.7 eV lamp	20,000ppm	.1ppm
Datalogs? Yes	Accessories		
Telemetry? Yes	Charger, Cradle, Alkaline Pack, 17L Regulator, Tedlar Bag 1L, Loaner Cal Gas		



ION SCIENCE Tiger LT

Ref # 1000

Entry-level handheld PID detector, Low cost but high on performance, Tiger LT is an entry-level version of the leading handheld Tiger PID detector.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	10.6 lamp	5000ppm	.1ppm
Datalogs? Yes	Accessories		
Telemetry? Yes	Charger, Cradle, Alkaline Pack, 17L Regulator, Tedlar Bag 1L, Loaner Cal Gas		



RAE Systems MiniRAE 2000

Ref # 1000

A compact monitor designed as a broadband VOC gas monitor and datalogger for work in hazardous environments.

Rentals? Yes	Options	Range	Resolution
Sales? No	10.6 or 11.7 eV lamp	10,000ppm	.1ppm
Datalogs? Yes	Accessories		
Telemetry? No	Charger, Alkaline Pack, 17L Reg., Tedlar Bag 1L, Loaner Cal Gas		



RAE Systems MiniRAE 3000

Ref # 1000

The MiniRAE 3000 delivers the most advanced VOC monitoring capabilities on the market.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	10.6 or 11.7 eV lamp	15,000 ppm	0.1ppm
Datalogs? Yes	Accessories		
Telemetry? Yes	Charger, Alkaline Pack, Travel Adaptor, 17L Reg., Tedlar Bag 1L, Loaner Cal Gas		



RAE Systems MiniRAE Lite

Ref # 1000

Hand-held monitor for VOCs provides superior reliability for leak detection, environmental cleanup, and remediation. Non-Intrinsically safe.

Rentals? No	Options	Range	Resolution
Sales? Yes	10.6 eV lamp	5000ppm	0.1ppm
Datalogs? No	Accessories		
Telemetry? No	Charger, Alkaline Pack, Travel Adaptor, 17L Reg., Tedlar Bag 1L, Loaner Cal Gas		

PHOTO IONIZATION DETECTORS

ION SCIENCE Cub

Ref # 1010

A personal VOC detector with leading PID technology worn within the breathing zone to detect volatile organic compounds, keeping you safe within your working environment.



Rentals? Yes	Options	Range	Resolution
Sales? Yes	10.6 or 11.7 eV lamp	5,000 ppm	0.1 ppm
Datalogs? Yes	Accessories		
Telemetry? Yes	Charging dock with AC cord, calibration cup		

RAE Systems ppbRAE 3000

Ref # 1020

Humidity resistant PID sensor for the most challenging environments.



Rentals? Yes	Options	Range	Resolution
Sales? Yes	9.8, 10.6 or 11.7 eV lamp	9999ppm	1 ppb
Datalogs? Yes	Accessories		
Telemetry? Yes	Charger, Alkaline Pack, Travel Adaptor, 17L Reg., Tedlar Bag 1L, Loaner Cal Gas		

ION SCIENCE Tiger PPB

Ref # 1020

The Tiger PPB is a VOC detector for the rapid, accurate detection of volatile organic compounds within the harshest of environments with a dynamic detection range down to 1ppb. The Tiger incorporates Ion Science patented PID sensor technology with ultimate resistance to humidity and contamination.



Rentals? Yes	Options	Range	Resolution
Sales? Yes	10.6 or 11.7 eV lamp	20,000ppm	1ppb
Datalogs? Yes	Accessories		
Telemetry? no	Charger, Cradle, Alkaline Pack, 17L Regulator, Tedlar Bag 1L, Loaner Cal Gas		

RAE Systems UltraRAE

Ref # 1030

The UltraRAE 3000 is the most advanced compound-specific monitor on the market and one of the few monitors that deliver accurate measurement of benzene from 50 ppb to 200 ppm and other VOCs up to 10,000 ppm.



Rentals? Yes	Options	Range	Resolution
Sales? Yes	9.8 or 10.6, 11.7 eV lamp	10,000 ppm	0.05 ppm
Datalogs? Yes	Accessories		
Telemetry? no	Charger, Alkaline Pack, Travel Adaptor, 17L Reg., Tedlar Bag 1L, Loaner Cal Gas		

ION SCIENCE Tiger Select

Ref #

Tiger Select is our handheld VOC detector with two mode operation for the detection of TACs and benzene providing accurate, reliable data in the most hazardous environments. Tiger Select utilizes our high output 10.0 eV detection system and benzene filter tube to ensure rapid detection and selective measurement.



Rentals? yes	Options	Range	Resolution
Sales? yes	10.0 eV stack	0-20000ppm	
Datalogs? yes	Accessories		
Telemetry? no	Stan .1ppm, TAC .01ppm Tube .001ppm		

PHOTO IONIZATION DETECTORS



ION SCIENCE Falco

Falco is our latest generation of fixed VOC detectors that continuously detect a wide range of volatile organic compounds (VOCs). Unique to Falco is its 'typhoon technology' safeguarding the PID sensor from condensing moisture for added reliability in severe weather conditions.

- Rentals? **no**
- Sales? **yes**
- Datalogs? **no**
- Telemetry? **no**

Options
10.0 ppm* 0.001 ppm • 50.0 ppm* 0.01 ppm • 1000 ppm* 0.1 ppm • 3000 ppm* 1 ppm



ION SCIENCE Titan

Titan is our fixed, continuous, real-time benzene-specific monitor designed for providing the ultimate device for plant and workforce. As with all our VOC detectors, Titan incorporates our patented PID sensor technology for ultimate resistance to humidity and contamination maximizing run time.

- Rentals? **no**
- Sales? **yes**
- Datalogs? **no**
- Telemetry? **no**

Options	Range
PID, 10.6 eV lamp coupled with selective filtering	0 - 20 ppm



ION SCIENCE TVOC

TVOC is a fixed detector for the continuous measurement of total volatile organic compounds, ideal for use in manufacturing and process industries. As with all our VOC detectors, TVOC utilizes our patented PID sensor technology with ultimate resistance to humidity and contamination.

- Rentals? **no**
- Sales? **yes**
- Datalogs? **no**
- Telemetry? **no**

Options	Range
10.6eV	Range: 0 to 10, 0 to 100 or 0 to 1000



Be Prepared.

Make sure to add calibration supplies to your gas monitor rental order. Each day, prior to use, a functional (bump) test should be performed. This verifies calibration by exposing the instrument to a known concentration of test gas. The instrument reading is compared to the actual quantity of gas present, but more importantly, the audible and visual alarms are verified to be functioning correctly. Otherwise, a full calibration must be performed.

Call your U.S. Environmental representative for more information.

PERIMETER AIR MONITORING

TSI DustTrak II 8530

Ref # 1040



The DustTrak™ II Aerosol Monitor 8530 is a desktop battery-operated, data-logging, light-scattering laser photometer that gives you real-time aerosol mass readings. It uses a sheath air system that isolates the aerosol in the optics chamber to keep the optics clean for improved reliability and low maintenance.

Rentals? Yes	Range:	400 mg/m3	Resolution:	0.001
Sales? Yes	Accessories			
Datalogs? Yes	Zero Filter, 37MM Filter, PM 2.5 Impactor, PM1 Top, PM4 Top, PM 10 Top, Impaction Plate, Power Supply, Envizor Environmental Enclosure, Autozero Module			
Telemetry? Yes				

TSI DustTrak DRX

Ref # 1050



Real-time dust monitoring takes a giant leap forward!! Only the DustTrak™ DRX Aerosol Monitor 8533 can simultaneously measure both mass and size fraction - no other monitor can do both.

Rentals? Yes	Range:	150 mg/m3	Resolution:	0.001
Sales? Yes	Accessories			
Datalogs? Yes	Zero Filter, 37MM Filter, PM 2.5 Impactor, PM1 Top, PM4 Top, PM 10 Top, Impaction Plate, Power Supply, Envizor Environmental Enclosure, Autozero Module			
Telemetry? yes				

Davis Vantage Vue

Ref # 1070



Davis Vantage Vue is the perfect weather station for the weather enthusiast, hobbyist or for industrial usage. The Vantage Pro2 is a rugged weather station model and comes with a wide range of exciting features to match you specific meteorological readings.

Rentals? Yes	Accessories			
Sales? Yes	Anemometer Cups, Vane, U-Bolt, Hardware, Serial Datalogger, USB Datalogger, Tripod			
Datalogs? Yes				
Telemetry? yes				

Netronix Thiamis 1000

Ref # 1500




The Netronix Thiamis 1000 is a remote monitoring device that combines control, data logging, digital processing, global positioning and telemetry into one. It links sensors and instruments in the field with the Netronix cloud network.

Rentals? Yes	Accessories			
Sales? Yes	3-way serial cable, Power Cable			
Datalogs? Yes				
Telemetry? Yes				

Envizor Cellara P3-S

Ref # 1500



The first environmental data monitoring system purpose-built for the North American market. CDMA and LTE-M networks. Simple, clean user interface equals less screen time, more productivity.

Rentals? Yes	Accessories			
Sales? Yes	Power Cable, Cellular Antenna, GPS Antenna, DustTrak Comm. Cable, RAE Systems Comm. Cable, Davis Comm. Cable, Svantek Comm. Cable, Envizor Environmental Enclosure			
Datalogs? Yes				
Telemetry? Yes				


Remote data acquisition is now easier and more reliable

Introducing the first environmental monitoring data system purpose-built for the North American market.



FEATURES

Strong Signal	The CDMA and LTE-M (CAT M1) networks have proven to be the largest, strongest, and best maintained networks in North America.
Secure, fixed power connectors	The threaded DC power connectors ensures that your device stays connected no matter what happens during deployment.
Simple, intuitive Status indicators	Three LED status displays—each supplied with green and orange colors—are engineered with logic to tell you which sensors are connected and working.
Test button	Sometimes, you want to see data right now! The Test button will send an immediate alert to you and your team.
envizor.io	Simple, clean user interface equals less screen time, more productivity.
Versatile, rugged enclosure	This enclosure is ready to be deployed anywhere, with any thing!



- ❖ **VOCs** down to ppb resolution
- ❖ Up to 5 **Toxic Gas** sensors
- ❖ Fugitive **Dust**
- ❖ **Weather**
- ❖ **Sound** level with octave analysis

COMBUSTIBLE GAS MONITORS



Industrial Scientific Ventis MX4

Ref # 1080

The Ventis MX4 is a portable multi-gas monitor. Offered as a diffusion monitor, it detects and measures gas(es) present in open space.

Rentals? Yes	Range
Sales? Yes	0-100 LEL; 0-30% O2; 0-1000ppm CO; 0-500ppm H2S
Datalogs? Yes	Accessories
Telemetry? No	Cradle, Cal Cup, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RAE Systems QRAE II

Ref # 1080

The QRAE II is a full-featured, compact, one- to four-sensor gas detector for oxygen, combustibles, hydrogen sulfide, or carbon monoxide. Key features include easy-to-change battery pack, a water-resistant case and a new state-of-the-art O2 sensor.

Rentals? Yes	Range
Sales? No	0-100% LEL; 0-30% O2; 0-1000 ppm CO, 0-100ppm H2S
Datalogs? Yes	Accessories
Telemetry? No	Travel Adaptor, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RAE Systems Qrae III

Ref # 1080

QRAE 3 is a versatile, rugged, one- to four-sensor pumped or diffusion gas monitor that provides continuous exposure monitoring of oxygen (O₂), combustibles, and toxic gases

Rentals? Yes	Range
Sales? Yes	0-100% LEL; 0-30% O2; 0-500 ppm CO, 0-100ppm H2S
Datalogs? Yes	Accessories
Telemetry? No	Travel Adaptor, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RAE Systems ToxiRAE

Ref # 1080

The industry's first and largest family of wireless, personal single-gas monitors that can reliably and accurately monitor a full range of common toxic industrial chemicals.

Rentals? Yes	Options
Sales? Yes	Cl2, CO, HCN, O2, NH3; H2S; NO; SO2; HCHO, more
Datalogs? yes	Accessories
Telemetry? No	Travel Adaptor, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



Industrial Scientific MX6 Ibrid

Ref # 1090

The Mx6 is the most adaptable six-gas monitor on the market. With hundreds of possible sensor combinations, and a robust list of available configuration settings.

Rentals? Yes	Range
Sales? Yes	0-100% LEL; 0-1500ppm CO; 0-500pm H2S; 0-30% O2; 0-2000 ppm VOC
Datalogs? Yes	Accessories
Telemetry? No	Cradle, Charger, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas

COMBUSTIBLE GAS MONITORS



RAE Systems Multirae

Ref # 1090

MultirAE is an advanced portable chemical detector. With the flexibility of up to six gas sensors and the convenience of wireless portability, this multi-gas monitor is versatile and customizable, while delivering real-time access to instrument readings.

Rentals? Yes	Range
Sales? Yes	0-100% LEL; 0-30% O2; 0-500 ppm CO, 0-100ppm H2S, 0-5000 ppm VOC
Datalogs? Yes	Accessories
Telemetry? Yes	Travel Adaptor, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RAE Systems Multirae Lite

Ref # 1090

This multi-gas monitor provides versatile, customizable detection and monitoring of up to six gases. It can test for VOCs, combustibles, and a range of toxic threats, as well as monitor sufficient oxygen levels, making it an excellent choice for personal protection and leak detection.

Rentals? Yes	Range
Sales? Yes	0-100% LEL; 0-30% O2; 0-500 ppm CO, 0-100ppm H2S, 0-5000 ppm VOC
Datalogs? Yes	Accessories
Telemetry? Yes	Travel Adaptor, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RAE Systems Multirae Pro

MultirAE is an advanced portable chemical detector. With the flexibility of up to six gas sensors and the convenience of wireless portability, this multi-gas monitor is versatile and customizable, while delivering real-time access to instrument readings.

Rentals? Yes	Range
Sales? Yes	0-100% LEL; 0-30% O2; 0-500 ppm CO, 0-100ppm H2S, 0-5000 ppm VOC
Datalogs? Yes	Accessories
Telemetry? Yes	Travel Adaptor, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RKI Gx-6000

A powerful hand-held instrument is capable of simultaneously monitoring up to 6 gases. In addition to the standard 4 confined space gases which include combustibles, O2, CO, & H2S, the GX-6000 has 2 additional smart channels that accept PID, IR or super toxic sensors.

Rentals? Yes	Range
Sales? Yes	0-6000 ppm VOC, 0-40% O2, 0-100ppm H2S, 0-500 CO
Datalogs? Yes	Accessories
Telemetry? yes	Charger, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas



RKI Eagle 2

Ref # 1100

The EAGLE 2 6gas meter includes a PID sensor for detecting high or low ppm levels (0-50 & 0-2,000) of VOC gases; % volume capability for CH4 and H2 using a TC sensor; PPM or LEL hydrocarbon detection at the push of a button.

Rentals? Yes	Range
Sales? Yes	0-2000 ppm VOC, 0-100% LEL, 0-500ppm CO, 0-100 H2S, 0-40% O2
Datalogs? Yes	Accessories
Telemetry? No	Charger, 58L Regulator, Tedlar Bag 1L, Loaner Cal Gas

FLAME IONIZATION DETECTORS

Infinicon Microfid

Ref # 1110

Photovac MicroFID FID Detector. The Photovac Microfid is one of the smallest and easiest to use flame ionization detectors made. It will run up to 12 hours continuous and has a range of up to 50,000 ppm. ... It is designed to be used with one hand and is lighter than most other FID meters.



Rentals? Yes	Accessories
Sales? No	Charger with AC cord, water trap filter, dust filter, probe tip, refill assembly, carrying strap, manual
Datalogs? No	
Telemetry? No	

Thermo TVA 1000B

Ref # 1120

The Thermo Scientific TVA-1000B Toxic Vapor Analyzer is capable of measuring a variety of organic vapors using FID technology, over a wide range of organic vapors can be measured, by the FID, over a wide dynamic range (0-50,000 ppm), monitoring some compounds that PID will not detect.



Rentals? Yes	Range	Resolution
Sales? No	PID: 0-2000; FID 0-50,000ppm	2.5ppm
Datalogs? Yes	Accessories	
Telemetry? No	H Tank, Filling Station, Charger, Probe Tip, Probe Gun, Wand	

Thermo 2020 Toxic Vapor Analyzer

Ref # 1120

The Thermo Scientific™ TVA2020 Toxic Vapor analyzer is the only intrinsically safe, portable field analyzer using both Flame Ionization Detection (FID) and Photo Ionization Detection (PID) technologies.



Rentals? Yes	Range	Resolution
Sales? Yes	PID: 0-2000; FID 0-50,000ppm	1 ppm
Datalogs? Yes	Accessories	
Telemetry? No	H Tank, Filling Station, Charger, Probe Tip, Probe Gun, Wand	



Be Prepared!

FIDs require Hydrogen to produce the flame. *How much Hydrogen will you need to complete your project? DON'T FORGET! We cannot ship Hydrogen. Local deliveries only.*

RELATED RENTAL ITEMS



Reference Number
7764
Description
Hydrogen Stubby

LANDFILL GAS MONITORS



Landtec Gem-2000

Ref # 1150

LANDTEC has provided the landfill industry with a technologically innovative family of products for more than a decade. The GEM™2000 and GEM™2000 Plus, designed by LANDTEC, are specifically for use on landfills to monitor landfill gas (LFG) extraction systems, flares and migration control systems.

Rentals? Yes	Range	Resolution
Sales? No	0-100% CH ₄ , 0-100% CO ₂ , 0-25% O ₂	0.3% CH ₄ and CO ₂ up to 5%; O ₂ 1%
Datalogs? yes	Accessories	
Telemetry? No	Charger, Temp. Probe, Comm. Cable, 17L Regulator, Tedlar Bag 1L, Loaner Cal Gas	




Landtec Gem-5000

Ref # 1150

The Landtec GEM 5000 is designed specifically for use on landfills to monitor Landfill Gas collection and control systems. The GEM 5000 samples and analyzes the methane, carbon dioxide and oxygen content of landfill gas with options for additional analysis.

Rentals? Yes	Range
Sales? Yes	0-100% CH ₄ , 0-25% O ₂ , 0-100% CO ₂ , 0-2000ppm CO, 0-500ppm H ₂ S
Datalogs? Yes	Accessories
Telemetry? No	Charger, Temp. Probe, Comm. Cable, 17L Regulator, Tedlar Bag 1L, Loaner Cal Gas



So much more than rentals...

Certified service, repairs, & training

Free estimates | 50% off rentals while your unit is in for repair

Since 1996, our family-owned company has been a leader in providing rentals of environmental and safety monitoring equipment, accessories, and related items. However, we do so much more. Not only are we authorized resellers and distributors for nearly all of the manufacturers we represent; we also have experienced, **factory-trained technicians** available for **training, service, and repairs** at each of our locations.

- Single and Multi-Gas Confined Space detectors
- Photoionization Detectors (PIDs)
- IAQ Monitors
- Landfill Gas Monitors
- Air Sampling Equipment
- Multi-Parameter Water Quality Instruments
- Level and depth meters and loggers
- Groundwater Pumps, controllers, and compressors
- Soil Sampling Equipment

MERCURY VAPOR ANALYZERS



Arizona Jerome 431-X

Ref # 1160

Mercury vapor analyzer uses our proprietary gold film sensor for accurate detection and measurement of toxic mercury concerns for applications such as industrial hygiene monitoring, mercury spill clean up and mercury exclusion testing. Simple push-button operation allows users to get readings in just seconds.

Rentals? Yes	Range	Resolution
Sales? No	0.999 mg/m3	0.001 mg/m3
Datalogs? Yes	Accessories	
Telemetry? No	Probe, Charger, Zero Filter	



Arizona Jerome J405

Ref # 1160

Mercury vapor monitor is redefining the portable mercury vapor analyzer market. Significant performance enhancements and modern communications capabilities have been combined to create a new option for mercury spill detection and clean-up analysis.

Rentals? Yes	Range	Resolution
Sales? Yes	999 µg/m3	0.01 µg/m3
Datalogs? Yes	Accessories	
Telemetry? No	Probe, Charger, Zero Filter	



Ohio Lumex Lumex Ra-915+

Ref # 1170

Ohio Lumex Mercury Vapor Analyzer RA-915 Light. Mercury analyzer RA-915 light is a low cost analytical instrument for measuring mercury concentrations in air. It is intended for assessment of indoor/outdoor air quality in residential and industrial settings.

Rentals? Yes	Range
Sales? No	2.0 ng/m3 – 20,000 ng/m3
Datalogs? Yes	Accessories
Telemetry? No	Charger, inlet adapter with filter, carrying bag and manual



ION SCIENCE MVI

Ref #

MVI is a portable mercury vapour indicator that accurately detects mercury in just three seconds, gives a real-time response and is ready to detect instantly on start up. Its dual beam UV absorption technology means MVI does not saturate or need regenerating between readings.

Rentals? yes	Range
Sales? yes	Range: 0.1 - 200 & 1.0 - 1999 microgram / cubic meter
Datalogs? no	
Telemetry? no	

RENTING VS. OWNING Why not have the best of both?

Long-Term Rental Program
U.S. Environmental's unique solution where you get the benefits of renting and owning!

- The equipment is always on-site or in your office.
- Replacements, when necessary, no additional cost.
- One monthly invoice. Easy!
- No hidden costs related to owning.

Terms & Conditions apply



RADIATION



Ludlum Model 19

Ref # 1180

The Model 19 is a highly sensitive gamma μR /meter employing an internally housed, 2.5 x 2.5 cm (1.0 x 1.0 in.) NaI detector. The measuring range is 0 to 50 $\mu\text{Sv/h}$ (0 to 5000 $\mu\text{R/hr}$).

Rentals? Yes	Range	Resolution
Sales? Yes	0 to 50 $\mu\text{Sv/h}$ (0 to 5000 $\mu\text{R/hr}$)	175 cpm per $\mu\text{R/hr}$
Datalogs? No	Accessories	
Telemetry? No	Alkaline batteries and manual	



Ludlum Model 2241-2

Ref # 1180

This instrument is a general purpose, digital ratemeter with a built-in scaler that provides timed counts over a user specified period.

Rentals? Yes	Range
Sales? Yes	0.0 $\mu\text{R/hr}$ –9999 R/hr
Datalogs? No	Accessories
Telemetry? No	Batteries and manual



Ludlum Model 3; Pancake Probe

Ref # 1180

The Model 3 is a general purpose, handheld, analog ratemeter known for accuracy and long-lasting dependability. It comes in a variety of measurement ranges and units to support the external radiation detector selected.

Rentals? Yes	Accessories
Sales? Yes	Alkaline batteries and manual
Datalogs? No	
Telemetry? No	



Don't Forget to stop your rental!

It's important to let U.S. know when you've finished your project...and we've made it easier than ever. On your smartphone, visit [usenvironmental.com/stop-rental](https://www.usenvironmental.com/stop-rental) and fill out the quick form. Of course, you can call, email, or just drop off the items, too.

AIR SAMPLING



Bios Defender

Ref # 2010

Digital flowmeters calibrator that make it easier than ever to calibrate air sampling pumps. Measure volumetric flow, standardized flow, which correct for temperature and pressure, or calibrate devices that read in mass flow.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories
Charger and manual



Bios DryCal DC-Lite Dcl

Ref # 2010

Air Flow calibrator is a field portable primary air flow standard. It uses 'near frictionless' piston technology--traversing a known volume to measure flow rate.

- Rentals? **Yes**
- Sales? **No**
- Datalogs? **no**
- Telemetry? **No**

Range
100 ml/min - 7 l/m, extended range = 10ml/min - 12 l/min
Accessories
Charger and manual



Gast 1532 Air Pump

Ref # 2010

Gast brand rotary vane pumps. The workhorses are heavy duty with a 1/10 hp motor that can be used for most all sampling applications. It can be used with PCM, TEM, Air-O-Cell and all viable impactors.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range
1.5 cfm
Accessories



SENSIDYNE Aircon-2

Ref # 2010

The AirCon-2 sampler is a high volume unit with an extended flow range, designed for collecting particulate in a given plant area.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Range
2-30 LPM
Accessories
Power Cable, Batteries



SENSIDYNE Gilian Challenger

Ref # 2010

An easy-to-use air flow calibrator for verifying and calibrating the flow rate of air sampling pumps. It has no moving parts and is battery powered.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
1-30 LPM	.75% of reading
Accessories	
AA batteries	

AIR SAMPLING

SENSIDYNE Gilian Gilair Plus

Ref # 2010

Personal air sampling methods with flow ranges between 1 and 5,000 cc/min. The GilAir Plus can perform both high-flow constant pressure and constant flow (450-5,000 cc/min) and low-flow constant pressure and constant flow (1-499 cc/min)



Rentals? Yes	Range	Resolution
Sales? Yes	1-5000 cc/min, 8hr run time	+/- 3cc/min
Datalogs? Yes	Accessories	
Telemetry? No	Cradle, Charger, hex tool, comm. Cable, manual	

SKC Aircheck Xr5000

Ref # 2010

The AirChek® XR5000 personal air sampling pump with Li-Ion battery provides powerful flows for particulate sampling, low flows for gas and vapor sampling, and the long run-times for low-concentration sampling.



Rentals? Yes	Range
Sales? Yes	5-5000 ml/min
Datalogs? No	Accessories
Telemetry? No	Charger, low flow kit, tube holder

SKC Vacuum Chamber

Ref # 2010

Vac-U-Chamber is a rigid air sample box that directly fills a sample bag using negative pressure provided by an air sample pump.



Rentals? Yes	Range
Sales? Yes	1-25L bag
Datalogs? No	Accessories
Telemetry? No	sample bag, tubing

Xitech 1060H

Ref # 2020

Model 1060H, 1–or 2–Liter High Vac Bag Sampler Accepts 1– or 2–liter sampling bags, See-through window Rechargeable battery, Installed rotameter valve for coarse fill rate control. Sample inlet: accepts any 1/4" OD tubing



Rentals? Yes	Range
Sales? Yes	Vacuum pump filling rate: .1-6.5L/min
Datalogs? No	Accessories
Telemetry? No	Carrying strap and operation manual

AIR PRESSURE

Ref # 2000



Dwyer 475 Mark III

Measures positive, negative, or differential pressures of air and natural gases in ranges from 1 in w.c. (0.249 kPa) to 150 psid (10.34 bar). The dual push pads on the front panel control the on/off, auto zero, and pressure unit selection, allowing for simple operation with no set up needed.

Rentals? Yes	Options
Sales? Yes	
Datalogs? No	Accessories
Telemetry? No	Alkaline battery, cut sheet


Ref # 2000



Dwyer Magnehelic Model 2000

Magnehelic® Gage for a versatile low differential pressure gage with a wide choice of 81 models and 27 options to choose from. Using Dwyer's simple, frictionless Magnehelic® gage movement, it quickly indicates air or noncorrosive gas pressures--either positive, negative (vacuum) or differential.

Rentals? Yes	Options
Sales? Yes	
Datalogs? No	Accessories
Telemetry? No	



Feeling distressed about data?

There are numerous obstacles related to managing the data related to your monitoring projects.

Why worry about all that? Just let us know before your rental that you'd like U.S. to take care of it. Our data experts will set up a pre-rental test to ensure proper recording using dedicated work stations with the most up-to-date software and peripherals. Our factory-trained and experienced technical staff is familiar with all products, software, and manufacturer procedures. Upon return, the devices will be immediately assigned to a device & data expert. Your data will be retrieved and exported into a commonly used format. Files will be sent to you within 24 hours.

ANEMOMETERS



Dwyer 485-1 Anemometer

Ref # 2030

Thermo-Hygrometer is a versatile, compact, handheld instrument for measuring percentage of relative humidity and temperature in °F or °C. Dew point and wet bulb temperatures are derived from the relative humidity and temperature measurements and are displayed on the LCD.

Rentals? Yes	Range	Resolution
Sales? Yes	Temperature Limits: Process: -40 to 176°F (-40 to 80°C)	0.1%, 0.1 °F/°C.
Datalogs? no	Accessories	
Telemetry? No	Alkaline battery	



Dwyer 471-1

Ref # 2030

Thermo-Anemometer Test Instrument is a versatile dual function unit that quickly and easily measures air velocity or volumetric flow as well as air temperature in imperial or metric units. A stainless steel probe is included, which has a comfortable hand grip and etched insertion depth marks.

Rentals? Yes	Range	Resolution
Sales? Yes	Range Air Velocity: 0 to 6000 FPM (0 to 30 m/s)	0.1%, 0.1 °F/°C.
Datalogs? no	Accessories	
Telemetry? No	Alkaline battery	



TSI VelociCalc 9535

Ref # 2040

The VelociCalc® Air Velocity Meter 9535 is like having multiple meters for the price of just one. This meter simultaneously measures and data log several ventilation parameters using a single probe with multiple sensors.

Rentals? Yes	Range	Resolution
Sales? Yes	0 to 6000 ft/min	1 ft/min (0.02 m/s)
Datalogs? Yes	Accessories	
Telemetry? No	Charger, alkaline battery	



TSI VelociCalc 9555

Ref # 2040

The VelociCalc 9555-P Multi-Function Ventilation Meter is a portable, hand held ventilation test instrument. This instrument is designed to work with a wide range of plug-in probes. The probes allow users to make various measurements by simply plugging in a different probes.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	Velocity, temp, humidity, CO and CO2	250 to 15,500 ft/min	1 ft/min (0.01 m/s)
Datalogs? Yes	Accessories		
Telemetry? No	Charger, alkaline battery		



TSI VelociCalc 9565

Ref # 2050

The VelociCalc® Multi-Function Ventilation Meter 9565 features a menu-driven user interface for easy operation in your local language. On-screen prompts and step-by-step instructions guide the user through instrument setup, operation and field calibration.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	Velocity, temp, flow rate and Dew Point	0-15, 500Ft/min	1 ft/min(0.01 m/s)
Datalogs? Yes	Accessories		
Telemetry? No	Charger, alkaline battery		

PERSONAL DUST MONITORS & IAQ



Thermo Pdr-1000An

Ref # 2060

This palm-sized aerosol monitor/datalogger measures mass concentrations of dust, smoke, mists and fumes in real-time.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Options	Range	Resolution
<i>passive sample</i>	<i>0.1-10 micron</i>	<i>mg/m3, every second</i>
Accessories		
Zero Bag, Comm. Cable, External Power, 9-Pin To USB Comm. Cable		



Thermo Pdr-1200

Ref # 2061

This model pDR-1200 includes a particle size-selective inlet cyclone which permits size segregated measurements.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Range	Resolution
<i>1-4LPM</i>	<i>+/- 2%</i>
Accessories	
Zero Bag, Comm. Cable, External Power, 9-Pin To USB Comm. Cable	



TSI Sidepak Am520

Ref # 2061

The SidePak AM520 Monitor is the perfect solution for real-time, personal aerosol sampling in a wide variety of workplace environments. It is used to reduce worker exposures and increase confidence of compliance before gravimetric testing.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Options	Range	Resolution
<i>PM10, PM4, PM2 and PM2.5</i>	<i>0.1 to 10 user adjustable</i>	<i>0.001 mg/m3</i>
Accessories		
Comm. Cable, software, battery charger		



TSI DustTrak DRX 8534

Ref # 1040

Only the DustTrak™ DRX Aerosol Monitor 8534 can simultaneously measure both mass and size fraction - no other monitor can do both.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Options	Range	Resolution
<i>PM10, PM4, PM2 and PM2.5</i>	<i>150 mg/m3</i>	<i>0.001 mg/m3</i>
Accessories		



TSI Q-Trak 7575

Ref # 2070

Providing a comfortable, safe and healthy indoor environment is an increasingly important concern. Good air quality increases concentration and productivity. It can also reduce lost days due to absence.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Options	Range	Resolution
<i>Rel. Humidity, CO, CO2, Temp</i>	<i>5000 ppm CO2 5 to 95% RH</i>	<i>1ppm CO2, 0.1% RH</i>
Accessories		
Cal Cup, alkaline battery		

GAS DETECTION TUBES & CHIPS

DRAGER Accurro Hand Pump

Ref # 2090

The Draeger Tube measurement system consists of a Draeger-Tube and a Draeger gas detector tube pump. Each Draeger-Tube contains a very sensitive reagent system that produces accurate readings when the technical characteristic of the gas detector pump precisely match the reaction of the reagent system.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
<i>Range is specific to the individual tube</i>	<i>Resolutions is specific to the tube</i>
Accessories	
Tube cutter	

ION SCIENCE Uniphos Air Pump

Ref # 2090

Gas detector tubes provide a simple measurement of chemicals in gas samples.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories
Tube cutter

RAE Systems Hand Pump

Ref # 2090

Hand Pump makes it easy to manually measure the presence of toxic and combustible gases. This hand-powered pump works seamlessly with RAE Systems colorimetric tubes.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range
<i>Draws fixed volume of gas - either 50 ml or 100 ml samples.</i>

SENSIDYNE Hand Pump

Ref # 2090

Detector tubes safely allow users to perform field screening and tests for the presence of hazardous and toxic gases, and chemical vapors at a very low cost-per-sample.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories
manual, carry pouch, lubricant, tube cutter

DRAGER Chip Mgmt System

Ref # 2100

Draeger CMS chip measurement system uses an analyzer and substance specific chip to obtain accurate, reliable measurements of gas and vapor concentrations. Bar code on each chip contains specific information such as gas type, measurement range, and other necessary parameters for measurement.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
<i>Range is specific to the individual chip</i>	<i>Accuracies of +/- 4 to 7% of measured value</i>
Accessories	
Alkaline battery, manual	

SVANTEK SV 104

Ref # 2110

Personal dosimeter that offers a new approach to occupational health and safety noise monitoring presenting features such as 1/1 octave band real-time analysis and audio events recording functions.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Options	Range
Octave band analysis	95db; 30Hz to 8kHz
Accessories	
Wind Screen, comm. Cable / charger	

3M Sound Level Meter

Ref # 2120

Sound Level Meters and Real-Time Analyzers help provide advanced sound level monitoring and comprehensive data analysis. Available in Class/Type 1 and Class/Type 2 models, these instruments feature large screen displays that enable real-time frequency analysis, and data-storing capabilities.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **Yes**

Range
120 dB+ (A-weighted) total dynamic measurement range over 8
Accessories
Microphone with wind screen, alkaline battery, AC power cord

SVANTEK Svan 971

Ref # 2120

SVAN 971 Class 1 Sound Level Meter is an extremely small instrument with options for 1/1 & 1/3 octave analysis.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **Yes**

Options	Range
1/3 Octave band	15 dBA RMS - 14 dBA Peak
Accessories	
Wind Screen with microphone, alkaline battery	

3M Ac-300 Calibrator

Ref # 2130

Precision calibrator designed to help you accurately field calibrate 3M sound level meters and noise dosimeters.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range
It produces two signals, 250 Hz or 1,000 Hz
Accessories
Alkaline battery

SVANTEK SV 34

Ref # 2130

Class 2 Acoustic Calibrator generates reference signal of 114 dB at 1 kHz and is designed to calibrate Class 2 sound level meters and noise dosimeters with 1/2 microphones.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
class 2	+/- 0.5 dB
Accessories	
Alkaline batteries	

THERMAL IMAGING & LEAK DETECTION



Flir 50bx

Ref # 2140

FLIR Systems, Inc. designs, develops, manufactures, markets, and distributes technologies that enhance perception and awareness. We bring innovative sensing solutions into daily life through our thermal imaging systems, visible-light imaging systems, locator systems, measurement and diagnostic systems.

Rentals? Yes	Options	Resolution
Sales? Yes	<i>Built-in Digital Lens Data FOV 53° × 41° Digital C</i>	$\pm 2^{\circ}\text{C}$ ($\pm 3.6^{\circ}\text{F}$)
Datalogs? yes	Accessories	
Telemetry? No	Sd card	



DIELECTRIC Mgd2002 He/H

Ref # 2500

Detects Leaks in most pressurized systems can be located with pinpoint accuracy through the use of common tracer gases such as Helium or a Hydrogen/Nitrogen mix.

Rentals? Yes	Range	Resolution
Sales? Yes	<i>Pinpoint accuracy with sensitivity from 25ppm up to 100%</i>	<i>ppm to % auto</i>
Datalogs? No	Accessories	
Telemetry? No	Charger, Needle Probe, Ground Probe, Desiccant, Sampling Handle	



ION SCIENCE Gascheck G

Ref # 2500

Handheld leak detector for fast, accurate measurement. Designed for the search and location of gas leaks, GasCheck G provides effective detection of almost any gas or gas mixture down to cc/sec, mg/m³ or ppm levels.

Rentals? Yes	Range
Sales? Yes	<i>• He 1 x 10⁻⁵, CH₄ 5 x 10⁻⁵, R12 5 x 10⁻⁵, Ar 1 x 10⁻⁴</i>
Datalogs? Yes	Accessories
Telemetry? No	



ION SCIENCE Gascheck Tesla

Handheld helium leak detector for MRI scanner maintenance. GasCheck Tesla is a highly sensitive helium leak detector designed for effective use within high magnetic fields found around the outside of Magnetic Resonance Imaging (MRI) scanners.

Rentals? no	Options	Range
Sales? yes	<i>Choice of readings in cc/ sec, g/yr, mg/m³</i>	<i>• He 1 x 10⁻⁵</i>
Datalogs? yes		
Telemetry? no		



ION SCIENCE SF6 LeakCheck PI:p

SF6 LeakCheck PI:p is designed for the location, leak testing, and measurement of SF6 leaks in high voltage electrical switchgear. The revolutionary SF6 leak detector rapidly detects leaks down to 1 x 10⁻⁸ ml/sec, with a response and clear down of less than 1 second.

Rentals? yes	Options
Sales? yes	<i>Standard SF6 GasCheck P1 and LeakCheck P1:p • 1 x 10⁻⁷ ml/sec, 1 ppm, 0.01 gm/yr SF6 • Highsense option • 1 x 10⁻⁸ ml/sec, 0.1 ppm, 0.001 gm/yr SF6</i>
Datalogs? yes	
Telemetry? no	

WATER LEVEL INDICATORS

AMS Water Level

Ref # 3010



Provides reliable and accurate measurements of groundwater levels. Water level readings are taken at the top of the casing. They utilize a durable polypropylene storage reel with a rugged solid aluminum frame. Their highly accurate Polyethylene-coated steel tape.

Rentals? Yes	Options	Range
Sales? Yes	5/8" probe or 3/8"	100FT, 200FT or 300FT tapes
Datalogs? No	Accessories	
Telemetry? No	9V battery (Installed) plus built in reel with handle	

GEOTECH Water Level

Ref # 3010



The Geotech ET and ETL Portable Water Level Meters are designed to provide reliable and accurate measurements of groundwater levels. Water level readings are taken at the top of the casing.

Rentals? Yes	Options	Range
Sales? Yes	5/8" probe or 3/8"	100FT, 200FT, 300FT 500FT and 1000FT tape
Datalogs? No	Accessories	
Telemetry? No	9V battery (Installed) plus built in reel with handle	

HERON Dipper-T

Ref # 3010



The Heron dipper-T is renowned for its premium, polyethylene coated yellow steel tape accuracy in measuring depth to water. Available in your choice of either metric or engineering scale.

Rentals? Yes	Range	
Sales? Yes	100'/200'/300'	
Datalogs? No	Accessories	
Telemetry? No		

HERON Skinny Dipper

Ref # 3010



The SKINNY DIPPER water level meter is ideal for measuring static water levels in narrow wells, boreholes, tubes and piezometers. The slim line tape and 1/4" probe enable users to take readings while the pump is still in the well, whereas wider tapes may get tangled.

Rentals? Yes	Range	
Sales? Yes	100'/200'/300'	
Datalogs? No	Accessories	
Telemetry? No		

QED Drawdown Mp30-Wlml

Ref # 3010



The MP30 switches between two modes- as a drawdown sensor and control when connected to the Micro-Purge basics controllers, and as a high quality water level meter.

Rentals? Yes	Range	
Sales? Yes	Probe Diameter .625 in; Probe Length 5/8 OD x 7.5 L, Tape 1	
Datalogs? No	Accessories	
Telemetry? No		

WATER LEVEL INDICATORS



SOLINST 107 TLC Meter

Ref # 3010

Model 107 is ideal for profiling conductivity and temperature in wells and open water, for salt-water intrusion studies, and a general indication of contamination levels. The 3/4" probe is attached to Solinst PVDF flat tape.

Rentals? Yes	Range	Resolution
Sales? Yes	50-80,000 microsiemens, 3/4" probe	5% or 100 microseimens
Datalogs? No	Accessories	
Telemetry? No	bag, tape guard, battery	



SOLINST Model 101

Ref # 3010

For measuring the depth to water in wells, boreholes, standpipes, and tanks. They are sturdy, easy to use and read accurately to 1/100 ft. or each millimeter.

Rentals? Yes	Range
Sales? Yes	tape length up to 300', 5/8"
Datalogs? No	Accessories
Telemetry? No	spare battery, tape guard



SOLINST Model 102 - Microprobe

Ref # 3010

Solinst Model 102 is designed to measure groundwater levels, especially in small diameter tubes and piezometers, or where a flexible assembly is needed to get past down hole instrumentation.

Rentals? Yes	Range
Sales? Yes	Tape length up to 300', 4mm or 10mm probe
Datalogs? No	Accessories
Telemetry? No	spare battery, tape guard



An appropriately developed, executed, and documented equipment decontamination procedure is an integral and essential part of any site investigation. Some of the numerous benefits of following strong decontamination procedures include: Minimizing the spread of contaminants within a study area and from site to site, reducing the potential for worker exposure by means of contact with contaminated equipment, and improved data quality and reliability. We stock all of the consumable and decontamination supplies you need for your next project.

INTERFACE PROBES

GEOTECH Interface Probe

Ref # 3020

The Geotech Interface Meter can be used in numerous applications including measuring oil and water levels in monitoring wells, detecting tank leakage and obtaining accurate measurements of water levels.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Options	Range
5/8" probe	100FT, 200FT, 300FT, 500FT and 1000FT tapes
Accessories	
9V battery (Installed) plus built in reel with handle	

HERON H. Oil

Ref # 3020

The H.OIL oil, water interface meter is used to measure the interface level between two liquids in the same tank, vessel, well or aquifer. The dissimilar density of two liquids means the lower density, non-conductive product (LNAPL) will float on top of the higher density, conductive liquid (water).



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Range
100'-500'
Accessories

SOLINST Model 122

Ref # 3020

Solinst Model 122 Interface Meters are easy-to-use and give reliable, accurate measurements. A steady tone and light indicate LNAPL or DNAPL. Intermittent signals indicate water.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **Yes**
- Telemetry? **No**

Range
tape length up to 300', 5/8" probe
Accessories
spare battery, tape guard, bag

Don't forget your gloves!

SMALL
MEDIUM
LARGE
EXTRA LARGE

Item #	Description
40002	NITRILE PF GLOVES SMALL
40003	NITRILE PF GLOVES MEDIUM
40004	NITRILE PF GLOVES LARGE
40005	NITRILE PF GLOVES X-LARGE

PRESSURE TRANSDUCERS

In Situ Baro Troll

Ref # 3030



The BaroTROLL Data Logger measures and logs barometric pressure and temperature, data needed to compensate for water level changes due to barometric fluctuations. Use this data logger with non-vented (absolute) Aqua TROLL 100/200 or Level TROLL 400/700 water level loggers.

Rentals? Yes	Range	
Sales? Yes	30 psia (usable up to 16.5 psi; 1.14 bar)	
Datalogs? Yes	Accessories	
Telemetry? No		

In Situ Level Troll 700

Ref # 3030



The Level TROLL 700 is a water level data logger, giving groundwater professionals higher data resolution, expanded memory and advanced logging modes for specialized applications. Designed specifically for aquifer characterization.

Rentals? Yes	Range	
Sales? Yes	5 psig: 3.5 m (11.5 ft) 15 psig: 11 m (35 ft) 30 psig: 21 m	
Datalogs? Yes	Accessories	
Telemetry? Yes	Cables starting at 25 feet up to 500 feet, USB Comm. Cable	

In Situ AquaTroll 200

Ref # 3030



The In-Situ Aqua TROLL 200 instrument simultaneously measures and logs water level, conductivity and temperature. Features 4-electrode conductivity cell is less subject to fouling and resists electrical field effects from pumps and well casings.

Rentals? Yes	Range	
Sales? Yes	5 psig: 3.5 m (11.5 ft) 15 psig: 11 m (35 ft) 30 psig: 21 m	
Datalogs? Yes	Accessories	
Telemetry? No	Cables starting at 25 feet up to 500 feet, USB Comm. Cable	

INW Pt2X

Ref # 3030



The INW PT2X Smart Sensor is an integrated data logger and pressure/temperature sensor and is ideal for monitoring groundwater, well, tank, and tidal levels, as well as for pump and slug testing. This sensor networks with all of the INW Smart Sensor family.

Rentals? Yes	Range	
Sales? Yes	PSI 5, 15, 30, 50, 100, 300	
Datalogs? Yes	Accessories	
Telemetry? Yes	Cables 25 feet up to 500 feet, USB Comm. Cable	

SOLINST 3001 Levellogger

Ref # 3040



The Levellogger records highly accurate groundwater and surface water level and temperature measurements.

Rentals? Yes	Range	Resolution
Sales? Yes	non-vented, 15' to 600'	+/- 0.05 degree C and FS
Datalogs? Yes	Accessories	
Telemetry? No	Level loader	

PRESSURE TRANSDUCERS & FLOW PROBES

SOLINST Barologger

Ref # 3040

Measures and logs changes in atmospheric pressure, which are then used to compensate water level readings.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **Yes**
 Telemetry? **No**

Range
<i>air barometric pressure</i>
Accessories
Optical Reader

SOLINST Barologger Edger 3001

Ref # 3040

Measures and logs changes in atmospheric pressure, which are then used to compensate water level readings.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **Yes**
 Telemetry? **No**

Range
<i>air barometric pressure</i>
Accessories
Optical reader

In Situ Rugged Reader

Ref # 3050

Collect, store, analyze, and transfer data using the versatile RuggedReader Handheld PC. When connected to In-Situ® Inc.'s water level or water quality instruments, the RuggedReader Handheld PC functions as a reliable, easy-to-use data management system.



Rentals? **Yes**
 Sales? **No**
 Datalogs? **Yes**
 Telemetry? **No**

Accessories
Charger, comm. Cable

SOLINST Leveloader

Ref # 3050

The Leveloader Gold is a data transfer device for use with all versions of Leveloggers.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **Yes**
 Telemetry? **No**

Accessories
USB and RS232 cables, direct read cable

HACH FH950

Ref # 3070

Hach's lightweight, battery-powered FH950 Velocity Flow Meter was designed to provide accurate velocity measurements while simplifying the entire measurement process in rugged field environments.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **Yes**
 Telemetry? **No**

Range
<i>Velocity 0 to +20 ft/s (0 to +6.09 m/s) Level 0 to 10 ft</i>
Accessories
Wading rod, charger

MULTIPARAMETER SONDES



HORIBA U-52 With Flow Cell

Ref # 3500

The U-50 Series multi-parameter water quality meters are equipped to measure and log data for as many as 11 parameters simultaneously with one single probe. Temperature, Conductivity, Specific Conductance, Salinity Resistivity, TDS, pH, ORP.

Rentals? Yes	Accessories
Sales? Yes	Flow Cell, Sensor Guard, Clear Cal Cup, Black Cal Cup, Small Cal. Kit
Datalogs? Yes	
Telemetry? No	



In Situ smarTROLL

Ref # 3510

The smarTROLL Multiparameter Handheld system allows you to instantly collect data on 14 water quality parameters, all from your Android™ or iOS™ mobile device. Our reliable water quality sensors record conductivity, pH, ORP, dissolved oxygen, water level/pressure, salinity, total dissolved solids, and more.

Rentals? Yes	Accessories
Sales? Yes	Android Transmitter, Apple Transmitter, Cal Cup, Flow Cell, Sensor Guard, Plate & Spike, Small Cal. Kit
Datalogs? Yes	
Telemetry? No	



YSI 556

Ref # 3510

YSI 556 MPS simultaneously measures dissolved oxygen, pH, conductivity, temperature, and ORP. Or, simply purchase the cable to measure DO, conductivity, and temperature if needed. The YSI 556 MPS conforms to GLP standards.

Rentals? Yes	Accessories
Sales? No	Flow Cell, Storage Cup, Small Cal. Kit
Datalogs? Yes	
Telemetry? No	



YSI 600XI

Ref # 3510

The YSI 600XL is a compact sonde that measures eleven parameters simultaneously: Temperature, Conductivity, Specific Conductance, Salinity Resistivity, TDS, pH, ORP, Depth or Level, Rapid Pulse™ DO (% and mg/L)

Rentals? Yes	Accessories
Sales? No	Cables starting at 8 feet up to 300 feet, Flow Cell, Storage Cup, Stand, Small Cal. Kit
Datalogs? Yes	
Telemetry? No	



YSI 600Xlm

Ref # 3510

The YSI 600XLM is a compact sonde, able to deploy long-term, that measures eleven parameters simultaneously: Temperature, Conductivity, Specific Conductance, Salinity Resistivity, TDS, pH, ORP, Depth or Level, Rapid Pulse™ DO (% and mg/L).

Rentals? Yes	Accessories
Sales? No	Cables starting at 8 feet up to 300 feet, Flow Cell, Storage Cup, Stand, Small Cal. Kit
Datalogs? Yes	
Telemetry? Yes	

MULTIPARAMETER SONDES



YSI ProDSS

Ref # 3520

The YSI ProDSS (digital sampling system) provides extreme flexibility for the measurement of optical DO, turbidity, conductivity, pH, ORP, ammonium, nitrate, chloride and temperature along with depth. Features digital smart sensors are automatically recognized by the instrument and store calibration data.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Cables starting at 8 feet up to 300 feet, Flow Cell, Storage Cup, Stand, Small Cal. Kit



YSI Professional Plus Quatro

Ref # 3510

The YSI Professional Plus handheld multiparameter meter provides extreme flexibility for the measurement of a variety of combinations for dissolved oxygen, conductivity, specific conductance, salinity, resistivity, total dissolved solids (TDS), pH, ORP, pH/ORP combination, and more.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Flow Cell, Storage Cup, Small Cal. Kit



In Situ Aquatroll 600

Ref # 3530

The Aqua TROLL 600 is a customizable, powerful multiparameter sonde. It combines industry-leading water quality sensors with revolutionary smartphone mobility, allowing you the ability to collect and analyze data using the VuSitu Mobile App on your Android™ device.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Cal Cup, Flow Cell, Sensor Guard, Transmitter Cable, Apple Lightning Cable



YSI 6820

Ref # 3530

Measure a wide variety of parameters for long-term monitoring, profiling or sampling in fresh, sea or polluted water. Measure multiple parameters simultaneously The YSI 6820 sonde measures the following parameters plus more: Temperature, Conductivity, Specific Conductance, Salinity Resistivity.

Rentals? **Yes**

Sales? **No**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Cables starting at 8 feet up to 300 feet, Flow Cell, Storage Cup, Stand, Small Cal. Kit



YSI 6920

Ref # 3530

Measure a wide variety of parameters for long-term monitoring, profiling or sampling in fresh, sea or polluted water. Measure multiple parameters simultaneously The YSI 6920 sonde measures the following parameters plus more: Temperature, Conductivity, Specific Conductance, Salinity Resistivity.

Rentals? **Yes**

Sales? **No**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Cables starting at 8 feet up to 300 feet, Flow Cell, Storage Cup, Stand, Small Cal. Kit

MULTIPARAMETER SONDES



HORIBA U-5000

Ref # 3540

Display for U52

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories



YSI 650Mds

Ref # 3540

Rugged and Reliable Display and Data Logging System Log real-time data, calibrate YSI 6-Series sondes, set-up sondes for deployment, and upload data to a PC.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Comm cable, alkaline battery



YSI Pro Series Display

Ref # 3540

Handheld display for Pro series.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Comm. Cable, alkaline battery



STAY ON SCHEDULE

If, for any reason, you have a problem with our instrumentation, call our reliable, expert technicians. They are factory trained and can solve almost any problem you have in the field. In the meantime, here's a few tips to remember:

- **Check the battery.** The most common problem we hear about is low voltage on the battery. Most batteries are field replaceable.
- **Filters.** Most air quality meters need to be used with clean filters. Make sure the filters are clean and being used correctly.
- **Connections.** All connections need to be made to the appropriate connector and secure. Make sure to double check each connection throughout the entire system.
- **Weather Conditions.** Except for submersible pumps and submersible water quality sensors, our rental equipment is not waterproof. Also, most electronics will malfunction if stored or used in high heat, high humidity, direct sunlight, or below freezing temperatures.
- **Power off.** All small electronics have glitches from time to time. Sometimes fixing these is as easy as powering off and back on a few seconds later. Also, some of our equipment have cold-start functions, reset functions, and/or return to factory settings functions.

TURBIDIMETERS

GEOTECH Turbidimeter

Ref # 3550



Geotech's Portable Turbidity Meter is designed to withstand the rigor of field analysis with laboratory precision and repeatability. The large membrane keypad makes operating the instrument simple when wearing gloves. The bright display can be viewed in varying light conditions.

Rentals? Yes	Range	Resolution
Sales? Yes	0 to 1000 NTU (FNU)	0.01 NTU
Datalogs? Yes	Accessories	
Telemetry? No	800 NTU, 100 NTU, 20 NTU, .1 NTU, Sample Vial	

HACH 2100Q Turbidimeter

Ref # 3550



The portable 2100Q turbidity meter is ideal for use in the field or around the plant. It is easy to carry around and take multiple measurements from various collection points in your treatment process. With its intuitive user interface, the 2100Q makes it easy to take measurements and perform calibration.

Rentals? Yes	Range	Resolution
Sales? Yes	0-1000 NTUs	0.01 NTU
Datalogs? Yes	Accessories	
Telemetry? No	10 NTU, 20 NTU, 100 NTU, 800 NTU, Sample Vial	

HANNA Turbidimeter

Ref # 3550



The HI98703 Precision Turbidity Portable Meter is specially designed for water quality measurements, providing reliable and accurate readings, especially in the low turbidity range. The instrument is based on a state-of-the-art optical system which guarantees accurate results, and assures long term stability.

Rentals? Yes	Range	Resolution
Sales? Yes	0.00 to 9.99; 10.0 to 99.9; 100 to 1000	0.01 NTU
Datalogs? Yes	Accessories	
Telemetry? No		

HF Scientific Micro TPW

Ref # 3550



Designed to provide the ease of portability needed in the field with rugged durability, the MicroTPW is a necessity for anyone monitoring turbidity on the go. The shock-resistant carrying case holds everything necessary for field operation while the instrument itself removes easily to go wherever it is needed.

Rentals? Yes	Range	Resolution
Sales? Yes	Auto ranging from 0 - 1100 NTU	0.01 NTU
Datalogs? no	Accessories	
Telemetry? No	10NTU, 1000NTU, .2NTU, Sample Vial	

LAMOTTE 2020/2020E/2020We

Ref # 3550



Compact handheld water analysis instrument with microprocessor-driven optical system and unique optics configuration.

Rentals? Yes	Accessories
Sales? Yes	Charger / comm. Cable, manual
Datalogs? Yes	
Telemetry? No	

HANDHELD WATER QUALITY METERS



OAKTON PcsTestr 35

Ref # 3560

Tester for pH, conductivity, TDS, salinity and temperature.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	
pH: 0.0 to 14 Conductivity: 0 to 2000 uS TDS: 0 to 1000	
Accessories	
Alkaline battery	



YSI Ecosense Ph10A

Ref # 3570

The pH10A is part of the EcoSense® family of products. It's the perfect tester for economical spot sampling of pH and temperature in many applications including wastewater, surface water, aquaculture, hydroponics, pools, and education.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories	
Alkaline battery	



HACH Dr-890

Ref # 3570

DR/890 Portable Colorimeter: with automatic wavelength selection. Preprogrammed: ready-to-use out of the box. Compact: true hand-held analysis, for use anywhere. Rugged: dustproof, waterproof, shockproof, worry-free (designed to meet IP67 standards)

- Rentals? **Yes**
- Sales? **No**
- Datalogs? **Yes**
- Telemetry? **No**

Accessories	
Sample Vial, Manual, alkaline battery	



LAMOTTE Smart 3 Colorimeter

Ref # 3570

The user-friendly SMART3 Colorimeter is the ideal direct reading colorimeter for complete on-site water analyses.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **yes**
- Telemetry? **No**

Accessories	
Alkaline battery, manual	



YSI 550A

Ref # 3570

Measure temperature and dissolved oxygen simultaneously using highly accurate thermistors and YSI's proven polarographic technology for dissolved oxygen. The fastest DO response times on the market using the Polyethylene (PE) Membrane.

- Rentals? **Yes**
- Sales? **No**
- Datalogs? **Yes**
- Telemetry? **No**

Range	Resolution
100%	0 to 50 mg/L Temp -5 to 45C
Accessories	
Alkaline battery, comm. cable	



WATERRA Hydrolift li

The Hydrolift-2 is a portable, electrically operated device that is used to automate the operation of the Inertial Pump. The Hydrolift is powered by a 3/4 horsepower electric motor (available in either 110 volt or 220 volt) and generates a 4 inch stroke at up to 200 cycles per minute.

Rentals? Yes	Range
Sales? Yes	130-200FT
Datalogs? No	Accessories
Telemetry? No	Power Cable, arm pin



Be Prepared!
Inertial pumps require HDPE tubing and check valves to be operated properly.



RELATED ITEMS

Item #	Description
10008	Tubing HDPE .170 X 1/4
10009	Tubing HDPE 1/4 X 3/8
10010	Tubing HDPE 3/8 X 1/2
10011	Tubing HDPE 1/2 X 5/8
42009	WATERRA FOOTVALVE D-25
42010	WATERRA FOOTVALVE D-22
42011	WATERRA FOOTVALVE D-16
42012	WATERRA FOOTVALVE D-13
42013	WATERRA FOOTVALVE SS-19
42014	WATERRA FOOTVALVE SS-16
42015	WATERRA FOOTVALVE SS-13
42016	WATERRA FOOTVALVE SS-10
42017	WATERRA FOOTVALVE SS-6
42018	WATERRA SURGE BLOCK SBD-25
42019	TU-BAH CHECK 1/2 X 5/8 OUTSIDE
42020	TU-BAH CHECK 1/2 X 5/8 INSIDE
42021	TU-BAH CHECK 3/8 X 1/2 INSIDE
42022	TU-BAH SURGE BLOCK

PERISTALTIC PUMPS

GEOTECH Geopump Model II

Ref # 4000

The Geotech Geopump™ Series I and II Peristaltic Pumps are designed for single and multi-stage pressure or vacuum pumping of liquids. They operate by mechanical peristalsis, so the sample only comes in contact with the tubing.



Rentals? Yes	Range
Sales? Yes	28 feet
Datalogs? No	Accessories
Telemetry? No	DC Cable Assembly, AC Cable, EZ Load II (White), 12V Battery

PEGASUS Alexis Peristaltic Pump

Ref # 4000

A self contained sampling station that includes all the best features of these devices. Packaged in the rugged Pelican™ 1430 case and incorporating its own power supply and charger, this pump will keep you sampling in the field.



Rentals? Yes	Range
Sales? Yes	28 feet
Datalogs? No	Accessories
Telemetry? No	Charger, alligator clips

SOLINST 410

Ref # 4000

Peristaltic Pump from Solinst is ideal for vapor sampling or water sampling from shallow wells and surface water. It can be used for vacuum pumping and for pressure delivery of liquids or gases



Rentals? Yes	Range
Sales? Yes	up to 33 feet
Datalogs? No	Accessories
Telemetry? No	

SPECTRA Field-Pro

Ref # 4000

The Spectra Field-Pro is a state-of-the-art peristaltic pump that features a heavy-duty, all-inclusive design.



Rentals? Yes	Range
Sales? No	up to 27', 14 hr. battery life
Datalogs? No	Accessories
Telemetry? No	



Be Prepared!

To make sure you receive the right pumps and accessories, be ready to answer the following:

- How many wells?
- What is the Depth to Water (DTW) for each?
- What is your desired sampling/purging depth?
- What is your desired flow rate?

SUBMERSIBLE MOTOR PUMPS



GRUNDFOS Redi-Flo 2

Ref # 4010

The Grundfos Redi-Flo2® Electrical Submersible Pump provides smooth, uninterrupted water flow during groundwater sampling or conducting aquifer tests to depths down to 280 ft. (85m). Both high flow rates needed for purging and low flows recommended for sampling are achieved with the same pump.

Rentals?	Yes	Range
Sales?	Yes	280 feet
Datalogs?	No	Accessories
Telemetry?	No	Cooling schroud



GEOTECH Ss Geosub Pump

Ref # 4010

The SS Geosub sampling pump is the most versatile single stage 12 Volt DC pump in the industry. Designed with all stainless steel components, the SS Geosub allows you to sample with confidence even in the harshest well conditions. The SS Geosub Pump operates with the Geotech SS Geosub Controller.

Rentals?	Yes	Range
Sales?	Yes	200 feet, 0.5 to 4 GPM (Depends on depth and head)
Datalogs?	No	Accessories
Telemetry?	No	



PROACTIVE SS Hurricane XI

Ref # 4010

The SS Hurricane XL pump with PVC motor lead is capable of pumping up to 150 feet from ground level. Has the ability to run in harsh conditions with higher turbidity.

Rentals?	Yes	Range
Sales?	Yes	150 feet DTW
Datalogs?	No	Accessories
Telemetry?	No	Spare Motor, Blue Power Cable, Black Power Cable, Brown Power Cable



PROACTIVE SS Mega Monsoon Pump

Ref # 4010

SS Mega-Monsoon is capable of pumping up to 175 feet from ground level to water level. Has the ability to run in harsh conditions with higher turbidity.

Rentals?	Yes	Range
Sales?	Yes	180 feet DTW
Datalogs?	No	Accessories
Telemetry?	No	Spare Motor, Blue Power Cable, Black Power Cable, Brown Power Cable



QED Power Pro ESP

Ref # 4010

Low-flow electric sampling pump is an all-in-one design with user friendly controls built into the reel.

Rentals?	Yes	Range
Sales?	Yes	Max Depth 155 feet
Datalogs?	No	Accessories
Telemetry?	No	

SUBMERSIBLE MOTOR PUMP CONTROLLERS



GEOTECH Ss Geosub Controller

Ref # 4020

The SS Geosub Controller is designed specifically for use with Geotech's SS Geosub Pump. It provides a safe conditioned variable DC output power from an AC power source. Built-in sensing gives the operator accurate and precise control over the pump during sampling events.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **No**

Telemetry? **No**

Accessories

Controller built into carrying case with manual



GRUNDFOS Converter

Ref # 4020

Converter is designed to protect and operate the RediFlo2 Sampling Pump and the Redi-Flo4 Sampling and Remediation Pump. Discharge flow rate from 100 mL/min to 50 GPM at depths up to 524 feet of head. Control discharge flow rates easily with push-button control pad.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **No**

Telemetry? **No**

Accessories



PROACTIVE All In One Controller

Ref # 4020

Designed to operate all of the Proactive Stainless Steel pumps.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **No**

Telemetry? **No**

Accessories

BLADDER PUMPS



GEOTECH Bladder Pump .675"

Ref # 4030

Geotech's portable bladder pumps are designed for single turn release head and quick change bladders allow for quick, in-the-field bladder changes and easy decontamination. Custom hose barbs allow the pump to be secured to tubing.

Rentals? Yes	Range
Sales? Yes	Max depth 200 feet
Datalogs? No	Accessories
Telemetry? No	



GEOTECH Bladder Pump .850"

Ref # 4030

Geotech's portable bladder pumps are designed for single turn release head and quick change bladders allow for quick, in-the-field bladder changes and easy decontamination. Single turn release head and quick change bladders allow for quick, in-the-field bladder changes and easy decontamination.

Rentals? Yes	Range
Sales? Yes	Max depth 200 feet
Datalogs? No	Accessories
Telemetry? No	



GEOTECH Bladder Pump 1.66"

Ref # 4030

Geotech's portable bladder pumps are designed for single turn release head and quick change bladders allow for quick, in-the-field bladder changes and easy decontamination. Single turn release head and quick change bladders allow for quick, in-the-field bladder changes and easy decontamination.

Rentals? Yes	Range
Sales? Yes	Max depth 200 feet Optional Drop-Tube assembly available for sampling from greater depths
Datalogs? No	Accessories
Telemetry? No	



GEOTECH Reclaimer

Ref # 4030

The Reclaimer System is a positive air displacement pump designed for hydrocarbon recovery, leachate, condensate and total fluids applications. The pumps are designed to withstand aggressive down-well environments, and highly corrosive fluids without material breakdown or failure.

Rentals? Yes	Range
Sales? Yes	Flow rates up to 4 GPM (15 LPM)
Datalogs? No	Accessories
Telemetry? No	



GEOTECH PFAS-free Bladder Pump (available for 1.66" and .850" Pumps)

Ref # 4030

Designed specifically for sampling Per- and Poly-fluoroalkyl chemicals such as perflourooctanoic acid (PFOA) and perflourooctane sulfonate (PFOS) in groundwater. Made with PFAS-free materials such as 316 stainless steel, high-density polyethylene (HDPE), and Buna-Nitrile to provide representative water samples.

Rentals? Yes	Range
Sales? Yes	Max depth 200 feet
Datalogs? No	Accessories
Telemetry? No	

BLADDER PUMPS



QED Sample Pro Pump .75"

Ref # 4030

The Sample Pro portable pump combines the unparalleled sample accuracy and high reliability of a bladder pump in an easy-to-use design.

Rentals? Yes	Range
Sales? Yes	200 feet Lift Max; 140mL/min. @ 25'
Datalogs? No	Accessories
Telemetry? No	



QED Sample Pro Pump 1.75"

Ref # 4030

The Sample Pro portable pump combines the unparalleled sample accuracy and high reliability of a bladder pump in an easy-to-use design.

Rentals? Yes	Range
Sales? Yes	200' Lift Max; 1.2 gal./min. @25'
Datalogs? No	Accessories
Telemetry? No	



QED St1102 Pm Pump

Ref # 4030

Dedicated bladder pump. Max lift 1000'

Rentals? Yes	Options	Range	Resolution
Sales? Yes			
Datalogs? No	Accessories		
Telemetry? No			

RELATED ITEMS

Item #	Description
42154	QED ST1102 TEFLON BLADDERS
42058	QED 3/4 POLY BLADDERS
42042	QED 1 3/4 POLY BLADDERS
42047	QED 1 3/4 TEFLON BLADDER
42043	QED 1 3/4 SCREENS
42044	QED 1 3/4 O-RINGS
42045	QED 1 3/4 GRAB PLATE 1/4 X 1/4
42046	QED 1 3/4 GRAB PLATE 1/4 X 3/8
42048	QED 1 3/4 CHECK BALLS
42094	QED POLY BLADDER KIT
42163	QED TEFLON BLADDER KIT
42135	QED BLADDER KIT T1200 SERIES
42136	QED BLADDER CLAMP TOOL / PUNCH

Item #	Description
42115	GEOTECH BP SPARE PART KIT 1.66"
42116	GEOTECH O-RING SRVCE KIT 1.66"
42117	GEOTECH PARTS KIT 1.66 (NO PFC)
42118	GEOTECH ORING KIT 1.66" NO PFC
42036	GEOTECH TEFLON BLADDER .85"
42034	GEOTECH POLY BLADDER .85"
42035	GEOTECH POLY BLADDER .675"
42073	GEOTECH POLY BLADDER 1.66"
42072	GEOTECH TEFLON BLADDER 1.66"
41033	GEOTECH BLADDER KIT

AIR COMPRESSORS



HUSKY Compressor

Ref # 4040

Portable Oil less Compressor, used with bladder pumps as a gas source

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories



Porter Cable Cable Compressor

Ref # 4040

Portable Oil less Compressor, used with bladder pumps as a gas source

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories



QED 3020 Air Compressor

Ref # 4040

Compressor is a useful option for low-flow sampling of wells at depths to 200 feet. It runs on a 12 volt DC electrical supply

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories




QED Mp-10 Controller

Ref # 4050

Controller is used to operate QED Well Wizard™ bladder sampling pumps to purge and sample ground water.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories



QED Mp-10H Controller

Ref # 4050

Controller is used to operate QED Well Wizard™ bladder sampling pumps to purge and sample ground water. (High pressure)

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories

BLADDER PUMP CONTROLLERS



QED Mp-15 Controller/Backpack

Ref # 4060

Backpack combines advanced low-flow control with the power of a built-in compressed gas source, for the ultimate in portability and ease of use in sampling ground water with bladder pumps.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **No**

Telemetry? **No**

Accessories

GEOTECH Compressor

Ref # 4070

The simple-to-use Bladder Pump (BP) Controller (300 or 500 PSI) utilizes accurate microprocessor-controlled fill/discharge timers to sustain true low-flow sampling techniques. Both Controllers are equipped with high-pressure valves and fine resolution regulators that can perform in deep-well applications.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **No**

Telemetry? **No**

Accessories

Controller built into carrying case, Air-In and Air-Out Hoses, AC Power Supply, DC Power Cord and Clip Adapter, Geotech Drawstring Bag, Carry Case



QED Mp-50 Controller/Compressor

Ref # 4070

All-in-one, controller / compressor using lightweight, rugged components designed for on-the-go sampling. Used with QED portable pumps.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **No**

Telemetry? **No**

Accessories



RELATED RENTAL ITEMS



Ref. #	Description
7760	Small Nitrogen Tank
7761	Nitrogen Tank 40
7756	Nitrogen Regulator
7757	Nitrogen Regulator HP
7763	Nitrogen Carry Cage

AUTOMATIC WATER SAMPLERS



ISCO 6700

Ref # 4080

Isco's 6700 Portable Sampler is recognized as the industry standard, providing the most comprehensive and durable performance available. The 6700 uses Isco's advanced 6700 Series Controller, a device that allows you to select from a variety of programming modes, assuring the most suitable routine for your application.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Strainer, Metal Barb, Battery, Battery Charger, Bottle Liner, AC Power Adaptor, Hanger, Rain Gauge



ISCO 6712

Ref # 4080

The 6712 Portable Sampler features a vacuum-formed ABS plastic shell to withstand exposure to pressure and abuse. Its tapered design and trim 20-inch (50.8 cm) diameter result in easy manhole installation and removal. Large, comfortable handles make transporting safe and convenient - even when wearing gloves.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

Strainer, Metal Barb, Battery, Battery Charger, Bottle Liner, AC Power Adaptor, Hanger, Rain Gauge



ISCO 730

Ref # 4080

Get the dependability and accuracy of Isco bubbler flow meters in a miniaturized package. The 730 is unaffected by changing stream conditions, and level measurement remains accurate despite temperature fluctuations or exposure to harsh chemicals.

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories



ISCO 750 Gives greater accuracy where weirs and flumes are not practical, and where submerged, full pipe, surcharged, and reverse flow conditions may occur. And, you don't have to estimate the slope and roughness of the channel.

Ref # 4080

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

AV 25FT cable with sensor

RELATED ITEMS

Item #	Description
42005	ISCO 10L SAMPLING JUG
42006	ISCO SAMPLER BOTTLES; 500ML
42007	ISCO SAMPLER BOTTLES; 1000ML
52198	ISCO SAMPLE TUBE ASSEMBLY
52199	ISCO PUMP HEAD TUBING

DISCREET WATER SAMPLERS

KEMMERER Water Sampler

Ref # 4090

Used for general water sampling in lakes, channels, wells and the sea. This sampler consists entirely out of plastic parts so that there is no risk of the sample coming into contact with metal.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Range
<i>Range: 0.1 - 200 & 1.0 - 1999 microgram / cubic meter</i>
Accessories

SOLINST Discrete Interval Sampler— 425 Discrete Interval Sampler is a stainless steel groundwater sampler, with LDPE tubing mounted on a convenient reel. Discrete interval sampling is ideal for obtaining truly representative groundwater samples from below floating product layers, or for obtaining samples of the product itself.

Ref # 4090



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Options	Range
<i>1"; 1.5"; and 2"</i>	<i>up to 500'</i>
Accessories	

WILDCO Bomb Sampler

Ref # 4090

The CONBAR stainless bomb samplers are manufactured from a high quality corrosion resistant type 304 stainless steel. The bomb samplers are designed to collect liquid samples from storage tanks, lakes, ponds, manholes, wells, and other hard to reach places.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Range
<i>500 ml capacity</i>
Accessories



NITON XI3T 500 Xrf Analyzer Niton XL3t instruments can be used for many nondestructive testing applications, including analysis of metal alloys, testing of electronics and consumer goods for prohibited substances, mining exploration and grade control, and more.

Ref # 4600

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

--



OLYMPUS Delta DELTA Alloys & Metals Handheld XRF Analyzers provide highly specific material chemistry to rapidly and accurately identify alloy grades and pure metals. Configured with a standard package of 25+ elements, the DELTA generates alloy chemistry and grade ID in seconds.

Ref # 4600

Rentals? **Yes**

Sales? **Yes**

Datalogs? **Yes**

Telemetry? **No**

Accessories

SRM 2573, SRM 2710A, Sm 2711A, SS 316 Coin, Cradle, Charger

--

Soil - Drilling & Scale

BOSCH Hammer Drill

Ref # 4700

Versatile drilling and hammering functions. It provides counter-balanced Vibration Control for more comfortable handling of the hammer. Ideal for masonry pros or general contractors.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Options
<i>SDS max or spline</i>
Accessories
Drill, drill bit, manual and carrying case

DEWALT Hammer Drill

Ref # 4700

Fast speed of application and light weight design make it ideally suited for drilling for larger diameter mechanical anchors. The E-Clutch[®] system provides enhanced control in a bind up situation and can help minimize sudden torque reaction compared to standard clutches alone.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Options
<i>SDS max or spline</i>
Accessories
Drill, drill bit, manual and carrying case

MAKITA Hammer Drill

Ref # 4700



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Options	Range	Resolution
Accessories		

HUSQVARNA Dms 240

Ref # 4700

DMS 240 is an electric drill motor and stand system for a wide variety of core drilling applications. An ideal system for medium core drilling in walls, floors and roofs up to 10 in. diameter. The stand is easy to tilt, and the back support provides reliable and stable angle drilling.



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Options
<i>AC power</i>
Accessories

OHAUS Scout Pro Balance

Ref # 4710



Rentals? **Yes**
 Sales? **Yes**
 Datalogs? **No**
 Telemetry? **No**

Accessories
Calibration weight



Ben Meadows Gopher Hand Auger

Ref # 4740

Collect your field samples with superior soil sampling equipment. Exclusive SquareLink connection system. The Gopher Auger Kit incorporates a square tube design with a link pin. During rotation of the auger, the extensions twist against the corners of the square tube and not directly against the pin.

Rentals? Yes	Options
Sales? Yes	3 1/4" auger
Datalogs? No	Accessories
Telemetry? No	Extension rods



WILDCO Handcore Sampler

Ref # 4740

Handle allows use in shallow water or by divers. Attach line to Clevis when taking deeper samples. Clevis is removable to attach extension handle for sampling from a pontoon boat, dock, or bridge. Simple, automatic valve for good seal.

Rentals? Yes	Accessories
Sales? Yes	Tubes and caps
Datalogs? No	
Telemetry? No	



AMS Sludge Sampler

Ref # 4720

sampler comes with core and auger tips that have been fitted with valves for retention of high quality soil core samples in non-cohesive, saturated materials. Versatile and easy to use for collection of either cored or augered samples of non-cohesive saturated materials in a liner.

Rentals? Yes	Options	Range
Sales? Yes	auger sizes 2 1/4" or 3 1/4" X 12"	3FT, 4FT or 5FT
Datalogs? No	Accessories	
Telemetry? No	Extension rods	



AMS Split Core Sampler

Ref # 4730

You can use the split soil core sampler without a liner to collect relatively undisturbed soil cores for immediate field examination and testing. Or, it can be used with a liner for collection of relatively undisturbed, sealed soil core samples that are suitable for EPA Level III or Level IV soil analysis.

Rentals? Yes	Options	Range
Sales? Yes	2 1/2" X 12" or 2 3/4" X 12"	3FT, 4FT or 5FT
Datalogs? No	Accessories	
Telemetry? No	Extension rods	



AMS Multi-Stage Sediment Sludge Sampler

Ref # 4730

This kit includes everything needed for multi-stage sludge and sediment sampling in a convenient Pelican carrying case. Designed to provide all the items needed for sampling in a convenient carrying case, 5/8" Threaded connection type.

Rentals? Yes	Accessories
Sales? Yes	multi-stage sludge core tip, 12" multi-stage SCS base, three 12" multi-stage SCS sections, three 4' extensions, plastic liner, plastic end caps, 2" soil core catcher, universal slip wrench, two crescent wrenches, SST cross handle, slide hammer, and the AMS deluxe carrying case.
Datalogs? No	
Telemetry? No	

AMS Hollow Stem Auger Kit

Ref # 4730

Provides the tools needed to reach a 6' depth. The augers cut a 3" diameter hole and have an ID of 1 1/8", making them suitable for soil, soil gas and groundwater sampling through a cased hole. A special Hollow-stem soil probe, 7/8" OD by 24" long with slide hammer is included to allow collection of a soil samples.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Options	Range
SDS Max Combination Hammer Drill or Slide hammer	3FT or 6FT depth
Accessories	
All extensions and components pictured	

KVA Macho Vapor Probe System

Ref # 4730



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Options	Range	Resolution
Accessories		

Dexsil Petroflag TPH Analyzer

Ref # 4750

PetroFLAG system is a field portable method for the determination of total petroleum hydrocarbons in soil. It is both safe and easy to use. PetroFLAG does not distinguish between aromatic and aliphatic hydrocarbons, but quantifies all fuels, oils, and greases as total hydrocarbons.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories
Scale, Stop Watch, 200G Cal. Weight

WILDCO Ekman Dredge

Ref # 4760

The 6" x 6" x 6" Ekman Dredge is used for sampling benthic communities inhabiting soft bottomed aquatic environments. Hinged upper doors swing open as the dredge is lowered, allowing water to pass through and minimize shock wave.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories
Rope

WILDCO Ponar Dredge

Ref # 4760

Wildco Ponar Grabs perform well in fresh- and saltwater for taking samples of hard bottoms such as sand, gravel, consolidated marl or clay.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Options	Range
6" x 6" Self-activating bucket or 9" X 9"	2400mL to 8200 mL
Accessories	
Rope	

SOKKIA C300

Ref # 5000

Automatic Level



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Options	Range	Resolution
Shock stability, waterproof	28X	0.5" Setting ac-
Accessories		
Plumb Bob, Survey Tripod, Graduated Rod		

TOPCON At-B4

Ref # 5000

Auto Level Features: 24X magnification, WATERPROOF to IPX6 rating, short focus (1.6 ft. min.) magnetic damping, 360-Degree Horizontal Circle, Sighting Guide, 1:100 Stadia, Approximate Range-250 feet.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
24X	4"
Accessories	
Plumb Bob, Survey Tripod, Graduated Rod	

CST BERGER Laser Level

Ref # 5030

Rotary laser provides vertical beam provides easy, precise layout of 90° corners and plumb applications. An Anti-Drift System ensures that level is maintained, and Single Axis Slope Control lets you change the laser's slope for complex leveling applications. Select from various rotational speeds and variable.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
up to 2000ft	Accuracy: ±1/16" at 100 ft.
Accessories	
Survey Tripod, Graduated Rod	

EAGL Laser Level

Ref # 5030

EAGL is a precision rotation laser offering superior accuracy for up to 2000 feet in diameter. For less demanding measuring situations, jobs with a 1000 foot diameter.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories
Survey Tripod, Graduated Rod

TRIMBLE Spectra Precision Laser

Ref # 5030

A rugged, automatic self-leveling laser with a working range of up to 2,600 feet. Used in a wide variety of grading, excavating and alignment applications, this construction rotary laser features PlaneLok and Grade Matching for increased accuracy in slope measurement.



- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Range	Resolution
2600FT	1/16 inch at 100FT
Accessories	
Survey Tripod, Graduated Rod	

TOTAL STATION & GPS



TOPCON Total Station Gts226

Ref # 5010

GTS-226 provides the construction professional with a dedicated lay-out solution. Use the on-board software to layout points in the field, confident that with Topcon, you'll be right on target. Or use any of Topcon's field controllers running one of our range of software packages tailored to your tasks.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	<i>Mini Prism. Prism 1,3 and 9.</i>	30X	(2mm +2ppm)
Datalogs? Yes	Accessories		
Telemetry? No	Survey Tripod, Graduated Rod, Prism		



TRIMBLE Geo 7X

Ref # 5040

The Trimble® Geo 7X handheld is from the Trimble GeoExplorer® series family of integrated, rugged, and high-accuracy GNSS handhelds. As a streamlined solution that enables faster and more productive data collection the Geo 7X is ideal.

Rentals? Yes	Options	Range	Resolution
Sales? Yes	<i>Decimeter accuracy \ Floodlight technology</i>	200m	0.05m
Datalogs? Yes	Accessories		
Telemetry? No	Rangefinder		



TRIMBLE Yuma 2 Mobile Computer

Ref # 5040

The Yuma 2 rugged tablet, which already offers the best sunlight readable display on the market, is available with a 1-2 meter real time Enhanced GPS positional accuracy using SBAS satellites, as well as coming standard with 2-4 meter accuracy.

Rentals? Yes	Options	Range
Sales? Yes	<i>Collect and transfer data in real time.</i>	2-4m
Datalogs? Yes	Accessories	
Telemetry? No	External Antenna	



Be Prepared!

Our data experts are ready to help with GPS data both before and after each rental. The first and most important question we will ask you:

What is the coordinate system being used on your project?

METAL & PIPE LOCATORS



SCHONSTEDT 72Cd Metal Detector

Ref # 5050

The GA-72Cd Locator detects the magnetic field of iron and steel objects. It provides audio detection signals that peak in frequency when the locator's tip is held directly over the target. The GA-72Cd has the option of nulling or peaking.

Rentals? Yes	Options	Range
Sales? Yes	4 levels of sensitivity	14" sensor spacing; 40hr battery
Datalogs? No	Accessories	
Telemetry? No	9V batteries, carry case	



SCHONSTEDT Ga-92Xtd

Ref # 5050

This unit offers one hand operation and new membrane switch makes finding faster, providing both audio and visual indication of ferrous objects up to 16 feet underground.

Rentals? Yes	Options	Range
Sales? Yes	extended mode for accuracy	9.5" sensor spacing; 24hr battery
Datalogs? No	Accessories	
Telemetry? No	9V batteries, carry case	



SUBSURFACE Instruments MI-3

Ref # 5060

Magnetic locator offers durable one-handed operation that's 100% waterproof.

Rentals? Yes	Range	
Sales? Yes	40hr battery; detection up to 8'	
Datalogs? No	Accessories	
Telemetry? No	batteries, bag	



SCHONSTEDT Mac 51Bx Detector

Ref # 5060

The MAC-51Bx pipe locator that consists of a receiver and a transmitter that simultaneously transmits on two frequencies - 571 Hx (LF) and 82.5 KHz (HF).

Rentals? Yes	Options	Range
Sales? No	Hi and low frequency	20" sensor spacing; 4000' signal
Datalogs? No	Accessories	
Telemetry? No	batteries, conductive cable assembly	



HONDA 2500

Ref # 5520

2500w Generator Honda 4-stroke overhead valve engine.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories

--



HONDA 3500

Ref # 5520

3500w Generator Honda 4-stroke overhead valve engine.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories

--



HONDA Eu2000i

Ref # 5520

Honda EU2000i1A1 2000 Watt Portable Generator is super quiet, fuel efficient, and portable. The Honda EU2000i has 2000W starting power, stabilizing at 1600W continuous power.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories

--



Miller Manhandler Hoist/Wench

Ref # 5510

The perfect solution for a range of applications including confined space entry, rescue, positioning and personnel/material handling.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories

--



AIR SYSTEMS Confined Space Fan

Ref # 5500

Positioning an axial blower or confined space fan in tight spots brings a rush of fresh air to your work environment. Make any confined space safe and airy with this selection of ventilation equipment, axial air blowers, and fans.

- Rentals? **Yes**
- Sales? **Yes**
- Datalogs? **No**
- Telemetry? **No**

Accessories

8FT feet of ducting with a storage bag

--

TUBING

Item #	Description
LDPE	
10001	Tubing LDPE 1/16 X 1/8
10002	Tubing LDPE 1/8 X 3/16
10003	Tubing LDPE .170 X 1/4
10004	Tubing LDPE .170 x ¼ Graduated
10005	Tubing LDPE 1/4 X 3/8
10006	Tubing LDPE 3/8 X 1/2
10007	Tubing LDPE 1/2 X 5/8
HDPE	
10008	Tubing HDPE .170 X 1/4
10009	Tubing HDPE 1/4 X 3/8
10010	Tubing HDPE 3/8 X 1/2
10011	Tubing HDPE 1/2 X 5/8
TEFLON OR TEFLON-LINED	
10054	Tubing Teflon 1/16 X 1/8
10055	Tubing Teflon 1/8 X 3/16
10056	Tubing Teflon 3/16 X 1/4
10051	Tubing Teflon-Lined 1/4 x 3/8
10052	Tubing Teflon-Lined 3/8 x 1/2
10053	Tubing Teflon-Lined 1/2 x 5/8
BONDED	
10101	Tubing Bonded Pol-Pol 1/4x1/4BLU
10102	Tubing Bonded Pol-Pol 1/4x3/8BLU
10106	Tubing Bond Pol-Tef 1/4x1/4BLU
10105	Tubing Bond Pol-Tef 1/4x3/8BLU
SILICONE	
10151	Tubing Silicone S15 Geotech
10152	Tubing Silicone S15 Generic
10153	Tubing Silicone 3/8 X 5/8
10155	Tubing Silicone S24 Geotech
VINYL	
10201	Tubing Vinyl 1/4 X 3/8
10202	Tubing Vinyl 3/8 x 1/2
10203	Tubing Vinyl ½ x 5/8
10204	Tubing Vinyl .160 X .285

BAILERS

Item #	Description	Case
POLY WEIGHTED		
20001	Bailer Poly Weighted 0.5 x 36	24
20002	Bailer Poly Weighted .75 X 36	24
20026	Bailer Poly Weighted .75 X 12	24
20003	Bailer Poly Weighted 1.5 X 36	24
20020	Bailer Poly Weighted 1.5 X 48	24
20005	Bailer Poly Weighted 1.5 x 12	24
20004	Bailer Poly Weighted 3 x 36	9
POLY NON-WEIGHTED		
20006	Bailer Poly Non-Weigh 1.5 x 12	24
20027	Bailer Poly Non-Weigh 0.5 x 36	24
20019	Bailer Poly Non-Weigh 1.5 X 36	24
TEFLON WEIGHTED		
20007	Bailer Teflon Weighted .5 x 36	12
20008	Bailer Teflon Weighted.75 x 36	12
20009	Bailer Teflon Weighted1.5 x 12	12
20011	Bailer Teflon Weighted1.5 X 36	12
TEFLON DOUBLE WEIGHTED		
20017	Bailer Teflon D.Weighted1.5X36	12
TEFLON NON-WEIGHTED		
20010	Bailer Teflon Non-Wei 1.5 x 12	12
PRESSURE BAILER		
20031	Bailer Poly Pressure 1.5 x 36	12
CLEAR PVC		
20012	Bailer Clear PVC .5 x 36	24
20013	Bailer Clear PVC .7 x 36	24
20014	Bailer Clear PVC 1.5 x 36	24
HYDROCARBON PVC		
20021	Bailer H/C Clear PVC 1.5 x 36	24
20022	Bailer H/C Clear PVC 3.3 x 36	8
TIE LINE & TWINE		
20015	Bailer Tie Line (600 FT.)	
20023	Bailer Twine (250ft.) A/B TNB	
20028	Bailer Twine (200ft.) A/B TNT	
20016	Bailer Twine (200ft.)	
20030	Bailer Twine (600ft.)	
TEFLON VOC TIPS/LEEDERS		
20018	Bailer Teflon VOC Tips	
20025	Bailer Special Clean Teflon	
20024	Bailer Teflon Leeder	

Below are the most commonly used tubing materials and diameters*. Please contact your U.S. Environmental representative if you have any questions regarding tubing for your next project.

*all diameters are approximate


Polyethylene & Teflon Tubing



ID:	1/16	1/8	3/16	1/4	3/8	1/2
OD:	1/8	3/16	1/4	3/8	1/2	5/8
Common Usage:	Small GED pump; Low flow sampling	Soil Vapor Probes	Peristaltic Pumps; Low Flow Sampling	Peristaltic Pumps; Low Flow Sampling	Grundfos & Proactive Pumps; Purging	Grundfos & Waterra Pumps; Purging; Development

All diameters are always in stock and available in Low-Density Polyethylene (LDPE) and Teflon or Teflon-lined Polyethylene. All diameters are available in 100' or 500' sections. 3/8 x 1/2 and 1/2 x 5/8 are available in High-Density Polyethylene (HDPE) which is recommended for well development.

Flexible Silicone Tubing




ID:	3/16	3/8
OD:	3/8	5/8
Common Usage:	Geotech Pumps; Low Flow Sampling	ISCO & Solinst Pumps; Water Sampling

Both diameters are always in stock. Available in sections from 1' up to 50'. In addition to peristaltic pumps, this tubing is commonly used to connect two sections of tubing.

Warning! Never use silicone tubing with LEL sensors.

Clear Vinyl Tubing



ID:	1/6	1/4	3/8
OD:	1/4	3/8	1/2
Common Usage:	Air Quality monitoring and sampling	Landtec Monitors; Air Quality monitoring	ISCO Samplers; wastewater sample line

All diameters are always in stock. Available in sections from 1' up to 100'.

CALIBRATION GAS

Item #	Description
17L Disposable	
30002	CYL 17L ISOBUTYLENE 10PPM
30001	CYL 17L ISOBUTYLENE 100PPM
30118	CYL 17L ISOBUTYLENE 1000PPM
30003	CYL 17L METHANE 100PPM
30013	CYL 17L METHANE 500PPM
30014	CYL 17L METHANE 2.5%
30031	CYL 17L METHANE 9000PPM
30015	CYL 17L UHP NITROGEN
30179	CYL 17L 4% OXYGEN
30043	CYL 17L UHP HELIUM
30020	CYL 17L ZERO AIR
30032	CYL 17L 50% LEL (0.7%) PENTANE
30004	CYL 17L 50% CH4 / 35% CO2 / N2
30022	CYL 17L 15% CH4/15% CO2/N2
30017	CYL 17L 50PPM CO/1000PPM CO2
30033	CYL 17L 2.5% CARBON DIOXIDE
30050	CYL 17L 1000PPM H2 & AIR
29L Disposable	
30006	CYL 29L H2S 25PPM
30011	CYL 29L AMMONIA 50PPM
30026	CYL 29L CHLORINE 5PPM
30030	CYL 29L AMMONIA 25PPM
30034	CYL 29L HCN 10PPM
30035	CYL 29L H2S 10PPM
30109	CYL 29L CHLORINE 10PPM
30007	CYL 29L 4-GAS W/ METHANE
30008	CYL 29L 4-GAS W/ PENTANE
30029	CYL 29L 25/100/50/18 (CH4)
30046	CYL 29L 25/50/2.5%/18 (CH4)
30044	CYL 29L 4 GAS W/ PENTANE SIMUL
34L Disposable	
30005	CYL 34L ISOBUTYLENE 100PPM
30129	CYL 34L METHANE 100PPM
30180	CYL 34L 4% OXYGEN
30111	CYL 34L BENZENE 5PPM
30124	CYL 34L FORMALDEHYDE 5PPM
30125	CYL 34L AMMONIA 10PPM
30126	CYL 34L HCN 10PPM
30141	CYL 34L 10PPM METHANE
30143	CYL 34L AMMONIA 25PPM

Item #	Description
34L Disposable, cont'd	
30171	CYL 34L CARBON DIOXIDE 5000PPM
30037	CYL 34L CARBON MONOXIDE 15PPM
30038	CYL 34L CARBON MONOXIDE 50PPM
30122	CYL 34L 50% CH4 / 35% CO2 / N2
30128	CYL 34L 4-GAS W/ METHANE
30197	CYL 34L 4-GAS W/ PENTANE
30195	CYL 34L 100/25/50/18 (CH4)
30114	CYL 34L CO/CO2/O2/LEL -PENTANE
58L Disposable	
30047	CYL 58L CHLORINE 5PPM
30048	CYL 58L AMMONIA 50PPM
30110	CYL 58L CHLORINE 10PPM
30123	CYL 58L HCN 10PPM
30140	CYL 58L 5PPM NITROGEN DIOXIDE 58L
30112	CYL 58L 25PPM NITROGEN DIOXIDE 58L
30113	CYL 58L 25PPM NITRIC OXIDE 58L
30018	CYL 58L 4-GAS W/ METHANE
30019	CYL 58L 4-GAS W/ PENTANE
30045	CYL 58L 4 GAS W/ PENTANE SIMUL
100L (103L, 116L) Disposable	
30012	CYL 100L ISOBUTYLENE 10PPM
30009	CYL 100L ISOBUTYLENE 100PPM
30121	CYL 103L ISOBUTYLENE 1000PPM
30010	CYL 100L METHANE 100PPM
30178	CYL 100L 4% OXYGEN
30100	CYL 103L UHP HELIUM
30016	CYL 100L UHP NITROGEN
30021	CYL 100L ZERO AIR
30023	CYL 100L 50% CH4/35% CO2/N2
30036	CYL 100L 15% CH4/15% CO2/N2
30049	CYL 100L 50PPM CO/1000PPM CO2

Supplies	
30069	1L Tedlar Bags
30070	3L Tedlar Bags
30093	DEMAND REGULATOR 58L/103L
30094	1.0 LPM MALE REGULATOR C-10
30095	1.0 LPM FEMALE REG. CGA600

CALIBRATION SOLUTIONS

Item #	Description
30ml	
30054	ORP STANDARD 100MV (30ML)
30089	ORP STANDARD 238MV (30 ML)
120ml	
30115	ORP STANDARD 200MV (120ML)
30076	PH BUFFER SOLUTION 4 (120ML)
30077	PH BUFFER SOLUTION 7 (120ML)
30078	PH BUFFER SOLUTION 10 (120ML)
30083	ZERO OXYGEN STANDARD (120ML)
30091	CONDUCTIVITY 718 US/CM(120 ML)
30058	CONDUCTIVITY 1000 US/CM(120ML)
30092	CONDUCTIVITY 1413 US/CM 120ML
250ml	
30051	QUICK CAL. SOLUTION (250ML)
30067	AUTO CAL STANDARD PH 4 (250ML)
30087	PH BUFFER SOLUTION 4 (250ML)
30074	PH BUFFER SOLUTION 7 (250ML)
30075	PH BUFFER SOLUTION 10 (250ML)
500ml	
30071	PH BUFFER SOLUTION 4 (500ML)
30072	PH BUFFER SOLUTION 7 (500ML)
30073	PH BUFFER SOLUTION 10 (500ML)
30066	PH BUFFER SOLUTION 12 (500ML)
30082	ZERO OXYGEN STANDARD (500ML)
30084	AUTO CAL STANDARD PH 4 (500ML)
30142	CONDUCTIVITY 84 US/CM (500ML)
30065	CONDUCTIVITY 147 US/CM(500 ML)
30107	CONDUCTIVITY 447US/CM (500ML)
30090	CONDUCTIVITY 718 US/CM(500 ML)
30057	CONDUCTIVITY 1000 US/CM(500ML)
30059	CONDUCTIVITY 1413 US/CM(500ML)
30172	CONDUCTIVITY 5K US/CM (500 ML)
30159	NTU SOLUTION 0.02 (500 ML)
30160	NTU SOLUTION 10 (500 ML)
30161	NTU SOLUTION 100 (500 ML)
30162	NTU SOLUTION 1000 (500 ML)
30163	NTU SOLUTION 2 (500 ML)
30201	HACH <0.1 NTU (500ML)
30202	HACH 10 NTU (500ML)
30203	HACH 20 NTU (500ML)
30204	HACH 100 NTU (500ML)
30205	HACH 800 NTU (500ML)

Item #	Description
1L	
30053	ORP STANDARD 200MV (LITER)
30055	ORP STANDARD 229MV (LITER)
30147	COND. 71.8 MS/M HORIBA (LITER)
30145	CONDUCTIVITY 50K US/CM (LTR)
Gallon	
30157	DI WATER / PURIFIED (GAL)
30206	DI WATER TYPE I (GAL)
30117	DI WATER TYPE II (GAL)
30096	PH BUFFER SOLUTION 4 (GAL)
30097	PH BUFFER SOLUTION 7 (GAL)
30098	PH BUFFER SOLUTION 10 (GAL)
30105	AUTO CAL STANDARD PH 4 (GAL)
30106	CONDUCTIVITY 447US (GAL)
30181	CONDUCTIVITY 718 US/CM (GAL)
30099	CONDUCTIVITY 1000 US/CM (GAL)
30137	CONDUCTIVITY 1413 US/CM (GAL)
30144	CONDUCTIVITY 3,000 US/CM (GAL)
42164	AMCO CLEAR TURB 0.0 NTU (GAL)
42165	AMCO CLEAR TURB 10 NTU (GAL)
42166	AMCO CLEAR TURB 100 NTU (GAL)
42167	AMCO CLEAR TURB 800 NTU (GAL)
20L	
30156	DI WATER / PURIFIED (20L)
30136	DI WATER TYPE I (20L)
30086	DI WATER TYPE II (20L)
30060	CONDUCTIVITY 84 US/CM (20L)
30052	CONDUCTIVITY 447US (20L)
30120	CONDUCTIVITY 500 US/CM (20L)
30064	CONDUCTIVITY 718 US/CM (20L)
30056	CONDUCTIVITY 1000 US/CM (20L)
30061	CONDUCTIVITY 1413 US/CM (20L)
30068	CONDUCTIVITY 5000 US/CM (20L)
30062	CONDUCTIVITY 10K US/CM (20L)
30079	PH BUFFER SOLUTION 4 (20L)
30080	PH BUFFER SOLUTION 7 (20L)
30081	PH BUFFER SOLUTION 10 (20L)
30085	AUTOCAL STANDARD PH 4 (20L)
42027	AMCO CLEAR TURB 0.0 NTU (20L)
42028	AMCO CLEAR TURB 10 NTU (20L)
42029	AMCO CLEAR TURB 100 NTU (20L)
42030	AMCO CLEAR TURB 800 NTU (20L)

AIR QUALITY SUPPLIES

Item #	Description
PID LAMPS	
41013	MINIRAE/PPBRAE 10.6EV LAMP
41014	MINIRAE/PPBRAE 11.7EV LAMP
41029	TIGER PID 11.7 EV LAMP
41032	TIGER PID 10.6 EV LAMP
41035	MINIRAE PROBE TIP 6"
PID/TVA FILTERS & LUERS	
41001	THERMO TVA WATERTRAP FILTER
41002	MILLEX-FG Filter 50MM .2UM
41003	DUALEX PLUS TP FILTER 25MM
41008	MINIRAE PID EXTERNAL FILTERS
41012	MULTIRAE/ QRAE EXTERNAL FILTER
41041	TIGER PTFE FILTER DISCS
41022	TIGER BLUE FILTER INTERNAL 5UM
51109	MULTIRAE MALE LUER 1/8"
4-GAS SENSORS	
41004	MX4 O2 SENSOR
41005	MX4 H2S SENSOR
41006	MX4 CO SENSOR
41007	MX4 LEL SENSOR
51026	MX6 PID SENSOR
51027	MX6 CO SENSOR
51028	MX6 H2S SENSOR
51029	MX6 O2 SENSOR
51030	MX6 CO2 SENSOR
51031	MX6 LEL SENSOR
41009	MULTIRAE/QRAE+ H2S SENSOR
41010	MULTIRAE/QRAE+ CO SENSOR
41011	MULTIRAE/QRAE+ O2 SENSOR
41016	MULTIRAE LEL SENSOR
41017	MULTIRAE O2 SENSOR
41018	MULTIRAE CO SENSOR
41027	MULTIRAE HCN SENSOR
41038	MULTIRAE H2S SENSOR
41034	MULTIRAE LITE PID SENSOR
41036	MULTIRAE CO & H2S COMBO SENSOR
41021	QRAE-3 O2 SENSOR
51130	QRAE-3 H2S SENSOR
41039	QRAE-3 CO SENSOR
41040	QRAE-3 LEL SENSOR
41031	QRAE-2 LEL SENSOR

SOIL SUPPLIES

Item #	Description
Scoops	
43001	STERILIZED & BAGGED SCOOP 2OZ.
43002	STERILIZED & BAGGED SCOOP 4OZ.
43003	STERILIZED & BAGGED SCOOP 8OZ.
43007	CLEANED & BAGGED SCOOP 4 OZ.
43008	CLEANED & BAGGED SCOOP 6 OZ.
43009	CLEANED & BAGGED SCOOP 8 OZ.
PetroFlag	
43004	PETROFLAG REAGENT (10CT)
43020	PETROFLAG CAL. STANDARD (12CT)
AMS Core & Sludge Samplers	
43027	2" x 12" CORE SAMPLER LINER
43028	2" x 24" CORE SAMPLER LINER
43029	2" x 36" CORE SAMPLER LINER
43030	2" x 48" CORE SAMPLER LINER
43031	2" CORE SAMPLER EGG CATCHERS
43032	2" CORE SAMPLER LINER ENDCAPS
43011	3" X 12" SLUDGE SAMPLER LINER
43010	3" SLUDGE SAMPLER LINER ENDCAP
43025	.75X24" HOLLOWSTEM AUGER LINER
43026	.75" HOLLOWSTEM AUGER ENDCAPS
WILDCO Hand Corer	
43022	2" x 20" HAND CORER LINER
43023	2" x 30" HAND CORER LINER
43014	2" HAND CORER EGG CATCHERS
43024	2" HAND CORER LINER ENDCAPS
Miscellaneous	
43012	TRANSFER VESSEL 1/4" X 1/4"
43005	ALUMINUM DRIVE POINT
43006	DRIVE POINT ANCHOR
43013	ENCORE SAMPLER (5 GRAM)
43017	ENCORE SAMPLER (25 GRAM)
43015	TERRA CORE (5 GRAM)
43016	TERRA CORE (10 GRAM)
43018	SOIL SYRINGES 5ML (100CT)
43019	OIL IN SOIL KIT

WATER QUALITY SUPPLIES

Item #	Description
Well Plugs	
42001	1" ECO WELL PLUG (GREEN)
42002	2" ECO WELL PLUG (GREEN)
42003	4" ECO WELL PLUG (GREEN)
42146	1" WELL PLUG LOCKING ORANGE
42076	2" WELL PLUG LOCKING ORANGE
Oil Pads & Well Socks	
42004	OIL-ONLY WELL SOCK 1.5" X 24"
42025	OIL-ONLY ABSORBENT PAD 15"X19"
42026	OIL-ONLY BILDGE SOCK 3X18 20CT
42074	UNV-ONLY ABSORBENT PAD 15"X19"
42095	OIL-ONLY WELL SOCK 3 X 48"
42096	OIL-ONLY WELL SOCK 1.5 X 18"
ISCO Bottles & Jug	
42005	ISCO 10L SAMPLING JUG
42006	ISCO SAMPLER BOTTLES; 500ML
42007	ISCO SAMPLER BOTTLES; 1000ML
Foot Valves & Surge Blocks	
42009	WATERRA FOOTVALVE D-25
42010	WATERRA FOOTVALVE D-22
42011	WATERRA FOOTVALVE D-16
42012	WATERRA FOOTVALVE D-13
42013	WATERRA FOOTVALVE SS-19
42014	WATERRA FOOTVALVE SS-16
42015	WATERRA FOOTVALVE SS-13
42016	WATERRA FOOTVALVE SS-10
42017	WATERRA FOOTVALVE SS-6
42018	WATERRA SURGE BLOCK SBD-25
Check Valves & Surge Blocks	
42019	TU-BAH CHECK 1/2 X 5/8 OUTSIDE
42020	TU-BAH CHECK 1/2 X 5/8 INSIDE
42021	TU-BAH CHECK 3/8 X 1/2 INSIDE
42022	TU-BAH SURGE BLOCK
Dye Tablets	
42032	FLUORESCENT RED DYE TABLETS
42033	FLUOR YELLOW/GREEN DYE TABLETS

Item #	Description
Horiba Probes & Parts	
42038	U-50 HORIBA DO SENSOR
42039	U-52 HORIBA TURBIDITY SENSOR
42063	U-50 HORIBA PH ELECTRODE
42089	U-52 CALIBRATION CUP (2-PCS)
42090	U-50 PH SENSOR (TOUPH)
42091	U-52 HORIBA ORP ELECTRODE TIP
42093	U-52 REF. ELECTRODE CAP (2/PK)
YSI Probes & Parts	
42049	YSI 6560 COND/TEMP PROBE
42050	YSI 6562 DO PROBE
42051	YSI 6565 COMBO PH/ORP PROBE
42059	YSI 6136 YSI TURBIDITY PROBE
42052	YSI 5775 MEMBRANE-KCL KIT
42053	YSI 1001 PH PROBE
42054	YSI 1002 ORP PROBE
42055	YSI 2003 DO PROBE POLARGRAPHIC
42141	YSI PRO 1003 PH/ORP PROBE
42056	YSI 5908 MEMBRANE KIT (YELLOW)
42057	YSI 5908 MEMBRANE KIT (BLUE)
42105	YSI PRODSS 1M CABLE 4 -PORT
42106	YSI PRODSS 4M CABLE 4 -PORT
42107	YSI PRODSS 10M CABLE 4 -PORT
42108	YSI PRODSS COND & TEMP SENSOR
42109	YSI PRODSS OPTICAL DO SENSOR
42110	YSI PRODSS TURBIDITY SENSOR
42111	YSI PRODSS PH/ORP SENSOR
42112	YSI PRODSS FLOW CELL 4-PORT
42113	YSI PRODSS REPLACEMENT BATTERY
42114	YSI PRODSS SMALL HARD CASE
42123	YSI PRO SERIES FRONT COVER
42124	YSI PRO SERIES REAR COVER
42139	YSI 556 FLOW CELL

WATER QUALITY SUPPLIES

Item #	Description
Disposable Pumps & Controllers	
42040	WATER SPOUT 1 PLASTIC PUMP
42041	WATER SPOUT 2 PLASTIC PUMP
42080	SUPERNOVA 70 PLASTIC PUMP
42081	SUPERNOVA 120 PLASTIC PUMP
42161	MINI-MONSOON PLASTIC PUMP
42088	MONSOON PLASTIC PUMP
42128	MEGA-MONSOON PLASTIC PUMP
42133	TYPHOON PLASTIC PUMP
42134	TEMPEST PLASTIC PUMP
42162	TORNADO PLASTIC PUMP
42129	POWER BOOSTER 3 CONTROLLER
42143	POWER BOOSTER 2 CONTROLLER
42144	LOW FLOW CONTROLLER W/ P.B. 2
42145	LOW FLOW CONTROLLER W/ P.B. 3
42142	LOW FLOW SAMPLING CONTROLLER
QED Accessories	
42154	QED ST1102 TEFLON BLADDERS
42058	QED 3/4 POLY BLADDERS
42042	QED 1 3/4 POLY BLADDERS
42047	QED 1 3/4 TEFLON BLADDER
42043	QED 1 3/4 SCREENS
42044	QED 1 3/4 O-RINGS
42045	QED 1 3/4 GRAB PLATE 1/4 X 1/4
42046	QED 1 3/4 GRAB PLATE 1/4 X 3/8
42048	QED 1 3/4 CHECK BALLS
42094	QED POLY BLADDER KIT
42163	QED TEFLON BLADDER KIT
42135	QED BLADDER KIT T1200 SERIES
42136	QED BLADDER CLAMP TOOL / PUNCH
Solinsts Parts	
42060	101 P7 SS WLM PROBE
42061	P7 101 FACEPLATE W/ELECTRONICS
42062	P8 122 FACEPLATE W/ELECTRONICS
42064	122/122M (CSA) P8 PROBE
42065	101/107/122 REPL. TAPE 100FT
42066	101/107/122 REPL. TAPE 200FT
42067	101/107/122 REPL. TAPE 300FT

Item #	Description
Grundfos Parts (Morris)	
42082	GRUNDFOS SHORT MTR SCREWS
42083	GRUNDFOS BRASS MTR WASHERS
42084	GRUNDFOS BULK CONNECTOR KIT
42085	GRUNDFOS MOTOR LEAD TERM KIT
42086	GRUNDFOS MALE PLUG
Graduated Cylinders	
42097	GRADUATED CYLINDER 25ML
42098	GRADUATED CYLINDER 50ML
42099	GRADUATED CYLINDER 100ML
42100	GRADUATED CYLINDER 250ML
42101	GRADUATED CYLINDER 500ML
42102	GRADUATED CYLINDER 1000ML (1L)
Geotech Parts & Bladders	
42115	GEOTECH BP SPARE PART KIT 1.66"
42116	GEOTECH O-RING SRVCE KIT 1.66"
42117	GEOTECH PARTS KIT 1.66 (NO PFC)
42118	GEOTECH ORING KIT 1.66" NO PFC
42036	GEOTECH TEFLON BLADDER .85"
42034	GEOTECH POLY BLADDER .85"
42035	GEOTECH POLY BLADDER .675"
42073	GEOTECH POLY BLADDER 1.66"
42072	GEOTECH TEFLON BLADDER 1.66"
41033	GEOTECH BLADDER KIT
42125	CONN,HRTG,FEMALE,STRAIGHT
42126	WASHER GROMMET PIN KIT
42127	CONN,AMP,FEMALE,PANEL
Qwater	
42119	QWATER 3/4" INCH
42120	QWATER 1" INCH
42121	QWATER 2" INCH
42122	QWATER 4" INCH
Miscellaneous	
42024	WELL KEY
42078	HACH REPLACEMENT LAMP 2100Q

PROJECT SUPPLIES

Item #	Description
Gloves	
40002	NITRILE PF GLOVES SMALL
40003	NITRILE PF GLOVES MEDIUM
40004	NITRILE PF GLOVES LARGE
40005	NITRILE PF GLOVES X-LARGE
40111	NITRILE SEMPERFORCE BLACK MED
40112	NITRILE SEMPERFORCE BLACK LG
40113	NITRILE SEMPERFORCE BLACK XL
40114	NITRILE SEMPERFORCE BLACK XXL
40107	BLAZE ORANGE NITRILE GLOVES M
40108	BLAZE ORANGE NITRILE GLOVES L
40109	BLAZE ORANGE NITRILE GLOVES XL
40110	BLAZE ORANGE NITRILE GLOVES 2X
40080	RADNOR GREY ACRYLIC GLOVES L
Field Books & Pens	
40006	FIELD BOOK USE ORANGE
40007	RITE IN RAIN FIELD BOOK 550F
40009	RITE IN RAIN FIELD BOOK 540F
40012	RITE IN RAIN FIELD BOOK 350
40013	RITE IN RAIN FIELD BOOK 300
40014	RITE IN RAIN FIELD BOOK 310
40097	RITE N RAIN FIELD BOOK 770F
40015	RITE IN RAIN NOTE BOOK 353
40098	RITE N RAIN FIELD BOOK 773
40099	RITE N RAIN FIELD BOOK 1973
40132	RITE RAIN SPIRAL NOTEBOOK 393
40010	RITE IN RAIN FIELD BOOK 311FX
40011	RITE IN RAIN FIELD BOOK 351FX
40016	RITE IN RAIN BLACK PEN #93
40017	RITE IN RAIN BLUE PEN #93
40096	RITE N RAIN PINK PEN
40130	RITE IN RAIN BLACK PEN REFILL
40131	RITE IN RAIN BLUE PEN REFILL
Flag Tape	
40031	FLAGGING TAPE - FLUOR. ORANGE
40032	FLAGGING TAPE - WHITE
40033	FLAGGING TAPE - FLUOR. GREEN
40034	FLAGGING TAPE - BLUE
40035	FLAGGING TAPE - FLUOR. PINK
40057	CAUTION TAPE 1000FT.

Item #	Description
Hazmat Boots & Tyvek Suits	
40118	RADNOR HAZMAT OVERBOOT L
40023	RADNOR HAZMAT OVERBOOTS XL
40024	RADNOR HAZMAT OVERBOOTS XXL
40090	RADNOR HAZMAT OVERBOOTS XXXL
40152	TYVEK COVERALL W/ BOOTS ONLY L
40151	TYVEK COVERALL W/ BOOTS ONLY XL
40054	TYVEK COVERALL HOOD & BOOTS MD
40055	TYVEK COVERALL HOOD & BOOTS LG
40056	TYVEK COVERALL HOOD & BOOTS XL
40072	TYVEK COVERAL HOOD & BOOTS 2XL
40073	TYVEK COVERAL HOOD & BOOTS 3XL
40101	TYVEK COVERALL ELASTIC A&L MD
40102	TYVEK COVERALL ELASTIC A&L LG
40103	TYVEK COVERALL ELASTIC A&L XL
40104	TYVEK COVERALL ELASTIC A&L 2XL
40105	TYVEK COVERALL ELASTIC A&L 3XL
40074	TYCHEM YELLOW HOOD & BOOTS LG
40075	TYCHEM YELLOW HOOD & BOOTS XL
40076	TYCHEM YELLOW HOOD & BOOTS 2XL
40079	TYCHEM YELLOW HOOD & BOOTS 3XL
Cleaning Solutions	
40025	LIQUINOX QUART
40027	ALCONOX PACKET (BOX 50CT.)
40026	ALCONOX 4LB BOX
40029	LIQUINOX GALLON
40121	LUMINOX GALLON SIZE
Flammable Cleaning Solutions	
40001	GR ACS METHANOL 4L
40129	GR ACS METHANOL (1L)
40120	ISOPROPYL ALCOHOL, ACS 4L
Survey Stakes	
40036	SURVEY STAKES 1FT. (24 CT.)
40037	SURVEY STAKES 2FT. (24 CT.)
40038	SURVEY STAKES 3FT. (24 CT.)
40039	SURVEY STAKES 4FT. (24 CT.)
Earplugs	
40061	MAX LITE EARPLUGS UNCORDED
40123	MAX LITE EARPLUGS CORDED
40062	HOWARD LEIGHT BELL EARPLUGS

THE BEST RENTAL EXPERIENCE POSSIBLE

Just a few of the benefits our satisfied clients enjoy

Flexible Rental Schedules: We recognize that your projects do not always last just one day, one week, or one month.

Long-Term Rentals: With our Long-Term Rental program, you enjoy the best of both worlds; it's like owning the equipment, but with the savings and low liability of rentals.

We're Local: Our convenient location, delivery service, and Fed Ex Shipping center mean you'll never have to worry about waiting for your equipment or supplies to arrive. No on site down-time.

Experience: We have the most experienced associates in our industry. Our knowledgeable sales team and technicians will provide training and help you through difficult decisions and on-site troubleshooting.

Expansive Inventory: We have new, updated equipment and supplies to address just about every environmental monitoring situation.

Technology: We genuinely enjoy studying and applying the newest technologies to our business and your applications.

Simple, Smart Accounting: With paperless invoices and prompt pay discounts, you save time & money.

So much more than rentals...

Since 1996, our family-owned company has been a leader in providing rentals of environmental and safety monitoring equipment, accessories, and related items. However, we do so much more. Not only are we **authorized resellers and distributors** for nearly all of the manufacturers we represent; we also have experienced, **factory-trained technicians** available for **training, service, and repairs** at each of our locations.



U.S. Environmental

Rentals • **Sales** • **Service**
DEVICE & DATA EXPERTISE

usenvironmental.com | (888) 550-8100

RENTING VS. OWNING

Why not have the best of both?

Long-Term Rental Program

U.S. Environmental's unique solution where you get the benefits of renting and owning!

Typically, our clients see over 40% percent savings when they switch from frequent short-term rentals to our Long-Term Rental Program.

- The equipment is always on-site or in your office.
- Replacements, when necessary, no additional cost.
- One monthly invoice. Easy!
- No hidden costs related to owning.

Terms & Conditions apply



Long-term rentals not right for you?

Short-Term Rentals

- Competitive, flexible pricing.
- Local Delivery or shipping to your office or site.
- Accurate, certified equipment

Equipment Purchasing

- Authorized distributor for RAE Systems, YSI, Geotech, QED, & more.
- Our purchasing power means you save when you purchase equipment and supplies.
- Support, training, and service on every item we sell.




U.S. Environmental
Rentals • Sales • Service
DEVICE & DATA EXPERTISE

usenvironmental.com | (888) 550-8100

Waltham, Massachusetts (HQ)

(781) 899-1560
166 Riverview Ave.
Waltham, MA 02453



usenvironmental.com

(888) 550-8100


East Hartford, Connecticut

(860) 289-8700
91 Prestige Park Circle, Suite 5,
East Hartford, CT 06108




Hamilton, New Jersey

(609) 570-8555
5C South Gold Drive
Hamilton, NJ 08691



Tampa, Florida

(813) 628-4200
1202 Tech Blvd.
Tampa, FL 33619



Elmhurst, Illinois

(630) 501-1847
781 Industrial Dr.
Elmhurst, IL 60126

