BLE4.2

Transparent Transmission Module User manual

XW32-BLE

V1.1 2019.09.11

CONTENTS

1.	Version History, Disclaimer and Notice	3
2.	General Description	
3.	Package and Dimensions	.4
4.	Pin Assignment	.5
5.	Product Function and Test Description	.6
6.	UUID	.6
7.	Communication Interface for Module and MCU 7.1 Asynchronous Serial Communication 7.2 Packet Format 7.3 Operation Mode Setting	6 6 6
8.	AT Command	 7 7 7 7 8 8 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9
9.	Power consumption	10
10	. Recommended Reflow Profile	10
11 FC	. Appendix: Reference Specification C Requirement(FCC warning - Module)	10 11

I.I Version history				
Version	Date	Author	Description	
V1.0	2019/03/26	Chen	First draft	
V1.1	2019/09/11	Chen	Update Description	

1. Version History, Disclaimer and Notice

1.2 Disclaimer and Notice

The document is provided "AS IS", without warranty of any kinds, including the implied warranties of merchantability and applies to any guarantee for a particular purpose, or non infringement, and any proposal, specification or sample of any guarantee mentioned anywhere else.

This document does not bear any responsibility, including the use of the document information from infringement of any patent infringement liability.

This document is not here by estoppel or otherwise, any intellectual property rights is granted the license, whether express or implied license.

The information in this document might be modified for upgrade or other reasons. XINWU corporation reserves the rights to make change without notice. This document is used for design guide only, XINWU corporation try the best to supply the correct information, but it does not assure there is not any error in this document. All the ostensive or implied states, information, suggestion are not guaranteed.

2. General Description

Module XW32-BLE is a highly integrated Bluetooth 4.2 dual mode with 2 Mbps data rate option. It integrates a high-performance RF transceiver, baseband, ARM9E core, rich feature peripheral units, programmable protocol and profile to support BLE application. The Flash program memory makes it suitable for customized applications.

3. Package and Dimensions



Length	Width	Height	PAD (bottom)	Pin pitch
(mm)	(mm)	(mm)	(mm)	(mm)
18	12	1.7±0.2	0.75 x 2.4	1.25

XW32-BLE module dimensions

4. Pin Assignment

No.	Pin name	Description
1、3、4、	GND	GND
9、18、26		
2	ANT	External antenna available when required
5	P31	IO interface, ADC1
6	P32	IO interface , ADC2
7	P14	IO interface , PWM4
8	VCCBAT	3.0V VCC
10	RSTN	Reset, low effective(controlled by external MCU
		IO)
11	P00/TXD1	IO interface or UART1 RXD , for UART sending
12	P01/RXD1	IO interface , UART1 RXD , for UART reception
13	P17	IO interface , UART_RXD2
14	P16	IO interface , UART_TXD2
15	P13	IO interface , PWM3
16	P33	IO interface , ADC3
17	P12	IO interface , PWM2
19	P10	IO interface , PWM0
20	P07	IO interface , PWM5 , SPI_NSS , JTAG_TMS
21	P06	IO interface , SPI_MISO , PWM4 , JTAG_TCK
22	P05	IO interface, SPI_MOSI, JTAG_TDO
23	P04	IO interface , SPI_SCK , JTAG_TDI
24	P03	IO interface , I2C_SDA , JTAG_NTRST
25	P02	IO interface , I2C_SCL

1

5. Product Function and Test Description

BLE slave mode support.

•Default setting:

Operation Mode: transparent transmission mode default. For using the AT command please switch to the command mode;

UART parameter: 9600, 8 bit data, no parity bit, 1 bit for stop;

BLE name: BleSerialPort;

Broadcast interval: "80, 80", max=50ms, min=50ms;

Connect interval: "36,24,2,100", max=36, min=24, latency=2,

timeout=300(max=45ms,min=30ms,latency=2,timeout=1000ms).

•UART ports could be enabled to switch operation status and sleeping status.

•AT command mode and transparent transmission mode could be swithed by using command.

•AT command for parameter configuration is available.

•At 0dBm Tx power, connecting distance reaches 40m in open area.

- •Each frame can packet up to 20 bytes data.
- •Sleeping current: refer to chapter 10

•Supply voltage: 1.55~3.5V, 3.0 V is recommended

- •Dimension: 18mm*12mm*1.7mm
- •Applications:

BLE health products, Wearable devices, Smart home, BLE toys, Lighting control, Bluetooth to serial products.

6. UUID

Slave service UUID: 0xFFB0 Eigenvalue UUID: 0xFFB1 Properties: Write Notify Eigenvalue UUID: 0xFFB2 Properties: Write Notify

7. Communication Interface for Module and MCU

7.1 Asynchronous Serial Communication

BLE module communicate with MCU by serial port (UART).

Default port parameter: baud rate 9600, 8 data, 1 stop, no parity.

7.2 Packet Format

Transparent transmission mode: BLE module forwards the data from MCU to APP without change. And the same as data from APP to MCU.

Instruction mode: Module can be configured by AT command by either APP or PC UART.

7.3 Operation Mode Setting

Switching between AT command mode and transparent transmission mode: Power on default transparent transmission mode. Send"+++" then return"AT+ok Mode=AT Mode\r\n", the module turns into AT command mode and AT command are available for setting and reading.

Send"AT+exit\r\n"then return"AT+ok Mode=Normal\r\n", the module turns back to transparent transmission mode and data will be transparently transmitted directly. **Notie: Don't insert any other characters inside "+++".**

8. AT Command

Notice: Power on default transparent transmission mode, and send"+++" into command mode. AT command finishes with "\r\n" in command mode. Tick "send new line" in serial port assistant.

9.1 AT Command List	
Command	Description
"AT+setBR 9600\r\n"	Set baud rate
"AT+getName\r\n"	Read BLE name
"AT+setName=bleName\r\n"	Set BLE name
"AT+getAddr\r\n"	Get BLE address
"AT+setAddr=112233445566\r\n"	Set BLE address
"AT+getStatus\r\n"	Get BLE status
"AT+setAdvInt 80 100\r\n"	Set broadcast interval
"AT+setConnInt 36 24 2 300 \r\n "	Set connection interval
"AT+disConnect\r\n"	Disconnect
"AT+reStart\r\n"	Restart
"AT+getPara\r\n"	Get config parameter
"AT+exit\r\n"	Exit command mode(truns to
	transparent transmission mode);
	Send "+++"swichs to command
	mode to transparent
	transmission mode.
"AT+shutDown\r\n"	Shut down
"AT+reStore\r\n"	Factory reset
"AT+getInfo\r\n"	Version inquiry
"AT+help\r\n"	Instruction help

9.2 Set Baud Rate

Notice: Not valid until manual restart.

Example: "AT+setBR 9600\r\n" ("\r\n"is end mark, hexadecimal as "0D 0A", the same below)

Hex: 41 54 2B 20 73 65 74 42 52 20 39 36 30 30 0D 0A (There is no space between each number. The space can be inserted by some software and some can ignore spaces automatically, the same below)

Replies: "AT+ok\r\n" (Operation completed); "AT+err_code\r\n" (Operation failed, refer to "Returned error code indication" for detailed err_code)

 Baud rate range: (Error indicated for incorrect baud rate)

 2400, 4800, 9600, 19200, 38400, 57600, 115200

9.3 Read BLE Name

Example: "AT+getName\r\n"

Hex: 41 54 2B 20 67 65 74 4E 61 6D 65 0D 0A

 $\label{eq:constraint} \begin{array}{l} Replies: ``AT+ok\r\n'' (Operation completed); ``AT+err_code\r\n'' (Operation failed, refers to ``Returned error code indication'' for detailed err_code) \end{array}$

9.4 Set BLE Device Name

Notice: Not availble until manual restart.

Example: "AT+setName=bleName\r\n"(such as SENSSUN FAT)

Hex: 41 54 2B 20 73 65 74 4E 61 6D 65 20 3D 62 6C 65 4E 61 6D 65 0D 0A Replies: "AT+ok restart effect!\r\n" (Operation completed, valid after sending command and restart); "AT+err_code\r\n" (Operation failed, refer to "Returned error code indication" for detailed err_code)

9.5 Read BLE MAC Address

Example: "AT+getAddr\r\n"

Hex: 41 54 2B 20 67 65 74 41 64 64 72 0D 0A

Replies: "AT+ok FF:11:22:33:66:FF\r\n" (Operation completed); "AT+err_code\r\n" (Operation failed, refer to "Returned error code indication" for detailed err_code)

9.6 Set BLE MAC Address

Example: "AT+setAddr=112233445566\r\n"

Hex: 41 54 2B 20 73 65 74 41 64 64 72 3D 31 31 32 32 33 33 34 34 35 35 36 36 0D 0A

Replies: "AT+ok restart effect!\r\n" (Operation completed, valid after sending command and restart); "AT+err_code\r\n" (Operation failed, refer to "Returned error code indication" for detailed err code)

9.7 Read BLE Status: Broadcast/Connected

Example: "AT+getStatus\r\n"

Hex: 41 54 2B 20 67 65 74 53 74 61 74 75 73 0D 0A

Replies: "AT+ok status_code\r\n"(Operation completed), status_code as below:

00	Idle
01	Broadcasting
02	Connecting
03	Scan with response
04	scan without response

"AT+err_code\r\n" (Operation failed, refer to "Returned error code indication" for detailed err_code)

9.8 Set Broadcast Interval

Not valid until manual restart.

Example: "AT+setAdvInt 80 100\r\n" (min interval 80*0.625ms, max interval 100*0.625ms)

Hex: 41 54 2B 20 73 65 74 41 64 76 49 6E 74 20 38 30 20 31 30 30 0D 0A (Maximum and minimum of broadcast interval, "min<=max", 80~16000 correspond to 50ms~10000ms)

Replies: "AT+ok restart effect!\r\n" (Operation completed, valid after sending command and restart); "AT+err_code\r\n" (Operation failed, refer to "Returned error code indication" for detailed err_code)

9.9 Set Connection Interval

Notice: valid immediately, constantly setting will get dropped.

Example: "AT+setConnInt 36 24 2 300 \r\n "(The value respectively max, min, latency, timeout)

Hex: 41 54 2B 20 73 65 74 43 6F 6E 6E 49 6E 74 20 33 36 20 32 34 20 32 20 33 30 30 0D 0A

In the example above, max interval 36*1.25ms, min interval 24*1.25ms, latency 2, connecting timeout 300*10ms.

Min and max broadcast interval range: 0x0006~0x0C80(7.5ms~4000ms), min<=max.

Latency: value range: 0x0000~0x01F3(0~499).

Connecting time out: value range: 0x000A~0x0C80. Connection interval must less than connecting timeout: [max*1.25 * (1+latency)] < 10 * timeout.

Replies: "AT+ok\r\n" (Operation completed, valid immediately without restart);

"AT+err_code\r\n" (Operation failed, refer to"Returned error code indication"for

detailed err_code)

9.10 Disconnect BLE

Example: "AT+disConnect\r\n"

Hex: 41 54 2B 20 64 69 73 43 6F 6E 6E 65 63 74 0D 0A

Replies: "AT+ok\r\n" (Operation completed); "AT+err_code\r\n" (Operation failed,

refer to "Returned error code indication" for detailed err_code)

9.11 Reset/Restart

Example: "AT+reStart\r\n"

Hex: 41 54 2B 20 72 65 53 74 61 72 74 0D 0A

Reply: "AT+ok restart now \r\n" (Operation completed, restart at once automatically)

9.12 Read Parameter

Example: "AT+getPara\r\n"

Hex: 41 54 2B 20 67 65 74 50 61 72 61 0D 0A

Reply: "AT+ok uart 9600,8,N,1; adv 120 160; con 36,24,2,300.\r\n" (Operation completed), returned parameter contains UART port, broadcast interval, connection interval.

9.13 Exit Command Mode

Example: "AT+exit\r\n"

Hex: 41 54 2B 20 65 78 69 74 0D 0A

Reply: "AT+ok Mode=Normal\r\n" (Operation completed, switches to transparent transmission mode)

9.14 Shut Down

Example: "AT+shutDown\r\n" Hex: 41 54 2B 20 73 68 75 74 44 6F 77 6E 0D 0A Reply: "AT+ok power off now!\r\n"(Operation completed)

9.15 Factory reset

Example:"AT+reStore\r\n" Hex: 41 54 2B 20 72 65 53 74 6F 72 65 0D 0A

Reply: "AT+ ok restart now\r\n" (Operation completed)

9.16 Version inquiry

Example:"AT+getInfo\r\n" Hex: 41 54 2B 67 65 74 49 6E 66 6F 0D 0A Reply:AT+ok HW=XW32-BLE-BLE-JXKJ,SW=V0.2

9.17 Instruction help

Example: "AT+help\r\n" Hex:41 54 2B 20 68 65 6C 70 0D 0A Reply:AT+ok Help: system_shutdown setBR getName setName getAddr setAddr getStatus setAdvInt setConnInt disConnect reStore reStart getPara

getInfo exit help 9.18 Returned Error Code Indication

err_code	Indication
"06"	The last operation was not
	completed
"07"	Command parameter is not valid
"08"	Disconnected
"09"	Connecting
"10"	Broadcasting
"11"	Operation failed

9. Power consumption

Broadcast interval 100ms : 220ua

Broadcast interval 500ms: 70ua

Broadcast interval 1000ms : 40ua

Deep sleep current(no broadcast): 7uA

10. Recommended Reflow Profile

Peak Temperature: <250°C

Number of Times: ≤ 2 times



11. Appendix: Reference Specification

《BLUETOOTH SPECIFICATION Version 4.2》 《IEEE 802.15.1》

FCC Requirement(FCC warning - Module)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and

(2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Please notice that if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC ID: 2AW97-XW32" any similar wording that expresses the same meaning may be used.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator & your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

The module is limited to OEM installation ONLY.

The OEM integrator is responsible for ensuring that the end-user has no manual instruction to remove or install module.

The module is limited to installation in mobile application.

A separate approval is required for all other operating configurations, including portable configurations with respect to Part 2.1093 and difference antenna configurations.

There is requirement that the grantee provide guidance to the host manufacturer for compliance with Part 15B requirements.

The OEM integrator is responsible for ensuring that the end-user has no manual instructions to rem-ove or install module.

The module is limited to installation in mobile or fixed application.

The final host / module combination may also need to be evaluated against the FCC Part 15B criteria for unintentional radiators in order to be properly authorized for operation as a Part 15 digital device. The FCC Part 15 Statement shall be included in the user manual of the end user product if applicable.

This modular complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Model No.: XW32-BLE FCC ID: 2AW97-XW32