

FTB-1



www.EXFO.com

Telecom Test and Measurement

EXFO

EXPERTISE REACHING OUT

Copyright © 2010–2013 EXFO Inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form, be it electronically, mechanically, or by any other means such as photocopying, recording or otherwise, without the prior written permission of EXFO Inc. (EXFO).

Information provided by EXFO is believed to be accurate and reliable. However, no responsibility is assumed by EXFO for its use nor for any infringements of patents or other rights of third parties that may result from its use. No license is granted by implication or otherwise under any patent rights of EXFO.

EXFO's Commerce And Government Entities (CAGE) code under the North Atlantic Treaty Organization (NATO) is 0L8C3.

The information contained in this publication is subject to change without notice.

Trademarks

EXFO's trademarks have been identified as such. However, the presence or absence of such identification does not affect the legal status of any trademark.

Units of Measurement

Units of measurement in this publication conform to SI standards and practices.

Version number: 18.0.1

End-User License Agreement

You have acquired a device ("DEVICE") that includes software licensed by EXFO Inc. (EXFO) from an affiliate of Microsoft Corporation ("MS"). Those installed software products of MS origin, as well as associated media, printed materials, and "online" or electronic documentation ("SOFTWARE") are protected by international intellectual property laws and treaties. Manufacturer, MS and its suppliers (including Microsoft Corporation) own the title, copyright, and other intellectual property rights in the SOFTWARE. The SOFTWARE is licensed, not sold. All rights reserved.

This EULA is valid and grants the end-user rights ONLY if the SOFTWARE is genuine and a genuine Certificate of Authenticity for the SOFTWARE is included. For more information on identifying whether your software is genuine, please see <http://www.microsoft.com/piracy/howtotell>.

IF YOU DO NOT AGREE TO THIS END USER LICENSE AGREEMENT ("EULA"), DO NOT USE THE DEVICE OR COPY THE SOFTWARE. INSTEAD, PROMPTLY CONTACT EXFO FOR INSTRUCTIONS ON RETURN OF THE UNUSED DEVICE(S) FOR A REFUND. **ANY USE OF THE SOFTWARE, INCLUDING BUT NOT LIMITED TO USE ON THE DEVICE, WILL CONSTITUTE YOUR AGREEMENT TO THIS EULA (OR RATIFICATION OF ANY PREVIOUS CONSENT).**

GRANT OF SOFTWARE LICENSE. This EULA grants you the following license:

- You may use the SOFTWARE only on the DEVICE.
- **Restricted Functionality.** You are licensed to use the SOFTWARE to provide only the limited functionality (specific tasks or processes) for which the DEVICE has been designed and marketed by EXFO. This license specifically prohibits any other use of the software programs or functions, or inclusion of additional software programs or functions that do not directly support the limited functionality on the DEVICE. Notwithstanding the foregoing, you may install or enable on a DEVICE, systems utilities, resource management or similar software solely for the purpose of administration, performance enhancement and/or preventive maintenance of the DEVICE.
- If you use the DEVICE to access or utilize the services or functionality of Microsoft Windows Server products (such as Microsoft Windows Server 2003), or use the DEVICE to permit workstation or computing devices to access or utilize the services or functionality of Microsoft Windows Server products, you may be required to obtain a Client Access License for the DEVICE and/or each such workstation or computing device. Please refer to the end user license agreement for your Microsoft Windows Server product for additional information.
- **NOT FAULT TOLERANT.** THE SOFTWARE IS NOT FAULT TOLERANT. EXFO HAS INDEPENDENTLY DETERMINED HOW TO USE THE SOFTWARE IN THE DEVICE, AND MS HAS RELIED UPON EXFO TO CONDUCT SUFFICIENT TESTING TO DETERMINE THAT THE SOFTWARE IS SUITABLE FOR SUCH USE.
- **NO WARRANTIES FOR THE SOFTWARE.** THE SOFTWARE is provided "AS IS" and with all faults. THE ENTIRE RISK AS TO SATISFACTORY QUALITY, PERFORMANCE, ACCURACY, AND EFFORT (INCLUDING LACK OF NEGLIGENCE) IS WITH YOU. ALSO, THERE IS NO WARRANTY AGAINST INTERFERENCE WITH YOUR ENJOYMENT OF THE SOFTWARE OR AGAINST INFRINGEMENT. IF YOU HAVE RECEIVED ANY WARRANTIES REGARDING THE DEVICE OR THE SOFTWARE, THOSE WARRANTIES DO NOT ORIGINATE FROM, AND ARE NOT BINDING ON, MS.
- **No Liability for Certain Damages. EXCEPT AS PROHIBITED BY LAW, MS SHALL HAVE NO LIABILITY FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE SOFTWARE. THIS LIMITATION SHALL APPLY EVEN IF ANY REMEDY FAILS OF ITS ESSENTIAL PURPOSE. IN NO EVENT SHALL MS BE LIABLE FOR ANY AMOUNT IN EXCESS OF U.S. TWO HUNDRED FIFTY DOLLARS (U.S.\$250.00).**
- **Restricted Uses.** The SOFTWARE is not designed or intended for use or resale in hazardous environments requiring fail-safe performance, such as in the operation of nuclear facilities, aircraft navigation or communication systems, air traffic control, or other devices or systems in which a malfunction of the SOFTWARE would result in foreseeable risk of injury or death to the operator of the device or system, or to others.
- **Limitations on Reverse Engineering, Decompilation, and Disassembly.** You may not reverse engineer, decompile, or disassemble the SOFTWARE, except and only to the extent that such activity is expressly permitted by applicable law notwithstanding this limitation.
- **SOFTWARE as a Component of the DEVICE - Transfer.** This license may not be shared, transferred to or used concurrently on different computers. The SOFTWARE is licensed with the DEVICE as a single integrated product and may only be used with the DEVICE. If the SOFTWARE is not accompanied by a DEVICE, you may not use the SOFTWARE. You may permanently transfer all of your rights under this EULA only as part of a permanent sale or transfer of the DEVICE, provided you retain no copies of the SOFTWARE. If the SOFTWARE is an upgrade, any transfer must also include all prior versions of the SOFTWARE. This transfer must also include the Certificate of Authenticity label. The transfer may not be an indirect transfer, such as a consignment. Prior to the transfer, the end user receiving the SOFTWARE must agree to all the EULA terms.
- **Consent to Use of Data.** You agree that MS, Microsoft Corporation and their affiliates may collect and use technical information gathered in any manner as part of product support services related to the SOFTWARE. MS, Microsoft Corporation and their affiliates may use this information solely to improve their products or to provide customized services or technologies to you. MS, Microsoft Corporation and their affiliates may disclose this information to others, but not in a form that personally identifies you.

-
- **Internet Gaming/Update Features.** If the SOFTWARE provides, and you choose to utilize, the Internet gaming or update features within the SOFTWARE, it is necessary to use certain computer system, hardware, and software information to implement the features. By using these features, you explicitly authorize MS, Microsoft Corporation and/or their designated agent to use this information solely to improve their products or to provide customized services or technologies to you. MS or Microsoft Corporation may disclose this information to others, but not in a form that personally identifies you.
 - **Internet-Based Services Components.** The SOFTWARE may contain components that enable and facilitate the use of certain Internet-based services. You acknowledge and agree that MS, Microsoft Corporation or their affiliates may automatically check the version of the SOFTWARE and/or its components that you are utilizing and may provide upgrades or supplements to the SOFTWARE that may be automatically downloaded to your DEVICE. Microsoft Corporation or their affiliates do not use these features to collect any information that will be used to identify you or contact you. For more information about these features, please see the privacy statement at <http://go.microsoft.com/fwlink/?LinkId=25243>.
 - **Links to Third Party Sites.** You may link to third party sites through the use of the SOFTWARE. The third party sites are not under the control of MS or Microsoft Corporation, and MS or Microsoft are not responsible for the contents of any third party sites, any links contained in third party sites, or any changes or updates to third party sites. MS or Microsoft Corporation is not responsible for webcasting or any other form of transmission received from any third party sites. MS or Microsoft Corporation are providing these links to third party sites to you only as a convenience, and the inclusion of any link does not imply an endorsement by MS or Microsoft Corporation of the third party site.
 - **Notice Regarding Security.** To help protect against breaches of security and malicious software, periodically back up your data and system information, use security features such as firewalls, and install and use security updates.
 - **No Rental/Commercial Hosting.** You may not rent, lease, lend or provide commercial hosting services with the SOFTWARE to others.
 - **Separation of Components.** The SOFTWARE is licensed as a single product. Its component parts may not be separated for use on more than one computer.
 - **Additional Software/Services.** This EULA applies to updates, supplements, add-on components, product support services, or Internet-based services components ("Supplemental Components"), of the SOFTWARE that you may obtain from EXFO, MS, Microsoft Corporation or their subsidiaries after the date you obtain your initial copy of the SOFTWARE, unless you accept updated terms or another agreement governs. If other terms are not provided along with such Supplemental Components and the Supplemental Components are provided to you by MS, Microsoft Corporation or their subsidiaries then you will be licensed by such entity under the same terms and conditions of this EULA, except that (i) MS, Microsoft Corporation or their subsidiaries providing the Supplemental Components will be the licensor with respect to such Supplemental Components in lieu of the "COMPANY" for the purposes of the EULA, and (ii) TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THE SUPPLEMENTAL COMPONENTS AND ANY (IF ANY) SUPPORT SERVICES RELATED TO THE SUPPLEMENTAL COMPONENTS ARE PROVIDED AS IS AND WITH ALL FAULTS. ALL OTHER DISCLAIMERS, LIMITATION OF DAMAGES, AND SPECIAL PROVISIONS PROVIDED BELOW AND/OR OTHERWISE WITH THE SOFTWARE SHALL APPLY TO SUCH SUPPLEMENTAL COMPONENTS. MS, Microsoft Corporation or their subsidiaries reserve the right to discontinue any Internet-based services provided to you or made available to you through the use of the SOFTWARE.
 - **Recovery Media.** If SOFTWARE is provided by EXFO on separate media and labeled "Recovery Media" you may use the Recovery Media solely to restore or reinstall the SOFTWARE originally installed on the DEVICE.
 - **Backup Copy.** You may make one (1) backup copy of the SOFTWARE. You may use this backup copy solely for your archival purposes and to reinstall the SOFTWARE on the DEVICE. Except as expressly provided in this EULA or by local law, you may not otherwise make copies of the SOFTWARE, including the printed materials accompanying the SOFTWARE. You may not loan, rent, lend or otherwise transfer the backup copy to another user.
 - **End User Proof of License.** If you acquired the SOFTWARE on a DEVICE, or on a compact disc or other media, a genuine Microsoft "Proof of License"/Certificate of Authenticity label with a genuine copy of the SOFTWARE identifies a licensed copy of the SOFTWARE. To be valid, the label must be affixed to the DEVICE, or appear on [COMPANY'S] software packaging. If you receive the label separately other than from EXFO, it is invalid. You should keep the label on the DEVICE or packaging to prove that you are licensed to use the SOFTWARE.
 - **Product Support.** Product support for the SOFTWARE is not provided by MS, Microsoft Corporation, or their affiliates or subsidiaries. For product support, please refer to EXFO support number provided in the documentation for the DEVICE. Should you have any questions concerning this EULA, or if you desire to contact EXFO for any other reason, please refer to the address provided in the documentation for the DEVICE.
 - **Termination.** Without prejudice to any other rights, EXFO may terminate this EULA if you fail to comply with the terms and conditions of this EULA. In such event, you must destroy all copies of the SOFTWARE and all of its component parts.
 - **EXPORT RESTRICTIONS.** You acknowledge that SOFTWARE is subject to U.S. and European Union export jurisdiction. You agree to comply with all applicable international and national laws that apply to the SOFTWARE, including the U.S. Export Administration Regulations, as well as end-user, end-use and destination restrictions issued by U.S. and other governments. For additional information see <http://www.microsoft.com/exporting/>.

Contents

Certification Information viii

1 Introducing the FTB-1 1

 Main Features 1

 LED Indicators Description 5

 Keypad Description 6

 Power Sources 8

 Optional Software Package 8

 Conventions 9

2 Safety Information 11

 Other Safety Symbols on Your Unit 12

 Laser Safety Information 13

 Electrical Safety Information 14

3 Getting Started with Your Unit 19

 Inserting and Removing Test Modules 19

 Using the Supports 23

 Securing Your Unit Using a Kensington Lock 24

 Using a Keyboard, Mouse or Other USB Devices 25

 Using the On-Screen (Virtual) Keyboard 28

 Right-Clicking with the Touchscreen 28

 Turning On or Off the Unit 29

 Installing or Upgrading the Applications 33

 Installing Third-Party Applications 38

 Configuring Your Unit to Work with the

 Write Filter Manager 40

 Activating Software Options 42

 Starting Module Applications 47

Contents

4	Setting Up Your Unit	49
	Adjusting Brightness	49
	Adjusting Microphone and Speaker Volume	50
	Recalibrating the Touchscreen	54
	Enabling or Disabling the Touchscreen Right-Click Feature	57
	Customizing the On-Screen Keyboard	60
	Enabling or Disabling the Automatic Logon	62
	Selecting the Startup Application	65
	Selecting the FIP Startup Application	67
	Configuring Network Printers	69
	Selecting the Language of Operation	72
	Setting Date and Time Formats	77
	Adjusting the Date, Time and Time Zone	80
	Configuring the Power Management Options	83
	Configuring the Internet Options	87
	Setting Other Parameters	87
5	Working with Your Unit	89
	Printing Documents	89
	Viewing PDF Files	92
	Taking Screen Captures	93
	Setting Storage Parameters for Screen Captures	96
	Reading Audio and Video Files	100
	Installing Adobe Flash Player on Your Unit	102
	Browsing the Web	104
	Accessing the Internet with a 3G USB Modem Key	106
	Retrieving the GPS Location of Your Unit	112
	Using the Calculator	116
	Using the Text Editor	116
	Accessing Other Tools	116
6	Using the Optional Built-In Power Meter and VFL	117
7	Inspecting Fibers with a Probe	119
8	Managing Data	121
	Transferring Data via Bluetooth	124
	Connecting to a Wireless Network	131
	Using the USB to RS-232 Adapter	136
	Enabling or Disabling the Bluetooth and Wi-Fi Devices	141
	Transferring Files with the USB Data Mover Application	143
	Connecting to a VPN from Your Unit	149

9 Accessing Your Unit Remotely	157
Working with Remote Desktop	158
Working With TightVNC	164
Configuring TightVNC Server to Start Automatically	171
Adding Exceptions to the Firewall	173
10 Testing Network Connections	175
Performing a Ping Test	175
Performing a Trace Route Test	178
Exporting the Results	180
11 Maintenance	181
Cleaning Detector Ports	182
Cleaning the Touchscreen of Your FTB-1 Unit	183
Recharging the Main Battery	183
Recalibrating the Battery	185
Replacing Batteries	188
Recalibrating the Unit	192
Recycling and Disposal (Applies to European Union Only)	193
12 Troubleshooting	195
Solving Common Problems	195
Restoring Your Unit to Normal Operation	201
Contacting the Technical Support Group	210
Transportation	210
13 Warranty	211
General Information	211
Liability	212
Exclusions	213
Certification	213
Service and Repairs	214
EXFO Service Centers Worldwide	215
A Technical Specifications	217
Index	219

Certification Information

North America Regulatory Statement

This unit was certified by an agency approved in both Canada and the United States of America. It has been evaluated according to applicable North American approved standards for product safety for use in Canada and the United States.

Electronic test and measurement equipment is exempt from FCC part 15, subpart B compliance in the United States of America and from ICES-003 compliance in Canada. However, EXFO Inc. makes reasonable efforts to ensure compliance to the applicable standards.

The limits set by these standards are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the user guide, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

If you purchased the Wi-Fi and Bluetooth option, your unit comes with an internal wireless module and antenna for which the following information applies:

- This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
- FCC Radiation Exposure Statement: This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

CSA Information

This unit is certified by the CSA (certificate number 162451) and was evaluated according to applicable CSA standards (as confirmed by cCSAus mark) as well as applicable IEC standards for use in Canada, the United States, and other countries.

European Community Declaration of Conformity

An electronic version of the declaration of conformity for your product is available on our website at www.exfo.com. Refer to the product's page on the Web site for details.

1 **Introducing the FTB-1**

The FTB-1 platform is a modular platform, optimized for network infrastructure construction and troubleshooting via its dedicated FTTH and Ethernet test applications.

Note: *In this documentation, the words “tap” and “double-tap” (related to the use of a touchscreen) replace the words “click” and “double-click”.*

Main Features

Your FTB-1 platform includes the following:


- Multitasking possibilities
- Seven-inch color touchscreen (LCD and touchscreen optimized for outdoor use available as an option)
- Optional built-in power meter and VFL
- Optional internal Wi-Fi and Bluetooth devices
- Two USB 2.0 ports (host)
- Ethernet port (10/100/1000 Base-T)
- Headset/microphone port (for any commercially available headset equipped with a microphone, and having a 2.5 mm connector)
- Fiber inspection probe port
- Optional GPS USB key
- Optional 3G USB modem key

Introducing the FTB-1


Main Features

- Windows Embedded Standard operating system
- VPN capability
- Remote access to your unit (via TightVNC or Remote Desktop)
- Direct Web access from your unit
- Possibility to take screen captures
- PDF file generator and viewer available from your unit
- Easy transfer of files and folders to a USB storage device
- Easy updates for applications via Update Manager

Front




Top



Introducing the FTB-1



Main Features

Back



LED Indicators Description

There are two LED indicators located on the front panel of your unit, providing you with information about the power and battery statuses.

LED	Status	Meaning
	Green	Unit is on.
	Green, blinking	Unit is in Standby mode.
	Off	Unit is off or in Hibernation mode.
	Green	Battery is fully charged.
	Green, blinking	Battery is charging.
	Yellow, blinking	Unit is not powered by AC and battery is low.
	Red	No battery in the unit or battery error.
	Off	Unit is off or unit is not powered by AC and battery level is above the “low-battery threshold”.






Keypad Description





In addition to the on-screen keyboard, your unit is equipped with a keypad which gives you access to various tools at all times.

The keypad comprises arrow keys for navigation (left, right, up, down), alphanumeric keys (similar to phone keys to enter both numbers and text), and other hardware buttons.

Note: *Not all applications support text entry with the alphanumeric keys.*

The table below shows an overview of their purpose.

Button	Meaning
	Adjusts screen brightness (5 levels).
	<ul style="list-style-type: none">➤ Displays the on-screen keyboard➤ Takes a screen capture (button held down for a few seconds)
	Enables you to switch from one task to another.
	Turns your unit on and off. For more information on the various ways to turn off your unit, see <i>Turning On or Off the Unit</i> on page 29.
	Starts/stops a test.

Button	Meaning
	Moves to the next group of features.
	Confirms last entry; equivalent of the ENTER button.
	Deletes the item/character.
	Exits or cancels last entry.

Power Sources

Your unit operates with the following power sources:

- AC adapter/charger (connected to standard power outlet—indoor use only). Compatible car outlet adapter available upon request.
- One lithium-ion rechargeable battery (automatically takes over if you disconnect the AC adapter/charger).

Note: *When it is connected with the AC adapter/charger, the unit will function even if the battery is not present.*

- Possible to switch from AC adapter/charger to battery power or vice versa without affecting operation.
- The battery recharges automatically when the AC adapter/charger is connected.
- The battery is offered in two formats: four-cell (small) and eight-cell (large).
- Rechargeable battery (for clock). This battery can keep the date and time for weeks even if AC power and the lithium-ion battery (main battery) are not connected.

Optional Software Package

An optional software package (IPT package) is offered with the application. With this package, you can perform *ping* and *trace route* tests. For more information on how to activate software options, see *Activating Software Options* on page 42.

Conventions

Before using the product described in this guide, you should understand the following conventions:



WARNING

Indicates a potentially hazardous situation which, if not avoided, could result in *death or serious injury*. Do not proceed unless you understand and meet the required conditions.



CAUTION

Indicates a potentially hazardous situation which, if not avoided, may result in *minor or moderate injury*. Do not proceed unless you understand and meet the required conditions.



CAUTION

Indicates a potentially hazardous situation which, if not avoided, may result in *component damage*. Do not proceed unless you understand and meet the required conditions.



IMPORTANT

Refers to information about this product you should not overlook.

2 ***Safety Information***



WARNING

Do not install or terminate fibers while a light source is active. Never look directly into a live fiber and ensure that your eyes are protected at all times.




WARNING

The use of controls, adjustments and procedures, namely for operation and maintenance, other than those specified herein may result in hazardous radiation exposure or impair the protection provided by this unit.



IMPORTANT

When you see the following symbol on your unit , make sure that you refer to the instructions provided in your user documentation. Ensure that you understand and meet the required conditions before using your product.



IMPORTANT









Other safety instructions relevant for your product are located throughout this documentation, depending on the action to perform. Make sure to read them carefully when they apply to your situation.

Safety Information

Other Safety Symbols on Your Unit

Other Safety Symbols on Your Unit

One or more of the following symbols may also appear on your unit.

Symbol	Meaning
	Direct current
	Alternating current
	Both direct and alternating current
	The unit is equipped with an earth (ground) terminal.
	The unit is equipped with a protective conductor terminal.
	The unit is equipped with a frame or chassis terminal.
	On (Power)
	Off (Power)

Laser Safety Information

Units with Built-In VFL

Your instrument is a Class 3R laser product in compliance with standards IEC 60825-1: 2007 and 21 CFR 1040.10, except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007. Laser radiation is emitted at the output port. It is potentially harmful in direct intrabeam viewing.

The following label(s) indicate that the product contains a Class 3R source:



Affixed to bottom panel of unit.

The VFL laser is active when the  symbol is displayed in the power meter and VFL application.

Units without Built-In VFL

If your unit is not equipped with a VFL, the laser class of your unit depends on the modules that you use. Refer to the user guide or the online help of the different modules for the exact information.

Electrical Safety Information

If you need to ensure that the unit is completely turned off, disconnect the power cable and remove the battery.



WARNING

- Use the external power supply indoors only.
- Position the unit so that the air can circulate freely around it.
- Operation of any electrical instrument around flammable gases or fumes constitutes a major safety hazard.
- To avoid electrical shock, do not operate the unit if any part of the outer surface (covers, panels, etc.) is damaged.
- Only authorized personnel should carry out adjustments, maintenance or repair of opened units under voltage. A person qualified in first aid must also be present. Do not replace any components while power cable and battery are connected.
- Unless otherwise specified, all interfaces are intended for connection to Safety Extra Low Voltage (SELV) circuits only.
- Capacitors inside the unit may be charged even if the unit has been disconnected from its electrical supply.



WARNING

- Use only the listed and certified AC adapter/charger provided by EXFO with your unit. It provides reinforced insulation between primary and secondary, and is suitably rated for the country where the unit is sold.
- Use only accessories (such as the car outlet adapter, batteries, and fiber inspection probe) designed for your unit and approved by EXFO. For a complete list of accessories available for your unit, refer to its technical specifications.
- When you use the unit outdoors, ensure that it is protected from liquids, dust, direct sunlight, precipitation, and full wind pressure.

Safety Information

Electrical Safety Information

Equipment Ratings	
Temperature	
➤ Operation	➤ unit powered by battery: 0 °C to 50 °C (32 °F to 122 °F) ➤ unit connected to AC adapter: 5 °C to 40 °C (41 °F to 104 °F)
➤ Storage	➤ unit without battery: -40 °C to 70 °C (-40 °F to 158 °F) ➤ unit with battery: -20 °C to 60 °C (-4 °F to 140 °F) ➤ AC adapter: -20 °C to 60 °C (-4 °F to 140 °F)
Relative humidity ^a	➤ unit: ≤ 95 % non-condensing ➤ AC adapter: 10 % to 80 % non-condensing
Maximum operation altitude	➤ 2000 m (6562 ft) (unit connected to external power supply) ➤ 5000 m (16405 ft) (unit operated from battery)
Pollution degree	➤ 2 (unit connected to external power supply) ➤ 3 (unit operated from battery) ^b
Overvoltage category	➤ unit: I ➤ AC adapter: II
Measurement category	Not rated for measurement categories II, III, or IV
Input power ^c	➤ unit: --- 24 V; 3.75 A ➤ AC adapter: ~ 100 - 240 V; 50/60 Hz; 1.6 A

- a. Measured in 0 °C to 31 °C (32 °F to 87.8 °F) range, decreasing linearly to 50 % at 40 °C (104 °F).
b. Equipment must be normally protected against exposure to direct sunlight, precipitation and full wind pressure.
c. Not exceeding ± 10 % of the nominal voltage.



IMPORTANT

The operation and storage temperatures of some modules may differ from the temperatures specified for your platform. In this case, always ensure that you comply with the most restrictive conditions (either module or platform).

3 **Getting Started with Your Unit**

Inserting and Removing Test Modules



CAUTION

Never insert or remove a module while the FTB-1 is turned on. This will result in immediate and irreparable damage to both the module and unit.




CAUTION

To avoid damaging your unit, use it only with modules approved by EXFO.

To insert a module into the FTB-1:

1. Turn off your unit (Shutdown).
2. Position the unit so that its front panel rests on a flat surface such as a table.
3. Place the module on the platform making sure that the bumpers and the shorter sides of the module are flush with those of the platform. If necessary, slightly move the module until alignment is correct.




Getting Started with Your Unit

Inserting and Removing Test Modules

4. Using a flat screwdriver, turn the screws (4) clockwise until they are tightened.


This will secure the module into its “seated” position.



When you turn on the unit, the startup sequence will automatically detect the module.

To remove a module from the FTB-1:


- 1.** Turn off your unit (Shutdown).
- 2.** Position the unit so that its front panel rests on a flat surface such as a table.
- 3.** Using a flat screwdriver, turn the screws (4) counterclockwise until they are loose. Since they are captive screws, you cannot remove them completely.



Getting Started with Your Unit

Inserting and Removing Test Modules

4. Hold the module by its sides (*NOT by the connectors*) and pull it up.



CAUTION

Pulling a module by its connectors could seriously damage both the module and connector. Always pull a module by its casing.

Using the Supports


Your unit has been designed to stand either vertically (with the screen facing you), or at an angle, using the two supports.

All the modules that you can use with your unit are equipped with two supports with which you can change the orientation of your unit. Once the module is inserted in your FTB-1, you can use the supports.

Note: *The supports ensure optimum stability to the unit during your tests.*

To change the orientation of the unit using the supports:

Pull out the two supports.



Getting Started with Your Unit


Securing Your Unit Using a Kensington Lock

Securing Your Unit Using a Kensington Lock

All the modules that you can use with your unit are equipped with a security slot to which you can connect an optional Kensington lock (security cable). Once the module is inserted in your FTB-1, you can secure your unit with this lock to help prevent theft.

To secure your unit:

Connect your lock to the security slot located on the side of your module.



Using a Keyboard, Mouse or Other USB Devices

Your unit supports many USB devices. The table below lists the supported USB devices.

Device	Details
Memory key	For data transfer between your unit and a computer when you do not have access to a network. If you need information on how to transfer data using a memory key, see <i>Managing Data</i> on page 121.
Keyboard	When you are required to enter alphanumeric data, an on-screen (virtual) keyboard is displayed. However, if you prefer, you can use a hardware keyboard. Note: <i>Even if a keyboard is connected, the on-screen keyboard will still be displayed when you work in Mini Toolbox.</i>
Mouse	If you prefer to use a mouse instead of the touchscreen, you can connect one.
Composite device	You can use composite devices, that is devices that input information to your unit using more than one mean (for example, combinations of keyboard and mouse).
Hub	This device will be particularly useful to you if you need extra USB ports.
USB to RS-232 adapter (purchased from EXFO)	To be able to transfer data between your unit and a device only equipped with RS-232 (serial) ports. For more information, see <i>Using the USB to RS-232 Adapter</i> on page 136.

Getting Started with Your Unit

Using a Keyboard, Mouse or Other USB Devices

Device	Details
GPS USB key (purchased from EXFO)	To be able to know the position of your unit (latitude and longitude coordinates). For more information, see <i>Retrieving the GPS Location of Your Unit</i> on page 112.
3G USB modem key (purchased from EXFO)	To access the Internet without having to connect to a Wi-Fi or an Ethernet network. For more information, see <i>Accessing the Internet with a 3G USB Modem Key</i> on page 106.

You can connect several devices at the same time.



IMPORTANT


Your unit does not support USB printers. If you want to print documents, you must use PDFCreator or a network printer (see *Printing Documents* on page 89), or transfer your files to a computer (see *Managing Data* on page 121) that has access to a network printer.

Getting Started with Your Unit

Using a Keyboard, Mouse or Other USB Devices

To use a USB device with your unit:

Connect the USB device to any of the USB ports (located on top of the unit).




Note: *It is not necessary to turn off the unit before connecting the USB device. The software will automatically detect its presence.*

Your device is automatically recognized and immediately usable (provided that it uses the drivers already available on your unit).

Using the On-Screen (Virtual) Keyboard

Your unit is equipped with an on-screen keyboard that supports multilingual features. This keyboard functions according to the keyboard settings of Windows.

To use the on-screen keyboard:

1. From the unit's keypad, press the  button.
2. Select the location where you want to enter text.
3. Enter the data as required.
4. Exit the location when you have finished entering data.

Right-Clicking with the Touchscreen

If you are used to work with a mouse, you may find it useful to be able to perform a right-click on your touchscreen.

To right-click with the touchscreen:

From the location where you want to right-click, using the stylus or any blunt pointing device, press the screen for a few seconds until the shortcut menu appears.

If you want to hide the shortcut menu without performing any action, simply tap anywhere outside the menu.

Turning On or Off the Unit

There are several ways to turn off the unit, including the following:

- *Standby*: keeps the unit's status information in memory (RAM). The next time you turn your unit on, you will quickly return to your work environment (running applications will still be running). This mode will take more battery power while the unit is off.
- *Hibernation*: saves the unit's status information that was in memory (RAM) to a special file on the disk. The next time you turn your unit on, this file will be used to ensure that you return to your work environment (running applications will still be running). The unit will take longer to start up than in *Standby* mode, but it requires less battery power when the unit is off. You can configure your unit to switch automatically from *Standby* to *Hibernation* mode after the specified delay.
- *Shutdown*: completely cuts power to the test modules and platform; the unit will perform a complete restart routine the next time you use it. You should perform a shutdown if you do not intend to use your unit for a week or more.

After a shutdown, the unit will start in Mini Toolbox or in the application you defined as the startup application.

Note: *Should the unit ever stop responding, you can force a hardware reset by pressing and holding down the power button for more than 10 seconds.*

By default, your unit will display the standard shutdown window from which you can select the desired shutdown mode. However, you can configure your unit to perform a different action when the power button is pressed.

You can also configure your unit to automatically restart when AC power comes back after the unit has turned off (emergency shutdown, standby, or hibernation modes) when battery level is too low.

Getting Started with Your Unit

Turning On or Off the Unit

To turn on the unit:

Press the On/Off button.

To turn off the unit:

1. Press the On/Off button.

OR


On the Windows taskbar, tap **Start**.

This will display the standard shutdown window, from which you have a choice of actions or shutdown modes.


2. Select **Shutdown**.

To define the behavior of the power button:


1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Power Options**.



3. Select the **Advanced** tab.



4. From the **When I press the power button on my computer** list, select the desired behavior (**Ask me what to do** option is selected by default).




5. Tap **Apply** to confirm the changes, and then **OK** to return to **Control Panel**.

Getting Started with Your Unit

Turning On or Off the Unit

To configure your unit to automatically restart after AC power comes back:


1. From the **Main Menu**, tap **System Settings**.
2. From the **System Settings** window, tap **Startup Applications**.



3. Select the **Power on the unit when AC outlet is connected or after power outage** box to enable the corresponding option.

OR

Clear the box if you prefer that your unit does not restart automatically after AC power comes back.



4. Tap  to confirm the changes and return to the main window.

Installing or Upgrading the Applications

All the necessary applications have been preinstalled and configured at the factory. However, you may have to upgrade some applications when new versions become available or to reinstall them.

Note: *Only administrator-level users can install software under Windows Embedded Standard.*

From the DVD that came with your unit, you can create an installation USB key in case you ever need to reinstall Mini ToolBox (the software that comes with your platform) and the module applications as well as Update Manager. All the necessary files will be copied to the USB key.

Each time you purchase a new module, you will also receive a DVD with which you could create a new installation USB key. It could be a good idea to verify that the most recent Update Manager application is installed on your unit.

When updates are available for an application, you will need to download them from Internet, either directly on your unit or on a computer. In the latter case, you will need to transfer the update files to your unit (see *Managing Data* on page 121). The update files must be copied to the location that has been specified for the deployment packages in Update Manager.

Getting Started with Your Unit

Installing or Upgrading the Applications



IMPORTANT

If you ever need to reinstall Update Manager on your unit, ensure that:

- The installation files for Update Manager remain on your unit. Otherwise, it will not be possible to install new versions of this application later.
- You choose the folder containing the Update Manager installation files carefully. If you move or rename this folder, you will have to manually browse for the modified folder when you want to install new versions of this application.

For the creation of an installation USB key, you will need:

- the installation DVD
- a computer equipped with a USB port; Windows must be installed on the computer
- a USB memory key

For the upgrades, you will need:

- an FTB-1 unit
- a computer equipped with a USB port; Windows must be installed on the computer
- a USB memory key

Note: *For the upgrades, the computer and USB key are only necessary if you do not wish to download the files directly on your unit.*

Note: *For more information on the installation, refer to the Update Manager online help.*

To update or reinstall Update Manager:

- 1.** If necessary, retrieve the desired installation files from the Internet.

If you do not intend to download files directly on your unit, connect a USB memory key to one of the USB ports of the computer and copy the installation files to this USB key.
- 2.** If it is not already done, turn on your unit.
- 3.** Exit Mini Toolbox and the modules' applications.
- 4.** If you want to install Update Manager using the USB key, disconnect it from the computer and connect it to one of the USB ports of your unit.
- 5.** On your unit, create a folder on the Windows desktop.
- 6.** Copy the installation files (from the USB key) to the newly created folder.
- 7.** From the newly created folder, tap the *Setup.exe* file to start the installation.
- 8.** Follow the on-screen instructions.
- 9.** When the installation is complete, simply disconnect the USB memory key.

Getting Started with Your Unit

Installing or Upgrading the Applications

To install or upgrade the applications:

- 1.** If necessary, retrieve the desired installation files from the Internet.

If you do not intend to download files directly on your unit, connect a USB memory key to one of the USB ports of the computer and copy the installation files to this USB key.
- 2.** If it is not already done, turn on your unit. If necessary, exit the modules' applications.
- 3.** If you want to install or update applications using the USB key, disconnect it from the computer and connect it to one of the USB ports of your unit.
- 4.** Copy the installation files (from the USB key) to the folder containing the update and installation packages on your unit. By default, Update Manager will search for files at the root of the USB key. For more information, refer to the Update Manager online help.
- 5.** From Mini ToolBox, on your unit, select the **Utilities** tab.
- 6.** Tap **Update Manager** to start the corresponding application. For more information on how to install or upgrade applications, refer to the Update Manager online help.
- 7.** When installation is complete, simply disconnect the USB memory key.

To create an installation USB key:

- 1.** Turn on the computer and insert the installation DVD in the CD/DVD drive.
- 2.** Connect a USB memory key to one of the USB ports of the computer.
- 3.** From the **Welcome** window on the installation DVD, click **Mini Toolbox and Tools**.
- 4.** Select the **Mini Toolbox** check box and click **Next**.
- 5.** Follow the on-screen instructions. All the necessary components will be copied to your USB key.
- 6.** When the operation is complete, click **Close**, and then **Exit** to close the installation DVD window.
- 7.** Disconnect the USB memory key from the computer.

Your new installation USB key is now ready.

Installing Third-Party Applications

Note: *Only administrator-level users can install software under Windows Embedded Standard.*

By default, your unit is locked to prevent the installation of unwanted applications and components. However, in some cases, you may need to install third-party applications such as those allowing you to connect to the 3G/4G network of your Internet services provider.

The Write Filter Manager enables you to unlock your unit to let you install third-party applications. The lock status of your unit (locked or unlocked) is displayed in the main window of the Write Filter Manager.

Note: *If you intend to work with the standard Sierra Wireless 319U USB key, you do not need to use the Write Filter Manager. For more information on the configuration and use of this USB key, see Accessing the Internet with a 3G USB Modem Key on page 106.*



CAUTION

- Installing applications that have not been previously approved by EXFO may prevent your unit from working properly.
- To preserve the integrity and stability of your unit, do not forget to lock it once the installation of the third-party application is complete.



CAUTION

DO NOT CONNECT any new 3G USB modem key to the unit before the unit has been unlocked with the Write Filter Manager.

To install third-party applications on your unit:

1. Unlock your unit:

- 1a.** On the Windows taskbar, tap **Start**, then select **All Programs > EXFO > Write Filter Manager > Write Filter Manager** to start the application.

Note: *If you do not see the Write Filter Manager application, see Configuring Your Unit to Work with the Write Filter Manager on page 40.*

- 1b.** Tap the **Unlock** button. The button label switches to “Lock”.

- 1c.** When the application prompts you to restart the unit, select **Yes**.

Wait for the startup sequence to complete.

2. Install your third-party application by following the instructions provided with it.

3. Lock your unit:

- 3a.** On the Windows taskbar, tap **Start**, then select **All Programs > EXFO > Write Filter Manager > Write Filter Manager** to start the application.

- 3b.** Tap the **Lock** button. The button label switches to “Unlock”.

- 3c.** When the application prompts you to restart the unit, select **Yes**.

Wait for the startup sequence to complete.

You are now ready to work with your third-party application.

Configuring Your Unit to Work with the Write Filter Manager

Note: *Only administrator-level users can install software under Windows Embedded Standard.*

By default, your unit is locked to prevent the installation of unwanted applications and components. To install applications that are not part of the standard EXFO products, you will need to unlock your unit first, using the Write Filter Manager application.



IMPORTANT

If you want to work with the Write Filter Manager, but the application is not present on your unit, you must install the most recent Platform kit first.

To do this, you will need a standard USB memory key and a computer with an Internet access. You can also retrieve the kit directly from your unit, but you will need an Internet access (other than the one that would be provided by the new 3G USB modem key).



CAUTION

Installing applications that have not been previously approved by EXFO may prevent your unit from working properly.



CAUTION

DO NOT CONNECT any new 3G USB modem key to the unit before the configuration is complete and the unit has been unlocked with the Write Filter Manager.

To configure your unit to work with the Write Filter Manager:

- 1.** If necessary, turn on your unit.
- 2.** Install the latest Platform kit:
 - 2a.** From your computer or your unit, open a Web browser and go to www.exfo.com.
 - 2b.** Log on to your My EXFO account.
 - 2c.** Under FTB-1, find the Platform kit. If you need information on how to download the kit, refer to the Readme file provided with the kit.
 - 2d.** Install the Platform kit on your unit. For more information, refer to the Readme file provided with the kit.

Note: *At this point, if you have used a USB memory key to transfer the installation files to your unit, you can remove it.*

You are now ready to work with the Write Filter Manager.

Activating Software Options

The software options purchased at the same time as your unit have been activated for you already. However, if you purchase options afterwards, you will have to activate them yourself.


Before being able to activate options, you need to contact EXFO with the following information:

- Purchase order number of the newly purchased options
- Module or platform serial number (depending on whether the software options were purchased for a module or the platform)
- Customer's name
- Customer's company name
- Customer's phone number
- Customer's e-mail address
- Module or platform on which the option will be installed

You will receive a single key (.key) file with which you will be able to unlock all the new options that you have purchased.

To activate the options for your unit:


- 1.** Connect a USB memory key to one of the USB ports of your computer.
- 2.** Copy the key file to the USB memory key.
- 3.** Disconnect the USB key from the computer and connect it to your unit.
- 4.** From Mini ToolBox, select the **Utilities** tab, then tap **Options Activation**.



Getting Started with Your Unit

Activating Software Options

5. In the **Platform Options** tab, use the **Browse** button to locate the key file that you want to use.



6. Press **Activate**.


The option indicator will turn into a green check mark to confirm that the option is now active.

7. Press **OK** to close the **Option Activation** window.

Note: *At this point, if you have used a USB key to copy your key file, you can remove it as it is not required to use your new options.*

To activate software options for your module:


- 1.** Connect a USB memory key to one of the USB ports of your computer.
- 2.** Copy the key file to the USB memory key.
- 3.** Disconnect the USB key from the computer and connect it to your unit.
- 4.** From Mini ToolBox, select the **Utilities** tab, then tap **Options Activation**.



Getting Started with Your Unit

Activating Software Options

5. In the **Module Options** tab, use the **Browse** button to locate the key file that you want to use.



6. Press **Activate**.

The option indicator will turn into a green check mark to confirm that the option is now active.

Note: You can see the supported options for the module in the **Options** list.

7. Press **OK** to close the **Option Activation** window.


Note: At this point, if you have used a USB key to copy your key file, you can remove it as it is not required to use your new options.

Starting Module Applications

Your modules can be configured and controlled from their dedicated applications in Mini Toolbox.

To start a module application:

From Mini Toolbox, at the bottom of the window, press the button corresponding to the desired application.



To start the Power Meter or Probe application:

From Main Menu, press Power Meter or Probe.


4 Setting Up Your Unit

Adjusting Brightness

To fit your work environment, you may adjust the LCD brightness. Values are kept in memory even when you turn the unit off.


Note: These settings do not apply to a fiber inspection probe display.

To adjust the display brightness:


Press the  key repeatedly to switch between brightness levels.


OR

1. From the **Main Menu**, tap **System Settings**.
2. If necessary, from **System Settings**, tap **Display & Sound**.



3. Move the slider until the screen appearance is to your liking.



4. Tap  to return to the Mini Toolbox window.

Setting Up Your Unit


Adjusting Microphone and Speaker Volume

Adjusting Microphone and Speaker Volume


To fit your work environment, you may adjust the microphone and speaker volume. Values are kept in memory even when you turn the unit off.

To adjust the microphone volume:

1. From the **Main Menu**, tap **System Settings**.
2. If necessary, from **System Settings**, tap **Display & Sound**.




3. Under **Volume**, tap the **Sound Options** button.




4. Select the **Voice** tab.

5. Under Voice recording, tap Volume.




6. Ensure that the microphone boost option is selected:

6a. From the Options menu, select Advanced Controls.



6b. Tap the Advanced button.



Setting Up Your Unit

Adjusting Microphone and Speaker Volume


- 6c.** Under **Other Controls**, select the **1 Microphone Boost** check box.




- 6d.** Tap **Close**.

Note: Normally, you only have to select this option the first time that you adjust the microphone volume (the option will be selected for all other users as well). Once it is done, you can control the volume with the slider as explained at the next step.


- 7.** Under **Microphone**, use the slider to adjust the sound of your microphone. Close the window when your settings are complete.




- 8.** Tap **OK** to return to the **Display & Sound** window.
- 9.** Tap  to return to the Mini Toolbox window.

To adjust the speaker volume:

1. From the **Main Menu**, tap **System Settings**.
2. If necessary, from **System Settings**, tap **Display & Sound**.




3. Under **Volume**, use the slider to adjust the sound of your speaker.



Note: You can also select the **Mute** check box if you want to quickly turn off the sound.

Note: You can tap the **Audio Mixer** button if you want to refine the volume according to the source of the sound (**Master Volume** and **Wave** controls).

4. Tap  to return to the Mini Toolbox window.

Recalibrating the Touchscreen


If you notice the touchscreen does not behave in the way it used to (for example, it is now difficult to select items) it probably needs a recalibration.

The default calibration method is performed using nine points, but you can also perform a 4-point, or even a 25-point calibration (linearization) if you need more accuracy.


You can stop the calibration process at any time, but the touchscreen will still need calibration. The parameters are taken into account only when the process is complete.

To recalibrate the touchscreen:


1. From the **Main Menu**, tap **System Settings**.
2. If necessary, from **System Settings**, tap **Display & Sound**.



3. From the **Calibration points** list, select the desired number of points for the calibration.




4. Tap **Calibrate**.




Setting Up Your Unit


Recalibrating the Touchscreen

5. Using the stylus (or any blunt pointing device), simply press the center of the different targets that appear on the screen. Keep pressing until the application displays **OK** to indicate that the new parameters have been taken into account.



Note: If you want to stop the calibration process, press  from the unit's keypad. The application will close automatically and you will return to the **Display & Sound** window.

When the calibration is complete, you will return to the **Display & Sound** window automatically.


6. Tap  to return to the Mini Toolbox window.

Enabling or Disabling the Touchscreen Right-Click Feature


By default, you can right-click with your touchscreen (see *Right-Clicking with the Touchscreen* on page 28). However, you can disable this feature if you prefer.

To enable or disable the right-click of the touchscreen:

1. From the **Main Menu**, tap **System Settings**.
2. If necessary, from System Settings, tap **Display & Sound**.




3. Under **Touchscreen**, tap the **Touchscreen Options** button.




Setting Up Your Unit

Enabling or Disabling the Touchscreen Right-Click Feature

4. Select the **Setting** tab.




5. Tap the **Option** button.




6. From the **Option** tab, select the **Enable Auto Right Click** check box to enable the option.

OR

Clear the check box if you prefer to disable the right-click.



7. Tap **OK** to confirm the changes.
8. Tap **OK** once again to close the touchscreen parameters window.
9. Tap  to return to the Mini Toolbox window.

Setting Up Your Unit

Customizing the On-Screen Keyboard


Customizing the On-Screen Keyboard

You can customize the appearance and behavior of the on-screen keyboard. For more information on the various parameters that you can set, refer to the on-screen keyboard online help.


For information on how switch from one of the available languages to another, see *Selecting the Language of Operation* on page 72.

To customize the appearance and behavior of the on-screen keyboard:


1. From the **Main Menu**, tap **System Settings**.
2. If necessary, from **System Settings**, tap **Display & Sound**.




3. Under **On-screen keyboard**, tap the **On-Screen Keyboard Options** button.



4. Configure the keyboard according to your needs.



Note: You can access the online help related to the keyboard options by tapping the **Help** button.

5. When you have finished, tap **Close**.
6. Tap  to return to the Mini Toolbox window.

Setting Up Your Unit

Enabling or Disabling the Automatic Logon

Enabling or Disabling the Automatic Logon

Note: Only administrator-level users can enable or disable the automatic logon feature.

You can configure your unit to automatically log on to Windows at startup (no need to select a user and enter a password). You can also disable this feature if you prefer to define separate user accounts with different user access rights and passwords.


Note: For security reasons, when the unit comes back from standby or hibernate modes, the application will prompt you to select a user and enter a password, even if you have enabled the automatic logon feature.

By default, the automatic logon is enabled for the *Supervisor* user account, with an empty password. If you want to create (or modify) a password for the user account for which the automatic logon is enabled, you will have to disable the feature first, and then enable it again once the new password is defined.


If you want to modify the account used for the automatic logon, you will also have to disable the feature first, and then enable it again for the new account.

To enable (or modify) the automatic logon:

1. From the **Main Menu**, tap **System Settings**.
2. From **System Settings**, tap **Automatic Logon**.




3. Enter the desired user name (account) and the corresponding password.



IMPORTANT

You cannot create user accounts or modify passwords from the Automatic Logon window.

The user name and password that you specify must correspond to those of an account that has been defined from User Accounts in Control Panel.

4. Tap **Enable Auto Logon**.
5. Tap  to return to the Mini Toolbox window.


At next startup, you will no longer need to specify a user name and password (except if the unit comes back from standby or hibernate modes).

Setting Up Your Unit


Enabling or Disabling the Automatic Logon


To disable the automatic logon:

1. From the **Main Menu**, tap **System Settings**.
2. From **System Settings**, tap **Automatic Logon**.



3. Tap **Disable Auto Logon**.



4. When the application prompts you, confirm with **Yes**.
 5. Tap  to return to the Mini Toolbox window.
- At next startup, you will have to specify the user name and password.

Selecting the Startup Application

The first time you start your unit, Mini Toolbox is displayed. However, you can configure your unit to automatically start in any of the available applications.


The selected application or applications will start automatically the next time you turn on your unit after a shutdown (not in standby or hibernate mode). For more information, see *Turning On or Off the Unit* on page 29.

If you want to configure your unit to start the TightVNC server automatically at startup (for remote control), see *Working With TightVNC* on page 164.

If the specified application cannot be started (for example, the required module is not present in the unit), Mini Toolbox is started automatically. You will have to select the application again when the module is inserted into the unit.

To select a startup application:


- 1.** From the **Main Menu**, tap **System Settings**.
- 2.** From **System Settings**, tap **Startup Applications**.



Setting Up Your Unit

Selecting the Startup Application


- Under **Module application** or **Utility applications**, select the application or applications you want to start automatically when you turn on your unit.



Note: You can select several utility applications, but only one module application at a time.

Note: If necessary, you can use the scrolling arrows located at the right of the **Module application** and **Utility applications** lists to browse through the available items.

Your changes are automatically saved.


- Tap  to return to the Mini Toolbox window.

Selecting the FIP Startup Application

Your unit supports both the fiber inspection probes (FIP) of the FIP-400 and FIP-400B series. By default, the unit prompts you to select the application corresponding to the FIP with which you want to work (FIP-400 or FIP-400B). If you prefer, you can configure the unit to always start your favorite application directly instead.

To select the FIP startup application:

- 1.** From the **Main Menu**, tap **System Settings**.
- 2.** From **System Settings**, tap **Startup Applications**.




Setting Up Your Unit


Selecting the FIP Startup Application

3. From the **When I tap the Probe button** list, select the desired behavior. If you want to be prompted each time to confirm the application to use, select the **Ask me what to do** option.

Note: If the list is not available, it means that the ConnectorMax2 application is not installed on your unit. In this case, the ConnectorMax application will start automatically, enabling you to work with the probes of the FIP-400 series. If you also wish to work with probes of the FIP-400B series, you will need to install the most recent ConnectorMax kit.



Your changes are automatically saved.

4. Tap  to return to the Mini Toolbox window.

Configuring Network Printers

To print documents and images on a network printer, you must configure the printer first. You must know the IP address of the network printer that you want to configure (contact your network administrator).




IMPORTANT

- Your unit does not support USB printers.
- Your unit only supports network printers compatible with PCL 6 (which is a "Printer Control Language"). If you are not sure whether a specific printer is compatible or not, contact your network administrator.

For more information on printing, see *Printing Documents* on page 89.

To configure the printer:


- 1.** On your unit, from the **Main Menu**, tap **Setup**.
- 2.** Double-tap **Printers and Faxes**.




Setting Up Your Unit

Configuring Network Printers


3. Select the **HP Universal Printing PCL 6** item.




4. From the menu, select **File > Printing Preferences**.
5. Under **Find a Printer**, select **Enter a Printer Address**.



6. Enter the IP address of the printer that you want to configure, and then tap **OK**.



- 7.** Select the **Add this printer to my Printers and Faxes** folder check box.



- 8.** Tap **OK** to confirm. The operation can take several minutes to complete.
- 9.** When the application prompts you, click **OK** to acknowledge the message.
- 10.** If desired, modify the printer preferences to your liking.
You can save the whole set of preferences for future use with the **Save As** button or press ✓ from the unit's keypad to save the parameters for the current work session.
- 11.** Close the **Printing Preferences** window, and then close the **Printers and Faxes** window to return to Mini Toolbox.

The printer is now ready to use.

Setting Up Your Unit

Selecting the Language of Operation

Selecting the Language of Operation

You may display the user interface in one of the available languages (default is English).

When you change the interface language, the corresponding keyboard is not automatically added to the list of available keyboards. You must add the desired keyboard separately if you want to enter text in a specific language (both on-screen or “real” keyboards). Once the keyboards are added, you can switch easily from one input language to another.



IMPORTANT

The keyboards that you add will not be available from the logon window.

To avoid problems, when you define or modify passwords, EXFO recommends that you always use the keyboard corresponding to the language of the unit at time of purchase. Otherwise, you might not be able to log on to your user account (unsupported characters, different keyboard layout, etc.)

Values are kept in memory even when you turn the unit off.



IMPORTANT


The language setting of the VLC media player is independent of the language setting of Mini Toolbox. You must configure both separately.

To select a new interface language:

1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Regional and Language Options**.



3. Select the **Languages** tab.



4. From the **Language used in menus and dialogs** list, select the desired language.
5. Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.


The new interface language will become available at the next startup.

Setting Up Your Unit


Selecting the Language of Operation

To add new input languages:


1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Regional and Language Options**.




3. Select the **Languages** tab.




4. Under **Text services and input languages**, tap **Details**.



5. Under **Installed services**, tap **Add**.



6. From the **Input language** list, select the desired language.





7. If necessary, from the **Keyboard layout/IME** list, select the desired option.
8. Tap **OK** to confirm.
9. Repeat steps 5 to 8 for all the languages that you want to add.
10. Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.

The added keyboards are available immediately. You can now switch from one input language to another.

Setting Up Your Unit

Selecting the Language of Operation

To switch from one of the available input languages to another:


1. From the unit's keypad, press the  button to display the on-screen keyboard.
2. From the on-screen keyboard, tap  to display the list of available input languages.
3. From the list of languages, select the desired one.

You are now ready to start entering text in the selected input language.

Note: *Modifying the input language does not modify the language of the interface.*

To modify the language of the VLC media player:

1. Close the Mini Toolbox window.
2. On the Windows taskbar, tap **Start**, then select **All Programs > VideoLAN > VLC media player**.
3. From the menu, select **Tools > Preferences**.



4. Under **Language**, select the desired language from the list.

By default, the language is set to **Auto**, to follow the *Standards and formats* setting of Windows, but you can select any other language.

5. Tap **Save** to confirm and close the application.

Note: *This operation has no impact on the date and time formats in Windows Embedded Standard and in the Mini Toolbox applications.*

Setting Date and Time Formats

The current date and time are displayed at the bottom of the **Main Menu**.


You can modify the format in which the date and time are displayed.

For information on how to adjust the date, the time, and the time zone, see *Adjusting the Date, Time and Time Zone* on page 80.

Note: *Modifying location, date and time settings will affect some of the Windows Embedded Standard settings.*

To set date and time formats:


- 1.** From the **Main Menu**, tap **Setup**.
- 2.** Double-tap **Regional and Language Options**.



Setting Up Your Unit

Setting Date and Time Formats


3. Select the **Regional Options** tab.




4. Under **Standards and formats**, select the desired language. This will determine the date formats available for the time as well as the short and long dates.

5. If necessary, refine the settings as follows:

5a. Tap **Customize** to display the detailed settings.



5b. Select either the **Time** or **Date** tab, depending on the settings that you want to modify.



6. Modify the settings.

7. Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.

Setting Up Your Unit

Adjusting the Date, Time and Time Zone

Adjusting the Date, Time and Time Zone

Note: Only administrator-level users can adjust the date, time and time zone.

The current date and time are displayed at the bottom of the main window. When saving results, the unit also saves the corresponding date and time.


Note: A dedicated clock battery keeps the date and time accurate.

For information on how to modify the format in which the date and time are displayed, see *Setting Date and Time Formats* on page 77.


Note: Modifying date and time settings will affect some of the *Windows Embedded Standard* settings.

To adjust the date and time:

1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Date and Time**.



3. Select the **Date & Time** tab.




4. Modify the settings according to your needs.
5. Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.

Setting Up Your Unit


Adjusting the Date, Time and Time Zone

To change the time zone:

1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Date and Time**.



3. Select the **Time Zone** tab.



4. Modify the settings according to your needs.
5. Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.

Configuring the Power Management Options

To get the optimum performance out of your FTB-1, your unit comes with three predefined sets of parameters (schemes) to manage power.

When you do not use the unit for a while, the display may be turned off to save power. You can also configure the unit to go into standby or hibernation mode after the specified duration has expired (see *Turning On or Off the Unit* on page 29).

For all of these actions, you can set idle durations for AC adapter/charger and battery operation. The values that you set are kept in memory even when you turn the unit off.

Note: *When the backlight is turned off, the unit operation is not interrupted. Press any key or touch anywhere on the screen to return to normal operation.*

Setting Up Your Unit

Configuring the Power Management Options

The table below indicates the default values that are included in each of the predefined power schemes.

Power Scheme	Action	When AC is connected	Running on batteries
Standard (selected by default)	Turn off monitor	Never	After 5 minutes
	System standby	Never	After 15 minutes
	System hibernates	Never	After 30 minutes
Always On	Turn off monitor	Never	Never
	System standby	Never	Never
	System hibernates	Never	Never
Max Battery	Turn off monitor	After 15 minutes	After 5 minutes
	System standby	After 30 minutes	After 15 minutes
	System hibernates	After 45 minutes	After 30 minutes

Note: *The Turn off hard disks setting is not taken into account (not applicable).*

You can either modify one of the existing power schemes or create one (based on an existing power scheme).




CAUTION


Your unit has been designed to manage power as well as battery alarms automatically. Never modify the parameters that appear on the Alarms tab. Doing so WILL prevent the unit from working properly.

To select a power scheme:

- 1.** From the **Main Menu**, tap **Setup**.
- 2.** Double-tap **Power Options**.



- 3.** From the **Power Schemes** list, select the desired predefined set of parameters.




- 4.** Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.

Setting Up Your Unit


Configuring the Power Management Options

To modify a power scheme:

1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Power Options**.



3. From the **Power Schemes** list, select the predefined set of parameters that you want to modify or on which you want to base your new scheme.
4. Modify the parameters to your needs.
5. Tap **Save As**.



- If you want to modify the existing power scheme, keep the name as is, and then tap **OK**.
- OR
- If you prefer to create a new power scheme, enter a new name, and then tap **OK**.
6. Tap **Apply** to confirm the changes, and then **OK** to return to the **Control Panel** window.


Configuring the Internet Options

You can browse the Web directly from your unit, provided that you have access to an Internet connection and that the Internet options are configured properly.

If you are not sure about how you should configure your Internet access, contact your network administrator.

To configure the Internet options:

1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Internet Options**.



3. Go to the **Connections** tab.
4. Modify the settings using the information provided by your network administrator.
5. Tap **OK** to return to the **Control Panel** window.

Setting Other Parameters

You can also configure other parameters via the **Control Panel** window. Refer to Microsoft Windows Embedded Standard documentation for details.

5 ***Working with Your Unit***

Printing Documents

You can print documents and images directly from your unit by using either the PDFCreator (for PDF files) or a network printer (for printing on paper).

You can view the PDF files from your unit, using the SumatraPDF reader. For more information, see *Viewing PDF Files* on page 92.

To print on a network printer, your unit must be accessible from this network by Wi-Fi or standard Ethernet. You must also define the printer on your unit before attempting to access it (see *Configuring Network Printers* on page 69).

If you cannot connect your unit to a network, you can use a USB memory key to transfer the files that you want to print to a computer connected to the network.

If you need more flexibility and a greater choice of report types, you can also transfer result files to a computer onto which applications such as EXFO FastReporter 2 are installed.


Note: *Some applications may not offer print functions.*

Working with Your Unit


Printing Documents

To print documents:

1. Open a Web browser as follows:
 - 1a. From Mini Toolbox, select the **Utilities** tab.
 - 1b. Tap the **Internet Explorer** icon to open the browser.



2. Select the document that you want to print as follows:
 - 2a. From the menu, select **File > Open**.
 - 2b. Tap **Browse** to locate the file that you want to open.



- 2c. Tap **Open** to load the file in Internet Explorer.
 - 2d. Tap **OK** to confirm.
3. From the menu, select **File > Print**.



4. From the **General** tab, select the desired printer (PDFCreator by default).
5. If necessary, tap **Preferences** to adjust the parameters to your needs.

Note: If you selected a network printer, you can save the whole set of preferences for future use with the **Save As** button or simply press

✓ from the unit's keypad to save the parameters for the current work session.

6. Tap **Print** to start the printing process.
7. If you selected PDFCreator, proceed as follows:
 - 7a. Enter the desired information.

To view the PDF file immediately after its creation

- 7b. Tap **Save**.
- 7c. Specify a location and a file name and tap **Save**.
If you have selected the option to view the PDF file after its creation, the SumatraPDF reader will display the new file.
- 7d. If necessary, tap  to close the SumatraPDF window.
8. Tap  to close Internet Explorer and return to the **Utilities** tab.

Working with Your Unit


Viewing PDF Files

Viewing PDF Files

You can view PDF files directly from your unit using the SumatraPDF reader. For more information on the available features for this reader, refer to the SumatraPDF online help.

To view PDF files:

1. From **Main Menu**, select **File Manager**.
2. Browse through the folders to find the desired PDF file.
3. Double-tap the file.
4. The file opens automatically in the SumatraPDF application.



Note: You can access the online help directly from the **Help** menu of the SumatraPDF application. You will need a connection to the Internet to view the online help.

Taking Screen Captures

You can take captures of what is displayed on your screen, directly from your unit. This could be useful for troubleshooting when you need another person to have a look at a specific configuration or problem. You could also use this tool for training purposes.

If you want to capture images of the fibers that you examine with the fiber inspection probe, you can use the capture feature of the probe instead.

For more information on how to modify the default file format and destination folder, see *Setting Storage Parameters for Screen Captures* on page 96.

- Images are saved using the defined file format. By default, images are created in .bmp format, but you can modify this parameter. By default, they are kept in the following folder:

D:\Documents and Settings\User_currently_logged_on\My Documents\Screen Snapshot

where *User_currently_logged_on* corresponds to the user name of the person that is currently logged on the unit.

It is possible to modify the folder in which images are automatically saved.

Working with Your Unit

Taking Screen Captures

- By default, the application generates file names as follows:

IMG_[YEAR]_[MONTH]_[DAY]_[HOUR]_[MINUTE]_[SEQUENTIAL NUMBER].bmp

Example:

For a screen capture taken on August 20, 2010, the file name could be:



IMG_2010_08_20_13_23_01.bmp.

Note: *The HOUR value will appear in a 24-hour format, regardless of your unit's time settings.*

Note: *The SEQUENTIAL NUMBER value is used to differentiate two captures that would have been taken at the same date and time.*

- There are two ways to capture images: a quick mode (the screen capture tool is automatically closed as soon as the capture is made) and a multiple-capture mode (the screen capture button is part of a floating toolbar that remains available until you close it). By default, this toolbar is located in the lower-right corner of the screen. However, you can move it to a location that better suits your needs.





To take only one screen capture:

From the unit's keypad, press the / button and hold it down for about 3 seconds.

The screen capture is automatically taken as soon as you release the button (a sound and visual effect typical of a camera taking a picture indicate that the capture is complete).

Note: *If a keyboard is connected to your unit, you can also press the PRINT SCREEN key.*

To take several screen captures:

1. From the unit's keypad, press the / button.
2. Once the on-screen keyboard is displayed, tap the  button.
3. From the floating toolbar, tap the  button.

The screen capture is automatically taken (a sound and visual effect typical of a camera taking a picture indicate that the capture is complete).

Setting Storage Parameters for Screen Captures

You can modify the file format of the screen captures as well as the destination folder, that is the folder to which the captures will be sent.

- By default, images are saved in .bmp format, but you can configure the application to save them in .jpg or .png format.
- By default, images are kept in the following folder:

D:\Documents and Settings\User_currently_logged_on\My Documents\Screen Snapshot


where *User_currently_logged_on* corresponds to the user name of the person that is currently logged on the unit.

You can select any other folder as the destination either locally on your unit, on a USB memory key.


Note: *If the specified folder is no longer available (folder name has been modified, folder has been deleted), the screen captures will be sent to the default folder. Similarly, if you have defined a destination folder on a USB key and this key is not connected to your unit when you take screen captures, the latter will be sent to the default folder.*

To set the default image format:

- 1.** From the Main Menu, tap **System Settings**.
- 2.** If necessary, from **System Settings**, tap **Display & Sound**.



- 3.** Under **Screen snapshot**, tap the **Screen Snapshot Options** button.
- 4.** Under **Image format**, select the option corresponding to the desired format.




- 5.** Tap **OK** to confirm the changes and close the window.

Working with Your Unit


Setting Storage Parameters for Screen Captures

To modify the destination folder:

1. From the Main Menu, tap **System Settings**.
2. If necessary, from **System Settings**, tap **Display & Sound**.



3. Under **Screen snapshot**, tap the **Screen Snapshot Options** button.
4. Under **Destination folder**, tap **Browse**.



5. From the **Browse for Folder** window, select the folder that you want to use to store the screen captures. If necessary, you can create a folder.



6. When your selection is made, tap **OK**.
7. Tap **OK** to confirm the changes and close the window.

Reading Audio and Video Files

Your unit is equipped with the VLC media player which enables you to read audio files and to view video files (such as .avi and .divx). This could be especially useful if your company wants to use multimedia files for training. The player can read files that are stored on your unit, on a USB memory key, on a network folder, or even on a Web site.



IMPORTANT

The VLC media player does not support the Flash format. If you want to read files in this format, you will need to install the Adobe Flash Player application (see *Installing Adobe Flash Player on Your Unit* on page 102).


For more information on how to configure the language of the media player, see *Selecting the Language of Operation* on page 72.

For more information on how to use the video player, refer to the VideoLAN online help.

To read video or audio files:

- 1.** From Mini Toolbox, select **File Manager**.
- 2.** Locate the video or audio file that you want to read.
- 3.** Double-tap the file.

The media player starts reading automatically if the file format is recognized.



Note: *You can access the online help from the **Help** menu of the VCL Media Player application. You will need a connection to the Internet to view the online help.*

Installing Adobe Flash Player on Your Unit

The Adobe Flash Player application is not installed on your unit by default, but you can install it if you need to read files in Flash format.



IMPORTANT

EXFO does not provide licenses for Adobe Flash Player. Contact Adobe to purchase a license that will entitle you to install Flash Player on your unit.

To download the installation files, you will need a connection to the Internet. You can either download the files directly to your unit or to a computer (and transfer them to your unit later using a USB key).

Note: *Only administrator-level users can install software under Windows Embedded Standard. However, when the installation is complete, all users will be able to read files in Flash format.*



IMPORTANT

Ensure to download the latest installation package for the 32-bit version of Flash Player for Windows (operating system), and Internet Explorer (browser). You should retrieve the EXE installer component.

To install Adobe Flash Player on your unit:

1. If necessary, turn on your unit.
2. From your computer or your unit, open a Web browser and go to http://www.adobe.com/special/products/flashplayer/fp_distribution3.html.
3. Locate the most recent version of Flash Player 32 bits.
4. Under Flash Player 32 bits, locate the entry corresponding to Windows (operating system) and Internet Explorer (browser).
5. Save the corresponding *EXE installer* to a location of your choice (on a USB memory key connected to your computer or on your unit).
6. If you have downloaded the file to a USB key, connect the key to your unit.
7. Double-tap the downloaded file, and follow the on-screen instructions.

Note: *At this point, if you have used a USB memory key to transfer the installation files to your unit, you can remove it.*

All users are now ready to read files in Flash format.


Browsing the Web


You can browse the Web directly from your unit, provided that you have access to an Internet connection.


If you need to modify the Internet options, see *Configuring the Internet Options* on page 87. For more information on how to connect to the Internet using a 3G USB modem key, see *Accessing the Internet with a 3G USB Modem Key* on page 106.

To browse the Web:

1. Open a Web browser as follows:
 - 1a. From Mini Toolbox, select the **Utilities** tab.
 - 1b. Tap the **Internet Explorer** icon to open the browser.



2. Enter the desired Web address in the address bar and tap the  button (located at the right of the address bar) to start browsing.



3. Close the window to return to the **Utilities** tab.

Accessing the Internet with a 3G USB Modem Key

Note: *Only administrator-level users can install software under Windows Embedded Standard. However, when the installation is complete, all users will have the possibility to access the Internet using a USB modem key.*

You can connect an optional 3G USB modem key to your unit to have a wireless access to the Internet.

When you receive your modem key, it contains no Subscriber Identity Module (SIM) card. This means that you will need to:

- Purchase a compatible and unlocked SIM card from a provider offering 3G services. If you need more information on the 3G coverage in your area, contact your regional EXFO sales representative.
- Have the card activated (you must subscribe to a package of mobile services).
- Insert the card in the modem key.

The very first time you connect a USB modem key to your unit, the AirCard Watcher application will be installed automatically on your unit. You will use this application to establish a connection with the mobile network whenever you want to work with your USB modem key. You only need to install this application once.



IMPORTANT

- Only the Sierra Wireless 319U keys provided by EXFO are supported on your unit.
- Before using the USB modem key for the first time, you must install the most recent System Upgrade and Platform kits for your unit. To do this, you will need a standard USB memory key and a computer with an Internet access. You can also retrieve the kits directly from your unit, but you will need an Internet access (other than the one that would be provided by the 3G USB modem key).
- Always turn your unit on *before* connecting the USB modem key to it. Otherwise, the USB modem may not be detected properly.

To upgrade your unit to the latest System Upgrade and Platform components:

- 1.** If necessary, turn on your unit.
- 2.** Retrieve the latest System Upgrade and Platform kits:
 - 2a.** From your computer or your unit, open a Web browser and go to www.exfo.com.
 - 2b.** Log on to your My EXFO account.
 - 2c.** Under FTB-1, find the System Upgrade and Platform kits. If you need information on how to download the kits, refer to the Readme files provided with the kits.

Working with Your Unit

Accessing the Internet with a 3G USB Modem Key

- 3.** Install the retrieved kits on your unit:
 - 3a.** Install the System Upgrade. For more information, refer to the installation procedure provided with the kit.
 - 3b.** Once the installation of the System Upgrade is complete, install the Platform kit on your unit. For more information, refer to the Readme file provided with the kit.

Note: *At this point, if you have used a USB memory key to transfer the installation files to your unit, you can remove it.*

You are now ready to install the AirCard Watcher application as explained hereafter.

To install the AirCard Watcher application on your unit:

- 1.** If necessary, turn on your unit and wait for the startup sequence to complete.
- 2.** If necessary, insert the SIM card into the USB modem key. For more information, refer to the documentation that came with your modem key.
- 3.** Connect the USB modem key to one of the USB ports of your unit.

The installation of the AirCard Watcher application will start automatically.

4. Follow the on-screen instructions.

You will know that the installation is complete when the AirCard Watcher application starts.



5. Close the AirCard Watcher application.
6. Disconnect the USB modem key from your unit.
7. Reconnect the USB modem key to your unit so that it can be detected properly.

All users are now ready to start working with the USB modem key as explained hereafter.

Working with Your Unit

Accessing the Internet with a 3G USB Modem Key

To work with a 3G USB modem key:

- 1.** If necessary, turn on your unit and wait for the startup sequence to complete.
- 2.** If necessary, insert the SIM card into the USB modem key. For more information, refer to the documentation that came with your modem key.
- 3.** If necessary, connect the USB modem key to one of the USB ports of your unit.
- 4.** From the Windows desktop, double-tap the AirCard Watcher icon to start the application.

5. Once the AirCard Watcher application starts, tap **Connect** to establish a connection with the mobile network.



As soon as the connection is established, you are ready to browse the Web.

Note: *If you want to customize the behavior and appearance of the AirCard Watcher application, refer to the online help provided with the application (available by tapping ? from the toolbar).*

Note: *The application will display a warning message if no SIM card has been inserted in the USB modem key.*

Note: *Depending on the package that you have purchased with your service provider and the type of network, you may have to set specific parameters. If you are not sure on how to proceed or need more information about the configuration, contact your service provider.*

6. When you have finished working, tap **Disconnect** from the AirCard Watcher application, and then remove the USB modem key from your unit.

Retrieving the GPS Location of Your Unit

With the optional GPS USB key and the provided GPS utility, you can retrieve the latitude and longitude coordinates of your unit as well as the date and time of the reading. You will see either the last known coordinates or the current ones, depending on if the GPS key can establish a connection with the GPS satellites or not.

Note: *To be able to establish a communication, the unit must be used outdoors and as far away as possible from buildings and other solid objects.*

In addition to viewing the GPS information on-screen, you can copy it to the Clipboard in two formats: a text string or a URL link. The text string contains the GPS coordinates as well as a date and time stamp. Once the information is in the Clipboard, you can paste it to any document or test report (in editable sections). If your unit is connected to the Internet, you can even directly paste the URL link to a Web browser to locate your unit on a map.



IMPORTANT

- Only the Canmore GT-730F(L) keys provided by EXFO are supported on your unit.
- Before using the GPS USB key for the first time, you must install the most recent System Upgrade and Platform kits for your unit. To do this, you will need a standard USB memory key and a computer with an Internet access. You can also retrieve the kits directly from your unit, but you will need an Internet access.

Note: *Only administrator-level users can install software under Windows Embedded Standard.*

To upgrade your unit to the latest System Upgrade and Platform components:

1. If necessary, turn on your unit.
2. Retrieve the latest System Upgrade and Platform kits:
 - 2a. From your computer or your unit, open a Web browser and go to www.exfo.com.
 - 2b. Log on to your My EXFO account.
 - 2c. Under FTB-1, find the System Upgrade and Platform kits. If you need information on how to download the kits, refer to the Readme files provided with the kits.
3. Install the retrieved kits on your unit:
 - 3a. Install the System Upgrade. For more information, refer to the installation procedure provided with the kit.
 - 3b. Once the installation of the System Upgrade is complete, install the Platform kit on your unit. For more information, refer to the Readme file provided with the kit.

All users are now ready to start working with the GPS USB key as explained hereafter.

Note: *At this point, if you have used a USB memory key to transfer the installation files to your unit, you can remove it.*

Working with Your Unit

Retrieving the GPS Location of Your Unit




IMPORTANT

Always turn your unit on *before* connecting the GPS USB key to it. Otherwise, the GPS key may not be detected properly.


To retrieve the GPS location of your unit:

- 1.** Go outdoors with your unit.
- 2.** If necessary, turn on your unit and wait for the startup sequence to complete.
- 3.** Ensure that the GPS USB key is connected to your unit.

4. From Mini Toolbox, select the **Utilities** tab, then tap **GPS Coordinates Viewer**.



The GPS coordinates are displayed.



Note: If you see “GPS not detected” at the bottom of the **GPS Coordinates** window, this means that the GPS key is not connected to your unit. Once the GPS key is connected properly, the utility will display “Searching”. Finally, when a connection can be established with the GPS satellites, the utility will display “Receiving coordinates”.

Note: As this is the case with any other GPS device, you may have to wait a few minutes to get a valid GPS signal.

- Tap **Copy Coordinates** to send the displayed information to the Clipboard as a text string.
- Tap **Copy Hyperlink** to send the displayed information to the Clipboard as a URL link.

5. When your work is finished, tap  to close the utility.

Using the Calculator

You can use Microsoft Calculator directly from your unit.

To use the Calculator:

1. From Mini Toolbox, select the **Utilities** tab.
2. Tap **Calculator**.

Using the Text Editor

You can use Microsoft Notepad directly from your unit.

To use the text editor:

1. From Mini Toolbox, select the **Utilities** tab.
2. Tap **Notepad**.

Accessing Other Tools

Your unit comes with free tools such as Wireshark to help you troubleshoot networks. For more information, refer to the online help provided with these tools.

You can also purchase advanced software tools if you need more flexibility and possibilities. Online help is available from these applications to guide you.

If you want one or more of these tools to start automatically at unit startup, see *Selecting the Startup Application* on page 65.

To access tools:

1. From Mini Toolbox, select the **Test Tools** tab.
2. Tap the icon corresponding to the tool that you want to use.

6 ***Using the Optional Built-In Power Meter and VFL***

The FTB-1 can be equipped with an optical power meter to measure absolute power (dBm or W) or insertion loss (dB). The power meter can detect modulated signals (1 kHz, 2 kHz, and 270 Hz).

The FTB-1 can also include a visual fault locator (VFL) to inspect or identify fibers.

If you have purchased a module with an inline power meter, you can also take measurements with this power meter instead of using the built-in power meter.


For more information on how to use the power meter or the VFL, refer to the power meter online help.

Note: *The appearance of your application may vary depending on the options that you have purchased and the module you are using. The illustrations presented hereafter show the application as it appears when the unit is equipped with a built-in power meter, a built-in VFL, and a module with an inline power meter.*


Using the Optional Built-In Power Meter and VFL

To access the built-in power meter or the VFL:


1. From Mini Toolbox, tap **Power Meter and VFL**.



2. If the module that you are using with your platform is equipped with an inline power meter, tap the item corresponding to the power meter that you want to use.



Note: If you want to use the built-in VFL, select either **Power Meter and VFL** or **VFL**, depending on the configuration of your unit.

Note: You can access the online help of the power meter and the VFL by tapping the  button from the power meter application.

7 ***Inspecting Fibers with a Probe***

The fiber inspection probe (FIP) is used to find dirty or damaged connectors by displaying an enlarged view of the connector surface. You can connect a probe to your unit to view fiber ends.

Your unit supports both the probes of the FIP-400 and FIP-400B series.


Fiber inspections are made using the ConnectorMax (FIP-400) or the ConnectorMax2 (FIP-400B) application, depending on the probe that you use. By default, you will be prompted to select the application with which you want to work. If you prefer, you can configure the unit to always start your favorite application directly instead (see *Selecting the FIP Startup Application* on page 67).

For more information on how to work with the probe, refer to the ConnectorMax or ConnectorMax2 online help.

To inspect fibers with a probe:

1. Connect the probe to your unit.
 - For a probe of the FIP-400 series, connect it to the probe port.
 - For a probe of the FIP-400B series, connect it to one of the USB ports.


Top panel




2. From the **Main Menu**, tap **Probe**.

Inspecting Fibers with a Probe

3. If the unit prompts you to select an application, tap the button corresponding to the probe that you want to use to start the corresponding application.



Note: If you have not updated the ConnectorMax product lately, the ConnectorMax2 application may not be installed on your unit. In this case, you will not be presented with a choice of applications. The ConnectorMax application will start automatically, enabling you to work with the probes of the FIP-400 series. If you also wish to be able to work with probes of the FIP-400B series, you will need to install the most recent ConnectorMax kit.

Note: You can access the online help by tapping the  button from the ConnectorMax or ConnectorMax2 application.

8 ***Managing Data***

You can copy, move, rename, delete files and folders directly on your unit.

You can transfer files from your unit to a USB memory key or a computer.

You can also transfer data from a storage device or a computer to your unit.


Your unit is equipped with the following ports and devices for data transfer:

- Two USB 2.0 ports to connect a memory key or a USB to RS-232 adapter (see *Using the USB to RS-232 Adapter* on page 136.)
- an Ethernet port to connect to a network (for transfer via VNC or Remote Desktop - see *Accessing Your Unit Remotely* on page 157)
- internal Wi-Fi device (optional) to connect to a wireless network
- internal Bluetooth device (optional) to transfer data via Bluetooth.

To view the free disk space on your unit:

1. From Main Menu, tap **System Info**.
2. Select **Platform**.

The free disk space is displayed next to the **Available Flash** on “D:\ (APP)” item.



3. When you have finished, tap **OK** to close **System Information**.

To manage files or folders on your unit only:

From Main Menu, select **File Manager**.

To transfer files or folders between your unit and a USB memory key:

- 1.** Connect the USB memory key to the USB port.
- 2.** From **Main Menu**, select **File Manager**.

The list of available drives and folders should include the memory key (**Removable Disk**). You can now manage your files and folders as you wish.

Note: *If you do not see the memory key, close File Manager and reopen it. You can also use the **Refresh** option from the **View** menu.*

- 3.** When you have finished, remove the memory drive.

Transferring Data via Bluetooth

If your unit is equipped with the optional Bluetooth device (internal), you can transfer data between your unit and a computer using the Bluetooth technology. By default, both the Bluetooth and Wi-Fi devices are enabled, but not connected to a network.

If you have disabled the devices, you must enable them before trying to transfer data via Bluetooth (see *Enabling or Disabling the Bluetooth and Wi-Fi Devices* on page 141).

The computer that you use must run Windows XP SP3 or later; otherwise, there could be problems during data transfer. The computer must also be equipped with a Bluetooth device and be configured properly.

Note: *If you prefer to use devices such as BlackBerry smartphones instead of a computer for data transfer, you must ensure that they are Bluetooth-compatible and configured properly. Some devices only allow data transfer between devices of the same make. In this case, you will need to use another type of device or a standard computer to transfer data from your FTB-1 unit.*

Your unit must be located within a 9-meter area from your computer (limitation of the Bluetooth technology).

If you need to transfer large files (more than 1 Gb), use a USB key, or connect to a Wi-Fi or an Ethernet network.


The procedure presented hereafter explains how to transfer data from your unit to a computer. Data transfer from the computer to your unit is similar, except that data will be sent using the Bluetooth Transfer Wizard of the computer (*Send a file* option) and received by the unit (*Receive a file* option).

To transfer data via Bluetooth:


1. Configure your unit as follows:

1a. From the **Main Menu**, tap **Setup**.

1b. Double-tap **Bluetooth Devices**.



1c. From the **Options** tab, under **Discovery**, select the **Turn discovery on** check box.



1d. Ensure that the **Allow Bluetooth devices to connect to this computer** check box is selected.


1e. Tap **OK** to confirm.

Managing Data

Transferring Data via Bluetooth


2. Configure the computer as follows:
 - 2a. On the computer, from **Control Panel**, double-click **Bluetooth Devices**.
 - 2b. From the **Options** tab, under **Discovery**, select the **Turn discovery on** check box.
 - 2c. Ensure that the **Allow Bluetooth devices to connect to this computer** check box is selected.
 - 2d. Tap **OK** to confirm.
3. On the computer, click the Bluetooth icon (located on the taskbar) and select **Receive a file**.
4. On your unit, from Mini ToolBox, select the **Utilities** tab.

5. Tap Bluetooth File Transfer Wizard.



6. From the Welcome window, tap Next.

7. Select Send a file and tap Next.




Managing Data


Transferring Data via Bluetooth

8. Select the computer to which you want to transfer data as follows:


8a. Tap **Browse**.



8b. Select the desired computer, and then tap **OK** to confirm.




9. If you want to use a passkey, select the corresponding check box and enter the passkey.



When you have finished, tap **Next**.

10. Tap **Browse** to select the file that you want to send to the computer.



11. Select the file, tap **Open** to confirm, and then **Next**.

Managing Data

Transferring Data via Bluetooth

- 12.** On the computer, when the application prompts you, allow the connection and enter the passkey if necessary.

Note: *Once you have established a secured connection using a passkey, this passkey is kept in memory both on your unit and on the computer until you remove this connection (**Setup** > **Bluetooth Devices** > **Devices**) or change the passkey.*

- 13.** On the computer, click **Finish**.
- 14.** From the Bluetooth File Transfer Wizard on your computer, if necessary, modify the name of the received file and the storage location. Click **Next** to save the file. Click **Finish** to close the wizard.
- 15.** On your unit, tap **Finish** to close the Bluetooth File Transfer Wizard.


Connecting to a Wireless Network

If your unit is equipped with the optional Wi-Fi device (internal), you can connect to a wireless network and benefit from all resources that are available on this network. You can transfer data exactly as you would do from an Ethernet network. By default, both the Bluetooth and Wi-Fi devices are enabled, but not connected to a network.

If you have disabled the devices, you must enable them before trying to connect to a wireless network (see *Enabling or Disabling the Bluetooth and Wi-Fi Devices* on page 141).

To connect to a wireless network:

1. If it is not already done, share all the required folders both on your unit and on your computer. If you are not sure on how to proceed, contact your network administrator.
2. If it is not already done, configure the firewall as follows:
 - 2a. From **Main Menu**, tap **Setup**.
 - 2b. Double-tap **Windows Firewall**.




- 2c. Select the **Exceptions** tab.


Managing Data

Connecting to a Wireless Network

- 2d. Ensure that the **File and Printer Sharing** item is selected.




- 2e. Tap **OK** to confirm.
3. On your unit, from Mini ToolBox, select the **Utilities** tab.
4. Tap **WiFi Connect**.




5. Tap **OK** to acknowledge the message on how to display the list of wireless networks.

6. Double-tap **Wireless Network Connection**.




7. If your unit is already connected to a wireless network, tap **View Wireless Networks** to display the list of wireless networks.



Managing Data


Connecting to a Wireless Network

8. From the **Wireless Network Connection** window, select the wireless network to which you want to connect.



9. Tap **Connect**.

- 10.** If the network is protected by a network key (password) enter it in the corresponding boxes and tap **Connect**.



Note: *Since all networks are different, you may also need to configure other parameters before being able to transfer data via Wi-Fi. For information on the configuration specific to your network, contact your network administrator.*

As soon as the connection is established, you can start working with the selected wireless network. When you have finished, from the **Wireless Network Connection** window, tap **Disconnect** to stop communication with the wireless network.

Using the USB to RS-232 Adapter

If you want to transfer data between your unit and a device that is only equipped with RS-232 (serial) ports, you have to use a USB/RS-232 adapter.



IMPORTANT


Only the USB/RS-232 adapters sold by EXFO are supported.

Once the adapter has been detected, the unit assigns it a COM port number (values begin at COM 3). This COM port number is kept in memory even when you turn the unit off. This means that next time you connect the same adapter to any of the USB ports, the unit will recognize the adapter and identify it with the saved COM port number.

The communication between your unit and the device is established using the PuTTY application.

To use the USB/RS-232 adapter:

1. Turn on both the unit and the serial device.
2. Connect as shown. You can connect the USB end of the adapter to any of the USB ports.



Note: *If the device that you want to use is a computer (not equipped with USB ports) you may want to use a null-modem serial cable as an “extension cable” between the device and the USB/RS-232 adapter.*

The adapter will be detected automatically on your unit.


Managing Data

Using the USB to RS-232 Adapter


3. From your unit, retrieve the COM port of the adapter as follows:

3a. On your unit, from the **Main Menu**, select **Setup**.

3b. Double-tap **Device Manager**.




3c. Expand the **Ports (COM & LPT)** list to retrieve the COM port number that has been assigned to the adapter and write it down.



3d. Close the *Device Manager*.

4. From your unit, configure the communication parameters as follows:
 - 4a. On your unit, from Mini ToolBox, select the **Utilities** tab, then tap **PuTTY**.
 - 4b. Configure the parameters.



- From the tree view, select **Connection** > **Serial** and set the parameters as needed. Ensure that the COM port that you specify corresponds to the one that you wrote down at step 3c.
 - If you want to view the characters that you type on screen, from the tree view, select **Terminal**. Under **Local echo**, set the value to **Force on**.
 - From the tree view, select **Session**. Select **Serial**. The COM port number and the speed should correspond to those that you have previously entered.
- 4c. Tap **Open**. The unit is now ready to receive or send data.

Managing Data

Using the USB to RS-232 Adapter

5. From the device, set the communications parameters.



IMPORTANT

To be able to establish a communication between the unit and the device, you must set the following parameters to the same values as those defined on your unit:

- Speed
- Data bits
- Stop bit
- Parity
- Flow control

Note: *The COM port number that you set on your device will probably differ from the one that you used on your unit.*

6. From the device, establish communication with the unit using your favorite communication tool (PuTTY, HyperTerminal, etc.).

Enabling or Disabling the Bluetooth and Wi-Fi Devices

By default, both the Wi-Fi and Bluetooth devices are enabled on units that are equipped with the corresponding options.


If you do not intend to transfer files via Bluetooth or to work with a wireless network for a certain period of time, you may wish to disable the devices to extend battery life.

As soon as you disable the Wi-Fi device, the Bluetooth is automatically disabled as well.

You can enable the devices again at any time.

To enable or disable the Bluetooth and Wi-Fi devices:


1. From the **Main Menu**, tap **Setup**.
2. Double-tap **Network Connections**.



Managing Data

Enabling or Disabling the Bluetooth and Wi-Fi Devices

3. Select Wireless Network Connection.



4. From the **File menu, select **Enable** or **Disable**, according to your needs.**

Transferring Files with the USB Data Mover Application

With the USB Data Mover application, you can copy folders and files from your unit to a USB storage device quickly.

You can retrieve files from the predefined source folders or specify your own folders.

The predefined folders are:

- My Documents, which path is *D:\Documents and Settings\User_currently_logged_on\My Documents*

where *User_currently_logged_on* corresponds to the user name of the person that is currently logged on the unit.

- Shared Documents, which path is *D:\Documents and Settings\All Users\Shared Documents*.

Note: *You cannot remove the predefined folders from the list of source folders, but you can remove the ones that you have added.*

By default, the application retrieves the files from all the folders appearing on the list of source folders. However, you can specify which folders you want to take into account.

Managing Data

Transferring Files with the USB Data Mover Application

Each time you copy data, the application creates a folder on the storage device. This folder will contain the copied files and subfolders (original folder structure as well as folder and file names are kept).

The application generates folder names as follows:

[YEAR]-[MONTH]-[DAY]_[HOUR]-[MINUTE]-[SECOND]

Example:


For a copy operation requested on September 20, 2013, the folder name could be:

2013-09-20-13_23-01-45.

Note: *The HOUR value will appear in a 24-hour format, regardless of your unit's time settings.*


To transfer files with the USB Data Mover:

1. Connect a USB storage device to one of the USB ports.
2. From Mini Toolbox, select the **Utilities** tab.
3. Tap **USB Data Mover**.



4. Select or clear the check boxes to adjust the folder selection to your needs.




5. If necessary, under **Destination media**, select the desired USB storage device.
6. Tap **Copy**. The files will remain on your unit after the transfer.
7. When you have finished, tap  to exit the USB Data Mover application.

Managing Data


Transferring Files with the USB Data Mover Application

To manage the list of source folders:

1. From Mini Toolbox, select the **Utilities** tab.
2. Tap **USB Data Mover**.




3. Tap **User Preferences**.




- 4.** If you want to add your own folders to the list of source folders, proceed as follows:

4a. Tap **Add a Folder**.



4b. Select the desired folder, and then tap **OK**.




Managing Data

Transferring Files with the USB Data Mover Application


5. If you want to remove folders from the list of source folders, proceed as follows:

5a. Select the folder that you want to remove.



5b. Tap **Remove Folder**.

Note: *The application will not prompt you to confirm the removal of the folder from the list.*

6. When you have finished, tap **Close**. Your changes are reflected automatically. All the newly added folders are selected by default.
7. Tap  to exit the USB Data Mover application.

Connecting to a VPN from Your Unit

Note: *Only administrator-level users can install software under Windows Embedded Standard. However, when the installation is complete, all users will have the possibility to connect to a VPN from the unit.*

You can connect to a Virtual Private Network (VPN) from your unit if you install one of the supported VPN clients (applications). Such clients allow you to connect to the VPN of your company from anywhere in the world and have access to network resources as if your unit was connected locally to the network. This could be useful if you need to transfer data to a centralized folder on the company's private network, for example.

To establish the communication between the VPN client and the VPN server, you can use either a Wi-Fi connection (see *Connecting to a Wireless Network* on page 131), a 3G USB modem key (see *Accessing the Internet with a 3G USB Modem Key* on page 106), or a standard Ethernet connection.

Note: *Since all networks are different, the parameters that you need to configure before being able to connect to the VPN may vary. For information on the configuration specific to your network, contact your network administrator.*

If you ever need to change to another VPN client or remove it, see *Solving Common Problems* on page 195.

Managing Data

Connecting to a VPN from Your Unit




IMPORTANT

EXFO does not provide any VPN clients. You must provide the installation files for one of the supported VPN clients yourself. The complete list is available from the VPN Installer application.


EXFO cannot guarantee that any VPN client other than those listed will work properly on your unit.

To retrieve the list of supported VPN clients:

1. On your unit, from Mini ToolBox, select the **Utilities** tab.
2. Tap **VPN Installer**.
3. From the VPN Installer first window, tap **Continue**.



4. All the supported VPN clients appear on the **Supported software and versions** list. You can write down this list and contact your network administrator to get the installation files.



5. Tap **Cancel** to close the VPN Installer.

You are ready to go to the procedure explaining how to install the VPN client on your unit.

Managing Data

Connecting to a VPN from Your Unit



CAUTION

- To ensure the proper installation of your VPN client, **NEVER** attempt to install it manually. Always use the VPN Installer.
- **DO NOT** restart your unit during the installation even if you are prompted to do so. Otherwise, the VPN client will not be installed properly. The EXFO VPN Installer will restart your unit automatically to complete the installation. If you updated the VPN client by mistake, see *Solving Common Problems* on page 195.
- Your unit has been designed to work with specific versions of VPN clients. **NEVER UPDATE** the VPN client manually and ensure that the VPN server will not update the client either. Otherwise, the VPN client may no longer work properly.



IMPORTANT

EXFO does not recommend to install more than one VPN client on a single FTB-1 unit.




IMPORTANT

To avoid communication problems between the VPN client and the VPN server, ensure that the date set on your unit corresponds to the current date.

To install a VPN client on your unit:


1. If the date on your unit does not correspond to the current date, modify it (see *Adjusting the Date, Time and Time Zone* on page 80).
2. Retrieve the installation files on your unit as follows:
 - 2a. On your unit, create a folder on the Windows desktop.
 - 2b. Copy the installation files (from a USB key or a folder network) to the newly created folder.
3. On your unit, from Mini ToolBox, select the **Utilities** tab.
4. Tap **VPN Installer**.




Managing Data

Connecting to a VPN from Your Unit

5. From the VPN Installer first window, read the information. When you have finished, tap **Continue**.



6. From the **Supported software and versions** list, select the entry corresponding to the VPN client for which you have retrieved installation files at step 2.




Tap **Continue**.

7. From the VPN Installer, select the corresponding setup file using the **Browse** button.



IMPORTANT

To avoid installation problems, ensure that the installation files are available from the Windows desktop of your unit. Never use installation files directly from a USB key.



Note: Depending on the VPN client that you have selected previously, you may have two installation files to select (two **Browse** buttons instead of one). For more information, refer to the online help provided with the VPN Installer.

8. Tap the **Install** button.
9. Follow the on-screen instructions.

Your unit will restart automatically to complete the installation of the VPN client. All users will now be able to connect to a VPN from the unit.

Managing Data

Connecting to a VPN from Your Unit

To connect to a VPN from your unit:

Start the VPN client and follow the on-screen instructions.

If you are not sure about the information that you should provide, contact your network administrator.

9 ***Accessing Your Unit Remotely***

You can access your unit remotely from a computer using either the Remote Desktop Connection or TightVNC Client applications.

The table below presents the differences between the two applications.

Characteristic	Remote Desktop Connection	TightVNC Client
Type of connection	Direct between the unit and the computer; only one user can be connected to the unit at a time.	Not exclusive; several users can be connected to the unit at the same time (sharing the same session).
Windows user rights	Taken into account.	Not taken into account.
Password-protected	Yes; mandatory. The user name and password are the same as those used to connect to the unit. By default, all the accounts with administrator rights can use Remote Desktop Connection. If you want accounts with limited rights to be able to use Remote Desktop as well, you must specifically grant them access.	Yes; mandatory. The password is defined on the TightVNC Server, the first time you start the server. This password is not related to the one used to connect to the unit. By default, all people that use TightVNC Client will enter the same password (as defined on the server). Each user to whom you provide the password will be able to connect to the unit via TightVNC.

Working with Remote Desktop

By default, all the accounts with administrator rights can use Remote Desktop. If you want accounts with limited rights to be able to use Remote Desktop as well, you must specifically grant them access.

You can also configure the unit to prevent users from accessing it remotely.

Accessing Your Unit with Remote Desktop

To be able to connect to the unit using Remote Desktop, you must:

- Know the IP address of the unit and provide it in the connection settings on the computer.
- Use an account that is secured by a password. Remote Desktop will not allow any connection with empty passwords.
- Enter the appropriate user name when Remote Desktop application prompts you. Usually, this user name must correspond to the user name of the person currently logged on the unit. Otherwise, you will disconnect the person that was already connected.

To access your unit remotely with Remote Desktop:

1. Connect both the computer and your unit to the same network and make sure they can “see” each other as network restrictions might prevent them from communicating.
 - If you want to use an Ethernet network, connect an RJ-45 (network) cable to the unit’s RJ-45 port located on its top panel.
 - If you want to use a wireless network, see *Connecting to a Wireless Network* on page 131.
 - You could also create a Private Area Network with your Bluetooth device (contact your network administrator).
2. Turn on both the computer and the unit.
3. On your unit, in Mini Toolbox, go to **Main Menu**. Select **System Info > Platform**.
4. Write down the IP address, and then close the window.


Note: *It may take a few seconds before you see the IP address on the list.*

5. From the computer, on the taskbar, click **Start**, then select **All Programs > Accessories > Remote Desktop Connection**.

Accessing Your Unit Remotely

Working with Remote Desktop

6. In the **Connecting to Remote Desktop** window, in the **Computer** list, type the IP address of the unit that you wrote down at step 4.



7. Click **Connect**.
8. When the application prompts you, enter your user name and password.




9. Click **OK** to open the session.

Allowing Users with Limited Accounts to Use Remote Desktop


By default, only the accounts with administrator rights can use Remote Desktop. However, you can assign extra user rights to accounts with limited rights so that they can also use Remote Desktop.


To allow a user with limited accounts to use Remote Desktop:

1. On your unit, from the **Main Menu**, select **System Settings**.
2. From **System Settings**, tap **Remote Session**.



3. Ensure that **Allow remote connections to this unit (from computer using Remote Desktop client application)** is selected.




4. From the list of users, select the boxes corresponding to the users to whom you want to grant access.
5. Tap  to return to the Mini Toolbox window.

Preventing Users from Connecting with Remote Desktop


You can also configure the unit to prevent users to access it using Remote Desktop. However, all users having administrator user rights will be able to modify this setting at any time.


To prevent users from connecting to the unit using Remote Desktop:

1. On your unit, from the **Main Menu**, select **System Settings**.
2. From **System Settings**, tap **Remote Session**.



3. Select the **Do not allow remote connections to this unit** option.



4. Tap  to return to the Mini Toolbox window.

Restarting or Turning Off Your Unit While Working with Remote Desktop


In some cases, you may need to restart or shutdown your unit while you are controlling it remotely.

To restart or turn off your unit with Remote Desktop:

- 1.** Close all applications, including Mini Toolbox.
- 2.** On the taskbar, click **Start**, then select **Run**.
- 3.** If you want to restart your unit, in the **Open** box, enter *Shutdown -r*.

OR

If you want to turn off your unit, in the **Open** box, enter *Shutdown -s*.



Working With TightVNC

The control of your unit with TightVNC requires the TightVNC Server (already installed on your unit) and the TightVNC Client Viewer (that you must install on your computer).

The first time you start the TightVNC Server on your unit, the application will prompt you to define passwords. Once these passwords are defined, you are now ready to connect to your unit using the TightVNC Client (on your computer).

If you want TightVNC Server to start automatically when you turn on your unit, see *Configuring TightVNC Server to Start Automatically* on page 171.



IMPORTANT

The passwords that you set for the application that is started automatically are independent of the passwords that you set for the application that you start manually (via the Utilities tab). This means that you could need to enter different passwords, depending on which TightVNC application you use to connect to your unit.

If you do not want to manage two different sets of passwords, you can set all passwords to the same value.



CAUTION

Be very careful if you use TightVNC to transfer files between a computer and your unit (TightVNC Server).

- *Transfer from a computer to your unit:* If the transfer is interrupted, all files on your unit having the same name as those on the computer **WILL BE DELETED**. However, the files on the computer will remain available.
- *Transfer from your unit to a computer:* If the transfer is interrupted, all files on the computer having the same name as those on your unit **WILL BE DELETED**. However, the files on your unit will remain available.

To be able to connect to the unit using TightVNC, you must:

- Know the IP address of the unit and provide it in the connection settings on the computer.
- Know the password (same for all users by default).


This section provides you with the basic information to control your unit with TightVNC. For more information, refer to the TightVNC online help.

Configuring the TightVNC Server

The TightVNC Server is already installed on your unit. You must configure passwords before establishing a connection between a computer and your unit.


To configure the TightVNC Server:

1. If you have configured TightVNC Server to start automatically when you turn on your unit, go directly to step 2. Otherwise, from Mini Toolbox, select the **Utilities** tab, then tap **TightVNC Server Start**.



2. Select the **Server** tab.

3. In the **Primary password** and **View-only password** boxes, type the desired passwords.



Note: *The two passwords are independent of each other. They do not have to be identical.*

4. Tap **Apply**, and then **OK**.

Installing the TightVNC Viewer on a Client Computer

If the TightVNC Viewer is not already installed on your computer, you can install it with the DVD that came with your FTB-1.

To install the TightVNC Viewer on your computer:

- 1.** Insert the installation DVD into the CD/DVD drive of your computer.
- 2.** From the DVD **Main Menu**, click **Explore this DVD**.
- 3.** Open the **Utilities** folder, and then copy the **VNC Client** folder.
- 4.** Paste the **VNC Client** folder to a location of your choice on your computer.

You are now ready to start working with the TightVNC Viewer.

Note: *If you want to access the TightVNC Viewer without having to install it on your computer, you can start it from the DVD (**Main Menu** > **Utilities** > **VNC Client**)*

Connecting to Your Unit with TightVNC

Once the TightVNC Viewer is installed on your computer, you are ready to access your unit remotely.

To connect to your unit with TightVNC:


- 1.** Connect both the computer and your unit to the same network and make sure they can “see” each other as network restrictions might prevent them from communicating.
 - If you want to use an Ethernet network, connect an RJ-45 (network) cable to the unit’s RJ-45 port located on its top panel.
 - If you want to use a wireless network, see *Connecting to a Wireless Network* on page 131.
 - You can also create a Private Area Network with your Bluetooth device (see *Transferring Data via Bluetooth* on page 124).
- 2.** Turn on both the computer and the unit.
- 3.** On your unit, in Mini Toolbox, go to **Main Menu**. Select **System Info > Platform**.
- 4.** Write down the IP address, and then close the window.

Note: *It may take a few seconds before you see the IP address on the list.*


Accessing Your Unit Remotely

Working With TightVNC

5. If you have configured TightVNC Server to start automatically when you turn on your unit, go directly to step 6. Otherwise, from Mini Toolbox, select the **Utilities** tab, then tap **TightVNC Server Start**.



6. From your computer, double-click the TightVNC Viewer shortcut on your desktop.
7. In the **VNC Server** list, type the IP address of your unit that you wrote down at step 4.



8. Click **Connect**.

Configuring TightVNC Server to Start Automatically

Note: *Only administrator-level users can configure the TightVNC Server to start automatically.*

By default, the TightVNC Server is not started automatically when you turn on your unit. However, you can modify this setting. This is especially useful if you need to remotely connect to your unit without having the unit close at hand. To benefit from all the advantages of this feature, you may also want to enable the automatic logon (see *Enabling or Disabling the Automatic Logon* on page 62). Otherwise, you will need to manually connect to a user account before the TightVNC Server could be started.



IMPORTANT

The passwords that you set for the application that is started automatically are independent of the passwords that you set for the application that you start manually (via the Utilities tab). This means that you could need to enter different passwords, depending on which TightVNC application you use to connect to your unit.


If you do not want to manage two different sets of passwords, you can set all passwords to the same value.

Accessing Your Unit Remotely


Configuring TightVNC Server to Start Automatically

To configure TightVNC server to start automatically:

1. On your unit, from the **Main Menu**, select **System Settings**.
2. Tap **Remote Session**.




3. Select the **Start TightVNC Server automatically at unit startup** check box.



4. When the unit prompts you, tap **Yes** to configure the TightVNC passwords (and other parameters) if necessary.

The new parameters are now taken into account. For more information on how to connect to your unit, see *Connecting to Your Unit with TightVNC* on page 169.

5. Tap  to return to the Mini Toolbox window.

Adding Exceptions to the Firewall


Note: Only administrator-level users can add exceptions to the firewall.

Your unit is protected by the Microsoft firewall to prevent unauthorized access when it is connected to a network or to the Internet. The firewall has been preconfigured so that all the applications that come with your unit work properly. However, you can allow other applications to access the network or the Internet by adding exceptions.

If you are not sure about how to configure the firewall, contact your network administrator.

To add exceptions to the firewall:


1. On your unit, from the **Main Menu**, tap **Setup**.
2. Double-tap **Windows Firewall**.



Accessing Your Unit Remotely

Adding Exceptions to the Firewall

3. Select the **Exceptions** tab.



4. Tap **Add Program** to add any application that you need.
5. When you have finished, tap **OK** (located at the bottom of the dialog box) to confirm the changes and return to the **Control Panel** window.

10 *Testing Network Connections*

Note: *This function is available with the optional IPT software package only.*

The two most common basic tests widely used in networking are the *ping* test and the *trace route* test. With these tests, you can ensure that IP packets travel as expected from a local host to a remote host and vice versa.



IMPORTANT

To avoid misleading results, always ensure that your unit is only connected to one network at a time (either standard Ethernet or wireless network) before performing ping or trace route tests.

Performing a Ping Test

The ping test is a basic test that measures the average time it takes for a packet to reach the remote host. With this test, you can quickly verify that the remote host functions properly.

The ping test has six common parameters:

- The URL (IP address)
- The number of packets to send
- The packet size
- The maximum time allowed for a packet to reach the remote host
- The maximum number of hops allowed for reaching the remote host (TTL)
- A flag to indicate whether a packet can be fragmented.


When the test is complete, you can export the results. You can later import the generated text file (tab-delimited) directly into Microsoft Excel.

Testing Network Connections

Performing a Ping Test

To perform a ping test:

1. From Mini Toolbox, select the **Test Tools** tab, then tap **IP Tools**.



2. From **IP Testing Tools**, select the **Ping** tab.

3. Enter a URL or an IP address to reach. You can tap the **Default** button to use the unit's default ping address. The default value cannot be configured.

The screenshot shows the 'IP Testing Tools' application interface. At the top, there are two tabs: 'Ping' (selected) and 'Trace Route'. Below the tabs, the 'Results' section contains a table with columns: '#', 'TTL (hops)', 'RTT (ms)', and 'From'. To the right of the table is a 'Statistics' section with labels for 'Packets', 'Sent', 'Received', 'Lost', 'Time (ms)', 'Min.', 'Max.', and 'Average', each followed by a dash. Below the results and statistics, there is a 'URL or IP address:' field with a 'Default' button next to it. Below this are four rows of controls: 'Packets to send:' with a minus button, a field containing '4', and a plus button; 'Packets size (bytes):' with a minus button, a field containing '32', and a plus button; 'Timeout (ms):' with a minus button, a field containing '1000', and a plus button; and 'Time to live (hops):' with a minus button, a field containing '255', and a plus button. At the bottom left is a checkbox labeled 'Allow fragmentation' which is checked. On the right side of the screen is a vertical sidebar with buttons for 'Start', 'Main Menu', 'Export', and 'About'. At the very bottom of the sidebar are three small icons: a keyboard, a globe, and a red 'X'.

4. Set the other parameters:
 - Number of packets to send
 - Packet size
 - Timeout limit
 - TTL limit
 - Clear the **Allow fragmentation** check box if you prefer sending complete packets to the host.
5. Tap the **Start** button.

You can stop a ping test at any time by tapping the **Stop** button.

Performing a Trace Route Test

The trace route test is used to evaluate the average number of nodes that are required to reach the final host. It is often used to troubleshoot networks (identify accesses blocked by firewalls or routing problems).

This trace route test utility enables you to:

- Enter a remote host address.
- Set the maximum time allowed for a packet to reach the remote host.
- Set the maximum number of hops allowed for reaching the remote host (TTL).
- Choose whether to resolve DNS for the IP address or not.

When the test is complete, you can export the results. You can later import the generated text file (tab-delimited) directly into Microsoft Excel.

To perform a trace route test:

1. From **IP Testing Tools**, select the **Trace Route** tab.
2. Enter an URL or an IP address to reach. You can tap the **Default** button to use the unit's default trace route address. The default value cannot be configured.

The screenshot shows the 'IP Testing Tools' application interface. The 'Trace Route' tab is selected. The 'Results' section displays a table with columns: Hop, RTT (ms), RTT (ms), RTT (ms), IP Address, and Domain Name. Below the table is a 'Statistics' section with the following data:

Statistics	
Packets	
Sent:	0
Received:	0
Lost:	0
Final IP address:	0.0.0.0

At the bottom, there are input fields for 'URL or IP address', 'Timeout (ms)' (set to 1000), and 'Time to live (hops)' (set to 30). A 'Default' button is next to the URL field, and a 'Resolve IP addresses' checkbox is at the bottom. A sidebar on the right contains 'Start', 'Main Menu', 'Export', and 'About' buttons.

3. Set the other parameters:
 - Timeout limit
 - TTL limit
 - Select or clear the **Resolve IP addresses** check box if you want to get the host name for the corresponding IP address of nodes.
4. Tap the **Start** button.

You can stop a trace route test at any time by tapping the **Stop** button.

Exporting the Results

When a test is complete, you can export the results of the current test page. If you want to keep your results for future use, you must export them because result files cannot be opened directly from your unit.

Results are sent to a text file. Fields are separated by the “TAB” character to simplify the importation into a Microsoft Excel worksheet.

By default, the application suggests a file name:

- For ping tests:

Ping for [URL] on [YEAR]_[MONTH]_[DAY].txt

- For trace route tests:

Trace Route for [URL] on [YEAR]_[MONTH]_[DAY].txt

Where:

- [URL] is the entered URL or IP address,
- [YEAR] is the year of the test,
- [MONTH] is the month of the test,
- [DAY] is the day of the test.

Example:

For a ping test at www.yoursite.org made on January 3rd, 2010, the suggested filename would be:

Ping for www.yoursite.org on 2010_01_03.txt

To export results:

Tap the **Export** button. If necessary, modify the suggested file name.

11 *Maintenance*

To help ensure long, trouble-free operation:

- Always inspect fiber-optic connectors before using them and clean them if necessary.
- Keep the unit free of dust.
- Clean the unit casing and front panel with a cloth slightly dampened with water.
- Store unit at room temperature in a clean and dry area. Keep the unit out of direct sunlight.
- Avoid high humidity or significant temperature fluctuations.
- Avoid unnecessary shocks and vibrations.
- If any liquids are spilled on or into the unit, turn off the power immediately, disconnect from any external power source, remove the batteries and let the unit dry completely.



WARNING

The use of controls, adjustments and procedures, namely for operation and maintenance, other than those specified herein may result in hazardous radiation exposure or impair the protection provided by this unit.

Cleaning Detector Ports

Regular cleaning of detectors will help maintain measurement accuracy.



IMPORTANT

Always cover detectors with protective caps when unit is not in use.

To clean detector ports:

1. Remove the protective cap and adapter (FOA) from the detector.
2. If the detector is dusty, blow dry with compressed air.
3. Being careful not to touch the soft end of the swab, moisten a cleaning tip with *only one drop* of isopropyl alcohol.



IMPORTANT

Alcohol may leave traces if used abundantly. Do not use bottles that distribute too much alcohol at a time.

4. While applying light pressure (to avoid breaking the detector window), gently rotate the cleaning tip on the detector window.
5. Repeat step 4 with a dry cleaning tip or blow dry with compressed air.
6. Discard the cleaning tips after one use.

Cleaning the Touchscreen of Your FTB-1 Unit

Clean the touchscreen with a soft, non-abrasive cloth, such as one used for cleaning reading glasses, dampened with water.



CAUTION

Using anything else than water can damage the special coating of the touchscreen.

Recharging the Main Battery

The main lithium-ion battery is offered in two sizes:

- A four-cell (small) battery
- An eight-cell (large) battery

The clock battery is recharged automatically along with the main battery.

- In Mini Toolbox, the charge status is shown above **Main Menu**.
- The unit also indicates the charge status with the LED on its front panel (see *LED Indicators Description* on page 5):

Status LED	Battery Charge Status
Green	Fully charged
Green, blinking	Charging
Red	Error or battery is not in the unit



CAUTION

Only charge the battery with the AC adapter/charger (or the car outlet adapter) provided by EXFO with your unit.

Maintenance

Recharging the Main Battery



IMPORTANT

- Batteries are not charged at the factory. Install the battery compartment on your unit (see *Replacing Batteries* on page 188), and then fully charge the battery before using the unit for the first time. The battery is fully charged after a few hours or when the battery LED indicator stops flashing.
- The time required to charge batteries depends on various factors such as the type of modules currently in use and the ambient temperature.
- To ensure that batteries function or charge properly, keep them in temperatures between 10 °C and 40 °C (50 °F and 104 °F). Store below 50 °C (122 °F).
- Depending on the way the unit is used, after a while, the charge status icon may no longer correspond to the actual power level of the battery (for example, icon indicates that power level is sufficient, but unit turns off because battery is too weak). A complete calibration cycle will be necessary (see *Recalibrating the Battery* on page 185).

To recharge the main battery:

Connect the unit to a power outlet using the AC adapter/charger. The charge cycle will start and end automatically.

Recalibrating the Battery

Depending on the way the unit is used, after a while, the charge status icon may no longer correspond to the actual power level of the battery (for example, the battery level icon indicates that power level is sufficient, but unit turns off because battery is too weak). A complete calibration cycle will be necessary.



IMPORTANT

When the estimate offset value (displayed in the battery calibration application) is of 10 % or more, EXFO recommends that you recalibrate the battery.

You can perform a recalibration with the battery calibration utility:

- The utility will charge the battery until it is full.
- It will then discharge the battery completely.
- You will have to let the battery recharge completely.

The whole calibration process can take several hours. You can stop the process at any time, but the battery will still need calibration and the battery will not necessarily be full (depending on the moment at which you stop the process).


When a calibration step is underway, the LED preceding the step name appears in yellow. When a step is complete, the LED turns to green.

Maintenance

Recalibrating the Battery

To recalibrate the batteries:


1. From the **Main Menu**, select **Setup**, and then double-tap **Battery Calibration**.



2. Connect the AC adapter/charger to your unit.

3. Tap the **Start Calibration** button (the **Stop Calibration** button will become available).

Once calibration is complete, the **Start Calibration** button becomes available again.



Replacing Batteries

Your unit uses batteries with built-in protection that have been especially designed for EXFO. For this reason, you can only replace the main battery with a battery designed for your FTB-1.

You can purchase new batteries and empty battery compartments (also known as “battery covers”) from EXFO.

The main lithium-ion battery is offered in two sizes:

- A four-cell (small) battery
- An eight-cell (large) battery

Note: *Since the battery must fit in the battery compartment, these compartments are also offered in two sizes.*

Note: *Batteries and battery compartments are sold separately, which means you can purchase extra batteries to use with a battery compartment that you already have. The size of the battery must match the size of the compartment.*



CAUTION

Use Li-Ion batteries of the same type and model only. Use of other batteries may damage your unit and compromise your safety.




WARNING

Do not throw batteries into fire or water and do not short-circuit the battery's electrical contacts. Do not disassemble.

To remove the main battery:

1. Turn off the unit.
2. Remove the battery compartment (located next to the module) as follows:

- 2a.** Position the unit so that its front panel rests on a flat surface such as a table.
- 2b.** Lift the mobile part of the battery compartment screws and turn the screws counterclockwise until the compartment is loose. Since they are captive screws, you cannot remove them completely.



CAUTION

Shocks and drops may have loosened the battery inside its compartment.

To avoid irremediable damage to the battery, always remove the battery compartment carefully, ensuring that the battery does not fall.

- 2c.** Hold the battery compartment by its sides and pull it up carefully.

Maintenance

Replacing Batteries

3. If necessary, release the battery from its compartment as follows:
 - 3a. Position the battery compartment so that the battery is facing you.
 - 3b. Pull on the battery tab to free the battery from its socket.

You are now ready to replace the battery.

To replace (or install) the main battery:

1. If you do not have a replacement battery, contact EXFO to purchase a new one.
2. Position the battery compartment so that you can view its hollow part.




IMPORTANT

Always use a battery whose size corresponds to the size of the battery compartment.

3. Install the battery as follows:

3a. Insert the new battery, respecting the polarity. You can use the image appearing inside the compartment as a guide.



Note: *When the battery is correctly positioned, its poles should be facing upwards and be placed on the same side as shown on the illustration in the battery compartment.*

3b. Apply slight pressure to the battery to secure it in place.

- 4.** Position the battery compartment so that you can see the two screws.
- 5.** Place the battery compartment on the platform, making sure that the bumpers and the shorter sides of the compartment are flush with those of the platform. If necessary, slightly move the battery compartment until alignment is correct.
- 6.** Lift the mobile part of the compartment screws and, while applying slight pressure, turn the screws clockwise until they are tightened.

Note: *You cannot replace the clock battery yourself.*

Recalibrating the Unit

EXFO manufacturing and service center calibrations are based on the ISO/IEC 17025 standard (*General Requirements for the Competence of Testing and Calibration Laboratories*). This standard states that calibration documents must not contain a calibration interval and that the user is responsible for determining the re-calibration date according to the actual use of the instrument.

The validity of specifications depends on operating conditions. For example, the calibration validity period can be longer or shorter depending on the intensity of use, environmental conditions and unit maintenance, as well as the specific requirements for your application. All of these elements must be taken into consideration when determining the appropriate calibration interval of this particular EXFO unit.

Under normal use, the recommended interval for your FTB-1 is: one year.

For newly delivered units, EXFO has determined that the storage of this product for up to six months between calibration and shipment does not affect its performance (EXFO Policy PL-03).

To help you with calibration follow-up, EXFO provides a special calibration label that complies with the ISO/IEC 17025 standard and indicates the unit calibration date and provides space to indicate the due date. Unless you have already established a specific calibration interval based on your own empirical data and requirements, EXFO would recommend that the next calibration date be established according to the following equation:

Next calibration date = Date of first usage (if less than six months after the calibration date) + Recommended calibration period (one year)

To ensure that your unit conforms to the published specifications, calibration may be carried out at an EXFO service center or, depending on the product, at one of EXFO's certified service centers. Calibrations at EXFO are performed using standards traceable to national metrology institutes.

Note: *You may have purchased a FlexCare plan that covers calibrations. See the Service and Repairs section of this user documentation for more information on how to contact the service centers and to see if your plan qualifies.*

Recycling and Disposal (Applies to European Union Only)

For complete recycling/disposal information as per European Directive WEEE 2012/19/UE, visit the EXFO Web site at www.exfo.com/recycle.

12 *Troubleshooting*





Solving Common Problems

Problem	Cause	Solution
Unit does not turn on.	Battery is discharged.	<ul style="list-style-type: none">➤ Charge the battery.➤ Replace the battery with a fully charged one.➤ Connect the unit to an external power supply using the AC adapter/charger.
	Unit is not connected to an external power supply.	Connect the unit to an external power supply using the AC adapter/charger.
	External power supply is disconnected.	Make sure the external power supply is connected at both ends.
Unit screen is dark.	Unit's backlight is off.	Press the backlight button.
	Battery is discharged and unit has shut down.	<ul style="list-style-type: none">➤ Charge the battery.➤ Replace the battery with a fully charged one.➤ Connect the unit to an external power supply using the AC adapter/charger.
At logon, no scroll bar is displayed to browse through all user accounts.	---	Select any of the user accounts that you can see on screen, and then press the down arrow (from the unit's keypad) to go to the next account. Use the up/down arrows to browse through the accounts.

Troubleshooting

Solving Common Problems

Problem	Cause	Solution
The System Settings window is not displayed correctly when you control the unit via Remote Desktop.	---	<ul style="list-style-type: none">➤ Ensure that the System Settings window is closed <i>before</i> you connect to the unit with Remote Desktop. OR <ul style="list-style-type: none">➤ If you are already connected to the unit with Remote Desktop, close the System Settings window, and then reopen it.
Some applications are not displayed correctly when you connect to the unit with Remote Desktop.	On your computer, the screen resolution that has been selected at the time of connection is too high.	On your computer, select a lower screen resolution in the Remote Desktop options <i>before</i> connecting to your unit.
External keyboard is not working.	External keyboard has not been detected.	<ul style="list-style-type: none">➤ Disconnect the keyboard, and then connect it again.➤ Turn off the unit, connect the keyboard, and turn on the unit.
Screen characters are dim.	Brightness is not set properly.	Adjust brightness.
Module is not detected.	The module's application has not been installed yet on your unit or the module's application is not up-to-date.	Ensure that the latest version for your module's application is available on your unit (see the <i>Installing or Upgrading the Applications</i> section).

Problem	Cause	Solution
One of the applications is not responding.		Press  and hold it down until the shutdown menu appears, then select Turn off . Turn the unit on again to reset it.
Impossible to calibrate the touchscreen via the calibration application in System Settings .	Screen calibration is very poor.	<ul style="list-style-type: none"> ➤ Press  and hold it down until the shutdown menu appears, then select Turn off. ➤ Turn on the unit. <p>While the system is displaying the boot menu (3 seconds), press the down arrow from the unit's keypad to select the emergency system tools operation mode.</p> <p>OR</p> <p>Press the ARROW DOWN key on the keyboard (if you have connected one).</p> <ul style="list-style-type: none"> ➤ Press  from the unit's keypad or ENTER on your keyboard to confirm your choice. ➤ Press  to start the screen calibration.
Unit's operating time is reduced.	Battery is probably worn out.	Replace the battery.
	Battery was not fully charged.	<ul style="list-style-type: none"> ➤ Charge the battery. ➤ Perform a complete battery calibration cycle^a.
Battery indicator remains low after a full charge.	Battery is not completely charged.	Perform a complete battery calibration cycle ^a .

Troubleshooting

Solving Common Problems

Problem	Cause	Solution
Batteries are not charging.	Ambient temperature is too high or too low.	Ensure that the temperature in the location where you charge the batteries is within the specifications.
	AC adapter/charger is not connected properly.	Ensure that the adapter/charger is connected both to your unit and the power outlet.
Unit switches to standby or hibernation mode unexpectedly.	Power schemes are not defined correctly.	Select one of the predefined power schemes (Always On or Max Battery). For more information, see the <i>Configuring the Power Management Options</i> section.
Unit is not responding.		<p>If you were not trying to install a VPN client and your unit stopped responding, restore your unit.</p> <p>To do so, see the <i>Restoring Your Unit to Normal Operation</i> section.</p> <p>If you were trying to install a VPN client, restart your unit and start a new installation. If the problem persists, restore your unit.</p>

Problem	Cause	Solution
The 3G USB modem key is connected, but you are not able to access the Internet.	➤ There is no SIM card in the USB modem key.	Insert the SIM card into the USB modem key. For complete instructions, refer to the documentation that came with your modem key.
	➤ The FTB-1 unit is not up to date.	Ensure that the latest System Upgrade and Platform kits are installed on your unit before connecting your USB modem key. For more information, see the <i>Accessing the Internet with a 3G USB Modem Key</i> section.
	➤ The USB modem key is not detected properly.	Disconnect the modem key from your unit, and try connecting it again. If the modem key is still not detected, try connecting it to another USB port.
	➤ The SIM card has not been activated or there is a problem with service package that you purchased.	Contact your provider of mobile services.
	➤ The SIM card is locked.	
	➤ There is a problem with the mobile network.	
The GPS USB key is not detected.	---	Disconnect the GPS key from your unit, and try connecting it again. If the GPS key is still not detected, try connecting it to another USB port.

Troubleshooting

Solving Common Problems

Problem	Cause	Solution
Problems or errors occurred during the installation of the VPN client.	---	Restart your unit and start a new installation. If the problem persists, restore your unit. To do so, see the <i>Restoring Your Unit to Normal Operation</i> section.
You want to change your VPN client for another client. OR You need to remove the VPN client from your unit.	---	Restore your unit. To do so, see the <i>Restoring Your Unit to Normal Operation</i> section.
The VPN client has been updated accidentally.	---	Restore your unit. To do so, see the <i>Restoring Your Unit to Normal Operation</i> section.

- a. A complete battery calibration cycle consists of a full charge, immediately followed by a full discharge, then followed by a full charge.

Restoring Your Unit to Normal Operation

Your FTB-1 is set to start using the standard Windows startup sequence. However, you can also use the emergency system tools feature if you need to:

- check the disk integrity
- back up some files directly onto a USB storage device for recovery purposes
- revert your unit to its initial state (as it was when you purchased it) or restore it with a specific Windows image (WIM) that could have been provided to you by EXFO customer service, for example.



IMPORTANT

The restoration of the system partition cannot be undone or stopped once it is started.

If you have installed other products that are not included in your image file, you will have to reinstall them afterwards.



To avoid losing the data that is stored on the D drive, you may want to back it up before restoring the system partition. Otherwise, all your files will be lost.

Note: *You may find useful to connect a keyboard and a mouse to your unit before using the emergency system tools.*

Troubleshooting

Restoring Your Unit to Normal Operation


To navigate in the various windows using the unit's keypad:

- Use up/down and left/right arrows.
- You can also press  to go to the next group of features (equivalent of the TAB key).
- Press  to select an item (equivalent of the ENTER key).

To restore the system partition:


1. Turn on the FTB-1.
2. While the system is displaying the boot menu (3 seconds), press the down arrow from the unit's keypad to select the *Maintenance and recovery* mode.

OR

Press the ARROW DOWN key on the keyboard (if you have connected one).
3. Press  from the unit's keypad or ENTER on your keyboard to confirm your choice.

Note: *The touchscreen becomes effective at this point.*


4. From the main window, select **Restore system partition from an image**, then tap **Next**.



5. If you want to revert your unit to its initial state (most cases), select **Factory recovery image**.

OR


If you prefer to use an image file (provided by customer service, for example), select **.wim** file and use the **Browse** button to locate the file.



Troubleshooting

Restoring Your Unit to Normal Operation

6. Tap **Next** to proceed to the next step.



7. Tap **Next** to start the restoration process. The unit will restart upon completion of the process.

To retrieve data from the D drive:

1. Turn on the FTB-1.
2. While the system is displaying the boot menu (3 seconds), press the down arrow from the unit's keypad to select the *Maintenance and recovery* mode.


OR

Press the ARROW DOWN key on the keyboard (if you have connected one).

3. Press ✓ from the unit's keypad or ENTER on your keyboard to confirm your choice.

Note: The touchscreen becomes effective at this point.

4. From the main window, select **Backup data and configuration files to USB flash drive**, then tap Next.




Troubleshooting

Restoring Your Unit to Normal Operation


5. Select the files to back up.

A check mark indicates a selection of the entire folder (subfolders and files). A shaded check box indicates that not all of the files of subfolders are selected.



6. If the USB device you want to use is not connected to the unit, connect it now so that the system can find it. Tap **Next**.

7. Select the USB device onto which you want to save the data from the list of available devices.



Note: *If you have forgotten to connect the USB device at this point and that it does not show up in the list, tap **Back**, connect the device, then tap **Next** to return to this window.*

8. Tap **Next** to start the file copy process.

A progress bar indicates which files are being copied. If you tap **Cancel** while the transfer is in progress, any file that was copied onto the USB device will still be on the USB device.

9. Once the transfer is complete, tap **Cancel** to return to the main window.

Troubleshooting

Restoring Your Unit to Normal Operation

To verify disk integrity:

1. Turn on the FTB-1.
2. While the system is displaying the boot menu (3 seconds), press the down arrow from the unit's keypad to select the *Maintenance and recovery* mode.


OR

Press the ARROW DOWN key on the keyboard (if you have connected one).


3. Press ✓ from the unit's keypad or ENTER on your keyboard to confirm your choice.

Note: *The touchscreen becomes effective at this point.*

4. From the main window, select **Check disk integrity**, then tap **Next**.



5. Tap **Next** to start the disk analysis.



Once the analysis is complete, you can view a report on each drive by tapping **Details**.

6. Tap **OK** once you have finished.
7. To exit the integrity analysis tool, tap **Cancel** to return to the main window.

Contacting the Technical Support Group

To obtain after-sales service or technical support for this product, contact EXFO at one of the following numbers. The Technical Support Group is available to take your calls from Monday to Friday, 8:00 a.m. to 7:00 p.m. (Eastern Time in North America).

Technical Support Group

400 Godin Avenue
Quebec (Quebec) G1M 2K2
CANADA

1 866 683-0155 (USA and Canada)
Tel.: 1 418 683-5498
Fax: 1 418 683-9224
support@exfo.com

For detailed information about technical support, and for a list of other worldwide locations, visit the EXFO Web site at www.exfo.com.

If you have comments or suggestions about this user documentation, you can send them to customer.feedback.manual@exfo.com.

To accelerate the process, please have information such as the name and the serial number (see the product identification label), as well as a description of your problem, close at hand.

Transportation

Maintain a temperature range within specifications when transporting the unit. Transportation damage can occur from improper handling. The following steps are recommended to minimize the possibility of damage:

- Pack the unit in its original packing material when shipping.
- Avoid high humidity or large temperature fluctuations.
- Keep the unit out of direct sunlight.
- Avoid unnecessary shocks and vibrations.

13 **Warranty**

General Information

EXFO Inc. (EXFO) warrants this equipment against defects in material and workmanship for a period of one year from the date of original shipment. EXFO also warrants that this equipment will meet applicable specifications under normal use.

During the warranty period, EXFO will, at its discretion, repair, replace, or issue credit for any defective product, as well as verify and adjust the product free of charge should the equipment need to be repaired or if the original calibration is erroneous. If the equipment is sent back for verification of calibration during the warranty period and found to meet all published specifications, EXFO will charge standard calibration fees.



IMPORTANT

The warranty can become null and void if:

- unit has been tampered with, repaired, or worked upon by unauthorized individuals or non-EXFO personnel.
- warranty sticker has been removed.
- case screws, other than those specified in this guide, have been removed.
- case has been opened, other than as explained in this guide.
- unit serial number has been altered, erased, or removed.
- unit has been misused, neglected, or damaged by accident.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL EXFO BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

Warranty

Liability

Liability

EXFO shall not be liable for damages resulting from the use of the product, nor shall be responsible for any failure in the performance of other items to which the product is connected or the operation of any system of which the product may be a part.

EXFO shall not be liable for damages resulting from improper usage or unauthorized modification of the product, its accompanying accessories and software.

Exclusions

EXFO reserves the right to make changes in the design or construction of any of its products at any time without incurring obligation to make any changes whatsoever on units purchased. Accessories, including but not limited to fuses, pilot lamps, batteries and universal interfaces (EUI) used with EXFO products are not covered by this warranty.

This warranty excludes failure resulting from: improper use or installation, normal wear and tear, accident, abuse, neglect, fire, water, lightning or other acts of nature, causes external to the product or other factors beyond the control of EXFO.



IMPORTANT

In the case of products equipped with optical connectors, EXFO will charge a fee for replacing connectors that were damaged due to misuse or bad cleaning.

Certification

EXFO certifies that this equipment met its published specifications at the time of shipment from the factory.

Service and Repairs

EXFO commits to providing product service and repair for five years following the date of purchase.

To send any equipment for service or repair:

- 1.** Call one of EXFO's authorized service centers (see *EXFO Service Centers Worldwide* on page 215). Support personnel will determine if the equipment requires service, repair, or calibration.
- 2.** If equipment must be returned to EXFO or an authorized service center, support personnel will issue a Return Merchandise Authorization (RMA) number and provide an address for return.
- 3.** If possible, back up your data before sending the unit for repair.
- 4.** Pack the equipment in its original shipping material. Be sure to include a statement or report fully detailing the defect and the conditions under which it was observed.
- 5.** Return the equipment, prepaid, to the address given to you by support personnel. Be sure to write the RMA number on the shipping slip. *EXFO will refuse and return any package that does not bear an RMA number.*

Note: *A test setup fee will apply to any returned unit that, after test, is found to meet the applicable specifications.*

After repair, the equipment will be returned with a repair report. If the equipment is not under warranty, you will be invoiced for the cost appearing on this report. EXFO will pay return-to-customer shipping costs for equipment under warranty. Shipping insurance is at your expense.

Routine recalibration is not included in any of the warranty plans. Since calibrations/verifications are not covered by the basic or extended warranties, you may elect to purchase FlexCare Calibration/Verification Packages for a definite period of time. Contact an authorized service center (see *EXFO Service Centers Worldwide* on page 215).

EXFO Service Centers Worldwide

If your product requires servicing, contact your nearest authorized service center.

EXFO Headquarters Service Center

400 Godin Avenue
Quebec (Quebec) G1M 2K2
CANADA

1 866 683-0155 (USA and Canada)
Tel.: 1 418 683-5498
Fax: 1 418 683-9224
support@exfo.com

EXFO Europe Service Center

Winchester House, School Lane
Chandlers Ford, Hampshire S053 4DG
ENGLAND

Tel.: +44 2380 246800
Fax: +44 2380 246801
support.europe@exfo.com

EXFO Telecom Equipment (Shenzhen) Ltd.

3rd Floor, Building 10,
Yu Sheng Industrial Park (Gu Shu
Crossing), No. 467,
National Highway 107,
Xixiang, Bao An District,
Shenzhen, China, 518126

Tel: +86 (755) 2955 3100
Fax: +86 (755) 2955 3101
support.asia@exfo.com

A Technical Specifications



IMPORTANT

The following technical specifications can change without notice. The information presented in this section is provided as a reference only. To obtain this product's most recent technical specifications, visit the EXFO Web site at www.exfo.com.

TECHNICAL SPECIFICATIONS	
Display	Touchscreen, color, 800 x 480 TFT, 178 mm (7 in)
Interfaces	Two USB 2.0 ports RJ-45 LAN 10/100/1000 Mbit/s Fiber inspection probe connector port (video) Built-in Bluetooth and Wi-Fi (hardware option)
Storage	8 GB internal memory (flash) 16 GB internal memory (flash), optional
Batteries	Rechargeable lithium-ion batteries 8 hours of operation as per Telcordia* (Bellcore) TR-NWT-001138
Power supply	Unit: ---- 24 V; 3.75 A AC adapter: ~ 100 - 240 V; 50/60 Hz, 1.6 A
Computer	Intel ATOM processor Windows Embedded Standard operating system

GENERAL SPECIFICATIONS	
Size (H x W x D)	190 mm x 252 mm x 66 mm (7 1/2 in x 9 15/16 in x 2 5/8 in)
Weight (with battery)	1.5 kg (3.3 lb)
Temperature Operation	Battery operated: 0 °C to 50 °C (32 °F to 122 °F) Charge mode: 5 °C to 40 °C (41 °F to 104 °F)
Storage	unit: -40 °C to 70 °C (-40 °F to 158 °F) ^b unit: -20 °C to 60 °C (-4 °F to 140 °F) with the battery pack AC adapter: -20 °C to 60 °C (-4 °F to 140 °F)
Relative humidity	0 % to 95 % non-condensing

ACCESSORIES			
FP4S	400x fiber inspection probe	GP-2028	Computer security cable kit
FP4D	200x/400x fiber inspection probe	GP-2112	3G Universal USB dongle
GP-10-086	Rigid FTB-1 carrying case	GP-2113	GPS USB dongle
GP-10-072	Semi-rigid FTB-1 carrying case	GP-2137	USB-to-RS-232 converter
GP-302	USB mouse	GP-2138	DC car adapter/inverter
GP-1002	Headset	GP-2144	USB 16G micro-drive
GP-1008	VFL adapter (2.5 mm to 1.25 mm)	GP-2155	Carry-on size backpack ^c
GP-2001	USB keyboard	GP-2158	FTB-1 utility glove
GP-2016	10 feet RJ-45 LAN cable	GP-2200	Module receptacle back panel

Technical Specifications

PM-1 BUILT-IN POWER METER SPECIFICATIONS^d

Calibrated wavelengths (nm)	850, 1300, 1310, 1490, 1550, 1625, 1650
Optional CWDM calibrated wavelengths (nm)	1270, 1290, 1310, 1330, 1350, 1370, 1390, 1410, 1430, 1450, 1470, 1490, 1510, 1530, 1550, 1570, 1590, 1610, 1383, 1625
Power range (dBm)	10 to -86 (InGaAs) 26 to -64 (GeX)
Uncertainty (%) ^a	±5 % ± 3 pW (InGaAs) ±5 % ± 0.4 nW (GeX)
Display resolution (dB)	
InGaAs	0.01 = max to -76 dBm 0.1 = -76 dBm to -86 dBm 1 = -86 dBm to min
GeX	0.01 = max to -54 dBm 0.1 = -50 dBm to -60 dBm 1 = -60 dBm to min
Automatic offset nulling range ^f	Max power to -63 dBm for InGaAs Max power to -40 dBm for GeX
Tone detection (Hz)	270/1000/2000

VISUAL FAULT LOCATOR (VFL) (OPTIONAL)

Laser, 650 nm ± 10 nm
CW
Typical P _{out} in 62.5/125 µm: 3 dBm (2 mW)

Notes

- a. With optional extended-life battery.
- b. -20 °C to 60 °C (-4 °F to 140 °F) with the battery pack.
- c. The selected model may change without notice.
- d. At 23 °C ±1 °C, 1550 nm and FC connector. With modules in idle mode. Battery operated.
- e. Up to 5 dBm.
- f. For ±0.05 dB, from 18 °C to 28 °C.

LASER SAFETY



Index

3G USB modem, using 106

A

AC requirements 16
 accessing
 Internet with a 3G USB modem 106
 power meter 117
 adapter 15
 after-sales service 210
 application, starting 47

B

battery
 charge status 183
 clock 80
 maintenance recommendations 183
 recharging 184
 replacing or removing 188
 browsing Web 104

C

calibrating the touchscreen 54
 Canadian Standards Association (CSA) ix
 capacitors 14
 capturing images 93
 car outlet, charging battery with 184
 caution
 of personal hazard 9
 of product hazard 9
 certification information viii
 changing batteries 188
 charger 15
 checking data integrity 208

cleaning
 detector ports 182
 front panel 181
 touchscreen 183
 connecting to a VPN 149
 ConnectorMax 119
 conventions, safety 9
 coordinates, GPS 112
 creating PDF files 89
 CSA ix
 current, electrical 16
 customer service 214

D

data
 integrity 208
 retrieving 205
 defining personal folders 143
 description, keypad 6
 detecting module 20
 detector port, cleaning 182
 documents, printing 89
 dongle
 3G USB 106
 GPS 112
 dual-boot 201

E

emergency system tools 201
 equipment returns 214
 Explorer, Internet 104
 exporting results 180
 external power supply 15

Index

F

fiber inspection probe	119
file	
format	180
name	180
FIP	119
Flash Player, installing	102
folders, removing	143
front panel, cleaning	181

G

GPS coordinates	112
-----------------------	-----

H

hazard, laser radiation	13
-------------------------------	----

I

identification label	210
image formats	96
input current	16
inserting a module	19
inspecting fibers	119
installing	
Flash Player	102
VPN clients	149
integrity, data	208
Internet	
connection	106
Explorer	104

K

keypad description	6
--------------------------	---

L

label, identification	210
laser safety information	13
localizing your unit	112
longitude and latitude	112

M

maintenance	
battery	183
detector ports	182
front panel	181
general information	181
touchscreen	183
maximum input current	16
modifying storage parameters	96
module	
detection	20
insertion	19
removal	19

N

navigating the Internet	104
-------------------------------	-----

O

options	
software	42
used at startup	65
other tools, accessing	116

P

parameters	
for ping	175
for trace route	178
PDF files, generating	89
ping, performing a test	175
power	
sources	16
supply	15
power button	6
power meter, accessing	117
predefined folders	143
printing documents	89
probe	119
product	
identification label	210
specifications	217

protective cap 182
purchased options..... 42

R

radiation hazard, laser..... 13
reading Flash files..... 102
removing a module 19
repairing unit 14
replacing or removing battery..... 188
restoring system partition 202
retrieving
 data 205
 position of unit 112
return merchandise authorization (RMA) .. 214

S

safety
 caution 9
 conventions 9
 information 13
 warning 9
saving test results..... 180
screenshots, taking 93
service and repairs..... 214
service centers 215
shipping to EXFO 214
software
 options 42
 options at startup..... 65
software. see application
specifications, product 217
startup option 65
storage requirements 181
storage, path..... 96
surfing the Internet 104
symbols, safety..... 9
system
 emergency tools 201
 partition, restoring 202

T

technical specifications..... 217
technical support..... 210
temperature for storage 181
tools system, emergency 201
touchscreen
 calibrating 54
 cleaning 183
trace route, performing a test 178
transportation requirements..... 181, 210

U

unit
 localizing..... 112
 repairing 14
 restoring 202
using a 3G USB modem..... 106

V

virtual private network (VPN)..... 149

W

warranty
 certification..... 213
 exclusions 213
 general..... 211
 liability 212
 null and void..... 211
Web browser 104
wireless connection 106

NOTICE
通告

CHINESE REGULATION ON RESTRICTION OF HAZARDOUS SUBSTANCES
中国关于危害物质限制的规定



NAMES AND CONTENTS OF THE TOXIC OR HAZARDOUS SUBSTANCES OR ELEMENTS
CONTAINED IN THIS EXFO PRODUCT
包含在本 EXFO 产品中的有毒有害物质或元素的名称和含量

O	Indicates that this toxic or hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in SJ/T11363-2006 表示该有毒有害物质在该部件所有均质材料中的含量均在 SJ/T11363-2006 标准规定的限量要求以下。
X	Indicates that this toxic or hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement in SJ/T11363-2006 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出 SJ/T11363-2006 标准规定的限量要求。

Part Name 部件名称	Toxic or hazardous Substances and Elements 有毒有害物质和元素					
	Lead 铅 (Pb)	Mercury 汞 (Hg)	Cadmium 镉 (Cd)	Hexavalent Chromium 六价铬 (Cr VI)	Polybrominated biphenyls 多溴联苯 (PBB)	Polybrominated diphenyl ethers 多溴二苯醚 (PBDE)
Enclosure 外壳	O	O	O	O	O	O
Electronic and electrical sub-assembly 电子和电子组件	X	O	X	O	X	X
Optical sub-assembly ^a 光学组件 ^a	X	O	O	O	O	O
Mechanical sub-assembly ^a 机械组件 ^a	O	O	O	O	O	O

- a. If applicable.
如果适用。

MARKING REQUIREMENTS
标注要求

Product 产品	Environmental protection use period (years) 环境保护使用期限 (年)	Logo 标志
This Exfo product 本 EXFO 产品	10	
Battery ^a 电池 ^a	5	

a. If applicable.
如果适用。

P/N: 1065710

www.EXFO.com · info@exfo.com

CORPORATE HEADQUARTERS	400 Godin Avenue	Quebec (Quebec) G1M 2K2 CANADA Tel.: 1 418 683-0211 · Fax: 1 418 683-2170
EXFO AMERICA	3400 Waterview Parkway Suite 100	Richardson, TX 75080 USA Tel.: 1 972-761-927 · Fax: 1 972-761-9067
EXFO EUROPE	Winchester House, School Lane	Chandlers Ford, Hampshire S053 4DG ENGLAND Tel.: +44 2380 246 800 · Fax: +44 2380 246 801
EXFO ASIA-PACIFIC	100 Beach Road, #25-01/03 Shaw Tower	SINGAPORE 189702 Tel.: +65 6333 8241 · Fax: +65 6333 8242
EXFO CHINA	Beijing Global Trade Center, Tower C, Room 1207, 36 North Third Ring Road East, Dongcheng District	Beijing 100013 P. R. CHINA Tel.: +86 (10) 5825 7755 · Fax: +86 (10) 5825 7722
EXFO SERVICE ASSURANCE	270 Billerica Road	Chelmsford MA, 01824 USA Tel.: 1 978 367-5600 · Fax: 1 978 367-5700
EXFO FINLAND	Elektroniikkatie 2	FI-90590 Oulu, FINLAND Tel.: +358 (0) 403 010 300 · Fax: +358 (0) 8 564 5203
TOLL-FREE	(USA and Canada)	1 800 663-3936

© 2013 EXFO Inc. All rights reserved.
Printed in Canada (2013-12)

