

Metering Bellows Valves, Manual

**Part No.**

SS-6BMG-MM

Part Description:

SS Metering Bellows-Sealed Valve, Gasketed, Metering Stem Tip, 6 mm Swagelok Tube Fitting

Product Specifications

General

Actuator Type	Manual
Body Material	Stainless Steel
Body Type	Straight
Flow Pattern	Straight (2-way)
Series	BM Series
Service Class	General
End Connection 1 Size	6 mm
End Connection 1 Type	Metric Swagelok® tube
End Connection 2 Size	6 mm
End Connection 2 Type	Metric Swagelok® tube
Handle Color	Not Applicable
Handle Style	Silver-mist Chrome-plated 313 SS
Bellows Material	321 Stainless Steel
Body Seal	Gasket with metal seat
Cleaning	Swagelok SC-10
Gasket	Silver-plated 316 SS gasket
ID Tag	No
Stem Type	Metering
Surface Finish	Standard
Testing	Helium leak testing according to SCS-00020
Stem Tip Material	Chrome-plated 316 Stainless Steel
Max Temperature Pressure Rating	600°F @ 300 PSIG /315°C @ 20.6 BAR
Room Temperature Pressure Rating	700 PSIG @ 100°F /48.2 @ BAR 37°C

! The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

⚠ Caution: Do not mix or interchange valve components with those of other manufacturers.

