


FORCETM USA

THE TRUSTED NAME IN STRENGTH EQUIPMENT

OWNER'S MANUAL **F-G9**



CAUTION!

Read all precautions and instructions in this manual before using this equipment.



Parts list	3-5
Assembly step 1	6-7
Assembly step 2	8-10
Assembly step 3	11-12
Assembly step 4	13-14
Assembly step 5	15-16
Assembly step 6	17-18
Assembly step 7	19-20
Assembly step 8	21-22
Assembly step 9	23-24
Assembly step 10	25-26
Assembly step 11	27-28
Assembly step 12	29-30

Parts list

No.	Description	Note	Qty.
1	connection tube		1
2	upright frame left		1
3	upright frame right		1
4	bending tube left		1
5	bending tube right		1
6	upper connection tube		1
7	upper bending tube right		1
8	upper bending tube left		1
9	hexagon bolt	M10x75	54
10	lock nut	M10	105
11	washer	Φ10	217
12	chin up bar		1
13	upper plate		4
14	pulley frame tube right		1
15	pulley frame tube left		1
16	upright tube		2
17	tube with hole right		1
18	tube with hole left		1
19	lower plate		4
20	sliding tube right		1
21	sliding tube left		1
22	foot tube cover		2
23	end tube		2
24	hexagon bolt	M10x80	14
25	lower base		2
26	upper base		2
27	guide rod	Φ25x1850	2
28	lock sleeve		2
29	sliding sleeve		2
30	rubber pad with groove	Φ60xΦ26x45	2
31	safety hook right		1
32	safety hook left		1
33	hexagon bolt	M10x90	8
34	socket set screw	M8x10	4
35	end cap		2

Parts list


36	check ring		2
37	pipe	Φ50x310xT0.5	2
38	button head socket screw	M12x40	2
39	spring washer	Φ12	6
40	washer	Φ12	6
41	barbell rod		1
42	inner pipe	Φ48x298x2.5T	2
43	rubber pad	Φ60xΦ26x25	2
44	upper connection tube short		1
45	lower connection tube		1
46	big sliding sleeve		1
47	guide rod hollow		2
48	rubber pad	Φ60xΦ26x45	2
49	hexagon bolt	M10x25	11
50	hexagon bolt	M10x95	3
51	hexagon bolt	M10x55	2
52	hexagon bolt	M12x30	4
53	double pulley bracket		1
55	back barbell plate holder		2
56	wire	Φ5x2745mm	2
57	pulley	Φ95	25
58	pulley plate		4
59	hexagon bolt	M10x45	17
60	hexagon bolt	M10x50	4
61	weight		2
62	wire	Φ5x4740mm	1
63	"-" shaped pulley frame		3
64	short bar		1
65	footplate		1
66	chain + 2 snap hook		1
67	wire	Φ5x4095mm	2
68	pulley spacer sleeve	Φ20x10.5xL20.5	16
69	pulley frame		1
70	wire	Φ5x1705mm	1
71	5 section chain + snap hook		1

Parts list


72	wire	Φ5x9715mm	1
73	pulley	Φ50	4
74	shield		1
75	barbell plate holder		6
76	hexagon bolt	M8x20	16
77	washer	Φ8	20
78	lock nut	M8	4
79	core trainer		1
80	powder metallurgy sleeve		2
81	barbell rod cup		1
82	big washer	Φ25x10x2.0	1
83	dip bar left		1
84	dip bar right		1
85	barbell rod holder right		1
86	barbell rod holder left		1
87	barbell rod holder short left		1
88	barbell rod holder short right		1
89	barbell rod ring		2
90	long bar		1
91	ship rod		1
92	hand belt		2
93	pull lift device		1
94	T shape pin	Φ10x100	1
95	leg curl tube		1
96	footplate		1



Assembly step 1




No.	Description	Note	Qty.
1	connection tube		1
2	upright frame left		1
3	upright frame right		1
4	bending tube left		1
5	bending tube right		1
6	upper connection tube		1
7	upper bending tube right		1
8	upper bending tube left		1
9	hexagon bolt	M10x75	16
10	lock nut	M10	16
11	washer	Φ10	32





- 1 Fix bending tube left-4 fastening on upright frame left-2 using M10x75 hexagon bolt-9, Φ 10 washer-11 and M10 lock nut-10
- 2 Fix bending tube right-5 fastening on upright frame right-3 using M10x75 hexagon bolt-9, Φ 10 washer-11 and M10 lock nut-10
- 3 Fix connection tube-1 fastening with bending tube left-4, bending tube right-5 using M10x75 hexagon bolt-9, Φ 10 washer-11 and M10 lock nut-10
- 4 Fix upper connection tube-6 fastening on upright frame using M10x75 hexagon bolt-9, Φ 10 washer-11 and M10 lock nut-10
- 5 Fix upper bending tube left-8 fastening on upright frame left-2 using M10x75 hexagon bolt-9, Φ 10 washer-11 and M10 lock nut-10
- 6 Fix upper bending tube right-7 fastening on upright frame right-3 using M10x75 hexagon bolt-9, Φ 10 washer-11 and M10 lock nut-10

Assembly step 2




No.	Description	Note	Qty.
9	hexagon bolt	M10x75	38
10	lock nut	M10	44
11	washer	Φ10	88
12	chin up bar		1
13	upper plate		4
14	pulley frame tube right		1
15	pulley frame tube left		1
16	upright tube		2
17	tube with hole right		1
18	tube with hole left		1
19	lower plate		4
20	sliding tube right		1
21	sliding tube left		1
22	foot tube cover		2
23	end tube		2
24	hexagon bolt	M10x80	6






- 1 Fix sliding tube left-21 on tube with hole left-18
- 2 Fix sliding tube right on tube with hole right-17
- 3 Fix upright tube-16 and tube with hole left-18 fastening on assembly step-1 using M10x75 hexagon bolt-9, $\Phi 10$ washer-11, M10 lock nut-10, upper plate-13 and lower plate-19
- 4 Fix pulley frame tube right-14 and pulley frame tube left-15 fastening on upper plate-13 using M10x75 hexagon bolt-9, $\Phi 10$ washer-11 and M10 lock nut-10
- 5 Fix end tube-23 fastening on upper plate-13 using M10x75 hexagon bolt-9, $\Phi 10$ washer-11 and M10 lock nut-10
- 6 Fix foot tube cover-22 fastening on lower plate-19 using M10x75 hexagon bolt-9, $\Phi 10$ washer-11 and M10 lock nut-10
- 7 Fix chin up bar-12 fastening on upper plate-13 using M10x80 hexagon bolt-24, $\Phi 10$ washer-11 and M10 lock nut-10

Assembly step 3




No.	Description	Note	Qty.
10	lock nut	M10	8
11	washer	Φ10	16
25	lower base		2
26	upper base		2
27	guide rod	Φ25x1850	2
28	lock sleeve		2
29	sliding sleeve		2
30	rubber pad with groove	Φ60xΦ26x45	2
31	safety hook right		1
32	safety hook left		1
33	hexagon bolt	M10x90	8
34	socket set screw	M8x10	2
35	end cap		2
36	check ring		2
37	pipe	Φ50x310xT0.5	2
38	button head socket screw	M12x40	2
39	spring washer	Φ12	2
40	washer	Φ12	2
41	barbell rod		1
42	inner pipe	Φ48x298x2.5T	2
43	rubber pad	Φ60xΦ26x25	2
89	barbell rod ring		2




- 1 Fix lower base-25 fastening on lower plate using M10x90 hexagon bolt-33, $\Phi 10$ washer-11 and M10 lock nut-10
- 2 Fix upper base-26 fastening on upper plate using M10x90 hexagon bolt-33, $\Phi 10$ washer-11 and M10 lock nut-10
- 3 Guide rod in turn through lock sleeve-28, sliding sleeve-29, rubber pad-43, safety hook left-32 and rubber pad with groove-30 fastening on base using M8x10 socket set screw-34
- 4 Barbell rod-41 in turn through sliding sleeve-29, check ring-36, inner pipe-42, pipe-37 and end cap-35 fastening using M12x40 button head socket screw-38, $\Phi 12$ spring washer-39 and $\Phi 12$ washer-40, then fit on barbell clamp collar-89
- 5 Guide rod in turn through lock sleeve-28, sliding sleeve-29, rubber pad-43, safety hook right-31 and rubber pad with groove-30 fastening on base using M8x10 socket set screw-34

Assembly step 4




No.	Description	Note	Qty.
10	lock nut	M10	2
11	washer	Φ10	7
39	spring washer	Φ12	4
40	washer	Φ12	4
44	upper connection tube short		1
45	lower connection tube		1
46	big sliding sleeve		1
47	guide rod hollow		2
48	rubber pad	Φ60xΦ26x45	2
49	hexagon bolt	M10x25	2
50	hexagon bolt	M10x95	1
51	hexagon bolt	M10x55	2
52	hexagon bolt	M12x30	4
53	double pulley bracket		1
34	socket set screw	M8x10	2
55	back barbell plate holder		2




- 1 Fix upper connection tube short-44 fastening on main frame using M12x30 hexagon bolt-52, Φ 12 spring washer-39 and Φ 12 washer-40
- 2 Fix lower connection tube-45 fastening on main frame using M12x30 hexagon bolt-52, Φ 12 spring washer-39 and Φ 12 washer-40
- 3 Fix double pulley bracket-53 fastening on double pulley bracket-45 using M10x55 hexagon bolt-51, Φ 10 washer-11 and M10 lock nut-10
- 4 Guide rod hollow-47 in turn through big sliding sleeve-46, rubber pad-48 fastening using M10x95 hexagon bolt-50, Φ 10 washer-11 and M10x25 hexagon bolt-49
- 5 Fix back barbell plate holder-55 fastening on big sliding sleeve-46 using M8x10 socket set screw-34

Assembly step 5




No.	Description	Note	Qty.
10	lock nut	M10	6
11	washer	Φ10	14
49	hexagon bolt	M10x25	2
56	wire	Φ5x2745mm	2
57	pulley	Φ95	6
58	pulley plate		4
59	hexagon bolt	M10x45	2
60	hexagon bolt	M10x50	4
61	weight		2




- 1 Connect wire-56 with weight-61, put them into upright frame
- 2 Fix pulley-57 fastening on upper bending tube using M10x50 hexagon bolt-60, pulley plate-58, $\Phi 10$ washer-11 and M10 lock nut-10
- 3 Fix pulley-57 fastening on upper bending tube using M10x45 hexagon bolt-59, pulley plate-58, $\Phi 10$ washer-11 and M10 lock nut-10
- 4 Fix wire-56 fastening on sliding sleeve outside using M10x25 hexagon bolt-49, $\Phi 10$ washer-11 and M10 lock nut-10

Assembly step 6




No.	Description	Note	Qty.
10	lock nut	M10	5
11	washer	Φ10	12
49	hexagon bolt	M10x25	2
57	pulley	Φ95	5
59	hexagon bolt	M10x45	5
62	wire	Φ5x4740mm	1
63	"-" shaped pulley frame		1
64	short bar		1
65	footplate		1
66	chain + 2 snap hook		1




- 1 As the shown in the figure fix pulley-57 fastening on main frame and "—" shape pulley frame-63 using M10x45 hexagon bolt-59, pulley plate-58, $\Phi 10$ washer-11 and M10 lock nut-10
- 2 As the shown in the figure put the wire-62
- 3 Connect short bar-64 to wire using chain + 2 snap hook-66
- 4 Fix footplate-65 fastening on main frame using M10x25 hexagon bolt-49, $\Phi 10$ washer-11 and M10 lock nut-10

Assembly step 7




No.	Description	Note	Qty.
10	lock nut	M10	8
11	washer	Φ10	16
24	hexagon bolt	M10x80	4
49	hexagon bolt	M10x25	2
57	pulley	Φ95	6
59	hexagon bolt	M10x45	2
63	"-" shaped pulley frame		2
67	wire	Φ5x4095mm	2
68	pulley spacer sleeve	Φ20x10.5xL20.5	8




- 1 As the shown in the figure fix pulley-57 fastening on upper plate using M10x80 hexagon bolt-24, $\Phi 10$ washer-11 and M10 lock nut-10 and pulley spacer sleeve-68
- 2 Fix pulley-57 fastening on "—" shape pulley frame-63 using M10x45 hexagon bolt-59, $\Phi 10$ washer-11 and M10 lock nut-10
- 3 As the shown in the figure put the wire-67 using M10x45 hexagon bolt-59, $\Phi 10$ washer-11 and M10 lock nut-10 fastening on bending tube, careful to keep the wire vertical

Assembly step 8




No.	Description	Note	Qty.
10	lock nut	M10	2
11	washer	Φ10	1
57	pulley	Φ95	1
59	hexagon bolt	M10x45	1
69	pulley frame		1
70	wire	Φ5x1705mm	1
71	5 section chain + snap hook		1




- 1 Fix pulley-57 fastening on "—" shape pulley frame-63 using M10x45 hexagon bolt-59, $\Phi 10$ washer-11 and M10 lock nut-10
- 2 As the shown in the figure connect wire-70, pulley frame-69 and 5 section chain + snap hook-71 on the main frame

Assembly step 9




No.	Description	Note	Qty.
10	lock nut	M10	26
11	washer	Φ10	13
24	hexagon bolt	M10x80	4
49	hexagon bolt	M10x25	2
57	pulley	Φ95	7
59	hexagon bolt	M10x45	7
68	pulley spacer sleeve	Φ20x10.5xL20.5	8
72	wire	Φ5x9715mm	1
73	pulley	Φ50	4




- 1 Fix pulley-57 fastening on main frame using M10x45 hexagon bolt-59, $\Phi 10$ washer-11 and M10 lock nut-10
- 2 Fix pulley-73 fastening on lower plate using M10x80 hexagon bolt-24, $\Phi 10$ washer-11 and M10 lock nut-10 and pulley spacer sleeve-68
- 3 As the shown in the figure put the wire-72 on the machine

Assembly step 10




No.	Description	Note	Qty.
74	shield		1
75	barbell plate holder		6
76	hexagon bolt	M8x20	16
77	washer	Φ8	20
78	lock nut	M8	4




- 1 Fix shield-74 fastening on main frame using M8x20 hexagon bolt-76, $\Phi 8$ washer-77 and M8 lock nut-78
- 2 Fix barbell plate holder-75 on main frame using M8x20 hexagon bolt-76, $\Phi 8$ washer-77

Assembly step 11




No.	Description	Note	Qty.
10	lock nut	M10	4
11	washer	Φ10	2
49	hexagon bolt	M10x25	1
50	hexagon bolt	M10x95	2
79	core trainer		1
80	powder metallurgy sleeve		2
81	barbell rod cup		1
82	big washer	Φ25x10x2.0	1




- 1 Fix core trainer-79 fastening on main frame using M10x25 hexagon bolt-49, $\Phi 10$ big washer-82 and powder metallurgy sleeve-80
- 2 Fix barbell rod cup-81 fastening on upright frame using M10x95 hexagon bolt-50, $\Phi 10$ washer-11 and M10 lock nut-10

Assembly step 12



No.	Description	Note	Qty.
83	dip bar left		1
84	dip bar right		1
85	barbell rod holder right		1
86	barbell rod holder left		1
87	barbell rod holder short left		1
88	barbell rod holder short right		1
90	long bar		1
91	ship rod		1
92	hand belt		2
93	pull lift device		1
94	T shape pin	Φ10x100	1
95	leg curl tube		1
96	footplate		1



- 1 Connect leg curl tube-95 and barbell rod holder short left-87 using T shape pin-94
- 2 Put the attached part on the machine