ROCOL™

TECHNICAL DATA

ROCOL Nickel Anti-Seize Compound

Anti-seize compound for stainless steel

Description

Rocol Nickel Anti-Seize Compound is formulated to prevent seizure of threaded components which are subjected to extremely high temperatures or adverse environmental conditions for long periods of time. Nickel Anti-Seize Compound contains lubricating solids to prevent galling and seizure during assembly or dismantling under heavy loads. Nickel Anti-Seize Compound has application on most surfaces subject to long term fretting and corrosion.

Areas of application

- Stainless steel fasteners
- Industrial fasteners

Features

- Excellent anti-seize properties due to high solids content (>35%)
- Excellent adhesion properties
- Protects against wet conditions and chemical attack
- Provides anti-seize properties up to 1400°C
- Does not contain sulphur or copper
- Aids assembly and dismantling under heavy loads
- NZFSA Approved C14 (All animal product except dairy)

Directions for use

Apply with the brush supplied a thin film to the surface. For best results all surfaces should be clean and dry.

Technical data

Appearance	Smooth brushable silver/grey paste
Carrier	Bentonite thickened mineral oil
Temperature Range	Up to 1400°C
Anti-Seize Solids	Nickel and mica
Solids content	> 35%
Consistency	NLGI 0-1

Health & safety information

The product is hazardous. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request.

Australia
ITW Polymers & Fluids Pty Ltd
100 Hassall Street, Wetherill Park, NSW, 2164
Phone: (02) 9757 8800
Fax: (02) 9757 3855

New Zealand
ITW Polymers & Fluids
18-26 Amelia Earhart Ave, Airport Oaks, Mangere
Phone: 09 256 2122
Fax: 09 256 2124