

☐

I'm not robot


reCAPTCHA

Continue

Rothenberger rp30 pressure testing pump manual

Rothenberger rp30.



High performance combined with a compact design ensure convenient operation for the installer.Choosen variant:RP Pro III, electricChoose another variantWorking area Temperature40 °CTest area0 - 40 barPower plug typePlug type F (CEE 7/4)Test mediumDrinking water, Glycol, ÖlPower pump0 - 6 l/minMains frequency with unit of measurement50 HzArticle61185EAN/GTIN4004625611852Net weight with unit of measure17,130 kgGross weight with unit of measure17,815 kgPackaging Length with unit of measurement40,000 cmPackaging Width with unit of measurement30,000 cmShipping weight with unit of measure17,815 kgPackaging height with unit of measurement38,000 cmSKU61185 Call 01473 559079 or email us for a bespoke design service for your underfloor heating project - FREE Maintive.com, Street 43, Community 598, DIP 1 - UAE. 1284Maintive. All Rights Reserved Reliable and precise testing results' the dual-valve system (Twin-Valve) enables self-testing of the pump, as well as a precise fine adjustment of the pressure. Testing hose with steel mesh prevents reading mistakes, that can when the hose expands during operation Specification Connection: R 1/2 Delivery rate: 16 ml/Hub Product length: 440 mm Product height: 240 mm Product weight: 4.5 kg Product width: 200 mm Size : NOS Products/Service and Maintenance/Leak detection/Water pressure testing Model # 61130Simple and light testing pump for compression testing up to 30 bar (440 psi).Pressure testing with water or oil of piping in residential and industrial construction as well as for industrial containers up to 30 bar in accordance with international and national standards.Testing hose with steel mesh prevents reading mistakes, that can happen when the hose expands during operation. Products/Service and Maintenance/Leak detection/Water pressure testing