


LXNAV RS485 to RS232 Bridge

Installation manual Version 2.10

Revision 19



[LXNAV d.o.o.](http://www.lxnav.com) • Kidričeva 24a, 3000 Celje, Slovenia • tel +386 592 33 400 fax +386 599 33 522
info@lxnav.com • www.lxnav.com

1	Important Notices.....	3
1.1	Limited Warranty	4
2	Installations.....	5
2.1	Packing Lists.....	5
2.2	Basics.....	5
2.3	Installation.....	5
2.4	Wirings.....	7
2.4.1	NMEA bridge.....	7
2.4.1.1	Oudie	7
2.4.2	Radios.....	8
2.4.2.1	Funkwerk ATR833.....	8
2.4.2.2	Dittel KRT2.....	8
2.4.2.3	Trig TY 91/92.....	9
I.	TY 91/92 without TC 90 head	9
II.	Trig TY 91/92 with TC90 head	9
2.4.2.4	Becker AR6201 / RT6201	10
I.	AR6201 single seater	10
II.	AR6201 twin seater	11
III.	RT6201 single seater remote control	11
2.4.3	Transponders.....	12
2.4.3.1	Becker BXP6402.....	12
2.4.3.2	Trig TT 21/22.....	12
2.4.4	Multifunction controllers	13
2.4.4.1	AIR Control Display 57	13
3	Revision History.....	14

1 Important Notices

Information in this document is subject to change without notice. LXNAV reserves the right to change or improve their products and to make changes in the content of this material without obligation to notify any person or organisation of such changes or improvements.



A Yellow triangle is shown for parts of the manual which should be read very carefully and are important for operating the system.



Notes with a red triangle describe procedures which are critical and may result in loss of data or any other critical situation.



A bulb icon is shown when a useful hint is provided to the reader.

1.1 Limited Warranty

This LXNAV product is warranted to be free from defects in materials or workmanship for two years from the date of purchase. Within this period, LXNAV will, at its sole discretion, repair or replace any components that fail in normal use. Such repairs or replacement will be made at no charge to the customer for parts and labour, provided that the customer shall be responsible for any transportation cost. This warranty does not cover failures due to abuse, misuse, accident, or unauthorised alterations or repairs.

THE WARRANTIES AND REMEDIES CONTAINED HEREIN ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED OR STATUTORY, INCLUDING ANY LIABILITY ARISING UNDER ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, STATUTORY OR OTHERWISE. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, WHICH MAY VARY FROM STATE TO STATE.

IN NO EVENT SHALL LXNAV BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, WHETHER RESULTING FROM THE USE, MISUSE, OR INABILITY TO USE THIS PRODUCT OR FROM DEFECTS IN THE PRODUCT. Some states do not allow the exclusion of incidental or consequential damages, so the above limitations may not apply to you. LXNAV retains the exclusive right to repair or replace the unit or software, or to offer a full refund of the purchase price, at its sole discretion. SUCH REMEDY SHALL BE YOUR SOLE AND EXCLUSIVE REMEDY FOR ANY BREACH OF WARRANTY.

To obtain warranty service, contact your local LXNAV dealer or contact LXNAV directly.

December 2020

© 2020 LXNAV. All rights reserved.

2 Installations

2.1 Packing Lists


- 485 to232 bridge
- Pair of spring locks for RS485 splitter

2.2 Basics

LXNAV RS485 to Rs232 bridge (Bridge) is connected to the RS485 bus through a RS485 splitter DB9 connector. A RS485 splitter is not part of package. If you don` t have spare port on your RS485 splitter you must order another 485 splitter.


2.3 Installation

The RS485 splitter needs a small modification before the Bridge can be fitted. It is necessary to remove two HEX screws, where the Bridge is to be connected, and replace them with the two spring locks that are in the package.



After that small modification, fixing the Bridge to the RS485 splitter will be very easy.

On the other side of the Bridge there is a RJ12 connector with a standard IGC/FLARM pinout



1 2 3 4 5 6
Pin numbers

Pin number	Description
1	(output) 12V DC, to supply GPS
2	3.3V DC (max 100mA)
3	GND
4	Flarm Data Out
5	Flarm Data In
6	Ground


By default, the Bridge is programmed to stream NMEA data at 4800bps. It streams standard GPS and Flarm data.

2.4 Wirings

The wiring diagrams show the minimum required connection for communication between a LXNAV instrument and a radio or transponder. The user should check the manual of the connected device for any further information.


2.4.1 NMEA bridge

2.4.1.1 Oudie




2.4.2 Radios

2.4.2.1 Funkwerk ATR833




2.4.2.2 Dittel KRT2




2.4.2.3 Trig TY 91/92

I. TY 91/92 without TC 90 head



II. Trig TY 91/92 with TC90 head



Minimum firmware versions for communication between Trig radio and RS485 to RS232 Bridge




Device	Minimum firmware version
TY 91/92	1.5
TC 90	1.4
RS485 to RS232 Bridge	1.18

2.4.2.4 Becker AR6201 / RT6201

A remote control should be enabled on the Becker radio. Please check the Becker radio's Manual to see how to enable it.

From Becker manual:




Try to enable "Tandem" mode on the radio itself. To do this, press MDE while turning on the radio. Input password 6435 and press STO. Move to "Configuration" screen with SCN and enable "Tandem" checkbox there. Also, on the "SPKR VOL SRC" select the "Both" option. Now you can turn off the radio (settings are saved on-the-fly) and check if the connection works. If it still doesn't work or you can't find the menu items, please specify the exact model of Becker radio (the "PN" label on the device).

Minimum firmware version for communication between Becker and Bridge





Device	Minimum firmware version
RS485 to RS232 Bridge	1.16
Becker SCI1050S305	3.05
Becker SCI1051S305	1.49

I. AR6201 single seater



2.4.4 Multifunction controllers

2.4.4.1 AIR Control Display 57



3 Revision History

August 2014	Rev 1	Initial release of owner manual
July 2015	Rev 2	Added chapters 2.4.2.3 TRIG TY 91/92
August 2015	Rev 3	Modified wirings for Trig TY 91/92, Trig TT 21/22 and Becker BXP6402
October 2015	Rev 4	Modified wirings with separated connectors from Bridge, Wired power ON pins for auto ON functions, Added chapter 1.5.1.4 Becker AR6201
October 2015	Rev 5	Cable shields wired to SUBD9 connector housings, Added colours to wires
Januray 2016	Rev 6	Instructions for Becker Radio configuration
February 2016	Rev 7	English correction, triggering the remote head description is added
March 2016	Rev 8	Added wirings for Becker radios with single and two seater configuration for AR6201 and RT6201
June 2016	Rev 9	Added wiring for Trig TY91/92 with TC90 head
July 2016	Rev 10	Added version requirements for Trig TY 91/92
March 2017	Rev 11	Added old color pinouts of Becker wiring v1.0: 2.4.2.4, 2.4.3
September 2017	Rev 12	Updated ch.2.4.2.4 Added new ch.2.4.1.1
August 2018	Rev 13	English correction done by JR
August 2018	Rev 14	Modified wiring for ATR833 in ch.2.4.2.1
April 2019	Rev 15	Added 2.4.4 (Multifunction controllers) and 2.4.4.1 (AIR Control display 57)
December 2019	Rev 16	Added version requirements for Becker radios in chapter 2.4.2.4
April 2020	Rev 17	Updated wiring diagram 2.4.4.1 with color labels
November 2020	Rev 18	Updated chapter 2.4.3
January 2021	Rev 19	Updated chapter 2.4.4.1