



CC600 Technical Accessory Guide



NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.








* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.



Communication Cables

Part Number	Picture	Description	Notes	Required Items
CBL-TC2X-USBC-01 or CBL-TC5X-USBC2A-01		USB-C Cable	► Used to communicate with CC6000 via the USB OTG port.	
(3rd party) *		USB-C to DisplayPort Cable	► Used to connect CC600 to external monitors.	

Mounting Options

Part Number	Picture	Description	Notes	Required Items
21-118517-01R		Wall Mounting Kit		
21-118517-02R		Pole Mounting Kit		

367-5142 (3rd party) * Contact: Bill Donehoo office: 630-549-6258 bdonehoo@ens-co.com http://www.ens-co.com		Wall Mount Bracket for CC600 and ZQ610	<ul style="list-style-type: none"> ▶ Allows CC600 and ZQ610 printer to be mounted side-by-side. ▶ Bracket tilts both devices for easy access and viewing. 	
Power Cords/ Power Supplies - Note: There are two ways to power the CC600, either Direct Connect or via 802.3af POE (Power over Ethernet)				
Part Number	Picture	Description	Notes	Required Items
CBL-DC-383A1-01		DC Line Cord	<ul style="list-style-type: none"> ▶ Used with Power Supply (PWR-BUA5V16W0WW) ▶ Cable length is 6 ft. 	
PWR-BUA5V16W0WW		Power Supply	<ul style="list-style-type: none"> ▶ 100-240VAC, 5.4V, 3A, 16W ▶ Meets US DOE Level VI efficiency standard ▶ Replaces PWRS-14000-249R 	DC Line Cord (CBL-DC-383A1-01) and AC Line Cord (50-16000-182R)
PWRS-14000-249R		Power Supply with integrated DC Cord	<ul style="list-style-type: none"> ▶ Discontinued 10/2016 in NALA and 1/2017 in EMEA/APAC - replaced by PWR-BUA5V16W0WW and CBL-DC-383A1-01 - PMB 2887. ▶ Replaces 50-14000-249R ▶ 100-240VAC, 5.4 VDC, 3A ▶ Energy Star Compliant 	50-16000-182R
50-14000-147R		Power Supply with integrated DC Cord	<ul style="list-style-type: none"> ▶ Discontinued 12/2007 - replaced by 50-14000-249R 	50-16000-182R
50-14000-249R		Power Supply with integrated DC Cord	<ul style="list-style-type: none"> ▶ Replaces 50-14000-147R 	50-16000-182R
POE29U-1AT(PL)D-R		Single-port High Power Gigabit 802.3at Power Injector	<ul style="list-style-type: none"> ▶ Discontinued 4/2020 ▶ Used to power CC600 via PoE ▶ 30W Single Port Power over Ethernet Midspan IEEE 802.3at Compliant Power Injector. 	AC Line Cord (23844-00-00R)

AP-PSBIAS-2P3-ATR		802.3at Power Injector	<p>► Can be used when Power over Ethernet is required, but switch does not provide 802.3at POE.</p> <p>► Discontinued 10/2016 due to sale of Zebra's WLAN business to Extreme Networks. Now source third party POE injector.</p>	23844-00-00R AC Line Cord
50-16000-182R		AC Line Cord	<p>► Used with 50-14000-147R/50-14000-249R/PWRS-14000-249R/PWR-BUA5V16W0WW.</p> <p>► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries.</p>	