



Anton bauer cine vclx 2 charger manual

Anton bauer vclx.

4Visions Spólka z ograniczona odpowiedzialnoscia Sp. K. Contact A. F.

Marcotec Warszawa Sp zo.o. Contact AW Tecnologia SA de CV Contact AVC Group Slovenia Contact AbelCine New York Contact Amperel Electronica Industrial, S.A. Contact Artste Brgineering SRL Contact AVC Group Accedonia Contact AVC Group Accedonia Contact AVC Group Slovenia Contact AVC Group Slovenia Contact AVC Group Slovenia Contact AVC Group - London Contact AVC Group - London Contact BAB Photo Slovenia Contact BAB Photo Slovenia Contact BBM Bray now Band Pro Film & Digital, Inc. Contact Brain Solvenia Contact CV Group - London Contact D& P Multimedia Provides Systems, Ltd. Contact Media Team Solvenia Contact AVC Group - London Slovenia Contact Master Dealer Africa (Pty) Ltd. Contact Media Team Solvenia Contact AVC Group - London Contact Slovenia Contact Master Dealer Africa (Pty) Ltd. Contact Media Team Solvenia Contact AVC Group - London Contact Slovenia Contact Superson Slovenia Contact Superson Slovenia Contact Master Dealer Africa (Pty) Ltd. Contact Media Team Solvenia Contact Master Dealer Africa (Pty) Ltd. Contact Master Dealer Africa (Pty) Ltd. Contact Moncada y Lorenzo S.A. Contact On&Off media CO., Ltd. Contact Star 2000 Broadcast Solvitions Contact Superson Slovenia Contact Superson Slo

Frequently Asked Questions Yes the VCLX NM2 is a NiMH battery and can be taken as hand luggage or placed into the hold of an aircraft. Because it is a NiMH battery there is no need to discharge it so it will be at 100% charged and ready to go when you get off your flight. The VCLX NM2 charges from 0 to 100% in 3.5 hours (with Firmware 2.0 installed). The VCLX NM2 is not IP rated.

However the base of the VCLX is water resistant. The VCLX NM2 has 2 x 4-pin XLR for 14.4v, 1 x 3-pin XLR for 28v or 48V and a USB A port. These provide 48VDC at a continuous 16A and 10-17 V at a continuous 24A This gives the rental houses access to Product ID, Learned Capacity, Cycle count, XLR outputs (V,A) condition of the battery packs, time stamped error/fault reports all in an Excel file format. The unit can either connect to the Rental house WiFi and upload this data to their network or the data can be downloaded on a USB stick. There is no need to discharge the VCLX. Yes, with an official Anton Bauer combiner unit.