

SHENZHEN KINGTECH TECHNOLOGY CO.,LTD

Add: Building 1,HongYe Industry Park, Lezhujiao, BaoAn,ShenZhen,China

DVB-T2 HD SPECIFICATION

Main SPEC& Features:			
* DVB-T2 HD Receiver with GX6701 Chipset * Fully comply with EWBS system with buzzer function * Fully supports DVB-T2/T/C, H.264,HD MPEG 2, MPEG4 Decoder * Supports 720P,1080i,1080P(FULL HD) * 2*USB 2.0, Media player for H.264,AVI, MKV, MP3, MP4, JPEG etc.. * PVR, Schedule recording * Support Youtube, Tiktok, Wetv, IPTV, RSS, Weather etc.... * Local language MENU,Multi-language OSD * Support H.264 & MPEG-2/MPEG4 8bit * TV Format: PAL, NTSC, PAL-M, * Time shift function * I/O ports: RF in,HDMI, RCA,2* USB input ,DC input		* With LED display * Dolby AC-3 included * 4: 3PS、4: 3LB、16: 9 * Supports updating software by USB * 7 days EPG * Banner-- time & transparency control ability * Display of signal strongness & quality * Powerful channel editor functions * Automatic or manual Area serching * Full function Remote Controller.	
Main system		Audio/video data in/out	
CPU	GX6701	Output:	RCA HDMI
Flash Memory	512M bites		
SDRAM	32M bites		
Tuner	R836 or R850 with amplifier		
Tuner & Demodulator		Power supply	
ANT. Connector	IEC TYPE, female	Input voltage:5V/1.5A	
Loop Outpur	IEC TYPE, male	Consumption:Max. 6W	
Input Frange range	170~230MHz ,470~860MHz	Protection:Separate fuse & chassis ground	
Input Impedance	75 Ω	or electric shock protection	
Input Signal level	78 dBm to -20 dBm (average power)		
IF Bandwidth	7MHz and 8MHz		
Mpeg Audio/ Vedio Decocding		Operation Enviroment:	
Video	MPEG 2(ISO/IEC 13818-2) MPEG-4 (ISO/IEC14496) H.264 (ISO/IEC14496-10)	Operation tempreture +5℃~55℃	
Profile Level	HD MPEG 2, MPEG4 HP@L4, MP@L3 MPEG-4 ASP D1(720*480*30/720*576*25)	Storage tempreture -40℃~ +65℃	
Input rate	Max. 60M bits		
Aspect ratio	4:3, 16:9, letter box		
Video Resolution	480i/576i /720P/1080i/1080P(FULL HD)		
Audio decoding	MPEG-1(Layer1&2&3)/,MP3		
Audio mode	Mono/Joint Stereo/Stereo/Dolby AC-3		
Audio standard:	ISO/IEC 14.496-3		
		Dimension	
		Size (W*D*H):120*62*23MM	
		Gift box:175*120*50mm	
		Carton:580*360*270mm 40PCS/Carton	
		N.W:9.63KG G.W:11.93KG	
		loading container:229000PCS/20GP, 68000PCS/40HQ	