

# **TECHNICAL MANUAL**

FlexPipe<sup>™</sup> FlexPipe<sup>™</sup> High Temperature FlexCord<sup>™</sup>

Toll Free: +1 888 FLX PIPE (+1 888 359 7473) Toll Free Fax: +1 888 359 7479

shawcor.com



Any technical advice, assistance, recommendations, testing or reports provided by Shawcor to you for any reason, including, but not limited to (i) the selection or use of a Shawcor product, (ii) the storing, handling or usage of a Shawcor product, or (iii) the modification of a Shawcor product in an end-use application, or (iv) assistance about technical feasibility of applications, or (v) assistance about design or installation methods or procedures (collectively, "Technical Assistance") is given and accepted at your sole risk and without any warranty whatsoever. Shawcor will have no liability or responsibility for the use of, results obtained from, or any other aspects of the Technical Assistance, including, but not limited to, the preparation and delivery hereof. You are encouraged to verify independently any such Technical Assistance.



**TECHNICAL MANUAL** 

Table of Contents

List of Tables	v
List of Figures	v
1 Introduction	1
2 Pipe	1
2.1 Product Lines	1
2.2 Design	2
2.3 Materials	4
2.4 Manufacturing	5
2.4.1 Liner	5
2.4.2 Reinforcement	6
2.4.3 Pipe	6
2.4.4 Quality Control	6
3 Fittings	7
3.1 Fitting Configurations	7
3.2 Design	9
3.3 Materials	11
3.4 Manufacturing	12
3.5 Corrosion Protection	12
4 Qualification	13
4.1 Introduction to Standards and Regulations	13
4.2 Standards	13
4.2.1 American Petroleum Institute (API)	13
4.2.2 Canadian Standards Association (CSA)	14
4.3 Regulations	15
4.3.1 Canadian Provincial Regulatory Bodies	15
4.3.2 United States Regulatory Bodies	15
4.3.3 Other Regulatory Bodies	16
4.4 Testing	16
5 Performance	17
5.1 Applications & Chemical Compatibility	17
5.1.1 Application Evaluations	17
5.1.2 Gas	17
5.1.3 Oil	17
5.1.4 Water	18
5.1.5 H₂S	18
5.1.6 CO <sub>2</sub>	19
5.1.7 Aromatic and Cycloalkane Hydrocarbons	19
5.1.8 Chemical Injection	19
5.1.9 Methanol and Ethylene Glycol	20
5.2 Pressure and Temperature Ratings	20
5.2.1 Maximum and Minimum Allowable Operating Temperature	20

5.2	2.2 Maximum Allowable Operating Pressures	21
5.2	2.3 Calculations for Determining Maximum Allowable Operating Pressure	e21
5.3	Cyclic Pressure	23
5.3	3.1 FP Cyclic Capabilities	24
5.3	3.2 FP HT Cyclic Capabilities	25
5.3	3.3 FC Cyclic Capabilities	25
5.3	3.4 Pump Jacks	25
5.4	Flow Characteristics	27
5.4	1.1 Pipe Flow	27
5.4	1.2 Fittings	28
5.5	Durability	29
5.6	Corrosion	29
5.7	Erosion	29
5.8	Ultra-Violet Protection	30
5.9	Bend Radius	31
5.10	Permeation	31
5.11	Expansion/Contraction and Axial Growth	33
5.12	External Load and Internal Vacuum Capability	33
5.13	Thermal Conductivity	35
6 Ins	stallation	36
6.1	Field Services Support	36
6.2	Liner Pull Considerations	36
6.3	Support Spacing	37
6.4	Buoyancy and Pipe Weights	37
6.5	Riser Supports	39
6.6	Tracer Wire	39
6.7	Heat Tracing	39
6.8	Cathodic Protection	40
6.9	Field Pressure Testing of New Pipelines	40
7 Op	perations	42
7.1	Startup	42
7.2	Pigging	43
7.3	Paraffin/Wax Removal	45
7.4	Shutdown and Depressurization Procedures	45
7.5	Static Electricity	46
7.6	Secondary Excavations	46
7.7	Field Pressure Testing of Existing Pipelines	47
8 Re	liability	47
8.1	History	47
8.2	Reliability Management	48
8.3	Integrity Verification	48
9 Ap	pendix	50
Proc	luct Data Sheets	50



#### **List of Tables**

Table 1: Product Lines	2
Table 2: Crimp Fittings	8
Table 3: Custom Crimp Fittings	9
Table 4: Shawcor Fitting Material List	11
Table 5: Links for Specific CSA Z662 Requirements	15
Table 6: Pipe and Fitting Tests	16
Table 7: Allowable Aromatic and Cycloalkane Hydrocarbon Content	19
Table 8: Maximum and Minimum Allowable Operating Temperatures	20
Table 9: Maximum Allowable Operating Pressure	21
Table 10: Flow Coefficients for Shawcor Spoolable Products	28
Table 11: K Factor for Shawcor Spoolable Products Coupling Fittings	29
Table 12: Minimum Bend Radius for Operation, Transport and Handling	31
Table 13: Permeability Coefficients	32
Table 14: Representative Permeation Rates for Shawcor Spoolable Products	32
Table 15: Axial Expansion/Contraction Coefficients	33
Table 16: FP and FP HT Thermal Conductivity and Resistivity	35
Table 17: Recommended Pipe Support Spacing for Shawcor Spoolable Products	37
Table 18: New Pipeline Hydrostatic Test Pressures and Durations	41
Table 19: Custom Polyurethane Disk Pigs	44
Table 20: Shawcor Pig Dimensions for Shawcor Spoolable Products	44

## **List of Figures**

3
4
10
40

# **SHAWCOR**

In an effort to provide useful product information, Shawcor makes available three main documents:

#### Technical Manual

This document is mainly addressed to engineers, supervisors and procurement personnel. It is intended to present a general description of Shawcor spoolable pipe products' materials, construction, qualification, performance, installation, operation and reliability.

#### Installation Guide

This document is mainly addressed to field personnel and is intended to provide general guidance on Shawcor spoolable pipe products' handling, joining, installing and testing.

#### **Operators Guide**

This document is mainly addressed to pipeline operations and is intended to provide general guidance on the operation of Shawcor spoolable pipe products.

Each of the three documents emphasizes particular aspects of the Shawcor product application. Familiarity with the three documents is recommended for a broader perspective. Updated information is issued in bulletin form between main document revisions with the Engineering Bulletins being incorporated into the main documents at their next revision. Where conflicting information is found, the information contained in the bulletins supersedes the information in the three documents. Shawcor TechTalk documents are marketing materials owned by the Shawcor Sales and Marketing Team and are interpretations of the Shawcor Engineering Manuals, Bulletins, and Testing documents.

This document is intended solely as a reference for use by persons of technical competence. It is the responsibility of the pipeline operator to ensure the suitability of Shawcor products for any specific pipeline application. While the information contained in this document is believed to be correct as of the date of issue, under no circumstances will Shawcor, or any of its subsidiaries, be liable in any way for any loss, damage or injury of any kind (whether direct, consequential, punitive or otherwise) incurred as a result of any omissions in this document or as a result of reliance on any information contained in this document. This document does not contain any warranty, express or implied.



 $\bigcirc$ 

All rights reserved. Any reproduction of this document in part or as a whole without the written permission of Shawcor is prohibited.



## 1 Introduction

Shawcor has designed, tested, and manufactured high pressure, corrosion resistant, spooled, continuous pipeline systems intended primarily for the Oil and Gas and Utility industries. Typical applications include oil and gas gathering; oilfield water transfer, disposal, and injection; gas distribution and transmission lines.

Shawcor has also developed an innovative crimp fitting technology that allows efficient joining directly to steel lines, standard flanged connections, or other Shawcor spoolable products pipelines. Shawcor holds patents for its unique pipe and fitting designs<sup>1</sup>.

No modifications to the pipe, fittings, or installation practices are allowed unless specifically approved in writing by Shawcor Engineering.

## 2 Pipe

## 2.1 Product Lines

Shawcor currently offers three spoolable composite pipe product lines:

- FlexPipe (FP)
- FlexPipe High Temperature (FP HT)
- FlexCord (FC)

The above products are each a type of reinforced thermoplastic pipe (RTP) and collectively referred to in this manual as Shawcor Spoolable Products. FP and FP HT are intended for static or mild cyclic pressure applications with service temperatures up to 60°C and 82°C, respectively. FC is suited for severe cyclic pressure applications with service temperatures up to 60°C.

The product range for each product line is shown in <u>Table 1</u>:

**Fiber reinforced pipe:** US patent number 6,889,716 (May 10, 2005); Canadian patent number 2,513,506 (August 3, 2010); Europe patent number 1592908 (April 7, 2010).

**Crimp-style fitting:** US patent numbers 7,946,629 B2 (May 24, 2011) and 8,042,252 B2 (October 25, 2011); Canadian patent number 2,562,823 (May 22, 2012).

**High temperature pipe:** US patent number 9,243,727 B2 (January 26, 2016); Canadian patent number 2,753,024 (May 1, 2018); Australian patent number 2010217166 (May 14, 2015).

Steel cord pipe: Canadian patent number 2,755,289 (February 20, 2018); China patent number 201,080,017,488.9 (December 3, 2014); GCC patent number GC0003910 (July 1, 2016).



#### Table 1: Product Lines

Pressure Rating	2,068 kPa (300 psi)	5,171 kPa (750 psi)	10,342 kPa (1,500 psi)	15,513 kPa (2,250 psi)
Shawcor Grade	150	301	601	901
Product Line	Nominal Size (inches)			
FP	3", 4"	2", 3", 4"	2", 3", 4"	
FP HT		2", 3", 4", 5"	2", 3", 4", 5", 6"*	
FC				3", 4"

\*6" size product launched on June 2022.

Note: 2" FC901/FC901AB are not covered in this document. 2" FC901AB product is suitable for shallow water applications (e.g., 30 meters water depth) Please contact Shawcor for more information.

Note: Shawcor Grade is meant to coincide with typical ANSI flange ratings of the same class, e.g., 601 pipe is meant for 600 ANSI flanges.

FP and FC are manufactured with a standard white jacket, and FP HT is manufactured with a standard grey jacket. All product lines provide a minimum of 20 years protection against exposure to ultraviolet (UV) light.

All three product lines will hereafter be collectively referred to as Shawcor Spoolable Products.

The product data sheets in the appendix list the Shawcor Spoolable Products dimensions and parameters.

#### 2.2 Design

Shawcor Spoolable Products are manufactured at the advanced semi-automated Shawcor production facility in Calgary, Alberta, Canada. Shawcor Spoolable Products are patented three-layer designs constructed from a thermoplastic liner (liner), helically wrapped continuous high strength reinforcement, and an external thermoplastic jacket (jacket). FP and FP HT product lines are reinforced with high strength glass fibers, while the FC product line is reinforced with high strength galvanized steel cords.

The liner acts as a bladder, the reinforcement provides strength, and the jacket protects the load-bearing layer. This unique manufacturing process has the following advantages:

- The reinforcement is not encased in a thermosetting matrix and is therefore very flexible, as a result Shawcor Spoolable Products are very rugged, durable and easy to handle.
- The simplicity of construction reduces the manufacturing costs.

# **SHAWCOR**

- The high strength reinforcement enables design for high-pressure applications.
- The liner ensures that the pipeline system is highly resistant to corrosion.
- The continuous, long lengths facilitate fast and easy installation with fewer connections and less disturbance to impacted parties.
- Environmental impact and soil disturbance can be reduced since Shawcor Spoolable Products can be trenched with a narrower trench and right of way than steel pipe or plowed in without trenching.
- Great Value: The combination of flexibility, ease of installation, and low weight per foot minimizes handling equipment requirements leading to lower installation costs when compared to stick and other spoolable products.



# **SHAWCOR**

## **TECHNICAL MANUAL**



Shawcor Spoolable Products have been designed using a sophisticated mathematical model that was developed specifically for the unique construction of these products. The mathematical model was used to design the reinforcement configuration and optimize pressure capacity and strain. The validity of the mathematical model and the material properties used by this model has been validated through extensive physical testing.

The design and manufacturing of Shawcor Spoolable Products are in accordance with standards and guidelines regarding qualification, quality control and testing of composite pipe and accessories. Please refer to <u>Section 4</u> in this document for additional information on these standards, and <u>Section 5.2</u> for a summary of the design methods and calculations.

#### 2.3 Materials

The materials used in Shawcor Spoolable Products have been widely used in the oil and gas industry for many years. The liner and jacket are manufactured using bimodal pressure-pipe-grade high density polyethylene (HDPE) thermoplastic resin. The reinforcement materials are either continuous glass fiber rovings for FP and FP HT or high strength steel cords for FC.

<u>HDPE Liner</u> – This material is designated PE4710 by PPI TR-3<sup>2</sup>, in accordance with ASTM D3350<sup>3</sup>. The advancement in material properties of PE4710 increases resistance

<sup>&</sup>lt;sup>2</sup> PPI TR-3 Policies and Procedures for Developing Hydrostatic Design Basis, Pressure Design Basis, Strength Design Basis, and Minimum Required Strength Ratings for Thermoplastic Piping Materials or Pipe.

<sup>&</sup>lt;sup>3</sup> ASTM D3350 Standard Specification for Polyethylene Plastics Pipe and Fittings Materials.



to crack growth while meeting rigorous standards for high strength. It also provides excellent wear resistance, reduced friction for decreased pressure losses, and increased impact toughness. A raised temperature (PE-RT) version of PE4710 is used for FP HT products.

<u>Glass Fiber Reinforcement (FP and FP HT)</u> – The glass fiber reinforcement utilized in FP and FP HT is constructed from a series of continuous glass fiber rovings. The fiber chemistry and coatings are specifically selected to optimize long-term performance.

<u>High-Strength Steel Cords Reinforcement (FC)</u> – The high-strength steel cords utilized in FC are constructed from a series of stranded galvanized wires for optimum performance.

<u>HDPE Jacket</u> – This PE4710 material has the same properties as the HDPE liner. Colorant and ultra-violet (UV) stabilizers are blended with the thermoplastic pellets during the extrusion process, providing resistance to weathering. The material properties of increased impact toughness and resistance to crack growth are especially important for the HDPE Jacket. A raised temperature (PE-RT) version of PE4710 is used for FP HT products.

Shawcor is committed to maintaining high standards of quality and reliability. Each individual supplier is qualified by Shawcor, in accordance with API Specification 15S (API 15S)<sup>4</sup> to ensure that quality inspections, physical testing, and material traceability meet Shawcor quality standards. Each specific material is qualified by Shawcor through rigorous physical testing, prior to use in manufacturing and in finished products.

## 2.4 Manufacturing

Raw materials required for manufacturing of Shawcor Spoolable Products are approved by rigorous testing and closely monitored throughout the manufacturing process. Fittings are supplied by approved venders to Shawcor specifications. All composite pipe is manufactured by Shawcor utilizing our advanced manufacturing facilities in Calgary. Each step of the manufacturing process is closely monitored, resulting in direct control over the quality of the products.



#### 2.4.1 Liner

The liner is manufactured and inspected by highly experienced operators using state-ofthe art equipment, in accordance with stringent dimensional requirements defined by ASTM D2513<sup>5</sup>. Each liner run is continuously inspected for diameter, wall thickness, and concentricity by online ultrasonic measurement.

<sup>&</sup>lt;sup>4</sup> API Specification 15S Spoolable Reinforced Plastic Line Pipe.

<sup>&</sup>lt;sup>5</sup> ASTM D2513 Standard Specification for Thermoplastic Gas Pressure Pipe, Tubing, and Fittings.

# **TECHNICAL MANUAL**

#### 2.4.2 Reinforcement

#### **Glass Fiber Reinforcement**

The fiber reinforcements for each product are constructed from a single type of input strand, purchased from qualified suppliers. Shawcor has a proprietary multistep process to combine glass fibers into a package that ensures the glass fibers' strength is maximized at the correct helical angle to gain desired properties of flexibility, reinforcement strength, and redundancy. Shawcor has developed extensive expertise in this area through critical evaluation and physical

testing of various materials, coatings, and processing methods. State-of-the-art roving machines are used with tensioning systems designed in-house specifically for this process.

#### Galvanized Steel Cord Reinforcement

The galvanized steel cord reinforcements are applied directly as purchased from qualified suppliers. Similar to the glass fiber reinforcement, the helical angle to the pipe axis is controlled to maintain specific final product characteristics regarding flexibility, weight, and pressure rating.

#### 2.4.3 Pipe

Each reel of pipe is manufactured in a single continuous production run that combines liner, reinforcement, and jacket into the finished product. The liner length is sufficient to complete an entire pipe production run without fusions.

The reinforcement is applied by sequential customdesigned winding machines, which wrap the reinforcement from multiple bobbins around the liner in a tightly controlled process. An automated control system measures the line speed and maintains the correct wrap angle by controlling the speed of each individual winding machine.

The jacket is applied over the reinforcement layer with a customized cross-head extrusion die, and immediately

cooled. Computerized laser and ultrasonic measurement systems are used to ensure that strict quality standards are maintained as the protective jacket is applied. The jacket is marked with identifying information by an inline printer. Finally, the finished product is spooled onto a reel for transportation.

#### 2.4.4 Quality Control

Quality Control (QC) is critical to the manufacturing process. Shawcor is an ISO 9001:2015 certified manufacturing facility. Quality control data is diligently reviewed from supplier evaluation and approval all the way to the qualification of every finished product ready for delivery. Shawcor is committed to using suppliers that provide material property







data and maintain certification and QC test results for all raw products. Material certification and traceability is critical to the Shawcor quality assurance program that cohesively links raw materials with production records and serial markings on pipe and fittings. Shawcor routinely verifies and audits the QC programs of its suppliers.

The manufacturing process is designed with many levels of quality monitoring. Sophisticated instrumentation systems, lasers, ultra-sonics, and production operators continually monitor the production line. Corrective action is implemented according to the established non-conformance reporting (NCR) system if design parameters are not within the specified tolerance limits.

Every finished product is tested in accordance with the Shawcor Production Qualification Testing (PQT) Standards, and in accordance with API 15S. Samples are taken from the beginning and the end of every pipe run. The samples are subjected to destructive burst testing. The results from these tests must meet or exceed stringent QC requirements.

In addition, Shawcor tests raw materials to ensure compliance with material specifications. Shawcor testing equipment includes burst chambers, ovens, a cold chamber, a cyclic testing station, an Instron tensile testing machine, density test equipment, and numerous custom jigs and fixtures.

## 3 Fittings

Shawcor has a series of metallic fittings to join composite pipe to steel pipe, steel fittings, or other composite pipe(s) to accommodate a wide range of field applications. For steel terminus situations, the fitting can terminate the composite pipe with a standard ASME B16.5<sup>6</sup> lap-joint flange or a weld neck transition to steel pipe, valves or facilities. The end of the Shawcor product from one reel can be attached to the beginning of the Shawcor product from a second reel with a pipe-to-pipe coupling, thus eliminating an underground flanged connection.

## 3.1 Fitting Configurations

The three types of fittings that are used with Shawcor Spoolable Products are shown in <u>Table 2</u>. Each of these fittings is available for each pipe size and grade. For design and installation purposes, it is important to note that Shawcor fittings are rated to match ASME and API flange ratings dimensionally and flange ratings are typically lower than the Shawcor Spoolable Products pressure rating. As with all fittings and pipelines, pressure ratings of all components must be considered along with safety considerations and the weakest link will likely dictate system pressure rating (often referred to as Maximum Operating Pressure or Maximum Allowable Operating Pressure with appropriate pressure testing considerations). A thorough Engineering and Design review is required to ensure applicable pipeline regulations are met.

<sup>&</sup>lt;sup>6</sup> ASME B16.5 Pipe Flanges and Flanged Fittings.



Refer to the installation manual document number 14-1096 for guidance on the installation of crimp fittings.

Shawcor also offers pre-assembled flow joint fittings in the configurations shown in <u>Table</u>  $\underline{3}$ .

 Table 2: Crimp Fittings

(	Flanged End Fitting	
@ SHAWCOR	Compatible with standard raised face flanges. Slip-on flange is free to spin until bolts are tightened, allowing easy connection without stressing existing flanges.	
(D.SHAWCOR	Coupling Fitting Used to connect two pieces of Shawcor Spoolable Products together.	Dimensional drawings available upon request.
	Weld Neck Fitting	
(1) SHAWCOR	Used to connect Shawcor Spoolable Products to steel pipe, using standard field welding procedures.	



#### Table 3: Custom Crimp Fittings

90 Degree Elbow Flow Joint	
Tee Flow Joint	Dimensional drawings available upon request
True Y Flow Joint	See <u>Section 7.2</u> for pigging guidance.
Y-Lateral Flow Joint	

#### 3.2 Design

The fitting consists of a mandrel that is inserted into the pipe, and a sleeve that is crimped around the pipe. The mandrel and sleeve are both equipped with uni-directional teeth that securely grip the liner and jacket of the pipe. Crimping the sleeve creates very high permanent clamping pressure, which holds the reinforcement securely in place. The fitting system does not require the application of heat or adhesives in order to mechanically bond components together.

## **TECHNICAL MANUAL**





Figure 3: Cutaway View of Shawcor Fitting

The mandrel is equipped with two O-rings that provide the primary seal.

The vent hole in the sleeve allows the annulus of the pipe (the space between the liner and jacket which contains the reinforcement layer) to vent freely at each fitting. This allows any gases that may have permeated through the liner to escape and prevents any pressure buildup in the annulus. It is important that the vent hole remains unobstructed. Water ingress through the vent hole must be prevented by using the proper fitting wrapping procedure. See the Installation Guide for more information.

Shawcor fittings are installed in a two-step process, using portable installation equipment. In the first step, the mandrel is inserted into the liner. In the second step, the sleeve is crimped to the pipe. The fitting is supplied with the sleeve already welded to the mandrel to hold it in the correct position. To view a simulation of the fitting installation process, visit the Shawcor website at <u>www.shawcor.com</u>.

Shawcor fittings have been tested together with our products as a complete system in long-term, high pressure tests, and have undergone rigorous testing to verify their performance in field conditions. More information on qualification testing is presented in <u>Section 4.4</u>.

The inside diameter of the mandrel in the fitting is smaller than the inner diameter of the pipeline. However, the restriction is minimal, and results in negligible pressure loss (see <u>Section 5.4</u> for further information). Fittings are compatible with pigging programs as detailed in <u>Section 7.2</u>.

# **SHAWCOR**

#### 3.3 Materials

Standard Shawcor fittings are manufactured from seamless steel that meets the requirements of NACE MR0175<sup>7</sup> for sour service. See <u>Table 4</u> for a full list of materials used in Shawcor fittings. Material certificates are reviewed by Shawcor prior to manufacture of the fittings and are retained as part of Shawcor's Quality Management System (Shawcor QMS).

Weld neck fitting mandrels are manufactured using the same alloy steel material as flange and coupling fittings, with a short carbon steel pup welded to the end of the mandrel. This pup makes the weld neck fitting suitable for field-welding to standard carbon steel pipe and fittings of various pipe schedules.

The steel used in 4" and 5" Shawcor fitting mandrels and flanges meet the low-temperature notch-toughness requirements of Category II of CSA Z662 with a minimum design temperature of -45°C. Whenever required, custom made mandrels and flanges in 2" and 3" sizes with proven low-temperature notch-toughness properties can also be supplied.

Custom made crimp fittings with a stainless steel mandrel can be specified. The end user is responsible for the material selection of the fittings.

Part	Material type	Material grade(s)	
Mandrel	Alloy steel <sup>a</sup>	AISI 4130, 4140 or similar	
	or	or	
	Stainless Steel <sup>a</sup>	Duplex 2205	
Sleeve	Carbon steel <sup>a</sup>	ASTM A106, A333, A519, or similar	
Flange	Carbon steel <sup>a</sup>	ASTM A105 or ASTM A350 LF2	
		Class 1	
Weld neck fitting	Carbon steel <sup>a</sup>	ASTM A106, A333 or similar	
welding end	or	or	
	Stainless Steel <sup>a</sup>	Duplex 2205	
Flow joints (tee, elbow,	Carbon steel <sup>a</sup>	ASTM A234 WPB or ASTM A420	
etc.)		WPL6	
O-rings	FKM	Viton A - 75 Durometer (for regular	
	Fluorocarbon	service) or	
	Elastomer	High Performance FKM - 90	
		Durometer (Low Temperature &	
		Rapid Decompression resistant)	
Coatings	Electroless Nickel or uncoated. Weld neck and stainless		
	steel fittings are not coated.		

 Table 4: Shawcor Fitting Material List

<sup>a</sup> Meets requirements of NACE MR0175 for sour service

<sup>&</sup>lt;sup>7</sup> ANSI / NACE MR0175 / ISO 15156 Petroleum and Natural Gas Industries—Materials for Use in H<sub>2</sub>S-Containing Environments in Oil and Gas Production



### 3.4 Manufacturing

Shawcor fittings are manufactured, coated, assembled, and labeled according to Shawcor specifications by suppliers whose processes have been qualified by Shawcor. Shawcor routinely verifies and audits the QC programs of these suppliers.

All welding required for the manufacture of Shawcor fittings is performed in shop conditions, by suppliers with qualified weld procedures in accordance with CSA Z662 or equivalent. These procedures are specific to the materials used and include appropriate heat treatments and inspections.

#### 3.5 Corrosion Protection

Shawcor fittings are supplied with high-phosphorus Electroless Nickel Coating (ENC). This ENC coating protects the fitting wetted surfaces from corrosion and erosion for many applications. Additional information about ENC is available upon request. Weld neck fittings are not coated, since the coating would be damaged by the heat input during welding. Prefabricated flow joints can be coated, since no welding is required during installation.

ENC can typically provide an effective barrier against corrosion for many of the products transported in the oil and gas industry and in a wide range of applications, however ENC may not be appropriate for all applications. As with all protective coatings, coating failure or damage is possible for a variety of reasons. For those customers with low tolerance for coating failures, other materials may be considered. Bare steel or stainless steel (Duplex 2205) fittings are also available.

The end user is responsible for the final decision regarding material selection of the fittings, compatibility of materials with the product transported, and the adequacy of corrosion mitigative measures including the effectiveness of coatings. End users may select and install externally supplied alternative coatings; please consult Shawcor Engineering regarding compatibility with Shawcor fitting design.

During fitting transportation and installation, the coating must be protected from damage. It is recommended to keep the protective caps supplied with fittings in place until the time the fitting is installed.

Although the sleeves may be coated with ENC, it is not intended for corrosion protection as the crimping process will damage the surface of the nickel coating. Flash surface rust may occasionally be present on the sleeve surface or the flange ring.

After fitting installation, Shawcor crimp fittings must be wrapped with tape to mitigate external corrosion, and to prohibit water ingress from reaching the pipe reinforcement. In both buried and surface installations, it is mandatory to apply the appropriate wrapping on all crimp fittings. Only materials and methods approved by Shawcor may be used. See the Shawcor Pipe Installation Guide for details.



To reduce the likelihood of water ingress past the fitting wrapping, a maximum of 1 meter (3 feet) of water depth above the vent hole is allowed. If the installation has more water depth than this, the vent hole must be eliminated. Discuss options to accomplish this with Shawcor Engineering.

In jurisdictions requiring, or in applications deemed advantageous, an optional sacrificial anode can also be applied to the crimp fitting. Shawcor has developed a sacrificial ribbon anode kit for buried steel fittings that provides external corrosion protection for a 50 year life in soil resistivities ranging between 1500 to 3000 ohm/cm. This is based on a fitting external wrapping efficiency of 95%. Please refer to the Shawcor Pipe Installation Guide for more information.

## 4 **Qualification**

## 4.1 Introduction to Standards and Regulations

According to industry terminology, Shawcor pipe is classified as a reinforced thermoplastic pipe (RTP). Various standards deal with this type of product, and cover topics such as materials, testing, manufacture, and installation. Standards are guidelines that are generally accepted throughout an industry as appropriate, usually on the basis of industry-wide experience. They are often referenced by regulations, which may adopt some or all of the guidelines, or even introduce more stringent requirements. Regulations are requirements that must be followed by law.

Standards that apply to Shawcor products are primarily performance-based. This means that they emphasize the demonstration of a product's capabilities through repeated testing, rather than relying only on theoretical design calculations. A detailed theoretical design model serves as a starting point for Shawcor product designs. The designs are validated through extensive testing in accordance with accepted test standards.

## 4.2 Standards

#### 4.2.1 American Petroleum Institute (API)

API was the first North American standards body to develop a standard specific to the spoolable composite pipe industry. API 15S, *Spoolable Reinforced Plastic Line Pipe*, includes guidelines for determining material properties, pressure ratings, safety factors, and minimum performance requirements. It also includes guidelines for manufacturing, quality control tests, and typical installation methods. This specification applies to spoolable reinforced line pipe with both helically wrapped steel or non-metallic reinforcing elements.



API 15S is based on expert knowledge and experience with the materials involved. It uses proven ASTM testing methods, such as ASTM D2992<sup>8</sup>, for establishing long-term performance.

All Shawcor products meet or exceed the stringent qualification requirements established by API 15S. API 15S is the standard most recognized internationally for the qualification of spoolable reinforced plastic line pipe.

#### 4.2.2 Canadian Standards Association (CSA)

CSA provides standards to which manufacturers should comply. CSA Z662, *Oil and Gas Pipeline Systems*, covers the design, construction, operation, and maintenance of oil and gas industry pipeline systems. Shawcor Spoolable Products fall under Clause 13.1 of this standard, which specifically addresses design, manufacturing, and installation requirements for reinforced composite pipelines.

Shawcor is fully compliant with CSA Z662 Clause 13.1. Some of the specific requirements are discussed below. Other requirements are discussed in more detail elsewhere in this document, as referenced in <u>Table 5</u>.

According to CSA Z662, reinforced composite pipelines may be used in low vapor pressure (LVP)<sup>9</sup>, gas gathering, and oilfield water pipelines. High vapor pressure (HVP)<sup>10</sup> pipelines are excluded by this standard. Shawcor Spoolable Products also meet the requirements of CSA Z662 Clause 12 for gas distribution systems<sup>11</sup>.

Design pressure calculations for RTP are outlined in Clause 13.1. This clause refers to API 15S as the industry standard according to which Shawcor Spoolable Products must be qualified. Design pressure calculations are shown in <u>Section 5.2.3</u>.

Shawcor fittings are engineered for suitable low-temperature notch toughness. The material properties meet CSA Z662 Category II requirements with a minimum design temperature of -45°C.

<sup>&</sup>lt;sup>8</sup> ASTM D2992 Standard Practice for Obtaining Hydrostatic or Pressure Design Basis for "Fiberglass" (Glass-Fiber-Reinforced Thermosetting Resin) Pipe And Fittings

<sup>&</sup>lt;sup>9</sup> Includes oilfield water, multiphase fluids, or liquid hydrocarbon mixtures with a vapor pressure of 110 kPa (absolute) or less at 38°C.

<sup>&</sup>lt;sup>10</sup> Hydrocarbons or hydrocarbon mixtures in the liquid or quasi-liquid state with a vapor pressure greater than 110 kPa (absolute) at 38°C.

<sup>&</sup>lt;sup>11</sup> Based on a design life of 50 years.



Requirement	Reference in this manual
Gas service design pressure limit	Section 5.1.2
Sour gas limits	Section 5.1.5
Cyclic service	Section 5.3
Tracer wire	Section 6.6
Cathodic protection	Section 6.8
Pressure testing – new installations	Section 6.9
Static electricity	Section 7.5
Maximum external pressure	Section 5.12

#### Table 5: Links for Specific CSA Z662 Requirements

#### 4.3 Regulations

#### 4.3.1 Canadian Provincial Regulatory Bodies

The Alberta Energy Regulator (AER) is a regulatory body that oversees the development of Alberta's energy resources, including oilfield pipelines. Any oilfield pipeline in Alberta must be approved by the AER before installation, in accordance with its regulations. Other provinces in Canada have regulatory bodies with a similar role. Cross provincial installations are licensed under the National Energy Board (NEB) in a similar manner.

The AER allows Shawcor Spoolable Product applications to be processed as routine for fresh water, salt water, multiphase, crude oil/LVP, and natural gas service. Shawcor has developed a positive history with the AER through provision of data on design, manufacturing, testing, installation, and in-service evaluations. More information on the results of these evaluations can be found in <u>Section 8</u>. Shawcor has also established relationships with the corresponding regulatory bodies in British Columbia, Saskatchewan, and Manitoba, and installations have been completed in each of these provinces.

#### 4.3.2 United States Regulatory Bodies

Shawcor Spoolable Products are extensively used in class 1 areas in the United States. In United States Department of Transportation (DOT) regulated areas, the DOT considers the use of Shawcor Spoolable Products through special permit applications submitted to the Office of Pipeline Safety. Currently, Shawcor is working with the Department of Transportation to eventually include Reinforced Thermoplastic Pipes as an approved material in 49 CFR Part 192 "Transportation of Natural and Other Gas by Pipeline: Minimum Federal Safety Standards" and Part 195 "Transportation of Hazardous Liquids by Pipeline".



#### 4.3.3 Other Regulatory Bodies

Australia:

Shawcor Spoolable Products have been accepted by several regulatory bodies in Australia, in accordance with AS 2885.1 "Pipelines – Gas and liquid petroleum" for use as emulsion and oil pipe lines.

Mexico:

Shawcor Spoolable Products have been certified by ABS Group Services de Mexico. FP and FP HT comply with NRF-185-PEMEX-2008 "Tubería Plástica Reforzada Enrollable para recolección y Transporte de Hidrocarburos Líquidos y Gaseosos" and FCLP complies with P.2.0730.01 "Tubería Plástica Reforzada Enrollable para recolección y Transporte de Hidrocarburos Líquidos y Gaseosos".

Shawcor also has qualified its product with several oil and gas operators in the Latin American Region.

### 4.4 Testing

Shawcor is committed to ensuring that its products are rugged, reliable, and safe. Shawcor Spoolable Products are tested together with fittings as a complete system. This system has undergone extensive testing to demonstrate that it meets and exceeds the strict requirements of API 15S.

Some of the specific tests in Shawcor's testing program are listed in <u>Table 6</u>. These tests have resulted in a comprehensive base of knowledge about product performance under a wide variety of service conditions.

Test description
Regression pressure testing
Elevated temperature pressure testing
Low temperature pressure testing
Minimum bend radius pressure testing
Short term burst pressure testing
Cyclic pressure testing
Respooling preconditioning
Axial load testing
Rapid gas depressurization
Impact resistance testing
Thermal expansion & pressure-expansion testing
Solar radiation resistance
Thermal cycle testing
External load testing
Corrosion testing - for steel cords

#### Table 6: Pipe and Fitting Tests

# **SHAWCOR**

## 5 Performance

## 5.1 Applications & Chemical Compatibility

The information in this section is intended to provide an understanding of the suitability of the products for a wide range of common applications. For these or other applications, Shawcor's engineering team will be pleased to evaluate the application and provide general guidance regarding compatibility of Shawcor Spoolable Products.

### 5.1.1 Application Evaluations

Shawcor has established a systematic process to evaluate proposed applications in order to compare conditions with the normal operational limits given in the following sections. These limits are intended to provide a consistent and conservative basis to potential applications.

Application evaluations are provided by the Shawcor Engineering team as a service to clients. Each evaluation assesses the details of a proposed application to identify potential risks and determines specific measures that can be taken to eliminate or minimize them. Recommendations resulting from these evaluations have allowed many projects to successfully take advantage of the full capabilities of Shawcor Spoolable Products. Shawcor believes that this approach reflects its commitment to public safety and has contributed to its outstanding service record, while allowing it to meet the unique needs of its clients. In order to maintain the above commitments, Shawcor reserves the right to not ship pipe until an application review has been approved and attached to the sales order.

#### 5.1.2 Gas

Shawcor has a strong historical record in gas applications. There is no requirement to further de-rate the Shawcor MAOP in gas applications (see <u>Section 5.2</u> for determination of pressure ratings). Suitable environments include natural gas, solution gas, and fuel gas. Shawcor Spoolable Products can also be used in sour (H<sub>2</sub>S) applications, but limits apply. Please refer to <u>Section 5.1.5</u> for more details. See <u>Section 5.1.6</u> for information on  $CO_2$  applications.

For gas applications in which condensates can form, a suitable pigging program should be implemented to prevent condensate buildup at low points along the pipeline.

Clause 13.1 of CSA Z662 limits the allowable design pressure for RTP gas pipelines to a maximum of 9930 kPa (1440 psi).

#### 5.1.3 Oil

Shawcor Spoolable Products are suitable for oil emulsion or oil transfer applications and are fully piggable. For applications with high wax content, suitable pigging programs should be in place. Please refer to <u>Section 7.2</u> for more information on pigging.



#### 5.1.4 Water

Shawcor Spoolable Products are an excellent option for oilfield water applications such as water transfer, frac water movement, disposal, and injection lines. However, these applications often involve cyclic pressure variations, and should be evaluated for compatibility. Please refer to <u>Section 5.3</u> for more information on cyclic pressure applications.

#### 5.1.5 H<sub>2</sub>S

H<sub>2</sub>S (hydrogen sulphide, also known as sour gas) is a toxic and potentially lethal substance commonly found in oilfield media. Accordingly, a greater risk exists in routine pipeline inspection or maintenance, or in the event of fluid release due to pipeline damage.

Non-metallic pipelines may allow some of the transported medium to absorb into and permeate through polymeric materials. The potential exists for this absorbed and permeated medium to accumulate to hazardous levels within the pipe material or fitting system. Accumulated H<sub>2</sub>S may be released during pipeline work. Examples of work include external damage, tie-ins, repairs, and removal of external tape and insulation from fittings.

Shawcor Spoolable Products are designed to vent gases that permeate through the liner. Permeated gases travel via the annulus reinforcement layer and are released at the fittings through a vent hole in each fitting. Permeated gases may also be released along the length of the pipeline (see <u>Section 5.10</u>).

Similar to other piping components in sour gas service (threaded fittings, gaskets, packing), due consideration should be given to the potential accumulation of H<sub>2</sub>S around the vent hole of the Shawcor fittings. Please refer to the *Shawcor Sour Service Pipeline Bulletin*, available from the Shawcor website, for more information.

Non-metallic pipelines may be more susceptible to external damage than metallic pipelines. Damage to or misuse of Shawcor Spoolable Products may result in uncontrolled release of the H<sub>2</sub>S containing medium being transported, which may result in serious injury or death. External forces, both during installation and during future disturbance or construction in the area, are potential causes of external damage to pipelines.

FP and FP HT are compatible with  $H_2S$ . Shawcor chooses to limit  $H_2S$  content of up to 10% by mol in the gas phase of liquids (oil and/or water), gas, or multiphase. CSA Z 662 Clause 13.1 limits the partial pressure of  $H_2S$  in gas to 50 kPa (7.25 psi) for all composite pipe used in sour gas applications. Applications above 10% are evaluated on a case by case basis<sup>12</sup>. FC is suitable for the transport of liquids (oil and/or water), gas, or multiphase with up to 3000 ppm of  $H_2S$ . This limit has been established by extensive

<sup>&</sup>lt;sup>12</sup>The AER (Directive 71) requires calculation of H<sub>2</sub>S release volumes for multi-phase pipelines.



corrosion testing on the steel cord reinforcements of the FC product and has been approved by an independent third party engineering firm.

#### 5.1.6 CO<sub>2</sub>

Shawcor Spoolable Products can be used for gases or liquids containing up to 100% CO<sub>2</sub> by volume. The suitability for CO<sub>2</sub> service has been confirmed by rapid decompression testing. The standard 75 Durometer FKM O-rings are suited for a wide range of CO<sub>2</sub> applications. For applications having higher than 10% CO<sub>2</sub> and operating at pressures above 750 psi, Shawcor recommends the use of special O-rings that provide superior performance for these conditions. Refer to <u>Section 3.5</u> for further information on the fitting corrosion resistance.

#### 5.1.7 Aromatic and Cycloalkane Hydrocarbons

Shawcor Spoolable Products are compatible with aromatic and cycloalkane hydrocarbons (e.g., benzene, toluene, ethyl benzene, xylene, naphthalene, and cyclohexane) in gas or liquids. <u>Table 7</u> lists the allowable aromatic and cycloalkane concentrations for normal operating pressures, based on Shawcor test data.

Product Line	Operating temperature	Maximum allowable aromatic and cycloalkane content (by volume)	
FP and FC	60°C (140°F) or below	50%	
FP HT	82°C (180°F) or below	50%	

 Table 7: Allowable Aromatic and Cycloalkane Hydrocarbon Content

#### 5.1.8 Chemical Injection

Common injection chemicals used in the oil gathering industry, such as corrosion inhibitors, biocides, paraffin dispersants, surfactants, scale inhibitors, defoamers, and demulsifiers, are not considered problematic to the HDPE liner. Shawcor recommends that chemical injection programs use dilute concentrations or batch treatments, as per the standard practice for HDPE applications as set out by the chemical manufacturing company.

Injection chemicals which are made up from aromatic and cycloalkane hydrocarbons are acceptable for use with the HDPE liner provided the concentration of the injection chemicals is controlled such that the aromatic and cycloalkane concentration stays within the limits listed in <u>Table 7</u> as applicable for the pipe service temperature. Any higher concentration batch treatment process should be of limited duration as recommended by the injection chemical manufacturer for use in HDPE pipe or Shawcor fittings.

This section addresses only the more common injection chemicals used in the oil gathering industry. Due to the variety of injection chemicals available, however, Shawcor recommends that the pipeline operating company develop an injection program in conjunction with the chemical manufacturing company to ensure there are no chemical compatibility concerns with HDPE or Shawcor fittings.



#### 5.1.9 Methanol and Ethylene Glycol

HDPE has good resistance to concentrated methanol and ethanol at temperatures up to 60°C (140°F). Alcohols may be used in Shawcor Spoolable Products during hydrotests to prevent freezing. They may also be used in FP and FP HT in batch programs. Due to the possible introduction of oxygen with alcohols, continuous injection of alcohols in FC is not recommended. Continuous injection of alcohols with FP and FP HT should be evaluated by the end user for compatibility with the metallic fittings.

#### 5.2 Pressure and Temperature Ratings

#### 5.2.1 Maximum and Minimum Allowable Operating Temperature

The Maximum Allowable Operating Temperatures (MAOT) and minimum allowable operating temperatures for Shawcor Spoolable Products are indicated in <u>Table 8</u>. These temperatures have been proven by the successful completion of the required qualification testing and the positive track record of field applications.

Product Line	Maxir Allow Opera Tempe	num vable ating rature	Minimum Allowable Operating Temperature (Standard O-rings)		Minimum Allowable Operating Temperature (Alternative LT O-rings, Standard for Canadian Applications)	
	(°C)	(°F)	(°C)	(°F)	(°C)	(°F)
FP	60	140	-10	14		
FP HT	82	180	-5	23	-29	-20
FC	60	140	-10	14		

#### **Table 8: Maximum and Minimum Allowable Operating Temperatures**

Note: LT O-rings are supplied as standard for all Canadian applications.

Shawcor Spoolable Products have excellent impact resistance properties and do not become brittle at low temperatures. Shawcor Spoolable Products can be installed at temperatures lower than 0°C (32°F). Refer to the Shawcor Installation Guide for cold temperature installation limits, fittings materials selection, and starting up pipelines at low temperatures.



#### 5.2.2 Maximum Allowable Operating Pressures

The Maximum Allowable Operating Pressures (MAOP) are shown in <u>Table 9</u>. These pressures have been established by performing the qualification testing at the MAOT of each product line.

Maximum Allowable Operating Pressure*								
Product Line	150		301		601		901	
	(kPa)	(psi)	(kPa)	(psi)	(kPa)	(psi)	(kPa)	(psi)
FP	2,068	300	5,171	750	10,342	1500		
FP HT	2,068	300	5,171	750	10,342	1500		
FC							15,513	2,250

#### Table 9: Maximum Allowable Operating Pressure

\*Check if your local regulation has a limit on the maximum allowable operating pressure, as it may be lower than the Shawcor Spoolable Products maximum allowable design pressure.

### 5.2.3 Calculations for Determining Maximum Allowable Operating Pressure

The MAOP listed in <u>Table 9</u> for FP and FP HT has been determined by the following calculations as per API 15S:

 $MPR = LCL_{RCRT} \times F_d$  $NPR \le MPR$  $MAOP = NPR \times F_{fluid}$ 

Where:

MAOP = Maximum Allowable Operating Pressure MPR = Maximum Pressure Rating NPR = Nominal Pressure Rating  $LCL_{RCRT}$  = Lower Confidence Limit, Regression Curve Reference Time  $F_d$  = Design Factor  $F_{fluid}$  = Service Fluid Factor

The Maximum Pressure Rating (MPR) has been determined at the qualification temperature and reference time (175,000 hours/20 years) for the pipeline in accordance with API 15S and includes the required Design Factor ( $F_d$ ). The chosen Nominal Pressure Rating (NPR) must be equal to or less than the MPR.

The Service Fluid Factor ( $F_{fluid}$ ) is the factor intended to provide additional protection based on consequence and not fluid compatibility. This factor is applied to the NPR to determine the MAOP at the qualification temperature.

The procedure utilized to establish the MAOP of FP and FP HT is illustrated in <u>Figure 4</u>, where data from multiple long-term pressure tests are plotted on a log-log graph. The

# **SHAWCOR**

## **TECHNICAL MANUAL**

MPR is derived using statistical calculations and includes a Design Factor ( $F_d$ ) which is the factor intended to account for normal variations in materials, manufacturing, and installation, to ensure that these variations do not cause the pipe's actual capabilities to be exceeded. Shawcor uses an  $F_d = 0.67$ , as per API 15S.



Figure 4: Illustration for Determining MPR and MOP<sup>13</sup>

Shawcor FP and FP HT Products have been designed using an  $F_{fluid} = 0.67$ . This value allows a consistent MOP for all types of fluids. It meets the API 15S and CSA Z662 requirements for gas and is more conservative than these requirements for other services.

Shawcor Spoolable Products are suitable for use in cyclic applications and have been tested using the test methodologies of API 15S.

<sup>&</sup>lt;sup>13</sup> API SPEC 15S Spoolable Reinforced Plastic Line Pipe.



The FC Maximum Pressure Rating is determined in accordance with API 15S. <u>Table 9</u>, includes the use of the required design factors, and considers the effects of the transported medium on the material properties. Accordingly, and in line with CSA Z662, FC's MAOP has been determined using a Fluid Factor ( $F_{fluid}$ ) of 1.0 for all service fluids shown in Table 13.1 of CSA Z662.

Because Shawcor's MAOP already includes the required design and fluid factors, Shawcor Spoolable Products can be operated in the field at pressures up to the MAOP published by Shawcor.

The effect of pressure cycling (i.e., cyclic pressure service factor  $F_{cyclic}$  of CSA Z662) is taken into account during the application evaluation conducted by Shawcor on a project by project basis. The amplitude of the pressure fluctuations that the system will see under typical operating conditions is compared to the cyclic test data generated by Shawcor during laboratory testing, and a safe cycling frequency is determined. A Cyclic Pressure Service Factor ( $F_{cyclic}$ ) of 1.0 has been used to determine the MAOP values shown in Table 9.

## 5.3 Cyclic Pressure

To ensure the optimal performance and reliability of Shawcor Spoolable Products, consideration must be given to the cyclic pressure characteristics of the operating regime.

As part of Shawcor's commitment to quality and customer satisfaction, an application evaluation process is required to ensure optimal performance of the product. The pipeline end user provides the operating parameters as per the Application Review Form for assessment. Shawcor applications engineers provide project specific recommendations regarding selection of the best product and operational considerations for the intended application. The recommendations of an application review are based on a minimum 20 year service life. The end user is responsible for performing a thorough engineering and design review to ensure they are meeting applicable pipeline regulations.

The key parameters that influence the selection of the pipe type for a cyclic service application are:

- Type of pump: The pump type plays a major role in determining the cyclic characteristics of a pipeline system. Pumps can be generally divided into pulsating and non-pulsating types.
  - Most pulsating pumps are of the reciprocating positive displacement type, such as Triplex, Quintuplex, and Diaphragm pumps. These pumps generate a pulsating flow and pressure output as a result of their back and forth mechanical action. A peristaltic pump is also a pulsating pump. Standard industry practice estimates the working peak-to-peak amplitude of highfrequency pulsations to be 10% of the mean pressure value. To protect Shawcor Spoolable Products from progressive damage, effective pulsation dampeners are required at the pump inlet and outlet, which are typically

designed to limit peak to peak amplitude to 3% of the operating pressure. In addition, a minimum of 100 feet of steel pipe between the pump and the pipe is required to assist with vibration dissipation.

- Non-pulsating pumps such as centrifugal, progressive cavity, screw, and gear, are characterized by their rotating mechanical action resulting in a smooth flow and pressure output.
- Pump Jacks are a unique type of positive displacement pump and are considered separately below.
- Pressure fluctuations:

SHAWCOR

- Pump start/stop cycles where the pressure in the pipeline system cycles between the operating pressure and the shut off pressure
- Typical pressure changes during operation
- Modifications to the system operation or layout, such as operating an additional pump or injecting into a different well
- Shawcor Spoolable Products have the capability to handle infrequent pressure excursions up to the pipe MAOP as shown in <u>Table 9</u>.

Depending on their magnitude and frequency, pressure pulsations and fluctuations could be detrimental to the pipe performance. Contact your Shawcor representative for a project specific application evaluation.

#### 5.3.1 FP Cyclic Capabilities

Applications with non-pulsating pumps can be operated at the full FP pressure rating, as this type of pump provides a steady pressure output free of high frequency pressure pulsations or excessive vibration. Additionally, FP can handle mild pressure fluctuations and these applications need to be evaluated on a case-by-case basis using the Shawcor application review process.

Applications with pulsating pumps can be detrimental to many pipeline materials. It is required to maintain the peak-to-peak amplitude of high-frequency pressure pulsations below 15 psi for FP301 and below 25 psi for FP601.

For all application types and in order to eliminate large amplitude pressure fluctuations resulting from pump on/off cycles, Shawcor strongly recommends using a variable frequency drive (VFD) to regulate the flow rate while maintaining continuous operation of the pump, and to provide a soft start/stop whenever the pump shuts down.



#### 5.3.2 FP HT Cyclic Capabilities

FP HT has reduced performance in cyclic applications but is otherwise similar to FP.

It is required to maintain the peak-to-peak amplitude of high-frequency pressure pulsations below 10 psi for FP301HT and below 20 psi for FP601HT.

#### 5.3.3 FC Cyclic Capabilities

FC is suitable for service in systems subject to severe cyclic pressure conditions with either pulsating or non-pulsating pumps. FC is adequate for use with pulsating pumps operating at pressures up to 15,513 kPa (2,250 psi) and peak-to-peak pressure pulsations of up to 1,551 kPa (225 psi). Pulsating pumps can generate large peak-to-peak pulsations well in excess of 225 psi.

FC is also suitable for applications with large amplitude pressure cycles of up to 10 cycles per day of 0 - 10,342 kPa (0 - 1,500 psi), 1 cycle per day of 0 - 13,790 kPa (0 - 2,000 psi), or 4 cycles per week of 0 - 15,513 kPa (2,250 psi) based on a minimum service life of 20 years.

#### 5.3.4 Pump Jacks

To ensure the optimal performance and reliability in pump jack applications, consideration must be given to the cyclic pressure characteristics of the system design and the operating regime.

In general, using sound system design and good industry operating practices will optimize the integrity and life of all production equipment. The pressure differential between the upstroke and downstroke pressures generated by the operation of the pump jack is of critical importance to the long-term integrity of the Shawcor Spoolable Product.

Some of the design and operational factors that can affect the magnitude of the pressure differential in the flow line include:

- Length and diameter of the flow line
- Production volumes
- Production fluid properties
- Down hole pump integrity
- Wax build-up
- Flow line check valve integrity
- Hot oiling and pigging practices

For FP and FP HT applications with upstroke pressures below 150 psi, it is required to routinely monitor the pressure profile to ensure the upstroke and downstroke pressures stay within the allowable 100 psi differential pressure for FP601, 75 psi differential pressure for FP301 and FP601HT product, and 50 psi differential pressure for FP301HT. For example, if the normal upstroke pressure in an FP301 flow line is 150 psi, the



minimum pressure during the downstroke should be no less than 75 psi. Infrequent pressure excursions beyond these limits are generally acceptable.

For FP and FP HT applications with upstroke pressures between 150-250 psi, it is required to routinely monitor the pressure profile to ensure the upstroke and downstroke pressures stay within the allowable 75 psi differential pressure for FP601, 50 psi differential pressure for FP301 and FP601HT product, and 30 psi for FP301HT. Infrequent pressure excursions beyond these limits are generally acceptable.

Contact Shawcor engineering for additional guidance regarding FP and FP HT applications with upstroke pressures above 250 psi.

FC is suitable for use in pump jack applications with severe pressure cycling parameters. It is required to routinely monitor the pressure profile to ensure the upstroke pressure stays within the allowable 500 psi differential pressure for FC901 product.

These recommendations are based on both qualification test results and field experience. They provide safe operating limits based on a minimum design life of 20 years. In order to ensure the long-term integrity of the piping system,

- Shawcor recommends:
  - Installing and maintaining a pressure switch (such as a Presco switch) set at a maximum of 100 psi above the upstroke pressure to limit the possibility of subjecting the pipeline to excessive pressure swings for extended time durations.
  - Routinely monitoring the upstroke and downstroke pressure values using a calibrated pressure gauge mounted between the well head and the flow line.
- Shawcor requires:
  - If wax or scale buildup is expected, to pig the line often enough, or use a wax dispersant program, to avoid having the normal operating pressures increase to the point of exceeding the guidance provided for the pressure differential between the upstroke and downstroke as a result of a reduced pipe cross section.
  - The use of properly maintained check valves to minimize the pressure fluctuation in the flow line.

## 5.4 Flow Characteristics

#### 5.4.1 Pipe Flow

Relative to bare steel pipe, the smooth internal surface of Shawcor Spoolable Products polyethylene liner provides favorable flow rates and reduced pressure losses as a result of reduced friction. Figure 5 and Figure 6 show representative pressure drops at various flow rates for salt water and methane @ 20°C (68°F), respectively. The results shown are based on calculation of the pressure drop for the given fluid in each size of the product using the Darcy-Weisbach method. The pressure drop for a given flow rate in the line will be significantly lower than for the similar ID steel pipe, as the surface of the steel can become rougher over time due to corrosion and scale buildup. Conversely, a higher flow rate can be attained for a given pressure drop using Shawcor Spoolable Products.

For other flow scenarios, the pressure drop can be calculated using any of the flow coefficients listed in <u>Table 10</u>.



**Figure 5: FlexPipe and FlexCord Pressure Drop Values for Sea Water** \*Calculations based on 1000 meter of pipe length, with sea water at 20°C (68°F)

## **TECHNICAL MANUAL**

# **SHAWCOR**



Figure 6: FlexPipe and FlexCord Pressure Drop Values for Gas \*Calculations based on 1000 meter of pipe length, with methane at 20°C (68°F) compressed to 1000 psi

Table 10: Flow Coefficients for Shawcor Spoolable Products
--

Hazen & Williams	150		
Darcy Weisbach	0.0015 mm (0.000005 ft)		
Manning	0.009		

## 5.4.2 Fittings

The inside diameter of the mandrel of the pipe fitting is smaller than the inner diameter of the pipeline (see <u>Section 3.2</u>). However, the restriction is minimal, and very few fittings are required even for very long lengths of pipe. The associated pressure loss is negligible compared to the pipe friction discussed above.

The following equations and K factors for Shawcor coupling fittings can be used to calculate the loss in pressure or pressure head due to the flow constriction.

Pressure loss:

$$\Delta P_{fitting} = K \frac{\rho V^2}{2}$$
$$h_{fitting} = K \frac{V^2}{2g}$$

Where:  $\rho =$ fluid density V =fluid velocity g =acceleration due to gravity K =factor from <u>Table 11</u>

Pressure head loss:

Fitting size	K factor
2"	0.56
3"	0.55
4"	0.33
5"	0.34
6"	0.31

#### Table 11: K Factor for Shawcor Spoolable Products Coupling Fittings

## 5.5 Durability

Shawcor Spoolable Products are a durable, rugged product. The high-strength, pipegrade thermoplastic used in the jacket protects the reinforcement from the environment. The jacket is highly resistant to cracking, and will not bruise, chip, or flake under normal handling. If the terrain is generally acceptable for steel pipelines it will be acceptable for Shawcor Spoolable Products.

Impact testing according to API 15S at -25°C (-13° F) has demonstrated a high level of resistance to impact loading from normal handling and installation activities.

Shawcor also tested a variety of its products to determine their ability to withstand exposure to an intense, fast moving brush wildfire. The test samples were exposed to a simulated intense, fast moving brush wildfire for three minutes and allowed to self-extinguish (burn until no flame was visible). FP601 and FP601 HT successfully held internal pressure until all flames self-extinguished. The FP601 and FP601 HT products were then pressurized to the 1,500 psi MAOP pressure and successfully passed this test. Finally, the FP601 and FP601 HT samples were burst at as much as 2.5 times MAOP.

## 5.6 Corrosion

Shawcor Spoolable Products liner and jacket will not corrode. See <u>Section 3.5</u> for a discussion on fitting corrosion protection.

FC is intended for applications where lined steel is typically specified and is expected to perform corrosion free.

#### 5.7 Erosion

Shawcor Spoolable Products will experience less erosion than steel in wet slurry applications (i.e., solid particles carried in a liquid) due to the elasticity and toughness of the liner material. However, a sufficient flow velocity should be maintained to prevent solid particles from settling out of the carrying liquid. Settled particles that slide along the bottom of the pipe may cause wear to the bottom surface.

To evaluate the erosion wear performance, the liner materials of Shawcor Spoolable Products were subjected to Shawcor's internal slurry jet erosion testing. The test was conducted with a slurry (1:10 silica to water by weight) velocity of 10 m/s at a 90° impingement angle for 7 hours in room temperature on triplicate samples. The erosion

# **SHAWCOR**

test results were then compared with similar test done on steel for two hours (See <u>Figure</u>  $\underline{7}$ ).



Figure 7: Erosion slurry test

Dry slurry applications (i.e., solid particles carried by a gas) may cause excessive static electricity build-up and/or heating due to dry particles sliding on the surface. Shawcor Spoolable Products may not be suitable for dry slurry applications. Please contact your Shawcor representative to conduct an application evaluation for your project in this case.

## 5.8 Ultra-Violet Protection

The outer jacket of Shawcor Spoolable Products are designed to withstand weathering effects due to solar heating and ultraviolet (UV) radiation. The outer jackets of all Shawcor Spoolable Products provide a minimum of 20 years protection against UV exposure.

To verify the UV life, samples were subjected to an accelerated weathering exposure according to the standard ASTM G155/ASTM D2565. The accelerated UV exposure test ran continuously to simulate 20 years of equivalent Florida conditions. The exposed specimens were removed for mechanical testing and the results were plotted in a semilog scale to allow evaluation of the mechanical integrity of the polymer samples after 20 years of simulated service life. The results met the requirement criteria that the tensile samples when elongated, should retain 50% of original (i.e., unexposed) elongation at break after their anticipated design life.



## 5.9 Bend Radius

The minimum allowable bend radius of Shawcor Spoolable Products differs in operation (pressurized) and transport/handling (un-pressurized) conditions, as shown in <u>Table 12</u>.

Shawcor Spoolable	Minimum k OPER	oend radius ATION	Minimum bend radius TRANSPORT & HANDLING			
Products	(m)	(ft)	(m)	(ft)		
2"	1.2	4.0	0.8	2.5		
3"	1.8	6.0	1.0	3.3		
4"	2.1	7.0	1.3	4.2		
5"	3.05	10	1.4	4.5		
6"	3.4	11	1.6	5.2		

Table 12: Minimum Bend Radius for Operation, Transport and Handling

Note: The minimum radius does not apply to fittings/couplings. These joints need to be kept straight to avoid point loading at the end of the fitting. Typically, there should be no bends within 1 meter (3 feet) from a fitting.

## 5.10 Permeation

Gas molecules are able to travel very slowly through pipe walls by moving through the spaces between the molecules of the pipe material. This is known as permeation. All piping materials allow gases to permeate to some extent, but composite materials allow more than steel pipes do. In rare cases permeation through the pipe can react with elements in the soil which can lead to discoloration of the surrounding soil or pipe jacket.

Shawcor Spoolable Products have a self-venting design which allows permeated gases to vent at the fittings. This prevents or reduces the pressure from building up within the annulus (the space between the liner and jacket that contains the reinforcement layer), thereby lowering the risk of liner collapse during line depressurization. Wherever it is desired to avoid venting permeated gas above grade, Shawcor offers fitting options where the vent hole can be connected to a venting system. In such installations, evaluation by Shawcor Engineering will be needed to determine the optimal distance to a vent location from the vented fittings to provide the pipeline with adequate venting capability. See Section 7.4 for depressurization guidelines.

The following calculations are based on a conservative model, in which the gases in the pipe permeate through the liner and then permeate through the jacket or travel along the annulus to exit through the vent hole at the fitting. The calculations use the permeability coefficients given in <u>Table 13</u>, which are experimentally determined from testing conducted on unreinforced polyethylene. The following example provides a representative illustration of the extent of permeation in Shawcor Spoolable Products.



Dormoont	HDPE Permeabi 60°C (	lity coefficient at 140°F)	PERT Permeability coefficient at 82°C (180°F)			
Fermeant	(cm³/cm-sec- MPa)	(inch³/inch-sec- psi)	(cm³/cm-sec- MPa)	(inch³/inch-sec- psi)		
Methane	2.23 x 10 <sup>-7</sup>	2.38 x 10 <sup>-10</sup>	6.64 x 10 <sup>-7</sup>	7.10 x 10 <sup>-10</sup>		
H <sub>2</sub> S	2 x 10 <sup>-6</sup>	2.14 x 10 <sup>-9</sup>	4.91 x 10 <sup>-6</sup>	5.25 x 10 <sup>-9</sup>		
CO <sub>2</sub>	8.43 x 10 <sup>-7</sup>	9.01 x 10 <sup>-10</sup>	2.01 x 10 <sup>-6</sup>	2.15 x 10 <sup>-9</sup>		

#### **Table 13: Permeability Coefficients**

Shawcor Spoolable Products liner has a similar DR (Dimension Ratio) in all sizes, which results in similar permeation rates for all sizes. <u>Table 14</u> shows expected permeation rates for a gas mixture of 89% methane, 1% H<sub>2</sub>S, and 10% CO<sub>2</sub>. To obtain expected permeation rates at different temperatures, it can be approximated that a 5°C (9°F) decrease in temperature results in a 30% decrease in permeation rate. The values listed in <u>Table 14</u> have been determined by the following equation:

#### Where:

Ρ

q =	PA(p'-p'')
<i>q</i> –	t

= F	Per	rmeability	coefficient	from	<u>Ta</u>	ble 13	<u>,</u>

q = Volume of gas permeating per unit length per unit time

- A = Surface area per unit length of pipe
- p' = Internal partial pressure
- p" = External partial pressure
- t = Wall thickness

#### Table 14: Representative Permeation Rates for Shawcor Spoolable Products

		Permeation rate						
		cm³/m	pipe/day)					
	Pipe	689 kPa	5171 kPa	10,342 kPa				
	pressure	(100 psi)	(750 psi)	(1500 psi)				
FP/FC at	89% methane	5 (0.1)	36 (0.7)	72 (1.3)				
10°C (50°F)	1% H <sub>2</sub> S	0.5 (0.009)	4 (0.07)	7 (0.14)				
	10% CO <sub>2</sub>	2 (0.04)	15 (0.3)	31 (0.6)				
	Total mixture	7.5 (0.14)	55 (1.0)	110 (2.1)				
FP/FC at	89% methane	23 (0.4)	175 (3)	349 (6)				
40°C (104°F)	1% H <sub>2</sub> S	2 (0.04)	18 (0.3)	35 (0.7)				
	10% CO <sub>2</sub>	10 (0.2)	74 (1.4)	148 (3)				
	Total mixture	36 (0.7)	266 (5)	533 (10)				
FP/FC at	89% methane	66 (1)	499 (9)	997 (19)				
60°C (140°F)	1% H <sub>2</sub> S	7 (0.1)	50 (0.9)	100 (2)				
	10% CO <sub>2</sub>	28 (0.5)	212 (4)	423 (8)				
	Total mixture	101 (2)	760 (14)	1521 (28)				
FP HT at	89% methane	198 (4)	1484 (28)	2969 (55)				
82°C (180°F)	1% H <sub>2</sub> S	16 (0.3)	123 (2)	247 (5)				
	10% CO2	67 (1)	505 (9)	1010 (19)				
	Total mixture	282 (5)	2113 (39)	4225 (79)				



## 5.11 Expansion/Contraction and Axial Growth

Shawcor Spoolable Products have been engineered to significantly minimize axial strain as a result of pressure or temperature changes in operation. Radial expansion will occur but will be far less than in unreinforced polyethylene.

When unpressurized, the product will display approximately the same amount of growth or contraction with temperature changes as unreinforced polyethylene. However, the low modulus and viscoelastic properties of the pipe allow it to shift and relax, thereby minimizing any loads exerted at end connections. Therefore, expansion loops and special consideration for end loads at termination points are not required\*.

See <u>Table 15</u> for expansion/contraction coefficients. The axial change can be expected to vary linearly with pressure.

Product	Length Change at 1500 psi (%)	Pressurized <sup>1</sup> Linear Coefficient of Thermal Expansion (m/m/°Cx10 <sup>-6</sup> )	Unpressurized Linear Coefficient of Thermal Expansion (m/m/°Cx10 <sup>-6</sup> )
2" FP601	0.23	107	157
4" FP601	0.25	106	141
2"FP601HT	0.32	145	130
6" FP601HT	0.36	105	93

#### Table 15: Axial Expansion/Contraction Coefficients

<sup>1</sup> Pressurized to 2250 psi

Sudden temperature and pressure changes should be avoided. Gradual or stepped flow increases should be used on very hot or very cold days to allow for gradual temperature and pressure changes in the system.

\*When Shawcor Spoolable Products are used as free standing liners, it is required to terminate the liner pull underground and provide a minimum of 7 meters of uncased buried length before bringing the pipe to surface. This ensures any expansion or contraction concentrated inside the existing casing is restrained by ground friction before coming to surface.

## 5.12 External Load and Internal Vacuum Capability

When the pressure outside the pipe may exceed the pressure inside the pipe, the pipe's ability to withstand collapse should be considered. External pressure arises from factors such as ground water pressure and the weight of soil above the pipe. Additional loads (such as the weight of water or live loads due to moving vehicles) must be considered if the pipe runs through a bore, through a casing, below a vehicle corridor, etc. Internal vacuums may result from liquid flow down a slope when the pipeline is unpressurized.



The ability of the products to withstand collapse is based on the total difference in pressure between the outside and inside of the pipe. The net external pressure can be calculated as follows:

 $P_{net,external} = P_{external} - P_{internal}$ 

Where P<sub>internal</sub> is a negative number (for an internal vacuum), P<sub>net.external</sub> is increased

Shawcor Spoolable Products external pressure resistance for buried applications has been measured according to ASTM D2412<sup>14</sup>. The maximum long term net external load that the pipe can withstand at 23°C (73°F) is 214 kPa (31 psi), when installed in backfill embedment material with a soil modulus of 1000 psi or greater and an internal pressure of 0 psi. This includes most soils, with the exception of very fine-grained or organic soils such as muskeg and clay. If the total combination of dead loads, live loads, and internal vacuum will exceed this, the pipe should be protected by a steel casing.

When on the surface, inside of a bore, or casing there is no support from surrounding soil. Under these conditions, the pipe can withstand a net vacuum pressure of 101 kPa (14.7 psi) at 23°C (73°F), the maximum vacuum pressure that will be created due to gravity flow down slopes.

When boring Shawcor Spoolable Products beneath large roads and rivers, it is sometimes required for the bore to be significantly deeper than standard boring. These bores, both cased and uncased, are likely to be filled with drilling mud or filled with ground water over time. This fluid within the bore or casing will exert an external load on the pipeline. Contact Shawcor Engineering for additional external collapse pressure guidance when the installations are deeper than 15 feet. If the deep bored pipeline will be left empty and unpressurized for extended periods of time (i.e., one year), contact Shawcor Engineering.

Higher temperatures or long term exposure to liquid hydrocarbons may reduce the net external load that the pipe can withstand. Shawcor Spoolable Products are not intended for subsea applications.

<sup>&</sup>lt;sup>14</sup>**ASTM D2412** Standard Test Method for Determination of External Loading Characteristics of Plastic Pipe by Parallel-Plate Loading.



## 5.13 Thermal Conductivity

Shawcor Spoolable Products thermal conductivity properties result from the properties of the polyethylene and the reinforcement materials. Accordingly, Shawcor Spoolable Products is a good thermal insulator with higher resistivity than metallic pipes. <u>Table 16</u> lists the approximate calculated thermal conductivity and resistivity values of the FP and FP HT products. FC will have somewhat higher conductivity values than listed below. Contact Shawcor for additional guidance. Laboratory testing of these values has not been conducted or confirmed.

Pipe		Wall		K <sub>eff</sub>	<b>Resist</b> eff	$K_{eff}$	<b>Resist</b> eff
Size	Product	Thic	kness	(18////////////////////////////////////		D4/la+f4+* E	
			in	(vv/m°K)	(1/K <sub>eff</sub> )	Btu/nr"ft"F	(1/ <b>K</b> eff)
2"							
	FP301/FP301HT	7.34	0.289	0.29	3.41	0.169	5.901
	FP601/FP601HT	8.99	0.354	0.25	4.05	0.143	7.005
	FP150	8.69	0.342	0.36	2.78	0.207	4.819
3"							
	FP301/FP301HT	9.45	0.372	0.30	3.35	0.173	5.795
	FP601/FP601HT	11.56	0.455	0.25	3.97	0.145	6.875
	FP150	10.92	0.430	0.36	2.80	0.206	4.844
4"							
	FP301/FP301HT	12.19	0.480	0.30	3.36	0.172	5.819
	FP601/FP601HT	14.96	0.589	0.25	4.02	0.144	6.965
5"	FP301HT	16.33	0.643	0.29	3.51	0.165	6.072
	FP601HT	20.42	0.804	0.24	4.16	0.139	7.208
6"	FP301HT	16.33	0.643	0.28	3.51	0.165	6.075
	FP601HT	20.42	0.804	0.24	4.21	0.137	7.280

#### Table 16: FP and FP HT Thermal Conductivity and Resistivity



## 6 Installation

Shawcor Spoolable products can be installed in a variety of ways including conventional trenching, plowing, liner pull, etc. This section provides a general overview of the installation processes. Detail and additional guidance provided in various bulletins and Installation Guide should be reviewed by the end user at the time of pipe ordering.

## 6.1 Field Services Support

The Shawcor Field Services Department provides support services for the installation of Shawcor Spoolable Products, including training courses, project coordination services, equipment rentals, onsite inspectors, and installation supervisors. Experienced managers and project coordinators are on call 24 hours per day, 7 days per week. Shawcor strives to ensure successful installation of its products on every project.

Fitting installation equipment is available from Shawcor for rental. Information on this equipment can be found in the Shawcor Installation Guide. In addition, Shawcor offers a variety of specialized installation accessories, including A-frames for carrying pipe reels, riser support trays, pull tools, custom cleaning pigs, moisture resistant Denso products, Polyken tape and sacrificial anode kits for cathodic protection. For more information on these accessories, see the Shawcor Installation Guide.

## 6.2 Liner Pull Considerations

For liner pull applications, multiple influencing factors can affect the pipelines performance and should be considered when planning the installation. Severe slugging, water hammer, high fluid velocities, impact forces, muskeg/swamp soil conditions and thermal expansion should all be considered.

• Emulsion pipelines that are prone to severe slugging can lead to impact forces at changes in direction (e.g., riser and pipeline bends) and misaligned transitions.

• High velocities (i.e., more than 1.5 m/s (5 ft/s)) can lead to significant fluid impact forces at changes in direction and water hammer during pump start/stops. Significant impact forces may lead to damaging the pipeline.

• For operating temperatures above 30°C, thermal expansion can create additional changes in direction or bends in the pipeline (snaking or lateral movement). Thermal expansion will be uncontrolled when there is inadequate restraint at pipeline transitions and can lead to damaging the pipeline.

• Muskeg/swamp conditions may not provide the same amount of restraint as in other soil conditions due to the low soil modulus of the backfill material. Preventing operating conditions that may lead to impact forces and impingement at transitions are more critical in muskeg conditions. Bell holes and risers with muskeg/swamp conditions typically require additional restraint to prevent floatation and movement of the pipeline.



Proper support and restraint is required to limit movement of the pipeline due to the above influencing factors. For liner pull applications that combine all of the influencing factors listed above,

- installed in muskeg/swamp conditions,
- operated at high velocities and
- operated at temperatures above 30°C.

It is strongly recommended to limit the liquid velocity to a maximum of 1.5 m/s (5 ft/s) and the installation must provide adequate restraint at bell holes and riser transitions. Additional information on restraint can be reviewed in the Liner Pull Bulletin and Shawcor Installation Guide.

#### 6.3 Support Spacing

For elevated support of Shawcor Spoolable Products, a continuous tray which is wide enough to allow for the expected thermal expansion and snaking is recommended. Shawcor Spoolable Products may also be supported using individual (non-continuous) pipe supports or hangers, as long as the expected thermal expansion can be accommodated. The pipe should be allowed to rest in a rounded cradle, with a length approximately equal to or greater than the nominal diameter of the pipe being supported. Supports should have rounded edges that will not cut into the pipe.

In order to prevent excessive sag between supports, Shawcor recommends spacing the supports no farther than the distances given in <u>Table 17</u>.

	Recommended maximum support spacing								
Pipe Size	Liquid	service	Gas service						
	(m)	(ft)	(m)	(ft)					
2"	1.1	3.5	1.2	4					
3"	1.2	4	1.5	5					
4"	1.5	5	1.7	5.5					
5"	1.5	5	1.8	6					
6"	2.4	8	2.9	9.5					

 Table 17: Recommended Pipe Support Spacing for Shawcor Spoolable Products

### 6.4 Buoyancy and Pipe Weights

Shawcor Spoolable Products will float in water or muskeg if not weighted or buried in a clay base. If conditions are suitable, the pipeline may be plowed into muskeg without weighting. The suitability of the conditions may be evaluated based on existing pipelines in the area and consultation with Shawcor Engineering.

If there is a concern that the pipe may float, the pipe can be weighted during installation. The weights should not have sharp edges that could point-load or cut the protective jacket of the product. Sand-filled saddlebag weights are recommended.



When weights are used t is preferable to place them while the pipe is in the ditch, if this is not possible, it is extremely important that the pipe is handled and lowered into the ditch by lifting on the weights directly. Lifting on the pipe may cause the pipe to kink or be damaged by the weights.

The following formulas can be used to calculate the pipe buoyancy per unit length (note that some unit conversions may be required). To keep the pipe submerged, the sand bag weight per unit length must be slightly more than the buoyancy force per unit length. Note that there will also be a buoyancy force on the sand bags themselves, which is compensated for in the formulas below.

Pipe cross – sectional area =  $OD^2 \times \frac{\pi}{4}$ 

Weight of fluid displaced per unit length of pipe = Pipe cross – sectional area  $\times$  Fluid density

Net buoyancy per unit length of pipe = Weight of fluid displaced per unit length – Pipe weight per unit length

Note that the pipe will sink if the net buoyancy is less than 0.

Submerged sand bag weight required per unit length of pipe = Net buoyancy per unit length of pipe  $\times 1.1$ 

Shawcor recommends multiplying by 1.1 to ensure the pipeline is adequately weighted to remain submerged.

Weight of fluid displaced by sand bag = Volume of fluid displaced by sandbag  $\times$  Fluid density

Submerged weight of sand bag = Weight of sand bag in air – Weight of fluid displaced by sand bag

Sand bag spacing =  $\frac{\text{Submerged weight of sand bag}}{\text{Submerged sand bag weight required per unit length of pipe}}$ 

Note: The sand bag spacing should be small enough to prevent the unrestrained pipe between sand bags from rising too far

The recommended dry sand bag weight can be found in the Installation Guide.



## 6.5 Riser Supports

Shawcor Spoolable Products may be terminated underground with either a flange or weld neck fitting. Alternatively, it can be brought to surface and supported by a metal support tray (riser support) mounted onto pilings. The purpose of the riser support is to prevent unnecessary shear or tensile loads on the pipe that could be caused by settling of backfill and earth movement. In particular, riser supports are recommended in locations where differential settlement from ground freezing or frost heaving is seen. For further information regarding risers see the Installation Guide.

The aboveground portion of the riser must be covered with insulation or white Polyken

tape. Shawcor Spoolable Products should be protected from mechanical damage similar to other piping materials above ground, depending on expected hazards in the area. Shawcor Spoolable Products is a ductile material and can withstand reasonable impact even at low temperatures.



## 6.6 Tracer Wire

Shawcor Spoolable Products are non-metallic. Therefore, tracer wire is required for buried installations to allow for future location of the pipe. The tracer wire should be installed simultaneously with the pipe and checked for electrical continuity immediately after installation. The wire termination points should be secured and clearly marked at readily accessible locations above ground.

## 6.7 Heat Tracing

Shawcor Spoolable Products may be heated by means of a heat tracer wire to prevent freezing. However, the heat tracer must be separated from the pipe by an insulation barrier to prevent concentrated hot spots or over-heating of the jacket.

Shawcor recommends a sandwich type insulated barrier with an insulation/heat-trace/insulation configuration, as shown in <u>Figure 8</u>. Because the pipe jacket material is a very poor thermal conductor, concentrated hot spots will appear directly below the heat tracing wire if an insulated barrier is not used.

The maximum operating temperature of FP and FC is 60°C (140°F). Therefore, it is very important to select the insulation thickness and the amount of heat tracing per unit length of pipe accordingly.

## **TECHNICAL MANUAL**

# **SHAWCOR**



Figure 8: Sandwich Type Insulated Barrier Configuration

## 6.8 Cathodic Protection

Shawcor Spoolable Products are corrosion resistant and do not require cathodic protection. Wherever regulations require cathodic protection for buried metallic fittings, Shawcor can make available ribbon anode kits tailored for Shawcor fittings. Further information is available in <u>Section 3.5</u>.

## 6.9 Field Pressure Testing of New Pipelines

Shawcor Spoolable Products are designed to accommodate the pressure-testing requirements specified by regulatory standards and codes. Due to the safety factors built into the pipeline design, there is no need to upgrade to a higher pressure-rated pipe if testing is required above the stated MAOP. Field pressure testing requirements and recommendations for Shawcor Spoolable Products depend on whether the pipeline is a new installation or a tie-in or repair job.

Shawcor recommends that new pipelines that have not been placed in operation be subjected to a hydrostatic hold test at  $1.25 \times MAOP$  as shown in <u>Table 19</u>. Refer to <u>Section 7.7</u> for hydrostatic testing of pipelines that have already been placed in operation.



Pressure Rating	2,068 kPa (300 psi)	5,171 kPa (750 psi)	10,342 kPa (1,500 psi)	15,513 kPa (2,250 psi)	
Flexpipe Grade	150	301	601	901	
Product Line	Hydrostatic test pressure and duration				
FP	2,586 kPa (375 psi) / 8 hrs.	6,467 kPa (938 psi) / 8 hrs.	12,928 kPa (1,875 psi) / 8 hrs.		
FP HT		6,467 kPa (938 psi) / 8 hrs.	12,928 kPa (1,875 psi) / 8 hrs.		
FC				19,395 kPa (2,813 psi) / 8 hrs.	

#### Table 18: New Pipeline Hydrostatic Test Pressures and Durations

Check with local regulations to ensure required hydrostatic test pressures are met. Shawcor requires monitoring the system carefully to ensure that the pipeline does not exceed 1.5 x MAOP at any point along the pipeline including low points at any time during the hydrostatic test.

Suggested procedures for pressure testing new pipelines are given in the Shawcor Installation Guide and in the Field Pressure Testing of New and Existing Pipelines bulletin.

Pressure testing with a compressible or gas medium is acceptable however for safety reasons, the below conditions are strongly recommended for pressure testing with a gas medium up to 2900 kPa (420 psi). Pressure testing with air or gas above 2900 kPa (420 psi) is at the discretion of the engineering resources of the pipeline operating company, but must also consider the conditions listed below:

- It is not prohibited by local regulations or standards;
- Appropriate precautions are taken to protect the pipeline from damage and minimize the risks associated with a pressure test failure;
- Follow the company procedures and safety measures for air testing.

Pressure test failures involving compressible media such as air result in the sudden uncontrolled release of a great deal of energy, with the potential for property damage, personal injury, or death. Until a pipe line has successfully passed a pressure test it should be considered as high risk to have equipment and personnel near the pressurized pipe line.

Under no circumstances will Shawcor be liable in any way for any loss, damage, or injury of any kind (whether direct, consequential, punitive, or otherwise) incurred as a result of the use of a gas medium for pressure testing.



To minimize the potential risk of injury or property damage in the unlikely event of a pressure test failure, a relatively incompressible liquid such as water is recommended as the pressurizing medium. Methanol is compatible with Shawcor Spoolable Products and is commonly used as an additive to prevent water from freezing at low temperatures.

Where new Shawcor pipelines have been hydrotested in sections or require repair after a successful hydrotest prior to operation, retesting of the entire pipeline system is not required after tying in provided:

- Pipe sections used for tie-ins, repairs, or replacement are pre-tested as per <u>Table</u> <u>19</u> where required by local regulations or standards.
- Joints of the tie-ins, repairs, or replacements are left exposed as the pipeline is brought into service and visually monitored for leaks for at least four hours, at the highest available operating pressure.

Note: Refer to <u>Section 7.7</u> for hydrostatic testing of pipelines that have already been placed in operation.

## 7 Operations

## 7.1 Startup

In the case of large temperature differences between the pipeline and the conveyed fluid, startup procedures for Shawcor Spoolable Products should include a gradual or stepped flow increase to allow for gradual temperature and pressure changes in the system. The system must be pressurized in a manner to prevent exceeding the MAOP, initiating water hammer, or creating uneven stress distributions due to rapidly changing pressures in the pipeline. It is recommended to pressurize the system at no more than 200 psi/minute. For depressurizations, line pressure should decrease at no more than 200 psi/minute in the case of a pump shut down or power loss.

There must be a mechanical protection device in place to prevent the line from being over pressured. A high-pressure shut-off should be installed and set to a pressure between the maximum typical operating pressure and the MAOP of the pipe. A pressure relief valve should be installed and set to relieve system pressure at no higher than the MAOP of the pipe. The set points of both devices should be inspected and recorded regularly (e.g., monthly). The devices should be function tested periodically (e.g., yearly).

Shawcor recommends limiting the fluid velocity of liquids and gases to a maximum of 3 m/s (10 ft/s) and 30 m/s (100 ft/s), respectively. High liquid velocities (e.g., more than 1.5 m/s (5 ft/s)) can lead to water hammer and pressure spikes if there are changes in direction, rapid starts/stops, or valve open/close events. High gas velocities can lead to erosion and excessive pressure drop. To reduce the risk of flow related damage, it is recommended to:

# **TECHNICAL MANUAL**

- Monitor the flow so liguid velocities are below 1.5 m/s (5 ft/s).
- Reduce the severity of severe slugging and on/off cycles in general. The installation of a Variable Frequency Drive (VFD) is recommended to reduce the number of on/off cycles to as low as possible.
- Support and restrain the pipeline to reduce lateral and vertical movement.
- Terminate the pipeline below surface at each end and use steel pipe risers to bring the pipe to the facility. This removes a direction change within the composite pipeline (horizontal to vertical) and reduces the likelihood of damage caused by high liquid velocity (e.g., more than 1.5 m/s (5 ft/s)).
- Provide additional restraint for surface lines by adding dirt piles or sandbags at the entry and exit areas of any pipeline change of direction, and at each fitting.

## 7.2 Pigging

🚺 SHAWCOR

Shawcor Spoolable Products are suitable for pigging. However, Shawcor Spoolable Product fittings have an ID that is smaller than the ID of the pipe. To ensure proper pigging, the use of a medium-density foam bullet pig, or a Shawcor disc (cleaning) pig is required. Any new pigging technology must be reviewed by Shawcor Engineering prior to being used with Shawcor Spoolable Products. Use of a pig not approved by Shawcor could result in the pig becoming stuck in a fitting. Shawcor supplies tags for installation on risers to warn operators of the temperature limitations of the pipe and pigging limitations.

Shawcor recommends medium-density foam bullet pigs for dewatering and Shawcor polyurethane disk pigs for removing wax build-up. The foam bullet pigs are also available with a polyurethane coated tip, which provides protection against damage during pigging operations. Ball pigs, brush pigs, or rigid pigs must not be used.

Shawcor polyurethane disk pigs are designed specifically for Shawcor Spoolable Products and offer more aggressive cleaning. However, a greater pressure differential is required to move them through fittings, and they require the presence of some liquid in the pipeline to provide lubrication. Polyurethane pigs are available from Shawcor in a variety of durometers to suit different pigging requirements (see <u>Table 19</u>).





Size	Durometer	Color		
<b>0</b> "	85	Yellow/Blue		
Ζ	75	Green		
	85	Yellow/Blue		
3"	75	Green		
	65	Purple		
۸ "	75	Green		
4	65	Purple		
5"	75	Green		
5	65	Purple		
6"	75	Green		

#### Table 19: Custom Polyurethane Disk Pigs

Note: Other pig styles having different durometers and lengths are also available. Check with your Shawcor account manager.

Shawcor polyurethane pigs cannot be used for threaded fittings and are not recommended for any T fittings or welded thin-wall elbows. They may be used with schedule 40 or 80 welded elbows ( $45^{\circ}$  or  $90^{\circ}$ ). If a pigging program is required on a Shawcor line joining another line, Shawcor recommends a y-lateral joint (see <u>Section</u> <u>3.1</u>), oriented to allow the pig to enter the joint from one of the two arms and exit from the y-lateral. Bar-stops and long pigs should be used for custom flow joints that involve pigging. Pig launchers must be sized to accommodate the Shawcor pig dimensions as indicated in <u>Table 20</u>.

Pipe Size (nominal)	Shawcor Polyurethane Pig, Composite Pipe with Rear Cup (CPC) mm (in)		Shawcor Polyurethane Pig, Composite Pipe (CP) mm (in)		Required pressure differential* kPa (psi)
(in)	Diameter	Length	Diameter	Length	Pressure
2"	N/A	N/A	57.15 (2.25)	95.25 (3.75)	138 (20)
3"	81.28 (3.2)	184.15 (7.25)	81.25 (3.2)	133.35 (5.25)	207 (30)
4"	104.14 (4.10)	228.60 (9.00)	104.14 (4.10)	165.10 (6.50)	276 (40)
5"	132.08 (5.20)	320.55 (12.62)	132.08 (5.20)	212.60 (8.37)	345 (50)
6"	154.94 (6.10)	327.66 (12.90)	154.94 (6.10)	218.44 (8.60)	414 (60)

 Table 20: Shawcor Pig Dimensions for Shawcor Spoolable Products

Note: Required pressure differential is approximate and assumes the line is lubricated and pigged using a lower durometer pig. Higher durometers and wax build up may require higher pressure differentials.

**SHAWCOR** 

## 7.3 Paraffin/Wax Removal

Shawcor Spoolable Products can be hot oiled. For lines that operate above 700 kPa (100 psi), a minimum 700 kPa (100 psi) residual pressure must be maintained in the line during all stages of hot oiling. The bore pressure will prevent liner collapse due to pressure in the pipe annulus in gas or emulsion applications. If the line pressure will be dropped lower than 700 kPa (100 psi) use the depressurization guidelines noted below in <u>Section 7.4.</u>

For lines that operate below 700 kPa (100 psi) and 38°C (100°F), the line can be depressurized as needed during hot oiling. For applications with temperature above 38°C (100°F) follow the depressurization guidance noted below in <u>Section 7.4</u>

At the start of a hot oil treatment, use a maximum flow of 1.5 GPM for the first 10 minutes. After 10 minutes of operation hot oil flow can be increased as required.

Once hot oiling has been completed, pig the line with a Shawcor urethane disk pig.

In addition, Shawcor recommends limiting hot oiling temperatures to less than 60°C (140°F) for FP Products, and 82°C (180°F) for FP HT Products. Contact Shawcor Engineering to discuss the details of your hot oiling program.

For internal water jet cleaning of wax and deposits, Contact Shawcor Engineering for additional guidance

#### 7.4 Shutdown and Depressurization Procedures

Shawcor Spoolable Products containing high pressure gas or  $CO_2$  (including multiphase or liquid content, water, oil,  $CO_2$  dense phase, etc) have the unique characteristic of having a high rate of gas permeation that is typical of a gas service.

Accordingly, in order to reduce the potential for liner collapse in these services at operating temperatures above 38 °C (100 °F), it is required to slowly depressurize the pipeline (i.e. no more than 500 psi per hour) to 100 psi and hold for a period of time as indicated below. This is to allow enough time for some of the gas in the annular space to vent out to the atmosphere, and to allow the pipeline to cool. For low pressure applications or where this hold period may be too operationally restrictive, contact Shawcor for case-by-case guidance.

- 100 to 120 °F, hold at 100 psi for 1 hour
- 121 to 140 °F, hold at 100 psi for 2 hours
- 141 to 160 °F, hold at 100 psi for 8 hours
- 161 to 180 °F, hold at 100 psi for 24 hours



## 7.5 Static Electricity

Standard operating and maintenance procedures for handling non-conductive pipe and dissipation of static electricity apply when working with Shawcor Spoolable Products. Static charge on a plastic pipe can be generated by friction during the physical handling of the pipe in storage, shipping, installation, and repairing operations. Also, flowing gas in an operational plastic pipe containing particulate matter in the form of scale, rust, or dirt, can generate static electricity. Other causes of static charge include gas flow disrupters such as pipe elbows, valves, reducers, and leaks.

Discharge of static electricity in the presence of a flammable gas-air mixture may cause an explosion or fire and result in property damage and/or personal injury. When conditions exist such that a flammable gas-air mixture may be encountered and static charges may be present, all company (pipeline operator, utility, contractor, etc.) procedures for static electricity safety and control should be followed, including procedures for discharging static electricity and personal protection. Information on handling static electricity in plastic pipelines is available in US Occupational Safety and Health Administration "Hazard Information Bulletin Static Electricity Buildup in Plastic Pipe"<sup>15</sup>.

## 7.6 Secondary Excavations

Excavation near installed pipe is the most common risk to the integrity of Shawcor Spoolable Products due to the potential for external damage. The preferred method for excavating buried pipe is hydro-excavation (hydrovac).

The following practices are recommended to minimize the risk of external damage to the pipe:

- Identify the location of the Shawcor Spoolable Product using the tracer wire installed with the pipe.
- Where possible, depressurize the lines that will be excavated.
- Follow hydro-excavation procedures that comply with industry best practices for excavation of thermoplastic piping, including:
  - Use of protective tips (e.g., rubber, neoprene, etc.) on spray nozzles and suction hoses.
  - Use of multi-jet nozzles with diverging spray patterns; not oscillating, rotating, or converging pattern nozzles.
  - o Continuous movement of the spray wand while excavating.
  - A distance of at least 12" between the spray nozzle and the pipe.
  - Spray pressures as low as practical and not above 1500 psi.
  - Water temperatures below 40°C (104°F).
- Inspect the exposed pipe thoroughly after the excavation is complete.
- Support the weight of exposed pipe at intervals of not greater than 3m (10 feet).
- Take appropriate precautions to avoid impact or sustained pressure from sharp or heavy objects.
- Exercise care during any mechanical excavation near Shawcor Spoolable Products.

<sup>&</sup>lt;sup>15</sup> <u>https://www.osha.gov/dts/hib/hib\_data/hib19880930.html</u>



- Inspect all exposed Shawcor Spoolable Products for external damage prior to backfilling.
- Replace any sections of Shawcor Spoolable Products that are damaged during excavation.
- Use proper backfill procedures.

## 7.7 Field Pressure Testing of Existing Pipelines

When a cut out is replaced, a failure is repaired, or a tie-in is connected to a previously operating pipeline, the integrity of the new pipe section and the connections used to join or repair the pipeline is ensured by both of the following:

• The pipe section used for repairs, replacement or tie-ins is pre-tested as per Shawcor Field Pressure Testing of New and Existing Pipelines Bulletin.

• The repaired, replaced, or connected section is left exposed as the pipeline is brought into service and visually monitored for leaks for at least four hours, at the highest available operating pressure.

Frequent hydrotesting of a pipeline after it has been commissioned into operation is not recommended. Hydro testing pipelines to a pressure greater than MAOP is generally only appropriate prior to a new pipeline being commissioned into operation, for infrequent integrity testing, or infrequent testing after repairs. Hydrotesting pipelines up to MAOP is typical after pipeline tie-ins, for frequent integrity testing, or when reactivating a shut-in pipeline. Contact Shawcor Engineering for clarification as required.

## 8 Reliability

## 8.1 History

As of 2022, over 46,000 kilometers (28,500 miles) of Shawcor Spoolable Products and 230,000 fittings have been installed throughout Western Canada, the United States, and internationally. Shawcor Spoolable Products are currently in service carrying a wide range of liquid and gas media, at various operational temperatures and pressures up to and including the published limits. A number of different installation methods have been employed over a wide range of climate, soil, and terrain conditions.

Shawcor Spoolable Products continuously meet the extensive challenges of operation in demanding applications and have earned an excellent record as high quality and dependable products in the field. This has been demonstrated through numerous evaluations of operating pipelines in a variety of applications.



### 8.2 Reliability Management

The reliability of Shawcor Spoolable Products is dependent on the proper engineering, installation, and operation of the pipeline system. The end user is ultimately responsible for final design, material selection, installation, and operation of the pipeline system. Shawcor provides guidance and recommendations to the end user for their evaluation regarding the design, material selection, installation, and operation of Shawcor Spoolable Products.

### 8.3 Integrity Verification

Many operators elect to limit their integrity verification activities to an initial pressure test after installation. Some operating companies may choose to exceed normal industry practice by incorporating one or more of the activities listed below into their integrity verification activities, in line with their risk management strategies. It would typically be appropriate for an operating company to make use of the options below.

Integrity verification options for Shawcor Spoolable Products include:

- Visual inspection of jacket. Where pipe is exposed above surface the jacket can be inspected for discoloration that may indicate UV degradation. Exposed pipe can also be inspected for damage and jacket breach.
- Visual inspection for corrosion of metallic fittings. The external condition of a fitting
  can be inspected by removing the petrolatum and pipeline tape. The condition of the
  interior coating of a flanged fitting can be inspected visually after unbolting the flanged
  connection. It is recommended that new gaskets and protective wrappings be used
  during reassembly. Visual inspection of the fittings should include installation quality
  such as open vent holes, proper crimping, etc.
- Gas detection testing. Fittings can be checked for leaks during operation using gas detection equipment.
- Integrity Pressure Testing. To verify the integrity of the pipe after a period of operation a pressure test may be conducted.
- Cut-out testing. A method for confirming pipe integrity is to remove a minimum of 3 samples of pipe, each approximately 8 feet in length and have these tested. Shawcor offers integrity assessment testing and analysis of such samples.

The extent and frequency of the integrity testing program is to be determined by the end user.



#### Head Office and Manufacturing Facility

3501 - 54<sup>th</sup> Avenue S.E. Calgary, Alberta Canada T2C 0A9 Tel: 403-503-0548 Fax: 403-503-0547

## **Midland Sales Office**

10 Desta Drive, Suite 175W Midland, Texas United States 79705 Tel: 432-685-0865

## **Houston Sales Office**

5875N Sam Houston Pkwy W, Suite 200 Houston, Texas United States 77086 Tel: 281-670-2105 Fax: 281-670-2164

## **Canada Solution Centers**

- Estevan, SK Tel: 306-861-0509
- Grand Prairie, AB Tel: 780-402-4765

#### **U.S. Solution Centers**

- Grand Junction, CO Tel: 970-243-0067
- Midland, TX Tel: 432-685-0865
- George West, TX Tel: 432-685-0865
- Dickinson, ND Tel: 970-243-0067

### **U.S. Deployment Centers**

- Myton, UT Tel: 970-243-0067
- Bakersfield, CA Tel: 970-243-0067

### **Australia Solution Center**

Mobile: +61 439390081

## Asia Pacific

Level 42, Suntec Tower Three, 8 Temasek Boulevard, Singapore 038988 Mobile: +61 439390081



9 Appendix

**Product Data Sheets** 



## FLEXPIPE<sup>™</sup> & FLEXPIPE HT

## Linepipe Designed to Withstand High Pressures and Corrosion

#### **QUICK INSTALLATION & TOTAL LIFE CYCLE COSTS**



- Approximately a 50% reduction in installation crew size and up to 35% installation cost savings compared to a steel pipeline
- Impact-resistant design eliminates the need for sand padding
- 20-year UV life protects pipe while in service or storage

#### EXPANDED OPERATING ENVELOPE



- Lower operating costs due to corrosion-resistant design
- Maximum operating temperature of 60°C (140°F) or 82°C (180°F)
- FlexPipe products are suitable for sour service applications
  Compatible with up to 50% aromatic and cycloalkane
- hydrocarbons
- HDPE liner provides excellent chemical resistance

#### PRODUCT RELIABILITY & SAFETY



Built to exceed the industry requirements of API, ASTM and CSA standards

Connections are made with robust leak-free fittings, available in two corrosion-resistant material options

FlexPipe products are abrasion-resistant, low friction and have higher flow rates compared to steel alternatives

#### THE SHAWCOR DIFFERENCE



- In-house engineers dedicated to ensuring FlexPipe is suitable for your application to maximize service life
- Project planning, technical and field services support to ensure on-time delivery and world-class installation
- Contractor installation training allows customers better control over project timing, costs and completion

60° - 82°C (140°F - 180°F) MAXIMUM CONTINUOUS OPERATING TEMPERATURE

1,500 psi (ANSI 600) MAXIMUM OPERATING PRESSURE

#### **APPLICATIONS:**

Oil, gas, water,  $H_2S$ , and  $CO_2$  (up to 100%)

**PIPE SIZES:** 2, 3, 4 and 5"

LENGTH PER REEL: 325–1,100 meters (1,066–3,610 feet)

#### **INSTALLATION:**

Trenching, plowing, chain ditching, surface lines, horizontal directional drilling (HDD), liner pulls (remediation)

SHAWCOR

Rev#: 4.2

Constructed from a winning combination of high-density polyethylene, helically wound epoxy-free dry fiberglass and a protective outer jacket, FlexPipe products are safe to install thanks to smaller crew sizes and less heavy equipment requirements.



		FP301 / FP301 HT			FP601 / FP601 HT				
		2"	3"	4"	5"	2"	3"	4"	5"
Pressure	psi		75	50			1,5	;00	
	kPa	5,171			10,342				
Temperature	°C		60 c	or 82		60 or 82			
importation	°F	140 or 180				140 or 180			
Outside Diameter	mm	69	97	124	157	73	101	130	165
- storage promotor	in	2.7	3.8	4.9	6.2	2.9	4.0	5.1	6.5
Inside Diameter	mm	54	77	99	125	54	77	99	125
inside Biumeter	in	2.1	3.0	3.9	4.9	2.1	3.0	3.9	4.9
Pine Weight	kg/m	1.7	3.0	4.9	8.3	2.4	4.3	6.9	11.8
i ipe weight	lb/ft	1.1	2.0	3.3	5.6	1.6	2.9	4.6	7.9
Operational MRD	m	1.2	1.8	2.1	3	1.2	1.8	2.1	3
	ft	4	6	7	10	4	6	7	10
l anath/raal*	т	1,100	760	735	365	1,100	700	570	325
Length/Teer	ft	3,610	2,495	2,410	1,198	3,610	2,300	1,870	1,066
Peel Diamotor	m	3.7				3.7			
Reel Diameter	ft	12				12			
Pool Width	m	1.2	1.2	2.4	2.4	1.2	1.2	2.4	2.4
	ft	4	4	8	8	4	4	8	8
Pool Woight Full	kg	2,520	2,945	4,735	4,170	3,355	3,710	5,085	4,985
Reel weight - Full	lbs	5,550	6,490	10,435	9,190	7,405	8,180	11,200	10,980
Pool Weight Empty	kg	680	680	1,150	1,150	680	680	1,150	1,150
Reel Weight - Empty	lbs	1,500	1,500	2,530	2,530	1,500	1,500	2,530	2,530
	mm	82	111	140	178	85	116	144	186
	in	3.2	4.4	5.5	7.0	3.4	4.6	5.7	7.3
Eitting ID**	mm	45	64	86	108	45	64	86	108
	in	1.8	2.5	3.4	4.2	1.8	2.5	3.4	4.2

\*Lengths and reel weights are approximate as they may vary depending on the manufacturing run.

\*\*Fitting dimensions do not include O.D. of flange provided for flanged end fittings. Fitting O.D. and I.D apply to flanged end, weld-neck and pipe-to-pipe coupling fittings.

Product data is subject to change without notice. Shawcor's products are patented by US Patents 6,889,716, 6,902,205, 7,946,629 B2 and 8,042,252 B2 by Canada Patents 2,513,506, 2,513,468 and 2,562,823 and by European Patent 1592908. Additional patents are pending. Shawcor products comply with API RP 15S, API 17J, CSA Z662-15, ASTM F2686 and ASTM D2992. Shawcor Ltd., 2021

Shawcor Ltd. is a global energy services company specializing in products and services for the pipeline and pipe services segment of the oil and gas industry and related products for petrochemical and industrial markets. The Company operates through a network of fixed and mobile manufacturing and service facilities located around the world and is valued for its integrity, technology, and proven capability to execute the most complex projects in our industry.





# **FLEXPIPE**<sup>™</sup>

# 6" FP301 HT

# Large Diameter Spoolable Product

#### QUICK INSTALLATION & LOGISTICS BENEFITS



- 20% capital cost savings compared to steel
- 30% faster installation time compared to steel
- Up to 1,215 feet/reel (370 meters/reel)
- Two standard Shawcor 14' diameter reels/ truck

#### EXPANDED OPERATING ENVELOPE



- Built to exceed the industry requirements of CSA, API and ASTM standards
- Suitable for high H<sub>2</sub>S and CO<sub>2</sub> systems
- Lower operating costs due to corrosion resistant design

#### **PRODUCT RELIABILITY & SAFETY**



- Suitable for many installation methods including: trenching, plowing, chain ditching, surface lines, horizontal directional drilling (HDD), liner pulls (remediation)
- Up to 50% aromatic and cycloalkane
   hydrocarbons by volume

180°F (82°C)

MAXIMUM CONTINUOUS OPERATING TEMPERATURE

750 psi (ANSI 300) MAXIMUM OPERATING PRESSURE

#### **APPLICATIONS:**

Oil, gas, water  $H_2S$  (up to 100,000ppm)  $CO_2$  (up to 100%)

#### LENGTH PER REEL:

370 meters / 1,215 feet

#### **INSTALLATION:**

Trenching, plowing, chain ditching, surface lines, horizontal directional drilling (HDD), liner pulls (remediation)



#### Launching early 2023



## **SPECIFICATIONS**

		6" FP301 HT
Prossure	psi	750
Pressure	kpa	5,171
Tomporaturo	°C	82
remperature	°F	180
Quitaida Diamatar	mm	179
Outside Diameter	in	7.1
Incido Diamator	mm	142
Inside Diameter	in	5.6
Dina Waight	kg/m	10.8
Pipe weight	lb/ft	7
Operational MPD	т	3.4
	ft	11
Longth/rool*	т	381
Length/reel	ft	1,250
Pool Diamator	т	4.3
Reel Didilleter	ft	14
Pool Width	т	2.4
	ft	8
Pool Woight Full	kg	5,590
Reel Weight – Full	lbs	12,323
Pool Woight Empty	kg	1,497
Reel Weight – Empty	lbs	3,300
	mm	203
	in	8
Eitting ID**	mm	124
	in	4.9







\*Lengths and reel weights are approximate as they may vary depending on the manufacturing run. \*\*Fitting dimensions do not include O.D. of flange provided for flanged end fittings. Fitting O.D. and I.D apply to flanged end, weld-neck and pipe-to-pipe coupling fittings.

Specifications subject to change without notice. Shawcor's products are patented by US Patents 6,889,716, 6,902,205, 7,946,629 B2 and 8,042,252 B2 by Canada Patents 2,513,506, 2,513,468 and 2,562,823 and by European Patent 1592908. Additional patents are pending. Shawcor products comply with API 15S, API 17J, CSA Z662-15, ASTM F2686 and ASTM D2992. Shawcor Ltd., 2021





# **FLEXPIPE**<sup>™</sup>

# 6" FP601 HT

# Large Diameter Spoolable Product

#### QUICK INSTALLATION & LOGISTICS BENEFITS



- 20% capital cost savings compared to steel
- 30% faster installation time compared to steel
- Up to 1,115 feet/reel (340 meters/reel)
- Two standard Shawcor 14' diameter reels/truck

#### EXPANDED OPERATING ENVELOPE



- Built to exceed the industry requirements of CSA, API and ASTM standards
- Suitable for high H<sub>2</sub>S and CO<sub>2</sub> systems
- Lower operating costs due to corrosion resistant design

#### **PRODUCT RELIABILITY & SAFETY**



- Suitable for many installation methods including: trenching, plowing, chain ditching, surface lines, horizontal directional drilling (HDD), liner pulls (remediation)
- Up to 50% aromatic and cycloalkane hydrocarbons by volume

180°F (82°C) MAXIMUM CONTINUOUS OPERATING TEMPERATURE

1,500 psi (ANSI 600) MAXIMUM OPERATING PRESSURE

#### **APPLICATIONS:**

Oil, gas, water H<sub>2</sub>S (up to 100,000ppm) CO<sub>2</sub> (up to 100%)

**LENGTH PER REEL:** 340 meters

(1,115 feet)

#### **INSTALLATION:**

Trenching, plowing, chain ditching, surface lines, horizontal directional drilling (HDD), liner pulls (remediation)



## SPECIFICATIONS

		6" FP601 HT
Drosquito	psi	1,500
Pressure	kpa	10,342
Townsystems	°C	82
Temperature	°F	180
Outside Dismeter	mm	191
Outside Diameter	in	7.5
Incido Diamator	mm	142
Inside Diameter	in	5.6
Dina Waight	kg/m	15.6
Fipe weight	lb/ft	10.5
Operational MPD	т	3.4
	ft	11
Longth/rool*	т	340
Length/reel	ft	1,115
Pool Diamotor	т	4.3
Reel Diameter	ft	14
Pool Width	т	2.4
	ft	8
Pool Weight - Full	kg	6,920
Keel Weight – Full	lbs	15,255
Pool Weight - Empty	kg	1,500
Reel Weight – Empty	lbs	3,300
Fitting OD**	mm	213
	in	8.4
Fitting ID**	mm	123
	in	4.9



 $^{\ast}\mbox{Lengths}$  and reel weights are approximate as they may vary depending on the manufacturing run.

\*\*Fitting dimensions do not include O.D. of flange provided for flanged end fittings. Fitting O.D. and I.D apply to flanged end, weld-neck and pipe-to-pipe coupling fittings.

Specifications subject to change without notice. Shawcor's products are patented by US Patents 6,889,716, 6,902,205, 7,946,629 B2 and 8,042,252 B2 by Canada Patents 2,513,506, 2,513,468 and 2,562,823 and by European Patent 1592908. Additional patents are pending. Shawcor products comply with API 15S, API 17J, CSA Z662-15, ASTM F2686 and ASTM D2992. ©Shawcor Ltd., 2021





#### FLEXCORD™

## Spoolable Composite Linepipe able to Overcome Cyclic Challenges

#### QUICK INSTALLATION & TOTAL LIFE CYCLE COSTS



Reinforced with high strength galvanized steel cords to handle pressure cycles and pulsations during cyclic applications Approximately a 50% reduction in installation crew size and up to 35% installation cost savings compared to a steel pipeline

#### EXPANDED OPERATING ENVELOPE



- Rigorous internal testing confirms no blistering or collapse after repeated cycles of rapid decompression at 1,000 psi/minute
- Steel cord design allows for enhanced venting of gasses that permeate through the liner allowing for rapid decompression

#### ANTI-BUOYANT OPTION



- Used in shallow water applications up to a depth of 30 meters (100 ft)
- Eliminate the need for using additional weights for anchoring
- Use with specialized couplings and terminations for no welding, fast and watertight installations

#### **PRODUCT RELIABILITY & SAFETY**



- Built to exceed the industry requirements of CSA, API and ASTM standards
- Designed with an industry accepted safety factor which does not require de-rating

#### THE SHAWCOR DIFFERENCE



- In-house engineers dedicated to ensuring our product is suitable for your application to maximize service life Project planning, technical and field services support
- to ensure on-time delivery and execution
- Contractor installation training allows customers better control over project timing, costs and completion

**COMPOSITE SYSTEMS** 

**60°C** [140°F] MAXIMUM CONTINUOUS OPERATING TEMPERATURE

2,250 psi (ANSI 900) MAXIMUM OPERATING PRESSURE

#### **APPLICATIONS:**

Oil, gas, water, EOR,  $H_2S$  (up to 3,000 ppm), and CO<sub>2</sub> (up to 100%)

ID SIZES: 3 and 4 inch

LENGTH PER REEL:

525-615 meters (1,722-2,018 feet)

#### INSTALLATION:

Trenching, plowing, chain ditching, surface lines, horizontal directional drilling (HDD), liner pulls (remediation)



Engineered for high frequency 225 psi peakto-peak pressure pulsations, combined with 10 full pressure on-off cycles of 0–1,500 psi per day with a 10x safety factor eliminating the need for de-rating in most cyclic applications.

		FC901 AB	FC901		
MAXIMUM OPERATING PRESSURE @ 60°C		15,510 KPA /2,250 PSI	15,510 KPA / 2,250 PSI		
Nominal Size		2"	3"	4"	
Outside Diameter	mm	75.1	100	129	
	inches	2.955	3.95	5.07	
Inside Diameter	mm	53.8	77	99	
	inches	2.12	3.02	3.90	
Weight	kg/m	4.82	5.1	8.4	
	Ibs/ft	3.24	3.4	5.6	
Min. Bend Radius (Operational)	m	1.2	1.8	2.1	
	ft	4	6	7	
Length / Reel	m	750	615	525	
	ft	2,460	2,018	1,722	
Reel Diameter	m	3.7	3.7	3.7	
	ft	12	12	12	
Reel Width	m	2.4	1.2	2.4	
	ft	8	4	8	
Reel Weight – Full	kg	4,750	3,820	5,560	
	Ibs	10,470	8,415	12,260	
Reel Weight – Empty	kg	1,150	680	1,150	
	Ibs	2,530	1,500	2,530	
Fitting Outside Diameter*	mm	87.1	115.6	144.3	
	inches	3.43	4.55	5.68	
Fitting Inside Diameter*	mm	44.5	63.5	85.9	
	inches	1.75	2.50	3.38	
Length / Coil*	m ft	750 2,460	-	-	
Coil Weight**	kg Ibs	3,615 7,970	-	-	

Lengths and weights are approximate as they may vary depending on the manufacturing run. "Fitting dimensions do not include O.D. of flange provided for flanged end fittings."

Fitting O.D. and I.D. apply to flanged end, weld-neck and pipe-to-pipe coupling fittings.

Product data is subject to change without notice. Shawcor's products are patented by US Patents 6,889,716, 6,902,205, 7,946,629 B2 and 8,042,252 B2 by Canada Patents 2,513,506, 2,513,468 and 2,562,823 and by European Patent 1592908. Additional patents are pending. Shawcor products comply with API RP 15S, API 17J, CSA Z662-15, ASTM F2686 and ASTM D2992. ©Shawcor Ltd., 2016







Shawcor Ltd. is a global energy services company specializing in products and services for the pipeline and pipe services segment of the oil and gas industry and related products for petrochemical and industrial markets. The Company operates through a network of fixed and mobile manufacturing and service facilities located around the world and is valued for its integrity, technology, and proven capability to execute the most complex projects in our industry.

