

PRODUCT GUIDE ASIA

Installation Systems for Screed | Floor Coverings | Wood Flooring

As of: January 2016



UZIN. THE FLOOR BELONGS TO YOU.



"UZIN actively supports me and guides me on the road to success."

At UZIN, our customers always come first. More than 900 employees around the world give their very best – their commitment, their knowledge, their abilities and all their experience – to achieve success on your behalf. Our cover picture symbolises that focus. One of our customers, Mr. John Chalk, owner of JC Contracts in the UK, is in the centre with a banner. Behind him stand a row of employees from our production, customer service, research & development, technology, marketing and product management departments (from left to right). All adhere to a particular philosophy: "We actively support our customers and guide them on the road to success." That means:

- We are close to our customers and follow unconventional approaches to be close.
- We support our customers across the board - because we are only successful when you are.
- We constantly adapt our products to the most recent demands of the market - and to the needs of our customers.
- We offer our customers the best solution for each project - even in the face of exceptional challenges.
- We are there when we are needed - and deliver before the product is needed. Each of our employees thinks and works by these principles, because UZIN is the partner by your side. The partner in your success.

CONTENTS

Subfloor Construction

24

Special Screeds

25 – 27

Subfloor Preparation

28

Primers

29 – 30

Reaction Resin Primer

31

Repair Smoothing Compound

32 – 33

Substrate Repairs

34

Self-Levelling Compounds

35 – 37

Cementitious Top Coatings

38

Floor Covering Adhesives

39

Resilient Flooring Adhesives

40 – 42

Linoleum Adhesive

43

Easy Release Systems

44

Adhesive for Profiles, Stairs and Vertical Surfaces

45

Adhesives for Heavy Wear Areas

46

Adhesives for Electrostatic Control Installation

47

switchTec®-Adhesive Technology

48

Adhesives for Floor Coverings

49 – 56

Tools for the Application of Skirtings

57

Adhesives for Stair Coverings

57

Adhesives for Skirtings and Coving

58

Wood Flooring Installation

59

1-Component STP-Adhesive

60

2-Component PUR-Adhesive

61

1-Component Reaction Resin Primer

62

2-Component Epoxy Primer-Sealer / Special Adhesive

63

Accessories | Tools

64

Accessories | Tools

65 – 68

Service

69

Contact Adresses Worldwide

70 – 71

Contact UZIN Asia

72



MILESTONES IN THE COMPANY'S DEVELOPMENT.

The brand UZIN is part of the Uzin Utz AG, a publicly listed company, active around the world. Over the last ten years, our turnover increased from 84 to 230,4 million Euros; the driving force is provided by our over 950 employees world-wide.

- 1911** Foundation of the company by Georg Utz
- 1948** Willi Utz takes over the management of the company; Registration of the UZIN brand at the patent office in Munich
- 1980** Dr. H. Werner Utz assumes the management of the company
- 1981** Development of a complete range of environmentally friendly first-generation adhesives
- 1997** Change of the corporate form to an AG (public company) and listing on the stock exchange
- 2001** Official opening of the European Logistics Centre; take-over of wood flooring lacquers specialist Pallmann
- 2002** Take-over of Wolff Spezialmaschinen GmbH, Vaihingen/Enz and the WOLFF brand for machines and tools
- 2004** Take-over of Unipro bv, Haaksbergen (Netherlands) and its affiliate Unipro nv, Gent (Belgium) with the Arturo brand for industrial and synthetic resin floor coverings
- 2005** Take-over of Siga Floor AG, Ruswil (Switzerland) and integration of the innovative switchTec® adhesive technology
- 2007** Introduction of the codex brand for ceramic tiles and natural stone; take-over of the wood flooring sanding machine manufacturer Herman Frank
- 2008** Take-over of RZ Chemie GmbH as well as Genial Produkte, suppliers of cleaning and care systems
- 2009** Acquisition of DS Derendinger AG in Thörishaus (Switzerland), Distributor for Machines and Tools
- 2010** Uzin is the first brand in the industry to get the EPD (Environmental Product Declarations) certification for a full product system.
- 2011** Uzin Utz AG's 100 year anniversary
- 2012** Acquisition of the flooring division of Collano Adhesives AG, Switzerland.
- 2013** Introduction of the sustainable product system Terra-Line and the UZIN ECO ID
- 2014** Opening of the new production facility of Wolff GmbH & Co. KG in Ilsfeld, Germany; Opening of the new factory of Unipro, Haaksbergen, Netherlands
- 2015** Grand Opening of Uzin Utz Manufacturing North America, Inc., Dover, Delaware, USA

UZIN. THE FLOOR BELONGS TO YOU.

UZIN, the market leader in installation systems for floors and wood flooring in Germany, is committed to providing flooring installers with the best support for their day-to-day business – and guiding them on the road to success. This is achieved by our close relationship with customers which we view as partners. With high-quality products and service as well as our passion for optimisation, further development and innovation.

Our solvent-free products have received multiple awards for their low-emission, sustainable properties and meet stringent workplace and environmental protection requirements – a good example of our innovative strength. Such innovation sees UZIN making a decisive step into the future and preparing the floor for your success. For our joint success.

UZIN is similarly demonstrating the importance of collaboration with flooring installers via its new brand image. Under the motto “UZIN. The floor belongs to you.”, genuine flooring installers present the successes they have had with UZIN and the challenges they have overcome with UZIN products.

The following is an overview of the individual products. On that note, I hope you enjoy reading and wish you success with your UZIN partner!



Dr. H. Werner Utz








UZIN – GLOBAL PARTNER FOR FLOORING INSTALLERS.

Every day, craftsmen all over the world are confronted with flooring challenges. Each project is different and requires expertise, experience and individual solutions. UZIN is the ideal partner for flooring installers – worldwide. The following pages show the most important areas where different system solutions are required



HEALTH CARE

Healthcare areas represent one of the most challenging and complex environments for flooring solutions. The floor has to meet all the required needs like resistance to heavy traffic, water and chemicals as well as compliance with static control and hygiene standards to improve the healthcare outcome and promote healing.



Example Construction



SHOP | RETAIL

„Time is money!“ This phrase exactly describes what is the key point in the shop/retail segment. The requirement is in most cases not to close the shop to avoid any loss in turnover which means that fast and uncomplicated products are needed.



Example Construction



AIRPORT

Airports are one of the most frequented areas generally since the air travel market is growing very fast and millions of people are flying to destinations all over the world. Thereby, the floor of an airport has to withstand large numbers of passengers, wheeled luggages and transportation vehicles every day, 365 days a year.

There is no doubt that the strongest products are needed to prepare the subfloor ideally for these conditions.



Rubber

Adhesive UZIN KR 430

Self Levelling Compound UZIN NC 169

Primer UZIN PE 460 (2. Coat) + Persand

Primer UZIN PE 460 (1. Coat)


Concrete

Example Construction



PUBLIC BUILDINGS

A public building's appearance says something about its owner and occupants. But what part of the building is used the most and affects the appearance? The floor! That's why a perfect subfloor preparation with reliable products is so important and essential for the long term success of a public building.



Example Construction




INDUSTRIAL

Nowadays, to have a floor with a cementious design becomes more and more popular in industrial areas like production halls, warehouses or show rooms. Although heavy machines and big forklifters have to move there every day, no problems appear due to the excellent performance of the special products for this solution.



- Wax, Laquer
- Self Levelling Compound UZIN NC 1700
- Primer UZIN PE 460 (2. Coat) + Perlsand
- Primer UZIN PE 460 (1. Coat)
- Concrete




Example Construction

A photograph of a modern interior space. On the left, a large window with a black grid frame looks out onto a street with trees and buildings. To the right, a corner is formed by two columns made of stacked, light-colored rectangular stone blocks, separated by dark horizontal bands. The floor is made of large, rectangular tiles in various shades of brown and tan. The lighting is bright, coming from the window.

RESIDENTIAL


Especially in residential areas like your own home you expect nothing but the best materials and care about a good and healthy environment for you and your family.




Example Construction

UZIN SYSTEM RECOMMENDATION

With an extensive range of products, it is often difficult to get an overview. UZIN has therefore put together a selection of products which cover your daily work requirements for 90% of all applications. This makes searching for a product easier and allows you to focus on few products. With a 100 years heritage we continue to provide a first-class range of reliable, ecological and innovative products.



The recommendations described here should only be used as a guide. Detailed product data sheets are available which should be used as reference when using the products.



OUR RESPONSIBILITY TO THE ENVIRONMENT AND TO YOUR HEALTH

Our commitment to the environment and to your health is not an afterthought. Together with our strongest objective quality, it is a key objective in our development process. As you can see on the following page, we submit our products to some of the most comprehensive quality and rigorous health and environmental testing on the planet. Our labelled products not only meet but exceed these demanding requirements. It's just one more way that you can count on our promise.





Conformité Européenne

The CE mark is a mandatory conformity marking for certain products sold within the European Economic Area (EEA) since 1985. It is the manufacturer's declaration that the product meets the requirements of the applicable EC directives. All UZIN leveling compounds are labeled with CE marking to guarantee that each bag has the specific compressive strength and flexural strength.




GEV-Emicode®

GEV represents the German acronym for the Association for the Control of Emissions in Products for Flooring Installation, Adhesives and Building Materials or Gemeinschaft Emissionskontrollierte Verlegewerkstoffe (see www.emicode.com). Emicode® is GEV's trademark-protected name for their stringent testing and labeling system that categorizes products into 3 emission classes: EMICODE EC 1 R PLUS = very low emission, regulated, EMICODE EC 1 PLUS = very low emission, EMICODE EC 1 = low emission



The Blue Angel

The Blue Angel was the first environment-related label for products and services in the world. Since 1978 it has set the standard for eco-friendly products and services determined by an independent jury and by defined testing criteria. The Blue Angel is only awarded to products and services which are of considerable benefit to the environment and, at the same time, meet high standards of effectiveness, health and occupational protection (see www.blauer-engel.de/en/). Products with this label are solvent-free, low in emissions and do not produce harmful ozone-depleting greenhouse gasses.



LEED® Contributing Product

LEED® or "Leadership in Energy & Environmental Design" is a program developed by the U.S. Green Building Council. LEED Certification provides independent, third-party verification that a home was designed and built to achieve high performance in key areas (sustainable sites, Water Efficiency, Energy, Atmosphere, Materials, Resources, Indoor Environmental Quality) of human and environmental health. For more information see www.usgbc.org/leed. Products and programs help to conserve energy, water and other resources.



ÖKOLINE


ÖKOLINE

UZIN's environmentally friendly Ökoline range of products meet the stringent 3rd party testing requirements of GEV Emicode and Blue Angel for environmental safety and indoor air quality without sacrificing product effectiveness. All Ökoline products are solvent-free and low-emitting which means they do not release damaging volatile organic compounds into the environment.



SGS

SGS is the world's leading inspection, verification, testing and certification company and recognized as the global benchmark for quality and integrity. Their service activities cover all industry sectors and touch the products and services that consumers around the world rely on every day.



0736

Marine / Wheelmark

The Wheelmark is a mark of conformity valid throughout the EU, confirming suitability of the respective product for marine equipment in accordance with Council of the European Community Directive 96/98/EC on marine equipment (EC Marine Equipment Directive – MED). To obtain this mark of conformity, a defined fire test must be passed.

Subfloor Construction



The brief descriptions of products should only be used as a guide.

Detailed product data sheets for all products are available which should be used as reference when using the products.

Self Levelling Cementitious Thin Screed

UZIN SC 927

Low-stress cementitious thin screed for commercial areas

Self-levelling cementitious thin screed for the fabrication of bonded thin screeds and screeds on separating membranes

- Low-tension, reliable use also with high thicknesses
- Rapid drying also with high thicknesses, saves long setting times
- For low-thickness heating systems

APPLICATIONS:

- For the fabrication of thin bonded screeds and thin screeds on separating layers
- For normal wear in residential and commercial areas
- For thicknesses from 3 – 50 mm
- For embedding thin layer hot-water underfloor heating systems

PROPERTIES:

- For textile / resilient floor covering, prefinished wood flooring and ceramic tiles / natural stones
- Low tension
- Suitable for chair castors



Packsize	Pack. Unit/Pallet	Consumption	Colour
25 kg bag	42	5,1 kg/m ² / 3 mm 8,5 kg/m ² / 5 mm 17,0 kg/m ² / 10 mm	grey

Subfloor Construction



Installation of the Self Levelling Cementitious Thin Screed UZIN SC 927

SPECIAL SCREEDS

UZIN SC 970

Low-Shrink Rapid Cement



Consumption-optimised large cementitious screed areas without joints*

Special binding agent for the economic fabrication of no-shrinkage, dimensionally stable rapid cementitious screeds

- Large-surface work without pre-determined breaking points, reduces costs/m² significantly
- Strength class CT-C30-F5 at mixing ratio 1 : 6 facilitates very economic solutions
- Early heating and defined readiness for covering; follow-up work is therefore possible after a short amount of time*

APPLICATIONS:

- For the fabrication of floating screeds, screeds on separating layers and composite screeds, heated screeds
- For large areas without joints of 200 m²*
- For screeds without curling and setting at the edges
- For the fabrication of screeds with fixed deadlines

* For readiness for covering and field settings, refer to Product Data Sheet

PROPERTIES:

- Strength class CT-C30-F5
- Low-tension and free from deformation
- Very easy to process
- Early heating and defined readiness for covering
- Waterproof
- For interior use
- Low-chromate according to Regulation (EC) No 1907/2006 (REACH)

Packsize	Shipping Unit / Pallet	Consumption	Thickness	Colour
25 kg bag	42	2.6 kg/m ²	1 cm**	grey

**mixing ratio 1:6 respective C30-F5

UZIN SC 966

Rapid, Light Smoothing Mortar



Screed mix for repair work

Pre-mixed rapid screed mortar with very rapid drying – interior and exterior

- Mixes only with water, totally reliable in use
- Ideal for small areas, no waste material
- Very rapid setting and drying, saves time

APPLICATIONS:

- For producing bonded and floating screeds, screeds on separating membranes or heated screeds
- For producing low-slump repair mortars
- For screed work under time pressure

*see Product Data Sheet for drying rates

PROPERTIES:

- Waterproof and frost-resistant
- Can be covered after 1 day*
- Strength classifications CT-C35-F6
- Interior and exterior use
- Low chromate content according to Regulation (EC) No 1907/2006 (REACH)

Packsize	Shipping Unit / Pallet	Consumption	Thickness	Colour
30 kg bag	36	20 kg/m ²	1 cm	grey

UZIN SC 966 in practice



With UZIN SC 966, rapid drying bonded and floating screeds, heated screeds as well as screeds on separating membranes can be installed especially if time is a big issue.


DIFFERENT KINDS OF INSTALLING A SCREED

A screed is a non bearing, load distributing layer that levels the concrete ceiling in higher thicknesses (from 3 cm up) and can be footfall sound absorbent and thermal insulating (depending on typ of construction).

Screeds can be installed in 3 ways:

- Composite screed
- Unbonded screed on separating membrane
- Floating floor screed on insulation

COMPOSITE SCREED



1. Wall 2. Screed 3. Primer
4. Subfloor (e.g. concrete)

Properties:

- Normally cementitious based because of the high durability
- Installed directly on the subfloor (e.g. concrete)
- Extremely able to withstand stress
- Can be used without top covering


Areas:

- Industrial halls
- Basements
- Garages
- In general: areas with high load bearing

Disadvantage:

- No thermal insulation and footfall sound absorption
- Moisture barrier can be necessary before installation of floor covering

UNBONDED SCREED ON SEPARATING MEMBRANE



1. Foam Expansion Strip with film 2. Screed
3. Bogus paper

Properties:

- Difference to composite screed is only the separating membrane
- As a barrier against moisture
- Perfectly suitable for the installation of e.g. parquet afterwards


Areas:

- Industrial halls
- Basements
- Garages
- In general: areas with high load bearing

Disadvantage:

- No thermal insulation and footfall sound absorption

FLOATING FLOOR SCREED ON INSULATION



1. Foam Expansion Strip with film 2. Screed
3. Bogus paper 4. Footfall sound insulation and thermal insulation

Properties:

- Superior properties for thermal insulation and footfall sound absorption

Areas:

- For all areas where thermal insulation and footfall sound absorption is required

Disadvantage:

- For areas with lower load bearing compared to composite screed

Subfloor Preparation



The brief descriptions of products should only be used as a guide.

Detailed product data sheets for all products are available which should be used as reference when using the products.

UZIN PE 360 PLUS

Universal Primer

Reduces
surface
absorbency

Prime new and old screeds

Dispersion primer for absorbent substrates, screeds and concrete floors

- Short drying times, time-saving
- Ready to use, avoids mixing errors
- Increases bond-strength and reliability

APPLICATIONS:

- For mineral levelling compounds and dispersion adhesives (not for wood flooring adhesives)
- On new subfloors, e.g. concrete or screeds
- Even on existing absorbent subfloors
- Adhesives and levelling compounds

PROPERTIES:

- Penetrates into the subfloor
- Binds surface dust
- Reduces surface absorbency
- High-speed construction product
- Interior and exterior use
- Solvent-free



Packsize	Pack. Unit/Pallet	Consumption	Colour
20 kg bucket	18	80 – 200 g/m²	light blue
10 kg square bucket	48		

UZIN PE 360 PLUS in practice



Drying times:

Leave to dry to a clear, transparent and almost tack-free film.

Cement-based subfloors:	approx. 1 hour
Calcium sulphate and gypsum-based subfloors, renders:	4 – 6 hours
Subfloors with low absorbency, e.g. old adhesives:	4 – 6 hours

What effect does Universal Primer UZIN PE 360 PLUS have?

- Protects moisture-sensitive subfloors
- Prevents suction of water content from leveling compounds
- Increases the bond-strength between base screed and leveling compound

PRIMERS

SUBFLOOR CONSTRUCTION

SUBFLOOR PREPARATION

FLOOR COVERING ADHESIVES

switchTec®

WOOD FLOORING INSTALLATION

ACCESSORIES | TOOLS

SERVICE

UZIN PE 360 NEW

Universal Primer



Dispersion primer for absorbent substrates, screeds and concrete floors

- Short drying times, time-saving
- Ready to use, avoids mixing errors
- Increases bond-strength and reliability

APPLICATIONS:

- For mineral levelling compounds
- On new subfloors, e.g. concrete or screeds
- On concrete (dry)
- On levelling compounds

PROPERTIES:

- Penetrates into the subfloor
- Binds surface dust
- Reduces surface absorbency
- Interior use
- Solvent-free

Packsize	Pack. Unit/Pallet	Consumption	Colour
20 kg round bucket	18	80 – 200 g/m²	milk-blue
10 kg square bucket	48		

UZIN PE 260

Multipurpose Primer



Dispersion primer for existing substrates in renovation work

- Can be used on the widest variety of surfaces

DRYING TIMES:

- On dense and low absorbent surfaces: 4 – 6 hours
- On absorbent surfaces: approx. 1 hour

APPLICATIONS:

- For mineral levelling compounds and dispersion adhesives (not for wood flooring adhesives)
- On wooden surfaces as well as dense and low-absorbency surfaces
- On existing substrates, e.g. old adhesives

PROPERTIES:

- Film-forming
- Interior use
- Solvent-free

Packsize	Pack. Unit/Pallet	Consumption	Colour
10 kg square bucket	48	100 – 150 g/m²	light red

UZIN PE 280

Super-Fast Primer



Bonding agent for refurbishments

Dispersion primer with carbon technology for smooth and dense surfaces

- Ready to use and rapid drying, therefore ideal for work under time pressure
- Rough and solid surface, ideal connection between substrate and levelling compound

DRYING TIMES:

- On dense and low absorbent surfaces: approx. 45 minutes
- On UZIN EP-Primers: approx. 45 minutes

APPLICATIONS:

- Mineral-based levelling compounds
- On dense and smooth surfaces or existing surfaces
- On existing surfaces in need of refurbishment, e.g. on waterproof residues of adhesives and levelling compounds
- On mastic asphalt that is old or not gritted
- On magnesia- or stone-wood-screeds
- On fixed, basic cleaned coatings

PROPERTIES:

- Film-forming
- Bonding agent on dense surfaces
- Rough surface due to the carbon technology
- Interior use
- Solvent-free

Packsize	Shipping Unit / Pallet	Consumption	Colour
12 kg oblong drum	50	70 – 150 g/m²	ochre

2-Component Epoxy Primer-Sealer

UZIN PE 460

A reliable barrier against residual moisture

Epoxy primer for damp or weak surfaces

- Allows fast installation on cement-based surfaces, reducing waiting time and costs

DRYING TIMES:

- Foot traffic / further coating: approx. 8 hours
- Final strength: 3 – 5 days

APPLICATIONS:

- For mineral levelling compounds and mortars
- As a barrier against moisture up to 6-7 CM %
- For surface hardening of "worn out" screeds
- On moisture-resistant substrates requiring renovation

PROPERTIES:

- Approx. 20 % faster cure
- Reduced odour during application
- System component in PAH decontamination
- Interior and exterior use
- Solvent-free



Packsizes	Pack. Unit/Pallet	Consumption	Colour
10 kg + 5 kg combi-can	18	200 – 400 g/m ²	yellowish transparent
4 kg + 2 kg combi-can	36		

REACTION RESIN PRIMER

1-Component PUR Rapid Primer

UZIN PE 414 Turbo

Fast and reliable priming

One-component reaction resin primer for wood flooring and floor covering work

- No mixing, fast, high coverage and reliable

DRYING TIMES:

- 1. coat: approx. 1 hour
- 2. coat: approx. 12 hours

APPLICATIONS:

- For priming under reaction resin wood flooring adhesives
- On cement- or calcium sulphate-screeds, concrete, etc.
- On existing surfaces, e.g. well-bonded adhesive residues
- As a barrier against moisture up to 5 CM-%
- For smoothing compounds when grit-binding with UZIN Quartz Sand 0.8 or UZIN PE 280

PROPERTIES:

- Rapid drying
- Thin consistency
- Good penetration
- Neutral odour
- Interior use
- Solvent-free



Packsizes	Pack. Unit/Pallet	Consumption	Colour
12 kg canister	60	approx. 50 g/m ² / squeegee trowel	brown
6 kg canister	60	80 – 150 g/m ² / UZIN Nylon fibre roller	

REPAIR SMOOTHING COMPOUND

UZIN NC 182

Low Slump Smoothing Compound

Adjustable
consistency

Spreads to „nil thickness“

Low-slump, fine and very fast setting cement smoothing compound for any thickness

- Universal use as a repair mortar
- Rapid setting, time saving
- No marks under visually sensitive coverings
- From coarse aggregate

APPLICATIONS:

- For filling holes and surface damage
- For levels adjustment and patch smoothing work
- For fine skimming or area scratch-coating
- On all surfaces as a repair-, filling- and smoothing-compound

PROPERTIES:

- Ready for covering after 60 min.
- From feather-edge to high thicknesses
- Ideal working properties
- Fine grain, eliminates smoothing edges
- High-speed construction product
- Interior use
- Low-chromate content according to Regulation (EC) No 1907/2006 (REACH)



Packsizes	Pack. Unit / Pallet	Consumption / Thickness	Colour
12.5 kg square bucket	48	–	grey
20 kg bag	42	–	grey

UZIN NC 182 in practice



The application of UZIN NC 182 is an effortless and quick-drying solution to the problem of level variations.

Drying times:

Typical application that, with UZIN NC 182, are possible although! "outside the norm"

- Smoothing the joints in chipboard or OSB board
- Rapid repairs on stairs and landings
- Smoothing over surfaces of existing floors with wellbonded, waterproof residues of adhesives and smoothing compounds, even to a feather-edge
- Filling surface defects up to full screed thickness
- As a system component in high-speed construction

Suitable to use for ramping and on all surfaces as a repair smoothing-compound



Suitable to use for filling cracks and holes



Suitable to use to repair areas of surface damage



Suitable to skim-coating or patch smoothing work



SUBSTRATE REPAIRS

SUBFLOOR CONSTRUCTION

SUBFLOOR PREPARATION

FLOOR COVERING ADHESIVES

switchTec®

WOOD FLOORING INSTALLATION

ACCESSORIES | TOOLS

SERVICE

UZIN KR 516

2-Component Repair Resin



Low-odour sealing of cracks

Low-odour casting and bonding resin for the quick restoration of cracks as well as bonding, filling and repairs

- Versatile 2-component resin for repairing cracks and joints but equally suitable for bonding, filling and repairing mineral-based substrates. It hardens particularly quickly and after 45 minutes it is firm enough to allow levelling or bonding work.

APPLICATIONS:

- Sealing narrow and wide joints and cracks in screeds and concrete
- Bonding of angle rails, nailboards, profiles and rods from metal, wood or plastic, or similar
- Repairs on concrete, ceramics, stone, or similar
- Use as installation and repair resin in building construction

PROPERTIES:

- Low odour
- Extremely fast setting
- Small amounts can be mixed
- No stirring tools required
- Adjustable consistency
- Interior and exterior use
- Solvent-free

Packsizes	Pack. Unit/Pallet	Consumption	Colour
1 x 300 ml bottle A 1 x 300 ml bottle B	36 boxes / 216 units	aprox. 100 ml per lin.m. for 4mm joint with	yellowish

UZIN KR 419

2-Component Repair Resin



Strong resin repair of screed cracks

Low viscosity, multipurpose acrylic resin for repairs to screeds and concrete

- Ideal for fine joints and cracks, very rapid setting, no waiting time

APPLICATIONS:

- For resin-bonding of joints and cracks
- As a poured filler for hollow-spots
- On all substrate types as a repair material

PROPERTIES:

- Supplied with corrugated screed-clamps
- Interior and exterior use
- Solvent-based

Packsizes	Pack. Unit/Pallet	Consumption / Thickness	Colour
A/B 0.75 kg can	30 cartons	approx. 100 – 150 g per lin. m. for 4 mm joint width	yellowish

UZIN NC 169 Levelling Compound

Surface preparation for all requirements

Self-levelling, high-strength, cement flooring compound for use at any thickness

- Wide range of uses, therefore truly universal
- Highest strength giving reliability in heavy-wear areas

APPLICATIONS:

- For high quality smoothing and levelling prior to all types of floor covering work
- On new substrates, e.g. cement screeds
- On existing substrates in need of renovation, e.g. on waterproof adhesive and levelling compound residues

PROPERTIES:

- Excellent flow properties and pumpable
- No thickness limitations
- Highly plasticised
- Interior use



Packsize	Pack. Unit / Pallet	Consumption / Thickness	Colour
25 kg bag	42	1.4 kg/m ² / 1 mm 4.2 kg/m ² / 3 mm 14.0 kg/m ² / 10 mm	grey

UZIN NC 169 in practice



What do you achieve when preparing new screeds and existing surfaces

- Consolidation of uneven, rough screeds to give uniformly smooth, consistent, fully prepared surfaces
- Achievement of a flat and level surface that meets not only the needs of DIN 18 202 but also the required conditions for the surface covering
- A surface providing the optimum, system-compatible grab performance of modern water-based dispersion adhesives
- Achievement of consistently absorbent surfaces for overall strong adhesion of the floor covering without bubbling
- Production of fully prepared surfaces in renovation work over old materials and substrates

SELF-LEVELLING COMPOUNDS

UZIN NC 159

Smoothing Compound



Surface preparation in project work

Self-levelling cement flooring compound for thickness up to 20 mm

- Excellent application properties
- Easy to rub down despite high strength, ideal for project work

APPLICATIONS:

- For smoothing and levelling work prior to bonding textile and resilient floor coverings
- On new substrates, e.g. cement screeds
- On existing surfaces in need of refurbishment

PROPERTIES:

- Easy to rub down
- Excellent absorbency
- For Interior use
- Low chromate content in accordance with RL 2003/53/EG



Packsize	Pack. Unit/Pallet	Consumption / Thickness	Colour
25 kg bag	42	1.4 kg/m ² / 1 mm 4.2 kg/m ² / 3 mm 14.0 kg/m ² / 10 mm	grey

UZIN NC 149

Levelling Compound



Economical surface preparation

Self-levelling cement flooring compound for thickness up to 10 mm

- Economical and efficient for standard levelling work

APPLICATIONS:

- Very easy to rub down
- For standard preparation work prior to floor covering installation
- On new substrates, e.g. cement screeds
- On existing surfaces for refurbishment, according to Regulation (EC) No 1907/2006 (REACH)

PROPERTIES:

- Good strength properties
- Interior use
- Low chromate content



Packsize	Pack. Unit/Pallet	Consumption / Thickness	Colour
25 kg bag	42	1.5 kg/m ² / 1 mm 4.5 kg/m ² / 3 mm 7.5 kg/m ² / 5 mm	grey

UZIN NC 145

Levelling Compound



Cost-effective surface preparation

Self-levelling cement flooring compound for thickness up to 6 mm

- Economical surface preparation for residential areas
- For standard surface preparation prior to floor covering installation

APPLICATIONS:

- On new substrates, e.g. cement screeds
- On existing surfaces for refurbishment, e.g. over water-resistant residues of adhesives and levelling compounds

PROPERTIES:

- Excellent flow properties
- Good strength performance
- Interior use
- Low-chromate content according to Regulation (EC) No 1907/2006 (REACH)



Packsize	Pack. Unit/Pallet	Consumption / Thickness	Colour
25 kg bag	42	1.5 kg/m ² / 1 mm 4.5 kg/m ² / 3 mm 7.5 kg/m ² / 5 mm	grey

Fibre-Reinforced Levelling Compound

UZIN NC 155

Fibre-reinforced preparation for wood flooring

Self-levelling, fibre-reinforced cement levelling compound for thickness from 3 to 10 mm

- Extremeley good flowing properties
- Stable even on „problem subfloors“, therefore high reliability
- Provides a stabilising levelling coat, no need to remove problem base constructions

APPLICATIONS:

- For smoothing and levelling prior to installation of floor coverings and wood flooring
- On wooden substrates; rapid drying
- On jointed substrates with slight deflection

PROPERTIES:

- Fibre-reinforced
- Very goog absorbency
- Smooth surface in spite of fibre reinforcement
- Highly plasticised
- Interior use
- Low-chromate content according to Regulation (EC) No 1907/2006 (REACH)



Packsize	Pack. Unit/Pallet	Consumption / Thickness	Colour
25kg bag	42	4.5 kg/m ² / 3mm 9.0 kg/m ² / 6mm 13.5 kg/m ² / 9mm	grey

Rapid Levelling Compound

UZIN NC 162 Turbo

Extremely rapid drying for fast installation

Extremely rapid drying, self-levelling cement compound with the Level Plus Effect for virtually all areas of use, all substrate types and to thickness up to 10 mm

- Extremely rapid drying and cost-saving
- Very smooth surface finish, therefore lower adhesive consumption and no grinding needed in most cases

APPLICATIONS:

- For fast installation of e.g. all types of textile coverings, PVC / cushioned vinyl, PVC design flooring, LVT, rubber sheet and tile coverings as well as ceramic tiling and natural stone
- For installation of wood flooring, polyolefin and polyurethane floor coverings after a drying time of 12 hours

PROPERTIES:

- Hydraulic setting
- Easy to rub down during initial cure-phase
- Very smooth surface finish
- Easy adhesive application and up to 10 % lower adhesive consumption
- Interior use
- Low-chromate content according to Regulation (EC) No 1907/2006 (REACH)



Packsize	Pack. Unit/Pallet	Consumption / Thickness	Colour
25kg bag	42	1.5 kg/m ² / 1mm 4.5 kg/m ² / 3mm 7.5 kg/m ² / 5mm	grey

CEMENTITIOUS TOP COATINGS

UZIN NC 1700



Industrial surface preparation

Self-levelling cementitious coating for industrial areas

- Designed for usage in industrial areas with heavy traffic and abrasion
- Especially production areas, warehouses, car parks, museums, etc.

APPLICATIONS:

- For the fabrication of wear layers in industrial areas without top covering
- On new substrates, e.g. cement screeds
- On existing surfaces for refurbishment, e.g. over water-resistant residues of adhesives and levelling compounds

PROPERTIES:

- Very smooth self levelling compound for industrial use
- Excellent flow properties
- Highest strength performance
- Interior use

Packsizes	Pack. Unit/Pallet	Consumption	Colour
25 kg bag	42	7,5 kg/m ² / 5 mm 15 kg/m ² / 10 mm	grey

UZIN NC 1600



Cementitious design surface preparation

Self-levelling cement flooring coating for light to medium loading

APPLICATIONS:

- For the fabrication of wear layers in industrial and commercial areas without top covering
- On new substrates, e.g. cement screeds
- On existing surfaces for refurbishment, e.g. over water-resistant residues of adhesives and levelling compounds

PROPERTIES:

- Extremely smooth self levelling compound for a perfect appearance
- Excellent flow properties
- Very good strength performance
- Interior use

Packsizes	Pack. Unit/Pallet	Consumption	Colour
25 kg bag	42	7,5 kg/m ² / 5 mm 15 kg/m ² / 10 mm	grey

Floor Covering Adhesives



The brief descriptions of products should only be used as a guide.
Detailed product data sheets for all products are available which should be used as reference when using the products.

UZIN KE 2000 S

Universal Pressure-Sensitive Adhesive

**Extremely
reliable**

Reliable adhesion of resilient floor coverings

Pressure-sensitive dispersion adhesive with very high bond-strength for resilient floor coverings

- As a semi-wet, pressure-sensitive, contact or double-drop adhesive with strong thread-formation and a wide range of uses
- High residual adhesive effect, reliable adhesion even on non-absorbent surfaces

APPLICATIONS:

- For homogeneous and heterogeneous PVC / CV floor coverings in sheets and tiles
- For luxury vinyl tiles
- For rubber flooring in sheets, e.g. noraplan® up to 4 mm
- For chlorine-free resilient floor coverings, e.g. Upofloor LifeLine®
- For PUR floor coverings in sheet up to 2.0 mm, e.g. WPT PURline®
- For Flotex
- For wall coverings, e.g. PVC floor coverings in bathrooms
- For all UZIN insulation and installation underlays


PROPERTIES:

- High coverage
- Very long working time, up to 2 hours
- High early and final strength
- For interior use only
- Solvent-free
- Short open time



Pack Size	Packaging Unit / Pallet	Consump. / Notch Size	Colour
15 kg square bucket	48	250 – 300 g/m ² / A1 300 – 350 g/m ² / A2 200 – 250 g/m ² / A5	cream-white

i UZIN KE 2000 S in practice



Typical applications where it's possible to also use UZIN KE 2000 S in a different way:

- Adhesion of Rubber and PVC / Vinyl floor coverings on dense, non-absorbent substrates, e.g. finishes or old floor coverings, as long as the requirements are met.
- Repair work, e.g. elimination of bubbling in resilient floor coverings with UZIN KE 2000 S.

In large areas UZIN KE 2000 S shows itself best – especially its proven adhesive power and the great reliability of the installation

UZIN FA 330 Universal Adhesive

Universal use with PVC- and textile coverings

Multipurpose dispersion adhesive for PVC and textile floor coverings

- Wide range of uses (dispersion adhesive for many standard coverings)

APPLICATIONS:

- For homogenous and heterogeneous PVC
- Cushioned vinyl coverings, incl. with textile felt backings
- Carpets with textile secondary backings (TR), with felt backings, with smooth or profiled foam backings, etc.
- Lightweight, lay-flat needlepunch
- Use on prepared, level and absorbent surfaces
- For all type of PVC and textile floor coverings

PROPERTIES:

- Long working time
- Good grab properties
- Excellent plasticizer resistance
- Solvent-free
- High final strength



Pack Size	Packaging Unit / Pallet	Consump. / Notch Size	Colour
24 kg bucket	18	250 – 300 g/m ² / A1 300 – 350 g/m ² / A2 350 – 450 g/m ² / B1 350 – 450 g/m ² / B2	cream-white
15 kg square bucket	48		

UZIN FA 330 in practice



Whether in project work or in domestic locations – for modern and fast installation of textile floor coverings, UZIN FA 330 is always there.

UZIN KR 430

2-Component Polyurethane Adhesive

Bonds rubber flooring "hard as nails"

Polyurethane adhesive for heavy duty floor coverings

- Very high dimensional stability even with special covering materials
- Highest bond-strength, therefore extremely reliable
- For (almost) any loading, therefore universal applications
- Available with green color as artificial grass adhesive
- Available with white color as adhesive for light color floor coverings

APPLICATIONS:

- For rubber flooring up to 10 mm thickness
- For rubber granulate or underlays
- Can also be used for linoleum
- On absorbent and non-absorbent surfaces
- In sports-halls, industrial and heavy wear locations

PROPERTIES:

- No shrinkage
- Extremely high final strength
- High resistance to heat and cold
- Interior and conditional exterior use
- Solvent-free



Pack Size	Packaging Unit / Pallet	Consumption	Colour
12,5kg + 2,5kg combi-can	18	250 – 300 g/m ² / A1/A5 300 – 350 g/m ² / A2/A3 400 – 600 g/m ² / B1/B2 800 – 1300 g/m ² / B2/C1	grey
5 kg + 1 kg combi-can	36		

UZIN KE 2000 S in practice



UZIN KR 430 is suitable for heaviest wear in commercial, industrial, heavy load and sports areas.

UZIN LE 31 Linoleum Adhesive

Economical adhesion of linoleum

Dispersion adhesive for linoleum

- Wet-bond adhesive with good thread-formation, reliable adhesion even at edges and joints
- Economical in price and usage, cost-effective

APPLICATIONS:

- For sheet linoleum and Korkment
- On level, prepared surfaces with good absorbency
- On UZIN Multibase and on UZIN insulating and installation underlays

PROPERTIES:

- Easy to spread
- Exceptional thread-formation
- Only for use on absorbent surfaces
- Interior use only



Pack Size	Packaging Unit / Pallet	Consumption	Colour
24 kg bucket	18	350 – 450 g/m ² / B1	cream white

UZIN LE 31 in practice



UZIN LE 31 meets the high demands placed on linoleum installation in project work, e.g. hospitals, nurseries, office buildings, schools, etc.

EASY RELEASE SYSTEMS

UZIN U 1200

Anti-slip coating



Non-slip installation of loose-laid tiles

Slip-resistant and tackifying dispersion for loose-laid carpet tiles

- Prevents "wandering" of tiles but allows easy removal at any time

APPLICATIONS:

- For loose-laid carpet tiles with bitumen-, PVC- or PU- backings
- On absorbent and non-absorbent surfaces
- On access and raised flooring, existing floor finishes
- In domestic and commercial locations

PROPERTIES:

- Easy roller application
- Very economical consumption
- Antistatic
- Interior use only
- Solvent-free

Packsizes	Shipping Unit / Pallet	Consumption	Colour
10 kg square bucket	48	50 – 100 g/m ² / roller application	white

UZIN Universal tackifier

Universal tackifier



Easy-release installation of soft textile coverings

Water-soluble dispersion fixative for PVC and textile coverings

- Easier to release than fully bonded, saves costs during later renovation

APPLICATIONS:


- For textile coverings with lightweight secondary or fleece- backings
- For soft PVC and cushioned vinyl
- On absorbent and non-absorbent surfaces
- On suitable, intact, existing floor coverings, e.g. PVC flooring
- In rented accommodation, domestic and lightweight project locations


PROPERTIES:

- Application by roller or notched trowel
- Easy to release on dense surfaces
- As a wet-bond or pressure-sensitive adhesive
- Interior use only
- Solvent-free

Packsizes	Shipping Unit / Pallet	Consumption	Colour
12 kg square bucket	48	100 – 200 g/m ² / roller 150 – 200 g/m ² / A4 250 – 300 g/m ² / A3 approx. 300 g/m ² / A2	cream-white

ADHESIVES FOR PROFILES, STAIRS AND VERTICAL SURFACES

Universal Pressure-Sensitive Adhesive				UZIN KE 2000 S
Reliable adhesion of resilient floor coverings Pressure-sensitive dispersion adhesive with very high bond-strength for resilient floor coverings <ul style="list-style-type: none"> As a semi-wet, pressure-sensitive, contact or double-drop adhesive with strong thread-formation and a wide range of uses High residual adhesive effect, reliable adhesion even on non-absorbent surfaces <div> <div> APPLICATIONS: <ul style="list-style-type: none"> For homogeneous and heterogeneous PVC / CV floor coverings in sheets and tiles For luxury vinyl tiles For rubber flooring in sheets, e.g. noraplan® up to 4 mm For chlorine-free resilient floor coverings, e.g. Upofloor LifeLine® For PUR floor coverings in sheet up to 2.0 mm, e.g. WPT PURline® For Flotex For wall coverings, e.g. PVC floor coverings in bathrooms For all UZIN insulation and installation underlays </div> <div> PROPERTIES: <ul style="list-style-type: none"> High coverage Very long working time, up to 2 hours High early and final strength For interior use only Solvent-free Short open time </div> </div>				
Packsize	Shipping Unit / Pallet	Consumption	Colour	
15 kg square bucket	48	250 – 300 g/m ² / A1 300 – 350 g/m ² / A2 200 – 250 g/m ² / A5	cream-white	

Profile Contact Adhesive				UZIN SK 840
The strongest contact adhesive Very powerful solvent-based contact adhesive for skirtings, profiles and coverings <ul style="list-style-type: none"> Touch-dry in minutes, saves waiting time <div> <div> APPLICATIONS: <ul style="list-style-type: none"> For skirtings, profiles and coverings For PVC, cushioned vinyl, linoleum, textiles and cork On all solvent-resistant surfaces and stairs </div> <div> PROPERTIES: <ul style="list-style-type: none"> Easy brush application Long contact bond time Interior use only High solvent content </div> </div>				
Packsize	Shipping Unit / Pallet	Consumption	Colour	
19 l can	18	100 – 150 g/m ² / A5 150 – 200 g/m ² / A1	yellow	
6 l can	72			

ADHESIVE FOR HEAVY WEAR AREAS

UZIN KR 420

2-Component Reactive Resin Adhesive



Reliable adhesion of flooring even in wet and heavy-wear areas

Reactive-resin adhesive for heavy-duty floor coverings in interior, exterior and wet areas

- A problem-solver in many situations

APPLICATIONS:

- For problematic, resilient flooring and outdoor coverings
- On absorbent and non-absorbent substrates
- In sports-halls, industrial and heavy-wear locations

PROPERTIES:

- For interior and exterior use
- Low solvent content

Packsize	Shipping Unit / Pallet	Consumption	Colour
A/B 12 kg combi-can	18	300 – 350 g/m ² / A2/A3 400 – 600 g/m ² / B1/B2 800 – 1300 g/m ² / B3/C1	white

UZIN KR 430

2-Component PU Adhesive



Bonds rubber flooring "hard as nails"

Polyurethane adhesive for heavy-duty floor coverings

- Highest bond-strength, high dimensional stability, therefore extremely reliable
- For use in areas with (almost) any loading, universal

APPLICATIONS:

- For rubber flooring up to 10 mm thickness
- For rubber granulate coverings or underlays
- Can also be used for linoleum
- On absorbent and non-absorbent substrates
- In sports-halls, industrial and heavy-wear locations

PROPERTIES:

- Extremely high final strength
- High resistance to heat and cold
- For interior and conditional exterior use
- Solvent-free

Pack Size	Packaging Unit / Pallet	Consumption	Colour
12,5kg + 2,5kg combi-can	18	250 – 300 g/m ² / A1/A5 300 – 350 g/m ² / A2/A3 400 – 600 g/m ² / B1/B2 800 – 1300 g/m ² / B2/C1	grey
5 kg + 1 kg combi-can	36		

ADHESIVES OR ELECTROSTATIC CONTROL INSTALLATION

Adhesive for conductive PVC

UZIN KE 2330 L

Wet-bond adhesive for the sensitive health sector

Conductive fibre-adhesive for all PVC floor coverings

- Rapid grab properties, allows efficient and time-saving installation
- High coverage for project work, therefore cost-effective

APPLICATIONS:

- For conductive PVC in sheet and tile
- On absorbent, prepared surfaces
- In commercial and project locations

PROPERTIES:

- Easy to spread
- Powerful thread-formation
- High initial and final strength
- Conductive in accordance with DIN EN 13 415
- Interior use only
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Colour
12,5 kg square bucket	48	300 – 350 g/m ² / 23/80	light grey

Conductive Adhesive for PVC and Rubber

KE 2000 SL

Semi-wet-bond adhesive for sensitive areas in the health sector

Conductive fibre adhesive for sheet rubber and all PVC coverings

- Rapid grab performance, fast work progress, time-saving
- High coverage in project work, therefore cost-effective
- Snap-off 28 cm/21 cm notched trowel blade supplied, option for large or small areas

APPLICATIONS:

- For conductive PVC sheet and tile coverings
- For conductive sheet rubber (up to 3.5 mm)
- On absorbent, prepared surfaces
- In commercial locations and project work

PROPERTIES:

- Easy to spread
- Powerful thread-formation
- High initial and final strength
- Electrically conductive
- For interior use only
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Colour
12,5 kg square bucket	48	300 – 350 g/m ² / 23/80	light grey

Conductive Adhesive for PVC and Rubber

UZIN KR 421 L

Heavy-duty installation of conductive resilient floor coverings

Conductive, flexible epoxy-resin adhesive for heavy-duty flooring in interior and exterior locations

- Highest adhesion power, therefore extremely reliable
- Especially for all conductive (special) installations, a problem-solver

APPLICATIONS:

- For conductive rubber tile flooring and conditionally also for sheet
- For conductive sheet and tile PVC flooring
- For conductive sheet and tile linoleum
- On absorbent and non-absorbent substrates

PROPERTIES:

- Very extreme high loading up to 5 N/mm²
- For interior and exterior use
- Low solvent content



Packsize	Shipping Unit / Pallet	Consumption	Colour
A/B 6 kg combi-can	60	approx. 300 g/m ² / A5 350 – 400 g /m ² / A1/A2 400 – 600 g /m ² / B1/B2	black



The brief descriptions of products should only be used as a guide.
Detailed product data sheets for all products are available which should be used as reference when using the products.

Sigan 1 High-Performance Adhesive

Easy
removal with
no residue

Fast adhesion of new coverings onto levelling compounds and chipboard

Patented, micro-perforated special foil carrier, dry adhesive on both sides, for the installation of textile and resilient floor coverings. Guarantees to leave no residues when removed later.

- For new resilient and textile floor covering
- On levelling compound, chip board, metal

APPLICATIONS:

- Installation of textile and resilient floor coverings
- Suitable for any size area
- Sigan is resistant to cleaning agents and spray extraction cleaning
- Sigan is suitable for underfloor heating
- Permits usage under high loads and traffic such as chair castors, lift trucks, forklift traffic

PROPERTIES:

- Quick and easy installation
- No trapped air bubbles thanks to micro-perforation and ventilation channels
- Floor covering immediately ready for foot traffic and loads
- Can be bonded / used immediately
- Can later be removed, guaranteed without residues
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Dimensions
1 roll Sigan 1 and 1 roll Sigan 1 tape	40	total content covers 20 m²	75 cm x 25 m 50 mm x 25 m

① Sigan 1 in practice



1. Apply special Primer Planus on the subfloor



2. Bond Sigan 1 on the prepared subfloor



3. Peel the protective paper from the Sigan 1 keeping it flat and straight



4. Lay in new flooring and press down avoiding stress or distortion

Sigan Elements Plus High-Performance Adhesive

Easy
removal with
no residue

Fast adhesion of new luxury vinyl tiles and PVC tiles onto levelling compounds, chipboard and metal

Dimensionally stabilising, dry adhesive system on both sides, for installing LVT and PVC tiles onto levelling compounds, chipboard and metal. Guarantees to leave no residues when removed later.

- For luxury vinyl tiles and PVC tiles
- On levelling compounds, chipboard, metal

APPLICATIONS:

- Installation of luxury vinyl tiles and PVC tiles
- Suitable for any size area
- Sigant is resistant to cleaning agents and spray extraction cleaning
- Sigant is suitable for underfloor heating
- Permits usage under high loads and traffic such as chair castors

PROPERTIES:

- Dimensionally stabilising
- Quick and easy installation
- Floor covering immediately ready for foot traffic and loading
- Immediately weldable
- PVC luxury floor covering and PVC tiles can be installed without joints
- Can later be removed, guaranteed without residues
- Solvent-free / complies with TRGS 610 (technical regulation for dangerous substances)
- Does not dry out or become brittle
- Interior use
- Solvent-free




Packsize	Shipping Unit / Pallet	Consumption	Dimensions
1 roll Sigan Elements Plus and 1 roll Sigan Elements Plus tape	40	total content covers 20 m²	75 cm x 25 m 50 mm x 25 m

① Sigan Elements Plus in practice



1. Apply special Primer Planus on the subfloor



2. Install Sigan Elements Plus in the running direction of the new floor covering.



3. Measure the room, divide into planks or tiles. Mark the starting point of the first row with a soft pencil or regular DVD marker on the protective paper. Place a steel rail along the measuring points. Pull the protective paper away from the Sigan Elements Plus horizontally and straight up to the steel rail. As an alternative way use Sigan Elements Universal Tape.



4. Install the planks or tiles along the reference line without stressing and press down firmly by hand.

ADHESIVES FOR FLOOR COVERINGS

Special Primer for Sigan 1 or Sigan Elements Plus

Planus

System component for Sigan 1 or Sigan Elements Plus

- Guarantees reliable adhesion of floor coverings with Sigan 1 or Sigan Elements Plus
- Guarantees residue-free removal of floor coverings bonded on Sigan 1 or Sigan Elements Plus

APPLICATIONS:

- On absorbent surfaces such as levelling compounds, chipboard, wood-fibreboards (OSB, MDF, etc.), magnesia screeds, wooden floors (untreated)
- On non-absorbent surfaces such as metal (untreated)

PROPERTIES:

- Suitable for underfloor heating system
- Can be re-coated without sanding down
- Can be coated with dispersion adhesives or levelling compounds* without sanding down
- Interior use
- Solvent-free

* Call in a technical adviser.



Packsize	Shipping Unit / Pallet	Consumption
2,5 kg canister	126	70 – 100 g/m²
10 kg canister	40	70 – 100 g/m²

Cork Rubbing Board textile-covered

Practical cork board for rubbing down Sigan and floor coverings

APPLICATIONS:

- For easy rubbing down

PROPERTIES:

- Strong construction textile covered with wooden hand-grip (professional quality)



Packsize	Weight
1 piece	0,5 kg

Sigan 2 High-Performance Adhesive

NEW

Fast adhesion of new coverings onto existing resilient floor coverings

Patented, metal-reinforced special dry adhesive system with micro-ventilation and ventilation channels for the installation of textile and resilient floor coverings which guarantees to leave no residues when removed later. Suitable for any size area.

- For new resilient and textile floor covering
- Existing resilient and ceramic surfaces

APPLICATIONS:

- Installation of textile and resilient floor coverings
- Suitable for any size area
- Sigan is resistant to cleaning agents and spray extraction cleaning
- Sigan is suitable for underfloor heating
- Permits usage under high loads and traffic such as chair castors, lift trucks, forklift traffic

PROPERTIES:

- Quick and easy installation
- No trapped air bubbles thanks to micro-perforation and ventilation channels
- Floor covering immediately ready for foot traffic and loads
- Can be bonded / used immediately
- Can later be removed, guaranteed without residues
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Dimensions
1 roll Sigan 2 and 1 roll Sigan 2 tape	40	total content covers 20 m²	75 cm x 25 m 5 cm x 25 m

① Sigan 2 in practice



1. Bond Sigan 2 in the appropriate direction onto existing PVC, cushioned vinyl or linoleum



2. Lay in new PVC, cushioned vinyl or carpet and press down avoiding stress or distortion



3. The floor covering is immediately ready to take traffic and loading



4. And years later remove the covering together with Sigan 2 leaving no residue

Sigan Elements High-Performance Adhesive

Easy
removal with
no residue

Fast adhesion of new luxury vinyl tiles and PVC tiles onto existing resilient floor coverings

Dimensionally stabilising, dry adhesive system on both sides, for installing LVT and PVC tiles onto existing smooth floor coverings. Guarantees to leave no residues when removed later.

- For luxury vinyl tiles and PVC tiles
- On existing smooth floor coverings

APPLICATIONS:

- Installation of luxury vinyl tiles and PVC tiles
- Suitable for any size area
- Sigan is resistant to cleaning agents and spray extraction cleaning
- Sigan is suitable for underfloor heating
- Permits usage under high loads and traffic such as chair castors

PROPERTIES:

- Dimensionally stabilising
- Quick and easy installation
- Floor covering immediately ready for foot traffic and loading
- Immediately weldable
- PVC luxury floor covering and PVC tiles can be installed without joints
- Can later be removed, guaranteed without residues
- Solvent-free / complies with TRGS 610 (technical regulation for dangerous substances)
- Does not dry out or become brittle
- Interior use
- Solvent-free




Packsize	Shipping Unit / Pallet	Consumption	Dimensions
1 roll Sigan Elements and 1 roll Sigan Elements tape	40	total content covers 20 m²	75 cm x 25 m 50 mm x 25 m

① Sigan Elements in practice




1. Install Sigan Elements in the running direction of the new floor covering onto the existing floor covering.



2. Measure the room, divide into planks or tiles. Mark the starting point of the first row with a soft pencil or regular DVD marker on the protective paper. Place a steel rail along the measuring points. Pull the protective paper away from the Sigan Elements horizontally and straight up to the steel rail. As an alternative way use Sigan Elements Universal Tape.



3. Install the planks or tiles along the reference line without stressing and press down firmly by hand.



4. Floor covering is immediately ready for foot traffic.

ADHESIVES FOR FLOOR COVERINGS

Sigan 3

High-Performance Adhesive



Fast adhesion of new coverings onto existing wood flooring / laminate

Patented, micro-perforated special foil carrier, dry adhesive on both sides, for the installation of textile floor coverings. Guarantees to leave no residues when removed later.

- For new textile floor coverings
- On existing wood flooring, laminate

APPLICATIONS:

- Installation of textile floor coverings
- Suitable for any size area
- Sigan is resistant to cleaning agents and spray extraction cleaning
- Sigan is suitable for underfloor heating
- Permits usage under high loads and traffic such as chair castors, lift trucks, forklift traffic

PROPERTIES:

- Quick and easy installation
- No trapped air bubbles thanks to micro-perforation and ventilation channels
- Floor covering immediately ready for foot traffic and loads
- Can be bonded / used immediately
- Can later be removed, guaranteed without residues
- Interior use
- Solvent-free

Packsizes	Shipping Unit / Pallet	Consumption	Dimensions
1 roll Sigan 3 and 1 roll Sigan 3 tape	40	total content covers 20 m²	75 cm x 25 m 5 cm x 25 cm

Sigaway

High-Performance Adhesive



Fast adhesion of new carpet onto textile surfaces

- For textile coverings
- On textile coverings

APPLICATIONS:

- Application of new carpets onto textile surfaces
- suitable for any size area
- Sigaway is resistant to cleaning agents and spray extraction cleaning
- Sigaway is suitable for underfloor heating

PROPERTIES:

- Quick and easy use
- Will not dry out or become brittle
- Floor covering immediately ready for foot traffic and loads
- Interior use
- Solvent-free

Article No.	Packsizes	Shipping Unit / Pallet	Consumption	Dimensions
35063	1 roll	40	total content covers 25 m²	100 cm x 25 m

SUPERTape 7900

High-Performance Adhesive



Adhesive tape for floor coverings

- For strengthening edge and seam adhesion of Sigaway installations

APPLICATIONS

- For strengthening edge and seam adhesion of Sigaway installation

PROPERTIES

- Quick and clean use
- Will not dry out or become brittle
- Floor covering immediately ready for foot traffic and loads
- Interior use
- Solvent-free

Packsizes	Shipping Unit / Pallet	Dimensions
1 roll	42 boxes / 504 units	5 cm x 25 m

ADHESIVES FOR FLOOR COVERINGS

Sigan Elements Universal Tape **NEW**

Dimensionally stabilising, dry adhesive system on both sides, for installing LV T and PVC tiles onto levelling compounds, chipboards, existing smooth floor coverings. Guarantees to leave no residues when removed later.

- For luxury vinyl tiles and PVC tiles
- On levelling compound, chipboard metal or existing smooth floor coverings

APPLICATIONS:

- Installation of luxury vinyl tiles and PVC tiles
- Suitable for any size area
- Resistant to cleaning agents and spray extraction cleaning
- Suitable for underfloor heating
- Permits usage under high loads and traffic such as chair castors

PROPERTIES:

- Dimensionally stabilising
- Quick and easy installation
- Floor covering immediately ready for foot traffic and loading
- Can later be removed, guaranteed without residues
- Interior use
- Solvent free



Packsize	Shipping Unit / Pallet	Dimensions
1 roll Sigant Elements Universal Tape	720	70 mm x 25 m

Special Skirting Tape for DÖLLKEN

Toptac 35

DÖLLKEN – UZIN system guarantee

- For DÖLLKEN core skirting boards
- On substrates up to 1 mm structure height

APPLICATIONS:

- Special adhesive system for the bonding of DÖLLKEN core skirting boards. Ensures the quick and solvent-free installation

PROPERTIES:

- DÖLLKEN-UZIN System Guarantee
- Does not become brittle, providing a strong & permanent bond
- Rapid even on concrete & metal
- Easier with Toptac applicator
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Dimensions	Base height
4 rolls	105 units / 420 rolls	35 mm x 50 m	40 – 100 mm

High-Performance Adhesive Tape for Textile Skirtings

Contact

Strong adhesion of whipped carpet

- For whipped carpet skirtings
- On surfaces with up to 1.5 mm deep texture

APPLICATIONS:

- Quick and secure installation of whipped carpet skirting. Allows quick and clean working without solvents.

PROPERTIES:

- Does not become brittle, providing a strong & permanent bond
- Clean & fast
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Dimensions	Base height
3 rolls	96 units / 288 rolls	85 mm x 50 m	90 – 110 mm
3 rolls	96 units / 288 rolls	70 mm x 50 m	75 – 85 mm
4 rolls	96 units / 384 rolls	55 mm x 50 m	60 – 70 mm
6 rolls	96 units / 576 rolls	40 mm x 50 m	45 – 55 mm

ADHESIVES FOR FLOOR COVERINGS

SUBFLOOR CONSTRUCTION

SUBFLOOR PREPARATION

FLOOR COVERING ADHESIVES

switchtec®

WOOD FLOORING INSTALLATION

ACCESSORIES | TOOLS

SERVICE

Pomur 46

Special tape for DÖLLKEN soft coved skirting WL 50 life



DÖLLKEN – UZIN system guarantee

- For DÖLLKEN soft coved skirting WL 50 life
- Onto surfaces with up to 1 mm deep texture

APPLICATIONS:

- Bonding of DÖLLKEN soft skirting on substrates with 1 mm structure depth
- Quick and solvent-free installation

PROPERTIES:

- DÖLLKEN-UZIN System Guarantee
- 3 - 5 times faster
- No prior fitting and priming
- Does not become brittle, providing a strong & permanent bond
- Interior use
- Solvent-free

Packsizes	Shipping Unit / Pallet	Dimensions	Base height
4 rolls	60 units / 240 rolls	40 mm x 50 m	45 – 55 mm

Bullran 45

High-Performance Tape for Coarse-Backed Textile Skirtings



Strong adhesion of carpet skirtings onto rough surfaces

High-performance adhesive for needlepunch, woven- and fleece-backings

- For whipped carpet skirtings 50 – 60 mm
- On surfaces with up to 3 mm deep texture

APPLICATIONS:

- High-performance adhesive for the installation of textile skirtings with different kind of backings

PROPERTIES:

- High-performance adhesive for needle punch, web and fleece backing
- Does not become brittle, providing a strong & permanent bond
- Clean & fast
- Interior use
- Solvent-free

Packsizes	Shipping Unit / Pallet	Dimensions	Base height
4 rolls	144 units / 576 rolls	45 mm x 25 m	50 – 60 mm

Contact 40

Special Tape for Flooring-Strips in DÖLLKEN Coving



Strong adhesion of carpet skirtings onto rough surfaces

High-performance adhesive for needlepunch, woven- and fleece-backings

- For whipped carpet skirtings 50 – 60 mm
- On surfaces with up to 3 mm deep texture

APPLICATIONS:

- High-performance adhesive for the installation of textile skirtings with different kind of backings

PROPERTIES:

- High-performance adhesive for needle punch, web and fleece backing
- Does not become brittle, providing a strong & permanent bond
- Clean & fast
- Interior use
- Solvent-free

Packsizes	Shipping Unit / Pallet	Dimensions	Base height
6 rolls	96 units / 576 rolls	40 mm x 50 m	45 – 55 mm

TOOLS FOR THE APPLICATION OF SKIRTINGS

Toptac Applicator

Suitable for fast and precise application of Toptac

- Quick application of Toptac

APPLICATIONS:

- Special development for Toptac skirting tape

PROPERTIES:

- Strong, precision equipment



Packsize	Shipping Unit / Pallet	Weight
1 piece	–	1,8 kg

Contact / Bullran Applicator

Suitable for fast and precise application of Contact / Bullran onto carpet skirtings

- During application, the Contact and Bullran are pressed into the structure of the carpet backing and consistent adhesion is produced

APPLICATIONS:

- Onto carpet backings

PROPERTIES:

- Equipment made from cast aluminium with powder coating



Packsize	Shipping Unit / Pallet	Weight
1 piece	–	8,0 kg

ADHESIVES FOR STAIR COVERINGS

Special adhesive system for the staircase area

Steptec

Secure gluing of floor coverings to steps

- For textile, linoleum, PVC and CV coverings
- On substrates with up to 1 mm structure height

APPLICATIONS:

- Dry adhesive system for the installation of textile and elastic floor coverings on stair cases

PROPERTIES:

- Staircase remains accessible at all times
- 3 – 5 times faster
- No need for contact adhesive
- Clean indoor air
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Dimensions
1 roll	140	220 mm x 25 m
1 roll	210	150 mm x 25 m

ADHESIVES FOR SKIRTINGS AND COVING

Remur 45, 55, 95

Special Tape System for PVC Skirting



- For PVC and CV skirting installation
- On smooth substrates

APPLICATIONS:

- Metal-reinforced special system for the dimensionally stable installation of rigid and flexible PVC and CV skirting on smooth substrates.
- Quick and clean working without solvents

PROPERTIES:

- Dimensionally stable
- Avoids use of contact adhesive
- No prior fitting and priming
- 3 – 5 times faster
- Will not dry out or become brittle
- Interior use
- Solvent-free

Packsize	Shipping Unit / Pallet	Dimensions	Base height
4 rolls	60 units / 240 rolls	45 mm x 50 m	50 – 60 mm
4 rolls	60 units / 240 rolls	55 mm x 50 m	60 – 70 mm
2 rolls	60 units / 120 rolls	95 mm x 50 m	100 – 110 mm

WOLFF Stair iron with roll



Usefull tool to apply Remur properly onto the wall or onto the floor

APPLICATIONS:

- For the proper instalation of Remur or skirtings

PROPERTIES:

- Strong, precision equipment

Packsize	Weight
1 piece	0.7 kg

Goman 50, 90, 240

Special tape for rubber skirting



- For rubber skirting boards
- On substrates up to 1 mm structure

APPLICATIONS:

- Installation of rubber baseboards, rubber stair angle, molded rubber base (for the bottom part), form-base corner units in projects like hospitals and retirement homes

PROPERTIES:

- Avoids use of solvent based contact adhesives
- Clean indoor air
- 3 – 5 times faster
- No prior fitting and priming
- Interior use
- Solvent-free

Packsize	Shipping Unit / Pallet	Dimensions	Base height
4 rolls	60 units / 240 rolls	50 mm x 50 m	55 – 60 mm
2 rolls	60 units / 120 units	90 mm x 50 m	
1 roll	30 boxes / 120 units	240 mm x 50 m	

Wood Flooring Installation



The brief descriptions of products should only be used as a guide.
Detailed product data sheets for all products are available which should be used as reference when using the products.

1-COMPONENT STP-ADHESIVES

UZIN MK 200 PLUS

1-Component Premium STP Wood Flooring Adhesive

Performing time-consuming wood flooring installation work technically perfect

Hard elastic adhesive for wood flooring with tongue and groove joints with long working time

- Long working time facilitates the installation of time-consuming installation patterns or room sections
- High filling strength and suction adhesion in combination with long working time support reliable installation of large-format wood flooring elements

MAIN AREA OF APPLICATION:

- Multi-ply wood flooring

EXTENDED AREA OF APPLICATION:

- Wood block flooring
- Solid wood flooring 15 – 22 mm
- Multi-ply wooden flooring

PROPERTIES:

- Excellent ridge formation
- Rapid grab
- Long working time
- Hard elastic adhesive in accordance with ISO 17 178
- Adhesive residues on wood flooring can be removed
- Interior use
- Solvent-free



Packsizes	Shipping Unit / Pallet	Consumption	Colour
16 kg bucket	33	1000 – 1200 g/m² / B11 for solid boards obtain technical advice	beige

UZIN MK 200 PLUS in practice



UZIN MK 200 PLUS supports in the difficult installation of solid and multi-ply wooden flooring with a long open time and high filling capacity. Hard, shear-resistant adhesive ridges limited wood deformations and produces a visually sophisticated appearance.

2-COMPONENT PUR-ADHESIVES

2-Component PUR Wood Flooring Adhesive

UZIN MK 92 S

Fast adhesion of wood flooring with no swelling

Hard, shear-resistant and quick-setting universal adhesive for all types of wood flooring

- For all types of wood flooring and laminates, universal applications

MAIN AREA OF APPLICATION:

- Mosaik wood flooring (8 mm solid wood flooring)
- Edge-laid strips
- Wood block flooring
- Solid wooden flooring
- 10 mm solid wood flooring
- End grain RE / WE

EXTENDED AREA OF APPLICATION:

- Multiply wood flooring
- Laminate

PROPERTIES:

- Universal use
- Excellent ridge formation
- Rapid setting
- Hard adhesive in accordance with ISO 17 178
- Harmonises with all wood flooring lacquers, oil / waxes
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Colour
A/B 5,6 kg combi-can	108	1000 – 1200 g/m² / B11	beige

2-Component PUR Wood Flooring Adhesive

UZIN MK 92 S dark

Adhesion of dark types of wood universally and quickly

Hard, shear-resistant and quick-setting universal adhesive for dark types of wood

- Gives visual advantages by matching adhesive joints / wood

MAIN AREA OF APPLICATION:

- Exotic woods, dark woods
- Mosaik wood flooring (8 mm solid wood flooring)
- Edge-laid strips
- Wood block flooring,
- Solid wooden flooring
- 10 mm solid wood flooring
- End grain RE / WE

EXTENDED AREA OF APPLICATION:

- Multiply wood flooring / wooden flooring

PROPERTIES:

- Universal use
- Excellent ridge formation
- Rapid setting
- Hard adhesive in accordance with ISO 17 178
- Harmonises with all wood flooring lacquers, oil / waxes
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Colour
A/B 5,6 kg combi-can	39	1000 – 1200 g/m² / B11	dark brown

1-COMPONENT REACTION RESIN PRIMER

UZIN PE 414 Turbo 1-Component PUR Rapid Primer

Quick
drying

Fast and reliable priming

One-component reaction resin primer for wood flooring and floor covering work

- No mixing, fast, high coverage and reliable

APPLICATIONS:

- For priming under reaction resin wood flooring adhesives
- On cement- or calcium sulphate-screeds, concrete, etc.
- On existing surfaces, e.g. well-bonded adhesive residues
- As a barrier against moisture on moisture-resistant surfaces
- For smoothing compounds when grit-binding with UZIN Quartz Sand 0.8

PROPERTIES:

- Rapid drying
- Thin consistency
- Good penetration
- Neutral odour
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Colour
12 kg canister	60	80 – 150 g/m² per layer	brown
6 kg canister	60		brown

UZIN PE 414 Turbo in practice



Applied with the UZIN nylon fibre roller you will achieve a fully covered and uniform layer.

Adhesive / Substrate	Curing times
Before direct bonding with UZIN MK 92 S	> 2 hours
Before direct bonding with UZIN MK 200 PLUS	> 12 hours
On poured asphalt screeds in general	> 12 hours

What is special about UZIN PE 414 Turbo?

UZIN PE 414 Turbo is easy to apply, has one component, acts as a barrier and provides security not only before laying wood flooring. Even before levelling work, the 1-component PUR rapid primer provides a firm support, for example as a barrier primer for other floor coverings.

2-COMPONENT EPOXY PRIMER-SEALER / SPECIAL ADHESIVE

2-Component Epoxy Primer-Sealer

UZIN PE 460

A reliable barrier against residual moisture

Epoxy primer for damp or weak surfaces

- Allows fast installation on cement-based surfaces, reducing waiting time and costs

DRYING TIMES:

- Foot traffic / further coating: approx. 8 hours
- Final strength: 3 – 5 days

APPLICATIONS:

- For mineral levelling compounds and mortars
- As a barrier against moisture up to 6 – 7 CM-%
- For surface hardening of "worn out" screeds
- On moisture-resistant substrates requiring renovation

PROPERTIES:

- Approx. 20 % faster cure
- Reduced odour during application
- System component in PAH decontamination
- Interior and exterior use
- Solvent-free



Packsize	Pack. Unit/Pallet	Consumption	Colour
10 kg + 5 kg combi-can	18	200 – 400 g/m ²	yellowish transparent
4 kg + 2 kg combi-can	36		

1-Component PUR Injection Adhesive

UZIN RK 37

Repairs hollow-spots in wood flooring

Hard, shear-resistant and quick-setting universal adhesive for repair work

- Eliminates hollow-spots in installed wood flooring, avoids possible claims

MAIN AREA OF APPLICATION:

- To eliminate loose and hollow sections
- To bond individual pieces of wood flooring
- Spot-bonding of floating floor materials

PROPERTIES:

- One-component and ready to use
- Good penetration and wetting properties
- Fills hollow sections
- Interior use
- Solvent-free



Packsize	Shipping Unit / Pallet	Consumption	Colour
250 gr bottle	–	–	yellowish / transparent



The brief descriptions of products should only be used as a guide.
Detailed product data sheets for all products are available which should be used as reference when using the products.

Self-Adhesive

UZIN Conductive Copper-Strip

Self-adhesive copper-strip for conductive flooring constructions

- Self-adhesive, therefore easy to install

APPLICATIONS:

- For all types of conductive installations

PROPERTIES:

- 10 mm wide, 0.035 mm thick



Packsize	Shipping Unit / Pallet	Consumption	Colour
2 rolls each 20 lin.m	–	–	copper colour

Screed Anchors

Corrugated, stainless steel clamps for strong stitch-bonding of screed cracks and joints

- Ideal for stitch-bonding screed bays

APPLICATIONS:

- For resin-bonding of joints and cracks
- For joining separate screed sections

PROPERTIES:

- Will not rust, 6 x 70 mm
- Corrugated for ideal fixing



Packsize	Shipping Unit / Pallet	Consumption	Colour
100 pieces	–	approx. 3 – 5 per lin. m.	stainless steel

UZIN Foam Expansion Strip B

Self-adhesive PE expansion strip with base; 5 mm thick and 50 mm high

- The self-adhesive base and the integrated fleece backing which presses the strip to the wall in a „spring-like“ manner ensure clean execution without any annoying adhesive residues on the wall

APPLICATIONS:

- For the mechanical separation between floor and wall prior to application of levelling compounds or thin screeds

PROPERTIES:

- Positively prevents acoustic bridges
- Perfect for thin screeds and smoothing compounds
- High adhesive strength
- Height 50 mm, thickness 5 mm



Packsize	Shipping Unit / Pallet	Consumption	Colour
1 roll / 20 lin.m	–	–	blue

Cleaning Cloths

UZIN Clean-Box

Highly effective cleaning cloths for removing adhesive residues from surfaces, hands and tools

APPLICATIONS:

- Removes both fresh and dried 1-component PUR and STP adhesive residues
- Removes fresh to slightly dried 2-component PUR and epoxy resin adhesive residues


PROPERTIES:

- Dries quickly with no residue
- Multipurpose applications
- Especially kind to skin
- Economical in use



Packsize	Shipping Unit / Pallet	Shelf Life	Colour
1 drum each 72 cloths	–	min. 24 months	green

UZIN Mixing Accessory



Mixers for blending UZIN primers, levelling compounds and adhesives

- 1. spiral whisk: special mixer attachment for 2-component reaction resin products
- 2. levelling compound mixer: special mixer attachment for UZIN levelling compounds

APPLICATIONS:

- For drill-chucks with min. 13 mm Ø

PROPERTIES:

- Fast and homogeneous mixing of all materials

Item	Shipping Unit / Pallet	Colour
Spiral Whisk	–	silver
Levelling Compound Mixer	–	silver

UZIN Mixing Bucket



Strong plastic bucket with handle-grips for mixing all types of UZIN powder products

- Correct size and strength = easy handling

APPLICATIONS:

- For mixing of UZIN levelling compounds
- For PUR and epoxy smoothing compounds or mortar

PROPERTIES:

- Strong construction
- Ideal for 25 kg powder products

Packsize	Shipping Unit / Pallet	Colour
1 bucket with 30 litre capacity	66	blue

Power X 1300



1260 Watt 2-speed gear mixer with speed control and speed lock

- For mixing viscous mortar (e.g. screed, tile adhesive)
- Solid-shaft electronics: Soft-start, temperature control, overload protection
- Variable speed control through throttle switch

INCLUDES:

Power X 1300, Stirrer type KR 120 S/M14

Artikel
Power X 1300

Screed Rake



Special stainless-steel tool for application of UZIN levelling compounds

- Improves the surface results of levelling and smoothing work

APPLICATIONS:

- For easy application of UZIN levelling compounds
- For 3 mm thickness using the attached R2 notched blade 55 cm wide

PROPERTIES:

- With handle-holder and screw-attached blade-clamp

Item	Shipping Unit / Pallet
Screed Rake	–

Large Surface Rake

Special tool from stainless steel for the application of UZIN levelling compounds with thick layers

- Uniform thickness with smoothing work through adjustable bases

APPLICATIONS:

- For thicknesses from 6 – 22 mm infinitely variable, with 80 cm width
- Ideal when pumping levelling compound for thick layers

PROPERTIES:

- Sturdy design, partially from stainless steel



Item	Shipping Unit / Pallet
Large Surface Rake	–

Spike Roller

For removing air and improving flow in freshly applied levelling compounds

- Improves the flow of self-levelling compounds, increases customer satisfaction

APPLICATIONS:

- Use the correct roller according to application thickness
- For the best surface finish results
- Essential when pump-applying levelling compounds

PROPERTIES:

- Strong metal / plastic construction
- Easy to clean



Article No.	Shipping Unit / Pallet
Spike roller 25 cm / 11 mm	–
Spike roller 25 cm / 21 mm	–
Spike roller 25 cm / 31 mm	–
Spike roller 50 cm / 11 mm	–
Spike roller 50 cm / 21 mm	–
Spike roller 50 cm / 31 mm	–

Spike Shoes

Spike shoes for walking through freshly applied UZIN levelling compounds

- Essential requirement for the best surface finish results when applying levelling compounds in larger areas

APPLICATIONS:

- For rake-application of levelling compounds

PROPERTIES:

- Strong construction



Item	Shipping Unit / Pallet
Spike Shoes	–

Adhesive Trowel

Ergo-Star

Ergonomically shaped adhesive trowel for the application of UZIN adhesives

- Correct shape and size = the easiest and non-tiring application work

APPLICATIONS:

- For the effortless application of UZIN adhesives

PROPERTIES:

- Ergonomic and strong construction



Width	Shipping Unit / Pallet
21 cm	–
28 cm	–

Trowel Blades



Item	Packsize
Notch A1, 21 cm	10
Notch A1, 28 cm	10
Notch A2, 21 cm	10
Notch A2, 28 cm	10
Notch A3, 21 cm	10
Notch A3, 28 cm	10
Notch A4, 21 cm	10
Notch A4, 28 cm	10
Notch A5, 21 cm	10
Notch A5, 28 cm	10
Notch B1, 21 cm	10
Notch B1, 28 cm	10
Notch B2, 21 cm	10
Notch B2, 28 cm	10
Notch B3, 21 cm	10
Notch B3, 28 cm	10
Notch B11, 21 cm	10
Notch B11, 28 cm	10
Notch R1, 56 cm	10
Notch R2, 56 cm	10

Hygrometer Universal V1-D4



Designed for moisture measurement of subfloors

- Non-invasive moisture test method with high measuring accuracy
- Real-time display of measurements on easy to read display
- Suitable for preliminary checks to determine the dryness of materials
- For CM and RH measurements
- RF-Measurement possible by additional air sensor

Item

Hygrometer Universal V1-D4

Service



CONTACT ADDRESSES WORLDWIDE

SUBFLOOR CONSTRUCTION

SUBFLOOR PREPARATION


FLOOR COVERING ADHESIVES

switchTec®

WOOD FLOORING INSTALLATION

ACCESSORIES | TOOLS

SERVICE



Australia
UFLOOR Systems NZ Ltd.
PO Box 426 – Whangaparaoa 0943
Telephone +64 21 933780
Telefax +64 9 4240366
E-mail info@ufloor-systems.net



Azerbaijan
Uzin Utz AG
Dieselstrasse 3
Germany, 89079 Ulm
Telephone +49 731 4097 205
Telefax +49 731 4097 107
E-mail boris.schulmann@uzin-utz.com
E-mail biuro@uzin-utz.com



Republik Belarus
Representative Office Uzin Utz AG
220035 Minsk
Cimirazieva Strasse 67, Office 932
Postfach 121
Telephone +375 (17) 235 00 50
Telefax +375 (17) 235 00 50
Mobil +375 (29) 655 56 26
Email ivan.rak@uzin-utz.com



Belgium
Unipro België n.v.
Poortakkerstraat 41a
B-9051 Gent
Telephone +32 9 2225848
Telefax +32 9 222 3380
E-mail info@unipro.be



China
Uzin Utz Construction
Materials (Shanghai) Co. Ltd.
N° 3968 Huguiping Highway
Zhaoxiang – District Qingpu
Shanghai 201703
Telephone +86 21 5975 8220
Telefax +86 21 5975 8695
E-mail info@uzin.com.cn



Croatia
Unikem d.o.o.
Trgovačka 6
CMP, Savica-Šanci
HR-10000 Zagreb
Telephone +385 1 2498214
Telefax +385 1 2498215
E-mail info@unikem.hr



Cyprus
IDS – Interior Design Services
Total Solution Contract
197 Old Nicosia
Limassol Road P.O. Box 11107
Nicosia
Telephone +357 22461133
Telefax +357 22610020
E-mail idsids@cytanet.com.cy



Czech Republic
Uzin s.r.o.
Českomoravská 12a
CZ-19000 Praha 9
Telephone +420 2 8308 3314
Telefax +420 2 8308 3419
E-mail info@uzin.cz



Denmark
Uzin Utz Denmark ApS
Kongelundsvej 294
2770 Kastrup
Telephone +45 40 88 94 92
E-mail info@uzin.dk



Finland
Betton Oy
Falläker 1 D
FI-02740 Espoo
Telephone +358 9 5102 517
E-mail info@betton.fi
Internet www.betton.fi




France
Uzin France SAS
6 avenue du Professeur
André Lemierre
F-75980 Paris Cedex 20
Telephone +33 1 41632720
Telefax +33 1 41632721
E-mail info@uzin.fr




Germany
Uzin Utz AG
Dieselstrasse 3
D-89079 Ulm
Telephone +49 731 4097 0
Telefax +49 731 4097 110
E-mail info@uzin-utz.com



Greece
Uzin Hellas
Polychimiki G. Matziaris S.A.
14 km National Road
Thessaloniki-Veria
GR-57011 N. Anchialos
Telephone +30 2310 7229 912
Telefax +30 2310 7225 71
E-mail uzin@otenet.gr



 **Hungary**
Uzin Utz
Magyarország Kft.
Újhegyi út 14
H-1108 Budapest
Telephone +36 1 431 9422
Telefax +36 1 431 9423
E-mail info-hungary@uzin-utz.com

 **Iceland**
Alfaborg ehf
Skútuvogi 6
104 Reykjavík
Telephone +354 568 6755
Telefax +354 568 1277
E-mail alfaborg@alfaborg.is

 **Indonesia**
PT Uzin Utz
Plaza Pasifik B2 No. 32
Kelapa Gading
ID – Jakarta 14240
Telephone +62 21 4587 6116
Telefax +62 21 4587 6115
E-mail sugi_wei@yahoo.com

 **Italy**
Uzin Utz AG - Filiale Italia
Luigi Riccio
Via Francesco Solimena, 155
IT-80129 Napoli
Telephone +39 348 3255 509
E-mail info.italia@uzin-utz.com

 **Lithuania**
UZIN Representative Office in Baltic
Architektu str. 64A-19
04110 Vilnius Lithuania
Telephone +370 52 483788
Telefax +370 52 483788
Mobil +370 617 39271
Mobil +48 607 419 907
E-mail jaroslaw.baum@uzin-utz.com

 **Malta**
de Valier Co. Ltd.
Fairline Centre – St. Marta Street
Victoria Gozo – VCT 2552
Telephone +356/21/556694
Telefax +356/21/554175
E-mail info@devalier.com.mt

 **Netherlands**
Unipro B.V.
Bouwstraat 18
7483 PA HAAKSBERGEN
Telephone: +31 (0)53 5737373
Telefax: +31 (0)53 5737333
E-mail: info@uzin.nl

 **New Zealand**
UFLOOR Systems NZ Ltd.
PO Box 426 – Whangaparaoa 0943
Telephone +64 21 933780
Telefax +64 9 4240366
E-mail info@ufloor-systems.net


 **Norway**
Uzin Utz Group Norge AS
Elveveien 34 – bygg 4
N-3262 Larvik
Telephone +47 35 50 64 00
Internet www.uzin.no


 **Poland**
Uzin Polska Sp.z o.o.
ul. Jaworzyńska 287
PL-59-220 Legnica
Telephone +48 76 723 9150
Telefax +48 76 723 9151
E-mail biuro@uzin-utz.com

 **Russia**
Uzin Utz AG
Dieselstrasse 3
Germany, 89079 Ulm
Telephone +49 731 4097 205
Telefax +49 731 4097 107
E-mail boris.schulmann@uzin-utz.com
E-mail biuro@uzin-utz.com

 **Serbia**
Unihem Trading d.o.o.
Kumodraška 257
11050 BEOGRAD
Telephone +381 11 3989 044
Telefax +381 11 3989 088
E-mail office@unihem.rs

 **Slovakia**
HA-UZ market s.r.o.
Štrková ulica č. 94
SK-01001 Žilina
Telephone +421 41565 1794
Telefax +421 41500 6014
E-mail ha-uz@za.psg.sk

 **Slovenia**
Unihem d.o.o.
Kajakaska c.30
SLO-1211 Ljubljana
Telephone +386 1 511 0200
Telefax +386 1 5116290
E-mail prodaja@unihem.si

 **South Africa**
Contract Flooring Distribution (Pty) Ltd.
22 Dublin Road
Brabley View Ext 6
Johannesburg 2090
Telephone +27 11 882 1000
Telefax +27 11 882 5403
E-mail info@cfdflooring.co.za

 **Spain**
Laboratorios Rayt S.A.
Garriga, 188-200 P.O.Box 39
E-08910 Badalona
Telephone +34 93 460 7820
Telefax +34 93 383 6356
E-mail info@rayt.com

 **Sweden**
Englund-Gruppen Sverige
Kryptogatan 20
S-43153 Mölndal
Telephone +46 31 670170
Telefax +46 31 871 678
E-mail stefan.englund@englund-gruppen.se

 **Switzerland**
Uzin Tyro AG
Ennetbürgerstr. 47
CH-6374 Buochs
Telephone +41 41 624 4888
Telefax +41 41 624 4889
E-mail info@uzin-tyro.ch

 **Turkey**
DENLAKS Adhesives
Cihangir Mash. Güvercin Cad. No:11
Haramidere
Avcılar 34310 Istanbul
Telephone +90 212 4221100
Telefax +90 212 4221099

 **United Kingdom**
Uzin Ltd.
Unit 2, Mitchell Court
Central Park, Rugby
Warwickshire, CV23 0UY
Telephone +44 1788 530 080
Telefax +44 1788 536 508
E-mail info@uzin.co.uk

 **Ukraine**
UZIN Representative Office
Dr. Yuri Rudchenko
DIC, 43, Borodinskaya St.
49029 Dnepropetrovsk, Ukraine
Telephone +38 056 744 8843
Telefax +38 056 448843
E-mail uzinua@i.ua

 **USA & Canada**
UFLOOR Systems Inc.
14509 E; 33rd Place
Unit G
Aurora, CO 80011
Telephone +1 720 374 4810
Telefax +1 720 374 2113
E-mail info@ufloorsystems.com

All other countries:
Uzin Utz AG
Dieselstrasse 3, D-89079 Ulm
Telephone +49 731 4097 0
Telefax +49 731 4097 110
Internet www.uzin.com

BUSINESS IN ASIA | PACIFIC

Stephan Bayer

General Manager Uzin Utz Construction Materials (Shanghai) Co. Ltd.

Uzin Utz AG | A Company of Uzin Utz Group

Dieselstrasse 3 | D-89079 Ulm,

Mobile China: +86 1582173 4778 | Mobile Germany +49 (0)160 3642 176

Telephone China: +86 21 5975 78110 | Telephone Germany: +49 (0)731 4097 427

Telefax Germany: +49 (0)731 4097 45427

E-Mail: stephan.bayer@uzin-utz.com

Responsibilities:

Overall management of business of China and Asia Pacific Region

Based in Germany and Shanghai

SALES IN CHINA | ASIA

Adam Huang

Sales Director

Uzin Utz Construction Materials (Shanghai) Co. Ltd.

No. 3968 Huqingping Road, Shanghai, China

Mobile: +86 136 0166 8866

Telephone: +86 21 5975 7890 106

Fax: +86 21 59757888

E-Mail: adam.huang@uzin.com.cn

Responsibilities:

In charge of Sales in China and Asia delivered from Uzin China. Customer service, price enquiries, product enquiries, shipments, payments, technical services and all other issues.

Based in Shanghai

SALES IN ASIA

Steffen Battran

Export Manager Asia

Uzin Utz Construction Materials (Shanghai) Co. Ltd.

No. 3968 Huqingping Road, Shanghai, China

Mobile: +86 136 6179 4991

Telephone: +86 21 5975 7890 104

Fax: +86 21 5975 7888

E-Mail: steffen.battran@uzin-utz.com

Responsibilities:

In charge of Sales and Marketing in Asia. Enquiries for products delivered from Germany and China, including Pallmann & WOLFF products.

Based in Shanghai

TECHNICAL SUPPORT

Frank Zaumsegel

Technical Customer Service Export

Uzin Utz AG | A Company of Uzin Utz Group

Mobile: +49 (0)160 3642 150

Telephone: +49 (0)731 4097 126

Fax: +49 (0)3661 4522 96

E-Mail: frank.zaumsegel@ufloorsystems.com

Responsibilities:

Technical support and technical sales for all products including WOLFF & Pallmann products.

Recommendations and solutions for projects and applications.

Based in Germany

WE LIVE FLOORS! STRONG BRANDS FOR STRONG WORKMANSHIP.

Uzin Utz AG is a company that essentially incorporates a whole wealth of flooring skills.

With the brands UZIN, WOLFF and PALLMANN we offer an extensive range of products, systems and services to our Asian customers. We encompass anything and everything to do with the installation, renovation and maintainance of all types of floor covering and wood flooring.

For all questions concerning flooring we are a competent and reliable partner.



UZIN. The floor belongs to you.

Installation systems for screeds, flooring and wood flooring.



WOLFF. Going beyond your limits.

Machinery and special tools for substrate preparation and installation of floor coverings.



PALLMANN.

Complete product range for the installation, renovation and maintenance of wood flooring.

UZIN | A Brand of Uzin Utz AG

Uzin Utz AG | Dieselstrasse 3 | D-89079 Ulm
Telephone +49 (0)731 4097-0 | Telefax +49 (0)731 4097-110
E-mail info@uzin.com | Internet www.uzin.com

Uzin Utz Construction Materials (Shanghai) Co.,Ltd.
3968 Huqingping Rd. | Shanghai 201703 | P.R.C
Telephone +86 21 5975 7890
E-mail info@uzin.com.cn | Internet www.uzin.com.cn