

IMS Version 9 Implementation Guide:

A Technical Overview

Get familiar with the HALDB online reorganization feature

See the possibilities of these new technologies - IMS Java and XML

Explore all the new features of IMS Version 9

Jouko Jäntti Yukari Andoh Knut Kubein Rich Lewis Geoff Nicholls Dave Viguers Suzie Wendler

Redbooks

ibm.com/redbooks



International Technical Support Organization

IMS Version 9 Implementation Guide: A Technical Overview

December 2004

Note: Before using this information and the product it supports, read the information in "Notices" on page xi.

First Edition (December 2004)

This edition applies to IMS Version 9 or later (program number 5655-J38) for use with the z/OS operating system.

Note: This book is based on a pre-GA version of a product and may not apply when the product becomes generally available. We recommend that you consult the product documentation or follow-on versions of this redbook for more current information.

© Copyright International Business Machines Corporation 2004. All rights reserved.

Note to U.S. Government Users Restricted Rights -- Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Notices	
Trademarks	. xii
Summary of changes	xiii
November 2004, First Edition.	xiii
November 2005, First Update	xiii
Preface	V.V
The team that wrote this redbook.	
Become a published author	
Comments welcome.	
Chapter 1. Introduction	
1.1 Leading the industry	
1.1.1 Unsurpassed performance	
1.2 IMS Version 9 highlights	
1.3 IMS Database Manager enhancements	
1.4 IMS Transaction Manager enhancements	
1.5 IMS system manageability enhancements	. 7
Chapter 2. Product packaging, installation and resource definition enhancements .	. 9
2.1 Product packaging	
2.2 Resource definition and installation changes	11
2.2.1 Shared SDFSRESL for different configurations and system definitions	
2.2.2 DBRC keyword ignored in the system definition	14
2.2.3 Removing conditional link-edit for online change modules	15
2.2.4 ETO feature checking	
2.2.5 Dynamic update of DBRC type 4 SVC	16
2.2.6 Replacing DFSMRCL0 by new resource cleanup services	17
2.3 IMS Application Menu	
2.4 Installation verification program (IVP) enhancements	
2.4.1 IVP sub-options with IMS Version 9	
2.4.2 The new "E" IVP steps	
2.4.3 The new "O" IVP steps	
2.4.4 The new "P" IVP steps	
2.4.5 DFSIVPEX IVP utility to export and import the variables	
2.4.6 IVP help text enhancements	
2.4.7 JES3 improvements in IVP	
2.4.8 IVP data set allocation enhancements	
2.4.9 IVP enhanced dump formatter setup	
2.4.10 Miscellaneous IVP changes 2.5 Syntax Checker enhancements	
2.6 Documentation changes	
2.6.1 IMS Information Center	
	_,
Chapter 3. Integrated HALDB online reorganization	
3.1 Overview of integrated HALDB online reorganization	
3.2 Details of OLR processing	
3.2.1 Data sets used by OLR	32

3.2.	.2 Reorganization by copying segments	 33
	.3 Current position during a reorganization - the cursor	
	.4 Application access during OLR	
	.5 Completion of reorganization	
	etting up for OLR	
	.1 DBRC setup	
	.2 Output data set creation	
	arting online reorganization	
	.1 Initiation	
	eorganization process	
	ormal termination and cleanup	
	ausing an online reorganization	
3.8 OL	_R commands	 39
3.8.	.1 Start an online reorganization	 39
3.8.	.2 Modify a reorganization in progress	 40
3.8.	.3 Terminate an online reorganization.	 40
3.8.	.4 Display reorganizations in progress	 41
	.5 Database commands	
	ogging, operations, I/O errors and restart	
	.1 Logging	
	.2 IMS normal termination and restart.	
	.3 I/O errors	
	4 Resuming online reorganization	
	5 IMS or z/OS failure	
	.6 FDBR with OLR	
	Jtilities	
	0.1 Image copy	
3.10	0.2 Change accumulation	 46
3.10	0.3 Database recovery	 46
3.10	0.4 Batch backout	 48
3.10	0.5 HD Unload and HD Reload	 48
3.11 🛙	DBRC changes for OLR	 48
	1.1 RECON records	
	1.2 DBRC commands	
	1.3 OLR coexistence with IMS Version 7 and IMS Version 8	
	Data sharing, FDBR, RSR, and XRF	
	2.1 Data sharing support	
	2.2 FDBR support	
	2.3 XRF support	
	2.4 RSR support	
	DLR performance	
	3.1 OSAM sequential buffering	
	3.2 Logging	
	3.3 Lock contention	
3.13	3.4 Buffer pool definitions	 54
3.10	3.5 Buffer contention	 55
3.10	3.6 DASD contention	 55
3.13	3.7 Pacing	 55
	3.8 TCBs used by OLR	
	3.9 Executing OLR in a sysplex	
	3.10 CPU use with OLR	
5.10		
Chapte	er 4. Fast Path enhancements in IMS Version 9	 57


4.1 Fast Path multi-area structures for SVSO	58
4.1.1 Single area structures	58
4.1.2 Multiple area structures	59
4.1.3 Multiple area structures additional considerations	
4.1.4 System managed duplexing versus IMS managed duplexing	
4.1.5 Failures without successful duplexing	63
4.2 Area open and close enhancements	64
4.3 Optional EMHQ structure for shared queues	67
4.4 Fast Path serviceability and usability enhancements	68
Chapter 5. DBRC enhancements	
5.1 DBRC application programming interface	
5.1.1 Application overview	
5.2 DBRC functional enhancements	
5.2.1 Command authorization for /RMxxxx	
5.3 More than 32K database registrations	
5.4 GENJCL.IC for HALDB	
5.5 DBRC migration and coexistence	
5.5.1 HALDB OLR coexistence	
5.5.2 DEDB shared VSO multiple area structures	
5.5.3 MINVERS format change	
5.5.4 DSPSLDRC eliminated	83
Chapter 6. Security considerations with IMS Version 9	85
6.1 Overview of security enhancements	
6.2 Resource access security (RAS)	
6.2.1 RAS and APSB security	
6.2.2 RAS migration examples.	
6.3 AOI security	
6.3.1 SAF support for type 1 AOI (CMD)	
6.3.2 SAF support for type 2 AOI (ICMD)	
6.3.3 SAF support for time controlled operations (TCO)	
6.3.4 Resource authorization	
6.4 MSC link security	
6.4.1 IMS Version 9 MSC security considerations	
6.5 /LOCK, /UNLOCK and /SET commands	
6.6 Signon verification security	
6.6.1 Sign on for static terminals	
6.6.2 Security level (SECLVL)	
6.6.3 SMU terminal (TERMNL) security	
6.6.4 SMU)(SIGN and STERM statements	
6.6.5 IMS Version 9 sign on security for static terminals	
6.6.6 New keywords on the OPTIONS statement	
6.6.7 Static terminal sign on security migration considerations	
6.7 LTERM-based terminal security	
6.7.1 Migration considerations for LTERM-based terminal security.	. 105
6.7.2 IMS commands	. 106
6.7.3 IMS transactions	. 108
6.7.4 Migration considerations for LTERM-based security	. 108
6.8 Additional migration considerations	. 110
6.8.1 Performance considerations	. 111
6.8.2 AOI considerations	. 111
6.8.3 User exit interface changes	. 112

6.8.4 SMU to RACF migration check list	112
Chapter 7. Type-2 commands and enhanced command environment	115
7.1 Type-2 command enhancements in IMS Version 9	
7.2 Type-2 database commands.	
7.2.1 QUERY DB command.	
7.2.2 QUERY AREA command	
7.2.3 UPDATE DB command.	
7.2.4 UPDATE AREA command	
7.2.5 UPDATE DATAGRP command	
7.2.6 Command security	
7.2.7 Log records	
7.2.8 Summary of the command enhancements	
7.3 Enhanced command environment	
7.3.1 IMS Version 8 Common Service Layer components	
7.3.2 IMS Version 9 Common Service Layer components	
7.3.3 CSL functions and requirements summary	
7.3.4 CSL start up options and implementation	
7.3.5 Online change alternatives	
7.3.6 Global online change	
7.3.7 OM security user exit	
7.3.8 Migration to OM	
7.3.9 Migrating from non-IMSplex to IMSplex with RMENV=N	
7.3.10 Migrating from RMENV=N to RMENV=Y	
7.3.11 Enhanced command environment summary.	
Chapter 8. Integrated IMS Connect support	135
8.1 IMS Connect overview	
8.1.1 IMS Connect enhancements in IMS Version 9	136
8.2 IMS Connect clients	137
8.3 IMS Connector for Java client overview	138
8.3.1 IMS Connector for Java functions	139
8.3.2 IMS Connector for Java clients	139
8.4 IMS transactions as Enterprise Service applications	140
8.5 IMS Enterprise Service component.	140
8.5.1 Interface WSDL	141
8.5.2 Binding WSDL	142
8.5.3 Service WSDL.	142
8.6 MFS-based transaction as Enterprise Service application	142
8.6.1 MFS Web Services Importer	142
8.6.2 MFS Web Services Adapter	
Chapter 9. XML storage in IMS databases	
9.1 IMS Version 9 XML database	
9.1.1 Storing XML information in IMS databases	
9.2 XML database overview	
9.2.1 XML schema definition language	
9.2.2 Decomposed storage	
9.2.3 Intact storage	
9.2.4 DLIModel Utility	153
9.3 JDBC interface	155
9.4 XML database summary	157
Chapter 10. IMS Java enhancements	159

10.1 IMS Java environment overview	. 160
10.2 IMS and DB2 interoperability	. 161
10.2.1 Setting up the IMS to DB2 connection using RRSAF	. 161
10.2.2 Accessing DB2 UDB for z/OS databases from JMP or JBP applications	. 162
10.3 IMS Java symbolic checkpoint and restart for JBP	. 163
10.3.1 Checkpoint call formats	. 163
10.3.2 Restart call formats	. 164
10.4 IMS Java GSAM support for JBP applications	. 166
10.5 Java-COBOL interoperability	
10.5.1 Enterprise COBOL as a back-end application in a JMP or JBP region	
10.5.2 Enterprise COBOL as a front-end application in a JMP or JBP region	
10.6 JDBC and SQL enhancement.	
10.6.1 JDBC enhancement	. 168
10.6.2 SQL enhancement	
10.6.3 SQL syntax enhancement.	
10.7 Remote database services	
10.7.1 Remote database services components.	
10.7.2 Security	
10.7.3 Installation steps	
Chapter 11. Knowledge Based Log Analysis (KBLA)	. 179
11.1 Overview of KBLA.	
11.2 Invoking KBLA	. 180
11.2.1 KBLA task selection 1 - IMS Log Utilities	
11.2.2 KBLA task selection 2 - IMS Log Formatting	. 185
11.2.3 KBLA task selection 4 - IMS Knowledge Based Analysis	
11.2.4 IMS KBLA - Log Data Set Analysis.	
11.2.5 KBLA MSC Link Performance Formatting.	
11.2.6 KBLA Statistic Log Record Analysis	
11.2.7 KBLA trace entry filtering	
11.2.8 KBLA IRLM Lock Trace Analysis	
11.2.9 KBLA DBCTL Transaction Analysis	
	. 100
Chapter 12. Miscellaneous enhancements in IMS Version 9	. 199
12.1 Miscellaneous Database Manager enhancements	
12.1.1 Parallel full function database open option	
12.1.2 Miscellaneous HALDB enhancements	
12.1.3 Improved message with DB abends	
12.1.4 Greater than 32K tape block size for image copies	
12.2 Miscellaneous Transaction Manager enhancements	
12.2.1 OTMA and APPC /EXIT command support	
12.2.2 Message level ACEE aging value for OTMA	
12.2.3 OTMA trace table enhancement.	
12.2.4 DFSYPRX0 pre-routing exit	
12.2.5 Input message ZZ protection for OTMA	
12.2.6 APPCIOT= in DFSDCxxx for IMS/APPC application time-out	
12.2.7 LU type 3 logon option as ETO SLUTYPE1 or 3270P	
12.2.8 Notify CQS outage to terminal users.	
12.2.9 Greater than 255 transaction classes	
12.3 Miscellaneous system manageability enhancements	
12.3.1 Operational enhancement for FDBR message DFS4172	
12.3.2 FDBR virtual storage constraint relief	
12.3.3 Independent ARM restart for FDBR	. 212

12.3.4 External subsystem resolve-in-doubt notification	213
12.3.5 Virtual storage constraint relief (VSCR)	215
12.3.6 Command recognition character (CRC) enhancement	215
12.3.7 /DIAGNOSE command	217
12.3.8 IPCS enhancement	219
12.3.9 Online change copy utility enhancements.	220
12.3.10 Disabling of z/OS DFSMS V1R5 PS EDI	221
Chapter 13. Migration and coexistence considerations	
13.1 Supported migration paths	
13.2 Supported connections and required maintenance	
13.3 Migration tasks and coexistence considerations	
13.3.1 CQS coexistence considerations	
13.3.2 Database utilities coexistence	
13.3.3 Remote Site Recovery (RSR) coexistence	
13.3.4 Additional coexistence considerations	
13.3.5 Using IRLM 2.2	
13.4 RECON upgrade	230
13.5 Fallback considerations.	232
Appendix A. DBRC API control blocks	
Constants and equates needed by the DBRC API	
DSPAPQHD header	
DSPAPQAL - allocation block.	
DSPAPQAR - Fast Path area block	
DSPAPQBO - backout block.	
DSPAPQCA - change accumulation execution block	
DSPAPQCG - change accumulation group block	
DSPAPQDB - full function database block	
DSPAPQDG - DBDS, database, and recovery group block	
DSPAPQDS - database data set block.	
DSPAPQFD - DEDB database block	
DSPAPQGG - global service group block.	
DSPAPQHB - HALDB block	
DSPAPQHP - HALDB Partition block	
DSPAPQIC - image copy block.	
DSPAPQLA - log allocation block.	
DSPAPQLG - RLDS/SLDS block	
DSPAPQLI - log information block	
DSPAPQNF - not found block.	
DSPAPQOL - online log data set block.	
DSPAPQRC - RECON status block	
DSPAPQRI - DBDS/area recovery information block	
DSPAPQRR - DBDS reorganization block	
DSPAPQRV - recovery block	
DSPAPQSL - DB/area authorized subsystem list block	
DSPAPQSS - subsystem block	285
Appendix B. Database Recovery Facility support	289
DRF functions inherited from ORS.	
DRF enhancements	-00
	290
Online invocation	
Online invocation	291

Execution enhancements	292
Appendix C. IMS Tools support for IMS Version 9 IMS Tools and IMS Version 9 compatibility	
Appendix D. IMS Control Center	299
IMS Control Center steps you need to know	
Workstation software	300
Migration	300
Host requirements	300
What set up steps you have to do	
Using the IMS Control Center	
Using the IMS Control Center and Command Editor with IMS Version 9	307
Abbreviations and acronyms	309
Related publications	313
IBM Redbooks	
Other publications	313
Online resources	
How to get IBM Redbooks	314
Help from IBM	315
Index	317



Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing, IBM Corporation, North Castle Drive Armonk, NY 10504-1785 U.S.A.

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrates programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. You may copy, modify, and distribute these sample programs in any form without payment to IBM for the purposes of developing, using, marketing, or distributing application programs conforming to IBM's application programming interfaces.

Trademarks

The following terms are trademarks of the International Business Machines Corporation in the United States, other countries, or both:

- CICS/ESA® CICS® DataPropagator™ DB2 Universal Database™ DB2® Enterprise Storage Server® ESCON® @server® FICON® IBM®
- ibm.com® IMS™ Language Environment® MQSeries® MVS™ Nways® OS/390® Parallel Sysplex® ProductPac® Redbooks™
- Redbooks (logo) RACF® RMF[™] SystemPac® TotalStorage® VTAM® WebSphere® z/OS® zSeries®

The following terms are trademarks of other companies:

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Windows and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other company, product, and service names may be trademarks or service marks of others.

Summary of changes

This section describes the technical changes made in this edition of the book and in previous editions. This edition may also include minor corrections and editorial changes that are not identified.

Summary of Changes for SG24-6398-00 for IMS Version 9 Implementation Guide: A Technical Overview as created or updated on October 27, 2005.

November 2004, First Edition


The revision of this First Edition, first published on December 14 2004, reflect the changes and additions described below.

November 2005, First Update

Changed information

Change bars identify the corrected area.

- Corrected the ICHERCDE macro in Example 6-6 on page 110 in order to facilitate migration matching the definitions used in RACF 1.6 and later.
- Removed the former Chapter 11, "MNPS replacement of XRF uservar' and related references.



Preface

This IBM® Redbook provides an overview of the new functions and enhancements in IBM Information Management System (IMS[™]) Version 9. IMS Version 9 contains over 50 enhancements, in all areas of the product, that address availability, scalability, capacity, usability, manageability, operations, on demand business, and application development requirements from its huge customer base. All of the enhancements in this new version resulted from specific customer requirements. The major enhancements include:

- Improved database availability for HALDB databases is provided by the long-awaited online reorganization (OLR) enhancement.
- The functionality of the IMS Connect product is included as an integrated function of IMS.
- DBRC provides a new API that allows assembler programs to query the RECON.
- ► IMS Java[™] users will have new JDBC SQL calls and DLIModel Utility support for retrieving existing IMS data in XML format as well as storing, indexing, searching, and retrieving valid XML documents into new or existing IMS databases.

We describe these enhancements and all other major changes in IMS Version 9. This redbook gives you the essential information that you need when you are migrating your IMS systems to IMS Version 9.

The team that wrote this redbook

This redbook was produced by a team of specialists from around the world working at the International Technical Support Organization, San Jose Center.

Jouko Jäntti is a Senior IT Specialist at IBM Global Services in Finland. Previously he was an IMS Specialist and a Project Leader with the IBM International Technical Support Organization, San Jose Center. He is the lead author of the 12 IMS related Redbooks, listed in the "Related publications" on page 313. Jouko has been working with IMS since 1986 starting with IMS Version 1.3 and has working experience in all IMS versions thereafter.

Yukari Andoh is an IT Specialist at the IMS group for IBM Japan Systems Engineering Co., Ltd., in Chiba, Japan. She provides technical support for IMS and IMS data management tools including three years of experience with the reorganization tools suite.

Knut Kubein is a Senior Advisory I/T Specialist with IBM Global Services in Germany. He has 30 years experience with IBM Large Systems Products working as a Technical Support Specialist, with 20 of those years devoted to IMS. He leads the IMS Support Team in EMEA. His areas of expertise include IMS data sharing, shared queues, and the Parallel Sysplex® architecture. He supports large bank accounts as well as other industrial IMS users. He has written extensively about shared queues.

Rich Lewis is a Senior Consulting IT Specialist with IBM Advanced Technical Support, for the Americas, located in Dallas, Texas. He has provided IMS technical support and consulting services as a member of the Dallas Systems Center for over 20 years. His areas of expertise include IMS database design, performance, and availability. He has developed and taught IMS classes for IBM and is a frequent speaker at IMS technical conferences, user group meetings, road shows, and seminars.

Geoff Nicholls is a Certified Senior IT Specialist, working in the IBM IMS Advocate team for the Silicon Valley Laboratory, and is based in Melbourne Australia. Geoff has 15 years of experience supporting IMS customers throughout the world. Previously, Geoff was an IMS Specialist with the International Technical Support Organization, San Jose Center. Geoff has a degree in Computer Science from the University of Melbourne, Australia. He has worked as an Application Programmer and Database Administrator for several insurance companies before specializing in database and transaction management systems with Unisys and IBM.

Dave Viguers is a member of the IBM IMS Development Team at Silicon Valley Lab working with performance, test, development, and customer support. Dave also develops and delivers education on IMS Parallel Sysplex. He has spent over 30 years working with IMS in various functions and organizations.

Suzie Wendler is a Consulting IT Specialist with IBM Advanced Technical Support, for the Americas, located in Dallas, Texas. Over the past several years her major responsibilities have included customer support, critical situation analyses, IMS e-business and connectivity projects, and design reviews, with an emphasis towards performance and DC communications. She has been involved in several on-site consulting projects including implementations of client/server environments, connectivity issues, and Web access. Additionally, she has made presentations for several user groups, including Guide and Share. She has also been involved in IBM-sponsored activities such as road shows and technical conferences, and has provided both technical and teaching support in IMS for IBM Education.

Thanks to the following people for their contributions to this project:

Paolo Bruni Deanna Polm International Technical Support Organization, San Jose Center

Rich Conway Bob Haimowitz International Technical Support Organization, Poughkeepsie Center

Rose Levin Merle Beghtel Jim Campbell Kiran Challapalli Kyle Charlet **Richard Cooper** Dario D'Angelo Jeff Fontaine Mike Gonzales Judi Hill Claudia Ho Shyh-mei Ho Chris Holtz Tawei Hu Jenny Hung Terry Krein Dorothy Lin Tom Morrison **Betty Patterson** Jack Pinto Frank Ricchio Pat Schroeck Alan Smith

Marc Spooner Clyde Tahara Judy Tse Judi Vera Jack Wiedlin Jerry Zentner IBM Silicon Valley Laboratory, San Jose, USA

Alonia Lonnie Coleman IBM Advanced Technical Support, Americas, Dallas Center

Alan Cooper IBM UK

Rober Hain IBM Australia

Philippe Sueur IBM France

Gen Sasaki IBM Japan

Special thanks for help during the project and for her marvelous contribution to reviewing:

Alison Coughtrie IBM Product Introduction Centre, Hursley Park, UK

Become a published author

Join us for a two- to six-week residency program! Help write an IBM Redbook dealing with specific products or solutions, while getting hands-on experience with leading-edge technologies. You'll team with IBM technical professionals, Business Partners and/or customers.

Your efforts will help increase product acceptance and customer satisfaction. As a bonus, you'll develop a network of contacts in IBM development labs, and increase your productivity and marketability.

Find out more about the residency program, browse the residency index, and apply online at:

ibm.com/redbooks/residencies.html

Comments welcome

Your comments are important to us!

We want our Redbooks[™] to be as helpful as possible. Send us your comments about this or other Redbooks in one of the following ways:

Use the online Contact us review redbook form found at:

ibm.com/redbooks

Send your comments in an email to:

redbook@us.ibm.com

• Mail your comments to:

IBM Corporation, International Technical Support Organization Dept. QXXE Building 80-E2 650 Harry Road San Jose, California 95120-6099

1

Introduction

IBM Information Management System (IMS) is unsurpassed in availability and speed for database and transaction processing. With the demands of the evolving on demand business environment and a marketplace that works in Web time, IMS continues to deliver the integrity, capability, and performance that customers have come to expect from IBM.

IBM is focused on strengthening IMS leadership, helping customers in on-demand business enablement, growth, availability, and systems management that newer environments and cost measures require. The enhancements in IMS Version 9 help you:

- Transform the way you do business with integrated information
- Build on demand applications that tolerate the rigors of doing business on the Internet
- ► Run a scalable, available, safe, and easily managed environment
- Leverage your information to make more informed decisions

This chapter provides the introduction and highlights of IMS Version 9.

1.1 Leading the industry

Industries worldwide rely on IMS to run their businesses. IMS is a part of everyday life. Chances are you use IMS when you turn on a light, make a telephone call, get a business loan, process accounting records, use your ATM card, put money in a bank, rent a car, purchase insurance, travel, send a package, track in-transit packages, trade stocks, control inventories, process payroll, update personnel records, control an assembly line, control a railroad, use a corporate database, run a government agency, conduct international business or banking, and many more tasks.

- More than 95% of the Fortune 1000 companies use IMS.
- IMS serves 200 million end users, managing over 15 million gigabytes of production data.
- IMS processes over 50 billion transactions every day.

IMS still owns the high-volume online transaction and database management environment. IMS customers have been driving their own growth with IMS.

IMS customers report:

- More than 100 million transactions were handled by one customer in a single day on a single sysplex system.
- 7 million transactions per hour and 120 million transactions per day were handled by another customer.
- One large customer has reached over 3000 days without an outage and is still going strong.
- Another large customer has transferred more than \$2.5 trillion through IMS in a single day.

IMS, the IBM premier hierarchical transaction and database management system, is the product of choice for critical online operational applications and data where support for high availability, performance, capacity, integrity, and low cost are key factors. Today, IMS manages the world's mission-critical data and has been at the forefront of the swing back to mainframe usage.

1.1.1 Unsurpassed performance

The IBM performance group achieves extremely high transaction rates with IMS Version 9 running in a high stress sysplex environment using four IMSs on a single IBM @server® zSeries® 990 model B16 processor.

IMS demonstrated 21,396 transactions per second with all database updates using the IMS Fast Paths shared expedited message handler queue capability, 4-way data sharing, shared virtual storage option areas, and new IMS Version 9 capabilities.

Using the new processor and the IBM TotalStorage[™] Enterprise Storage Server[™] model 800, IMS was able to reach 28.5 MB per second logging bandwidth. This shows that IMS scales up to large logging requirements for high stress IMS activity, such as integrated online reorganization for HALDBs, multiple systems coupling, and shared queues.

These performance tests demonstrate that nothing can match the performance of IMS and the zSeries in transaction and database access, making IMS the industry leader for on demand business and all of your business needs.

1.2 IMS Version 9 highlights

IMS Version 9 is evolving with on demand business by providing product integration openness with tools for application development and connectivity. IMS Version 9 offers manageability with autonomic computing to ease use, eliminate or reduce outages, and minimize the education curve for users. IMS scalability enhancements provide flexibility for growth and expansion.

With IMS Version 9, new hardware and software facilities, combined with many data and application sources, optimize IMS performance, capacity, availability, and recovery. IMS DB Version 9 offers enhancements in:

Integration and openness

Broadened access and storage of XML data in IMS databases, with XML and Java[™] technology.

Manageability

Expanded, autonomic, user friendly commands and interfaces that are accessible across environments. Eased installation and system generation, as well as enhanced security and serviceability.

Scalability

Improved availability and recovery, with fully-integrated online reorganization for High Availability Large Databases (HALDB), which provide concurrent online update and availability of data.

Improved performance, capacity and virtual storage constraint relief (VSCR) for Database Recovery Control (DBRC) and Fast Path.

IMS TM Version 9 offers enhancements in:

Integration and Openness

Broadened application development and execution tools, with XML and Java technology and with integrated IMS Connect function.

Manageability

Extended autonomic network switchover capability, and eased installation and system generation, as well as enhanced security and serviceability.

Scalability

Improved system availability, performance, and capacity for workload balancing.

IBM also provides a robust portfolio of tools and utilities to help you manage IMS efficiently and gain the best possible performance. To learn more about the IBM IMS products and tools, visit the Web site at:

http://www.ibm.com/ims

1.3 IMS Database Manager enhancements

In the areas of integration and open access with new application development and connectivity, IMS Version 9 includes the following enhancements:

XML storage in IMS databases

XML enablement provides support for storage and retrieval of XML documents into and from IMS databases. The XML enablement extends the IMS Java JDBC interface to allow the composition of XML documents from pre-existing non-XML IMS data. Additionally, IMS

can store XML documents into IMS either wholly intact or decompose them into standard IMS segments and fields that can be used by existing or new non-XML enabled applications. XML enhancements are described later in this book in Chapter 9, "XML storage in IMS databases" on page 145.

Tooling for XML storage

The DLIModel Utility enhancement generates XML schemas from database definitions (DBDs) and program specification blocks (PSBs). The DLIModel Utility supports XML storage and retrieval at run time. This enhancement automates schema generation to accelerate IMS application development.

Distributed database access

IMS Java remote database services enable IMS DB access from an Enterprise Java Bean (EJB) that runs on a distributed J2EE application server, without requiring additional z/OS® application programming.

- Additional enhancements including the following:
 - Symbolic checkpoint and restart support for the Java batch region
 - SQL enhancements for new SQL keywords and aggregate functions
 - JDBC[™] 2.0 support, including the ability to obtain scroll insensitive result sets
 - IMS-DB2 interoperability from within a Java dependent region
 - Provides a Java interface to access GSAM
 - The DLIModel Utility graphical user interface (GUI) provides a graphical version of the DLIModel Utility built as an Eclipse plug-in

We describe these features more in detail in Chapter 9, "XML storage in IMS databases" on page 145 and in Chapter 10, "IMS Java enhancements" on page 159 in this book.

IMS Version 9 Database Manager enhancements in the areas of scalability in high performance, capacity, availability, and recovery include the following:

HALDB online reorganization enablement

integrated HALDB online reorganization (OLR) is designed to address customer requirements for enhanced IMS data availability. OLR provides online reorganization by partition with concurrent online update and availability during reorganization. OLR is designed to be totally nondisruptive, there is no outage. You can adjust the pace of OLR to further minimize online impact. Multiple partitions can be reorganized in parallel. Coordination is provided through IMS Database Recovery Control (DBRC).

We describe the HALDB OLR feature in more detail in Chapter 3, "Integrated HALDB online reorganization" on page 29 in this book.

Database Recovery Control (DBRC) enhancements

The new DBRC application programming interface (API) enables customer-written application programs to obtain services from DBRC. The application obtains these services by issuing DBRC API requests; DBRC returns results to an area in storage where the application can retrieve them.

Command authorization support, initially provided in IMS Version 8 for DBRC batch commands, is now also provided for the online DBRC /RMxxxx commands. DBRC modules have been moved above the 16 MB line for enhanced capacity.

DBRC can reassign and reuse currently unused database management block (DMB) numbers to reduce the potential for outages.

We describe the DBRC enhancements in IMS Version 9 in more detail Chapter 5, "DBRC enhancements" on page 73 in this book.

Fast Path enhancements

Enhancements provide improved performance of Fast Path data entry database (DEDB) area open/close processing. Increased parallelism is obtained by exploiting multiple task control blocks (TCBs) to process multiple area open/close requests simultaneously. This can provide a performance advantage when many areas are open. Additional usability enhancements improve the handling of DEDB area open/close processing during IMS emergency restarts and other system error recovery scenarios.

Fast Path shared virtual storage option (SVSO) multi-area structure support provides for housing multiple DEDB areas in a single Coupling Facility structure. Instead of having one Coupling Facility structure per area, multiple areas can reside in a single Coupling Facility structure. This reduces the total number of Coupling Facility structures that must be defined in a system.

A number of additional enhancements increase the serviceability and usability of Fast Path. These enhancements include, among other items, additional log record information for sequential dependent (SDEP) segments that can be exploited by the IMS Performance Analyzer.

We describe the DBRC enhancements in IMS Version 9 in more detail Chapter 4, "Fast Path enhancements in IMS Version 9" on page 57 in this book.

IMS Version 9 Database Manager includes also the following database utilities and other scalability enhancements:

- Support for tape block size greater than 32 KB provides a performance advantage in the image copy and recovery utilities.
- Enhanced recoverability of external subsystem indoubt units of work enables you to resolve indoubt units of work before IMS restart.
- IMS dynamic allocation provides virtual storage constraint relief (VSCR) by ensuring that generated data set association blocks (DSABs) are allocated above the 16 MB line. For example, a customer with 20,000 full function or Fast Path data sets that are dynamically allocated could have more than a megabyte of storage allocated above the 16 MB line.
- Logger enhancements improve the availability of online log data sets (OLDSs) for restart and the integrity of log data that is obtained for write ahead data sets (WADSs).

1.4 IMS Transaction Manager enhancements

IMS Transaction Manager offers many enhancements and improvements in the areas of integration and open access with new application development and connectivity. As of IMS Version 9, the functionality of the IMS Connect product (program number 5655-K52), Version 2.2, is included in IMS as an integrated feature. Refer to Chapter 8, "Integrated IMS Connect support" on page 135 for details.

Open transaction manager access (OTMA) security and serviceability enhancements provide the following performance advantages:

- OTMA clients can now set the access control environment element (ACEE) security aging value for user IDs in the OTMA message prefix without requiring the client to reconnect to OTMA.
- The OTMA trace table entries for the OTMA user exit routines (DFSYIOE0, DFSYPRX0, and DFSYDRU0) are standardized so that you can view the return code set by the exit routines. The DFSYPRX0 user exit routine for OTMA can set the OTMA destination TPIPE name.

The Z2 field of IMS application data can now be set or changed for OTMA translation input and output.

OTMA and many other IMS Transaction Manager enhancements are discussed later in this book in Chapter 12, "Miscellaneous enhancements in IMS Version 9" on page 199.

Other IMS Version 9 Transaction Manager enhancements in this area include the following:

- IMS Version 9 has enhancements to support RACF® (or an equivalent product) replacement of the security maintenance utility (SMU) security. IMS now consolidates implementation of all security under RACF. SMU security is available in IMS Version 9 to enable migration to RACF. This and other security enhancements are discussed later in this book in Chapter 6, "Security considerations with IMS Version 9" on page 85.
- The allowable number of named classes of transactions is increased from 255 to 999 to enhance usability and customization of the system.
- An added option allows a type 3 logical unit device to log on as an Extended Terminal Option (ETO) type 1 secondary logical unit (SLU1) or 3270P device, making IMS available for these devices.
- COBOL XML support through WebSphere® Studio Enterprise Edition Version 5-generated XML converters allows IMS COBOL applications to parse and transform XML documents. You can now send and receive XML documents directly to and from IMS COBOL applications that run inside IMS regions.
- Message Format Service (MFS) Web Services support through WebSphere® products enables you to publish existing MFS transactions on the Internet as Web Services and connect to IMS using simple object access protocol (SOAP) and Enterprise Java Bean (EJB) bindings.

In the areas of scalability in high performance, capacity, availability, and recovery IMS Version 9 offers the following:

► Fast Path enhancements

The Fast Path optional expedited message handler queue (EMHQ) structure eases manageability, enabling you to bypass allocating an EMHQ structure and its associated data sets when the shared EMH is not being used. This and other Fast Path enhancements are discussed further in Chapter 4, "Fast Path enhancements in IMS Version 9" on page 57.

Database Recovery Control (DBRC) enhancements

The new DBRC application programming interface (API) enables customer-written application programs to obtain services from DBRC. The application obtains these services by issuing DBRC API requests; DBRC returns results to an area in storage where the application can retrieve them.

Command authorization support, initially provided in IMS Version 8 for DBRC batch commands, is now also provided for the online DBRC /RMxxxx commands.

DBRC modules have been moved above the 16 MB line for enhanced capacity. DBRC enhancements are described in more detail in Chapter 5, "DBRC enhancements" on page 73.

Utilities and other scalability enhancements:

Enhanced recoverability of external subsystem indoubt units of work enables you to resolve indoubt units of work before IMS restart.

Logger enhancements improve the availability of online log data sets (OLDSs) for restart and the integrity of log data that is obtained for write ahead data sets (WADSs).

1.5 IMS system manageability enhancements

With IMS Version 9, IMS systems manageability continues to evolve. New enhancements for IMS TM and IMS DB enable you to manage operations more effectively, while reducing system generation time and effort and various miscellaneous enhancements to fulfill customer requirements. These enhancements include the following:

- Operations management enhancements, which include:
 - Command environment enhancements simplify the Common Service Layer (CSL), which enables you to use IMS enhanced format commands and the IMS single point of control (SPOC) without requiring the Resource Manager.
 - Sysplex-wide database commands expand operations management single point of control to handle database commands. In IMS Version 8, an Operations Manager (OM) application programming interface (API) was provided to enable you to issue IMS commands from the OM. In IMS Version 9, commands for database and area resources are added to provide you with the ability to better manage the IMS sysplex and to provide a single-system image.

These enhancements are described in more detail in Chapter 7, "Type-2 commands and enhanced command environment" on page 115.

Note: IMS Version 9 publications use new terminology to distinguish the types of IMS commands. Classic commands are called type-1 commands. IMSplex or enhanced commands are now called type-2 commands. Type-1 commands are generally preceded by a leading slash character, and they may be entered from any valid IMS command source. Type-2 commands may be entered only through the Operations Manager (OM) API.

- ► System generation time and effort enhancements, which include:
 - System generation enhancements stage the removal of conditional binds currently done by system generation. This removes the restriction of requiring separate execution libraries for IMS environments. These enhancements eliminate the conditional link of composite modules, thus eliminating a step and reducing the impact of the system generation process.
 - Online change modules enhancements remove most online change modules from the nucleus link-edit step and place them in their own load module. The value to the customer is saving space below the 16 MB line private storage. This is another step toward limiting the impact of IMS system generation, easing the process for defining IMS resources.
 - Extended Terminal Option (ETO) feature checking has been moved to the initialization phase, eliminating the need for an IMS system generation to add this feature.
 - DBRC type 4 SVC module enhancements enable you to apply maintenance to the module without having to restart IBM z/OS.
 - Dynamic add of the resource cleanup module enhances availability and serviceability.
 - Enhancements to the Syntax Checker, which provides detailed assistance with the tailoring of IMS, include support for the definition and maintenance of additional IMS PROCLIB members, and the addition of usability features.
 - Installation verification program (IVP) enhancements provide new sample applications that support the Common Queue Server (CQS) and the enhanced command environment. In addition, a number of usability improvements are provided, including the ability to import IVP variables from previous versions of IMS.

These enhancements are described in more detail in Chapter 2, "Product packaging, installation and resource definition enhancements" on page 9.

Miscellaneous enhancements

Miscellaneous enhancements in the system manageability area include the following improvements to fulfill customer requirements:

- High Availability Large Database (HALDB) usability eases partition initialization without requiring the use of DBRC commands.
- The new /DIAGNOSE command eases IMS serviceability.
- Command recognition character registration eases operations management by providing unique subsystem registration so that an operator can enter a command from any system in a sysplex and have it routed to the correct subsystem. With unique subsystem registration, the operating system can detect collisions between subsystems, and can inform operators or system programmers which prefixes are currently in use.
- A new write-to-operator (WTO) message replaces the WTO-reply (WTOR) message for Fast Database Recovery (FDBR). The new message notifies the operator when FDBR is started before the active IMS, without having to wait for a reply. FDBR waits for the active IMS to start up. This eases operations usability in this environment.
- Enhancements to the online change copy utility support the IEBCOPY utility data set parameters WORK, SIZE, and LIST. The online change copy utility passes the values for these parameters to the IEBCOPY utility. These enhancements reduce outages because they enable you to override default values.

These enhancements are described in more detail in Chapter 12, "Miscellaneous enhancements in IMS Version 9" on page 199.

2

Product packaging, installation and resource definition enhancements

This chapter describes the new features and changes from the previous version in the areas that you will be dealing with first, after you have ordered and received IMS Version 9 software and begin to install it.

This chapter covers the following topics:

- Product packaging
- Resource definition and installation changes
- IMS Application Menu
- Installation verification program (IVP) enhancements
- Syntax Checker enhancements

When you start planning the migration of your existing environment, please also refer to Chapter 13, "Migration and coexistence considerations" on page 223, which provides information about the coexistence between different IMS versions and some migration considerations.

2.1 Product packaging

The IMS Version 9 product number is 5655-J38. IMS products are ordered by Function Modification Identifiers (FMIDs). Table 2-1 lists the FMIDs for IMS Version 9.

Table 2-1	FMIDs for IMS	Version 9.
	1 111120 101 11110	

Function modification identifier	Function description
НМК9900	System Services
JMK9901	Database Manager
JMK9902	Transaction Manager
JMK9903	Extended Terminal Option (ETO)
JMK9904	Recovery Level Tracking (RSR RLT)
JMK9905	Database Level Tracking (RSR DLT)
JMK9906	IMS Java
HIR2101	IRLM 2.1
HIR2102	IRLM 2.2

Note that both IRLM releases 2.1 and 2.2. can be used with IMS Version 9, and it is a customer's decision which one to use. Both releases can coexist with each other and you can have members in a data sharing environment on either release. The release/s of IRLM distributed with IMS Version 9 depend on the order type as below:

- CBPDO, ProductPac® or Standalone ==> both IRLM 2.1 and IRLM 2.2 are included
- ServerPac, FunctionPac or SystemPac® ==> IRLM 2.2 is included
- CustomPac ==> CustomPac is made up of three offerings: FunctionPac, ProductPac, and SystemPac. Which IRLM version you get with CustomPac depends on which offering you order.

Integrated IMS Connect function

The IMS Connector for Java 9.1.0.1 runtime component for z/OS is delivered with IMS. The IMS Connector for Java 9.1.0.1 development component which ships with WebSphere Studio Application Developer Integration Edition (WSADIE) and is delivered as an update to WSADIE 5.1.1.

IMS Java remote database services

To use IMS Java remote database services (RDS) to access IMS databases from applications that run on WebSphere Application Server on a non-z/OS, you must download IMS Java files from the IMS Java Web site. These files are required in addition to the files that are installed as part of the SMP/E installation of the IMS Java FMID. To download the required IMS Java files, go to the IMS Web site and link to the IMS Java Web page for more information:

http://www.ibm.com/ims

2.2 Resource definition and installation changes

It has been a customer requirement for a long time to reduce IMS system generation time and effort. IMS has responded to that requirement by providing enhancements over the several versions. The major steps in this area have been the following:

- IMS Version 4 stopped using system generation to support major new functions by introducing ETO.
- IMS Version 5 and 6 removed conditional assembly modules.
- ► IMS Version 7 put non-conditional link-edit modules under SMP/E control.
- IMS Version 8 provided the Resource Manager, coordinated global online change, Syntax Checker, packaging, installation and IVP enhancements, and removed the RSR RLT/DLT features install checking.

There are substantial changes to IMS system definition in IMS Version 9 to further simplify this process. In the short term, we are continuing to reduce the IMS system generation effort by:

- Removing the restriction of maintaining SDFSRESL libraries for different system definitions.
- ► Removing online change modules from the nucleus link-edit step.
- Removing the ETO feature install checking.
- Allowing the dynamic install of DBRC type 4 SVC.
- Replacing DFSMRCL0 by new resource cleanup services.

2.2.1 Shared SDFSRESL for different configurations and system definitions

With IMS Version 9, you do not need separate IMS SDFSRESL libraries for system generation of any of the following environments: DB/DC, DBCTL, DCCTL or Fast Path. You can use separate IMS SDFSRESLs or combine them, as needed for your environment. This is accomplished through two capabilities: the removal of system generation conditional binds and support for a generic DFSVC000 module through the ability to override required values through new IMS Control Region parameters. Three new control region parameters, SVC2 (type 2 SVC number), MCS (IMS route code), DESC (IMS descriptor code), replace the equivalent IMSCTF and IMSCTRL system definition parameters. The IMSGROUP (defines the IMSID) control region parameter must be added to each IMS/DBC/DCC procedure.

A new batch region parameter RGSUF for DFSPBxxx member provides batch specific overrides for the parameters.

Removal of system generation conditional binds

In previous releases, the mechanism to bind (link edit) required modules to support a specific IMS environment was done through conditional bind controls in the system generation process. With this enhancement, all non-suffixed modules for all possible configurations are always bound during SMP/E install. During IMS initialization, the appropriate modules for the specific configuration are loaded into SDFSRESL as standalone modules. The nucleus which is a suffixed module is still conditionally bound.

This capability removes the need to maintain separate resource libraries for different configurations.

Generic DFSVC000 module

DFSVC000 is a module that IMS uses to maintain information unique to a specific execution environment such as the IMSID, subsystem type, SVC numbers, and so on. In releases prior to IMS Version 9, when users wanted to share SDFSRESL, a common practice was to place the DFSVC000 module unique to an execution environment into a library that was concatenated in front of the shared SDFSRESL.

With IMS Version 9, an enhancement has been introduced that allows a generic DFSVC000 to be used for all execution environments. Module DFSVC000 continues to be built during system generation into the SDFSRESL, and it is based on most recent system generation that used the library. If a system requires a type 2 SVC number, route code or descriptor code that is different than what is in the DFSVC000 member, the following new parameters are available to provide the values:

SVC2

SVC2 specifies the type 2 SVC number reserved for use by the IMS subsystem. The value provided can range from 200 to 255. If not specified, then the value defined in the IMSCTF macro during system generation is used or the default of 254.

MCS

MCS specifies the z/OS routing code or codes to be assigned to the IMS system console and is applicable when multiple console support is included in the operating system. If not defined, the value from the IMSCTRL macro is used or the default of (2,7).

DESC

DESC specifies the descriptor code to be assigned to the IMS system console messages when multiple console support is included. It defaults to the IMSCTRL macro specification or the default of 7.

Considerations for sharing DFSVC000

The generic DFSVC000 member can be created to contain whatever default values you choose as the most appropriate. These can be overridden by execution parameters.

► SVCNO (IMSCTF)

SVCs are downward compatible, so the recommendation is to use the highest level for all releases.

MCS and DESC (IMSCTRL)

Recommendation is to use the most common set of parameters.

IMSID (IMSCTRL)

Specify the value you want for the default.

The existing techniques to provide override values for IMSID continue to be used:

IMSID which is always unique to an IMS environment continues to be overridden with the IMSID= specification on the control region.

For associated dependent regions, in other words, MPPs, BMPs, IFPs, JMPs, JBPs (and even any DLISAS/DBRC regions that are manually started), the IMSID value can match that of the target control region's IMSID or IMSGROUP value.

► The IMSGROUP parameter is a technique that allows a dependent region to use MVSTM name token services to find the correct IMSID to use.

This facilitates creating generic dependent region JCL that can be moved from one system to another.

RGSUF parameter for batch

The RGSUF parameter is now available in IMS Version 9 systems for batch regions. This allows batch to use a DFSPBxxx member of PROCLIB for overriding the execution parameter values that are applicable to batch (DBRC=, IRLM=, IMSID=, SVC2=, MCS=, DESC=). RGSUF has no default value and must be specified in the batch region if access to DFSPBxxx is desired.

Note that as in the past, an override value for DBRC is honored only if the installation default is NO or YES. If the installation default is defined as FORCE then the value in this override parameter is ignored. The IMSID= value in a batch environment is used as an identifier to relate messages that are routed to the z/OS system console with the batch job. This is the value that is displayed along with the message on the console. To avoid confusion as to which region issued the console message, each batch region can specify a unique value.

Figure 2-1 on page 14 shows how the IMS1 control region JCL overrides the default values that were generated in DFSVC000.

Since the control region JCL includes a specification of IMSGROUP=IMSA, MVS name token services are invoked to create a token called IMSA that is associated with the control region IMSID value of IMS1. Dependent regions that need to connect to IMS1 can specify one of the following in the execution JCL:

IMSID

The target IMSID value, for example an MPP which directly specifies IMSID=IMS1.

► The IMSGROUP name value

BMPA which specifies IMSID=IMSA and results in MVS name token services equating IMSA with IMS1.

► No IMSID specification

BMPB which results in using the default IMSID value in DFSVC000. Since the default IMSID value is not equal to an actual control region IMSID, MVS name token services in this case also provide the translation from the name IMSA to the actual IMSID value of IMS1.




Figure 2-1 DFSVC000 override

2.2.2 DBRC keyword ignored in the system definition

Starting in IMS Version 9 the default for DBRC in batch is no longer set in the system definition. The default is DBRC=YES in batch and utility regions. The IMSCTRL macro specification for DBRC= in the system definition is ignored, and if coded, the following informational message will be printed:

GO11 WARNING: THE DBRC | MAXIO KEYWORD IS NO LONGER USED AND IS IGNORED.

A new module, DFSIDEF0, is used by batch and utilities. DFSIDEF0 contains the batch and utilities installation default for DBRC. A sample of DFSIDEF0 is provided by IMS. If DFSIDEF0 cannot be loaded at initialization time, DBRC defaults to YES as the initial value. It can be overridden by JCL or in PROCLIB member DFSPBxxx.

If it is not desired to have DBRC used in batch and utility regions, this can be changed in one of three ways:

- Assemble and bind DFSIDEF0 into IMS execution library.
- Override the value in IMS.PROCLIB DFSPBxxx.
- Override the value in JCL.

Batch and utility regions use the DFSIDEF0 module during initialization. A sample DFSIDEF0 module is provided with IMS in IMS.ADFSSMPL library. The provided sample module contains a batch and utility region default of DBRC=YES. This value is coded on the DFSIDEF macro. If DBRC is to be used for batch and utilities, creating the DFSIDEF0 module is not required.

A sample job for creating the DFSIDEF0 module is also provided as a new IVP job, IV_E207J. The JOB can be found in IMS.INSTALIB library and it can be run as part of IVP.

Example 2-1 shows the contents of the JOB provided by IVP. Without modifications the module has the default value of "DBRC=YES" coded. If you want to change the DBRC default to NO or FORCE, make the changes by commenting out and uncommenting the appropriate lines, and then assemble and bind the module into the SDFSRESL.

Example 2-1 Job for assembling and binding the module DFSIDEF0

```
//ASSEMBLE EXEC PGM=ASMA90,PARM='NOOBJ,DECK'
//SYSLIB DD DSN=IMS910G.SDFSMAC,DISP=SHR
//SYSPUNCH DD DISP=OLD,DSN=IMS910G.OBJDSET(DFSIDEF0)
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=SYSDA,DISP=(,DELETE),SPACE=(CYL,(15,15))
//SYSIN
         DD *
IDEFO TITLE 'DFSIDEFO - IMS INSTALLATION DEFAULTS BLOCK'
DFSIDEF0 CSECT
        SPACE 1
        DFSIDEF TYPE=BEGIN
   ------
  DBRC= DBRC FOR BATCH
   DBRC=YES - USE DBRC.
    DBRC=NO - DO NOT USE DBRC
    DBRC=FORCE - USE DBRC. CAN NOT BE OVERRIDDEN WITH EXEC PARM *
*_____
        DFSIDEF TYPE=PARM, DBRC=YES
*****
        DFSIDEF TYPE=PARM, DBRC=NO
*****
        DFSIDEF TYPE=PARM, DBRC=FORCE
        DFSIDEF TYPE=END
        END DFSIDEF0
/*
//*
//BIND
       EXEC PGM=IEWL,
           PARM='SIZE=(880K,64K),NCAL,LET,REUS,XREF,LIST',
11
           COND=(0,LT,ASSEMBLE)
11
//SYSPRINT DD SYSOUT=*
//SYSPUNCH DD DSN=IMS910G.OBJDSET, DISP=SHR
//SYSLMOD DD DSN=IMS910G.SDFSRESL,DISP=SHR
//SYSUT1 DD UNIT=(3390,SEP=(SYSLMOD,SYSLIN)),
11
            SPACE=(CYL, (10, 1))
//SYSLIN DD *
  INCLUDE SYSPUNCH (DFSIDEFO)
  NAME DFSIDEFO(R)
//*
```

2.2.3 Removing conditional link-edit for online change modules

Approximately 33 online change modules are removed from the nucleus link-edit step of IMS system definition and they become standalone modules. Approximately 20 of these modules are moved to above-the-line private storage. This is another step towards simplifying system definition and allows you to save below-the-line private storage.

2.2.4 ETO feature checking

The Extended Terminal Option (ETO) feature installs completely with the SMP/E install process and no longer requires system generation to validate the install. The validation will occur during IMS initialization.

ETO installation in IMS Version 9 continues to be done through the SMP/E install process. There is no longer a system generation requirement to validate the installation. The system generation process, however, will still continue to build ETO descriptors, if requested. In the stage 1 system definition, the IMSCTRL macro has been changed to ignore the first two subparameters of the ETOFEAT parameter. These were used, in previous releases, to determine whether or not validation of the ETO feature was to take place during system generation. If specified in IMS Version 9, an informational system generation G1209 message will be produced to inform the user that the subparameters are no longer valid and are ignored. The third subparameter is still valid and used to request ETO descriptor generation, with the following values:

- NO is the default and produces a normal system definition without descriptors.
- ► ALL requests that descriptors be generated as part of normal system definition.
- ONLY requests that this invocation of system definition produce only descriptors.

NO is the new default value in IMS Version 9.

During IMS startup if the ETO=Y parameter is specified, then the IMS initialization process will attempt validation of the install. If the feature is not installed, IMS will issue a user abend U3476 and will print message DFS3676I. The response to this abend is to turn off the ETO feature request with ETO=N or go back and review the SMP/E install of the feature.

2.2.5 Dynamic update of DBRC type 4 SVC

The dynamic SVC update (DFSUSVC0) utility has been enhanced to allow dynamic update of the DBRC type 4 SVC module. Thus, you can apply maintenance to the DBRC type 4 SVC module without having to re-IPL z/OS after each update. The SVC module, however, must still be installed into the z/OS system and placed in LPALIB or an MLPA library.

In previous releases, the utility only worked for type 2 SVCs. When it ran, there could not be any active IMS images (control regions or batch regions) using the SVC number. The code searched the IMS SVC directory table to determine if there was an active IMS using the SVC number and failed if one was found. Any updates to the DBRC type 4 SVC required re-IPLing z/OS.

As in previous releases, IMS system definition still creates the SVC routines using the IMSCTF macro-defined user-specified numbers, or the IMS-provided default numbers. The name created for the type 4 SVC is IGC00xxx where, xxx indicates the signed decimal type 4 SVC number. IMS system definition copies the load modules representing the SVC routines into the SDFSRESL library.

IMS dynamic SVC update utility (DFSUSVC0) continues to support dynamic updates of the type 2 SVC and adds support for type 4 SVC. As in previous releases, for updates to the type 2 SVC, the utility checks to see if there is an active IMS using the SVC number. If so, the update fails. The same does not apply to the DBRC type 4 SVC. DBRC regions are not required to be down when the type 4 SVC is updated. The utility determines the SVCs to be updated and dynamically changes the z/OS SVC table to point to the new SVC modules.

The SVCs that are to be updated are specified by a new parameter in DFSUSVC0 JCL. The EXEC statement must be in one of the following forms:

//STEP001 EXEC PGM=DFSUSVC0
//STEP001 EXEC PGM=DFSUSVC0,PARM='SVCTYPE=(2)'
//STEP001 EXEC PGM=DFSUSVC0,PARM='SVCTYPE=(4)'
//STEP001 EXEC PGM=DFSUSVC0,PARM='SVCTYPE=(2,4)'

The EXEC statement allows you to specify whether the IMS type 2 SVC module, the DBRC type 4 SVC module, or both are to be updated. When SVCTYPE=(2) is specified, the IMS

type 2 SVC module is updated. When SVCTYPE=(4) is specified, the DBRC type 4 SVC is updated. When SVCTYPE=(2,4) is specified, both the IMS type 2 SVC module and the DBRC type 4 SVC module are updated. If a value is not specified for the SVCTYPE= parameter, the IMS type 2 SVC module is updated by default.

For more information about DFSUSVC0 utility, refer to the manual *IMS Version 9: Utilities Reference: System,* SC18-7834.

2.2.6 Replacing DFSMRCL0 by new resource cleanup services

IMS dynamically installs its resource manager cleanup routine; you do not need to install the DFSMRCL0 module as part of the IMS installation. Registration of the IMS resource manager cleanup routine with the operating system is done automatically during IMS startup and it is established as a dynamic rather than static resource manager.

With the invocation of the z/OS RESMGR service to dynamically register the new IMS resource cleanup routine during IMS initialization, DFSMRCL0 no longer needs to be bound into LPALIB nor does it need to be defined as a static z/OS resource manager in CSECT IEAVTRML of module IGC0001C.

The RESMGR service actually calls a stub module DFSMRC00 which calls the new IMS resource cleanup module DFSMRC20. This allows for transparent application maintenance. DFSMRC20 also contains a version number. If a dynamic update is done, the old copy will remain until the next IPL.

As long you are using earlier versions of IMS than IMS Version 9 in your environment, those prior releases still require DFSMRCL0 to be installed as part of z/OS. IMS Version 9 resource cleanup can coexist with DFSMRCL0 from previous releases. If a pre-IMS Version 9 and IMS Version 9 run on the same LPAR, use the highest version pre-IMS Version 9 DFSMRCL0 or DFSMRCL0 that is shipped with IMS Version 9 for binding it into LPALIB. The name "DFSMRCL0" still must be zapped into IEAVTRML CSECT of the z/OS module IGC0001.

When migration to IMS Version 9 is complete, in other words, there is no pre-IMS Version 9 systems (online or batch) in the same LPAR, DFSMRCL0 can be removed from LPALIB and IEAVTRML.

Note: Name DFSMRCL0 must be removed from IEAVTRML before the module is removed from LPALIB. If the name is still in IEAVTRML and the module is not in LPALIB, IPL will fail.

2.3 IMS Application Menu

Over several releases, IMS has provided a number of applications that run on TSO and ISPF. This is a trend that will continue for several more releases to come. As such, the growing challenge for a user is remembering how to start each application using its own unique command name and parameters. The IMS Application Menu addresses this issue by providing a common interface to the applications. This allows a quick way to view and invoke the available applications.

There are alternative ways to set up IMS Application Menu. First, the IMS.SDFSEXEC data set may be included in the SYSPROC DD concatenation. This is the library that contains the DFSAPPL application. The IMS menu can then be displayed by typing the following on an ISPF command line:

```
TSO %DFSAPPL HLQ(IMS910).
```

Another way is to call the exec directly:

```
EXEC 'IMS910.SDFSEXEC(DFSAPPL)' 'HLQ(IMS910)'
```

The HLQ parameter value must be set to the high level qualifier for IMS Version 9 libraries and it is required on the first use. If it is not specified on subsequent uses, the most recently specified HLQ is used. In our examples, we are having the value IMS910 for the HLQ. The user may want to add a link to their own ISPF menu where the IMS Application Menu can then be invoked as an option.

Figure 2-2 shows the IMS Application Menu in IMS Version 9.

Help		
Command ===>	IMS Application Menu	
(C) Copyright IBM Corp. 2003. All rights reserved. Select the desired application and press Enter.		
1 2 3 4 5 6 7	Single Point of Control (SPOC) Knowledge-Based Log Analysis (KBLA) HALDB Partition Definition Utility (PDU) Syntax Checker for IMS parameters (SC) Installation Verification Program (IVP) IVP Export Utility (IVPEX) IPCS with IMS Dump Formatter (IPCS)	
To exit the	application, press F3.	

Figure 2-2 IMS Application Menu

To select an application from the IMS Application Menu, type the number of the application and press Enter or position the cursor on the desired application and press Enter. The IMS Application menu allows an easy invocation of the following applications:

► TSO Single Point of Control (TSO SPOC)

By selecting this option you can invoke a TSO SPOC session. TSO SPOC was introduced with IMS Version 8, refer to IBM Redbook *IMS Version 8 Implementation Guide - A Technical Overview of the New Features*, SG24-6954 for more information.

Knowledge Based Log Analysis (KBLA)

KBLA is a new feature introduced with IMS Version 9. Refer to Chapter 11, "Knowledge Based Log Analysis (KBLA)" on page 179 for more information about KBLA.

HALDB Partition Definition Utility (PDU)

PDU was introduced with High Availability Large Database feature in IMS Version 7. Refer to IBM Redbook *The Complete IMS HALDB Guide, All You Need to Know to Manage HALDBs,* SG24-6945 for more information about HALDB PDU.

Syntax Checker

Syntax Checker was introduced with IMS Version 8, refer to IBM Redbook *IMS Version 8 Implementation Guide - A Technical Overview of the New Features,* SG24-6954 for more information. IMS Version 9 provides enhancements to Syntax Checker, and we describe them later in this chapter.

Installation verification program (IVP)

You can also access the IVP dialog from the IMS Application Menu. IVP has some changes and enhancements in IMS Version 9. They are described later in this chapter.

► IVP Export Utility

IVP Export Utility is new with IMS Version 9 and is used to export IVP variables pre-version 9 releases. These variables can be imported into IMS Version 9, easing migration.

IPCS with IMS Dump Formatter

Access to IPCS with IMS Dump Formatter is available from the IMS Application Menu. IPCS panels have some enhancements for IMS Version 9. They are described in 12.3.8, "IPCS enhancement" on page 219.

2.4 Installation verification program (IVP) enhancements

For IMS Version 9, the IMS installation verification program (IVP) provides the following enhancements:

- New sub-option for CSL
- ► The "E" IVP steps support creating of the DBRC default module DFSIDEF0.
- ► The "O" IVP steps support for a Common Queue Server (CQS) sample application.
- ► The "P" IVP steps provide an Enhanced Command Environment sample application.
- The IVP help text for the IVP steps:
 - Uses the variables from variable gathering.
 - Uses color to emphasize important information.
- Support for JES3 job classes is improved, and problems encountered by the IVP jobs that cannot run in a JES3 environment have been eliminated.
- SMS storage class and management class parameters are available for allocating all data sets.
- A new and separate high level qualifier variable, IXUVSMHQ, for VSAM data sets is introduced.
- New steps are introduced to complete and test the install of the IPCS for IMS dumps.
- ► IVP variables can be exported and imported between IMS releases for easier migration.
- The IVP for Java has been enhanced to include an example of running the IMS Java IVP for remote database services. See IMS Version 9: IMS Java Guide and Reference, SC18-7821 for details.

2.4.1 IVP sub-options with IMS Version 9

The supported sub-options in IMS Version 9 include the following:

Use IRLM in IVP Applications

The default is to use this sub-option (marked by a slash) for DB batch, DBCTL, DB/DC, and DB/DC with XRF. This sub-option is not available for DCCTL. If you select this sub-option, the IRLM is defined during system definition and the IVP is run using the IRLM for the single-lock manager. If you do not select this sub-option, the IRLM is not used and program isolation (PI) is used as the single-lock manager. Use of IRLM is only required if you plan to use block-level data sharing. Optionally, you can elect to use the IRLM, instead of PI, as the single-lock manager. If you select IRLM, IVP creates a simulated inter-CPC block-level data sharing configuration using two IRLMs. ► Use Fast Path in IVP Applications

The default is to use this sub-option (marked by a slash) for DBCTL, DCCTL, DB/DC, and DB/DC with XRF. This sub-option is not available for DB batch.

ETO Feature Installed

For DCCTL, the default is not to use this sub-option (no slash). For DB/DC and DB/DC with XRF, the default is to use this sub-option (marked by a slash). This sub-option is not available for DB batch or DBCTL.

Add CQS to CSL Application

The default is not to use this sub-option (no slash). If you select this option, the IVP adds the necessary jobs and tasks to the CSL sample application to use CQS. This option is new in IMS Version 9.

Figure 2-3 shows the sub option selection panel in IVP.

Figure 2-3 Sub option selection panel in IVP

2.4.2 The new "E" IVP steps

The new "E" IVP steps include:

► IV_E207J JOB

A job for creating the DFSIDEF0 module for DBRC default value.

IV_E304J JOB

Add CQS Members to IMS.PROCLIB. This adds the following PROCLIB members:

DFSSQ000	Shared queues PROCLIB member
CQSIP000	CQS initialization parameters
CQSSL000	CQS local structure definition
CQSSG000	CQS global structure definition

► IV_E307J JOB

Define CFRM policy for CQS to z/OS. Look at the information rather than run the job. Your installation may already have a CFRM policy set up and will only need to add the information pertaining to CQS.

2.4.3 The new "O" IVP steps

The new "O" IVP steps include:

► IV_0102J JOB

Allocate CQS Execution Data Sets. This step defines the allocation of the CQS execution data sets:

- System checkpoint data set
- Structure recovery data sets
- IV_0203J JOB

Start CQS.

► IV_O205T: TASK

SPOC Sample I. This updates the help text to show the CQS as part of the IMSplex.

► IV_0215J: JOB

Start DB/DC Region IVP1. This brings up shared queues.

2.4.4 The new "P" IVP steps

The enhanced command environment removes the requirement for a Resource Manager and also supports a non-Parallel Sysplex configuration. The use of type-2 commands still requires the Operations Manager (OM) and Structured Call Interface (SCI) address spaces to be enabled. The IVP introduces a new set of "P" steps to verify the installation and demonstrate this new environment. Two SPOC samples are also included.

For the DB/DC environment, the full set of "P" steps are as follows:

IV_P001T: NOTE	Introduction - Enhanced Command Environment
IV_P101J: JOB	Allocate Data Sets
IV_P102J: JOB	Initialize RECON / Register Data Bases
IV_P103J: JOB	Data Base Initial Load
IV_P104J: JOB	Batch Image Copy
IV_P215J: JOB	Start DB/DC Region IVP1
IV_P217T: TASK	SPOC Sample I
IV_P218T: IVP1	Cold Start IMS
IV_P221T: SPOC	SPOC Sample II
IV_P230T: IVP1	Stop IMS with a /CHE FREEZE
IV_P232T: MVS	Shut Down SCI - Shut down OM and SCI using z/OS command
	F IVP91SCI,SHUTDOWN CSLPLEX
IV_P401J: JOB	Scratch Data Sets

Additionally, IMS PROCLIB members can be displayed by issuing "SPR" or "R" command on the IVP Task that Starts IMS (IV_P215J for DB/DC). "SPR" is an acronym for Special Processing Routine.

Refer to Chapter 7, "Type-2 commands and enhanced command environment" on page 115 for detailed information about the enhanced command environment.

2.4.5 DFSIVPEX IVP utility to export and import the variables

There are over 280 variables that can be set by a user in the IVP variable gathering phase during installation. Specifying these values can be a tedious and time consuming task. IMS

Version 9 introduces a new IVP utility, DFSIVPEX, that can save the variables from one release and reload them into the IMS Version 9 IVP. The utility uses the table data set IMS.INSTATBL which contains the ISPF tables that are read and updated by the IVP dialog.

When using the export capability, the IVP variables are copied from the INSTATBL data set associated with the high level qualifier specified in the panel and written to the export data set name that is also identified. The export option will work on any supported IMS IVP release.

When using the import capability, the variables are written from the export data set name to the table data set associated with the specified high level qualifier. This option only reloads the variables into the IMS Version 9 IVP.

In the Variable Gathering phase of the IVP, the panel provides an action code option to either Import or Export the variables. The Figure 2-4 shows that an Import is being requested to a target IMS Version 9 IVP environment.

You can invoke the DFSIVPEX either from IMS Application Menu by selecting option 6 or by issuing the following command from ISPF option 6. Replace hlq in the example by your high level qualifier of IMS system libraries.

EXEC 'hlq.SDFSEXEC(DFSIVPEX)' 'HLQ(hlq)'

IVP Variable Gathering (LST Mode) - DBT . Row 1 to 12 of 157
Command ===> Scroll ===> <u>CSR</u>
Action Codes: Chg Doc eNt Rfr Imp Exp CHG is default if item modified
Variable = Value
Var-Title
imp IXUIVPHQ = IMS910G
IVP - High level DSNAME qualifier for IVP (IVP) data sets
* IXURLMHO = IMS910G
IVP - High level DSNAME gualifier for IRLM (RLM) data sets
* IXUDLBHO = IMS910G
IVP - High level DSNAME gualifier for IMS DLIB (DLB) data sets
* IXUSYSHO = IMS910G
IVP - High level DSNAME gualifier for IMS System (SYS) data sets
* IXUEXEHO = IMS910G
IVP - High level DSNAME gualifier for Execution (EXE) data sets
* IXUUTLHQ = IMS910G

Figure 2-4 Import function

The dialog requests the name of the IVP export data set that was used to save the variables from another system and then compares the export versus import environments. If they do not match, an option is provided to cancel the import or to continue.

2.4.6 IVP help text enhancements

IMS Version 9 provides a customized help text for the IVP steps. In prior releases, generic names (for example, IMS.SDFSRESL) were always used to represent data set names and other items. This sometimes caused confusion and errors because the names in the help text did not necessarily match the names in the user environment. IMS Version 9 resolves this ambiguity by displaying the actual user-defined high level qualifiers (for example, IMSPSA.IM0B.SDFSRESL) as specified in the variable gathering phase.

The addition of color to the help text is also designed to emphasis important information that may otherwise be missed.

2.4.7 JES3 improvements in IVP

The IMS IVP process has historically experienced problems when running in a JES3 environment due to the IVP support of a single character job class where JES3 supports job classes that can be from one to eight characters.

In IMS Version 9, the job class variables IXUJCLAS (JOB statement CLASS parameter for IVP jobs) and IXUJCLS2 (JOB statement CLASS parameter for SYSDEF STAGE2 jobs) have been modified based on the variable IXUJESTY (JES version) for a particular environment.

If IXUJESTY is set to JES2 then the IVP will continue to function as before:

- ► The job class variables will accept only one character.
- ► The "CLASS=" parameter will be added to the JOB card.

If IXUJESTY is set to JES3 then:

- ► The job class variables will accept up to 8 characters.
- The "CLASS=" parameter will not be added to the JOB card, rather a //*MAIN CLASS= statement will be added to the JCL following the JOB card.

Another problem for the JES3 users has been that the IVP jobs use IDCAMS to define data sets in one step and reference these data sets in later steps with DISP=SHR. This can cause problems in a JES3 environment. In IMS Version 9, the DISP processing for all jobs that allocate data sets will be changed as follows:

- The data sets will be allocated using IEFBR14 with a DISP=(,PASS).
- Any references to the data set in subsequent job steps will also use a DISP of PASS.
- ► The last DD statement to reference the data set will catalog the data set as needed.

This change applies to both JES2 and JES3 environments.

2.4.8 IVP data set allocation enhancements

IMS Version 9 introduces some enhancements to facilitate data set allocations.

The first change deals with the use of SMS. In prior releases, SMS allocation of data sets was only done for the IVP sample application data sets. This has now been extended to allow SMS storage and management class parameters to be used when allocating all data sets.

The second enhancement affects VSAM allocations. In many customer shops, VSAM data sets have specific high level qualifiers that differ from those of non-VSAM data sets. For these environments, the IVP jobs had to be converted to accommodate the change. This task was often frustrating, time consuming and error prone. IMS Version 9 addresses the issue by introducing a new variable IXUVSMHQ as part of the variable gathering phase. This is a required variable and will be used when allocating and referencing VSAM data sets.

2.4.9 IVP enhanced dump formatter setup

There are additional steps to complete and test the installation of IPCS for IMS dumps. The new steps are the following:

- IV_D216T Example for IPCS ISPF data set concatenation.
- IV_D217T Example for defining MVS dump options.
- IV_H311T Task for bringing up IPCS session for sample dump in DB/DC and XRF environments.
- IV_J309T Task for bringing up IPCS session for sample dump in DCCTL environment.
- IV_G309T Task for bringing up IPCS session for sample dump in DBCTL environment.

2.4.10 Miscellaneous IVP changes

The following changes in IVP are also introduced with IMS Version 9:

► Remove TSO VTAM definitions from VTAM APPL definition samples

The IVP dialog member IV_D301T now contains VTAM APPL definition samples only for IMS. The VTAM definitions for TSO have been removed because they are not needed. For the IVP to work, TSO had to have already been installed. Additionally, for DBCTL environments where IMS VTAM definitions are not needed, IV2D301T will not be presented.

Allow a blank value for variable IXUUSRID

In prior releases, when IXUUSRID was defined in the variable gathering phase without a value, the IVP dialog automatically assigned it the value of the submitter's TSO id. This caused the dialog to include USER= parameters in the job cards of all the JCL members of INSTALIB. To explicitly prevent the USER= parameter from being included in the job card, the variable IXUUSRID had to be explicitly set to blank every time the variable gathering phase was run. In IMS Version 9, the IVP dialog recognizes and accepts a null value.

2.5 Syntax Checker enhancements

The Syntax Checker provides an ISPF user interface that enables you to define, verify, and validate parameters and their values in the DFSPBxxx member of IMS.PROCLIB. With IMS Version 9, new IMS Version 9 parameters are supported, as well as IMS Versions 7 and 8. Additionally, checking is now provided also for the following two PROCLIB members:

- Data communications options member, DFSDCxxx
- CQS address space member for shared queues, DFSSQxxx.

With Syntax Checker, you can:

- View default values for parameters.
- Use the new select command "P" for process which enables you to interrupt the processing of the current member and begin processing the selected member.
- ► Update the DFSPBxxx members for new IMS Version 9 parameters.
- ► Process the DFSPBxxx, DFSDCxxx and DFSSQxxx members.

Depending on the parameter member being processed, additional information such as the release of IMS and the type of control region may be necessary to correctly process the parameters. If the Syntax Checker cannot determine the information required, the user will be prompted for the information through additional panels. Syntax Checker can be used to assist with IMS release to release migrations when converting PROCLIB members.

New with IMS Version 9 is that you can process the DFSPBxxx members for FDBR and DLI/DBB environments. Figure 2-5 on page 25 shows the selection panel with new options 4 and 5.

```
      Eile Help

      IMS Parameter Syntax Checker

      Command ===>

      Enter the following information and press enter.

      IMS Release
      1. IMS 9.1

      2. IMS 8.1
      3. IMS 7.1

      Type of Control Region
      1. DBCTL Control Region

      2. DCCTL Control Region
      3. DB/DC Control Region

      3. DB/DC Control Region
      4. FDBR Region

      5. DLI/DBB Batch (IMS 9.1 only)
```

Figure 2-5 Environment selection panel for Syntax Checker

Figure 2-6 is an example of the Syntax Checker keyword display panel. It displays the keywords and values and indicates any errors. IMS Version 9 adds the option to show the default values for keywords. F6 key provides the toggling capability which changes the display back and forth from displaying the defaults to not displaying them.

<u>F</u> ile <u>E</u> dit ⊻iew <u>H</u> elp			
Command ===>IMS 9.1 Parameters for DB/DC			
Press enter (without other input)	to check for errors.		
Data Set Name : IMSPSA.IM0B.PROCLIB(DFSPB01N) IMS Release : 9.1			
Sel Codes: C = Comment D = Delete P = Process / = Select			
Sel Keyword Value	Description More: +		
- ALOT = , APPC = N APPLID1 = IMS1B ARC = 01 ARMRST = N ASOT = , AUTO = N BSIZ = 4096 - = , CIOP = , CMDMCS = Y CRC = 0	 1440 ETO Auto Logon Off Time N Activate APPC/IMS (Y N) IMS VTAM NODE NAME O1 Automatic Archive: 1-99, 0 - NOT Autom. Y DETERMINES AUTOMATIC RESTART FOR THIS IMS 1440 ETO Auto Signoff Time N Automatic Restart Desired (Y N) Data Base Buffer Size 256 Number of CCB Hash Table Slots "26-1" CIOP Pool Upper Limit N ALLOWS COMMAND ENTRY FROM E-MCS CONSOLE / COMMAND RECOGNITION CHARACTER - SAME FOR 		
_ CSAPSB = 300 _ DBBF = 600 _ DBFX = 50 _ <u>DBRCNM</u> = IM1BDBRC _ DBWP = 60	"2G-1" DLISAS: CSA PSB Pool Size 10 Number of Database Buffers 0 Num. DB Buffs available at FP Reg Start DBRC DBRC Problib Member Name "2G-1" Database Work Pool Size		

Figure 2-6 Syntax Checker sample

The new "P" line command option stands for process and is valid on all keywords whose value is used to identify another member in the IMS.PROCLIB data set. This causes Syntax Checker to interrupt the processing of the current member and begin processing the member selected. At the completion of the processing of the selected member, the user can select F3 key to return processing to the original member that was being processed prior to the interruption.

If the member selected is not processed by Syntax Checker a panel will be displayed asking if the member should be edited using the ISPF editor (a blank member will be created if the member doesn't exist). The member can be edited in the current data set or in a different data set.

2.6 Documentation changes

The following changes and additions have been made to IMS manuals:

- New books:
 - IMS Version 9: IMS Connect Guide and Reference, SC18-7821
 - To complement the IMS Version 9 library, a new book will be available in January 2005:

An Introduction to IMS: Your Complete Guide to IBM's Information Management System, by Dean Meltz, et. al. Prentice Hall. ISBN 0131856715.

- New chapters:
 - Integrated HALDB online reorganization is described in *IMS Version 9: Administration Guide: Database Manager,* SC18-7806.
 - New commands are in command reference manual, *IMS Version 9: Command Reference*, SC18-7814
 - New part in DBRC manual, IMS Version 9: Database Recovery Control (DBRC) Guide and Reference, SC18-7818
 - New exits in customization guide, IMS Version 9: Customization Guide, SC18-7817
- Changed title (new name):
 - IMS Version 9: IMS Java Guide and Reference, SC18-7821
- Reorganization:
 - IMS Version 9: Installation Volume 1: Installation Verification, GC18-7822
 - The chapter "DLIModel Utility" moved from IMS Java Guide and Reference to IMS Version 9: Utilities Reference: System, SC18-7834
 - The DLIModel Utility messages that were in IMS Java Guide and Reference have moved to IMS Version 9: Messages and Codes Volume 1, GC18-7827

When ordering IMS Version 9, you are entitled to the following books (one hardcopy included per order):

- IMS Version 9: Installation Volume 1: Installation Verification, GC18-7822
- IMS Version 9: Installation Volume 2: System Definition and Tailoring, GC18-7823
- Licensed Programming Specification, GC18-7825
- IMS Version 9: Release Planning Guide, GC17-7831
- Licensed Product Kit, LK3T-7213 (CD)

The following manuals are available as a soft copy only:

- ► IMS Version 9: Base Primitive Environment Guide and Reference, SC18-7813
- IMS Version 9: Common Queue Server Guide and Reference, SC18-7815
- IMS Version 9: Common Service Layer Guide and Reference, SC18-7816
- ► IMS Version 9: IMS Java Guide and Reference, SC18-7821

All remaining books and additional entitled books are available for a fee.

2.6.1 IMS Information Center

DB2® Information Management Software Information Center for z/OS Solutions contains documentation for IMS and IMS Tools. It can be found in the Internet at:

http://publib.boulder.ibm.com/infocenter/dzichelp/index.jsp



3

Integrated HALDB online reorganization

It has been the goal of most database administrators to avoid having to work an overnight or weekend shift to perform database reorganization. It has also been the goal of many Chief Information Officers to achieve the same thing, due to an outage that must be taken during a reorganization and its potential impact on business operations. Availability of data in a database should not be affected by reorganization. All of the data should be available all the time.

IMS Version 9 helps both groups of people achieve their goal — the ability to reorganize a database without taking it offline. Integrated HALDB online reorganization (OLR) provides the capability to reorganize your HALDB databases as a background process, while they continue to be read and updated by online and batch programs. OLR is provided as part of the base of IMS Version 9, and is therefore available for immediate use in your organization.

The benefits of using integrated HALDB online reorganization include:

- Elimination of database outages for reorganization
- 100% availability with zero outages of your database during reorganization
- Applications are unaffected; they never get data unavailable conditions due to online reorganization
- Full integrity and recoverability are maintained

3.1 Overview of integrated HALDB online reorganization

In the beginning, when data is initially loaded into an IMS database, the physical location of each segment is chosen by IMS to minimize the number of I/Os needed to access records and segments in the database. As programs modify, insert, and delete segments over time, the cost of accessing the data in the database tends to increase, leading to longer processing times for application programs accessing these databases.

Database reorganization is the process of relocating segments in a database, with the goal of optimizing the I/O cost for accessing the data in the database. In the past, an offline reorganization process has been necessary for full function databases, including HALDB. This process reads every segment in the database, writes them to a sequential data set, re-initializes the database data sets, and reloads the data into the database in this new sequence. With this process, reorganization needed to be an offline process. That is, access to the database was stopped prior to the reorganization, and started again only after the reorganization had completed and an image copy (preferably) had been taken.

Integrated HALDB online reorganization (OLR) allows you to reorganize your HALDB databases while they are concurrently accessed for read or update processing by application programs. It can be used for PHDAM and PHIDAM database organizations, in an IMS TM/DB or DBCTL environment. The databases can also be reorganized when being accessed in a data sharing environment, as well as being available to Extended Recovery Facility (XRF) and Remote Site Recovery (RSR) environments.

The OLR process does not support changes to the data definitions for HALDBs. It provides only reclustering and space distribution advantages, although DBDS space allocation changes are allowed.

A reorganization is initiated by operator command, using either the classic type-1 or the new type-2 commands. The progress of the reorganization can also be checked through operator command.

The pace of an online reorganization is determined by the RATE specified on the OLR operator commands, system resources and system utilization. The amount of updates to the IMS log and system contention can also affect the speed at which an OLR runs. The rate can be changed when adjustments are desired depending on system contention (that is, slow down the OLR) or lack of system contention (i.e., speed up the OLR). The reorganization process can also be temporarily paused if required, and resumed at some later time.

OLR uses two sets of database data sets during the reorganization process. One set of database records, known as the unit of reorganization (UOR), is read from the input data sets (initially the A-J and X, if PHIDAM, data sets) and then written to the output data sets (initially the M-V and Y, if PHIDAM, data sets), as shown in Figure 3-1 on page 31. When all the segments in the current UOR have been processed, the current location (cursor) is moved forward, and the set of records in the next UOR is read. A subsequent reorganization will read the M-V (and Y, if PHIDAM) data sets as the input, and write the A-J (and X if PHIDAM) data sets. IMS, through DBRC, automatically and transparently takes care of which data sets are the active copy of the database. Both sets of data sets are used during OLR. At the end of the reorganization, the old data sets may be discarded (to save DASD space).




Figure 3-1 Data sets in use during an online reorganization

Concurrent IMS updates are allowed while records are moved and reorganized by OLR. IMS determines whether to expect a given database record to be in either the input or the output data sets based on whether the record is either beyond or prior to the cursor, as shown in Figure 3-2. This is completely transparent to all application programs accessing the database.




Figure 3-2 Use of the cursor when reorganizing from the input to the output data sets

For possible recovery of either an input or an output data set, all database changes are logged. The indirect list data set (ILDS) list entries (ILEs) are updated with new target RBAs, but these changes are not logged. Databases can therefore be recovered using the standard recovery utilities or the IMS Database Recovery Facility (DRF) tool. OLR also provides full DBRC support. Note that a standard batch database reorganization does not log any changes.

Databases are reorganized at the partition level, with each partition independently reorganized. This provides flexibility; partitions can be reorganized in parallel, and it is not required to reorganize the whole database at once. The online reorganization runs in the DLISAS address space, with a separate process (ITASK) used for each partition being reorganized.

OLR can be used to reorganize the PHDAM data component, the PHIDAM data component and primary index, including HALDBs which have secondary indexes and logical relationships. Database with secondary indexes can be reorganized, but the secondary index (PSINDEX) cannot be reorganized. In a data sharing environment, online reorganization may be run on any data sharing system, with concurrent access and update allowed to these databases from other systems.

Before the OLR starts, there is a single active set of data sets for the HALDB partition - either the A-J (and X) set or the M-V (and Y) set. The data sets in the other set contain no useful

information. At the end of the OLR initialization process, the OLR status of the partition is recorded in the RECON with a cursor-active status. Once the OLR initialization process has completed, the original active set of data sets is treated as the input set and the other (paired) set becomes the output set. Both sets of data sets are active, since they both contain active data as you can see in Figure 3-2 on page 31.

After all database records have been copied, the input data sets become the inactive set. Unless an initial load or an offline reorganization is done, successive OLRs for the partition then alternate between the two sets of data sets.

At the completion of OLR, the input data sets and their contents become obsolete. Image copy and recovery records are no longer applicable for inactive data. The records of prior image copies and log data of inactive data sets remain in the RECON, and can be used for time stamp recovery if required.

3.2 Details of OLR processing

In this section, we describe the detailed setup and processing of HALDBs for OLR.

3.2.1 Data sets used by OLR

OLR extends the group of data sets required to support HALDB. Prior to IMS Version 9, HALDB databases were stored in one or more database data sets. These data sets, usually referred to as the A-J (and X) data sets, were used to store the segments and indexes, and the primary index data, as shown in Figure 3-3.




Figure 3-3 Single set of data sets in a HALDB that is not OLR capable

OLR requires the use of two sets of database data sets for each HALDB that is capable of being reorganized by OLR, as shown in Figure 3-4 on page 33. The data is read from the current set of data sets (initially the A-J and X data sets), and written to the other set of data sets (the M-V and Y data sets). The A-J, X and M-V, Y data sets swap roles at the end of each reorganization.




Figure 3-4 Two sets of data sets in HALDB that is OLR capable

Before or after reorganization, the active data sets are either the A-J (and X) data sets, or the M-V (and Y) data sets. These are the data sets being accessed by applications, and the selection of data sets to use is handled transparently by IMS. The inactive data sets are the data sets which are not being accessed by applications.

During a reorganization, all data sets (A-J, X and M-V, Y) are active data sets. The input data set contains the unreorganized data, including both active and inactive data. The output data set contains reorganized data which are active.

The cursor is the dividing line between active data and inactive data. A diagram of the cursor is shown in Figure 3-2 on page 31. The cursor is only used while reorganization is in progress or suspended.

3.2.2 Reorganization by copying segments

The process of database reorganization is simply the relocation of segments in the database, with the goal of reducing the I/O cost when later accessing the segments.

Reorganization is performed by copying segments from their current location to their optimal location in the database. With OLR, segments are read from one set of HALDB data sets (for example A-J, and X), and then written (inserted) back to the other set of HALDB data sets (for example M-V, and Y). The ILDS entries for the secondary index and logical relationship targets are also updated during this process.

The reorganization process is similar to that of a long-running BMP. Segments are read from the database, processed by the application (in this case, OLR), and then written back to the database. To protect the integrity of the information in the database, locking protocols are used to prevent simultaneous access to the data.

Similarly, when segments are copied from the old to the new data sets during an online reorganization, all updates are captured to the IMS logs. Therefore, IMS databases can be recovered across the time of an OLR.

3.2.3 Current position during a reorganization - the cursor

The cursor is used to track the progress of the reorganization through the database, by pointing to the last committed reorganized record. For PHDAM databases, the cursor is a root anchor point (RAP) relative byte address (RBA). All records chained from it and previous RAPs have been copied to the output data sets. For PHIDAM the cursor is a root key. All records with this key and lower keys have been copied to the output data set. The cursor is stored in the block after the first bit map in the input data set.

Figure 3-5 shows the usage of the cursor during a reorganization.

3.2.4 Application access during OLR

When an application is reading data from a HALDB which is being reorganized, the selection of data set to be read is based on the cursor value.




Figure 3-5 Location of access to a database during online reorganization

When reading the database shown in Figure 3-5, where the cursor is on record 6, segments from record 1 through 6 are accessed from the M data set. Segments from record 11 will be accessed from the A data set. Any program attempting to access records 7 through 10 will wait for the online reorganization to finish processing the current unit of reorganization, due to the lock held by online reorganization. When OLR has completed processing that UOR, the locks are released and the program accesses the reorganized information from the M data set. The example is not correct for a PHIDAM with TB pointing. In that case record 6 would be locked too.

3.2.5 Completion of reorganization

When OLR completes, the previously active data sets (A-J and X in our example) become the inactive set, and may be deleted. The other set of data sets (M-V and Y data in our example)

become the active set, and the cursor-active status is reset to inactive. Next time this partition is reorganized, online reorganization will reorganize from the currently active M-V and Y data sets to the A-J and X data sets.

3.3 Setting up for OLR

The basic process for OLR involves two parts:

Setup

This means allowing OLR for the selected databases, and optionally allocating the second set of data sets.

Start

Issuing the commands to invoke OLR.

3.3.1 DBRC setup

Online reorganization must be enabled through DBRC for each of the HALDB databases you want to be able to process with online reorganization. This is achieved by using the **OLRCAP** (online reorganization capable) parameter of either the **INIT.DB** or **CHANGE.DB** command in DBRC. The **OLRCAP** attribute allows online reorganization for all partitions of this database. OLRCAP is the default for new HALDBs registered in IMS Version 9. You can also choose to register a HALDB database as not OLR capable through the use of the **OLRNOCAP** parameter.

If you register a HALDB as capable of being accessed by online reorganization, this database can no longer be accessed from, or even visible to, either an IMS Version 7 system, or from an IMS Version 8 system which has not had the OLR coexistence SPE installed.

The *OLRNOCAP* attribute allows a HALDB to be accessible from IMS Versions 7, 8 and 9. It also prevents online reorganization for this HALDB.

DBRC will check the authorization status for a database before it will allow the *OLRCAP* flag to be set. The command is disallowed if any of the database's partitions are authorized unless MINVERS of 9.1 is set in the RECON. A database cannot have the OLRNOCAP value set if online reorganization is active or if the M-V data sets are active.

To enable OLR for all HALDB databases, the command CHANGE.DB ALL OLRCAP can be used. The command skips any HALDB databases that are authorized, and issues warning message DSP0195I for any skipped databases and their partitions. The command CHANGE.DB ALL OLRNOCAP is not allowed.

3.3.2 Output data set creation

To simplify the OLR process for a HALDB partition, each of the output data sets can be created automatically by IMS. For each data set group defined in the DBD and for the primary index of a PHIDAM database, the output data set is created if it doesn't already exist as a cataloged data set. The indirect list data set (ILDS) is not created automatically because there is not a corresponding output version of it.

In order to reserve approximately the same amount of space that was reserved for the input data set regardless of the DASD types involved, the output data set's space is requested as a number of OSAM blocks or VSAM records.

If an input data set is SMS-managed, then the corresponding output data set is SMS-managed as well, and the storage class used to create the output data set is the same

as that of the input data set. If the input data set has extents on only one DASD volume, the output data set is also created on a single volume. If the input data set has extents on more than one DASD volume, the output data set is created to allow the same number of volumes. If the storage class of the input data set has the guaranteed space attribute, the primary space allocation will be taken on each of the volumes when the output data set is created.

For a non-SMS-managed input data set, IMS automatically creates the output data set only if the input data set is a on a single volume. If you need a multi-volume non-SMS-managed output data set, you must create the data set yourself before starting the OLR.

If an input data set is not SMS-managed and is a single-volume OSAM data set, the output data set is created as though UNIT=SYSALLDA has been specified on a DD statement. This causes the data set to be created on a storage volume or, if no storage volume is available, on a public volume.

If an input data set is not SMS-managed and is a single-volume VSAM data set, the output data set is created on the same volume as the corresponding input data set. This limits the usefulness of automatic data set creation for a non-SMS-managed VSAM data set, because there may not be enough space. Not having enough space is one of the reasons why the reorganization might not start. Note that the situation of not having enough space is not unique to the non-SMS-managed VSAM case; it applies to any type of data set. However, this problem is certainly more likely to occur with non-SMS-managed VSAM because there is only one volume on which IMS tries to create the output data set.

Optionally, you can create and catalog the output data sets prior to the start of online reorganization. You may use preallocation if you want to allocate the data sets on specific volume, change the space allocation, the number of blocks/Cls, the primary and secondary allocations, or, for a PHIDAM primary index, the free space percentage. Note that the PHIDAM primary index Cl size cannot be changed during an OLR.

3.4 Starting online reorganization

An online reorganization is started through operator commands. The command can be either a type-1 or type-2 command. The format of type-1 command is:

/INIT OLREORG NAME(partname1)

The format of the type-2 command is:

INIT OLREORG NAME(partname1,partname2,...)

Both of these commands have two keywords. They allow you to set the rate of execution and, optionally, to not to delete the input data sets at the completion of the reorganization (delete option is the default).

There are the following steps in the start process for online reorganization of HALDBs:

- Initiation
 - Validation
 - DBRC actions
 - Output data set initialization
- Start processing

3.4.1 Initiation

OLR initiation process consists of the following parts:

Validation

Before IMS will begin the online reorganization of a HALDB, the status of the HALDB master and partition is checked. OLR will not start while the partition or master is stopped, locked, /DBRed, /DBDed, or opened with ACCESS=RD or RO. Reorganization will not start if IMS is being shutdown.

DBRC actions

Once a partition has completed the OLR validation process, IMS updates the RECON to indicate the partition is to be processed by OLR. The IMS system performing this online reorganization is recorded in the RECON partition record for this database. The output data sets are registered in the RECON if not already registered, and an ALLOC record is created for the output data set (A or M), and a REORG record is created with a start time equal to the ALLOC time.

For each partition being reorganized, the RECON is updated to indicated that a cursor is active. That is, a reorganization is in progress and must be completed. The IMSID for the system owning the reorganization of this partition is also recorded in the RECONs. Lastly, if running in a data sharing environment, each of the sharing subsystems are notified that a "cursor is active" for the partition.

Output data set initialization

After OLR has been started, and after any nonexistent output data sets are created automatically and any preexisting ones are validated by IMS, the output data sets are initialized. Block 1 contains the reorganization number, which is one greater than the previous reorganization number. Block 2 contains the cursor to be used for the reorganization as follows:

- For PHDAM databases, the cursor is the RBA of last PHDAM RAP reorganized.
- For PHIDAM databases, the cursor is the key of the last PHIDAM root segment reorganized.

3.5 Reorganization process

The online reorganization process consists of the following tasks:

1. Determine the size of unit of reorganization (UOR)

The first part of the reorganization process is to determine the size of the unit of reorganization (UOR). The algorithm used is an internal function, and is designed to minimize the impact of OLR processing on other applications accessing this database. During a reorganization, the size of the UOR may be dynamically adjusted to prevent long elapsed times. This is performed internally by IMS, with statistics on the quantity of data processed in each UOR captured to the x'2950' log record, described further in 3.9.1, "Logging" on page 43.

2. Get database record locks for the UOR

Database records in the UOR are locked by OLR. For a PHDAM database, locks are taken for each of the RAPs in the UOR. For a PHIDAM database, locks are taken for all the records in the UOR.

If a lock request cannot be granted, online reorganization does not wait. Instead, it ends the UOR at the previous PHDAM RAP or PHIDAM key. There is one exception. If the lock is the first one in the UOR, online reorganization waits to get the lock. Obviously, it would do no good to end a UOR without having processed any records.

If online reorganization is the victim in a deadlock, dynamic backout of the UOR is done and the reorganization continues at this UOR. The user does not have to restart the reorganization. This is similar to what happens when an online IMS transaction is the victim in a deadlock.

3. Read and copy each segment in the UOR

Segments are read from the input data sets, and are inserted into the output data set using the space management algorithm for load mode. When space is not available for a segment in the most desirable block, space may be found for it in a block that is already in the buffer pool. This tends to produce writes in physical sequential order, but there may be exceptions.

In a data sharing environment, block locks are acquired to prevent the sharing IMSs from updating the blocks in the UOR while OLR is updating them.

All segments moved during the reorganization process are logged for recovery purposes, and their entry in the ILE is also updated if necessary.

This process is repeated until the end of the UOR is reached (that is, the proposed cursor value is reached).

4. Commit UOR

All changes made to the UOR are committed. IMS then updates the cursor and notifies any data sharing systems of the new cursor value as part of this notify. IMS purges the buffers through the standard processes, writes the x'3730' log records, and finally release all the locks.

5. Repeat process until end of partition is reached

Keep doing all the above until the end of the partition is reached.

3.6 Normal termination and cleanup

When all data has been reorganized, OLR notifies the sharing systems that the reorganization has completed. The sharing subsystems close and deallocate the input data sets before responding to the notify. IMS closes and deallocates the input data sets, closes the input ALLOC record with the STOPTIME, and cleans up the RECON records:

- Set the A or M data set indicator
- Set the cursor to inactive
- Reset the reorganization ownership to 'none'
- Update the REORG record (stoptime = DEALLOC time).

When OLR receives notification responses from the data sharing subsystems, it deletes the data sets unless the NODEL option was specified on the OLR initiation command. OLR waits for up to 5 minutes for notification responses. If no response is received, OLR tries to delete the input data sets, but if it can't do so, due to another system holding them, then OLR just ends normally. The user can optionally delete the data sets at a later time if required.

3.7 Pausing an online reorganization

Once an online reorganization has commenced and the cursor-active status has been recorded, the partition has current data stored across both the A-J (and X) set of data sets as well as the M-V (and Y) set. From this point, the reorganization must eventually be run through to completion. If it becomes impossible to complete an online reorganization for any reason, an offline reorganization must be run in order to reset the online reorganization settings. Note that offline reorganization reload always loads the A-J data sets. Also, the partition cannot be accessed unless both sets of data sets are available if an OLR has not completed.

The online reorganization can be suspended and resumed (terminated and re-initiated) as often as desired through operator commands, as described in 3.8.3, "Terminate an online reorganization" on page 40 and 3.8.1, "Start an online reorganization" on page 39 respectively.

3.8 OLR commands

IMS Version 9 has added a number of new commands for OLR. The commands used with OLR are:

- ► INITIATE and /INITIATE
- ► UPDATE and /UPDATE
- ► TERMINATE and /TERMINATE
- QUERY and /DISPLAY

Both type-1 and type-2 commands have been added, and may be used interchangeably.

Type-1 commands for OLR

The type-1 commands for OLR are /INITIATE, /UPDATE, /TERMINATE and /DISPLAY. They can be entered via a z/OS console, a master terminal, an LTERM, a CMD or ICMD call, or through OM. Type-1 commands are passed to IMS AOI exit, and are logged to the secondary master terminal.

Type-2 commands for OLR

The type-2 commands for OLR are **INITIATE**, **UPDATE**, **TERMINATE**, and **QUERY**. These commands can be entered via TSO SPOC, the IMS Control Center, a REXX exec, or a user program. The responses are in XML format.

3.8.1 Start an online reorganization

The **INITIATE** command is used to start an online reorganization, and can also be used to reinitiate a previously terminated reorganization.

Type-1 command:

/INITIATE OLREORG NAME(partname1)

```
SET(RATE(100 nn))
```

OPTION(DEL NODEL)

Type-2 command:

INITIATE OLREORG NAME(partname1, partname2,...)

```
SET(RATE(100 nn))
```

```
OPTION(DEL|NODEL)
```

The parameters are:

NAME

Partition name(s).

Only one name may be specified when a type-1 command is used.

RATE

Rate of reorganization.

The **RATE** parameter allows you to alter the pacing of the reorganization. Specifying **RATE(100)** allows OLR to runs at maximum speed. If you specify a rate of less than 100, online reorganization waits after each commit so that average speed of reorganization is nn% of the unconstrained speed. **RATE(100)** is the default.

Examples: For RATE(50); after each commit, reorganization waits for the same period of time as it took to process the previous UOR. If the last UOR was reorganized in 1 second, OLR would wait for the same elapsed time (1 second), run for 1 second, wait 1 second, and so on. For RATE(25); after each commit, OLR waits for 3 times as long as the last interval took. So if a UOR processed in, say, 1 second, OLR would wait 3 seconds, run 1 second, wait 3 seconds, and so on.

OPTION

Whether or not to delete the inactive (original input) data sets upon completion of the reorganization. **OPTION(DEL)** is the default.

3.8.2 Modify a reorganization in progress

Both type-1 and type-2 commands can be used to modify a reorganization in progress.

Type-1 command:

```
/UPDATE OLREORG NAME(partname)
SET(RATE(100|nn))
OPTION(DEL|NODEL)
```

Type-2 command:

UPDATE OLREORG NAME(* | partname1, partname2,...)

```
SET(RATE(100|nn))
```

OPTION (DEL NODEL)

The parameters for both the type-1 and type-2 commands are the same as for the **INITIATE** command shown in 3.8.1, "Start an online reorganization" on page 39.

3.8.3 Terminate an online reorganization

Both type-1 and type-2 commands can be used to suspend an online reorganization. The reorganization can be restarted at any IMS in the data sharing group some time in the future with the **INITIATE** command.

Type-1 command:

/TERMINATE OLREORG NAME(partname)

OPTION(FORCE ABORT)

Type-2 command:

TERMINATE OLREORG NAME(*|partname1,partname2,...) OPTION(FORCE|ABORT)

The parameters are:

NAME

Partition name(s).

Only one name may be specified when a type-1 command is used.

OPTION

When to terminate the OLR.

When the **OPTION** parameter is omitted, OLR terminates at the end of the current UOR. When **OPTION(FORCE)** is specified, OLR ends at the next PHIDAM root or PHDAM RAP. When **OPTION(ABORT)** is specified, OLR terminates immediately with a user abend, and the output of the current UOR is backed out.

After processing a **TERMINATE** command, the cursor is still active in the RECONs. Both sets of database data sets are used until the OLR is subsequently completed. The reorganization can be resumed by any IMS in the data sharing group by using the **INITIATE OLREORG NAME(partname)...** command.

The **DEL NODEL** and **RATE** options, specified at the time the OLR was initiated, are not retained after the **TERMINATE** command, although they may be specified again on the **INIT OLREORG** command used for resumption of the OLR.

3.8.4 Display reorganizations in progress

IMS Version 9 provides a number of commands to query reorganizations in progress.

Type-1 command:

/DISPLAY DB name1 name2 ... ALL

The response shows 'OLR' in the CONDITIONS field if the partition has a reorganization in progress locally.

Type-2 command:

QUERY OLREORG NAME(* partname1, partname2,...)

STATUS (RUNNING OWNED NOTOWNED UNKNOWN)

SHOW (ALL | RATE | BYTES | STATUS)

The parameters are:

NAME

Partition name(s), optional.

The default is "NAME(*)" which returns all partitions with reorganizations in progress.

STATUS

Optional, show partitions with reorganization status.

RUNNING

Show all online reorganizations running on IMSs to which this command is routed.

OWNED

Show those reorganizations owned by other IMSs, as well as those "RUNNING".

NOTOWNED

Show those reorganizations that are suspended, and thus not owned by any IMS.

UNKNOWN

Show those with unknown status (not authorized on this subsystem).

SHOW

Specifies the output fields to be displayed.

RATE

Returns the RATE value for each reorganization.

BYTES

Returns the number of bytes written to the output data sets.

STATUS

Returns status of RUNNING, OWNED, NOTOWNED, or UNKNOWN for each reorganization.

ALL

Returns output from RATE, BYTES, and STATUS options

There is no equivalent type-1 command which shows all the information available with the type-2 **QUERY** command shown in Example 3-1. The type-1 command /**DIS DB OLR** can be used to display all partitions that have reorganizations in progress locally. The OLR keyword cannot be combined with other conditions.

Example 3-1 QUERY OLREORG command example

QRY OLREOR	G NAME(PVHDJ	15A) S	SHOW(BY	TES)	
Response:					
Partition I	MbrName C	C BY	TES MOV	ED	
PVHDJ5A	IMS2	0	1256	256	

Example 3-2 shows an example of type-1 command /INIT OLREORG.

Example 3-2 Type-1 /INIT OLREORG command example

/INIT OLREORG NAME(PDHDOKA) SET(RATE(50)) Response: DFS058I 12:08:07 INITIATE COMMAND IN PROGRESS DFS2970I - OLR STARTED FOR NAME=PDHDOKA DFS0725I INIT OLREORG COMMAND FOR DB DBHDOKA COMPLETE.

Example 3-3 shows an example of /DIS DB OLR command.

Example 3-3 Display online reorganization status

/DIS DB OLR Response: DATABASE PART RATE BYTES STATUS DBHDOKO1 PDHDOKA 50 86776 RUNNING *03099/120858*

Example 3-4 shows an example of /DIS DB command.

Example 3-4 Display database status command

/DIS DB PE	OHDOJA DBHDOKO1		
Response:			
DATABASE	TYPE TOTAL UNUSED	TOTAL UNUSED ACC	CONDITIONS
DBHD0J01	PHIDAM	UP	
PDHDOJA	PART	UP	ALLOCS, OLR
DBHDOK01	PHDAM	UP	
PDHDOKA	PART	UP	ALLOCS, OLR
PDHDOKB	PART	UP	ALLOCS
PDHDOKC	PART	UP	ALLOCS

3.8.5 Database commands

There have been changes to the following commands in an online reorganization environment:

- ► /DBD DB
- /DBR DB
- ► /STOP DB
- ► /START DB

If these commands are issued for partitions that are being reorganized, IMS rejects the command, and message DFS0488I RC=58 is issued.

Similarly, if the command is issued for a master database, the command is not processed if any partitions are being reorganized in the IMS processing the command. Message DFS0488I RC=58 identifies any partitions for which the commands have not been processed.

3.9 Logging, operations, I/O errors and restart

In this section, we discuss logging, system operations, I/O errors, and restart after system and reorganization failures in an online reorganization environment.

3.9.1 Logging

All updates to IMS databases being processed by online reorganization are logged, as though the OLR was an application program.

Scheduling and termination

IMS logs an X'08' record when scheduling an online reorganization. This is comparable to the scheduling of any application program (PSB schedule). The PSB name is x'F0' concatenated with the partition name. For example, the PSB name for partition ABCD is 0ABCD.

IMS logs an X'07' log record at the termination of an online reorganization.

Database change log records

IMS logs an X'50' record for inserts and updates to the output data sets. This is the same as the logging performed for an application program change to the database.

The DCB number has X'80' bit on for M-V (and Y) data sets, and the M-V data sets have the low order bit on in the RBA fields.

Commit processing

At the completion of processing for each UOR, IMS logs an x'3730' record.

OLR log records - x'29xx'

The online reorganization x'29xx' log records are as follows:

Log Record Type	Description
x'2900'	OLReorg command received

Log Record Type	Description
x'2910'	Ownership established
x'2920'	UPDATE OLR command processed
x'2930'	Output data set information
x'2940'	Cursor active
x'2950'	Cursor movement - includes statistics for UOR
x'2970'	Cursor inactive
x'2990'	Ownership relinquished

Statistics log record

Statistics for OLR are available in the x'2950' log records, and are recorded for each UOR. The information stored includes:

- Segments moved in this UOR
- Bytes moved in this UOR
- Total segments moved before this UOR
- Total bytes moved before this UOR
- ► UOR size in either RAPs (PHDAM) or roots (PHIDAM) depending on the partition
- Locks held by this UOR
- Start time of this UOR
- Execution time (elapsed time) of this UOR
- Time interval waited before this UOR (due to the RATE parameter).

3.9.2 IMS normal termination and restart

If OLR is running when IMS is shutdown with the /CHECKPOINT FREEZE or /CHECKPOINT DUMPQ command, IMS terminates OLR at the next commit point. The cursor remains active, and ownership is not relinquished.

If the /CHECKPOINT PURGE command is used to terminate IMS while an online reorganization is in progress, IMS waits for OLR to complete before terminating.

When IMS is normally restarted (/NRE) after termination with OLR active, IMS authorizes, allocates, and opens all input and output data sets, and resumes OLR automatically.

3.9.3 I/O errors

Should IMS encounter a write error during an online reorganization, IMS processes it in the same way as other database write errors. That is, IMS will write to the I/O toleration buffer, create an EEQE, notify any sharing subsystems, and continue processing the reorganization.

If there is a failure in an online reorganization, including a database read error, the processing of the UOR is ended, and dynamic backout is invoked to backout all the in-flight work for this UOR. IMS then relinquishes ownership of the online reorganization, but leaves the cursor still active indicating that both sets of the data sets are in use.

3.9.4 Resuming online reorganization

A suspended or failed reorganization may be restarted from the cursor position in the partition. The **INIT** or **/INIT** command is used, with any delete and rate options needing to be

specified again on the resumption, as they are NOT retained from the previous execution. This is done with the **OPTION(DEL|NODEL) SET(RATE(nn))** options on the **INIT** or **/INIT** command.

OLR may be restarted on any IMS system in a data sharing environment.

3.9.5 IMS or z/OS failure

If an IMS system fails with OLR active, OLR is treated much like an in-flight application program. Any locks held for the OLR in a data sharing environment become retained locks, with conflicting lock requests from other systems for these resources being rejected. These lock rejects are likely to cause applications to abend. Requests for shared locks, such as reads of the data in the UOR, are not rejected. This means that updates within the UOR are not allowed. Of course, the records in the partition which are not in the in-flight UOR are available. The cursor remains active and is used to find which data set holds the requested database records. Ownership of the OLR remains with the failed IMS system, since OLR cannot be restarted on another IMS.

Emergency restart backs out the in-flight UOR and releases the locks. Releasing the locks allows other data sharing systems to have access to the database without experiencing lock rejects. Emergency restart also resumes the OLR.

3.9.6 FDBR with OLR

Fast Database Recovery (FDBR) tracks an active IMS system in a data sharing environment. If the IMS system fails, FDBR quickly backs out its in-flight work and releases its locks. This applies to OLR as well as application programs. Releasing the locks allows other data sharing systems to have access to the database without experiencing lock rejects.

FDBR does not release the ownership of the OLR by the failed IMS system. Ownership is recorded in the RECONs. FDBR does not access the RECONs. Since ownership is not released, OLR cannot be resumed on another IMS system in the IMSplex. When you restart the IMS system, the OLR is not automatically resumed, because at the end of /ERE restart, IMS will notify DBRC that the partition is no longer authorized. IBM is looking for the way to change this so that the OLR will be resumed after a successful /ERE.

3.10 Utilities

The following utilities have been enhanced for the OLR environment:

- Image copy
- Change accumulation
- Database recovery
- Batch backout
- HD Unload and HD Reload.

3.10.1 Image copy

The Image Copy, Image Copy 2, and Online Image Copy utilities may be used to create image copies of HALDB data sets. These utilities have been enhanced to copy the active HALDB data set. It does not matter whether the control statements specify an A-J data set DDNAME or an M-V data set DDNAME, as the utility uses the information in the RECON to determine which data set is active and copies it. Dynamic allocation should be used for image copies. The utilities will dynamically allocate the active data set. If a DD statement is supplied

for an inactive data set, the utility will deallocate the inactive data set and allocate the active data set.

If you use GENJCL.IC, DBRC creates a control statement for the active data set. The skeletal JCL supplied by IMS will not create DD statements for database data sets - it uses dynamic allocation for these data sets.

There is a case where the use of static allocation will cause a failure. If the DD statement specifies an inactive data set which no longer exists, the job will fail due to a "data set not found" condition.

IMS does not allow an image copy to be processed for a partition while OLR is active for that partition (that is, a cursor is active). This remains true even if the OLR is temporarily suspended by the use of the **TERMINATE OLREORG** command.

A recovery of the output data sets from an online reorganization can be done without an image copy. The recovery is done by using only logs or logs and change accumulation data sets. Since the logs may contain many other records, it may be desirable to take image copies of the partition data sets soon after the completion of online reorganization. This will limit the number of logs required for a subsequent recovery. The image copies are likely to be concurrent image copies since this does not require the deallocation of the partition. A recovery using a concurrent image copy requires the input of the logs being written at the time of the concurrent image copy. This makes it desirable to switch logs between the completion of the OLR and the start of the concurrent image copy.

3.10.2 Change accumulation

The change accumulation utility (DFSUCUM0) has been enhanced to accumulate changes for both the A-J and M-V data sets. The control statements need only specify the A-J or the M-V DDNAMEs, as DBRC includes the partner data sets in the same CA group (for example, both the A and the M data sets).

The time of the start of OLR should be treated as purge time for output data sets, as this is equivalent to the image copy or reorganization time.

GENJCL.CA treats the start of OLR as the purge time for output data sets, and generates the DB0 statement with the correct purge time. This causes the utility to accumulate changes only since the beginning of OLR.

3.10.3 Database recovery

The IMS database recovery utility (DFSURDB0) recovers either the A-J or the M-V data sets, and the control statement *must* specify the correct DDNAME. DD statements *must* be included in the JCL.

Full recovery to the middle of an OLR is allowed, but time stamp recovery to the middle of OLR is not allowed. IMS Database Recovery Facility (DRF) tool may be used for this type of time stamp recovery.

Recovery of the output data sets after OLR starts but before an image copy is complete does not use image copy input. In this situation, the DFSUDUMP DD statement must specify DUMMY.

Timestamp recoveries cannot be done to a time in the middle of an OLR. This is true even if the time is one at which the OLR was suspended with a **TERMINATE** command. If a user attempts a time stamp recovery to a time between the start and stop times of an OLR, the

utility detects this and will not execute. GENJCL.RECOV also detects this situation and will not generate recovery JCL.

If a database data set needs to be recovered due to a failure during an OLR, a full recovery is allowed. Of course, the partition must be /DBRed for the full recovery.

GENJCL.RECOV

The GENJCL.RECOV command can be used to generate the JCL to recover a database data set being used for OLR. If DDNAME is not specified, DBRC generates recovery JCL for active data sets. If the time is during OLR, both the A-J and M-V data sets are recovered.

If DDNAME is specified, GENJCL.RECOV fails if an inactive data set is specified.

The **USEOLRRG** keyword has been added for GENJCL.RECOV. When USEOLRRG is specified, the generated JCL will contain the logs created during the OLR, but no image copy.

IMS Database Recovery Facility (DRF)

IMS Database Recovery Facility (DRF) can recover partitions of OLR capable databases. It recovers the active data sets for the databases and partitions specified in any of the following commands:

/REC ADD DB dbname or partname /REC ADD DBDS dbname or partname ddname /REC START ...

DRF time stamp recovery is supported to a time during an OLR, and will recover the A-J and M-V data sets. DRF uses RECON information to decide which data sets, A-J or M-V, to recover. It recovers the data sets which were active at the time specified for the recovery. If the cursor was active at the time to which the recovery is being done, then both the input and output data sets are selected (since both sets are active), otherwise only the active set of data sets are recovered. This is true even when a data set DDNAME is specified with the command:

/RECOVER ADD DBDS dbname ddname

If the ddname specified in the command was inactive during an OLR at the time to which we are recovering, its partner data set is recovered.

Full recovery using DRF

If OLR is complete and no post-reorganization image copy is available, DRF recovers the output data sets using the logs and/or the change accumulation data sets since the reorganization start time to recover the database.

If OLR is complete and a post-reorganization image copy is available, OLR recovers output data sets using the image copy plus any change accumulation data sets and the logs for the recovery.

If OLR is not complete, DRF recovers the input data sets from the most recent image copy, the change accumulation data sets and the logs. DRF also recovers the output data sets using the logs since the reorganization start time. Change accumulation data sets are not used, even if available.

Point-in-time recovery (PITR)

DRF can be used to recover a database to a point in time. DRF uses the same process as for a full recovery as detailed above, except that change accumulation data sets are not used.

3.10.4 Batch backout

The batch backout of an OLR in progress is generally not required. Any OLR abends invoke dynamic backout, and an IMS emergency restart also invokes dynamic backout.

Batch backout is required when IMS system fails and is then cold started. The backout must be run in a DLI (not DBB) region, as this is necessary in order to build an OLR PSB. IMS recognizes OLR by its PSB name, which is a numeric zero(0) followed by the partition name.

3.10.5 HD Unload and HD Reload

The HD Unload (DFSURGU0) and HD Reload (DFSURGL0) utilities may be used to complete a reorganization. They would only be needed when OLR cannot complete successfully, that is, OLR terminated with its cursor active.

The partition must first be /DBRed from all subsystems. The HD Unload utility reads both sets of data sets, and uses the cursor to determine from which to read. Dynamic allocation is used to allocate all the required data sets. The HD Reload utility always writes to A-J, X data sets, and dynamic allocation allocates only A-J, X data sets. The reload utility cleans up RECONs, setting the cursor to not active, and notifying DBRC that the A-J, X data sets are the active data sets.

3.11 DBRC changes for OLR

A number of changes have been made to DBRC for OLR. In this section, we discuss the extra fields that have been added to the RECON records and DBRC commands, as well as the coexistence of OLR with IMS Versions 7 and 8.

3.11.1 RECON records

The RECON records have been modified to include additional fields for OLR.

Master database record

The master database record has a flag indicating that this database is online reorganization capable. This flag can only be set for PHDAM and PHIDAM databases.

Partition database record

The partition database record has a number of new fields:

- Cursor active flag
- SSID of IMS owning OLR, if any
- Indicator for active data sets (A-J, M-V, or both sets)

When both sets are active, this also indicates which are input and which are output.

Flag for online reorganization capable

DBDS records for A-J and M-V data sets

The database data set records in the RECON have been extended, with the M-V records having many of the same attributes as the corresponding A-J data sets:

- GENMAX, RECOVPD, REUSEINOREUSE values are the same
- ► They are members of the same CAGRP and DBDS groups.

Image copy cleanup processing treats corresponding data sets as a whole, and hence an Image copy of M may result in deletion of image copy record for A, and an image copy of M turns off the *image copy needed* flag for A.

REORG record

Recoveries cannot use inputs from both before and after a reorganization. REORG records are written to allow DBRC to create correct recovery JCL and verify recovery JCL. OLR makes the recovery JCL generation process more complex. Additional REORG records are needed and additional information is needed in the REORG records.

REORG records for both input and output data sets are created when OLR begins. If a partition has two data set groups, an OLR would create REORG records for the A, B, M, and N data sets. This information is used to prevent attempted recoveries of the input data sets to a time after the OLR. It is also used to allow recoveries of output data sets without image copies.

For offline reorganizations, the REORG record contains the time of the completion of reload or prefix update. This is the RUNTIME. For online reorganizations, both the start and stop times are recorded in the REORG record. The start time is the RUNTIME.

There is a flag in the REORG record for the database data set to indicate whether the online reorganization start time may be used for a recovery without an image copy. The flag is set to yes for output data sets and set to no for input data sets.

Change accumulation group

Partner data sets (A-J and M-V) must belong to the same CA group. If data sets from either is defined or added to a change accumulation group, the partner is also defined or added by DBRC.

DBDS group

Partner data sets must belong to the same DBDS group. If data sets from either is defined or added to a database data set group, the partner is also defined or added by DBRC.

3.11.2 DBRC commands

The following commands have been enhanced for OLR:

- ► INIT.DB
- ► INIT.PART
- ► CHANGE.DB
- CHANGE.DBDS
- NOTIFY.REORG
- NOTIFY.IC
- NOTIFY.UIC
- GENJCL.RECOV
- GENJCL.CA

INIT.DB

The INIT.DB command has had new parameters for master database:

OLRCAP | OLRNOCAP

These indicate whether master database is OLR capable or not.

INIT.PART

There are no new parameters on the INIT.PART command for OLR. DBRC automatically creates the M-V or Y DBDS records as necessary when the first OLR for the partition is performed. These records are deleted by a CHANGE.DB... OLRNOCAP command.

CHANGE.DB

With CHANGE.DB command, there is one new parameter for a master database:

```
OLRCAP | OLRNOCAP
```

This indicates whether the master database is OLR capable.

All partitions must be unauthorized before this command is executed unless MINVERS of 9.1 is set in the RECON. The A-J data sets must be the active set before OLRNOCAP can be specified.

There are some new parameters for HALDB database partitions. As these commands can compromise database integrity, these parameters should not be used for normal operations.

```
OLRRGOFF | OLRRGON
```

Indicates whether OLR is in progress.

```
OLRIMSID(name) | NOOWNER
```

Identifies owner of an OLR in progress.

```
OLRDBDS (A | M)
```

Identifies the active set of DBDSs for this partition.

CHANGE.DBDS command

The parameters to the CHANGE.DBDS command now apply either to both data sets, or can be applied separately.

The parameters of the CHANGE.DBDS commands that apply to both data sets are:

- ICJCL
- OICJCL
- RECOVJCL
- RECVJCL
- ► GENMAX
- RECOVPD
- REUSE
- NOREUSE

The parameters of the CHANGE.DBDS commands that apply to just one data set are:

- ADDEQE
- ► DELEQE
- ICON
- ► ICOFF
- RECOV
- NORECOV

NOTIFY.REORG

There are several new parameters for the NOTIFY.REORG command, but they should only be required with OLR in exceptional circumstances.

The new parameters are:

OFFLINE | ONLINE

Indicates whether the reorganization is offline or OLR. ONLINE requires that both A-J and M-V DBDS records exist.

STOPTIME(timestamp)

Specifies the stop time of an OLR. Required with ONLINE and only valid with ONLINE.

OLDSTOPT(timestamp)

Specifies previous stop time. Used when DRF PITR recovers partition to middle of a completed OLR.

RECOV | NORECOV

Indicates whether the data sets may be used as input for recovery. Only valid with ONLINE.

NOTIFY.IC and NOTIFY.UIC

These commands fail if the specified RUNTIME of the image copy falls within the time frame of an OLR.

GENJCL.RECOV

There is one new parameter for GENJCL.RECOV:

USEOLRRG

Indicates that active data sets are input to recovery (an image copy is not used as input).

GENJCL.IC and GENJCL.OIC

The GENJCL.IC and GENJCL.UIC commands do not generate DD statements for HALDB data sets, as dynamic allocation of the active data sets is done by the image copy utility.

GENJCL.CA

The GENJCL.CA command generates control statements for partner (A-J and M-V) data sets.

3.11.3 OLR coexistence with IMS Version 7 and IMS Version 8

There are some decisions that need to be made before a HALDB is made OLR capable in an environment where the database can be accessed by IMS Version 7 or IMS Version 8.

If HALDB is made online reorganization capable, then an IMS Version 7 system cannot access the database. Similarly, unless the required maintenance has been applied to an IMS Version 8 system, it will not be able to access a database that has been made online reorganization capable.

The IMS Version 8 OLR coexistence SPE consists of the following maintenance: PQ78493, PQ78758, PQ78916, and PQ78917. When these have all been successfully applied, an IMS Version 8 system can access databases that have been made online reorganization capable, and can participate in data sharing while OLR is active in an IMS Version 9 system. However, the IMS Version 8 systems cannot invoke OLR.

When the database is HALDB OLR capable, the database utilities (GENJCL processing, Database Image Copy, Database Image Copy 2, Database Recovery, Database Recovery and Change Accumulation) must be run using the IMS Version 9 utilities.

3.12 Data sharing, FDBR, RSR, and XRF

This section discusses the support for OLR in IMS Version 9 data sharing, Fast Database Recovery (FDBR), Remote Site Recovery (RSR), and Extended Recovery Facility (XRF) environments.

3.12.1 Data sharing support

IMS Version 9 supports the use of OLR in all data sharing environments, including batch data sharing and online data sharing.

The OLR owner system notifies sharers of:

- Cursor active (OLR started)
- Cursor updated (UOR completed)
- Cursor inactive
- OLR completed

The sharing systems process these notifies, and use the cursor to identify which data sets to use for a request. Normal call processing for applications programs will wait for locks if there is a conflict in accessing segments in a UOR.

3.12.2 FDBR support

Fast Database Recovery is supported in a system which uses OLR. When FDBR detects an IMS failure in a system with OLR active, it backs out in-flight UORs, releases data sharing locks, closes and unauthorizes the partition. When you restart the IMS system, IMS does not resume the online reorganization because the partitions are not authorized after the FDBR terminates.

3.12.3 XRF support

The IMS Extended Recovery Facility (XRF) supports IMS systems running OLR. The alternate system reads x'29xx' log records, in order to keep track of the status of OLR. At takeover the in-flight UOR is dynamically backed out, and OLR is automatically resumed.

3.12.4 RSR support

IMS Remote Site Recovery (RSR) supports IMS systems running OLR.

For DBRC RECON tracking, the log router routes some x'29xx' log records to the DBRC tracker. These are:

x'2910'	OLReorg ownership established
x'2940'	Cursor active
x'2970'	Cursor inactive
x'2990'	OLReorg ownership relinquished

For recovery level tracking, the x'29xx' and x'50' log records are written to the SLDS.

For database level tracking if the partition is online at the tracking site during OLR, when the x'2930' (output data set information) log record is received, the output data sets are used if they exist. Otherwise, they are created. When x'50' (database update) log records are received, the output data sets are updated. When the x'2970' log record (cursor inactive and OLR complete) is received, the input data sets are deleted if the **INITIATE** command included **OPTION(DEL)**.

For database level tracking if the partition is offline at the tracking site during OLR, log records are archived to the SLDS and the OLR status is updated in the RECONs.

If the partition was offline when the OLR was done, online forward recovery (OFR) is invoked when the partition is started. If OLR is in progress when the partition is started, OFR recovers A-J and M-V data sets. If OLR has completed when the partition is started and no image copy is available, the output data set is recovered from the OLR start time. If the OLR has completed when the partition is started and an image copy is available, the output data set is recovered and an image copy is available, the output data set is recovered and an image copy is available, the output data set is recovered using the image copy and subsequent log records.

RSR does not track ILDS or PHIDAM index updates. These data sets must be rebuilt using DFSPREC0 after takeover.

If there is an unplanned takeover initiated at the tracking site (/RTAKEOVER UNPLAN command), the tracking IMS completes its current work and shuts down. Any databases marked as recovery-level-tracking (RLT) must be recovered (or changed to database level tracking (DLT)) so that online forward recovery (OFR) recovers them.

The emergency restart (/ERESTART) at the RSR site does not automatically restart any OLR in progress at the time of the failure. This is different from a normal /ERE. The resumption must be done with an INITIATE command after DFSPREC0 has been used to rebuild the ILDS and primary index for PHIDAM.

3.13 OLR performance

The reorganization of HALDB databases with OLR can now be achieved without the need for any database outage. Online database reorganization is now no longer on the critical path, in contrast to the high priority critical task that usually categorizes an offline reorganization. OLR can be initiated at any time it is deemed necessary without the need to quiesce any system activity. This aspect of OLR is part of the design to provide the ultimate data availability solution. While reorganization of data is key to the performance health of a database, being able to reorganize online with full access to the data being reorganized brings with it some additional performance considerations.

There are a number of options which can influence the performance of OLR. These include:

- OSAM sequential buffering
- Logging
- Lock contention
- Database buffer pools
- Buffer contention
- DASD contention
- Pacing
- Address space priority
- Spreading the work across a sysplex

3.13.1 OSAM sequential buffering

OSAM sequential buffering can be used by OLR to reduce the elapsed time for reading and writing the records in a unit of reorganization. The *SBONLINE* parameter needs to be specified in the DFSVSMxx member of your IMS PROCLIB. The use of OSAM sequential buffering is recommended when OLR is being used for OSAM databases. It is also recommended that the DFSVSMxx member does not include the MAXSB keyword unless storage constraints exist.

3.13.2 Logging

The amount of data logged by OLR may impact online performance. All data is logged when segments are moved during an online reorganization. OLR has also introduced a few additional log records, which are described in "Logging" on page 43. Planning for additional log volumes is critical to the success of OLR. As an estimate, assume 10 cylinders of OLDS data will be created for every 1 cylinder of data moved during the online reorganization process.

Because the volume of log data can be overwhelming when considering the change accumulation process, it is recommended that OLR be run on one or more IMS systems which are dedicated to OLR processing. This will avoid excessive log processing for change accumulation for non-HALDB databases and partitions not using OLR.

When using multiple LPARs dedicated to OLR it is recommended that the LPAR have a minimum of 2 CPs (shared or dedicated) to allow more parallelism between IMS and IRLM.

Where OLDS logging becomes a performance bottleneck, it is recommended to use a 24K log block size, increase the number of log buffers to the maximum of 999, and use fast DASD in the most cache friendly configuration possible. The impact of OLR to the logging rate on the IMS system can be adjusted through the OLR rate. Reducing the OLR rate will have the side effect of lowering the OLDS logging rate.

When planning for running multiple concurrent OLRs consideration must be given to the impact of logging on the rest of the IMS system. It is recommended that no more than 4 OLRs (using rate=100) should execute concurrently in a single IMS system in which there is online activity to prevent excessive waits for logging due to high log latch contention.

3.13.3 Lock contention

OLR could create lock contention, but this is likely to be minimal. OLR limits the size of its UORs in an attempt to hold locks for no more than a second. That is, its algorithm for UOR size includes an adjustment to limit the times that locks are held. The data base record locks on PHDAM RAPs and PHIDAM roots are exclusive locks. Applications requesting locks on these resources will wait until they are released at the end of a UOR. Block locks are obtained on output data set OSAM blocks and VSAM Cls. Data sharing users could be affected by these locks. They prevent updates of the same block or Cl. They do not prevent reads of other database records in the blocks and Cls.

Locking of database records by OLR hardly ever causes a deadlock. This is because OLR almost always uses conditional lock requests when already holding a lock. This means that if the requested lock is not available, OLR does not wait for it. Instead, it ends the UOR at the current location.

OLR requests block locks unconditionally. These lock requests could cause a deadlock in a data sharing environment. When OLR creates a deadlock, it is the victim. The other participants in the deadlock are not affected. UOR is dynamically backed out and automatically restarted.

3.13.4 Buffer pool definitions

The M-V (and Y) data sets are assigned to the same buffer pools as the corresponding A-J (and X) data sets. Only the A-J, L, and X identifiers may be specified in the DBD statements of DFSVSMxx members and DFSVSAMP data sets for HALDB data sets. The M-V (and Y) identifiers are not allowed on these DBD statements.

3.13.5 Buffer contention

OLR makes intensive use of buffer pools for the data sets it is reading and writing. The input and output data sets always use the same pool or subpool. Users should ensure that they have adequate buffers in these pools and subpools. OLR uses a VSAM string (PLH). IMS dependent regions and threads also use strings. A string is needed for each concurrent I/O in the pool. The number of strings for a pool defaults to the MAXREGN specification of system definition or the PST execution parameter. It may be overridden by specifying the STRINGNM parameter on the POOLID statement used to define the VSAM pool. Users should ensure that they have enough strings to support the maximum number of concurrent I/Os for a pool. If there are inadequate strings, I/Os must wait.

3.13.6 DASD contention

OLR is a highly I/O intensive process. DASD contention could occur. It is beneficial to use fast DASD with large cache where possible. It is also beneficial to use FICON® channels where high path utilization can contribute to I/O delays.

3.13.7 Pacing

The affect of OLR on the performance of systems and applications may be limited by using the RATE parameter on the INIT or UPD command to pace the OLR process. OLR does not hold any locks when the waits for this pacing are done, nor is the locked data held for a longer duration.

The RATE of the OLR controls the interval between UORs. While it is recommended to reorganize a database during periods of low activity for the database, when a database must be reorganized immediately, OLR can be initiated and the impact to the system and application tasks can be adjusted by increasing or decreasing the OLR rate until an acceptable balance is achieved.

3.13.8 TCBs used by OLR

OLR runs in the DL/I address space (DLISAS). This address space has a "parent" TCB with ten "child" TCBs, used for dynamic allocation. This was added in IMS Version 8. The parent TCB is used for HSM processing, and the child TCBs are used for database allocation, open, close and end of volume processing, as well as OLR. Each executing OLR will use one of these 10 TCBs, determined by the local DMB number using modulo 10 arithmetic. For example, if 3 partitions are being reorganized, 1 to 3 TCBs will be used.

3.13.9 Executing OLR in a sysplex

OLR may be run on any IMS in a data sharing sysplex. Some installations may decide to run online reorganizations on a dedicated system. The buffer pool definitions can then be tuned specifically for OLR, which would avoid buffer contention in this IMS. It has the added advantage of using a separate set of logs, reducing any potential logging contention.

Logs produced by a system dedicated to OLR will only have log records from databases using OLR. If a CA Group does not contain any of these databases, it will never need logs produced by this IMS system for change accumulations of other databases or for recoveries of other databases.

3.13.10 CPU use with OLR

OLR CPU requirements vary based on the OLR rate and partition size. A single OLR running at full speed (rate=100) can cause the LPAR (using 2 cps) CPU utilization to increase by as much as 18% on a zSeries processor for the duration of the OLR. The CPU utilization can be reduced by reducing the OLR rate. Reducing the OLR rate will also have the effects of reducing the logging rate and elongating the OLR elapsed time.

4

Fast Path enhancements in IMS Version 9

In this chapter we introduce IMS Fast Path enhancements in IMS Version 9. This chapter contains information relating to the following items:

- Multi-area structures for SVSO
- Area open and close enhancements
- Optional EMHQ structure for shared queues
- Serviceability and usability enhancements

4.1 Fast Path multi-area structures for SVSO

Previous releases of IMS required that each shared VSO area has its own structure. For availability reasons, duplexed structures were recommended. For users with many shared VSO areas, this could be a problem since z/OS limits the number of structures that may be defined. For z/OS 1.4 no more than 512 structures may be defined in a CFRM policy. Duplexing of structures exacerbates the problem.

IMS Version 9 now allows multiple areas to share a structure see Figure 4-1. This has two advantages. First, it may be used to avoid the restriction on the number of structures. Second, fewer structures simplify the management of structures.




Figure 4-1 Multi-area structures for SVSO

4.1.1 Single area structures

With single area structures, each area has its own structure or pair of structures. Areas with the same CI size and the same buffer look aside option may share a private buffer pool. This is the pool that resides in the IMS control region. Single area structures remain an option in IMS Version 9.

Single area structures are defined to DBRC. The VSO keyword is for the use of VSO. CFSTR1 is used to define the primary structure used by the area. CFSTR2 is optional. It defines the duplex structure for the area. The LKASID or NOLKASID keyword is used to specify if look aside buffering is used for the area.

A private buffer pool may be defined for an area. It is specified in the DFSVSMxx member with a DEDB statement. A private buffer pool is devoted to an area or the areas of one DEDB. The definition includes the primary buffer allocation, the secondary buffer allocation, and the maximum number of buffers allowed for the pool as follows:

DEDB=(poolname,cisize,pri,sec,max,lkasid,DBorAreaName)

A private buffer pool may be defined without specifying an area name or DEDB name. This pool is used by areas which are not assigned to pool which specifies an area name or DEDB name. Such areas whose CI sizes and look-aside attributes match those specified for the pool use the pool as follows:

DEDB=(poolname,cisize,pri,sec,max,lkasid)

A default pool is built for the area if the appropriate DEDB statement is not present. The pool is shared by areas with the same CI size and look-aside attributes.

4.1.2 Multiple area structures

IMS Version 9 supports multiple area structures. These structures may be used for multiple shared VSO areas. All areas using a structure must have the same CI size and must share the same buffer pool. Accordingly all areas in the buffer pool use the same structure.

The use of a multiple area structure by an area is specified to DBRC. The MAS keyword on the INIT.DBDS or CHANGE.DBDS command of DBRC is used to specify that an area will use a multiple area structure. CFSTR1 keyword indicate that SVSO is used for the area and it specifies the structure name this area shares. There is no CFSTR2 keyword when MAS is specified. This means that IMS managed duplexing is not available for multiple area structures, and system managed duplexing is recommended instead.

All areas using a structure must also use the same shared private buffer pool. The definition of the pool differs from that used for single area structures. The statement is the DEDBMAS statement. The DEDBMAS statement includes the name of the structure. It does not include the name of the areas or DEDBs using the pool. The default pool is built for the structure's areas if the appropriate DEDBMAS statement is not present. DEDBMAS is coded as follows in DFSVSMxx:

DEDBMAS=(poolname,cisize,pri,sec,max,lkasid,StructureName)

Example definitions

Figure 4-2 shows an example of definitions in DBRC for multiple area structures, and the correlation between the DBRC definitions and buffer pool definitions in DFSVSMxx as follows:

- AREA1 and AREA2 of database DEDB1 use structure MASSTR1.
- AREA4 of database DEDB2 and AREA5 of database DEDB3 use structure MASSTR2.




Figure 4-2 Multiple area definitions in DBRC and in DFSVSMxx

Example 4-1 on page 60 shows the CFRM policy definitions for three SVSO areas in our test environment. IMS duplexing is used for the structures and each area has its own individual pair of structures defined.

Example 4-1 CFRM policy for single area structures

/*-			*	/	
/* *_	IMS DATA SHARING - VSO - B-PLEX	- SINGLE AREA STRU			
			,		
	STRUCTURE NAME(IMOB_AREAWH01A) PREFLIST(CF06,CF03)	SIZE(4096)			
	STRUCTURE NAME(IMOB_AREAWH01B) PREFLIST(CF03,CF06)	SIZE(4096)			
	PREFEISI (CFUS, CFUU)				
	STRUCTURE NAME(IMOB_AREAWHO2A) PREFLIST(CF06,CF03)	SIZE(4096)			
	STRUCTURE NAME(IMOB_AREAWH02B) PREFLIST(CF03,CF06)	SIZE(4096)			
	CTRUCTURE NAME (TMOR ADEAUUO2A)	CI7E (400C)			
	STRUCTURE NAME(IMOB_AREAWHO3A) PREFLIST(CF06,CF03)	SIZE(4096)			
	STRUCTURE NAME(IMOB AREAWHO3B)	STZE (4096)			
	PREFLIST (CF03, CF06)	0122(1090)			

In our environment, we want to reduce the number of defined structures and with IMS Version 9, we can define all the areas to use one shared structure. As the DEDB SVSO structures now also support system managed duplexing, we can also define the DUPLEX(ENABLED) for the new structure. As mentioned earlier, IMS managed duplexing is not available for multiple area structures. Because this structure will be shared by all of the three areas used in the previous example, we increase the size accordingly. Example 4-2 shows the CFRM policy definitions for the shared multiple area structure which replace the single area structure definitions shown in Example 4-1.

Example 4-2 CFRM policy for the multiple area structure

```
STRUCTURE NAME(IMOB_AREAWHOM1) SIZE(12288)
DUPLEX(ENABLED)
PREFLIST(CF03,CF06)
```

We also have two other DEDB SVSO databases in our test system, which we want to change to use the shared structure. Example 4-3 shows the single area structure definitions for these databases.

Example 4-3 CFRM policy for single area structures

/* ______*/
/* IMS DATA SHARING - VSO - B-PLEX - SINGLE AREA STRUCTURES - IMS DUPLEXING */
* ______*/
STRUCTURE NAME(IMOB_AREADIO1A) SIZE(4096)
PREFLIST(CF03,CF06)
STRUCTURE NAME(IMOB_AREADIO2A) SIZE(4096)
PREFLIST(CF06,CF03)
STRUCTURE NAME(IMOB_AREADIO2B) SIZE(4096)
PREFLIST(CF03,GF06)

```
STRUCTURE NAME(IMOB_AREAITO1A) SIZE(8192)
PREFLIST(CF06,CF03)
STRUCTURE NAME(IMOB_AREAIT01B) SIZE(8192)
PREFLIST(CF03,CF06)
```

These areas have a different CI size compared to areas in the previous example, so we cannot change them to use the same shared structure. To convert them to system managed duplexing, we define DUPLEX(ENABLED) for this new structure. This structure will be shared by three areas in two different DEDB SVSO databases. We give the structure a generic name of IM0B_AREASMAS1. Example 4-4 shows the CFRM policy definitions for the shared multiple area structure which replace the single area structure definitions shown in Example 4-3 on page 60.

Example 4-4 CFRM policy for the multiple area structure

```
STRUCTURE NAME(IMOB_AREASMAS1) SIZE(16384)
DUPLEX(ENABLED)
PREFLIST(CF03,CF06)
```

In IMS.PROCLIB, we define the shared private buffer pool for the newly defined structures by adding the following lines to the appropriate DFSVSMxx member:

```
DEDBMAS=(WAREMAS1,500,100,2000,LKASID,IMOB_AREAWHOM1)
DEDBMAS=(GENEMAS1,1000,100,5000,LKASID,IMOB_AREASMAS1)
```

So, now we have removed the old structures from the CFRM policy, defined two new structures, and defined the shared private buffer pools for these new structures. To finalize this change, we still have to do the following:

- Close and deallocate the areas from IMS(s)
- Run the IXCMIAPU utility for updating the CFRM
- Issue the command for activating the new policy
- Issue the DBRC commands in IMS as shown in Example 4-5
- Start the areas

CHANGE.DBDS	DBD(WAREDB) AREA(AREAWH01) -
	VSO MAS CFSTR1(IMOB_AREAWHOM1)
CHANGE.DBDS	DBD(WAREDB) AREA(AREAWH02) -
	VSO MAS CFSTR1(IMOB_AREAWHOM1)
CHANGE.DBDS	DBD(WAREDB) AREA(AREAWHO3) -
	VSO MAS CFSTR1(IMOB_AREAWHOM1)
CHANGE.DBDS	DBD(DISTDB) AREA(AREADI01) -
	VSO MAS CFSTR1(IMOB_ARESMAS1)
CHANGE.DBDS	DBD(DISTDB) AREA(AREADIO2) -
	VSO MAS CFSTR1(IMOB_AREASMAS1)
CHANGE.DBDS	DBD(ITEMDB) AREA(AREAITO1) -
	VSO MAS CFSTR1(IMOB_AREASMAS1)

As a result of this exercise, we managed to reduce the number of structure definitions for these three DEDB SVSO databases with six areas from the original 12 structures to two by combining the areas having the same CI size to use a common structure, and by converting from using the IMS managed structure duplexing to using system managed structure duplexing.

4.1.3 Multiple area structures additional considerations

As you saw in the previous examples, all areas sharing a structure must have the same CI size, but the sharing areas may be from any DEDB. This is because all areas sharing a structure also share a buffer pool. There is no restriction on the number of areas that share a structure.

Duplexing of structures is recommended for shared VSO. If a non-duplexed structure is lost, the structure cannot be rebuilt. SVSO structures are *store-in* structures. They typically hold data which has not been written to DASD and which is no longer in buffer pools. If a non-duplexed structure is lost, its area or areas must be recovered. This makes the duplexing of structures critical for most installations.

The use of look aside buffering is determined by the specification on the DEDBMAS statement. LKASID or NOLKASID may be specified in the DBRC RECONs for areas using MAS, but it is ignored.

IMS does not determine if a multiple area structure is large enough to hold the areas that are assigned to it. This is different from single area structures with the PRELOAD option. The **/DIS FPV** command response is expanded in IMS Version 9 to include the count of CIs in the root addressable part as well as the number of CIs in the structure. This makes it easier to determine any requirement to increase the size of the structure for areas with the PRELOAD option.

4.1.4 System managed duplexing versus IMS managed duplexing

System managed duplexing has hardware and software requirements. There are no special requirements for multiple area structures. They have the same requirements as other structures using system managed duplexing.

The software requirement for system managed duplexing is z/OS 1.2 or higher; IMS Version 9 requires z/OS 1.4 or higher. The hardware requirements for system managed duplexing with IMS Version 9 are the same as with previous IMS releases:

- zSeries or G5/G6 servers
- ► Two or more Coupling Facilities
 - zSeries or 9672 G5/G6 with appropriate CFLEVEL
- CF-to-CF links

For more details on system managed duplexing refer to the technical white paper that can be found on the Web at the following address:

http://www.ibm.com/server/eserver/zSeries/library/techpapers/gm130103.html

IMS can manage duplexing for the DEDB VSO structures unless they are using the multiple area structure support introduced in IMS Version 9. The VSO structure uses the store-in model. As records gets updated, the data is asynchronously written to the structure, but not to DASD. At system checkpoints, updated data is then hardened to DASD. The issue then is that if a structure or Coupling Facility should fail, the data on DASD cannot be assumed to be valid and a database recovery process is needed. This requires restoring the last image copy and applying the logs, and could take a substantial amount of time. To assist with this, IMS has implemented support for IMS-managed software duplexing of DEDB VSO structures on an area by area basis since IMS Version 6. If one structure should become unavailable, the IMS managed duplexed structure is still available for reads and updates in simplex mode. To reinstate duplex mode, an IMS /VUNLOAD command is issued followed by a /STA AREA command. IMS does not stop data sharing during this process. The /VUNLOAD command

copies the data to DASD. The /STA AREA command populates the two structures. All data is available during this time.

Compare this time-consuming IMS recovery procedure with system managed duplexing, where the duplexed structure may be automatically reestablished when the backup Coupling Facility comes online. There are no IMS commands required with system managed duplexing. Also, the VSO structure recovery will be consistent with other IMS database and system structures which currently support rebuild. Therefore there is no need for multiple operational recovery procedures. System managed duplexing provides the benefit of much easier system management characteristics compared with IMS managed software VSO duplexing. In addition, IMS managed duplexing is not available for multiple area structures.

4.1.5 Failures without successful duplexing

Normally, duplexing avoids failures associated with structures. This discusses what happens when duplexing is not used or when duplexing does not prevent the failure. The following types of failures can occur without duplexing:

Structure failure

If a structure fails, the data in the structure is not available. All of its areas are stopped and marked recovery needed.

Loss of connectivity to a structure

If there is a loss of connectivity to a structure, all of the areas in the structure are stopped on each system losing connectivity. Committed updates which are not yet written to the structure are written to DASD. Structure remains in a failed persistent status.

Loss of connectivity from all IMS systems

If connectivity is lost from all IMS systems, all of the areas in the structure are stopped. The structure remains in a failed persistent status.

► A read or write error

A read or write error for a structure is treated as a loss of connectivity. If the duplexed structure is available, sharing continues. If not, the error is treated as a loss of connectivity.

Messages

This shows the IMS messages that are written with multiple area shared VSO structures.

Connection when IMS connects to structure for first area using it in this IMS:

DFS2822I AREA area CONNECT TO STR str SUCCESSFUL

Association when other areas start using structure with existing connection:

DFS28511 AREA area ASSOCIATE TO STR str SUCCESSFUL

Disassociation when area is taken out of a multi-area structure:

DFS28511 AREA area DISASSOCIATE FROM STR str SUCCESSFUL

Disconnection when last area for an IMS is taken out of a multi-area structure: DFS28531 AREA area DISCONNECT TO STR str SUCCESSFUL

/DIS command

Example 4-6 on page 64 shows an example of the response to a **/DIS FPV** command. The ENTRIES column shows the number of CIs in the structure. The CHANGED column shows the number of changed CIs that have been written to the structure. They will be written to DASD by cast out processing which will reset the count. The AREA CI# column is new in IMS Version 9. It shows the number of CIs in the direct part of the area.

Example 4-6 /DIS FPVirtual

AREANAME	STRUCTURE	ENTRIES	CHANGED	AREA CI#	POOLNAME	OPTIONS
DD01AR0	DD01AR0STR1	0000045	0000025	00000045	DD01	PREO, PREL
DB21AR8	MAS1KSTR	0000044	0000044	00000150	MAS1K	PREO
DB21AR5	MAS1KSTR	0000099	0000044	00000150	MAS1K	PREO, PREL
DB21AR6	MAS1KSTR	0000150	0000044	00000150	MAS1K	PREO, PREL

In the example, area DB21AR5 has 150 CIs in the direct part, but only 44 CIs from the area are in the structure. The OPTIONS column indicates that it is a preloaded area. This means that the structure is not large enough to hold the direct part of the areas using it. The size of the structure should be increased to hold all of the CIs for the AREAs using it.

4.2 Area open and close enhancements

IMS Version 9 opens and closes areas in parallel. Parallel processes are done with multiple TCBs. The parallel open is an asynchronous process that happens with online activity, so it does not delay IMS restart completion. IMS now restarts and reopens the areas after the reconnection to IRLM, and reopens the areas after /ERE completes. There are several options associated with these opens. The new options can improve the performance of restarts and simplify operations.

The FPOPN=D option has been added to IMS Version 8 by the APAR PQ74606. It disables the preopen process for DEDB areas. It applies to cold starts, warm starts, and emergency restarts. The open of areas with PREOPEN specified in the RECONs is like the open of other areas. It occurs either when they are first referenced by applications or as a result of a /START AREA command.

AREAs with the VSO PRELOAD option are affected by this process. They are not loaded until after they have been opened due to the first reference or as a result of a /START AREA command.

New parameters for IMS restart in IMS Version 9

The FPOPN=P option causes PREOPEN processing to be done outside of restart processing. This allows new work to begin more quickly. It applies to both normal and emergency restarts.

The FPOPN=R option causes /ERE processing to open all areas which were open at the time of the IMS abnormal termination. /ERE will not open areas that were closed. If an area with PREOPEN specified to DBRC was closed at the time of the IMS termination, /ERE will not open it.

The FPOPN=A option combines the P and R options. /ERE processing opens all areas that either were open at the time of the IMS abnormal termination or have PREOPEN specified to DBRC.

IMS (re)start option for opens of areas:

FPOPN=N

N (no), preopen executes in line as part of restart before online activity begins. This is like previous releases.

► FPOPN=P

P (preopen), initiate preopen at end of restart and executes asynchronously with online activity.

FPOPN=R

R (restore), for /ERE, reopen all areas that were open at termination. For /NRE command, treated as P option. Executes asynchronously with online activity.

► FPOPN=A

A (all), for /ERE, combines P and R; for /NRE command, treated as P option

► FPOPN=D

D (disable preopen) disables preopen

IMS restart processing

In previous releases, areas with PREOPEN specified to DBRC were opened as part of the restart process. The restart process did not complete until these opens completed. Online processing could not begin until restart completed. Figure 4-3 illustrates the processing time lines for IMS versions before IMS Version 9.




Figure 4-3 Pre-IMS Version 9

In IMS Version 9 with the FPOPN=N option, preopen processing remains part of restart processing, but it is shortened. These opens are done in parallel using 10 TCBs. This shortens the elapsed time of restart processing. Figure 4-4 shows the timing for an IMS Version 9 system that has FPOPN=N specified.

- IMS restart processing -	IMS online processing —
	Preopen areas

Figure 4-4 IMS Version 9 with FPOPN=N

In IMS Version 9 with FPOPN=P, R, or A, the open process is not part of restart. This allows online processing to begin sooner. Open processing is done in parallel. For normal starts, only areas with PREOPEN specified are opened. For emergency restarts, the areas opened depend on the option chosen. Figure 4-5 illustrates these options.

 IMS restart processing 	-			 IMS online processing
	*******	Open areas	* * * * * * * * *	

Figure 4-5 MS Version 9 with FPOPN=P, R, or A

IRLM reconnect options

When IRLM fails, IMS does not fail. Instead, it quiesces its work and waits to reconnect to IRLM. It also stops all of the DEDB areas. Previous releases of IMS did not restart these areas when IMS reconnected to IRLM. Operators had to issue the /START AREA commands. IMS Version 9 gives users the option to cause IMS to automatically restart the areas when the reconnect is done.

The new IRLM reconnect options are controlled by the FPRLM start up parameter. All actions that are taken, are executed asynchronously with online activity. You can specify FPRLM parameter as follows:

FPRLM=N

The N (no) option causes IMS to act as it did with previous releases. It does not start areas when the reconnection to IRLM is made.

► FPRLM=P

The P (preopen) option applies to areas with the PREOPEN parameter. They are started and opened when IMS reconnects to IRLM regardless of their status prior to the IRLM abnormal termination.

► FPRLM=S

The S (start) option causes IMS to start all of the areas which were stopped during the IRLM disconnect. The starts are done when IMS reconnects to the IRLM.

► FPRLM=R

The R (restore) option starts and opens only those areas which were stopped as part of the IRLM disconnect process. It does not start areas which were already stopped, including those with PREOPEN specified to DBRC. Message DFS3210I is issued after all of these areas have been started.

New messages

There are new messages associated with the parallel open, start, close, and stop processes in IMS Version 9. Message DFS3715I is issued when a process starts, and it has the following format:

DFS3715I DEDB AREA XXXXXXX PROCESS STARTED, RSN=rr

DFS3719I is issued when a process completes, and it has the following format:

DFS3719I AREA xxxxxxx PROCESS COMPLETED, RSN=rr

The text of the message identifies the process, which can be one of the following:

PREOPEN	The process used to open the areas with the PREOPEN parameter.
REOPEN	The process used to open the areas that were open at termination or IRLM disconnect time.
RESTART	The process used to start areas which were started at the time of the IRLM disconnect.
SHUTDOWN	The process used to close areas in parallel when IMS is shut down.
RLM REVR	The IRLM reverify process. It is used to close and stop areas in parallel for an IRLM disconnect.

Operations considerations

We suggest the following choices:

► FPOPN=R and FPRLM=R

With these values defined you can gain the following benefits:

- Emergency restart restores system to state at time of IMS failure
- ► Restart completes earlier, new work begins earlier
- Reconnect to IRLM restores system to state at time of IRLM failure

Automated operations may be adjusted. Users who currently have automation to reopen and restart areas after a restart or reconnect can eliminate this automation.

4.3 Optional EMHQ structure for shared queues

In previous IMS releases there was a need to define EMHQ structures even though the environment did not use shared expedited message handler (EMH) messages when Fast Path was included in the system. IMS Version 9 does not require that the EMHQ structures be defined when not using shared EMH. These actions are required if you do not require the EMHQ structure:

► IMS

The EMHQ= parameter in the IMS DFSSQxxx PROCLIB member specifies the primary structure for the EMH queues. It is deleted when no structure is required. This disables shared EMH processing in IMS.

► CQS

Each CQS member has a local PROCLIB member, CQSSLxxx. There is a global PROCLIB member, CQSSGxxx, which is shared by all of the members. The STRUCTURE statements for the EMH structure may be deleted when no structure is required. When STRUCTURE statements for shared EMH structure in CQSSLxxx and CQSSGxxx PROCLIB members are not present, CQS does not allocate EMHQ resources any longer in the following restart.

CFRM policy

You may also delete the STRUCTURE statements for the EMHQ structure and its logger structure from the CFRM policy. This is not required, because it is permissible to have definitions for structures which will not be built. Nevertheless, you will want to clean up the policy by deleting these definitions, so the recommendation is to delete STRUCTURE statement for EMHQ and its CQS log from policy.

LOGR policy

You may delete the DEFINE LOGSTREAM statement for the EMHQ log from the LOGR policy. This is not required because it is permissible to have definitions for log streams which will not be created. Nevertheless, you will want to clean up the policy by deleting this definition, so the recommendation also here is to delete DEFINE LOGSTREAM statement for EMHQ log.

Automation

If there is any automation which issues commands for the deleted structures, it should be modified.

► IMS restart

To change from or to the usage of EMHQ, you must use a cold start of IMS. The cold start may be either a /NRE CHECKPOINT 0 or a /ERE COLDCOMM. EMHQ usage cannot be changed across a warm or emergency restart, so you cannot use /ERE COLDSYS, an /NRE warm start command, or any other form of /ERE command.

4.4 Fast Path serviceability and usability enhancements

There are several small enhancements for serviceability, usability, and documentation including the following:

- Expanded log records
- ► Fast Path log records in ILOGREC
- Expanded /DIS commands
- Data space elimination
- Trace table
- Utility enhancements
- Fewer Fast Path snap dumps

Log records

In IMS Version 9, the following enhancements have been made to Fast Path log records:

- ► When a dependent region abends, the Fast Path dependent region blocks, EPST and EMHB, are written in the x'6706' log records. However, the x'6706' log records are not written for U0777 and U3303 abends.
- The Fast Path dependent region buffer values, NBA and OBA, are included in the Fast Path sync point log record (x'5937'). These are the normal and overflow buffer allocations for the dependent region. The number of buffers actually used is also in the log record. It was included in previous releases. The number of SDEP segments inserted are included in the log record. The IMS Performance Analyzer product reports these new fields.

Fast Path log records in ILOGREC macro

Fast Path records are now included in ILOGREC macro. You can use the following specifications to map the Fast Path log records:

► ILOGREC RECID=ALL

Includes all Fast Path log records

ILOGREC RECID=59nn

Creates specific Fast Path log record

Old Fast Path log record macros, such as DBFLGSYN and DBFLSRT, are still available.

Commands

The response to the /DIS AREA command has been expanded to include the identification of the IMSID where IMS Fast Path utility is active. The utilities include:

- High Speed Sequential Processing utility (HSSP)
- DBFUHDR0, High Speed Reorganization utility (HSRE)
- DBFUMDL0, SDEP Delete utility (MDL0)
- DBFUMSC0, SDEP Scan utility (MSC0)
- DBFUMRI0, DEDB Create utility (MRI0)
- DBFUMMH0, DEDB Compare utility (MMH0)
- VSO Preload is active (PRLD)
- An IBM DBTOOL Online utility (TOOL)

Example 4-7 shows a response to /DIS AREA command issued in IMS3 system, and you can see that there is an HSSP utility running in IMS2.

Example 4-7 /DIS AREA

/DIS AREA DB21AR0

DFS000I	AREANAME	EQECT	TOTAL UNUSE	TOTAL U	NUSED	DBNAME	EEQECT	CONDITIONS		IMS3
DFS000I	DDNAME	REMAIN	SEQ DEPENDEN	DIR ADDR	ESSABLE					IMS3
DFS000I	DB21AR0	N/A	29 28	74 0	-UW	DEDBJN21	0	VIR, PREO,	PREL	IMS3
DFS000I	UTILITY:	HSSP	PVTTOT# 4	5 PVTAVL#	30	IMSID	: IMS2			IMS3
DFS000I	DB21AR01	10	N/A N//	N/A	N/A	N/A				IMS3

When the /START DB command is issued at an RSR tracking site, online forward recovery (OFR) is activated without requiring /START AREA commands for each area. These /START AREA commands were required with previous IMS releases.

VSO data space

IMS Version 9 does not create any VSO data spaces unless VSO is used. The first data space is created when the first open of a VSO area is done. Some installations limit the number of data spaces that may be created. The change will potentially benefit such installations when they do not use VSO.

Fast Path trace table

In IMS Version 9 there is a new trace table for Fast Path. Fast Path trace in previous releases is actually a dependent region trace, and it does not use the IMS internal trace function. New trace has similar format to DL/I trace table. These traces are documented in *IMS Version 9: Diagnosis Guide and Reference*, LY37-3203. Fast Path trace is turned on by the command shown in Figure 4-6. The IPCS dump formatter is changed to reflect this new trace entry as well.

/TRACE	SET	ON	TABLE	FPTT	OPTION	NOLOG	VOLUME	MEDIUM
						LOG		LOW
								HIGH

Figure 4-6 Fast Path trace command

High speed reorg utility

In previous releases high speed reorg utility would stop after five failures due to insufficient buffers for IOVF. This is the default for IMS Version 9, but the new STOPAFTERFAIL#= specification may be used to change the number of failures required for the stopping of the reorg. Example 4-8 shows an example how to specify this new control statement.

Example 4-8 Example control statements

```
TYPE HSR
STOPAFTERFAIL#=10
AREA DB21AR1
GO
```

If STOPAFTERFAIL# is not specified, the default of 5 is taken. If STOPAFTERFAIL#=0 is specified, the utility will continue to run until it reaches the end of the DEDB area. The maximum value for STOPAFTERFAIL# is 999. Example 4-9 shows the messages when the STOPAFTERFAIL#=1 is specified and reached.

Example 4-9 Stopafterfail

TYPE REORG STOPAFTERFAIL#=1 AREA DB21AR3 GO TEM00100

TEM00150

AREA DB21AR3 HAS 5 UOW'S. EACH UOW HAS 15 CI'S; 5 AP CI'S, 10 DOVF CI'S. EACH CI IS 2K, ONE BUFFER SET REQUIRES 30K OF STORAGE INDEPENDENT OVERFLOW HAS 1 OVERFLOW UNITS, A TOTAL OF 74 DATA CI' STATS FOR REORG OF AREA DB21AR3 : 5; LOW UOW # OF UOWS REQUESTED TO REORG= O, HIGH UOW 4 # OF UOWS ACTUALLY REORG'D= 2; LOW UOW 0, HIGH UOW 4 # OF UOWS SKIPPED= 2, ALL ANCHOR POINT CI'S WERE EMPTY # OF UOWS FAILED= 1, MAX OF 999 FOLLOWS: UOW 1 FAILED; REASON: 02, INSUFFICIENT BUFFERS FOR IOVF I/O 0 (REUSED) = 0 (REUSED) = # OF IOVF CI'S FREED BY REORG: 0 -0 # OF IOVF CI'S ALLOCATED: 0 (NEW) + 0 # OF FREE IOVF CI'S AFTER REORG= 74, PERCENT FREE= 100 PRIVATE BUFFER SET INITIAL ALLOCATION= 3, EXTENSION COUNT= 0 RAP INPUT BUFFER SETS= 1, OUTPUT/IOVF BUFFER SETS= 2 UOW 0 USED 0 BUFFERS FOR IOVF I/O, THE HIGHEST USAGE PERFORMANCE STATS: # OF ASYNCHRONOUS READ AHEAD I/O'S= 0, # OF WAITS FOR UOW LOCKS= 0, # OF WAITS FOR PRIVATE BUFFERS= 0 DFS2662A UTILITY NOT EXECUTED AS REQUESTED

SDEP utilities

For enhancing the diagnostics, some messages written by SDEP utility processing have been modified to add the area name as follows:

DFS2634I AREA=xxxxxx HWM CI OWNED, SDEP HARDENED LOCALLY

This message is written when SDEP SCAN/DELETE runs and a sharer needs to harden update buffers. When SDEP SCAN/DELETE has QUITCI in SYSIN, but the sharer does not own HWM (high water mark) CI and RBA of HWM CI is greater than the one of current CI, this message is written on the sharer.

DFS2635I AREA=xxxxxxx HWM CI HARDENED REMOTELY

This message is written when the SCAN or DELETE utility runs on non-HWM-Owned partner(s).

DFS2636I AREA=XXXXXXX PARTNER QCI FREE LOCKS

This message is written when I/O request of Fast Path utility detects CI locks on pre allocated CIs.

SDEP CI format

IMS Version 9 does not support the IMS Version 5 DEDB CI format. Migration to the format introduced in IMS Version 6 must be done before the migration to IMS Version 9. It is highly unlikely that this will affect any installations. If an SDEP CI has been written to an area by IMS Version 6, 7, or 8, the CI format has been migrated to the *new* format.

Fast Path abend reduction

Prior to IMS Version 9, some Fast Path modules issue user abends even though the situation is not critical, for example, when a /DIS command finds a problem in its processing and causes termination of the control region.


For reducing abends, U3275, U2484, U0732 and U3999 abends are eliminated where appropriate. Instead of these user abends, a few messages are changed and a few are added. The changed messages are:

DSP0175I UNAUTHORIZATION PROCESSING WAS UNSUCCESSFUL DSP0230I UNAUTHORIZATION PROCESSING WAS UNSUCCESSFUL The solution or new messages are:

DFS0015I mmmm nn FAILED TO GET CONTROL BLOCK cccc DFS0019I DBRC UNAUTH REQUEST FAILED FOR DBD=dbdname, AREA=areaname RC=xx DFS0020I NO DDIR WAS FOUND, /DIS STATUS DB COMMAND REJECTED DFS0020I NO DMCB WAS FOUND NO FP DB IS AVAILABLE, /DIS STATUS DB COMMAND REJECTED DFS0020I DMCB HAS BAD POINTER TO DDIR, /DIS STATUS DB COMMAND REJECTED DFS0020I DMAC HAS BAD POINTER TO DMCB, /DIS STATUS DB COMMAND REJECTED

Refer to *IMS Version 9: Messages and Codes Volume 2,* GC18-7828 for the explanation of these messages.

Fast Path abend reduction is retrofitted to IMS Version 8 by APAR PQ73630 and to IMS Version 7 by APAR PQ73631.



DBRC enhancements

This chapter describes these topics:

- ► The new application programming interface (API) for DBRC
- The functional enhancements to DBRC
- ► RECON migration and coexistence.

5.1 DBRC application programming interface

Many IMS customers have created their own methods for accessing the information stored in the RECON. In the past, many organizations have parsed the output of **LIST.RECON** commands, or written their own programs that read the RECON data set directly. The problem with this approach is the requirement to modify these programs for each new release of IMS and sometimes even for the same release after the maintenance has been applied.

There is now a supported method for retrieving data from the RECON. IMS Version 9 provides an application programming interface (API) for DBRC, which allows users to write programs which read data from the RECON. These programs can access any of the records that are in the RECON. Programs using this API are now the supported and preferred method for retrieving data from the RECON. A sample program using the API is provided, in the IMS.ADFSSMP library, called DSPAPSMP.

With the DBRC API, it will not be necessary to modify the programs which read the RECON through the API. Hence users do not need to understand any of the internal formats of the information in the RECON, such as the segmentation of logical records into multiple physical records, or the format of the records.

The API is provided using the assembler language macro interface. The functions provided include:

- Start the API environment, which allocates and opens the RECONs.
- Query the RECONs, to retrieve information from the RECON into an area of memory which is allocated by the API
- Release buffer storage, after the program has finished using the information previously retrieved.
- Stop the API environment, which will deallocate the RECONs.

The DBRC API environment supports access to RECONs in IMS Version 9 or later format. Programs can access information from RECONs being used for IMS Version 7 and Version 8 systems only after the RECONs being used for these systems have been upgraded to IMS Version 9 format.

The assembler macros are in the IMS.ADFSMAC and IMS.SDFSMAC libraries, and invoke modules in SDFSRESL. The API allocates RECONs in the same manner as the utilities, with enqueues and reserves. This prevents programs for accessing information that has only been partially written by DBRC, although it also adds an extra potential lockout if the application program reads large amounts of information from the RECON.

Programs using the DBRC API execute in an application program address space, using AMODE 31/RMODE ANY. Cross memory mode is not supported. IMSplex is supported, with the PLEX name supplied in the JCL or provided by the SCI registration exit routine.

The DBRC API is documented in *IMS Version 9: Database Recovery Control (DBRC) Guide* and *Reference*, SC18-7818.

5.1.1 Application overview

The functions provided by the DBRC API macros are:

- ► DSECT
- STARTDBRC
- ► QUERY,TYPE=xxxxxxxx,...
- ► RELBUF

STOPDBRC

DSPAPI FUNC=DSECT

This macro includes into your program the required DSECTs and equates used by the API. It is required by any program using the API. The DSECTs included into your program by this macro are described in the Appendix A, "DBRC API control blocks" on page 233.

DSPAPI FUNC=STARTDBRC

This macro provides several functions. Firstly, it returns the API TOKEN, which must be stored by the program and provided on subsequent macro calls. It is used to identify this program to DBRC. The macro then opens the RECONs. The RECONs are allocated using MDA if they have not been previously allocated by the user. Alternatively, you may allocate RECONs with DD statements or by dynamic allocation (SVC 99). Finally, the macro opens the output data set (SYSPRINT), which is used for any API messages.

The default DD name for the output data set is SYSPRINT, although this may be overridden if desired.

DSPAPI FUNC=QUERY

This macro specifies the type of information that you want to access from the RECON, through the use of the TYPE parameter. The valid values for TYPE are:

RECON

Information about the status of the RECON is returned to your program.

► DB

Information about one or many databases is retrieved.

xxxGROUP

The API supports the retrieval of information from several different types of groups. These are the change accumulation group (CAGROUP), database data set groups (DBDSGROUP), database groups (DBGROUP), recovery group (RECOVGROUP), and global service group (GSGROUP).

► LOG

The recovery log and system log data set (RLDS and SLDS) information is returned.

OLDS

The online log data set (OLDS) information is returned.

SUBSYS

Subsystem information for a specific subsystem or for all subsystems is retrieved.

BACKOUT

Backout information is returned to your program, either for one subsystem or for all subsystems.

The macro will also acquire storage to hold the information provided to your program, and returns the address of the storage to the program. The format of the information is documented by the DSPAPQxx macros, which are described in Appendix A, "DBRC API control blocks" on page 233.

DSPAPI FUNC=RELBUF

This macro releases the storage acquired by IMS to hold the information returned in previous QUERY calls. This call is required, otherwise the storage allocated by previous calls by this program will not be released.

DSPAPI FUNC=STOPDBRC

This macro closes the RECONs, deallocates them if STARTDBRC allocated them, and closes SYSPRINT. It does not release the storage holding QUERY information.

Examples of database QUERY calls

The following are examples of DSPAPI FUNC=QUERY calls:

To retrieve the information from the first database record in the RECON, the following call would be used:

DSPAPI FUNC=QUERY, TYPE=DB, LOC=FIRST,...

The LOC=FIRST parameter returns first database in the RECON.

To retrieve the information for a specific database:

DSPAPI FUNC=QUERY,TYPE=DB,DBNAME=ACCDB,...

To retrieve the information about the database data set, and allocation and image copy information for database ACCDB:

DSPAPI FUNC=QUERY,TYPE=DB,DBNAME=ACCDB, DDN=ACCDS1,LIST=(ALLOC,IC),...

► To retrieve the information from the next database after ACCDB:

DSPAPI FUNC=QUERY, TYPE=DB, DBNAME=ACCDB, LOC=NEXT,...

To retrieve the information for a list of databases:

DSPAPI FUNC=QUERY, TYPE=DB, DBLIST=MYLIST,...

The data requested through FUNC=QUERY macro is returned to the program through linked blocks of storage.

The format of each of the different types of blocks that can be returned through the DBRC API is described in the *IMS Version 9: Database Recovery Control (DBRC) Guide and Reference,* SC18-7818. They can be included into your program through the DSPAPI FUNC=DSECT macro. There is a header to each block that is described by the DSPAPQHD macro, and the data portions of the blocks is described by the DSPAPQxx macros:

DSPAPQAR	Fast Path Area block
DSPAPQBO	Backout block
DSPAPQCA	CA Execution block
DSPAPQCG	CA Group block
DSPAPQDB	Full Function DB block
DSPAPQDG	DBDS, Database, and Recovery Group block
DSPAPQDS	Database Data Set DBDS) block
DSPAPQEL	EEQE List
DSPAPQFD	Fast Path DEDB block
DSPAPQGG	Global Service Group block
DSPAPQHB	HALDB block

DSPAPQHD	DBRC API query output header
DSPAPQHP	HALDB Partition block
DSPAPQIC	Image Copy block
DSPAPQLA	Log Allocation block
DSPAPQLG	RLDS/SLDS block
DSPAPQLI	Log Information block
DSPAPQNF	Not Found block
DSPAPQOL	Online Log Data Set block
DSPAPQRC	RECON Status block
DSPAPQRI	DBDS/Area Recovery Information block
DSPAPQRR	DBDS Reorganization block
DSPAPQRV	DBDS Recovery block
DSPAPQSL	DB/Area Authorized Subsystem List block
DSPAPQSS	Subsystem block

The general structure of each of these blocks is shown in Figure 5-1.




Figure 5-1 Structure of the blocks returned by the DBRC API

The information returned by the API contains two types of information, namely data and pointers. The information is chained, with pointers between the blocks, and the blocks are chained in a hierarchy.

For example, the blocks returned for a full function (non-HALDB) database are shown in Figure 5-2 on page 78. The first piece of information returned is the database block. The database block points to the block for the next database in the list. The database block also points to the first DBDS block for each database. The DBDS block points to the subsequent DBDS block for the database, as well as to recovery information for the DBDS. The recovery information block points to the allocation, image copy, recovery, and reorganization blocks. Each of these blocks (allocation, image copy, recovery, and reorganization blocks) points to

the next block of the same type (allocation to the next allocation, IC to the next IC, and so on). IMS will return only the blocks of information requested, in the macro call, to your program.




Figure 5-2 Blocks returned from a DBRC API call for a full function (non-HALDB) database

The version parameter

Programs using the DBRC API can be written to be independent of the release of IMS. The API macros have a version parameter, which is specified by the user. This parameter allows programs to remain the same when new data is added by an IMS release.

The version determines the parameters which may be specified, as well as the information returned and the format of information returned. New data is only returned to a program when a new version is specified. A version may change with IMS releases, although the version for function or type will be changed only when parameters or returned data is changed.

Version for IMS Version 9 is '1.0', which is the default.

Version numbers are not tied to a release. Each function has its own version number, and each TYPE for the QUERY function has its own version number. If a future release does not change the format of the information returned for a function or type, the version number for the function or type will not change.

Sample program overview

The structure for a typical program using the DBRC API would be as follows:

Include the API DSECTs and supply working storage, using these macros:

DSPAPI FUNC=DSECT DSPAPQxx macros

The program uses the DSPAPI FUNC=DSECT to include the required API DSECTs and equate statements which the program will use with later DSPAPI macros. The program

includes the DSPAPQxx macros to generate the DSECTs which map the blocks which it will request. The DSPAPQHD block is always used, so this macro is always needed. Other mapping macros, such as DSPAPQDB for databases, are included.

Initialize the API, which will open the RECONs and receive the API token

DSPAPI FUNC=STARTDBRC

Issue one or more QUERY requests

DSPAPI FUNC=QUERY

QUERY functions are used to retrieve information from the RECONs. These create blocks. The blocks are processed by the program to accomplish its requirements. When the blocks from a previous QUERY call are no longer needed, their storage is released with a RELBUF request.

- Process the information returned from the QUERY requests
- Release buffer storage returned for each QUERY request DSPAPI FUNC=RELBUF
- Terminate the DBRC API, which will close the RECONs

DSPAPI FUNC=STOPDBRC

DBRC API token

The DBRC API uses a token to distinguish each of the programs using the API which are running concurrently. The token is a four-byte field, returned by the DSPAPI FUNC=STARTDBRC call. The token must be supplied each time the program uses one of the DSPAPI macros to request information. When the program has finished accessing the RECON, and has processed the DSPAPI FUNC=STOPDBRC macro call, the API token is no longer valid and cannot be used again.

Storage used by programs

IMS automatically acquires storage during the processing of queries to the DBRC API. This storage is used to hold the blocks of information passed back to the application program. The address of the first block is passed to the application upon return from the macro.

DBRC never releases this storage unless specifically requested to do so. This is performed by the DSPAPI FUNC=RELBUF BUFFER=addr call. The BUFFER parameter points to first block in the chain to be released, and will release all storage connected to the block at that address.

The DSPAPI FUNC=STOPDBRC call, which is used to terminate the connection between the application and DBRC, does not release storage.

5.2 DBRC functional enhancements

There are a number of enhancements that have been added to IMS for Version 9. These include:

- Command authorization security for /RMxxxx commands
- Allow more than 32K database registrations
- ► GENJCL.IC enhancement for HALDB

5.2.1 Command authorization for /RMxxxx

IMS Version 8 added command authorization for DBRC commands, support for the DBRC utility (DSPURX00) and the Partition Definition Utility (PDU). It did not include authorization checking for the /RMxxxx commands.

IMS Version 9 support

DBRC command authorization security has been enhanced to include checking for the /RMxxxx commands through RACF (or an equivalent security product). This enhancement extends consistent security to cover online DBRC commands. The optional DBRC command authorization exit routine (DSPDCAX0) can also be used to verify that a user is authorized to issue a particular command.

The authorization support for /RMxxxx commands does not apply to commands issued from the z/OS console (MCS/E-MCS consoles and WTOR replies). They are always authorized for these DBRC commands. For other terminals, the user ID is used to evaluate authorization when it is available. The user ID is available when a user is signed on. If the user ID is not available, the LTERM name is used. For application programs using AOI, the user ID is the user ID assigned to the dependent region where the program is executed. There is an exception to the use of user ID. If a transaction whose TRANSACT macro specifies AOI=TRAN issues a /RM command by using AOI, the transaction code, not the user ID, is used to evaluate authorization.

DBRC command authorization invocation

DBRC command authorization is activated for batch and online commands by:

```
CHANGE.RECON CMDAUTH(SAF EXIT BOTH NONE, safhlq)
```

Profiles can differ for different RECONs, which is controlled by safhlq. Commands can be authorized at:

Command verb level

For example, GENJCL command

Command verb + resource type level

For example, GENJCL.RECOV command

Command verb + resource type + resource name level

For example, GENJCL.RECOV DBD(ACCDB)

Example RACF definitions:

RDEFINE FACILITY IMOA.GENJCL.RECOV.ACCDB UACC(NONE)

This restricts GENJCL.RECOV DBD(ACCDB) command for the RECONs with high level qualifier of IM0A.

PERMIT IMOA.GENJCL.RECOV.ACCDB CLASS(FACILITY) ID(JOUKO4) ACCESS(READ)

This permits user JOUKO4 to issue the command.

Example command:

/RMGENJCL DBRC='RECOV DBD(ACCDB) DDN(ACCDB1)'.

This command is only allowed when submitted by user JOUKO4.

5.3 More than 32K database registrations

The maximum number of databases that could be registered to IMS in earlier releases was 32,767. When the last DMB number assigned reached 32,767, new database registrations would fail. If a database was deleted from the RECONs, its global DMB number was not reused.

IMS Version 9 allows the registration of more than 32,767 databases, although the maximum registered at any time is still 32,767. A global DMB number is assigned to each database when it is registered. The last number assigned is kept in the RECON header. This number is incremented when a database is registered.

With IMS Version 9, when the last number assigned reaches 32,767, IMS reads the database records to discover which numbers are in use. A bit map of these numbers is created. This bit map is used to reassign numbers no longer in use. The RECON header has been modified to add a field. In IMS Version 9 there is a last number reused field. IMS Version 9 uses this to process the bit map when reusing DMB numbers. The last number reused is listed as "LAST USED DMB#=" in a listing of the RECONs. It only appears when DMB numbers have reached 32767 and are being reused. The DMB#= field indicates the highest DMB number ever used in this RECON. An example of the LIST.RECON command output is shown in Example 5-1.

Example 5-1 Sample LIST.RECON illustrating the global DMB number for a database.

```
RECON
RECOVERY CONTROL DATA SET, IMS V9R1
DMB#=32767 LAST USED DMB#=6 INIT TOKEN=02296F1600074F
...
```

The following message is issued when the global DMB number reaches the old limit and the reassignment of global DMB numbers begins:

DSP1100I DBRC IS BUILDING THE DMB TABLE RECORD

If 32,767 databases are currently registered in the RECONs, an attempt to register another database will result in the issuing of the following message:

DSP1102I THE DMB LIMIT HAS BEEN REACHED

5.4 GENJCL.IC for HALDB

The **GENJCL.IC** command does not generate DD statements for HALDB data sets. These DD statements are never needed since dynamic allocation using DBRC information is always available for HALDB. The supplied ICJCL skeletal JCL member changed from IMS Version 8, so that dynamic allocation is now used.

The benefit, especially useful for HALDB OLR users, is that the IC utilities determine which are the active data sets. It then uses this data set. For example, if the M data set is active, the utility determines this and uses the M data set. It also dynamically allocates this data set. Including a DD statement for the A data set would cause a JCL error if the A data set did not exist. For this reason, it is recommended that DD statements for HALDB data sets never be included in image copy utility JCL.

5.5 DBRC migration and coexistence

IMS Version 9 provides the usual supported migration and coexistence paths as earlier releases. You can migrate from IMS Version 7 to IMS Version 9, and fall back is supported as long as you have the IMS Version 7 DBRC SPE installed (PQ72838).

You can also migrate from IMS Version 8 to IMS Version 9, with fallback supported through the IMS Version 8 DBRC SPE (PQ72840).

To upgrade your RECONs to IMS Version 9 format, the IMS Version 9 DBRC Utility (DSPURX00) is used with the following control card:

CHANGE.RECON UPGRADE

This utility may be executed while IMS subsystems are running. The upgrade fails if there is a subsystem record for an IMS Version 7 or IMS Version 8 subsystem without the DBRC SPE installed. Some utilities do not create subsystem records, and are therefore not protected by the check of subsystem records. If they are running without the SPE, unpredictable results may occur. Examples of such utilities include: change accumulation, log archive, DSPURX00, and the HALDB Partition Definition Utility (PDU).

The RECON upgrade process, from IMS Version 7 to IMS Version 9, reads the subsystem (SSYS) records to check for the DBRC SPE. The utility then updates every record from IMS Version 7 to IMS Version 8 format, which is done for segmented record support added in IMS Version 8. The RECON header is then upgraded from IMS Version 7 to IMS Version 9 format. The time required for the upgrade depends on the number of records in the RECON.

The upgrade of IMS Version 8 RECONs is much simpler. Only the header must be changed, since the other records do not have to be read or changed. This upgrade process should be very quick.

During the RECON upgrade process, existing HALDBs are upgraded to reflect that they are not capable of running HALDB online reorganization. There is a new field for the master database listing:

ONLINE REORG CAPABLE =YES NO

There is also a new field for a partition listing:

ONLINE REORG CAPABLE =YES NO

If you are running RSR, the following RSR fields will be created:

OLR ACTIVE HARD COUNT =n OLR INACTIVE HARD COUNT =n

5.5.1 HALDB OLR coexistence

The ability to reorganize a HALDB while it is online is a new feature of IMS Version 9. However, this function is not retrofitted into earlier releases of IMS.

If a HALDB is capable of being reorganized online with OLR, then an IMS Version 7 system cannot access this database.

An IMS Version 8 system must have the OLR coexistence SPE installed before it is allowed to access any HALDB databases that are accessible with OLR. The SPE is provided through four APARs. They are PQ78493, PQ78758, PQ78916, and PQ78917. These IMS Version 8 systems can participate in data sharing while OLR is active in the IMS Version 9 system, but cannot invoke OLR.

An IMS Version 8 system without the OLR coexistence SPE cannot access a HALDB database that is defined as OLR capable in the RECON.

5.5.2 DEDB shared VSO multiple area structures

DEDBs using multiple area structures are flagged with the MAS attribute in the RECON. The MAS attribute is shown in Example 5-2.

Example 5-2 DEDB shared VSO using multiple area structures

DBDS

```
DBD=DISTDB AREA=AREADIO1 TYPE=FP
SHARE LEVEL=3 DSID=00001 DBORG=DEDB DSORG=VSAM
GSGNAME=**NULL** USID=0000000060
AUTHORIZED USID=00000000000
RECEIVE NEEDED USID=0000000000
CAGRP=PSAFPCA1 GENMAX=3 IC AVAIL=0 IC USED=3 DSSN=00000059
NOREUSE RECOVPD=0 VSO PREOPEN PRELOAD
CFSTR1=MASSTR1 CFSTR2=**NULL** LKASID MAS
```

```
•••
```

If you are using DEDBs with multiple area structures, these areas are not available to be shared with IMS Version 7 or IMS Version 8 systems.

5.5.3 MINVERS format change

The minimum version of IMS that is allowed to read the RECONs is stored using the MINVERS parameter. This is a parameter to the **INIT.RECON** and **CHANGE.RECON** commands. In prior releases of IMS, the value was stored as 71 or 81. With IMS Version 9, a period has been added to the release number displayed from the RECON, for readability. An example of the command for changing the MINVERS is as follows:

CHANGE.RECON MINVERS('9.1')

The value of MINVERS is now 7.1, 8.1, and 9.1, although 71, 81, 91 continue to be accepted for compatibility. The minimum value for MINVERS with IMS Version 9 is 7.1. If a RECON with MINVERS of 61 is upgraded to IMS Version 9, the MINVERS value is changed to the minimum, 7.1. Otherwise, upgrades do not change the MINVERS value.

An IMS Version 8 system with the DBRC SPE installed will accept either format.

5.5.4 DSPSLDRC eliminated

The SLDS RECON record mapping macro (DSPSLDRC) has been removed from IMS Version 9. The RLDS (PRILOG) mapping macro (DSPLOGRC) may be used in its place, as the SLDS and RLDS RECON records have the same format.



6

Security considerations with IMS Version 9

In this chapter we describe and provide information about security options, that is, IMS Version 9 System Authorization Facility (SAF) enhancements that provide replacement functions for security maintenance utility (SMU) security and considerations for migrating from SMU security to SAF based security. We discuss these topics:

- 6.1, "Overview of security enhancements" on page 86
- ► 6.2, "Resource access security (RAS)" on page 86
- ► 6.2.2, "RAS migration examples" on page 89
- 6.3, "AOI security" on page 91
- ▶ 6.4, "MSC link security" on page 95
- ► 6.5, "/LOCK, /UNLOCK and /SET commands" on page 97
- 6.6, "Signon verification security" on page 99
- ► 6.7, "LTERM-based terminal security" on page 104
- 6.8, "Additional migration considerations" on page 110

6.1 Overview of security enhancements

IMS Version 9 provides several security enhancements. These enhancements provide System Authorization Facility (SAF) support for several security functions that were previously provided only by IMS internal modules known collectively as the security maintenance utility (SMU).

SAF is a system service that is part of the z/OS operating system. When the SAF receives a request from IMS, it routes the request to external security products such as the Resource Access Control Facility (RACF), user-supplied pre-RACF and post-RACF SAF exit routines, or both. IMS invokes the SAF by issuing the RACROUTE macro with keywords and parameter values that describe the authorization checking request. The SAF interface provides support for RACF as well as other equivalent vendor products. Although the term RACF is used throughout this chapter, the reader should interpret the term to mean 'RACF or an equivalent security product'.

Since IMS Version 9 is the last release to provide SMU support, the security enhancements in IMS Version 9 allow IMS users to eliminate the use of SMU and migrate to SAF/RACF. From a security perspective, IMS Version 9 is a migration release because it provides the same SMU security functions that are available in prior releases as well as SAF/RACF replacements for many of the SMU functions.

This enhancement is intended to satisfy the customer requirement to eliminate the need for SMU for any security function in IMS. For any SMU function not currently supported by RACF, support is added via the SAF interface in IMS Version 9. Customers don't want to have to maintain two security packages. The IMS Version 8 announcement letter stated that SMU security will no longer be supported in a future release. Additionally SMU limits the number of resources it supports, and this continues to be a frequent problem for IMS customers. There needs to be an alternative way to request that a statically-defined terminal be required to sign on.

6.2 Resource access security (RAS)

In prior releases of IMS, application group name (AGN) security was implemented with a combination of SMU and RACF or an IMS user exit (DFSISIS0) to provide resource access security. SMU was always required. This capability allowed an IMS security administrator to define groups of resources (PSB, transaction, LTERM) by an application group name (AGN) and provide a security mechanism to determine whether or not regions, for example, BMPs, could access the resources in the protected group.

In a SMU and AGN environment, the checking process is a two-step process. The first check involves RACF. The second does not:

- Each dependent region has a user ID associated with it. Before a dependent region can connect to IMS, IMS performs a RACF authorization check to see whether the dependent region user ID can use the application group name specified in it's AGN= startup parameter. IMS performs this check using the RACF class name (AIMS) and the name of the AGN passed to it in the EXEC statement parameter list. If the region's user ID is not PERMITted to use the application group name, RACF returns a "not authorized" return code, and IMS does not allow the dependent region to connect. If RACF returns an "authorized" return code, the connection is made.
- 2. The second part of the two-step process is an IMS function only. IMS checks the name of the transaction or PSB or logical terminal that is being requested by the dependent region

against the entries in the AGN Table and allows or disallows use depending on whether the name is in the entry for the application group name.

For message processing regions and Fast Path regions, application resource access security is somewhat like class scheduling in that transactions can be scheduled only in regions whose application group name allows them. For batch message processing regions, this level of control prevents unauthorized users from starting an z/OS job that can access the resources defined in the control region.

The Figure 6-1 describes the use of SMU and AGN as a review to better understand the changes in IMS Version 9. Note that systems migrating to IMS Version 9 can continue to use this process until a migration to RACF can be completed.




Figure 6-1 Prior releases - SMU and AGN

In IMS Version 9, the two-step process is now a direct check of the user ID authorization against the specific resource. To accomplish this and ensure that the new RAS capability in IMS Version 9 provides equivalent protection, four new security classes for PSBs and LTERMs have been added.

The four new RACF security classes will be added to the RACF product as default classes. If your environment does not have the level of RACF that includes the new classes as defaults then they must be added to the installation-defined class descriptor table. Macro ICHERCDE is used to define a new class. The procedure for adding classes to this table is described in "Adding Installation-Defined Classes" in the *z/OS V1R5.0 Security Server RACF System Programmer's Guide,* SA22-7681. This is the same procedure that is used to change the default class names, for example, TIMS to Txxx where xxx is more meaningful to a specific environment. We provide an example of this later in this book, refer to "Additional migration considerations" on page 110.

IMS Version 9 provides direct SAF authorization checking of user to IMS resource by supporting the following new RACF security classes for PSBs and LTERMs:

IIMS Program specification block (PSB)

JIMS	Grouping class for PSB
LIMS	Logical terminal (LTERM)
MIMS	Grouping class for LTERM

The existing TIMS and GIMS classes continue to be used to protect transactions and groupings of transactions. APSB security using the existing AIMS security class will also continue to be done as in prior releases. The AIMS class will only be used for APSB security when SMU with AGN security is not selected for use.

The new support in IMS Version 9 is called resource access security (RAS). It is no longer called AGN. RACF, a new user exit, or both are used to provide protection. Either AGN security, or the new RAS can be used, but not both. If both are specified, then RAS is used. RAS is requested by using the system definition SECURITY macro with TYPE parameter or by execution parameter ISIS= definition. In both cases, the new values are provided in addition to the values that are already supported.

With IMS Version 9 you can have the following new specifications in system definition SECURITY macro:

TYPE=RASRACF	RAS security invokes RACF
TYPE=RASEXIT	RAS security invokes an IMS user exit DFSRAS00
TYPE=RAS	RAS security invokes RACF and user exit DFSRAS00
TYPE=NORAS	No security (turns off both RAS and SMU)

ISIS continues to be used for AGN and RAS security specifications. The parameters for AGN and RAS are unique, and can therefore correctly define the type of security desired. If ISIS=N is specified, there will be no authorization checking for the use of transactions, PSBs, and LTERMs by dependent regions. SMU will not be used either, because ISIS=1 or 2 must be specified (if the SECURITY macro has no specification) for SMU to be used for AGN. If ISIS is not specified, the default is the specification on the TYPE parameter of the IMS system definition SECURITY macro.

New specifications for ISIS execution parameter are the following:

ISIS=N	No security (turns off both RAS and SMU)
ISIS=R	RAS security invokes RACF
ISIS=C	RAS security invokes an IMS user exit DFSRAS00
ISIS=A	RAS security invokes RACF and user exit DFSRAS00
ISIS=,	defaults to SECURITY TYPE= specification

The values that already existed for ISIS include:

ISIS=0	Deactivates AGN security and (RAS)
ISIS=1	Activates AGN security using SMU and RACF
ISIS=2	Activates AGN security using SMU and the resource access security exit routine (DFSISIS0)

A new user exit interface called the resource access security exit routine (DFSRAS00) provides authorization of IMS resources to IMS dependent regions. Although this exit replaces the use of the DFSISIS0 exit routine in a RAS environment, it is not quite a direct replacement.

DFSISIS0 was called to authorize a user to an AGN name. The AGN table with that AGN name contained the IMS resources that were indirectly authorized for use. DFSRAS00 user exit is optional and available in DCCTL, DB/DC, and DBCTL environments. DFSISIS0 remains available in an AGN environment for Version 9, but AGN security and the new RAS security cannot coexist in a single IMS system.

New user exit (DFSRAS00) is called after RACF (when both are used). It provides authorization of IMS resources to IMS dependent regions in a RAS environment.

RACF and/or DFSRAS00 make checks at scheduling time using region's user ID as follows:

- Authorize user ID against transaction (MPP, JMP)
- ► Authorize user ID against PSB (IFP, NMD BMP, JBP, DRA,CCTL,ODBA)
- Authorize user ID against transaction and PSB (MD BMP)
- Authorize user ID against PSB and OUT=LTERM (NMD BMP, JBP)
- Authorize user ID against PSB and OUT=transaction (NMD BMP, JBP)

6.2.1 RAS and APSB security

When RAS is enabled, RAS check is made at every program schedule using the dependent region's (MPP, JMP, BMP, IFP and JBP) user ID. The same applies to every CICS/DBCTL program schedule; the check is made using the user ID of the CICS® address space. Completely separately, CICS can perform a check of the terminal user against the PSB. RAS checking takes place at a program schedule, and requires that the PSB is defined in the IIMS RACF class. APSB security checking takes place for an "APSB Call" and requires that the PSB is defined in the AIMS RACF class. IMS never uses both checks for the same schedule. For the ODBA APSB call, whether to use APSB or RAS security is determined by the execution parameter ODBASE as follows:

- ODBASE=Y means use APSB security
- With ODBASE=N, RAS (or AGN) security applies (if enabled)

For explicit APPC (CPI-C) APSB calls, if APSB security is performed (with the caller's user ID), the RAS check will not be made. If APSB security is not performed, RAS check (if enabled) will be performed using the region's user ID.

6.2.2 RAS migration examples

The next figures provide examples of converting from the use of SMU to SAF security.

Figure 6-2 on page 90 provides definitions for a BMP that is accessing PSB and LTERM resources.




Figure 6-2 BMP accessing PSB, LTERM resources

Figure 6-3 provides definitions for an AGN name with access to all entities of a particular resource.




Figure 6-3 AGN name with access to all entities of a particular resource

Figure 6-4 on page 91 shows a combination of resource grouping and generic resources definitions.




Figure 6-4 Combination of resource grouping and generic resources definitions

6.3 AOI security

Prior to IMS Version 9, commands issued by type 1 automated operator (AO) programs (programs using CMD calls) were secured using SMU transaction command security profiles. AO programs were restricted to issuing only the commands defined in the SMU profiles. When the type 1 AOI CMD call was issued, IMS performed the security checking using the tables/matrixes loaded during restart.

On the other hand, commands issued by type 2 AO programs (programs using ICMD calls) were secured using command profiles stored in the RACF CIMS class. Type 2 programs were also optionally secured using a user exit routine (DFSCCMD0) which could perform command authorization independently or in conjunction with RACF. When security checking was required for command keywords, the exit provided a way to implement more granular levels of command security.

IMS Version 9 provides several enhancements in this area. Type1 AOI CMD calls are now secured using the SAF interface in a fashion similar to that which was already provided for the type 2 ICMD calls. Additionally, a new parameter on the TRANSACT macro provides a greater level of granularity that can make the SAF security check closer to that which was provided for SMU.

6.3.1 SAF support for type 1 AOI (CMD)

Prior to IMS Version 9, the ICMD call of type 2 AOI (DFSAOE00) already uses the SAF interface and the command authorization exit (DFSCCMD0) for security. The CMD call of type 1 AOI (DFSAOUE0), used SMU security in prior releases. In IMS Version 9, this has been enhanced to provide the option of using the SAF interface and the DFSCCMD0 user exit.

A new startup parameter in IMS Version 9, AOI1= can be specified to indicate which security product is to be used for authorization of commands for type 1 AOI, and the level of security. If no value is specified, then IMS uses the specification in the SECURITY macro as defined in the system definition process. AOI1= parameter can be specified as follows:

AOI1=A	Includes options C and R below. SAF (RACF) is called first then DFSCCMD0
AOI1=N	No authorization security checking is done
AOI1=C	DFSCCMD0 is called for command authorization
AOI1=R	RACF is called for command authorization
AOI1=S	SMU security is called for command authorization
AOI1=,	Defaults to system definition specification on SECURITY macro

Because the AOI1 specification is not included in a checkpoint record, the AOI1 value can be changed each time IMS is initialized.

During an IMS restart, the /NRE or /ERE can specify a value of either TRANCMDS or NOTRANCMDS. This only applies to TYPE 1 AOI security. If neither value is specified on a restart then IMS uses the AOI1 startup specification or what has been defined in the SECURITY macro. A specification of TRANCMDS causes SMU to be used for type 1 AOI security and overrides TRANCMD=N in system definition and AOI1 in startup. NOTRANCMDS results in no TYPE 1 AOI security, unless prevented by the specification of TRANCMD=F during system definition and a further override by AOI1= parameter.

New parameter for TRANSACT macro

The TRANSACT macro in IMS system definition has a new parameter, AOI=, which specifies whether or not a particular transaction is allowed to issue the AOI command (CMD) call. In prior releases, this information was derived during IMS restart from the SMU matrix tables. This new parameter applies to both type 1 and type 2 AOI and is modifiable by online change. AOI= can be specified as follows:

- ► AOI=YES
- ► AOI=NO
- ► AOI=TRAN
- ► AOI=CMD

When AOI=YES is specified, the authorization of the commands for the CMD calls issued by the transaction is done using the user ID of the user who entered the transaction. For some environments, if a get unique (GU) call has not yet happened, then the program name rather than the user ID is used for the authorization.

When AOI=NO is specified, no authorization is permitted. Type 1 AOI CMD calls cannot be issued.

AOI=TRAN specification is similar to that of YES, but requests that the transaction code, be used instead of the user ID of the user who entered the transaction. Use of the transaction code provides authorization checking more like that provided by the SMU transaction-command security. When a transaction is defined with AOI=TRAN, the first authorization check done for AOI for the transaction results in the access control environment element (ACEE) being built and being kept for use by future authorization checks. In this case, the type 1 AOI transactions have to be defined to RACF as a user. The transactions must also be specified on RACF PERMIT statements for each command they are allowed to issue from a type 1 AOI transaction.

AOI=CMD specification is also similar to that of YES, but requests that the command code (first three characters of the command), be used instead of the user ID for the authorization check. Use of the command code provides authorization checking more like that provided by the SMU transaction-command security. When a transaction is defined with AOI=CMD, the first authorization check done results in the security environment (ACEE) being built, and

being kept for use by future authorization checks. In this case, the IMS command codes have to be defined to RACF as a user. The command codes must also be specified on RACF PERMIT statements for each type 1 AOI transaction that is allowed to issue them.

6.3.2 SAF support for type 2 AOI (ICMD)

The ICMD call for type 2 AOI (DFSAOE00) already uses the SAF interface along with the command authorization exit (DFSCCMD0) for security. The existing parameter AOIS continues to be valid with the following values:

- AOIS=A RACF and DFSCCMD0 are called for ICMD command authorization. RACF is called first, then DFSCCMD0.
- AOIS=C DFSCCMD0 is called for ICMD command authorization.
- AOIS=N ICMD is not issued by any application program. N is the default.
- AOIS=R RACF is called for ICMD command authorization.
- AOIS=S Skip command authorization; all application programs can issue ICMD calls.

The new parameter, AOI=, which was described in the section about type 1 AOI, also applies to type 2 AOI security. However, if AOI=NO is specified or defaulted, all transactions are still allowed to use type 2 AOI and issue the ICMD call. It will be as though AOI=YES had been specified.

If the TRAN or CMD specification is used for type 2 AOI, IMS uses the transaction code or command code, instead of the user ID of the user who entered the transaction. This is used to check the authorization of the commands for the ICMD calls issued by the transaction. Use of the transaction code or command code provides authorization checking more like that provided by the SMU transaction-command security. If the IMS environment does not support the use of a transaction, such as a non-message-driven BMP, then this new AOI= specification will not be available, and the security checking will be like prior IMS releases (or as though YES was specified).

6.3.3 SAF support for time controlled operations (TCO)

Time controlled operations (TCO) is an IMS capability to execute time-initiated commands and transactions. TCO can generate any IMS input that an IMS operator can, except for the IMS restart commands, /NRESTART and /ERESTART. Additionally, it cannot initiate conversational transactions, full-function response mode or Fast Path input transactions.

The scripts used by TCO to execute the time-initiated commands, transactions, and message switches are stored in IMS.TCFSLIB. TCO support provides security at two different levels. One capability restricts who can load TCO scripts. The other restricts which IMS commands or transactions can be accessed.

The determination of who can load TCO scripts is done by the TCO CNT edit exit (DFSTCNT0). This exit is used instead of the message switching (input) edit routine (DFSCNTE0) when the message switch destination is DFSTCF. Neither SMU security nor RACF are used to determine who is authorized. This is not a change from previous releases.

6.3.4 Resource authorization

In prior releases, IMS commands and transactions issued by TCO had the choice of using either SMU or RACF for authorization. The use of SMU security for TCO command and transaction authorization was predicated on defining the TCO LTERM names DFSTCF and

DFSTCFI in the SMU definitions. More specifically, the SMU definitions were used to define which resources could be issued by a TCO script running under this LTERM name as shown in Example 6-1.

Example 6-1 SMU sample for TCO

```
)( TERMINAL
               DFSTCFI
          COMMAND
                     START
          COMMAND
                     STOP
    TRANSACT
                STATTRN
) ( COMMAND
              START
          TERMINAL
                      DFSTCFI
) ( COMMAND
              STOP
    TERMINAL
                DFSTCFI
```

On the other hand, when the IMS startup parameter RCF was specified, SMU authorization was not used. If the script issued a /SIGN ON command, an ACEE was created and the associated user ID was available to be used in SAF calls to authorize access to transactions, but not for SAF authorization of commands.

SAF was not called to authorize access to commands because TCO was already automatically authorized to issue the same set of commands as the system console and master terminal. If the command authorization exit (DFSCCMD0) existed, it was called for command authorization.

The values of RCF = A | B | C | N | R | S | T | Y that were available in previous releases of IMS are still valid in IMS Version 9.

In IMS Version 9, a new execution parameter, TCORACF=, is used to indicate whether (Y) or not (N) the SAF interface should be called to perform an authorization check of commands from a TCO script. The value can be changed each time IMS is initialized. Therefore, specification of RCF has additional criteria. Only if both the IMS startup parameter RCF=AISIRIB and TCORACF=Y are specified, is the SAF interface invoked to call RACF. The command authorization exit routine (DFSCCMD0) is also called, if it exists. Coding a /SIGN ON command at the beginning of the TCO script can provide the user ID which will be used for authorization. The user ID defined in the /SIGN ON is signed on to IMS and not signed off until a /SIGN OFF at the end of the script. Any commands after the /SIGN ON are checked by RACF for being authorized for use by the signed on user. The commands are also passed to the DFSCCMD0 exit. DFSCCMD0 can check the input CNTNAME to see if the input is from TCO (DFSTCFI), and if it is, allow the /SIGN command without checking the user ID. For other commands, the exit can authorize the signed on user to enter that particular command.

Note: When providing a user ID/group in the /SIGN ON at the beginning of a script, the user ID/group provided must have been previously defined to RACF. If it has not, RACF returns a RC=4. As a result of the RC=4, IMS issues a FASTAUTH using the IMS control region's ACEE. If the control region's user ID/group is authorized to the command then the TCO script can also access the command. If the control region's user ID is not authorized to the command then an RC=8 is issued to deny access.




Figure 6-5 TCO command authorization sample

The Figure 6-5 assumes that RACF security profiles already exist for the START and STOP commands and for the STATTRN transaction. The TCO user ID, TCOUSID, is added to the access lists for each of the commands and for the transaction.

Although this definition could be provided in prior releases, it is not until IMS Version 9 that IMS will invoke the CIMS profile to authorize access for a TCO script.

6.4 MSC link security

Multiple systems coupling (MSC) directed routing is a function of IMS that allows for the routing of messages to other IMS systems without the target resources having to be defined as remote resources in the sending IMS. This capability relies on the application, in the sending IMS, to specify the logical link path (MSNAME) as the destination of the message. Additionally, the sending application provides the actual target LTERM or transaction name in the first few bytes of the IOAREA. When the message is received at the destination, the LTERM or transaction code is removed from the message by the link receive entry point of the DFSMSCE0 exit and the message enqueued for the proper destination.

Non-directed routing, on the other hand, relied on all target destinations in the remote IMS to be defined as remote resources on the sending system. For releases prior to IMS Version 9 where MSC link input to transaction destinations used directed routing, SAF(RACF) and the DFSCTRN0 user exit were called before and after the DFSMSCE0 user exit call. Otherwise, for non-directed routing, SMU security was called after the DFSMSCE0 call. Figure 6-6 on page 96 shows the difference between directed and non-directed routing.




Figure 6-6 MSC link security

For IMS Version 9, a new startup parameter defines the type of security required for MSC. In the DFSDCxxx PROCLIB member, the new keyword is MSCSEC, and it can be defined as follows:

MSCSEC=(parm1,parm2)

The first parameter (parm1) can have the following values:

LRDIRECT	Link receive directed routing transaction security checking
LRNONDR	Link receive non-directed routing transaction security checking
LRALL	LRDIRECT and LRNONDR
LRNONE	No link receive security checking

The value of the second parameter (parm2) in MSCSEC specifies the level of authorization and can be one of the following:

CTL	Authorization by CTL address space security
MSN	Authorization by MSNAME
USER	Authorization by user ID of inputting terminal
EXIT	Authorization by user exit (DFSCTRN0)
CTLEXIT	Authorization by CTL address space security and by user exit (DFSCTRN0)
MSNEXIT	Authorization by MSNAME and by user exit (DFSCTRN0)
USREXIT	Authorization by user ID of inputting terminal and by user exit (DFSCTRN0)
NONE	No security authorization checking

With the link receive security available in previous releases, directed routing and non-directed routing use different user IDs. To provide similar flexibility with the new security, the DFSMSCE0 user exit can be used to dynamically set the required level of authorization by overriding the parm2 value.

6.4.1 IMS Version 9 MSC security considerations

Some considerations in the IMS Version 9 environment include the following:

- SMU security can still be invoked when non-directed routing is used and MSCSEC=LRNONDR is not specified.
- There will no longer be calls to SAF and the DFSCTRN0 user exit prior to calling the DFSMSCE0 user exit during link receive processing.
 - DFSMSCE0 can set the level of authorization checking
 - Calls to SAF and DFSCTRN0 are made after DFSMSCE0
- Additional data will be passed to the DFSMSCE0 user exit including: user ID, group name, and user ID indicator. The user ID indicator clarifies the value in the user ID field as being one of: user ID, LTERM name, PSB name, MSNAME, or other.
- RACF profiles should be kept synchronized on sending and receiving systems

The DFSMSCE0 user exit call during link receive processing has the ability to control the level of authorization checking. The user exit response in field MSLRFL3 specifies the level of authorization as one of the following:

- Authorization by MSNAME where the ACEE is dynamically created for the first authorization, then reused.
- Authorization by CTL address space security.
- Authorization by user ID of inputting terminal where the ACEE is dynamically created and deleted for each authorization.
- Authorization by user exit DFSCTRN0.
- No security authorization checking.

On entry to the DFSMSCE0 user exit for link receive, the MSLRFL3 field contains the system default value from the MSCSEC= startup parameter.

The security authorization options that can be returned by the DFSMSCE0 user exit in field MSLRFL3 are also provided as a startup option. These new options are specified as the second value in the MSCSEC= keyword in the DFSDCxxx PROCLIB member as described in the previous section.

6.5 /LOCK, /UNLOCK and /SET commands

The /LOCK command is used to stop the sending and receiving of messages to and from a terminal, stop the scheduling of messages containing a specific transaction code, stop the scheduling of a specific program, stop the use of a database, and stop the sending of messages to and from an LTERM, a NODE or a physical terminal. The /UNLOCK command releases the resource. /SET command establishes the destination of all messages entered into this terminal to another terminal or to a particular transaction code. If the terminal is in conversation, the /SET command also sets the destination of only the next message to the specified transaction.

The /LOCK, /UNLOCK and /SET commands also support specification of password security for the defined resource. In prior releases, this was accomplished with the use of SMU. If the resource was not defined with password protection in SMU, the check was not made and the password ignored.

Password protections was by the specification of the PASSWD= parameter on the SECURITY macro along with the appropriate SMU definitions. There were, however, certain restrictions:

- ► The /LOCK DATABASE, /LOCK PROGRAM, and /LOCK TRANSACTION commands are only valid when entered from a master terminal, system console, TCO script, or AO program.
- The /LOCK TRANSACTION command cannot be used for CPI-C driven programs.
- The /LOCK LTERM, /LOCK NODE, and /LOCK PTERM commands apply only to the entering physical terminal.

In prior releases, SMU provided password security. For example, if the SMU definitions were provided as seen in Example 6-2, and the following conditions were met:

- in SECURITY macro in IMS system definition, PASSWD=YES is defined
- IMS is started using /NRE or /ERE COLDSYS PASSWORD -command

The operator needed to specify the password to be able to enter the /LOCK, /UNLOCK or /SET command, as follows:

- /LOCK DATABASE payroll (uomecash)
- /UNLOCK DATABASE payroll (uomecash)
- /SET TRANSACTION paytran (uomecash)

Example 6-2 SMU definition sample

)(DATABASE PAYROLL PASSWORD UOMECASH)(PASSWORD UOMECASH DATABASE PROGRAM TRANSACT PAYROG PAYTRAN

In IMS Version 9, the security of the LTERM, database, program, and transaction parameters include the use of SAF (RACF) and/or the transaction authorization exit (DFSCTRN0). The resources are defined to RACF in the classes: LIMS, PIMS, IIMS, and TIMS respectively. Because this SAF and exit call were not made in prior releases, the call cannot be made unconditionally beginning in IMS Version 9. Therefore, a new startup option LOCKSEC=YIN (where N is the default) has been added to the DFSDCxxx IMS.PROCLIB member.

If LOCKSEC=Y is specified, the new SAF and user exit calls are made after the optional call to SMU security. If the resource is not defined to RACF, or is defined and is authorized to the user, the command is processed. If the resource is defined to RACF but is not authorized for use by the user entering the command, the command is rejected with the following new message:

DFS3689W USE OF <TRANSACTION | LTERM | DB | PROG> resourcename BY <LOCK | UNLOCK> REJECTED

If the user is authorized to issue the /LOCK, /UNLOCK and /SET commands with CONVERSATION and TRANSACTION keywords, another check is made to authorize access to resources. Refer to Figure 6-7 on page 99. Note that no SAF call is made for /LOCK and /UNLOCK NODE | PTERM. Protection of VTAM nodes and BTAM terminals relies on the use of RACF TERMINALIGTERMINL support. The password after the parameter "payroll" can optionally be checked if the authorization check of the parameter is successful. If the RACF profile for the IMS resource (such as "payroll") is defined with the parameter

"APPLDATA('REVERIFY')", then IMS will check that the password is the same as the user's signon password.

		IGNORED (uopecash)
RACF RESOURCE CLASS LIMS IIMS TIMS * PIMS *	RESOURCE(S) LTERMs PROGRAMs TRANSACTIONS DATABASEs	new resource classes existing resource classes

Figure 6-7 /LOCK command authorization checking

6.6 Signon verification security

In previous releases, statically defined terminals were only required to signon if the terminal was defined in SMU as being required to do so. This was done with the)(SIGN control statement. SMU, however, was limited to supporting:

- A maximum of 65535 LTERM definitions
- A maximum of 32767 different patterns for sets of commands and transactions (a pattern is a unique set of commands and/or transactions that can be issued by terminals)
- A maximum of 32767 terminals to require sign-on

Example 6-3 shows the SMU method for static terminal signon verification, that defines which terminals have to sign on using the /SIGN ON command.

Example 6-3 SMU input statements for requesting signon security

)(SIGN			
STERM	TERM1		
STERM	TERM2	OR	STERM ALL
STERM	TERM3		

In IMS Version 9, a new initialization parameter, SIGNON=, is provided in the DFSDCxxx PROCLIB member to request that static terminals be required to signon. The format and the options for SIGNON are:

- ► SIGNON=ALL
- SIGNON=SPECIFIC

Specification of ALL requests that all static terminals be required to signon. This is equivalent to the SMU definition of)(SIGN STERM ALL. Note that like the SMU support, SIGNON=ALL will not set sign on required in LU6.1, 3284/3286, SLU1 (when printer-only device), and master terminal devices.

The use of SPECIFIC defines that individual static terminals may be required to signon. These terminals will be specified in either system definition with the OPTIONS=SIGNON parameter on the TYPE and/or TERMINAL macros, or via SMU definitions with the)(SIGN statements.

Signon verification security can also be defined for individual terminals via new options on the IMS system definition TYPE and TERMINAL macro statements. The new parameters on the OPTIONS= keyword are SIGNON and NOSIGNON, with NOSIGNON as the default on the TYPE macro. The specification on the TERMINAL macro, if specified, overrides the value from the TYPE macro and no specification on the TERMINAL macro defaults to TYPE macro.

Signon verification for BTAM terminals can be requested on the IMS system definition TERMINAL macro statement using the OPTIONS= SIGNON | NOSIGNON. This specification only applies to TERMINAL macro, and is not available on LINEGRP or LINE macros.

Whatever signon option is requested in system definition for a static terminal, can also be requested in SMU. The SMU settings are applied during IMS restart. The setting in the terminal control block specifying signon required is not reset by not being specified in SMU. The signon required specification can be made in system definition and SMU.

6.6.1 Sign on for static terminals

By default, IMS does not require static terminals to sign on. In IMS Version 8 and prior releases, three specifications are coded to:

- Determine whether or not sign on security is activated for one or more static terminals. The sign on security option is specified on SECLVL statement on the SECURITY macro.
- Determine whether or not SMU is invoked to enforce sign on for the static terminals that are required to sign on. The value specified on the TERMNL statement on the SECURITY macro specifies whether:
 - SMU sign on security is activated for static terminals
 - LTERM-based terminal security is activated for commands and transactions entered from static terminals
 - Both sign on and LTERM-based security are activated
- Identify the specific static terminals for which SMU is invoked to enforce sign on. The static terminals that are required to sign on are identified in SMU statements which supply the input for the SMU generation process. The static terminals that are required to sign on are identified in)(SIGN and STERM statements in SMU generation input.

6.6.2 Security level (SECLVL)

The value supplied for the sign on security level on the SECLVL= keyword on the SECURITY macro determines whether or not sign on security is activated for one or more static terminals. It is important to note that the value supplied for SECLVL has no effect on SMU security. It only indicates whether or not sign on security is activated in the IMS system. SECLVL does not designate which security facility (for example SMU, RACF, a user-coded exit routine, or a combination of these) is to be invoked to enforce sign on. Table 6-1shows the possible SECLVL values and their meanings.

Table 6-1	SECLVL	values
-----------	--------	--------

SECLVL Value	Meaning
SECLVL=(,NOSIGN)	Sign on security is not activated, but may be activated on the /NRE or /ERE command issued to restart IMS. NOSIGN is the default.

SECLVL Value	Meaning
SECLVL=(,SIGNON)	Sign on security is activated, but may be deactivated on the /NRE or /ERE command issued to restart IMS.
SECLVL=(,FORCSIGN)	Sign on security is activated and FORCED. This means sign on security cannot be deactivated on the /NRE or /ERE command issued to restart IMS.

The value specified (or defaulted to) for the sign on security level on the SECLVL keyword on the SECURITY macro may be overridden by the value specified for the SGN= keyword in IMS execution parameters in the DFSPBxxx member of IMS.PROCLIB. SGN=Y and SGN=F activate sign on security for static terminals and are equivalent to SECLVL=(...,SIGNON) and SECLVL=(...,FORCSIGN), respectively. The USER keyword on the /NRE and /ERE commands also activates sign on security. Specification of the USER keyword on the /NRE and /ERE and /ERE overrides both SECLVL= (...,NOSIGN) on the SECURITY macro and SGN=N in IMS execution parameters.

Note: Forced sign on security may be deactivated on the SGN= keyword in IMS execution parameters in the DFSPBxxx member or IMS.PROCLIB.

Since the specifications for SECLVL and SGN merely activate or deactivate sign on security for static terminals and do not affect SMU security, replacement functions are not needed. The specifications for SECLVL and SGN have the same meanings in IMS Version 9 as in prior releases.

6.6.3 SMU terminal (TERMNL) security

The value supplied for the TERMNL= keyword on the SECURITY macro determines whether or not SMU modules are invoked to enforce LTERM-based terminal security in the IMS system. Table 6-2 shows the possible TERMNL values and their meanings.

TERMNL Value	
TERMNL=NO	SMU modules are not invoked to enforce LTERM-based terminal security. LTERM-based terminal security may be activated on the /NRE or /ERE command issued to restart IMS. TERMNL=NO is the default.
TERMNL=YES	SMU modules are invoked to enforce LTERM-based terminal security. LTERM-based terminal security may be deactivated on the /NRE or /ERE command issued to restart IMS.
TERMNL=FORCE	SMU modules are invoked to enforce LTERM-based terminal security. LTERM-based terminal security cannot be deactivated on the /NRE or /ERE command issued to restart IMS.

Table 6-2 TERMNL values

IMS Version 9 SAF/RACF replacement for SMU does not provide a replacement for SMU LTERM-based terminal security. SMU LTERM-based terminal security is used to restrict the entry of IMS commands and/or transactions to one or more authorized LTERMs. SAF/RACF functions provide user ID-based command and transaction authorization checking. Unlike SAF/RACF, SMU provides terminal-based command and transaction authorization checking. If your company has a requirement to provide LTERM terminal-based security checking for commands and transactions entered from static terminals, a user-coded exit routine may be used in conjunction with SAF/RACF user ID-based command and transaction authorization security to accomplish this.

The migration considerations for LTERM-based terminal security are described in the topic "LTERM-based terminal security" on page 104.

6.6.4 SMU)(SIGN and STERM statements

The static terminals that are required to sign on can be specified in SMU using the)(SIGN and STERM control statements. The terminals required to perform sign on are identified in SMU input statements that are processed during the execution of the security maintenance utility, or SMU generation. SMU security definitions are created by executing the SECURITY procedure, a member of IMS.PROCLIB. One of the outputs of a SMU generation is the signon offset list (DFSISSOx) module. The signon offset list may be referred to as the signon matrix or the signon table. Example 6-4 shows a sample input statements of SMU generation to require several static terminals (NODE1, NODE2, and NODE3) to sign on, and a sample statement to require all static terminals to sign on.

Example 6-4 SMU generation sign on input statements

```
)( SIGN
STERM NODE1 *Sign on is required for NODE1*
STERM NODE2 *Sign on is required for NODE2*
STERM NODE3 *Sign on is required for NODE3*
-OR-
)( SIGN
STERM ALL *Sign on is required for all static terminals*
```

When SMU is used to enforce sign on, DFSISSOx is loaded from the active IMS.MATRIX data set into IMS control region storage during restart. Any input from a static terminal causes IMS to check DFSISSOx to determine if the terminal is required to sign on. When a static terminal is required to sign on, the terminal will only accept the /SIGN and /RCLSDST commands.

6.6.5 IMS Version 9 sign on security for static terminals

In prior IMS versions, either SAF/RACF or a user-coded exit routine is needed to perform sign on security for static terminals. Although SMU modules can ensure the /SIGN ON command is entered from a static terminal, there is no logic in SMU modules that verify the user ID and password supplied on the command. SAF/RACF, the sign on exit routine (DFSSGNX0), the sign on/off security exit routine (DFSCSGN0), or a combination of these is required to validate the user ID and password supplied on the /SIGN ON command.

As in prior versions, the inclusion of one or both of the user-coded exit routines in the IMS system and the value specified for the RCF= execution parameter in the DFSPBxxx member of IMS.PROCLIB determine whether user exits and/or SAF/RACF is used to validate the user ID and password. The RCF= values that cause IMS to invoke RACF for sign on security checking for static terminals are: RCF=T, RCF=S, RCF=A, RCF=B, and RCF=R. The RCF= values have not changed and continue to work the same way in IMS Version 9 as in prior IMS releases. What has changed in IMS Version 9 is that new non-SMU methods are available for identifying the static terminals that are required to sign on.

The sign on security enhancements for static terminals in IMS Version 9 are:

- A new execution parameter, SIGNON=ALL | SPECIFIC, in the DFSDCxxx member of IMS.PROCLIB, is used to specify whether all or a subset of the static terminals are required to sign on.
- Two new keywords, SIGNON and NOSIGNON, on the OPTIONS statement on the TYPE and TERMINAL macros define sign on security requirements for static terminals

The value specified for the new SIGNON= keyword in DFSDCxxx and the SIGNON and NOSIGNON keywords on the OPTIONS statements for the TYPE and TERMINAL macros provide replacements for the SMU generation process where)(SIGN and STERM statements are used to define static terminal sign security requirements in SMU environments. An additional benefit of the new enhancement is that the signon offset list (DFSISSOx) matrix table does not have to be maintained or loaded during IMS restart.

6.6.6 New keywords on the OPTIONS statement

Sign on verification security can be defined for VTAM terminals via new options on the IMS system definition TYPE and TERMINAL macro statements. To implement sign on verification for statically defined VTAM terminals, set the OPTIONS= keyword to OPTIONS=SIGNON in the TYPE or TERMINAL system definition macro. No specification for OPTIONS= on the TERMINAL macro defaults to the value specified for OPTIONS= on the TYPE macro. A specification of OPTIONS=SIGNON or OPTIONS=NOSIGNON on a TERMINAL macro overrides the value set on the TYPE macro for that specific static terminal. The default for OPTIONS= on both the TYPE and TERMINAL macros is NOSIGNON.

Sign on verification for BTAM terminals can only be requested on IMS system definition TERMINAL macro statements using OPTIONS= SIGNON or OPTIONS=NOSIGNON. To implement sign on verification for statically defined BTAM terminals, set the OPTIONS= keyword to SIGNON in the system definition TERMINAL macro. The default for OPTIONS= in the TERMINAL macro is NOSIGNON.

SIGNON=ALL and SIGNON=SPECIFIC

Instead of specifying OPTIONS=SIGNON or OPTIONS=NOSIGNON in multiple TYPE and TERMINAL macro statements, all static terminals may be required to sign on by specifying a single parameter, SIGNON=ALL, in the DFSDCxxx member of IMS.PROCLIB. There are some exceptions when SIGNON=ALL is specified. The following devices are not required to sign on when SIGNON=ALL is used unless the OPTION statement on the TYPE or TERMINAL macro is set to OPTIONS=SIGNON:

- LU6.1 devices
- ► 3284/3286 devices
- SLU1 printer-only devices
- Master terminals

Alternatively, a specification of SIGNON=SPECIFIC in DFSDCxxx indicates that individual static terminals might be required to sign on. SIGNON=SPECIFIC is the default value for the SIGNON= keyword in the DFSDCxxx member. The static terminals which are required to sign on are identified in either:

- System definition TYPE or TERMINAL macro statements with the OPTIONS=SIGNON parameter
- ► By SMU generation input)(SIGN and STERM statements

6.6.7 Static terminal sign on security migration considerations

The use of SMU to identify and enforce sign on for static terminals may be eliminated in IMS Version 9. Migration to SAF/RACF user ID-based sign on security may be accomplished by performing all of the following tasks.

 Specify SIGNON=ALL or SIGNON=SPECIFIC in the DFSDCxxx member of IMS.PROCLIB.

- If SIGNON=SPECIFIC is used, identify the static terminals that are required to sign on by specifying OPTIONS=SIGNON in IMS system definition TYPE or TERMINAL macro statements.
- Specify values for RCF= and SGN= in the DFSPBxxx member of IMS.PROCLIB that cause IMS to invoke SAF/RACF for sign on security checking without loading the signon offset list (DFSISSOx) matrix table during IMS restart. These specifications are:
 - RCF=B or RCF=R
 - SGN=D, SGN=E, SGN=W, or SGN=X

The RCF and SGN values above may be used on IMS Version 7 and subsequent releases.

Performing the above tasks causes IMS to invoke SAF/RACF to enforce sign on for static and ETO terminals. RACF verifies that the user ID and password supplied on the /SIGN ON command are valid. Optionally, the sign on exit (DFSSGNX0) and or the sign on/off security exit (DFSCSGN0) may be used in lieu of SAF/RACF or in conjunction with RACF.

To further restrict specific user IDs or groups to signing on from specific IMS terminals, define terminal profiles in the RACF TERMINAL and GTERMNL resource classes to protect the terminals and authorize the user IDs/groups that are authorized to use the protected terminals to sign on.

6.7 LTERM-based terminal security

SMU provides LTERM-based terminal security for IMS commands and/or transactions entered from static terminals. LTERM-based terminal security restricts the entry of certain IMS commands and/or transaction codes to specific LTERMs. LTERM-based terminal security is activated by specifying one of the following:

- TERMNL=YES or TERMNL=FORCE on the SECURITY macro in IMS system definition macros. A description of these SECURITY macro specifications is provided in Table 6-2 on page 101, TERMNL values.
- TERMINAL on the /NRE or /ERE command issued to restart IMS.

The IMS commands and/or transactions that are restricted to entry from specific (or authorized) LTERMs are identified in input statements to the SMU generation process. The output from the SMU generation is a set of matrix tables which contain the LTERM restrictions. The matrix tables created for enforcement of LTERM-based terminal security are the:

- Terminal offset list
- Transaction offset list
- Communications terminal matrix

Figure 6-8 on page 105 illustrates how an LTERM-based entry restriction for a command is defined to the SMU generation process. It shows that the /LOCK command and TRANA may only be entered from the static terminal (in this case NODE5) which has LTERM5 assigned to it.




Figure 6-8 Generating LTERM-based security

If LTERM-based terminal security is activated, IMS loads the matrix tables from the active IMS.MATRIX data set into control region storage during restart. When an IMS command or transaction code is entered from a static terminal, IMS invokes SMU modules to determine if LTERM-based entry restrictions exist for the command or transaction code. SMU modules use the matrix tables loaded during restart to enforce the LTERM-based terminal entry restrictions for commands and transactions entered from static terminals.

6.7.1 Migration considerations for LTERM-based terminal security

IMS Version 9 does not provide a SAF/RACF replacement for LTERM-based terminal security. As with prior IMS versions, SAF/RACF user ID-based command authorization and transaction authorization security checking is provided. IMS users should migrate LTERM-based terminal security to SAF/RACF user ID-based command and transaction authorization security checking. This may be accomplished by performing the following tasks:

- Define command profiles to protect IMS commands in the CIMS, DIMS, or equivalent installation-defined RACF resource classes.
- Define transaction profiles to protect IMS transactions in the TIMS, GIMS, or equivalent installation-define RACF resource classes.
- Authorize the RACF user IDs, or preferably the RACF groups, to the appropriate profiles.
- Activate the RACF resource classes (CIMS, DIMS, TIMS, GIMS, or equivalent installation-defined classes) if they are not already activated.
- If the current specification on the SECURITY macro in IMS system definition macros is set to TERMNL=FORCE, change the value to specify TERMNL=NO and regenerate IMS.
- If the current specification on the SECURITY macro in IMS system definition macros is set to TERMNL=YES, add the NOTERMINAL keyword to the /NRE or /ERE command issued to restart IMS.

Specify a value for the RCF= keyword in IMS execution parameter that causes IMS to invoke SAF/RACF for command and/or transaction authorization security checking. Any values other than RCF=N and RCF=C may be used.

If LTERM-based terminal security is still required for certain commands and/or transaction codes entered from static terminals, there may be a number of ways to restrict terminal input to specific LTERMs.

6.7.2 IMS commands

One way to restrict IMS commands to specific LTERMs when the commands are entered from static terminals is to use SAF/RACF in conjunction with the command authorization exit routine (DFSCCMD0). Normal RACF command authorization checking, based on user ID/group, may be used. When both RACF and the exit are used to provide command security, DFSCCMD0 is invoked after SAF/RACF. The parameter list passed to the exit contains the SAF and RACF reason and return codes.

Figure 6-9 on page 107 shows an example of the DFSCCMD0 exit logic flow. The sample DFSCCMD0 exit is coded to determine if command input is entered from a STATIC or ETO terminal. The sample exit branches to the label 'STATIC' when the command input is from a static terminal. If DFSCCMD0 determines that RACF authorized the user ID to the command (or that the command was not protected) and the command is from a static terminal, the exit could be coded to re invoke SAF/RACF to check a RACF resource class to determine if the command can be entered from the inputting LTERM.

For example, a FACILITY class profile or a user-defined installation resource class could be used to determine if the command and static LTERM combination are valid. The exit could obtain the name of the static LTERM used to enter the command. Next, DFSCCMD0 could be coded to construct a RACF profile name from a combination of the command verb and the inputting LTERM name. Finally, the exit could invoke SAF/RACF to determine if the user ID/group is authorized to the command-LTERM profile.




Figure 6-9 Sample DFSCCMD0 flow

Security administrators can define RACF profiles in the FACILITY resource class (or an installation-defined resource class) to protect the command-LTERM combination. Example 6-5 shows sample RACF commands to create profiles in the FACILITY class for the /LOCK command entered from static LTERM5. In the example, USERA must be authorized to command-LTERM combination to successfully enter the /LOCK command from LTERM5.

Example 6-5 Sample class profile

RDEFINE FACILITY LOC.LTERM5 UACC(NONE) PERMIT LOC.LTERM5 CLASS(FACILITY) ID(USERA) ACCESS(READ)

Finally, prior to returning control to IMS, DFSCCMD0 can set register 15 to a return code that indicates the result of the SAF/RACF check:

RACF RC=0

The user ID (for example, USERA) is authorized to the command-LTERM combination

RACF RC=4

The command-LTERM combination is not defined to RACF. By default, IMS allows the command from the LTERM.

RACF RC=8

The user ID (for example, USERA) is not authorized to the command-LTERM combination

There are several other ways to accomplish the same thing using SAF/RACF and DFSCCMD0.

An advantage of this type of implementation is that it does not have to be limited to commands entered from static terminals. The scheme could work for restricting the entry of certain commands entered from ETO terminals as well.

6.7.3 IMS transactions

A similar scheme as the one described for restricting IMS commands to entry from specific static LTERMs can be used for IMS transactions entered from static terminals. The exception is that the transaction authorization exit (DFSCTRN0) is used instead of DFSCCMD0.

One difference in exit processing for transactions is that if RACF denies access (RACF RC=8) to the inputting user ID (for example USERA), DFSCTRN0 is not invoked. This is as it should be because if the user ID is not authorized to the transaction, additional security checking is unnecessary.

An additional consideration for transactions is that if the security reverification exit (DFSCTSE0) exists, it is invoked for transactions requested by DL/I CHNG and AUTH calls. Application programs are already coded to make the final decision for transactions requested by AUTH calls, so the major consideration here is for transactions requested by CHNG calls. If either SAF/RACF or DFSCTRN0 denied authorization to a transaction-LTERM combination, DFSCTSE0 should also be coded to deny authorization.

6.7.4 Migration considerations for LTERM-based security

Figure 6-10 show the considerations when migrating LTERM-based security from the use of SMU to the use of SAF/RACF. The first three areas show specific SAF/RACF solutions to assist in LTERM migration considerations.




Figure 6-10 SMU SAF considerations

Figure 6-11 on page 110 shows two additional areas of concern. These two areas in Figure 6-11 on page 110 are a little more complex since there is no direct SAF equivalent.

To migrate LTERM-based command security, consider using RACF in conjunction with the command authorization exit (DFSCCMD0) routine. Normal RACF command authorization checking based on user ID/group may be used. If it exists, the command authorization exit DFSCCMD0 is always invoked after RACF for commands entered from IMS terminals. The sample DFSCCMD0 exit that was described in the previous section, is coded to determine if a terminal is ETO or STATIC. If DFSCCMD0 determines that the command is from a static terminal, rather than accept the command, the exit could be changed to re invoke RACF to do one of the following:

Check a special user-defined RACF profile.

For example, the exit could obtain the name of the static LTERM used to enter the command and construct a RACF profile name from a combination of the command verb and inputting LTERM name. Finally, the exit could invoke RACF to determine if the user ID/group is authorized to the command/LTERM profile.

Invoke the command as a user ID.

This alternative approach would be to RACF protect all the static LTERMS that were defined in SMU using the new RACF LIMS resource class. Additionally, since there are only about 50 commands, they could be defined to RACF as user IDs. DFSCCMD0 could then verify (build the ACEE) for the IMS command as a user ID and authorize it against the LTERM name.

Similar techniques as those described above for restricting commands could be used for restricting transactions. The difference would be that the transaction authorization exit (DFSCTRN0) would be used instead of DFSCCMD0. Note, however, that DFSCTRN0 is not called for any further security checking if the user ID is not authorized to the transaction. As with the command examples, you could also do all of the following to accomplish the same thing:

- Protect all of the static LTERMs in the new LIMS resource class provided by IMS Version 9
- Define the affected IMS transactions as RACF user IDs
- Use RACF's VLF ACEE cache so the transaction ACEEs are always in storage to eliminate I/O to the RACF DB
- Invoke RACF to VERIFY (build the ACEE) for the IMS transaction name as user ID if one did not already exist.




Figure 6-11 SMU SAF LTERM based

6.8 Additional migration considerations

There is a software dependency on the RACF product to include the four new RACF security classes as default classes. If the new classes have not yet been added to the RACF product, they must be added to the installation-defined class descriptor table (CDT). Macro ICHERCDE is used to define a new class.

The procedure for adding classes to this table is described in "Adding Installation-Defined Classes" in the *z/OS V1R5.0 Security Server RACF System Programmer's Guide*, SA22-7681. These classes are provided with z/OS 1.6 Security Server Defined Resource Classes.

RACF supplies jobs to update the CDT in SYS1.SAMPLIB. These new classes should also be defined to the RACF router table, ICHRFR01. The member RACTABLE has a sample for updating the router table. Example 6-6 shows how the macros can be modified to define the new IMS classes IIMS, JIMS, LIMS and MIMS.

Example 6-6 A sample update of the CDT for the new IMS classes

IIMS	CSECT	
	ICHERCDE CLASS=IIMS,GROUP=JIMS,ID=128,RACLIST=DISALLOWED,POSIT=575,	
	OPER=NO,FIRST=ALPHA,OTHER=ALPHANUM,DFTUACC=NONE	
	ICHERCDE CLASS=JIMS,MEMBER=IIMS,ID=129,RACLIST=DISALLOWED,POSIT=575,	
	OPER=NO,FIRST=ALPHA,OTHER=ALPHANUM,DFTUACC=NONE	
	ICHERCDE CLASS=LIMS,GROUP=MIMS,ID=130,RACLIST=DISALLOWED,POSIT=576,	
	OPER=NO,FIRST=ALPHANUM,OTHER=ALPHANUM,DFTUACC=NONE	
	ICHERCDE CLASS=MIMS,MEMBER=LIMS,ID=131,RACLIST=DISALLOWED,POSIT=576,	
	OPER=NO,FIRST=ALPHANUM,OTHER=ALPHANUM,DFTUACC=NONE	
	ICHERCDE	

L

L

END

... (left out the JCL statements from here... ICHRFR01 CSECT ICHRFRTB CLASS=IIMS,ACTION=RACF ICHRFRTB CLASS=JIMS,ACTION=RACF ICHRFRTB CLASS=LIMS,ACTION=RACF ICHRFRTB CLASS=MIMS,ACTION=RACF ICHRFRTB TYPE=END END ICHRFR01

For environments that migrate to IMS Version 9 and choose to start out using only SMU security, a specification of RCF=N is supported. When migrating to the use of SAF begins, the RCF parameter will need to be specified appropriately. Switching from a value of "N" to anything else requires that the IMS system be cold started.

If an IMSplex contains IMS Version 9 systems along with prior release systems, the NORSCCC(MODBLKS) parameter in the DFSCGxxx PROCLIB member should be specified to disable a part of the resource consistency checking. By including the specification, the MODBLKS and MATRIX data set names are not checked for consistency which means that the IMSs in the IMSplex do not need to define the same data sets for the MODBLKS and MATRIX library. The MATRIX data sets are still required in IMS Version 9, but they may be empty if SMU security is not used.

Customers could possibly have a conflict between transaction names for AOI defined as users to RACF and current user IDs for users defined to RACF. A similar conflict could exist for MSNAMEs used for MSC security and user's user IDs.

From an operations point of view, notice that messages DFS066 (password security violation) and DFS067 (terminal security violation) are replaced by RACF ICH408I messages.

6.8.1 Performance considerations

The use of RACF security may be slower than checking a SMU security matrix table, however the frequency of the type of security checking being made available is not that high, so the performance impact should not be significant.

When taking advantage of MSC link security, several options are provided to control the level of security. The choices impact the amount of checking, and overhead that is used. In the link receive environment, the calls to SAF and DFSCTRN0 are limited to being made after the call to DFSMSCE0 instead of before and after, as in previous releases.

6.8.2 AOI considerations

There are three new return/reason codes for an ICMD call when AOI=CMD is specified:

▶ 0110/0054 - Command not authorized to RACF.

An AO application tried to issue an IMS command. Security checking determined that the command is not authorized to RACF as a user ID.

 \blacktriangleright 0110/0058 - Command not authorized to be issued by the transaction.

An AO application tried to issue an IMS command. Security checking determined that the command is not authorized to RACF to be issued by the transaction.

► 0110/005C - DFSCCMD0 indicated command was not authorized to be issued by transaction.

An AO application tried to issue an IMS command. The command authorization exit routine (DFSCCMD0) indicated the command was not authorized to be issued by the transaction.

There are also three new return/reason codes for an ICMD call when AOI=TRAN is specified:

- 0110/0044 Transaction not authorized to RACF.
- 0110/0048 Transaction not authorized to issue the command.
- ▶ 0110/004C DFSCCMDO indicated transaction was not authorized to issue command.

The explanations for these are similar to the ones for AOI=CMD with transaction replacing command in the text.

The X'10' log record (described by DFSLOG10) has four new error codes defined for the SCERROR field. The codes and their meanings are the following:

CMD FAILED, DFSCCMD0 UNAVAILABLE

160	CMD USERID NOT DEFINED TO RACF
161	CMD USERID NOT AUTH TO COMMAND
162	CMD REJECTED BY DFSCCMD0

6.8.3 User exit interface changes

163

The following changes have been made for the user exit interface:

DFSRAS00

This is the new resource access security exit routine that provides authorization of IMS resources to IMS dependent regions. It replaces DFSISIS0 for environments that use RAS instead of AGN security with SMU.

► DFSCCMD0

The input parameter list supports two new values for the type of caller in CCMD_RQSTTYPE: CMD FOR TRANSACTION and ICMD FOR TRANSACTION. In both cases, the user ID field will also contain the transaction name, and CCMD_UIDIND will contain CCMD_UIDT ('T').

DFSISIS0

In prior releases, this exit was called the resource access security exit routine. In IMS Version 9 the exit has been renamed to application group name (AGN) security exit routine to avoid confusions with DFSRAS00. Its function will be the same.

DFSMSCE0


At the end of the main exit parameters section, the following fields have been added: user ID, group name and a user ID indicator. Additionally, in an existing field of the link receive routing parameters, MSLRFL3 (Link Receive Exit Flag 3), the exit can specify the level of authorization as being: security based on MSNAME, security based on CTL address space, security based on user ID, security based on Exit, or no link receive security. On entry to the DFSMSCE0 user exit for link receive, the MSLRFL3 field contains the system default value from the MSCSEC= startup parameter.

6.8.4 SMU to RACF migration check list

The following is a high-level migration checklist of tasks we discussed in this chapter:

Translate AGN definitions to RACF

- Add the new classes to RACF
- Define new RAS parameters (SECURITY macro and ISIS= execution parameter)
- Create DFSRAS00 to replace DFSISIS0
- Review JCL for AGN= specifications
- For static terminals required to sign on
 - Specify SIGNON=ALLISPECIFIC parameter in DFSDCxxx
 - Optionally, specify OPTIONS=SIGNON on applicable TYPE/TERMINAL macros
- Enable SAF support for TCO command authorization
 - TCORACF=Y and RCF=AISIRIB
- Review AOI requirements
 - Specify AOI parameter on TRANSACT macro where needed
 - For TYPE 1 CMD security, additionally specify AOI1 = AINICIRIS
- Migrate /LOCK and /UNLOCK security
 - Specify LOCKSEC=Y in DFSDCxxx
- Review MSC requirements for link receive security
 - Specify use of SAF/DFSCTRN0 and level of authorization checking in the new MSCSEC parameter in DFSDCxxx
 - Modify DFSMSCE0 if needed
 - Synchronize RACF profiles on sending and destination systems
- Determine the need to change or write exit routines



7

Type-2 commands and enhanced command environment

In this chapter we introduce the IMS Version 9 enhancement for the use of type-2 commands and the enhanced command environment.

IMS Version 9 publications use new terminology to distinguish the types of IMS commands. Classic commands are called type-1 commands. IMSplex or enhanced commands are now called type-2 commands. Type-1 commands are generally preceded by a leading slash character, and they may be entered from any valid IMS command source. Type-2 commands may be entered only through the Operations Manager (OM) API. IMS Version 9 further enhances the type-2 commands to include database resources and introduces new commands for integrated HALDB online reorganization.

7.1 Type-2 command enhancements in IMS Version 9

IMS Version 9 improves the use of type-2 commands in two ways. First, the enhanced command environment does not require a Resource Manager (RM). This allows some installations to simplify their environments and procedures. Second, type-2 commands may be used for database resources. This allows users to consolidate operations through the use of type-2 commands. In other words the environment is simplified, procedures are easier and operations are consolidated.

All type-2 commands have a common syntax. The command begins with an action verb and resource type. Parameters are enclosed in parentheses following a keyword. This avoids any potential conflicts between keywords and resource names. There are five action verbs for these commands. IMSplex action verbs available with IMS Version 9 are the following:

- QUERY or QRY verb
- UPDATE or UPD verb
- INITIATE or INIT verb
- ► TERMINATE or TERM verb
- DELETE or DEL verb

Each verb may be followed by a resource type. Resource types OLREORG, DB, AREA, and DATAGRP are introduced in IMS Version 9. OLREORG indicates HALDB online reorganization. DB is used for databases. AREA is used for Fast Path DEDB areas. DATAGRP is used for database groups.

Type-2 commands are issued by using the Operations Manager (OM) API. This requires the implementation of the Common Service Layer (CSL). There must be at least one OM address space in the IMSplex and an SCI address space on each LPAR in the IMSplex. IMS Version 9 does not require an RM address space for support of type-2 commands.

IMS includes a TSO implementation of the API. This is the TSO single point of control (TSO SPOC). IMS also provides a sample REXX program which uses the API. The IMS Control Center is a tool which provides a GUI implementation of the API. The IMS Control Center is executed on a Windows® or UNIX® workstation.

The type-2 commands require the use of the OM API. They cannot be entered from IMS terminals or the system console. The IMS control region AOI user exits are not invoked for type-2 commands or their responses.

Figure 7-1 on page 117 illustrates a full CSL environment. Each system in the IMSplex contains an OM, SCI, and RM address space. There is SCI function in these address spaces, the IMS control regions, and Common Queue Server (CQS) address spaces, and any instances of DBRC. CQS is used to manage the resource structure in the Coupling Facility (CF).




Figure 7-1 Full CSL configuration

Figure 7-14 on page 130 illustrates the minimal IMS Version 9 CSL environment required for type-2 commands. There is one OM address space and one Structured Call Interface (SCI) address space. If there were multiple systems (LPARs) in the IMSplex, each system would require an SCI address space, but only one OM address space would be required in the IMSplex.

Command clients

Type-2 commands are entered through command clients. They use the OM API for entering commands and receiving responses. Typically, they format the responses for presentation to users, although this is not required. For example, an automation package might issue commands, examine the responses, and take other actions based on the responses.

As mentioned previously, the TSO SPOC is distributed with IMS for ISPF users. The SPOC receives responses in XML format and formats them for presentation to the user. The IMS Control Center may be downloaded from the Web. It's a GUI command client for workstations and available with the IBM DB2 Universal Database[™] (DB2 UDB) Administration Client, Version 8.2. Follow the links from the IMS home page for download details:

http://www.ibm.com/ims

TSO SPOC

The TSO SPOC is an ISPF application. Users may set preferences and defaults, such as the IMS systems to which the commands will be sent. Users may also create groups and shortcuts for use in commands. For example, a set of IMS systems might be collected into a group so that only the group name is required to reference all of these IMS systems. Similarly, a set of characters, such as &DAR might be used as a shortcut for "DISPLAY ACTIVE REGIONS".

The TSO SPOC may be used to enter both type-1 and type-2 commands. Type-1 commands are those classic commands which used a "/", such as /DISPLAY. Responses from both types of commands are displayed to the user. The user may search and sort this output when it is a response for a type-2 command.

The TSO SPOC saves previous commands and their responses. The user may recall these commands, edit them, and enter the modified commands. The TSO SPOC formats the returned XML responses from OM so it's readable by the user.

TSO SPOC command response

This Figure 7-2 shows a sample response screen. At the top there is an area for the entering of commands. The response to a previous command is shown below it.

<u>F</u> ile	<u>D</u> isplay	View	<u>O</u> ptic	ons <u>H</u> elp
PLEXG				S Single Point of Control
Comman	3 ===> <u>URY</u>	<u>IRAN I</u>	VAMELE	PART*) SHOW(QCNT, STATUS, CLASS)
·				Plex . <u>PLEXG</u> Route Wait
Respons	se for: QRY	TRAN	NAME ((IVT*) SHOW(QCNT,STATUS,CLASS)
Trancode	e MbrName	- CC 1	Cls	LQCnt LclStat
IVTCB	IMSG	0	1	0 CONV
IVTCC	IMSG	Θ	1	0 CONV
IVTCJ	IMSG	Θ	1	0 CONV
IVTCM	IMSG	Θ	1	0 CONV
IVTCP	IMSG	0	1	0 CONV
IVTCV	IMSG	Θ	1	0 CONV
IVTCX	IMSG	Θ	1	0 CONV
IVTFD	IMSG	0	1	0 FPE, RESP
IVTFM	IMSG	Θ	1	0 FPE, RESP
IVTNO	IMSG	Θ	1	0
IVTNV	IMSG	Θ	1	Θ

Figure 7-2 TSO SPOC command response

IMS Control Center

The IMS Control Center may be used to enter type-1 and type-2 commands through a GUI application on a workstation. The IMS Control Center is part of the IBM DB2 UDB Version 8 Control Center, available with the IBM DB2 Universal Database (DB2 UDB) Administration Client, Version 8.2. If you have a workstation which does not have DB2 UDB, you may download the DB2 UDB Administration Client from the Web. There is no charge for this function. Follow the IMS Control Center links from IMS home page:

http://www.ibm.com/ims

The IMS Control Center uses TCP/IP to communicate with the z/OS system. IMS Connect or the integrated IMS Connect function of IMS Version 9 on the z/OS system is required for this TCP/IP connectivity. IMS Connect uses SCI to connect to the IMS OM address space.

IMS Control Center allows you to enter type-2 commands. These include commands introduced in IMS Version 8, such as those that query IMSplex members, and those introduced in IMS Version 9. Of course, the IMS Control Center also allows you to enter the classic IMS commands (type-1 commands).

Figure 7-3 on page 119 show you a sample IMS Control Center screen, you may sort the rows by any column. In Appendix D, "IMS Control Center" on page 299 we show you how to connect the command center to your IMS Connect.

mmands Detailed F esults history					
UERY DB NAME(*)					
UERT DE NAME(")					
ISplex Cor	nmand master	Route			
LEXB IM1	IB	All_Member	'S		
1 1					
Results Errors T	ïme				
DBName ≙	AreaName 👙	: PartName ⇔	MbrName 🔶	CC	
			IM1B		
00100		CUSTD1	IM1B	0 PART	
		CUSTD2	IM1B	0 PART	
		CUSTD3	IM1B	0 PART	
CUSTSI			IM1B	0 PSINDEX	
CUSTSI		CUSTS1	IM1B	0 PART	
DBFSAMD1			IM1B	0	
DBFSAMD2			IM1B	0	
DBFSAMD2 DBFSAMD3			IM1B IM1B	0 0 DEDB	
	CUSDB				
DBFSAMD3 DBFSAMD3	CUSDB		IM1B	0 DEDB	
DBFSAMD3	CUSDB		IM1B IM1B	0 DEDB 0 AREA 0 DL/I 0 DEDB	
DBFSAMD3 DBFSAMD3 DBFSAMD4	CUSDB AREADI01		IM1B IM1B IM1B	0 DEDB 0 AREA 0 DL/	
DBFSAMD3 DBFSAMD3 DBFSAMD4 DISTDB			M1B M1B M1B M1B M1B M1B M1B	0 DEDB 0 AREA 0 DL/I 0 DEDB	
DBFSAMD3 DBFSAMD3 DBFSAMD4 DISTDB DISTDB			M1B M1B M1B M1B M1B M1B	0 DEDB 0 AREA 0 DL/ 0 DEDB 0 AREA 0 DL/ 0 DL/ 0 DEDB	
DBFSAMD3 DBFSAMD3 DBFSAMD4 DISTDB DISTDB DI21PART			M1B M1B M1B M1B M1B M1B M1B	0 DEDB 0 AREA 0 DL/ 0 DEDB 0 AREA 0 DL/	

Figure 7-3 IMS Control Center sample response screen

7.2 Type-2 database commands

IMS Version 9 adds database resources to the type-2 commands. In IMS Version 8, you could only enter classic database commands (type-1 commands), such as /DBR DB through the OM API: there was no type-2 equivalent command. IMS Version 9 allows you to enter DB commands using the type-2 format. The new type-2 database commands are the following:

- QUERY or QRY verb with resource types DB and AREA
- ▶ UPDATE or UPD verb with resource types DB, AREA, and DATAGRP

7.2.1 QUERY DB command

Figure 7-4 on page 120 shows the format of the QUERY DB command.




Figure 7-4 The format of QUERY DB command

The QUERY DB or QRY DB command specifies either a database or a generic database name. Generic names use * as a wildcard. NAME(*) is equivalent to the use of ALL in a type-1 IMS command. NAME(*) is also the default.

If the database specified is a HALDB master, the master database and all its partitions are returned. If the database specified is a HALDB partition, the partition database and the master database are returned. If the database is a DEDB, the database and all of its areas are returned.

The values that may be used with the STATUS keyword are:

ALLOCF, ALLOCS, BACKOUT, EEQE, LOCK, NOTINIT, NOTOPEN, OFR, OLR, OPEN, RECALL, RECOV, RNL, STOSCHD, and STOUPDS.

Most of these are the attributes which may be displayed with a /DIS DB command. Others are unique to QRY DB. OLR indicates that an online reorganization is active. STOSCHD indicates that the database is stopped for scheduling. This could be the result of a /STOP DB command or an UPD DB STOP(SCHD) command. STOUPDS indicates that the database is stopped for updates. This could be the result of a /DBD DB command or an UPD DB STOP(UPDATES) command. RNL indicates that the randomizer is not loaded for the DEDB.

SHOW determines what is returned by the command processing. Database name, IMS member name, database type, DEDB area names, HALDB partition names, and completion code are always returned.

QRY DB and equivalent type-1 commands

In Table 7-1 on page 121 we show a few examples of QRY DB commands and the equivalent type-1 commands.

Since NAME(*) is the default for QRY DB commands, the QRY DB STATUS(ALLOCF NOTINIT) is equivalent to a QRY DB NAME(*) STATUS(ALLOCF NOTINIT) command. It returns only those databases which either have had an allocation failure or have failed database directory (DDIR) initialization.

There is no equivalent of the QRY DB NAME(AB*) command. Wildcard commands cannot be used with /DIS DB commands.

The QRY DB NAME(AB34) SHOW(STATUS) command returns a subset of the data returned by a /DIS DB AB34 command because the SHOW keyword is used to limit the data to only the status and the information which is always returned. Database name, IMS member name, database type, HALDB partition names, and completion code are always returned.

QRY DB Command	Equivalent Type-1 Command				
QRY DB NAME(*)	/DIS DB ALL				
QRY DB NAME(AB34 AB56)	/DIS DB AB34 AB56				
QRY DB STATUS(ALLOCF NOTINIT)	/DIS DB ALLOCF NOTINIT				
QRY DB NAME(AB*)	No equivalent; returns only databases beginning with 'AB'				
QRY DB NAME(AB34) SHOW(STATUS)	Subset of data from /DIS DB AB34				

Table 7-1 QRY DB examples

QRY DB output examples

These are two examples of the responses seen when using the TSO SPOC with QRY DB commands. 'PartName' and 'AreaName' columns do not appear if there is no data for the column.

In Figure 7-5, the 'PartName' column appears because database CUSTDB and ORDRDB are HALDBs. The response includes partition names for these databases.

<u>F</u> ile	<u>D</u> isplay	<u>V</u> iew <u>O</u> pti	ons	<u>H</u> elp	J			
PLEX1 IMS Single Point of Control								
Command ===>								
				— РТ	lex . <u>PLE</u>	<u>XB</u> Route . <u>IM1B</u> Wait		
Respons	e for: QR	Y DB STATUS	(ALI	LOCS)	SHOW(ALL	.)		
DBName	PartName	MbrName	CC	TYPE	LACC	: LclStat		
CUSTDB	CUSTD1	IM1B	Θ	PART	UPD	ALLOCS, OPEN		
CUSTDB	CUSTD2	IM1B	0	PART	UPD	ALLOCS, OPEN		
CUSTDB	CUSTD3	IM1B	Θ	PART	UPD	ALLOCS, OPEN		
NOIX		IM1B	Θ	DL/I	UPD	ALLOCS, OPEN		
NORDDB		IM1B	Θ	DL/I	UPD	ALLOCS, OPEN		
ORDRDB	ORDRD1	IM1B	0	PART	UPD	ALLOCS, OPEN		
ORDRDB	ORDRD2	IM1B	0	PART	UPD	ALLOCS, OPEN		
ORDRDB	ORDRD3	IM1B	Θ	PART	UPD	ALLOCS, OPEN		
ORDRDB	ORDRD4	IM1B	0	PART	UPD	ALLOCS, OPEN		

Figure 7-5 QRY DB STATUS(ALLOCS) SHOW(ALL) issued from TSO SPOC

In Figure 7-6 on page 122, the 'AreaName' column appears because there are some DEDBs displayed. The response includes area names for these databases.

<u>F</u> ile	Display	<u>V</u> iew <u>O</u> p [.]	tions <u>H</u>	<u>l</u> elp				
PLEX1 IMS Single Point of Control								
Command	===>							
				- Plex	. <u>PLEXB</u>	Route	. IM1B	Wait .
Response	e for: QR\	/ DB NAME	(*) SHOU					More: +
DBName	AreaName	PartName	MbrName	e CC	TYPE	LACC	LclStat	
CUSTDB			IM1B	Θ	PHDAM	UPD		
CUSTDB		CUSTD1	IM1B	Θ	PART	UPD	ALLOCS, OPEN	
CUSTDB		CUSTD2	IM1B	Θ	PART	UPD	ALLOCS, OPEN	
CUSTDB		CUSTD3	IM1B	Θ	PART	UPD	ALLOCS, OPEN	
CUSTSI			IM1B	Θ	PSINDEX	UPD		
CUSTSI		CUSTS1	IM1B	Θ	PART	UPD	NOTOPEN	
DBFSAMD1			IM1B	Θ			NOTINIT, STOS	
DBFSAMD2			IM1B	Θ			NOTINIT, STOS	CHD
DBFSAMD3			IM1B	Θ	DEDB	UPD	NOTOPEN	
DBFSAMD3	CUSDB		IM1B	-	AREA		NOTOPEN	
DBFSAMD4			IM1B	-	DL/I	UPD	NOTOPEN	
DISTDB			IM1B	-	DEDB	UPD	OPEN	
DISTDB	AREADI01		IM1B	-	AREA		OPEN, PRELOAD	, PREOPEN, VSO
DI21PART			IM1B	-	DL/I	UPD	NOTOPEN	
HISTDB			IM1B		DEDB	UPD	NOTOPEN	
HISTDB	AREAHI01		IM1B	-	AREA		NOTOPEN	
ITEMDB			IM1B	-	DEDB	UPD	OPEN	
ITEMDB	AREAIT01		IM1B	Θ	AREA		OPEN, PRELOAD	, PREOPEN, VSO

Figure 7-6 QRY DB NAME(*) SHOW ALL issued from TSO SPOC

7.2.2 QUERY AREA command

The QUERY AREA command is similar to the QUERY DB command. Figure 7-7 shows the format of the QUERY AREA command.




Figure 7-7 The format of QUERY AREA command

The values that may be used with STATUS are:

EEQE, IC, MAS, NOTOPEN, OFR, OPEN, PRELOAD, PREOPEN, RECALL, RECOVERY, RECOVNEEDED, SAS, SHARED, STOPPED, UTIL, and VSO.

SHOW determines what is returned by the command processing. Area name, DEDB name, IMS member name, and completion code are always returned. ADS information is returned if available. CI, STATUS, and UTILITY may be used to limit the other information returned. If SHOW is not specified, only a list of resource names is returned.

QRY AREA and equivalent type-1 commands

In Table 7-2 these are examples of QRY AREA commands and the equivalent type-1 commands. There is no equivalent of the QRY AREA NAME(BX*) STATUS(RECALL) command. Wildcard commands cannot be used with /DIS AREA commands.

QRY AREA Command	Equivalent Type-1 Command
QRY AREA NAME(*) SHOW(ALL)	/DIS AREA ALL
QRY AREA NAME(BXJ21) OPTION(REFRESH)	/DIS AREA BXJ21 IOVF
QRY AREA NAME(*) STATUS(STOPPED)	/DIS AREA STOPPED
QRY AREA NAME(BX*) STATUS(RECALL)	No equivalent; Returns only areas beginning with 'BX' which are being recalled
QRY AREA NAME(BXJ21) SHOW(STATUS)	Subset of data from /DIS AREA BXJ21

Table 7-2 QRY AREA examples

QRY AREA output example

Figure 7-8 shows the response when using the TSO SPOC with QRY AREA command with SHOW(STATUS) for selected databases. The EQCnt column contains different data for areas and area data sets. For areas it is the number of EEQEs. For area data sets it is the number of EQEs remaining out of the ten available. If multiple area data sets are not used, EQEs are not used and the value will always be 10. The LclStat column contains statuses for areas.

With SHOW(CI), the response would have columns for SDEP information. Sdep-T is the total number of CIs defined for sequential dependents. SDep-U is the number of these CIs which are unused. Dir-T is the total number of CIs defined for independent overflow. Dir-U is the number of these CIs which are unused.

<u>F</u> ile <u>D</u> isplay <u>V</u> iew <u>O</u> ptions <u>H</u> elp							
PLEX1	IMS S	ingle Poin	it of C	ontrol			
Command ===>							
				Route . <u>IM1B</u> Wait			
Response for: QUE	RY AREA NAME(I	AREAD*, ARE	AI*,AR	EAW*)SHOW(STATUS)More: >			
AreaName ADSName	MbrName DBNa	me CC	EQCnt	LclStat>			
AREADI01	IM1B DIST	DB 0		VSO, PREOPEN, PRELOAD, OPEN, SAS, SHAR			
AREADI01 DISTDD01	IM1B	Θ	10				
AREAIT01	IM1B ITEM	DB 0		VSO, PREOPEN, PRELOAD, OPEN, SAS, SHAR			
AREAIT01 ITEMDD01	IM1B	Θ	10				
AREAWH01	IM1B WARE	DB 0		VSO, PREOPEN, PRELOAD, OPEN, SAS, SHAR			
AREAWH01 WAREDD01	IM1B	Θ	10				

Figure 7-8 QRY AREA output example

7.2.3 UPDATE DB command

Figure 7-9 on page 124 shows the format and keywords for UPDATE DB command.




Figure 7-9 The format and keywords for UPDATE DB command

The use of the NAME keyword with the UPDATE DB or UPD DB command is similar to its use with other type-2 DB commands, but there is a difference in the responses when NAME(*) is specified. There is no response for databases which are updated successfully unless OPTION(ALLRSP) is specified.

The UPD DB command with START(ACCESS) is equivalent to a /START DB command. The SET(ACCTYPE(...)) specification is equivalent to the ACCESS= specification on the /START DB command. The OPTION(...) specifications are equivalent to the same keywords which are used with the /START DB command.

The UPD DB command with STOP(ACCESS) is equivalent to the /DBR DB NOFEOV command. It stops scheduling and deallocates the database(s). NOFEOV is the default for the OPTION keyword. If OPTION is not specified with STOP(ACCESS) the log will not be automatically switched to the next OLDS.

The UPD DB command with STOP(SCHD) is equivalent to the /STOP DB command. It stops scheduling for the database(s).

The UPD DB command with STOP(UPDATES) is equivalent to the /DBD DB NOFEOV command. It prevents updates to the database(s). NOFEOV is the default for the OPTION keyword. If OPTION is not specified with STOP(UPDATES) the log will not be automatically switched to the next OLDS.

NAME(*) cannot be specified with either SET(LOCK(ON)) or SET(LOCK(OFF)). Note that the UPD DB NAME(dbname) SET(LOCK) and UPD DB NAME(dbname) SET(UNLOCK) commands do not have SMU support for passwords. This differs from the /LOCK and /UNLOCK type-1 commands.

There is also a SCOPE keyword which may be used with UPD DB commands. Valid parameters with SCOPE are ACTIVE or ALL, however, they produce the same results in this release. They both apply changes to all active systems.

UPDATE DB and equivalent type-1 commands

Table 7-3 shows some examples of UPD commands and their equivalent type-1 commands.

UPD DB Command	Equivalent Type-1 Command
UPD DB NAME(AB34) START(ACCESS)	/START DB AB34
UPD DB NAME(AB34) STOP(SCHD)	/STOP DB AB34
JPD DB NAME(AB34) STOP(ACCESS) /DBR DB AB34 NOFEOV	
UPD DB NAME(AB34) STOP(UPDATES)	/DBD DB AB34 NOFEOV
UPD DB NAME(AB34) START(ACCESS) SET(ACCTYP(READ)) OPTION(OPEN)	/START DB AB34 ACCESS=RD OPEN
UPD DB NAME(AB*) START(ACCESS)	No equivalent; starts all databases beginning with AB

Table 7-3 UPD DB examples

UPDATE DB output example

An example of the response is shown in Figure 7-10 where the TSO SPOC is used to issue an UPD DB NAME(*) START(ACCESS) command. OPTION(ALLRSP) is used here to produce response lines for each database started. Otherwise only the databases that resulted in errors would have been listed. The completion code of 10 indicates that the data base does not exists, resource not found. You can find the condition codes in the *IMS Version 9: Command Reference*, SC18-7814.

<u>F</u> ile	<u>D</u> isplay	View	<u>O</u> ptions	<u>Н</u> е l p
PLEX1 Command	===>		IMS Si	ngle Point of Control
				— Plex . <u>PLEXB</u> Route . <u>IM1B</u> Wait
Response			B NAME(*)	START(ACCESS) OPTION(ALLRSP)
DBName	MbrName	CC		
CUSTDB	IM1B	0		
CUSTSI	IM1B	Θ		
DBFSAMD3		0		
DBFSAMD4		Θ		
DISTDB	IM1B	Θ		
DI21PART		0		
HISTDB	IM1B	Θ		
ITEMDB	IM1B	Θ		
IVPDB1	IM1B	Θ		
IVPDB2	IM1B	Θ		
IVPDB3	IM1B	Θ		
NOIX	IM1B	Θ		
NORDDB	IM1B	Θ		
ORDLDB	IM1B	Θ		
ORDRDB	IM1B	0		
ORDRSI	IM1B	Θ		
STCKDB	IM1B	Θ		
WAREDB	IM1B	Θ		

Figure 7-10 UPD DB START(ACCESS) sample

7.2.4 UPDATE AREA command

Figure 7-11 shows the format of the UPDATE AREA command.

UPD AREA NAME(areaname,areaname*|*) * NAME(*) returns responses for areas that resulted in errors * OPTION(ALLRSP) overrides this and returns responses for all areas START(ACCESS) * equivalent to /START AREA STOP(ACCESS) OPTION(FEOV|NOFEOV) * equivalent to /DBR AREA, NOFEOV is the default STOP(SCHD) * equivalent to /STOP AREA

Figure 7-11 The format of UPDATE AREA command

The UPD AREA command is similar to the UPD DB command. It is used for DEDB areas, not databases. The keywords for the UPD AREA command have the same meaning as they have for UPD DB commands as seen in Table 7-4.

NOFEOV is the default for the OPTION keyword with STOP(ACCESS). If OPTION is not specified, the log will not be automatically switched to the next OLDS.

There is also a SCOPE keyword which may be used with UPD AREA commands. Valid parameters with SCOPE are ACTIVE or ALL, however, they produce the same results in this release. They both apply changes to all active systems.

UPD AREA Command	Equivalent Type-1 Command
UPD AREA NAME(BXJ21) START(ACCESS)	/START AREA BXJ21
UPD AREA NAME(BXJ21) STOP(SCHD)	/STOP AREA BXJ21
UPD AREA NAME(BXJ21) STOP(ACCESS)	/DBR AREA BXJ21 NOFEOV
UPD AREA NAME(BX*) STOP(ACCESS)	No equivalent; Stops access for all areas beginning with 'BX'

Table 7-4 UPD AREA command examples

7.2.5 UPDATE DATAGRP command

Figure 7-12 on page 127 shows the format and the keywords of the UPDATE DATAGRP command.




Figure 7-12 The format of UPDATE DATAGRP command

The UPD DATAGRP command is similar to the /START, /STOP, and /DBR commands with the DATAGRP keyword. There is no QRY DATAGRP command, just as there is no /DIS DATAGRP command.

Only one data group may be specified on a command. The asterisk cannot be used for the NAME parameter with the UPD DATAGRP command. Table 7-5 shows examples and their equivalent type-1 commands.

The NAME(datagroup) returns responses for databases and areas that result in errors. The OPTION(ALLRSP) overrides this and returns responses for all databases and areas.

For the START(ACCESS) there are the following additional keywords: SET(ACCTYPE(BRWS | READ | EXCL | UPD) OPTION(DBALLOC | NODBALLOC).

There is also a SCOPE keyword which may be used with UPD DATAGRP commands. Valid parameters with SCOPE are ACTIVE or ALL, however, they produce the same results. They both apply changes to all active systems.

UPD DATAGRP Command	Equivalent Type-1 Command
UPD DATAGRP NAME(GP35) START(ACCESS)	/START DATAGRP GP35
UPD DATAGRP NAME(GP35) STOP(SCHD)	/STOP DATAGRP GP35
UPD DATAGRP NAME(GP35) STOP(ACCESS)	/DBR DATAGRP GP35 NOFEOV

Table 7-5 UPD DATAGRP command examples

7.2.6 Command security

Security is available in OM for commands entered through it. There are two types of security available in OM, SAF (RACF) and the OM security exit. Either or both may be used. *IMS Version 9: Command Reference,* SC18-7814, lists resource names and RACF authority for IMS Commands. The "IMS Command, RACF Access Authorities and Resource Names Table" in the appendix of the command reference manual has been expanded to include the new DB commands. Table 7-6 on page 128 shows an example of an entry in that table.

Table 7-6 Resource names and RACF authority

Command	Keyword	Authority	Resource Name
UPD	DB	UPDATE	IMS.plxname.UPD.DB

The corresponding RACF definition for this could be as the one shown in Example 7-1.

Example 7-1 RACF definitions

REDEFINE OPERCMDS IMS.*.UPD.DB UACC(NONE) PERMIT IMS.*.UPD.DB CLASS(OPERCMDS) ID(KNUT) ACCESS(UPDATE)

The OM security user exit routine is documented in *IMS Version 9: Common Service Layer Guide and Reference*, SC18-7816.

7.2.7 Log records

The type x'02' log record is written for type-1 (classic) IMS commands. Type-2 commands are logged in type x'22' instead of type x'02' log records. Type x'22' log records will be written when, for example, START(ACCESS) or STOP(SCHD) is specified on the following commands:

- UPD DB
- UPD AREA
- UPD DATAGRP

Log record x'22' can be mapped with the DFSLOG22 macro.

7.2.8 Summary of the command enhancements

IMS Version 9 command enhancement extends type-2 commands by using the SPOC to query and update IMS database resource status. The benefit of this enhancement is the consistency with type-2 commands for other resources. Responses from multiple IMS systems are consolidated, and further enhanced to allow wildcards with NAME parameters. Responses are encapsulated in XML tags, so command clients may manipulate output for presentation as well as for automation. With the TSO SPOC and IMS Control Center support, output is easily sorted and manipulated by users.

7.3 Enhanced command environment

The enhanced command environment of IMS Version 9 allows installations to enter type-2 commands without including a Resource Manager (RM) address space in their environment. This simplifies the execution environment by eliminating these address spaces. In this environment users are able to automatically start the SCI and OM address spaces when the control region is started. This enhancement is ideal for DBCTL users and non-sysplex environments, which do not need the features of, for example, sysplex terminal management and global online change, which require Resource Manager.

7.3.1 IMS Version 8 Common Service Layer components

In IMS Version 8 the Common Service Layer (CSL) includes an SCI address space on each LPAR in the IMSplex. At least one OM address space is required in the IMSplex. Additional OM address spaces may be used to provide increased availability. At least one RM address space is required in the IMSplex. If a resource structure is included, multiple RM address

spaces may be used to provide increased availability. If there is no resource structure, only one RM address space may be used. A Coupling Facility resource structure is required if the sysplex terminal management (STM) function is used. The resource structure is optional if RM is used only for global online change.

7.3.2 IMS Version 9 Common Service Layer components

IMS Version 9 removes the RM address space requirement for the Common Service Layer, unless the functionality of sysplex terminal management or global online change is required. Type-2 commands do not require an RM address space. They do require an SCI address space in each LPAR and at least one OM address space.

Online change using the INIT command does not require an RM address space, but the RM address space is recommended. Without the RM address space, the change is not "global". It is made in only one IMS system.

Figure 7-13 is an illustration of an enhanced command environment CSL configuration. There is no RM address space or resource structure. Two of the LPARs have an OM address space. Only one is required, but the second provides increased availability.




Figure 7-13 Enhanced command environment CSL configuration

Figure 7-14 on page 130 shows the minimum CSL configuration which may be used for entering type-2 commands. There is one LPAR with one OM address space and one SCI address space.




Figure 7-14 Minimum CSL configuration

7.3.3 CSL functions and requirements summary

This summarizes the minimum configurations required for the use of various functions provided by the Common Service Layer. Automatic RECON loss notification requires only SCI. An SCI address space is required on each LPAR in the IMSplex.

- SCI only required
 - Automatic RECON loss notification (ARLN)
- SCI + OM required
 - Type-2 commands
 - Online change using the INIT command
 - Dynamic LE runtime options
 - HALDB online reorganization commands
 - Other commands
- SCI + OM + RM without resource structure required
 - Global online change without resource consistency checking
- SCI + OM + RM with resource structure required
 - Sysplex terminal management
 - Global online change with resource consistency checking

7.3.4 CSL start up options and implementation

IMS Version 8 required that an installation start each CSL address space. Either an operator or automation had to start each address space. IMS Version 9 has a new option which causes the IMS control region to start the OM and SCI address spaces. This is intended for installations that are using the CSL only for type-2 commands in an enhanced command environment and, possibly, automatic RECON loss notification.

The automated start of OM and SCI address spaces is controlled by the parameters in DFSCGxxx member in IMS.PROCLIB. The parameters are the following:

► RMENV=

RMENV=Y is the default and indicates that an RM address space will be used. It is not automatically started by the IMS control region. RMENV=Y does not allow the control region to automatically start the SCI or OM address spaces.

SCIPROC=

This parameter is used to specify the procedure name for the SCI address space. When it is specified, the control region will start the SCI address space if one is not already available on the LPAR, and RMENV=N is also specified.

OMPROC=

This parameter is used to specify the procedure name for the OM address space. When it is specified, the control region will start the OM address space if one is not already available in the IMSplex, and RMENV=N is also specified

Example 7-2 shows a sample DFSCGxxx PROCLIB member that makes it possible to use automatic start of OM and SCI address spaces when IMS control region is started.

Example 7-2	A sample contents of DFSCGxxx member	
-------------	--------------------------------------	--

* IMS COMMON SERVICE		*
CMDSEC=N, IMSPLEX=PLEXG, RMENV=N OMPROC=IVP910M, SCIPROC=IVP91SCI *	/* NO CMD AUTHORIZATION CHECKING /* IMSPLEX NAME	*/ */
* NORSCCC=(ACBLIB,FO * OLCSTAT=IMSTESTG.G		*
* END OF MEMBER DFSCG *		
*****	**************************************	*****

7.3.5 Online change alternatives

There are three ways of implementing online change.

 OLC=LOCAL specification causes IMS to use the online change functions available in IMS releases before IMS Version 8.

Online change is invoked with /MODIFY commands and keeps statuses in the MODSTAT data set. An online change affects only one IMS. Each IMS system must have its own MODSTAT data set.

 OLC=GLOBAL specification with RMENV=N causes IMS to use the online change functions introduced in IMS Version 8.

Online change is invoked with INIT OLC commands using OM. Since there is no RM, the online change affects only one IMS system. Each IMS system must have its own OLCSTAT data set.

 OLC=GLOBAL specification with RMENV=Y causes IMS to use the online change functions introduced in IMS Version 8.

Online change is invoked with INIT OLC commands using OM. Since there is an RM, the online change affects all of the IMS systems in the IMSplex. The IMS systems share an OLCSTAT data set.

7.3.6 Global online change

The use of global online change is optional. This is true for both IMS Version 8 and Version 9. IMS Version 9 adds the capability to run an IMSplex without an RM address space. This may affect the capabilities of global online change.

The use of global online change requires that OLC=GLOBAL be specified in the DFSCGxxx PROCLIB member. If there is no RM address space, OLC=GLOBAL does not invoke a global online change. Instead, the OLC commands must be issued separately for each IMS system. Since online changes for different IMS systems are processed separately, each IMS system must have its own OLCSTAT data set.

The IMS system using an OLCSTAT data set, writes its name in the data set. If a restart of IMS reads the OLCSTAT data set and finds another IMS name in the data set, restart fails. The name in the data set may be changed by using the OLC utility (DFSUOLC0).

Resource consistency checking cannot be done without RM. Resource consistency checking is the function which checks to ensure that each IMS system is using the same ACBLIB, MODBLKS, MATRIX, and FORMAT data sets.

Note: Without an RM, there is no check for the use of the same data sets ACBLIB, MODBLKS, MATRIX, and FORMAT.

7.3.7 OM security user exit

Users may implement an OM security user exit. It is used to perform security checking during OM command processing. It is optional.

The exit is invoked when the CMDSEC= parameter on the OM procedure is specified as A or E. A indicates that both the OM security user exit and RACF are used for OM command security. E indicates that only the OM security user exit (and not RACF) is called for OM command security. The exit is defined as TYPE=SECURITY in the EXITDEF statement in the BPE user exit list PROCLIB member.

The input parameter list for the OM security exit has two new parameters:

- OSCX_ROUTLEN is the length of the route list. This is the list of IMS systems to which the command is routed. This list may be used in security decision.
- OSCX_ROUTPTR is the address of a copy of the route list.

The new parameters are included in the CSLOSCX mapping macro. This change applies to IMS Version 9 whether or not the enhanced command environment is used.

QUERY commands with RMENV=N

The responses to QUERY calls are affected by the lack of an RM. These effects are explained here:

QUERY MEMBER response

RMENVNO attribute returned when RMENV=N

QUERY OLC response

Information about other IMS systems is not available

- Command is only processed by the command master
- OLCSTAT is not shared when RMENV=N

May need to route to the appropriate IMS

QUERY TRAN response

Only information local to the IMS processing the query is returned

7.3.8 Migration to OM

Instructions for implementing OM are included in the Operations Manager chapter of the *IMS Version 9: Common Service Layer Guide and Reference,* SC18-7816. The DFSCGxxx member to be used for the IMSplex is specified in the CSLG= in DFSPBxxx or as an execution parameter for the IMS control region. A warm start is sufficient, when the CSLG= parameter value is changed.

The IMSplex parameters in the DFSCGxxx member include RMENV=, CMDSEC=, IMSPLEX=, NORSCCC=, OLC=, OLCSTAT=, and LEOPT=. NORSCCC= is not applicable when RMENV=N is specified. The IMSPLEX specification must match the IMSPLEX specification for the SCI and OM address spaces.

Procedures for the OM and SCI address spaces must be created. Their initialization parameters are specified in the CSLSIxxx and CSLOIxxx PROCLIB members. As mentioned before, if SCIPROC and OMPROC are specified in the DFSCGxxx member used for the control region and the SCI and OM address spaces are not already active, the control region will start these address spaces. If the SCIPROC and OMPROC parameters are not specified, the address spaces must be started by the operator.

7.3.9 Migrating from non-IMSplex to IMSplex with RMENV=N

Follow these steps when migrating from a non-IMSplex environment to an enhanced command environment, in other words, an IMSplex environment with RMENV=N.

- 1. Add CSLG=xxx to IMS control region parameters
 - Specifies DFSCGxxx PROCLIB member
- 2. Create DFSCGxxx member with RMENV=N
 - Specify the same IMSplex name as used by SCI and OM
- 3. Create SCI and OM startup procedures
- 4. Create initialization parameter PROCLIB members for SCI and OM
 - CSLSIxxx
 - CSLOIxxx
- 5. Start SCI and OM or specify procedure names in DFSCGxxx
- 6. Shut down IMS

7. Warm start IMS

7.3.10 Migrating from RMENV=N to RMENV=Y

To migrate from the enhanced command environment (no RM address space) to a Common Service Layer including an RM address space, the RMENV parameter for the control region must be changed so that RMENV=N is not specified. Either RMENV=Y may be specified or the RMENV= parameter may be removed.

The IMS control region will not start the SCI and OM address spaces when RMENV=Y is specified. If this was being done with RMENV=N, operations procedures must be modified to start these address spaces. The RM address space is started and then IMS is restarted with a warm start. A cold start of IMS is not required.

Follow these steps for migrating from enhanced command environment to CSL with Resource Manager:

- 1. Update DFSCGxxx member to specify RMENV=Y, or take the default by removing RMENV=N
- 2. Create RM startup procedure
- 3. Create initialization parameter PROCLIB member CSLRIxxx for RM
- If previously using IMS to start SCI and OM, update operations procedures to start SCI and OM
- 5. Start RM
- 6. Shut down IMS
- 7. Warm start IMS

7.3.11 Enhanced command environment summary

To summarize the previous pages, the enhanced command environment is an IMSplex with SCI and OM address spaces but without Resource Manager (RM) address spaces. This environment may be used to enter commands through the OM interface. These commands may be type-1 IMS commands or new type-2 commands including commands to initiate HALDB online reorganization, commands to dynamically modify LE runtime options, and commands to invoke the online change process introduced in IMS Version 8.

The enhanced command environment is simpler than the full IMSplex environment. Since the IMS control region can automatically start the OM and SCI address spaces, the enhanced command environment is simpler to operate.

Integrated IMS Connect support

The functionality of IMS Connect Version 2 Release 2 (program number 5655-K52) — one of IBM DB2 and IMS Tools products — is included as part of IMS Version 9. This functionality is included in the IMS systems services Function Modification Identifier (FMID) HMK9900.

You can use IMS Connect 2.2 to provide communications between one or more TCP/IP clients and one or more IMS Version 7 or IMS Version 8 clients. For communications with an IMS Version 9 client, you can use the integrated IMS Connect functionality with IMS Version 9. IMS Connect 2.2 will continue to be supported for IMS Version 7 and IMS Version 8 clients, but future enhancements to the IMS Connect functionality will be made available only with IMS Version 9 or later.

8.1 IMS Connect overview

Integrated IMS Connect function provides advanced security and transactional integrity in TCP/IP and local/390 access to IMS and the Internet, as IMS Connect itself has been providing. It supports high performance communications between one or more TCP/IP or local/390 clients, and one or more IMS systems. It provides commands to manage that environment and assist with workload balancing. It reduces the design/coding effort for client applications, and it provides easier access to IMS applications and operations.

Integrated IMS Connect function used with the WebSphere Development Tooling and the IMS Connector for Java, can significantly ease the development of on demand business solutions that access IMS transactions. These solutions can be deployed in IBM WebSphere Application Servers, allowing you to use Web applications, J2EE applications, or Web Services to quickly transform static Web sites into sources of dynamic Web content.

Integrated IMS Connect function, used with IBM DB2 Version 8 Universal Database Control Center, allows a single, graphical user interface to control both IMS and DB2, easing IMS operations. For more information about setting up the DB2 and IMS Control Center, refer to Appendix D, "IMS Control Center" on page 299.

IMS Connect runs in an address space on z/OS system, and performs router functions between TCP/IP clients and local option clients with IMS. Request messages received from TCP/IP clients, using TCP/IP connections, or local option clients, using the z/OS Program Call (PC), are passed to IMS through cross-system coupling facility (XCF) sessions. Then IMS Connect receives response messages from IMS and passes them back to the originating TCP/IP or local option clients. Figure 8-1 shows IMS Connect functions for TCP/IP clients.




Figure 8-1 IMS Connect overview

8.1.1 IMS Connect enhancements in IMS Version 9

For IMS Version 9, IMS Connect is an integrated function, which offers a functional replacement for the IMS Connect tool (program number 5655-K52). Basically, the integrated IMS Connect function in IMS Version 9 provides the same functionality and enhancements to IMS as provided by the stand-alone tool, IMS Connect Version 2.2.

For IMS Connect Version 2.2 and IMS Version 9 integrated IMS Connect function, the improvements and enhancements include:

- Commit mode 0 persistent socket support
- Purge not deliverable support
- New and enhanced IMS Connect commands
 - IMS Connect commands can now be issued through the z/OS modify interface. This is a z/OS command. The response to it is presented by z/OS to the issuer of the command, which enhances consistency and ease of use
 - Query member command enhancements add IMS Connect IP address and version
- Cancel timer support
- New RESUME_TPIPE single with wait option
- The MAXSOC= parameter has changed and requires APAR PQ90051
- IMS Connect event recording support
- Improved performance and availability reporting
- IMS Connector for Java adds:
 - Commit Mode 0 persistent socket for improved performance
 - Socket timeout for enhanced usability
 - Retry for improved availability

IMS Connect 2.2 and the integrated IMS Connect function in IMS Version 9 are the last releases which support user message exits, HWSIMSO0 and HWSIMSO1. These two user message exits will not be available in future.

8.2 IMS Connect clients

Using IMS Connect, you can develop applications as a:

- Roll Your Own (RYO) client
- IMS Connector for Java client

A RYO client can be written in any language which supports the TCP/IP interface. You need to know the protocol provided by IMS Connect and OTMA to develop this TCP/IP socket application. The advantage of a RYO client compared to an IMS Connector for Java client is that the RYO client has similar functionality to and flexibility of MQ-IMS Bridge client applications, which support the OTMA protocol and the message routing.

IMS Connector for Java development environment is included in WebSphere Studio Application Developer Integration Edition and the runtime component is provided with IMS. The IMS Connector for Java client may have a little less flexibility than a RYO client, depending on your requirements. But you can build an IMS Connector for Java client without in-depth knowledge of the protocol of IMS Connect and OTMA, and you can use utilities which aid programmer productivity.

Functions regarding the connectivity using IMS Connect introduced here are not a new function of IMS Version 9, but of IMS Connector for Java Version 2.2.2 for WebSphere Studio Application Developer Integration Edition (WSADIE) Version 5.1.1.

For additional information about OTMA and IMS Connect, see the following IBM Redbook: *IMS e-business Connectors: A Guide to IMS Connectivity*, SG24-6514.

8.3 IMS Connector for Java client overview

IMS Connector for Java is based on the J2EE Connector Architecture (J2C) to connect to an IMS system, which is the standard architecture of J2EE. In this architecture, IMS is a so called Enterprise Information System (EIS) as is CICS, thus the IMS resource adapter is provided based on J2C architecture. However, from the IMS point of view, there is no difference between RYO clients and IMS Connector for Java clients. They both issue the transaction code through IMS Connect and OTMA.

IMS Connector for Java provides its own functions which RYO clients do not have. For example, you can use the local option if your J2EE application component is running on WebSphere Application Server for z/OS. With this option, you can submit IMS transaction messages that participate in global transaction processing. This transaction processing is coordinated by Resource Recovery Services (RRS) on z/OS and WebSphere Application Server for z/OS. IMS Connector for Java is RRS-compliant and is designed specifically to work with RRS so that the Java transaction manager in WebSphere Application Server and IMS, as the resource manager, can work together to make consistent changes to multiple protected resources. The XA protocol is not used by IMS Connector for Java when running global transactions with the local option.

Note that different resource adapters are provided depending on platforms, and that some functions of OTMA messaging protocol or flow are not supported depending on IMS version, IMS Connect version and IMS Connector for Java version. It is necessary to check your components and their versions to know which function is available at that time.

With IMS Version 9 and IMS Connector for Java Version 2.2.2, the send only message flow is supported as a new function. See Figure 8-2.




Figure 8-2 Commit-then-send and send-only transaction flow

The message type is specified as a send-only transaction in the IRM header. With IMS Connector for Java, you can specify a send-only flag as an interactionVerb property based on J2C architecture. So you do not need to be aware of which field in the IRM header is used to specify it.

8.3.1 IMS Connector for Java functions

As IMS Connector for Java is based on J2C, its functions are J2C compliant. You specify the information regarding connection, for example IMS Connect connected to or OTMA commit mode, on ConnectionSpec and InteractionSpec which are provided by J2C as standard. These Specs wrap the detail for the interaction protocol between OTMA, IMS Connect and a client application. Thus you do not need to study which fields of the message have what kind of information, thus making IMS Connector for Java easier compared to developing a RYO client.

ConnectionSpec and InteractionSpec contain the following information:

- Connection information to IMS Connect, IMS security information
- ► OTMA commit mode, message flow information
- ► IMS internal timeout value
- Information of conversational transaction

IMS Connector for Java provides the following functions as J2C System Contract, which are available only for IMS Connector for Java clients:

- Socket connection management (for example, connection pooling, timeout)
- Component-managed, Container- managed sign on security, or SSL as security
- Global transaction
- Trace function

For more detail of these functions, refer to manual *IMS Connector for Java 2.2.2 and 9.1.0.1 Online Documentation for WebSphere Studio Application Developer Integration Edition 5.1.1,* SC09-7869, which is available at the following Web site:

http://www.ibm.com/software/data/db2imstools/imstools/imsjavcon.html

8.3.2 IMS Connector for Java clients

Regarding IMS Connector for Java original functions, WebSphere tooling today enables IMS transactions using COBOL, C, and MFS-based applications as Web Services. Using IMS transactions as Web Services leverages customers' past investment in applications development. It can also eliminate or greatly reduce new programming effort, reduce end-to-end business process transformation, and facilitate application integration with partners, suppliers, and customers.

Using IMS Connect and IMS Connector for Java of WSADIE, you can develop the following type of applications with distributed Web access across platforms:

- J2EE Connector Architecture (J2C) Common Client Interface (CCI) applications
- Enterprise Service applications

IMS Connector for Java CCI applications have the advantage that you can utilize the CCI API which covers up the access logic detail required to connect to IMS, and you can develop applications in a simple MVC model. However, you may need to code applications manually including logic to build input and output messages and to convert character sets.

If you choose an Enterprise Service application, GUI-based application development functions provided by WSAD IE are available. You may just follow the steps provided by the GUI tools, in which case Enterprise Service applications corresponding to Web Services are generated automatically. Note the simple MVC-model-based applications are not generated using these GUI tools, and this method requires the skills regarding servlet, JSP and Web Service components like XML, SOAP, WSDL, WSIF and EJB.

8.4 IMS transactions as Enterprise Service applications

Here we introduce the way to see IMS transactions as Enterprise Service applications. From the client application's point of view, IMS transactions appear as an exchange of message which have their own layout as required by IMS or an IMS online application. So client applications are not necessarily aware of the process inside of IMS online applications. They recognize IMS transactions simply as an interaction of messages. The format of messages can be given by:

- I/O area of COBOL or C applications' source
- MFS source

This exchange of messages is known as a service. Once you define an IMS transaction as a service, access to an IMS system from any platform or protocols is allowed with mechanisms on z/OS or OS/390®.

With Enterprise Service, all of the information regarding IMS transaction message exchange, that is, IMS service is defined using Web Service Description Language (WSDL). WSDL is the open standard format to describe a Web Service. IMS Enterprise Service provides the way to invoke this Web Service, with the Web Service Invocation Framework (WSIF). WSIF is the API is used to invoke a Web Service and enables Web Service to be accessed from Java, RMI/IIOP, and SOAP. IMS Enterprise Service uses IMS Connector for Java and IMS Connect, and can therefore utilize the functions provided by J2C.

8.5 IMS Enterprise Service component

You describe all of the information about sending and receiving IMS transactions in WSDL. See Figure 8-3 on page 141.




Figure 8-3 IMS Enterprise Service components

WSDL is the origin standard used to describe Web Service information, but with an Enterprise Service, you can describe information about not only Web Services but also various protocols like J2C, JMS, SOAP, and EJB and so on. When WSDL describes an IMS Service it has input and output message format information, an encoding specification, and J2C binding information corresponding to InteractionSpec and ConnectionSpec.

IMS Enterprise Service uses this information described in WSDL, and performs input and output processing of IMS transactions. WSIF is a Java API package which supports various protocols and transports such as SOAP, original Java, EJB, or COM objects, and executes services based on WSDL. WSIF is enhanced to correspond to J2C so that you can modify InteractionSpec or ConnectionSpec property described in WSDL. Compared to Web Services based on SOAP, IMS Enterprise Service can deal with more protocols because it has the benefits of WSIF.

IMS Enterprise Service is used by classes generated automatically from WSDLs. These classes have WSIF code to invoke Service whose detailed processing is covered up, so that clients can transparently invoke Service simply by passing arguments to the methods in Proxy.

You can deploy IMS Enterprise Service as an EJB, then RMI/IIOP or SOAP can access this Service. In this case, those protocols use Binding WSDL and Proxy by WSIF.

8.5.1 Interface WSDL

In the Interface WSDL, as message elements and type elements, message formats of IMS transactions are expressed by XML schema. This description can automatically be generated

from COBOL and C application source or MFS source. Only fundamental information is described here, so it is common regardless of how it is deployed.

8.5.2 Binding WSDL

In the Binding WSDL, J2C binding information is described to use the IMS resource adapter. It has physical format elements and format elements which describe encoding information for IMS transaction messages. This information is used to convert EBCDIC-Unicode, endian, or used for byte operation. Physical format element and formant elements can automatically be generated from COBOL and C application source or MFS source.

8.5.3 Service WSDL

In the Service WSDL, the location of Service is described. In the case of J2C binding, Service location information corresponds to the J2C ConnectionSpec. You can utilize J2C binding in a managed environment without EJB deployment because the connection factory resource name can be written here directly.

8.6 MFS-based transaction as Enterprise Service application

With valid MFS source, MFS-based IMS enterprise service can be developed using MFS Web Services Importer inside WebSphere Studio Application Developer Integration Edition. The service runs on WebSphere Application Server and uses MFS Web Services Runtime, IMS Connector for Java, and IMS Connect.

8.6.1 MFS Web Services Importer

Available in WebSphere Studio Application Developer Integration Edition, the importer wizard takes users through parsing the MFS source file, selecting the device type, device feature, input MID, input logical page number, and output MODs, and populating the transaction information into the WSDL files. Infopops provide explanations for each control on the wizard pages. Multiple MODs can be chosen for multiple possible output types. System default MODs are provided in the selection by default. After running through the wizard, XML schema representation of the chosen MID and MODs is stored in the Interface WSDL. The information described in the WSDL files is used to generate Java beans and perform input and output processing. A Java bean represents each MID or MOD.

8.6.2 MFS Web Services Adapter

The MFS Web Services Adapter is packaged with IMS Connector for Java. Invoked by WSIF on input, the adapter transforms input bean into host input data stream and returns populated output bean from host output data stream. On output, the adapter transforms host output data stream to populate the output bean, as specified by the mapname in the OTMA header which is the same as the MOD name for the IMS application. See Figure 8-4 on page 143





Figure 8-4 MFS Web Services adapter

For more information, refer to *IMS Connector for Java 2.2.2 and 9.1.0.1 Online Documentation for WebSphere Studio Application Developer Integration Edition 5.1.1,* SC09-7869, which is available at the following Web site:

http://www.ibm.com/software/data/db2imstools/imstools/imsjavcon.html



9

XML storage in IMS databases

In this chapter we introduce the enhanced ability of IMS to provide a storage facility for XML documents. XML stands for Extensible Markup Language, and throughout this chapter we will use XML only. This enhancement is provided as part of the IMS Java function. See Chapter 10, "IMS Java enhancements" on page 159 for other functionality regarding IMS Java.

This chapter includes:

- XML database overview
- Storing XML information in IMS databases
- XML schema definition language
- Decomposed storage
- Intact storage
- DLIModel Utility
- ► JDBC interface

9.1 IMS Version 9 XML database

Extensible Markup Language (XML) is a simple, very flexible text format derived from SGML (ISO 8879). Originally designed to meet the challenges of large-scale electronic publishing, XML plays an increasingly important role in the exchange of a wide variety of data on the Web and elsewhere. In IMS we use XML in similar way to how we use the DBD. It describes the fields and segments of i.e. a WEB format versus a IMS Database.

An increasing amount of information is being transferred inside and between organizations in the form of XML documents. IMS databases are ideally suited to the storage and retrieval of information in XML documents, given that both are structured hierarchically. IMS Version 9 provides support for:

- Storage and retrieval of XML documents in IMS databases
- Composition of XML documents from existing IMS databases
- Creation of IMS segments from XML documents (decomposition)
- Intact storage of XML documents into IMS databases (without decomposition)

IMS also provides tools to assist you to define the metadata for mappings between your IMS database definitions and those required for XML. This is provided through an extension of the DLIModel Utility.

It is now a simple process to exchange data between your existing IMS databases and XML documents. It is straightforward to use existing IMS databases to create XML documents, which can be done without the need to alter any of your existing IMS applications.

IMS Java application programming support has also been extended to the following environments:

- IMS TM
- CICS
- ► DB2
- WebSphere Application Server

All DEDBs and full function databases, including HALDBs support these XML enhancements. Secondary indexes and logical relationships can be used for retrieval of information from IMS databases, although there are some restrictions on the insertion of segments through these facilities.

9.1.1 Storing XML information in IMS databases

There are two ways of storing XML documents in IMS databases:

Decomposed storage

The use of *decomposed storage* is a data-centric approach to storing the information in IMS database. In this case, the XML data is converted to traditional IMS data types, when stored into the database. Since the data is not stored as XML, the information in these IMS databases may be read and updated by existing IMS applications.

Intact storage

The use of *intact storage* is a document-centric approach to storing the information into your IMS database. In this case, the XML data is not converted when stored in an IMS database. The data is stored as XML, and includes all the XML tags as well as the information. This data cannot be manipulated by non-XML applications.

9.2 XML database overview

An XML schema can be created by the IMS DLIModel Utility. This utility reads PSB and DBD source, (XML Metadata Interchange Format) XMI files, and control statements. WebSphere Studio Application Developer Integration Edition (WSADIE) may be used to create these XMI files from COBOL copybooks. The XML schema is used by an IMS Java application to compose an XML document from an IMS database record, or to compose IMS database segments from an XML document.

The XML schema is also used by IMS Java applications to compose and decompose XML documents, as shown in Figure 9-1.

The XML Metadata Interchange Format (XMI) specifies an open, information interchange model that gives developers working with object technology the ability to exchange programming data over the Internet in a standardized way. The XMI standard will allow developers to leverage the Web to exchange object-oriented data among tools, applications, and repositories. The standard will also allow developers to build secure, distributed applications in a team development environment.




Figure 9-1 DLIModel Utility

IMS XML DB uses XML schema

An XML schema defines what data may be present in an XML document. The schema can be used to create an XML document from IMS database data, by describing how to copy data from the segments into an XML document.

The schema may also be used to store a document in a database. The XML data can either be stored in a decomposed or an intact format in the database.

9.2.1 XML schema definition language

An XML schema definition language is a language for defining the legal building blocks of a valid XML document. An XML schema defines the following:

- ► The elements and attributes that can appear in a document
- Which elements are child elements
- The order and number of child elements
- Whether an element is empty or can include text
- Data types for elements and attributes
- Default and fixed values for elements and attributes

The schema also defines an agreed-upon communication contract for exchanging XML documents. The generated XML schema must be made available at runtime in order to provide the XML structure of the data retrieved from the database or conversely of an incoming XML document being stored into IMS.

9.2.2 Decomposed storage

An XML document must be parsed and validated in order to extract the information from the document. The data must then be converted to traditional IMS types:

- EBCDIC characters (picture strings)
- Numeric types (COMP-1, COMP-2, and so on.)

The stored data is immediately usable by traditional IMS applications, without any further transformation. These traditional applications need have no knowledge of XML, since the data is stored in decomposed format in the database. Because the XML document does not have to be regenerated when the data is retrieved from the database, the retrieval of the XML data is typically faster than when it is stored without its XML tagging.

The definition of the mappings of data in an XML document to segments and fields in an IMS database is performed by the XML schema, as shown in Figure 9-2 on page 149.




Figure 9-2 Mapping of XML to IMS DB

The transformation of data between an XML document and the IMS database record is performed by the *retrieveXML* and *storeXML* functions. An example of this is shown in Figure 9-3.




Figure 9-3 The transformation of information from XML to IMS DB

An example of a generated XML schema is shown in Example 9-1 on page 150.

Example 9-1 A generated XML schema

```
<?xml version="1.0" encoding="UTF-8"?>
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"</pre>
       xmlns="http://www.myNamespace.net"
       targetNamespace="http://www.myNamespace.net"
       elementFormDefault="qualified">
   <xsd:element name=""A">
     <xsd:complexType>
       <xsd:sequence>
         <rr><rd:element name="field1" type="xsd:int"/></r>
         <rsd:element name="field2">
           <xsd:simpleType>
             <xsd:restriction base="xsd:string">
               <rsd:maxLength value="30"/>
             </xsd:restriction>
           </xsd:simpleType>
         <xsd:element name="B" minOccurs="0" maxOccurs="unbounded">
         </xsd:element>
         <xsd:element name="C" minOccurs="O" maxOccurs="unbounded">
           <xsd:element name="D" minOccurs="0" maxOccurs="unbounded">
           </xsd:element>
</xsd:schema>
```

An XML document may also be stored in a subset of a database record, from a non-root segment and its dependents, as shown in Figure 9-4. The subset must be a segment and its dependents. The highest level segment in the subtree is the XML root element segment. All of its dependents are included in the XML document. Of course, the XML root element segment may be the database root segment. In this case, the XML document would correspond to the entire database record.




Figure 9-4 An XML document may be stored in a subset of a database record

9.2.3 Intact storage

Information from an XML document can be inserted, retrieved or deleted from the document intact into an IMS database. This can be a new or existing database. The data is stored as XML, and includes both the XML tags and the data fields. The data in these databases can only be manipulated by applications that are knowledgeable of XML, since traditional applications will not understand the XML format.

For intact storage, the data is stored in segments based on the number of bytes in the document, without regard to XML tags. There are two segment types per document, one "root" segment and as many overflow segments as necessary to store the entire document. There is no correspondence between XML elements and database segments. The root segment contains a fixed number of bytes of XML data. Each overflow segment also contains a fixed, but different, number of bytes. The illustration in Figure 9-5 shows that elements from the XML document may span database segments.




Figure 9-5 Intact storage of an XML document into an IMS database

We will see later that the IMS database may also contain special segments used for secondary indexes.

When intact storage is used, the XML document is not parsed or validated when it is stored in an IMS database unless secondary indexing is used. The XML document is stored in the database as Unicode. Traditional IMS applications do not process XML or Unicode, so they are not able to process XML documents when they are stored intact. These documents are accessible to applications which can process XML and Unicode. Data is not converted to traditional IMS types, but is stored as Unicode. These documents are only accessible by XML-enabled applications.

Secondary indexing for intact XML documents

When an XML document is stored intact in an IMS database, one or more *side segments* may be used for secondary indexing. A side segment is a source segment, which has had its segment data converted to traditional data types. Data may come from either an element or an attribute of the XML document - this data remains in the document root or overflow segments. The target segment is segment above source segment in the database hierarchy. In Figure 9-6 on page 152, the S1, S2 through Sn segments contain the data used for the secondary indexes. The target of the secondary index is segment A.




Figure 9-6 Secondary indexing for intact stored XML documents

An XML document may also be stored in a subset of the database record. In this situation, the XML root element segment is different to the database root segment. This is shown in Figure 9-7.




Figure 9-7 An intact XML document may be stored in a subset of a database record

Mixing decomposed and intact storage

A schema may include both decomposed and intact storage. The intact part must be a complete subtree of elements in the XML element hierarchy, as shown in Figure 9-8 on page 153.

This means that the intact segments will be a subtree of database segments containing XML data.




Figure 9-8 Mixing decomposed and intact storage of an XML document

9.2.4 DLIModel Utility

The DLIModel Utility is used to create the XML schema for an XML document. This is a new function of the utility for IMS Version 9. The schemas are created from PSBs, DBDs, and COBOL copybook XMI files, as shown in Figure 9-9.

The DLIModel Utility was first introduced with IMS Version 7, to create IMS Java metadata classes from PSBs and DBDs. The utility also incorporates additional field information from XMI input files that describe COBOL copybook members, since many DBDs do not completely describe the fields in the database. The utility can be run as a z/OS batch job, or from a command prompt under UNIX System Services.




Figure 9-9 The DLIModel Utility

There are a number of control statements that can be specified for this utility, with new options for the creation of XML schemas. The OPTIONS statement has new parameters, indicating whether an XML schema is to be generated (GenXMLSchemas=YES|NO), as well as the path where the schema is to be stored (XMLSchemaPath=path).

The PCB statement also has new parameters:

- GenXMLSchema=RETRIEVE|STORE|NO
- XMLRootElement=segmentname

The SEGM statement has a new parameter:

XMLStorageType=DECOMPOSED INTACT

And the FIELD statement has a new parameter:

XMLType=ELEMENT | ATTRIBUTE | NONE

GenXMLSchema=STORE checks for the following PCB limitations:

- The PCB must be based on a physical DBD
- The PCB PROCOPT includes I or A
- No segments in the hierarchy may be logical children
- The hierarchy must be based on a primary access path
 - Not a secondary index access path (PROCSEQ)
- All segments must have their key fields present
 - that is, they have not been excluded by field-level sensitivity
- No segments may have PROCOPT=K.

Example 9-2 on page 155 is an example of a the control statements that could be used to generate a schema using the DLIModel Utility. The utility is also used to create metadata for IMS Java. The additional keywords and parameters used to create a schema are:

GenXMLSchemas=yes on the OPTIONS statement

This specifies that XML schemas will be generated.

GenXMLSchema=store of the PCB statement for PCB1

This specifies that an XML schema will be generated for this PCB and that a check will be made to ensure that the PCB may be used for storing XML documents.

XMLRootElement=DEALER

This specifies that the DEALER segment will be the XML root element segment.

XMLType=attribute on the FIELD statement for DLRNO

This specifies that the data in the DLRNO field will be mapped to an attribute in the XML document.

Two defaults are documented in comments:

 XMLStorageType=decomposed is the default on the SEGM statement for the DEALER segment.

This specifies that decomposed storage is used for the data mapped to this segment.

XMLType=element is the default on the FIELD statement for DLRNAME.

This specifies that the data in the DLRNAME field will be mapped to an element in the XML document.

The CITY, ZIP, and PHONE fields also use the default for XMLType. They will be mapped to elements. Defaults are used except on the FIELD statement for MAKE. XMLType=none specifies that this field in the database is not mapped to the XML document.

FIELD statements are not required if you have a COBOL copybook XMI file which describes the fields. This is shown in the last SEGM statement. A FIELD statement is used in the example to specify that the COLOR field is not mapped to the XML document. This is done by specifying XMLType=none. A COBOL copybook XMI file may be generated from a COBOL copybook by using WebSphere Studio Application Developer Integrated Edition (WSADIE).

There are other options for statements. These are documented in the *IMS Version 9: Utilities Reference: System,* SC18-7834 manual in its explanation of the DLIModel Utility. For example, one may code FIELD statements which completely describe fields including their offsets and sizes in segments. One would do this if the fields were not defined in the DBD or an XMI file.

Example 9-2 DLIModel control statements used to generate an XML schema

OPTIONS PSBds=IMSVS.TEST.PSBSRC DBDds=IMSVS.TEST.DBDSRC GenJavaSource=YES GenXMLSchemas=yes PSB psbName=fA02psb JavaName=AUTPSB11 PCB pcbName=PCB1 JavaName=Dealer GenXMLSchema=YES XMLRootE1ement=DEALER // Physical Segments for DEALERDB SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment //defaults to XMLStorageType=decomposed FIELD Name=DLRNO JavaType=INTEGER JavaName=DealerNo XMLType=attribute FIELD Name=DLRNAME JavaType=CHAR JavaName=DealerNo XMLType=attribute FIELD Name=ZIP JavaType=CHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerZip FIELD Name=PHONE JavaType=CHAR JavaName=DealerZip FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelKey FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=PACKEDDECIMAL TypeQualifier=Sy999999 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR XMLType=none	
GenXMLSchemas=yes PSB psbName=f402psb JavaName=AUTPSB11 PCB pcbName=PCB1 JavaName=Dealer GenXMLSchema=YES XMLRootElement=DEALER // Physical Segments for DEALERDB SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment //defaults to XMLStorageType=decomposed FIELD Name=DLRNO JavaType=INTEGER JavaName=DealerNo XMLType=attribute FIELD Name=OLRNAME JavaType=CHAR JavaName=DealerName //defaults to XMLType=element FIELD Name=CITY JavaType=CHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODEL JavaType=CHAR JavaName=ModelType FIELD Name=MODEL JavaType=CHAR JavaName=ModelKey FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=COUNT JavaType=CHAR JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	OPTIONS PSBds=IMSVS.TEST.PSBSRC
PSB psbName=f402psb JavaName=AUTPSB11 PCB pcbName=PCB1 JavaName=Dealer GenXMLSchema=YES XMLRootElement=DEALER // Physical Segments for DEALERDB SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment //defaults to XMLStorageType=decomposed FIELD Name=DLRNO JavaType=INTEGER JavaName=DealerNo XMLType=attribute FIELD Name=DLRNAME JavaType=CHAR JavaName=DealerName //defaults to XMLType=cHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModDTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODELY JavaType=CHAR JavaName=ModelType FIELD Name=MODELY JavaType=CHAR JavaName=ModelKey FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=CHAR JavaName=Model FIELD Name=MSRP JavaType=CHAR JavaName=Model FIELD Name=MSRP JavaType=CHAR JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	DBDds=IMSVS.TEST.DBDSRC GenJavaSource=YES
PCB pcbName=PCB1 JavaName=Dealer GenXMLSchema=YES XMLRootElement=DEALER // Physical Segments for DEALERDB SEGM DbdName=DEALERDB segmentName=DEALER JavaName=DealerSegment //defaults to XMLStorageType=decomposed FIELD Name=DLRNAME JavaType=INTEGER JavaName=DealerNo XMLType=attribute FIELD Name=DLRNAME JavaType=CHAR JavaName=DealerName //defaults to XMLType=element FIELD Name=CITY JavaType=CHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerCity FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODYPE JavaType=CHAR JavaName=ModelKey FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	GenXMLSchemas=yes
<pre>XMLRootElement=DEALER // Physical Segments for DEALERDB SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment</pre>	PSB psbName=f402psb JavaName=AUTPSB11
<pre>// Physical Segments for DEALERDB SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment</pre>	PCB pcbName=PCB1 JavaName=Dealer GenXMLSchema=YES
<pre>SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment</pre>	XMLRootElement=DEALER
<pre>SEGM DbdName=DEALERDB SegmentName=DEALER JavaName=DealerSegment</pre>	
<pre>//defaults to XMLStorageType=decomposed FIELD Name=DLRNO JavaType=INTEGER JavaName=DealerNo XMLType=attribute FIELD Name=DLRNAME JavaType=CHAR JavaName=DealerName //defaults to XMLType=element FIELD Name=CITY JavaType=CHAR JavaName=DealerCity FIELD Name=ZIP JavaType=CHAR JavaName=DealerZip FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODEL JavaType=CHAR JavaName=ModelKey FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MAKE JavaType=CHAR JavaName=Model FIELD Name=MAKE JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=GUINT JavaType=PACKEDDECIMAL TypeQualifier=S99999V99 JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=DLRNO JavaType=INTEGER JavaName=DealerNo</pre>	
<pre>XMLType=attribute FIELD Name=DLRNAME JavaType=CHAR JavaName=DealerName</pre>	
<pre>FIELD Name=DLRNAME JavaType=CHAR JavaName=DealerName</pre>	
<pre>//defaults to XMLType=element FIELD Name=CITY JavaType=CHAR JavaName=DealerCity FIELD Name=ZIP JavaType=CHAR JavaName=DealerPione SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MOKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Make XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S99999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=CITY JavaType=CHAR JavaName=DealerCity FIELD Name=ZIP JavaType=CHAR JavaName=DealerZip FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S99999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=ZIP JavaType=CHAR JavaName=DealerZip FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=PHONE JavaType=CHAR JavaName=DealerPhone SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODKEY JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Make XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>SEGM DbdName=DEALERDB SegmentName=MODEL JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Model FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
JavaName=ModelSegment FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Make XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
<pre>FIELD Name=MODTYPE JavaType=CHAR JavaName=ModelType FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Make XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=MODKEY JavaType=CHAR JavaName=ModelKey FIELD Name=MAKE JavaType=CHAR JavaName=Make XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=MAKE JavaType=CHAR JavaName=Make XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
XMLType=none FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
<pre>FIELD Name=MODEL JavaType=CHAR JavaName=Model FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
<pre>FIELD Name=YEAR JavaType=Date TypeQualifier=yyyy JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR</pre>	
JavaName=Year FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
FIELD Name=MSRP JavaType=PACKEDDECIMAL TypeQualifier=S999999V99 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
TypeQualifier=S999999999 JavaName=MSRP FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
FIELD Name=COUNT JavaType=SMALLINT JavaName=ModelCount SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
SEGM DBDName=DEALERDB SegmentName=STOCK JavaName=StockSegment CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	FIELD Name=COUNT JavaType=SMALLINT JavaName=ModerCount
CobolXMI=imsjava/mdlex4/AutoStock.xmi FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	SECM DRDName-DEALEDDR SegmentName-STOCK lavaName-StockSegment
FIELD Name=COLOR JavaType=CHAR JavaName=COLOR	
	· · · · · · · · · · · · · · · · · · ·

9.3 JDBC interface

The Java Database Connectivity interface (JDBC) has been extended with two user defined functions (UDF). They are *retrieveXML()*, and *storeXML()*.

The retrieveXML statement is included in the select list of a JDBC SELECT operation, to retrieve XML document(s) from an IMS database. The information is returned as a character large object (CLOB) in the returned JDBC ResultSet per row.

The storeXML() statement is included in a JDBC INSERT statement, which stores an XML document in an IMS database. The position of the record in the database is determined by the WHERE clause.

An example of the use of RetrieveXML() is shown in Figure 9-10. The XML root element segment is C. It is specified in retrieveXML(C). The WHERE clause requests documents which have a value of 35 in a fieldA instance. Segment D112 meets this qualification, so the document stored in instance C11 of the C segment and its dependents is returned. Segment D221 also meets this qualification, so the document stored in instance C22 and its dependents is returned.




Figure 9-10 RetrieveXML()

An example of the use of storeXML() is shown in Figure 9-11 on page 157. The XML root element segment is C. The INSERT statement requests that the document be stored under instance of segment A which has a value of 62 in fieldA. The document is stored in segments C22, D221, and D222. You may notice that the WHERE clause is not like standard SQL which does not use a WHERE clause with INSERT.




Figure 9-11 StoreXML()

9.4 XML database summary

IMS XML DB allows you to view existing or new IMS databases as XML databases, offering easy exchange of data between IMS DBs and XML documents. IMS XML DB offers two storage modes:


- Decomposed storage
 - Ideal for data-centric XML documents requiring full searching or legacy interoperability
 - Existing IMS databases may be used to create XML documents
 - Existing IMS applications are unaffected
- Intact storage
 - Ideal for document-centric XML documents or requiring increased retrieval performance
 - Search capability only through use of side segments and secondary indices

The DLIModel utility has been extended to:

- Assist in building XML metadata mapping to IMS
- Generate XML schema definitions for XML documents

The IMS Java JDBC interface has been extended to:

- Include a retrieveXML keyword for XML retrieval
- Include a storeXML keywork for XML insertion



10

IMS Java enhancements

IMS Version 9 provides enhancements for the IMS Java environment. In this chapter, we focus specifically on IMS Java enhancements as well as remote database access which uses WebSphere Application Server for z/OS Version 5.0 and WebSphere Application Server on any other platforms. IMS Java enhancements also include XML storage in IMS Databases, and is dealt with exclusively in Chapter 9, "XML storage in IMS databases" on page 145.

In this chapter we provide an overview of the IMS Java environment first, and then we introduce IMS Java enhancements in IMS Version 9:

- IMS Java environment overview
- IMS-DB2 interoperability
- Symbolic checkpoint and restart in a JBP region
- Java-COBOL interoperability
- IMS Java GSAM support for JBP applications
- JDBC and SQL enhancements
- Remote database access services using WebSphere Application Server

You can find IMS Java updates for each IMS version at the following URL:

http://www.ibm.com/software/data/ims/imsjava/javenhance.html

10.1 IMS Java environment overview

Since IMS Version 7, IMS has provided the capability to allow Java programs to access IMS resources. The supported environments include IMS application programs running in a Java message processing region (JMP) or a Java batch processing region (JBP), as well as Java programs running in other environments such as DB2 stored procedures, JCICS, and WebSphere Enterprise Java Beans (EJBs). This is shown in Figure 10-1.




Figure 10-1 Java in the IMS environment

IMS Java is delivered in a layered set of class libraries. This concept allows for the high-level classes to focus strongly on ease-of-use, and the lower-level classes to provide complete access to IMS services and serve as the implementation vehicle for the higher-level classes. The diagram in Figure 10-2 shows the layered set of class libraries.




Figure 10-2 The layered set of class libraries used for Java with IMS

Access to IMS data from a Java program is provided by Java Database Connectivity (JDBC), which is the standard Java API for accessing data. IMS JDBC support allows SQL statements to be used to access an IMS database, and processes the data returned by the database. Execution of query statements establishes and opens a connection to the database, executes the query to obtain results, processes the results, and then closes the connection. IMS Version 9 no longer ships the IMS Java API specification on z/OS, but this specification is available in the Web.

10.2 IMS and DB2 interoperability

IMS Version 9 has extended the support for Java programs running in a JMP or JBP region. These programs are now able to access DB2 databases, as well as IMS databases. This support is provided as part of the base IMS Version 9, and through the service process for IMS Version 8 with UQ80615.

The support for access to DB2 uses the DB2 resource recovery service attach facility (RRSAF), and requires the SSM and RRS parameters in the IMS control region. With RRSAF, the dependent region builds an attachment thread to DB2 UDB for z/OS using Resource Recovery Services (RRS). RRS coordinates the commits of the updates that the JMP or JBP applications make to both IMS and DB2 resources. IMS is a participant, not the coordinator, of these updates and commits.

Unlike other dependent regions, JMP and JBP regions do not use the external subsystem attach facility (ESAF) which MPP, BMP, IFP, DLI, DBB, and DBCTL BMPs programs uses when they access external subsystems such as DB2 UDB for z/OS.

Only one active DB2 connection at a time is supported, although future support for multiple connections is a known requirement. Access to DB2 through JDBC and SQLJ is supported. DB2 UDB for z/OS provides different JDBC drivers:

- JDBC/SQLJ driver for DB2 for OS/390 and z/OS with JDBC 2.0
- ► JDBC/SQLJ driver for DB2 for OS/390 and z/OS with JDBC 1.2
- DB2 Universal JDBC driver

The JDBC/SQLJ drivers are type 2 JDBC drivers which allow access to DB2 databases only when IMS is on the same z/OS image as DB2 UDB for z/OS. DB2 Universal JDBC driver supports Universal Driver type 4 connectivity which allows access to DB2 databases from IMSs that are on different z/OS images from one DB2 UDB for z/OS is on. It also provides the type 2 implementation.

10.2.1 Setting up the IMS to DB2 connection using RRSAF

There are several parameters in your IMS system that need to be specified to connect your IMS system to DB2 using RRSAF:

In your IMS.PROCLIB, create an SSM member which specifies the connection to DB2. The member name must follow the same naming conventions as when attaching DB2 with the traditional external subsystem attach facility (ESAF), like xxxxnnn: xxxx is of IMSID=, nnnn is of SSM=. Refer to *IMS Version 9: Installation Volume 2: System Definition and Tailoring*, GC18-7823 for more detail of SSM PROCLIB member. The following three parameters must be specified in this member:

SST=DB2,SSN=db2name,COORD=RRS

Add a DFSJVMMS member to your IMS.PROCLIB, specifying a DB2 JDBC driver path, to the ZIP file and to the ZIP file name, to the trusted middleware path, for example: -Dibm.jvm.trusted.middleware.class.path=>
/usr/lpp/db2/db2710/classes: >
/usr/lpp/db2/db2710/classes/db2j2classes.zip

Add a DFSJVMEV member to your IMS.PROCLIB, specifying a DB2 JDBC driver path to the LIBPATH environment variable, for example:

LIBPATH=/usr/lpp/db2/db2710/lib

- In your IMS control region startup parameters, add the subsystem name with the SSM=name parameter, as well as telling IMS to use Resource Recovery Services through the RRS=Y parameter.
- For the DFSJMP or DFSJBP procedure of the regions that access DB2, add the DFSDB2AF DD pointing to the DB2 libraries, which must be authorized.

10.2.2 Accessing DB2 UDB for z/OS databases from JMP or JBP applications

Accessing DB2 UDB for z/OS data from a JMP or JBP application is similar to accessing IMS data. When writing a JMP or JBP application that accesses DB2 data, consider both the differences from IMS database access and the differences from accessing DB2 data in other environments:

- ► You can have only one active DB2 UDB for z/OS connection open at any time.
- For type 2 JDBC drivers, you must use the default connection URL in the application program, for example, jdbc:db2os390: or db2:default:connection.
- For type 4 JDBC drivers, you can use a specific connection URL in the application program.
- To commit work, you must use this method:
 - IMSTransaction.getTransaction().commit()
 - For JMP, this method commits all work; SQL call and connection closures.
 - For JBP, this method commits SQL calls.
- ► To roll back work, you must use this method:
 - IMSTransaction.getTransaction().rollback()
- ► Because RRS is the coordinator, you cannot use these methods:
 - Connection.setAutoCommit()
 - Connection.commit()
- You must always call IMSTransaction.getTransaction().commit() after closing a connection to DB2 UDB for z/OS to commit the connection closure.
- ▶ You cannot use COBOL to access DB2 UDB for z/OS in a JMP or JBP region.

JMP application that accesses DB2 UDB for z/OS data

When a JMP application accesses only IMS data, it needs to open a database connection only once to process multiple transactions. However, a JMP application that accesses DB2 data must open and close a database connection for each message processing, with IMSTransaction.getTransaction().commit() method.

JBP application that accesses DB2 UDB for z/OS data

Like a BMP application that accesses IMS data, a JBP application that accesses DB2 data connects to a database, performs database processing, periodically commits, and disconnects from the database at the end of the application. However, the application accessing DB2 data must issue a final commit after closing the database connection. Thus,

application issues IMSTransaction.getTransaction().commit() as periodic commit, closes the connection, then issues IMSTransaction.getTransaction().commit() again.

10.3 IMS Java symbolic checkpoint and restart for JBP

IMS Version 9 extends the IMS symbolic checkpoint and restart capability to the IMS Java environment. It is supported only for JBP applications, and allows them to take application checkpoints, so they can restart from the last checkpoint after a failure. The program can save critical application Java objects as a part of the checkpoint processing. IMS restores those objects at restart, as well as the database positions at the time of the checkpoint.

The support for IMS Java symbolic checkpoint and restart is provided through two new methods in the IMSTransaction class, checkpoint() and restart(). These methods perform analogous functions to the existing IMS system service calls: (symbolic) CHKP and XRST, respectively.

The IMSTransaction.restart() method is used at the initial application start, to notify IMS to enable checkpoint and restart capability. At a program restart, the program must provide the checkpoint id to use from either a restart call parameter, similar to providing the id to the XRST call in IMS, or the CKPTID= parameter through the JBP region JCL. If both methods are used in the same program, the CKPTID= parameter takes precedence. The method will obtain the checkpointed objects from an earlier checkpoint.

The IMSTransaction.checkpoint() method allows the program to invoke an IMS checkpoint and supply a checkpoint id. The program can optionally provide String checkpoint id, or an object (com.ibm.ims.application.SaveArea) containing the Java objects whose state is to be saved with the checkpoint.

The IMS Java symbolic checkpoint and restart capability is based on the existing symbolic checkpoint and restart facility in IMS, as provided for BMP applications. It implements a Java interface to the traditional IMS checkpoint and restart facility and shares the functional capabilities of that facility.

Symbolic checkpoint and restart support in IMS Java allows user applications in JBP regions to:

- ► Take application checkpoints, and to restart from the last checkpoint after a failure.
- Save critical application Java objects as part of the checkpoint, and to restore those objects at restart.
- Save database positions as part of the checkpoint and verify repositioning of those databases at restart.

Note: IMS Java is adding the capability to do symbolic checkpoints and restarts in a JBP much like the capability that has been available for years in an IMS BMP. What is being documented is the set of calls to do this. The considerations for the use of these calls in a JBP are the same as the considerations for the same calls in a BMP.

10.3.1 Checkpoint call formats

The formats of the Java checkpoint call provided by IMSTransaction class are:

- public void checkpoint() throws IMSException
- public void checkpoint(SaveArea objectsToSave) throws IMSExeption

- public void checkpoint(String chkpId) throws IMSException
- public void checkpoint(String chkpId, SaveArea objectsToSave) throws IMSException

All of these checkpoint methods are used to perform a checkpoint call for JBP application that uses symbolic checkpoints. JBP application using checkpoint and restart function calls these methods at intervals to cause checkpoints to be written to the IMS log. The difference is:

- The first method without parameters is used in the cases where the application needs to take checkpoint without having to specify a checkpoint id and also without having to save any application objects, which is described as SaveArea object later. When using this method for taking checkpoints, the application should use the 4-character constant "LAST" as the checkpoint id to restart from.
- If the application needs to save application objects, it should use one of the following forms of the checkpoint method:
 - checkpoint(SaveArea objectsToSave)
 - checkpoint(String chkpId, SaveArea objectsToSave)
- If the application needs to specify a checkpoint id, it should use one of the following forms of the checkpoint method:
 - checkpoint(String chkpId)
 - checkpoint(String chkpId, SaveArea objectsToSave)

Checkpointed objects may be instances of standard Java classes (for example, Integer, String, and so on), or user defined application classes (for example, Customer, Part).

The checkpoint() method uses Java serialization to prepare the objects for checkpointing by IMS. This means that all objects that are passed in the SaveArea must implement the Java serializable interface. Additionally, each invocation of checkpoint() may specify different numbers or types of objects in its SaveArea parameter. Note, however, that the application must be able to interpret the returned objects at restart time. If different objects are to be saved on each checkpoint, consider including descriptive information in the saved data (i.e., in an object). A size limit is set on the objects to be checkpointed. The default total length of all the objects in serialized form may not exceed 64KB. An IMSException is thrown if the objects in a checkpoint exceed this limit. The default total length of all objects in serialized form is 64K which may be changed by issuing the setCheckpointSizeLimit() method.

The other methods available for the com.ibm.application.SaveArea are:

add0bject	Adds Java objects to be checkpointed
get0bject	Gets the Java objects back
verifyPCBPosition	Verifies the database position after restart
setCheckpointSize	Sets the maximum possible checkpoint length for the application to use.

10.3.2 Restart call formats

The formats of the Java restart call provided by IMSTransaction class are:

- public SaveArea restart() throws IMSException
- public SaveArea restart(String chkpId) throws IMSException

These methods are equivalent to the IMS XRST call. As is the case for non-Java programs, the ID specified can be one of following:

1 to 8 character checkpoint ID

- ► 14 character time stamp ID from IMS message DFS0540I
- ► The literal "LAST"

These restart method is used in two ways:

- At normal program start, these methods just tell IMS that subsequent checkpoint calls are symbolic checkpoint calls. You may use restart method that takes no parameters, or may use restart method with null checkpoint id parameter. The CKPTID= in the JBP region procedure also must be null.
- If the application is restarting from a checkpoint, pass a restart checkpoint id either with restart(String id) method, or with restart() method and valid CKPTID= parameter in the JBP region procedure. If the String id parameter and the CKPTID= parameter are set to a non-null value, the CKPTID= parameter in the EXEC statement takes precedence.

The invocation of the restart() method should be done only once and should be early in the execution of the program. It does not need to be the first call in the program but it should precede any invocation of the IMSTransaction.checkpoint method. The restart method call are not within the scope of a restart.

A restart is performed operationally in a very similar manner to existing non-Java BMP restarts. The job is resubmitted, supplying a checkpoint ID in one of two ways, either as a restart call parameter or in a JCL parameter. Both approaches require appropriate user operational procedures to manage master terminal messages, checkpoint ids, and so on. The first approach requires a suitable application program design to obtain the checkpoint ID by some means, and to provide it to the restart() invocation. These are user responsibilities that are the same as for non-Java IMS programs that use the checkpoint and restart facility. The second approach is perhaps an easier mechanism and takes advantage of specifying the ID in the CKPTID= field of the PARM= parameter on the EXEC statement in the program's JCL.

During the restart, a SaveArea object is returned that contains the Java objects that were saved with the checkpoint. The objects are contained in the returned SaveArea object in the same sequence as they were saved by a checkpoint method. It is an application responsibility to retrieve these objects from the SaveArea object, to cast them to the correct application object types, and to prepare the application for continued execution. If no application objects were saved with this checkpoint, the method returns a null reference is returned.

Under the covers, the SaveArea class issues the system service call INQY with the FIND subfunction using the PCB name to get the PCB address. This address is used to check the PCB status code to determine if the database has been repositioned properly after the restart() call.

IMS repositions the application databases if possible. It is an application responsibility, however, to follow the restart with one or more invocations of the verifyPCBPosition method to confirm that repositioning was successful for each significant PCB.

The **SaveArea.verifyPCBPosition** method verifies that IMS was able to reposition a database(s) during restart. There are two variations of this call:

specify the name(s) of the PCB(s) as String with this format:

public boolean verifyPCBPosition(String pcbName) throws IMSException

► specify the name(s) of the PCB(s) as an array of Strings parameter with this format:

public boolean verifyPCBPosition(String [] pcbNames) throws IMSException

The design of this support contains an arbitrary default upper limit on the total serialized length of the checkpointed objects, which is set at 64KB. The limit exists because at restart time the application (and the IMS Java checkpoint and restart code) do not know the length of

the serialized object data on the IMS log. This necessitates making an assumption about the length when preparing a receiving memory extent for the IMS XRST call. The assumed length must be at least as large as the data on the log. The arbitrary upper limit could be increased to more than 64KB, but the trade-off is that at restart time IMS Java must create a byte array of this length in the dependent region. An application program obtains the SaveArea object by invoking the static SaveArea.getSaveArea() method.

Since the IMS Java restart() call is converted to an IMS XRST, an attempt is made to reposition all databases to the position that was held when the last checkpoint was taken. This is done by including each PCB and PCB key feedback area in the checkpoint record. Issuing XRST causes the key feedback area from the PCB in the checkpoint record to be moved to the corresponding PCB in the PSB that is being restarted. Then IMS issues a GU call, qualified with the concatenated key (using the C command code), for each PCB that held a position when the checkpoint was taken.

After the XRST call, the PCB reflects the results of the GU repositioning call, not the value that was present when the checkpoint was taken. The GU call is not made if the PCB did not hold a position on a root or lower-level segment when the checkpoint was taken. A GE status code in the PCB means that the GU for the concatenated key was not fully satisfied. The segment name, segment level, and key feedback length in the PCB reflect the last level that was satisfied on the GU call. A GE status code can occur because IMS is unable to find a segment that satisfies the segment search argument that is associated with a Get call for one of the following reasons:

The call preceding the checkpoint call was a DLET call issued against the same PCB.

In this case, the position is correct because the not-found position is the same position that would exist following the DLET call. The functionality and operational characteristics of using the symbolic checkpoint and restart should be similar to those of IMS applications such as BMPs that use the existing checkpoint and restart facility of IMS.

The segment was deleted by another application program between the time the program terminated abnormally and the time it was restarted.

A GN call issued after the restart returns the first segment that follows the deleted segment or segments.

The above explanation assumes that position at the time of checkpoint was on a segment with a unique key. XRST cannot reposition to a segment if that segment or any of its parents have a non unique key.

For a DEDB, the GC status code is received when position is not on a segment but at a unit-of-work (UOW) boundary. Because the XRST call attempts to reestablish position on the segment where the PCB was positioned when the symbolic checkpoint was taken, the XRST call does not reestablish position on a PCB if the symbolic checkpoint is taken when the PCB contains a GC status code.

10.4 IMS Java GSAM support for JBP applications

With IMS Version 9, JBP applications can process GSAM databases. This support, along with symbolic checkpoint and restart support for JBP applications, gives JBP applications more of the functionality of BMP applications.

GSAM databases are useful if you need a JBP application that accesses z/OS data sets to use the IMS symbolic checkpoint call. Because GSAM databases are supported in a DCCTL environment, you can also use them when a JBP application needs to process sequential

non-IMS data sets. From a JBP application, you can open, read, write, and close a GSAM database. There are three new IMS Java classes for processing GSAM databases:

- com.ibm.ims.db.GSAMConnection
- com.ibm.ims.db.GSAMRecord
- ► com.ibm.ims.application.RSA.

See the IMS Java API Specification for details on these classes.

10.5 Java-COBOL interoperability

From within JMP or JBP applications, you can call an object-oriented (OO) COBOL application with IMS Enterprise COBOL for z/OS and OS/390 Version 3 Release 2. And, you can build an OO COBOL application containing a main routine that can invoke Java routines. This functionality is provided through IMS Version 7 (with UQ75641) and Version 8 (with UQ74520). Refer to *IMS Version 9: IMS Java Guide and Reference*, SC18-7821, for more details.

10.5.1 Enterprise COBOL as a back-end application in a JMP or JBP region

From an OO COBOL class, the Enterprise COBOL compiler generates a Java class definition with native methods and the object code that implements the native methods. After compiling the class, you can create an instance and invoke the methods of the class from a Java program that runs in a JMP or JBP region.

When Java is the front-end language, you must perform all message-queue and message-synchronization processing in Java. In the back-end application, you can access IMS databases by either using Java or calling a COBOL routine.

10.5.2 Enterprise COBOL as a front-end application in a JMP or JBP region

You can write an application for an IMS Java dependent region entirely with OO COBOL, but a more likely use for a front-end COBOL application is to call a Java routine from a COBOL application.When running within the JVM of an IMS Java dependent region, Enterprise COBOL run-time support automatically locates and uses this JVM to invoke methods on Java classes.

This COBOL application with a main routine that runs in a JMP or JBP region has the same requirements as a Java program. For example, it must commit resources before reading subsequent messages or exiting the application. This COBOL GU call does not implicitly commit resources when the program is running in an JMP or JBP region as it does when the program is running in an JMP or JBP region as it does when the program is running message processing and transaction synchronization, a CHKP call in an IMS Java dependent region does not automatically retrieve a message from the message queue.

10.6 JDBC and SQL enhancement

These enhancements are supported as UQ74475 for IMS Version 8. As additional information, we introduce the future enhancement of SQL syntax.

10.6.1 JDBC enhancement

IMS Version 9 supports Java Database Connectivity (JDBC) including the ability to obtain scroll insensitive result sets. This is the new types of result sets provided as java.sql.ResultSet interface's static constants, ResultSet.TYPE_SCROLL_INSENSITIVE and ResultSet.TYPE_FORWARD_ONLY.

TYPE_SCROLL_INSENSITIVE indicates the type for a ResultSet object that is scrollable but generally not sensitive to changes made by others. This result set contains data which is not sensitive to underlying changes in the database while the result set is open. Result sets of this type may also be traversed in reverse order, by absolute position, or by relative position.

TYPE_FORWARD_ONLY indicates the type for a ResultSet object whose cursor may move only forward. This is the default result set type unless another type is explicitly requested or an SQL query is processed that contains aggregates, ORDER BY, or GROUP BY clause.

Refer to *IMS Version 9: IMS Java Guide and Reference*, SC18-7821 for more detail about supported JDBC interfaces.

10.6.2 SQL enhancement

Structured Query Language (SQL) enhancements for new SQL keywords and aggregate functions are supported in IMS Version 9, which are SUM, AVG, MIN, MAX, COUNT, ORDER BY, and GROUP BY.

For the SUM and AVG functions, arguments must be numbers and the data type of the result is the same as the data type of the argument. There are some exception, that the result is a long if the argument type is a byte, short, or an integer. Or that the result is a double-precision floating point if the argument type is a single-precision floating point.

For the MIN, MAX functions, arguments values can be any built-in type except BIT, BLOB, and BINARY. The data type of the result is the same as the data type of the argument. For the COUNT function, the argument can be any field name in a segment.

The DISTINCT keyword is not supported as an argument to any of the functions.

The field names specified in a GROUP BY or ORDER BY clause must exactly match the field name specified in the SELECT list.

The AS clause is used to rename any field in a SELECT list. If an AS clause is used, the new field name must be used to reference the field. In the event that an aggregate function is used without an AS clause, the resulting column name is the function name, followed by an underscore, followed by the field name. For example, MAX(age) will result in a column name of MAX_age. The name MAX_age is then to be used for all subsequent references to the field like ResultSet resultSet.getInt("MAX_age").

10.6.3 SQL syntax enhancement

IBM intends to enhance SQL syntax pertain to the usage of fields in an SQL WHERE clause. This is going to be the enhancement after the general availability of Version 9.

At this time, only searchable fields, which mean that they are defined in an IMS DBD, are allowed in a WHERE clause. However, there are situations where a searchable field is further broken down into subcomponents via COBOL copybooks, depending your applications.

For example, the field 'Address" can be broken down into 'city', 'state' and 'zip code'. This case is supported by IMS Java, however, we do not support using the fields city, state, or zip

code in the WHERE clause itself. We are adding support to allow for this in near future. We call these fields ('city', 'state', and 'zip code') Non-searchable fields. Non- searchable fields will be able to be used in a WHERE clause with the following rules adhered:

- All subfields of a searchable field must be provided
- All subfields must be provided consecutively, although they can be in any order
- All subfields must be ANDed with one another
 - No sense to say:

```
WHERE City = X OR State = Y
```

- These fields are going to be concatenated together to form the actual searchable field
- The '=' operator is the only supported operator when a subfield is compared to a value
 - No sense to say:

WHERE City > someValue AND State < another Value

- These fields are going to be concatenated together to form the actual searchable field

With this support, you can simply concatenate the fields together themselves to form the key field. For example, to continue with the notion of an 'Address' field broken down into 'City', 'State', and 'Zip', it seems it would be quite easy to just combine the three into one String object and use it in the SQL query:

```
SELECT *
FROM MyPCB.MySegment
WHERE Address = 'Los Gatos California 95030'
```

as opposed to:

```
SELECT *
FROM MyPCB.MySegment
WHERE City = 'Los Gatos' AND State = 'California' AND Zip = '95030'
```

Imagine if the City field was a double-precision (double in Java), State was a single-precision (float in Java), and Zip was an integer, as we have seen that the subfields are not necessarily of the same type. It is extremely difficult to manually convert all of those data types, especially since Java doubles and floats use the IEEE 754 standard and z/OS or OS/390 does not. It makes the first query quite difficult. However, with this support you can simply use the second query above and IMS Java library will handle all of the type conversion on behalf of the applications.

10.7 Remote database services

IMS Version 9 provides IMS Java remote database services in which you can develop and deploy applications that run on WebSphere Application Server on non-z/OS platform and access IMS databases remotely through EJB on WebSphere Application Server for z/OS.

Through several IMS versions, you have been able to write applications that run on WebSphere Application Server for z/OS and access IMS databases. See Figure 10-3 on page 170.





Figure 10-3 WebSphere Application Server for z/OS EJB using IMS Java

This shows an EJB on WebSphere Application Server for z/OS is accessing IMS data. JDBC or IMS Java hierarchical interface calls (which are also classes and methods provided by IMS Java, whose formats are similar to DL/I calls), are passed to the IMS Java layer, which converts the calls to DL/I calls. The IMS Java layer passes these calls to IMS Open DataBase Access (ODBA), which uses the database resource adapter (DRA) to access the DL/I region in IMS. Note you still need to develop a z/OS application to access IMS data, that is, DB access logic is still on z/OS.

For more detail about ODBA and DRA, refer to manuals *IMS Version 9: Application Programming: Database Manager,* SC18-7809 and *IMS Version 9: Application Programming: Design Guide,* SC18-7810.

With IMS Java remote database services provided by IMS Version 9, you can develop a non-z/OS application to access IMS data, that is, IMS database access logic is on non-z/OS platform. See Figure 10-4 on page 171.



non-z/OS platform WebSphere Application Server EJB DB access logic IMS distributed JDBC resource adapter IIOP z/OS WebSphere Application Server for z/OS **IMS Java EJB** IMS JDBC Resource Adapter IMS **ODBA** DL/I DRA **IMS DB**

Figure 10-4 IMS Java remote database services and WebSphere Application Server components

Chapter 10. IMS Java enhancements 171

The EJB, that contains your business logic, and is deployed on WebSphere Application Server on non-z/OS platform, passes database access requests to IMS distributed JDBC resource adapter provided by IMS Version 9 as imsjavaRDS.rar file. This resource adapter contains a type 3 JDBC driver. Then Internet Inter-ORB Protocol (IIOP) is used between WebSphere Application Server for z/OS and WebSphere Application Server running on another platform. IIOP allows the servers to exchange data, which is securely transferred across the internet using the SSL (Secure Sockets Layer). IMS Java-supplied EJB on z/OS side receives the data through IIOP, then passes transaction information to the IMS JDBC resource adapter that is deployed on the z/OS platform. The IMS JDBC resource adapter passes data to ODBA, which uses the DRA.

For system requirements, installing, configuring the servers, and running sample applications, refer to *IMS Version 9: IMS Java Guide and Reference*, SC18-7821.


10.7.1 Remote database services components

IMS Java remote database services is a set of J2EE components that provide remote access to IMS data through IMS ODBA. The client-side and server-side components support retrieval, update, delete, and insert activity to the IMS databases. These requests are sent (transparently to the application) across the network and processed in IMS. This support provides an architected solution that allows EJB applications deployed on Distributed WebSphere Application Server to issue JDBC calls to access IMS Databases.

Client-side component

For the client-side of the connection, IMS Java RDS provides an IMS distributed JDBC resource adapter. To condition the distributed WebSphere Application Server V5.0 server for JDBC access to IMS, the IMS JDBC resource adapter must first be installed. This component contains a type 3 JDBC driver which interprets the JDBC request to access and manipulate the IMS data. A type 3 JDBC driver is defined as a standard net-protocol fully Java technology-enabled driver that translates JDBC API calls into a DBMS-independent net protocol which is then translated to a DBMS protocol by a server.

After it is installed, a J2C Connection Factory instance can be deployed. This is a DataSource object deployed in JNDI (Java Naming and Directory Interface) that can be used to obtain a JDBC 2.0 connection. The DataSource object defines properties that pertain to the actual target data source for the connection. See Figure 10-5 on page 173.






Figure 10-5 Remote database services: client-side components

The Datasource properties consist of:

- Java Naming and Directory Interface (JNDI) name JNDI name in J2C Connection Factories
- DatabaseView name
 Fully qualified name of the DLIDatabaseView subclass
- ► DRA table name

Target IMS system

Host name

Name of the target host or IP Address

Port number

Internet Inter-ORB Protocol (IIOP) port number of the target host WebSphere Application Server z/OS

Once the connection is obtained, then a customer-written application running as an EJB in that distributed server can use the JDBC 2.0 API to access IMS DB data. To the application EJB, JDBC access appears local, that is, the application does not have to be written with any knowledge that network traffic is involved.

Server-side component

For the server-side (IMS side) of the connection, a server EJB is delivered as part of the IMS Java RDS support. This EJB must reside on a WebSphere Application Server for z/OS V5.0 environment because it uses the IMS JDBC resource adapter. The reason for the WebSphere Application Server for z/OS requirement for the IMS JDBC resource adapter is that this environment provides a mechanism to invoke a custom service when the J2EE server is brought up and down. The existing IMS JDBC resource adapter (originally introduced to provide JDBC access from WebSphere Application Server for z/OS - PQ57320 for IMS Version 7) uses the custom service. When the server is brought up, the IMS adapter initializes the ODBA environment and correspondingly terminates it when the server is brought down. As such, once the server is brought up, every application running in the server can use an already initialized ODBA environment. In ODBA environment, and for WebSphere Application Server for z/OS, Resource Recovery Services (RRS) is used, so the RRS component requires the use of the **RRS=Y** in your IMS startup parameters. See Figure 10-6.




Figure 10-6 Remote database services: server-side components

The server EJB that is provided is a stateful session bean that allows it to act as a server-side extension of the client's IMS distributed JDBC resource adapter. The primary responsibility of the server EJB is to maintain the state of a client application with respect to IMS and forward all database requests to the IMS JDBC resource adapter. The server EJB is actually invoked as one of two different types: a container-managed EJB (CM EJB) and a bean-managed EJB (BM EJB).

When the server EJB runs as a container-managed EJB, it supports a client EJB application that has requested global transaction semantics. This means that the client application operates under one transaction context, or unit of work for all its database activity. In this case the distributed J2EE application server has the responsibility for being the coordinator of the global transaction.

On the other hand, when the server EJB runs a a bean-managed EJB, it supports a client EJB application that is using local transaction semantics. Each database connection operates under its own transaction context. When a commit is issued against work done on one connection (database), this does not affect work on another connection. In this scenario, WebSphere Application Server for z/OS becomes the coordinator of the transaction. This is because ODBA requires a transaction context to be present. What really happens is that the BM EJB starts a global transaction context on the server side to communicate with IMS while maintaining the local transaction aspect with respect to the client application's connection.

Client-server interaction

A diagram of the client-server interaction components is shown in Figure 10-7.




Figure 10-7 Client-Server interaction

This figure shows the flow of a request from a client-side EJB application issuing a JDBC call all the way to where it is serviced in IMS. The IMS distributed JDBC resource adapter hides the remote access interaction from the client-side EJB, takes the request and establishes communication with the server EJB on the z/OS platform. All activity is kept within the distributed resource adapter until a JDBC connection statement is executed. At this point, an IIOP connection is established with the server-side EJB. IIOP is a transport mechanism standard that supports seamless interoperation between J2EE distributed objects.

The IMS distributed JDBC resource adapter chooses an EJB type (CM or BM) based on whether or not a transaction context exists. A transaction context exists and a CM EJB will be

created if the client-side EJB application had previously issued a getTransaction() method requesting the use of global transaction semantics. Otherwise, local transaction semantics are used and a BM EJB will be created. Information from the client-side DataSource (DRA name, DLIDatabase View subclass) is also propagated to the EJB. Once the instance of the server-side EJB (CM or BM) is created, a connection to ODBA is requested. This results in the loading of the metadata classes and the allocation of the PSB. Note that the database metadata classes, that are produced by the DLIModel Utility provided through several IMS versions, are stored on the mainframe for use by the IMS JDBC resource adapter. They do not need to be moved to the distributed platforms. Once the connection is established, an indication of success or failure is sent back to the client.

The IMS distributed JDBC resource adapter, on a successful connection indication, creates the Statement object. Once this object is handed to the client EJB, a JDBC query can be executed.

10.7.2 Security

There are several resources that need to be properly secured in an IMS Java remote database services environment.

Access to client-side EJB

In a J2EE environment, the security context (or the identity) on the execution thread is determined by a deployment property of the application component known as "run-as". The run-as value can be one of the following:

- System Identity which specifies that the application component runs as the identity of the server region id.
- Caller Identity which specifies that the application component runs as the identity of its caller.
- Role which specifies that the application component runs as a particular identity that is defined by the administrator in the J2EE server.

Note that run-as values of Caller Identity and Role are not supported in this implementation. For information about run-as options and other security issues, see the WebSphere Application Server information center.

Network security

Secure Socket Layer (SSL) is used to protect the communication between WebSphere Application Server on distributed platforms and WebSphere Application Server on z/OS. The client application which uses the IMS distributed JDBC resource adapter must be deployed with a run-as identity of System. This is currently a requirement for interoperation between a distributed application server and WebSphere Application Server for z/OS. As such, the client application should be protected with restricted access so only authorized users can access it on the distributed platform. Communication between distributed WebSphere Application Server and WebSphere Application Server for z/OS. No support for user ID and password that is provided from either the application or the authentication alias should be protected with restricted access.

There is no support for passing the caller identity of the client application. At this point, the use of SSL and IIOP requires the identity to be switched to "system identity" when communicating between distributed and z/OS application servers.

Security on WebSphere Application Server for z/OS

Security regarding WebSphere Application Server for z/OS can be separated into two topics, server-side EJB and between IMS.

Server-side EJB

The distributed application server propagates the run-as property of the client-side EJB, and, WebSphere Application Server for z/OS places an appropriate security identity on the thread that will be used to access IMS. The server-side EJB defaults to the "run-as" identity value of system, which is the server region ID of WebSphere Application Server for z/OS. You can change the "run-as" property in the deployment descriptor of the server-side EJB before installing it.

Between IMS

The ODBA environment requires a previously verified access control environment element (ACEE), which WebSphere Application Server for z/OS places on the execution thread. ACEE is a control block which is built when a call to RACF or equivalent security product is issued. In the WebSphere Application Server for z/OS environment, the IMS JDBC resource adapter uses Sync-to-Thread processing to ensure that a security context is place on the thread during execution to access an IMS database. This places an ACEE on the execution thread, based on the "run-as" property of the server-side EJB.

10.7.3 Installation steps

There are actions both on the client and the server-side for setting up the IMS Java remote database services.

Client-side steps

On the client side, the imsjavaRDS.rar file that is the IMS distributed JDBC resource adapter is to be installed. After it is installed and before it can be used, a J2C Connection Factory (DataSource) instance needs to be deployed. This is a DataSource object deployed in JNDI that will be used to obtain a JDBC 2.0 connection. It must contain the values for: DRA table name, DLIDataBaseView subclass (that is, metadata classes) name, IIOP port number, and server-side host name.

Additionally, client-side applications can access multiple IMS databases simultaneously by deploying multiple J2C Connection Factory instances or DataSources, each with a unique set of properties specific to an IMS database. Note that it is not actually necessary to deploy multiple DataSource objects to access multiple databases. An application can configure a DataSource instance for access to a particular database after it has been looked up in the JNDI namespace, as opposed to fully configuring the DataSource prior to deployment into JNDI.

Server-side steps

On the server-side, the imsjava91.rar file that is the IMS JDBC resource adapter is to be installed. This needs to be installed in WebSphere Application Server for z/OS V5.0 along with configuring the custom service that allows the ODBA environment to be initialized or terminated when the server comes up or down. The RAR file contains the following:

ra.xml, which is the heart of the rar file. It includes things like which Java classes (located in the jar file) which are to be used for the Connection Factory. The return value will be of type DataSource, and indicates to the installation tool which values must be set, for example, DRA Name, DatabaseView.

- The IMSJdbcCustomService.xml file, which enables and points to a class in the Jar file with custom services, in this case the calling of CIMS INIT and CIMS TALL call. CIMS INIT initializes ODBA thread, and CIMS TALL terminates it.
- The howto.html file, which is a verbose description including steps on how to deploy the rar file.

Then the EAR file named imsjavaRDS.ear that contains the two IMS Java-provided EJBs is to be installed. These two EJBs are stateful session beans and act as server-side extensions of the IMS Distributed JDBC resource adapter.

For more details of installing steps, settings, and running sample applications, refer to *IMS Version 9: IMS Java Guide and Reference*, SC18-7821.

11

Knowledge Based Log Analysis (KBLA)

This chapter discusses the new IMS Version 9 Knowledge Based Log Analysis (KBLA) functions which are supplied as a standard part of the IMS product. KBLA has an ISPF panel driven interface which may be used to invoke existing log and trace utilities as well as several new programs which provide more interpretative and user friendly information. KBLA may significantly reduce the need to reference the utilities manuals and avoid JCL or control statement errors. It should also reduce or eliminate the need to cross reference with control block DSECTS.

This chapter contains the following:

- Invoking KBLA
- A description of the KBLA tasks
- ► KBLA setup
- Supported IMS log utilities
- New IMS log and trace utilities
- Examples of using the new functions

11.1 Overview of KBLA

Knowledge Based Log Analysis is actually a set of tools and utilities to assist with finding and interpreting information about the IMS log or IMS trace data sets. The tedious and error prone process of coding JCL and control cards is replaced with a set of ISPF panels and help text for invoking both the pre existing log utilities and the new KBLA functions. These functions make the task of analyzing log and trace data much easier. Several options are available for formatting the data depending on the level of detail desired.

While KBLA is a valuable tool and part of the IMS Version 9 product it is not considered to be a replacement for the IMS Problem Investigator product which is a separately priced tool. IMSPI provides some similar function but is more interactive in nature.

11.2 Invoking KBLA

KBLA may be invoked by the following TSO command where *hlq* is the high level qualifier for the IMS execution libraries:

```
EX 'hlq.SDFSEXEC(DFSKBSRT)' 'HLQ(hlq)'
```

The above command is also imbedded within the IMS Application menu and may be invoked by selecting option 2 from the menu shown in Figure 11-1.

Help			
IMS Application Menu Command ===> (C) Copyright IBM Corp. 2003. All rights reserved. Select the desired application and press Enter.			
 Single Point of Control (SPOC) Knowledge-Based Log Analysis (KBLA) HALDB Partition Definition Utility (PDU) Syntax Checker for IMS parameters (SC) Installation Verification Program (IVP) IVP Export Utility (IVPEX) IPCS with IMS Dump Formatter (IPCS) 			
To exit the application, press F3.			

Figure 11-1 IMS Application Menu

Selecting option 2 from the IMS Application Menu will take you to the primary KBLA menu shown in Figure 11-2 on page 181.

Knowledge-Based Log Analysis IMS Version 9.1 Command ===>
TIME09:11:20 DATE2004/07/23 JULIAN2004.205 USERIDV993546
Tasks 0. KBLA Environment Maintenance 1. IMS Log Utilities 2. IMS Log Formatting 3. IMS Log Data Set Summary 4. IMS Knowledge-Based Analysis 5. Log Selection
6. User-Supplied Utilities
To Exit the KBLA MAIN menu, press END . For Help place cursor on any field and press PF1 .

Figure 11-2 KBLA primary menu

The following is a list of the Task selections available and a short description of each selection. You may press PF1 on any of the KBLA panels for a more complete description of the task or individual fields.

0. KBLA Environment Maintenance

You will need to go here first to perform some setup functions including required data set names.

1. IMS Log Utilities

Here you will find an interface to various standard IMS log utilities including a new user data scrub utility.

2. IMS Log Formatting

This selection will allow you to extract, search, and format log records using specific criteria.

3. IMS Log Data Set Summary

This option will read the log and provide summary information about the records, timestamps, and so on.

4. Knowledge-Based Analysis

This selection is for a set of tools to process log or trace data and provide usable information for debugging or performance analysis.

5. Log Selection

This function allows you to specify which log data sets to process.

6. User Supplied Utilities

This selection allows you to add your own functions to be initiated from KBLA.

The first time you invoke KBLA you should select Task 0 to perform some setup functions. Selecting task 0 will take you to the KBLA maintenance panel shown in Figure 11-3 on page 182. From there select option 1 to setup the default values to be used for various KBLA functions and fill in the values similar to those shown in Figure 11-4 on page 182.

IMS K.B.L.A Environment Maintenance Command ===>			
Select any of the following subtasks and press ENTER .	TIME12:37:18.05 DATE2004/07/23 JULIAN2004.205		
Subtasks 1. KBLA Default Parameter Maintenance 2. KBLA Create Work Dataset List 3. KBLA View Work Dataset List 4. KBLA Delete Work Datasets			
To Exit the KBLA menu, press END . For Help place cursor on any field and press PF1 .			

Figure 11-3 KBLA Environment Maintenance panel

IMS K.B.L.A Define KBLA Environment Command ===>
Fill out the following variables and press ENTER . JULIAN2004.205
KBLA Loadlib
Verify LOG DSN Exists <u>Y</u> (Y/N) Default: Y Default Output Space Parms: Type <u>CYL</u> Primary <u>100</u> Secondary <u>50</u> Default SLDS Unit
Retain output reports in dataset _ (Y/N) Default: Y JOB JCL statement Y (Y/N) Default: N Route output to alternate system N (Y/N) Default: N Alternate system userid/node /

Figure 11-4 Define KBLA Environment panel

Pressing the enter key with Y selected for the JOB JCL statement will show you the generated JOB statement which you may then edit as appropriate for your installation. After editing and saving your JOB statement you can PF3 back to primary KBLA menu.

11.2.1 KBLA task selection 1 - IMS Log Utilities

If you then select option 1 from the primary KBLA menu previously shown in Figure 11-2 on page 181 you will see the list of utilities shown in Figure 11-5 on page 183. The first six utilities have been in IMS for many years and selecting any of them will take you to another panel where you can enter information which will be filled into the various JCL parameters or control statements as appropriate. Help is available for any of the fields by pressing PF1.

IMS K.B.L.A IMS Log Utilities Command ===>	
Select any of the following subtasks and press ENTER	TIME12:54:00 DATE2004/07/23 JULIAN2004.205
Subtasks 1. IMS Log Transaction Analysis 2. IMS Fast Path Log Analysis 3. IMS Statistical Analysis 4. IMS Log Merge Utility 5. IMS Log Recovery Utility 6. Program Isolation Trace Report 7. IMS Records User Data Scrub	- (DFSISTS0) - (DFSLTMG0) - (DFSULTR0) - (DFSPIRP0)
To Exit the KBLA menu, press END . For Help place cursor on any field and press PF1 .	

Figure 11-5 IMS Log Utilities panel

KBLA IMS Records User Data Scrub

There is one new utility which may be invoked from the IMS Log Utilities panel for IMS Version 9 which is the data scrubbing utility. IMS Records User Data Scrub is a routine that scans all the IMS log and deletes those record parts that may contain sensitive or customer business transaction information without compromising the integrity nor the content of the vital IMS system data. Selecting Subtask 7 will take you to the panel shown in Figure 11-6. Once you have filled in the Input log data set name and the other fields you press enter and it should take you to an edit panel with the JCL to run the job.

```
      DFSKBSRT IMS K.B.L.A. - IMS Records User Data Scrub

      Command ===>

      Fill out the following variables and press ENTER .

      Input IMS Log DSN IMSPSA.IM1B.OLP00
      Cataloged? Y

      IMS Log Version . . . . 9_

      Output DSN Keyword . . IEST1
      Output DSN: VIGUERS.Keyword.KBLA.L.*

      Create a New Log dataset with no User Data. . Y (Y/N)

      Log DSNs were extracted from RECON . . _

      PDS member containing logs . . . . . . _
```

Figure 11-6 IMS Records User Data Scrub panel

In the previous example we selected Y to create an new log data set with the user data removed from specific records. The output of the job will show the records which have had the user data removed. An sample of the summary output is shown in Example 11-1.

Example 11-1 User Data Scrub summary output

```
* IMSPSA.IM1B.SAVEOLDS
*
* RECORDS USER DATA SCRUB
                                     *
                                     *
*
OPTION COPY E=DFSKSCR0
*
DFS707I END OF FILE ON INPUT
#01 RECORDS PROCESSED:
                          384
#03
    RECORDS PROCESSED:
                        2,929
#50 RECORDS PROCESSED:
                       12,120
#5901 RECORDS PROCESSED:
                       1,967
                        1,967
#5903 RECORDS PROCESSED:
#5950 RECORDS PROCESSED:
                        26,917
#67
   RECORDS PROCESSED:
                            0
DFS708I OPTION COMPLETE
DFS703I END OF JOB
```

KBLA option 2.3 was used with the basic formatting option to print a sample log record showing the user data before running the scrub utility in Example 11-2and after running the KBLA user data scrub utility in Example 11-3.

Example 11-2	Input message record	before running scrub

01 RECORD INPUT MSG PREFIX HEADER	MESSAGE QUEUED	DATE/TIME: 20	04-07-28 02:12:17.9	03302 GMT	
00000000 000000 00000020 000020	018C0000 01C18194 38A8F2A1 C9D4F1C2	04000053 04000053 40404040 BB94E081	01669001 C9D4F1C2 38A8F2A1 80000100		*AAM
SYSTEM PREFIX 00000000 000000 00000020 000020		E3D7F0F0 F0F1F9F5 E3D7C3C3 C4404040	00260000 0000000 00000000 00000000	00000000 00000001 E3D7C3C3 C4D6F240	*. A.HTP000195 *WH002005TPCCDTPCCD0
EXTENDED PREFIX HE 00000000 000000	ADER 00108600 00E67400	00000000 00000000			*FW
SECURITY PREFIX 00000000 000000	00168800 E6C8F0F0	F2F0F0F5 40404040	40404040 E400		*H.WH002005 U.
WORK LOAD MANAGER 00000000 000000		BB94E081 38ABF981	0000000 00000000		*IJM.A9A
SYSTEM EXTENSION P 00000000 000000	REFIX 00188A00 2004210F	02121790 3294016D	0000000 00080000		*M
TRANSACTION MANAGE 0000000 00000 0000020 000020 0000040 000040 0000060 000060 00000080 000080		00000000 0000000 0000000 0000000 0000000	E3D7C3C3 C4404040 0000000 0000000 0000000 00001E3 00000910 0000000	E6C8F0F0 F2F0F0F5 0000000 0000000 D7C3C3C4 4040404 0000000 00000000	*TPCCD WH0020 * *TPCCD * *
USER DATA 00000000 000000	00160301 E3D7C3C3	C4404040 E6C8F0F0	F2F04040 F0F3		*TPCCD WH0020 03
RECORD SUFFIX 00000000 000000	BB94E081 38AC6801	00000000 001FB780			*.M.A

Example 11-3	Input message record	after running scrub

01 RECORD INPU	T MESSAGE QUEUED	DATE/TIME: 20	04-07-28 02:12:17.9	03302 GMT			
MSG PREFIX HEADER							
0000000 0000000	018C0000 01C18194	04000053 04000053	01669001 C9D4F1C2	40404040 BB94E081	*AAM	IM1B	.M
00000020 000020	38A8F2A1 C9D4F1C2	40404040 BB94E081	38A8F2A1 80000100	00000000 00000000	*.Y2.IM1B	.M.A.Y2	••••

SYSTEM PREFIX 00000000 000000 00000020 000020	00408100 88000000 E6C8F0F0 F2F0F0F5		00260000 00000000 00000000 00000000	00000000 00000001 E3D7C3C3 C4D6F240	*. A.HTP000195 *WH002005TPCCDTPCCD0
EXTENDED PREFIX H 00000000 000000	EADER 00108600 00E67400	0000000 00000000			*FW
SECURITY PREFIX 00000000 000000	00168800 E6C8F0F0	F2F0F0F5 40404040	40404040 E400		*H.WH002005 U.
WORK LOAD MANAGER 00000000 000000		BB94E081 38ABF981	00000000 00000000		*IJM.A9A
SYSTEM EXTENSION 00000000 000000		02121790 3294016D	00008000 00000000		*M
TRANSACTION MANAG 00000000 000000 0000020 000020 00000040 000040 00000060 000060 00000080 000080	ER PREFIX 00908C00 0000000 0000148 4000000 0000000 0910000 4040404 4040000 0000000 0000000	00000000 0000000 00000000 0000000 00000000 0000000 00000000 0000000 00000000 0000000 00000000 0000000	E3D7C3C3 C4404040 0000000 0000000 0000000 000001E3 00000910 0000000	E6C8F0F0 F2F0F0F5 0000000 0000000 D7C3C3C4 40404040 0000000 00000000	*TPCCD WH0020 *
USER DATA 00000000 000000	60C3D3C5 C1D9C5C4	606E0000 00000000	0000000 0000		*-CLEARED->
RECORD SUFFIX 00000000 000000	BB94E081 38AC6801	00000000 001FB780			*.M.A

11.2.2 KBLA task selection 2 - IMS Log Formatting

Selecting task 2 from the KBLA primary menu will take you to the panel shown in Figure 11-7.

```
      IMS K.B.L.A. - Log Formatting Selections

      Command ===>)

      TIME....13:58:26

      DATE....2004/07/30

      JULIAN..2004.212

      Select any of the following subtasks and press ENTER .

      Subtasks ..._ 1. IMS Resources Formatting

      2. IMS Subcomponent Log Filtering

      3. KBLA Log Record Formatting

      4. IMS Trace Formatting

      4. IMS Trace Formatting

      5. KBLA menu, press END .

      For Help place cursor on any field and press PF1 .
```

Figure 11-7 Log Formatting Selections

The following functions may be selected from the Log Formatting Menu shown above.

- I. IMS Resources Formatting this option allows you to extract information from the log such as input/output messages, transactions scheduled, security violations, and so on based on a specific resource name. There is no need to know the log record type since KBLA formatting routines will determine those automatically.
- 2. IMS Subcomponent Log Filtering allows you to select log records related to a
 particular component of IMS such as DB, TM, FP, and so on. You may select any or all of
 the subcomponents and also filter by a specific resource name if desired.

- 3. KBLA Log Records Formatting provides many options for selection and formatting of the log records. A sample of this selection screen is shown in Figure 11-8.
- 4. IMS Traces Formatting allows you to select specific trace entries to be formatted using the standard DFSERA30 and DFSERA60 exits but also provides enhanced formatting for NODE trace entries.
- 5. Program Isolation Trace Report generates the JCL and control cards to invoke DFSPIRP0 to create the PI trace report.

The subtask selections are well documented with help panels and therefore we will not go into much further detail in this book. However, there is a common field on the first 3 selections which is the Log Formatting type. An example of this field is shown in Figure 11-8. As you can see this field may be B, S, K, or U. The meaning of these options are as follows:

- B basic formatting similar to DFSERA30 for most records but enhanced formatting where the log record is actually broken into multiple sections such as with the 01 input message and the 03 output message record. An example of this is shown in Example 11-4.
- S summary formatting shows only the log record type followed by a short description and then the log sequence number and the date/time. This is shown in Example 11-5 on page 187.
- K this option provides a much more interpretative description of the various log records and makes it easy to identify the important field contents. An example of the K formatting type is shown in Example 11-6 on page 187.
- U the unformatted selection is used to copy all or selected records from the input log file to a separate data set. There is no formatting or printing from this option.

== K.B.L.A. Log Record	Formatting ==
Input IMS Log DSN <u>'IMSPSA.IM1B.SAVEOLD</u>	<u>S'</u> Cataloged? <u>Y</u>
IMS Log Version <u>9</u> Extract Record(s)	(eg. 01 02 5912)
Log Formatting Type <u>B</u> Output DSN Keyword <u>IMSV9</u>	(B,S,K or U)
	Output DSN: VIGUERS.Keyword.KBLA
Optional parameters	
Print /TRA Log Record <u>N</u>	(Y/N)
Print Internal Traces <u>N</u>	(Y/N)
Filter by Keyword <u>DAVE</u>	
(SYSID, PSB, PST, DBD, RBA, BLOCK, USERID,	KEY, OFFSET, UNDO, REDO, DATA)
No. Records to Scan	
No. Records to Skip	
Log DSNs were extracted from RECON.	
PDS member containing logs	

Figure 11-8 KBLA Log Record Formatting menu

Example 11-4	Basic log record	formatting

37 RECORD	SYN	CPOINT PROC	ESSOR LOG	RECORD DAT	TE/TIME:	2004-07-28	02:12:17.	392038 GMT		
00000000	000000	00680000	37380000	00000000	1CBE8118	C9D4F1C2	40404040	00000070	00000734	*A.IM1B
00000020	000020	BB94E080	BBD39505	FFFFCA5B	00000000	00000000	00000000	00000000	00000000	*.MLN\$
00000040	000040	00000000	00000000	00000000	400000C0	00010000	00000005	BB94E080	BBDA6D85	*M
00000060	000060	00000000	001FB6B2							*
59 RECORD	FP :	SUCCESSFUL	SYNCPOINT	RECORD DAT	TE/TIME:	2004-07-28	02:12:17.	392039 GMT		
00000000	000000	00C40000	59370100	00010000	E3D7C3C3	D7404040	2004210F	02121739	2036016D	*.DTPCCP
00000020	000020	4000003A	00010000	00000000	00000004	00010001	00000000	00000000	C9D4F1C2	*IM
00000040	000040	40404040	00000070	00000734	00000000	0000001	0000002	000A0002	00000000	*

00000060 0000002 0000 00000080 000080 E080BBDA 58450 000000A0 0000A0 40404040 BB94E 000000C0 0000C0 001FB6B3	80 AD54AA21 0000002	40404040 BB94E080 00010000 BB94E080	00000000 0000BB94 A86EE986 C9D4F1C2 BBDA7605 00000000	* *
	000000008000000022400000000230000000004004040404040404040	00000000 0000023C	C9D4F1C2 40404040 00000000 00000000 40404040 C9D4F1C2	*KIROBIM1B *K * IM1B IM
	10 04000051 04000051 C2 40404040 BB94E080		40404040 BB94E080 00000000 00000000	*CB
	00 0000000 0000000 FF E2D4C1E2 E3C5D940		00000000 00000001 40404040 40404040	*. A.H *SMASTER
EXTENDED PREFIX HEADER 00000000 000000 00108600 00E67	00 0000000 0000000			*FW
SECURITY PREFIX 00000000 000000 00168800 C4C6E	D4 E3C3D5E3 40404040	40404040 D300		*H.DFSMTCNT L.
WORK LOAD MANAGER PREFIX 00000000 000000 00188900 00000	00 BB94E080 BBC77240	0000000 0000000		*IMG
SYSTEM EXTENSION PREFIX 00000000 000000 00188A00 20042	OF 02121739 1734016D	00000000 00000000		*
TRANSACTION MANAGER PREFIX 0000000 000908C00 00908C00 00000 00000000 00000108 000000 000000 00000040 0000040 00000000 09108 00000060 0000060 4040404 40400 00000080 000080 00000000 000000	00 00000000 0000000 00 00000000 00000000 00 00000000 00000000	00000000 0000000 00000000 000005E2 00000910 00000000	C4C6E2D4 E3C3D5E3 0000000 00000000 D4C1E2E3 C5D94040 0000000 00000000	*SMASTER DFSMTC *SMASTER DFSMTC *SMASTER *
USER DATA 00000000 000000 00410B00 C4C6E 00000020 000020 C3C8C5C4 40604 00000040 000040 15	F3 F2F5F7C9 40D6D5D3 IC6 D9D6D440 C4C6E2D6		D5D6E640 E2E6C9E3 C4C6E2D6 D3D7F0F3	*DFS3257I ONLINE LOG NOW SW *CHED - FROM DFSOLPOO TO DFSOLP *.
RECORD SUFFIX 00000000 000000 BB94E080 BBDCD	A5 0000000 001FB6B5			*.MNV

Example 11-5 Summary log record formatting

OPTION P	RINT E=DFSKBLAS		
43 RECORD	STATUS OF CURRENT OLDS D/S	LSN: 001FB6AB	DATE/TIME: 2004-07-28 02:12:17.391904 UTC
59 RECORD	FP INPUT MESSAGE RECEIVED	LSN: 001FB6AC	DATE/TIME: 2004-07-28 02:12:17.391905 UTC
59 RECORD	FP OUTPUT MESSAGE RECEIVED	LSN: 001FB6AD	DATE/TIME: 2004-07-28 02:12:17.391908 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6AE	DATE/TIME: 2004-07-28 02:12:17.391912 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6AF	DATE/TIME: 2004-07-28 02:12:17.391914 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6B0	DATE/TIME: 2004-07-28 02:12:17.391917 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6B1	DATE/TIME: 2004-07-28 02:12:17.391920 UTC
37 RECORD	SYNCPOINT PROCESSOR LOG RECORD	LSN: 001FB6B2	DATE/TIME: 2004-07-28 02:12:17.392038 UTC
59 RECORD	FP SUCCESSFUL SYNCPOINT RECORD	LSN: 001FB6B3	DATE/TIME: 2004-07-28 02:12:17.392039 UTC
42 RECORD	OLDS SWITCH/CHKPT WAS TAKEN	LSN: 001FB6B4	DATE/TIME: 2004-07-28 02:12:17.392048 UTC
03 RECORD	OUTPUT MESSAGE QUEUED	LSN: 001FB6B5	DATE/TIME: 2004-07-28 02:12:17.392077 UTC
35 RECORD	MSG WAS ENQUEUED/RE-ENQUEUED	LSN: 001FB6B6	DATE/TIME: 2004-07-28 02:12:17.392958 UTC
03 RECORD	OUTPUT MESSAGE QUEUED	LSN: 001FB6B7	DATE/TIME: 2004-07-28 02:12:17.393000 UTC
35 RECORD	MSG WAS ENQUEUED/RE-ENQUEUED	LSN: 001FB6B8	DATE/TIME: 2004-07-28 02:12:17.393006 UTC
31 RECORD	GET UNIQUE (GU) ISSUED FOR MSG	LSN: 001FB6B9	DATE/TIME: 2004-07-28 02:12:17.393332 UTC
59 RECORD	FP INPUT MESSAGE RECEIVED	LSN: 001FB6BA	DATE/TIME: 2004-07-28 02:12:17.395421 UTC
59 RECORD	FP OUTPUT MESSAGE RECEIVED	LSN: 001FB6BB	DATE/TIME: 2004-07-28 02:12:17.395423 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6BC	DATE/TIME: 2004-07-28 02:12:17.395425 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6BD	DATE/TIME: 2004-07-28 02:12:17.395426 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6BE	DATE/TIME: 2004-07-28 02:12:17.395428 UTC
59 RECORD	FP DEDB UPDATED	LSN: 001FB6BF	DATE/TIME: 2004-07-28 02:12:17.395429 UTC

Example 11-6 KBLA interpretative formatting

5950RECORD - FP DEDB UPDATEDPROGNAME: PSBPAAREA NAME: AREAWH01RBA FIRST CI: 00001000VSO/SVSO: ONDMHR BUFF #: 0011DB CHANGE OFFSET: 006BRCVY TOKN: C9D4F1C240404040000007000000734DBD NAME: WAREDBDATE/TIME: 2004-07-28 02:12:17.391920 UTCLOG SEQ NO: 001FB6B1

37 RECORD - IMS SYNCPOINT TRANSFER DESTINATION IS: SMB PST #: 0001 NO INPUT/OUTPUT NO APPC/OTMA MSG RCVY TOKEN: C9D4F1C2404040400000007000000734 DATE/TIME: 2004-07-28 02:12:17.392038 UTC	PCB ADDR: 1CBE8118 LOG SEQ NO: 001FB6B2
5937 RECORD - FP SUCCESSFUL SYNCPNT RECORD	
BATCH APPLICATION	
RCVY TOKN: C9D4F1C2404040400000007000000734	
UOW: C9D4F1C240404040BB94E080A86EE986C9D4F1C240404040	BB94E080AD54AA210000
DATE/TIME: 2004-07-28 02:12:17.392039 UTC	LOG SEQ NO: 001FB6B3
42 RECORD OLDS SWITCH/CHKPT WAS TAKEN	
	RLM NAME/ID: IROBIM1B/01C0
PRILOG 1ST LSN: 0000000001D5F10 PRILOG START TIME	
LOG TIMESTAMP: 2004210F01462576 LOG SWITCH TIME:	
*** CHECKPOINT INFORMATION SECTION **	
CURR. CHKPT ID: 2004210/01560987 CHKPT ZERO ID:	
OLDEST LCRE ID: 2004210/01473201 COLDBASE/COLDCOMM	ID: 0000000/0000000
OLDEST BMP ID: 2004210/01560987 FP CHKPT ID:	
SNAPQ CHKPT ID: 0000000/00000000 DC CHKPT ID:	2004210/01560987
DUMPQ CHKPT ID: 2004208/08052741	
DATE/TIME: 2004-07-28 02:12:17.392048 UTC	LOG SEQ NO: 001FB6B4
03 RECORD OUTPUT MESSAGE QUEUED	
	LTERM/TRAN: SMASTER
	G TIMESTAMP: 2004210 02121662
1ST/CURRENT DRRN: 04000051/04000051	
UOW: C9D4F1C240404040BB94E080BBC5CE60C9D4F1C240404040	BB94F080BBC5CF608000
** SQ MESSAGE - PUT PROCESS *	
DATE/TIME: 2004-07-28 02:12:17.392077 UTC	LOG SEQ NO: 001FB6B5

11.2.3 KBLA task selection 4 - IMS Knowledge Based Analysis

Selecting task 4 from the primary KBLA menu will take you to the menu shown in Figure 11-9.

```
IMS K.B.L.A. - IMS Knowledge Based Analysis

Command ===>

TIME....14:03:10

DATE....2004/07/30

JULIAN..2004.212

Select any of the following subtasks and press ENTER .

Subtasks . . _ 1. IMS Knowledge Based Log Analysis

2. MSC Link Performance Analysis

3. Statistic Log Record Analysis

4. Trace Entry Filtering

5. IRLM Lock Trace Analysis

6. DBCTL Transaction Analysis

7. To Exit the KBLA menu, press END .

For Help place cursor on any field and press PF1 .
```

Figure 11-9 Knowledge Based Analysis menu

11.2.4 IMS KBLA - Log Data Set Analysis

Subtask 1 of KBLA allows you search the log based on specific criteria and also optionally create an output file which is a subset of the input log with only those records matching the processing criteria. The selection panel is shown in Figure 11-10. A very interesting function on this panel is the Create Dynamic Search Keys option. This function will use the selection criteria specified and in addition it will search for related records.

An example would be if you chose to process based on a transaction name and specified the dynamic keys options. In this case a log record would be selected even though the transaction name may not be carried in a particular record but, because the UOW was the same as a prior record, it would be included. The Processing Criteria and Dynamic Search Key option provide some very powerful tools in processing the log.

TMC V D L O Los Date Cat Oralunia
IMS K.B.L.A Log Data Set Analysis Command ===>
Input IMS Log DSN was used
Fill in the following fields and press ENTER .
Input IMS Log DSN <u>'IMSPSA.IM1B.SAVEOLDS'</u> Cataloged? Y
IMS Log Version <u>9</u>
Output DSN Keyword IMSV9 Output DSN: VIGUERS.Keyword.KBLA.R.*
Output DSN Regword <u>INSV9</u> Output DSN: VIGUERS.Regword.RDEA.N.* Output DSN: VIGUERS.Keyword.KBLA.S.*
(Optional) Processing Criteria
Create/Process Subset of log _ (Y/N) A selection panel will be displayed
PGM TRAN DBD AREA
NODE LTERM USER RBA Recovery Token.
UOW
Scan DAVE
Create Dynamic Search Keys _ (Y/N) Output DSN: VIGUERS.Keyword.KBLA.D.*
Log DSNs were extracted from RECON
PDS member containing logs Check LSN Seq _ (Y/N)

Figure 11-10 KBLA Log Data Set Analysis

11.2.5 KBLA MSC Link Performance Formatting


Subtask 2 of KBLA is the MSC Link Performance Formatting function. This program uses the MSC link trace written to the log by the /TRA SET ON LINK n command. Multiple links may be traced and input to the program. Figure 11-11 on page 190 shows the panel used to generate the job to analyze the trace. The output of the formatting program shows a line for each link send or receive containing three different delta times and the actual time that operation completed so that send or receive can be matched against the full trace data for further analysis if necessary.

The delta times are:

- RECV DATA TO ACK This is the number of milliseconds from a receive data trace record until the acknowledgement of that message is sent back to the other system. This time includes queuing of the message to the IMS message queue and a logger CHECKWRITE.
- SEND DATA TO ACK This is the number of milliseconds from when IMS sends a message to another system and receives the acknowledgement that the message has been received and queued on that system. This time includes the time on the physical link.
- SEND CHECK WRITE This is the time from when this link task issued the CHECK WRITE function until it was re-dispatched to continue processing. This time is included in the SEND DATA TO ACK time above. The time here included the actual I/O time (typically to the WADS) and the time until the IMS control task can re-dispatch this unit of work to continue.

If it is possible to run the link trace on the remote systems as well then the two can be compared to determine where any delays may be taking place. At the end of the report is a summary line for each of the links that were traced. If you look at the summary you can see that overall the largest delays were in the SEND DATA TO ACK but that the SEND CHECK WRITE component of that was relatively small. This would tend to indicate the delay was in the physical link processing which after some investigation was found to be the case in this example.

COMMAND ===> == K.B.L.A. MSC Link Performance Formatting ==	
Input IMS Log DSN <u>'IMSPSA.IM1B.SAVEOLDS'</u> IMS Log Version <u>9</u>	Cataloged? <u>Y</u>
Output DSN Keyword <u>IMSV9</u> The Output DSN will be: VIGUERS.keyword.KBLA Log DSNs were extracted from RECON PDS member containing logs	



-	RECV DATA TO ACK (MS)	SEND DATA TO ACK (MS) SEND CHECK WR	RITE (MS)	TIME
SEND FOR ID = EA		69	51	18:44:02.149
RECV FOR ID = EA	9			18:44:02.563
SEND FOR ID = EA		63	7	18:44:02.675
RECV FOR ID = CA	18			18:44:02.695
RECV FOR ID = EA	8			18:44:02.949
RECV FOR ID = AE	6			18:44:03.086
SEND FOR $ID = EA$		57	10	18:44:03.122

Example 11-7 MSC Link Trace Formatti	ום output
--------------------------------------	-----------

SEND FOR $ID = AE$			181	12	18:44:03.546
RECV FOR ID = EA	12				18:44:03.557
RECV FOR $ID = AE$	9				18:44:03.634
RECV FOR $ID = AB$	10				18:44:03.728
SEND FOR $ID = AE$			120	9	18:44:03.789
SEND FOR $ID = EA$			90	22	18:44:03.800
RECV FOR $ID = EA$	7				18:44:03.895
SEND FOR $ID = AE$			110	8	18:44:03.958
•••••					
SEND FOR $ID = EA$			180	13	18:44:04.153
SEND FOR $ID = AE$			179	7	18:44:32.180
RECV FOR $ID = EA$	38				18:44:32.266
SEND FOR $ID = AD$			1,556	45	18:44:32.267
RECV FOR $ID = AE$	14				18:44:32.271
SEND FOR $ID = AB$			15	11	18:44:32.286
RECV FOR ID = DA	36				18:44:32.302
SEND FOR ID = DA			1,552	37	18:44:32.305
SEND FOR ID = AE			152	46	18:44:32.379
DFS707I END OF FILE ON INF					
	• •			SEND CHECK WRITE (MS)	
AE	14	80	121	15	79
EA	12	72	115	15	73
CA	12	13	19	14	5
AB	15	35	27	18	22
BA	13	7	20	12	7
DA	20	36	725	23	37
AD DFS708I OPTION COMPLETE	21	36	715	27	37

11.2.6 KBLA Statistic Log Record Analysis

This function of KBLA will process the x'45' statistics log records written at each IMS checkpoint. Every checkpoint will create a complete set of statistics records with the exception of the /CHE STATISTICS command which will not create the IRLM statistics. The Statistic Log Record Analysis will create a report for each checkpoint interval so there must be at least two checkpoints on the log(s) being input to the program. The panel to create the JCL for this job is very simple and basically just requires the input log data set names as shown in Figure 11-12. An example of the output showing the general information about the checkpoint interval and a sample of the logger statistics is shown in Example 11-8.

COMMAND ===>	
Input IMS Log DSN <u>'IMSPSA.IM1B.SAVEOLDS'</u> IMS Log Version <u>9</u>	Cataloged? <u>Y</u>
Output DSN Keyword <u>IMSV9</u> The Output VIGUERS.key	DSN will be: word KBLA
Log DSNs were extracted from RECON PDS member containing logs	

Figure 11-12 KBLA Statistic Log Record Analysis

STATISTICS	INFORMATION:		
	BEGINNING YE	AR/DAY	2004/210
	BEGINNING TI		2:12:46
	ENDING YEAR/	'DAY	2004/210
	ENDING TIME	(UTC)	2:14:43
	OFFSET TO LO		- 16
	ELAPSED TIME		117.06
	COMPUTE TIME	IN SECONDS	117
	IMS RELEASE		910
	REGION TYPE		ONLINE DB/DC
	IMSID		IM1B
	OPERATING SY	STEM NAME	SC42
	OS PRODUCT		z/OS
	OS VERSION		010500
	FEATURE FLAG	iS	APPC=Y
			ETO=Y
			NOT XRF CAP.
			HSB=N
			NOT XRF SYNC
			NOT RSR CAP.
			SHARED QUEUES
			LSO=S
••••			
LOGGER STAT	ISTICS	#	#/SEC
LOG BLOCK S		26,624	",510
NUMBER OF B		10	
WADS TRACK		4	
NUMBER OF R		54,447	465.35
CHECK WRITE		5,357	45.78
WAIT WRITE		497	4.24
WAIT 4 BUFF		0	.00
WAIT 4 BUFF	NON-CKPT	0	.00
AWE SUBMITT	ED ON WRT	1,632	13.94
WADS EXCPVR	S	3,034	25.93
2K SEGMENT	WRITES	7,735	66.11
OLDS WRITES	j	400	3.41
OLDO MILITED		0	.00
OLDS READS		-	
	KW REQ	13	.11

Example 11-8 Partial output of Statistic Log Record Analysis

11.2.7 KBLA trace entry filtering

Trace entry filtering allows you to extract trace records, which can be on the DFSTRAxx data sets or on the IMS log. In either case you can specify specific search criteria as a filter to locate only those entries related to a specific set of data. Using the panel shown in Figure 11-13, you can set the search criteria to W* meaning any word in the trace table entry and then a specific RBA that you may be concerned with, such as 0075BDE4, which happens to be one of the RBAs in the following lock trace analysis example. This allows you to search for only those entries in the trace which contain that RBA value. An example of the output using this search criteria is shown in Example 11-9 on page 193.

== K.B.L.A. Trace Entry Filtering == COMMAND ===>	
Input IMS Log DSN <u>'IMSPSA.IM1B.SAVELOCK'</u> IMS Log Version <u>9</u>	Cataloged? <u>Y</u>
Trace Table Ids:	
Optional Fields For Trace Records Filtering Start Date/Time (UTC) - (e.g 2004103-13002 Stop Date/Time (UTC) - (e.g 2004103-13002 Records to Skip. - (e.g 2004103-13002 Records to Skip. - Records to Process. Scan Only - Records to Process. Output DSN Keyword. - IMSV9 Log DSNs were extracted from RECON. - PDS member containing logs -	25)

Figure 11-13 KBLA Trace Entry Filtering

Example 11-9 Trace Entry Filtering output

FUNCTION	WORD 0	WORD 1	WORD 2	WORD 3	WORD 4	WORD 5	WORD 6	WORD 7	PAGE 0001
* DLD TRACE	TABLE - DATE	2004210 TI	IME 0213439	11336 OFFS	ET 016D S	KIP 0000 T(TAL SKIP	00000000 RE	CORD NUMBER 8001B958
PSTGTSPC	31059EC2	001855E4	E2C90000	21B5F5E4	0075BDCC	0075BDE4	00110144	00000000	BUSI5UUU
LOCK	C8059EC3	0206001E	1CB41060	00000000	09740580	0456CEC0	0075BDE4	800B01D7	HCP
GRIDU UNC U	CC059ECE	0075BDE4	7F740740	80400302	00000000	00000000	E8366FB4	8001B958	U"Y.?

11.2.8 KBLA IRLM Lock Trace Analysis

The IRLM Lock Trace Analysis panel is shown in Figure 11-14. It uses as input the trace data created by using the command /TRA SET ON TABLE LOCK OPTION LOG. Normally you would allocated separate trace data sets to avoid this trace going to the IMS log since it creates a large amount of data. In this particular example the trace data sets were not available and so the trace data inadvertently went to the OLDS. There may be multiple output reports selected. By default you will get a summary report of the lock contention sorted by both database name and by total wait time for a database. A default detail report will also be generated showing lock contention by the time the request was granted.

The lock trace analysis input panel also allows you to specify that you want to create a separate output data set (also in request granted order) but without the heading lines. This is the create data set with raw output option. You could then use this output data set to process the data in any way you choose. In addition you may also request a report sorted by any of the criteria shown on the panel such as RBA or lock wait time depending on your needs. An sample of the summary report is shown in Example 11-10. A sample of the detail report in the default lock request completion time is shown in Example 11-11 on page 195.

== K.B.L.A. IRLM Lock Trace Analysis == COMMAND ===> Input Trace DSN. <u>'IMSPSA.IM1B.SAVEOLDS'</u> IMS Log Version. <u>9</u> COPY1 DSN. . . . <u>IMSPSA.IM0B.RECON1</u> Cataloged? Y The Output DSN will be: VIGUERS.keyword.S.KBLA.* Create dataset with raw output . . . _ (Y/N) VIGUERS.keyword.R.KBLA.* Raw output sort selection: Sorted by Database Name. . . . <u>N</u> (A/D/N)Sorted by RBA . . (A/D/N). <u>N</u> Sorted by Database Name & RBA. . <u>N</u> (A/D/N) Sorted by PST Number N (A/D/N)Sorted by Wait Elapsed Time. . . \overline{N} (A/D/N) Log DSNs were extracted from RECON . _ PDS member containing logs

Figure 11-14 KBLA IRLM Lock Trace Analysis

Example 11-10 IRLM Lock Trace Analysis summary report

- Suspended IRLM Lock Requests Summary Report - Wait Time Order Page 001 Trace Date = 07/27/2004 Trace Start Time = 22:13:43 Trace End Time = 22:14:15 Trace Elapsed Time (secs) = 31 Trace Input DSN = IMSPSA.IM1B.SAVELOCK

Database	DS	Lock Req	Wait	Not Int	Total	Average	Maximum
Name	Id	Count	Count	Count	Time	Time	Time
DISTDB	01	444	85	85	3.570	0.042	1.54
WAREDB	01	424	167	167	0.991	0.005	0.19
STCKDB	02	1493	755	755	0.895	0.001	0.15
STCKDB	05	1966	811	811	0.766	0.000	0.16
STCKDB	04	1205	622	622	0.602	0.000	0.23
ITEMDB	01	2102	1184	1182	0.529	0.000	0.08
STCKDB	03	1037	395	395	0.487	0.001	0.26
STCKDB	01	501	186	186	0.148	0.000	0.06
ORDRSI	01	965	336	336	0.071	0.000	0.05
ORDLDB	02	292	85	85	0.046	0.000	0.03
NORDDB NOIX ORDLDB CUSTDB ORDRDB CUSTSI HISTDB	01 01 01 01 01 01 01	857 856 172 1126 493 5781 209	438 290 65 475 242 1719 32	438 290 64 466 242 1718 32	0.043 0.024 0.023 0.016 0.016 0.015 0.002	0.000 0.000 0.000 0.000 0.000 0.000	$\begin{array}{c} 0.01 \\ 0.01 \\ 0.00 \\ 0.00 \\ 0.00 \\ 0.00 \\ 0.00 \end{array}$
FP DMY Totals	00	209 424 20347	1 7888	0 7874	0.002 0.000 8.251	0.000	0.00

Example 11-11 IRLM Lock Trace Analysis detail report

Trace Date = 07/27/2004 DSN = IMSPSA.IM1B.SAVELOCK												
Lock Request Lock Request	Wait PSTLoc	(-Resource FlagIRLMCall Tra	ice								
Start Time End Time	Elapsed Type Num Type	v1 DB	DS RBA/HASH S RCFB TRAC Type Num Time Se	eq#								
22:13:43.766 22:13:43.766	0.004 F 001 BIDP	4 CUSTSI	01 03540001 P CPKF 0000 08C0 GN 082 22:13:43.766 95	09								
22:13:43.774 22:13:43.774	0.004 F 001 BIDP	6 CUSTDB	01 0FD04014 P PKF 0000 08C0 GHU 369 22:13:43.774 97	'E6								
22:13:43.783 22:13:43.783	0.004 F 001 BIDP	4 CUSTDB	01 15796000 P CPKF 0000 08C0 REPL 369 22:13:43.783 98	865								
22:13:43.811 22:13:43.811	0.004 F 001 BIDP	4 CUSTSI	01 035E9001 P CPKF 0000 08C0 GN 105 22:13:43.811 99	DA								
22:13:43.887 22:13:43.887	0.004 F 005 BIDP	4 CUSTDB	01 12F4A000 P CPKF 0000 08C0 GU 735 22:13:43.887 9E	6B								
22:13:43.895 22:13:43.895	0.004 F 005 BIDP	6 NORDDB	01 007582D4 P CPKF 0000 08C0 ISRT 469 22:13:43.895 9E	90								
22:13:43.895 22:13:43.895	0.004 F 005 BIDP	6 NORDDB	01 0075BDCC P CPKF 0000 08C0 ISRT 469 22:13:43.895 9E	A6								
22:13:43.895 22:13:43.895	0.004 F 005 BIDP	4 NORDDB	01 00756800 P CPKF 0000 08C0 ISRT 469 22:13:43.895 9E	B4								
22:13:43.895 22:13:43.895	0.004 F 005 BIDP	6 NORDDB	01 0075BDE4 P CPKF 0000 08C0 ISRT 469 22:13:43.895 9E	C3								
22:13:43.895 22:13:43.895	0.004 F 005 BIDP	6 NOIX	01 AC308505 P PKF 0000 08C0 ISRT 469 22:13:43.895 9E	D1								
22:13:43.895 22:13:43.895	0.004 F 005 BIDP	4 NOIX	01 00546001 P CPKF 0000 08C0 ISRT 469 22:13:43.895 9E	EA								
22:13:43.911 22:13:43.911	0.004 F 005 BIDP	6 ORDRDB	01 0065D0E0 P PKF 0000 08C0 ISRT 470 22:13:43.911 9F	18								
22:13:43.911 22:13:43.911	0.004 F 005 BIDP	4 ORDRDB	01 0065D000 P CPKF 0000 08C0 ISRT 470 22:13:43.911 9F	2E								
22:13:43.911 22:13:43.911	0.004 F 005 BIDP	6 ORDRSI	01 638BE1CF P PKF 0000 08C0 ISRT 470 22:13:43.911 9F	3F								
22:13:43.911 22:13:43.911	0.004 F 005 BIDP	4 ORDRSI	01 00C90001 P CPKF 0000 08C0 ISRT 470 22:13:43.911 9F	61								

11.2.9 KBLA DBCTL Transaction Analysis

The DBCTL Transaction Analysis uses information from the IMS log similar to what is reported by the utilities DFSILTA0 and DBFULTA0. It reports on a single line for each transaction both the Full Function information from the x'07' log record and any Fast Path information from the x'5937' log record.

While this program may be run with input from any IMS log it is most meaningful in the case where only one transaction is processed per schedule thus there is one x'07' record for each transaction. This is the case in a DBCTL environment but is usually not so where IMS is the transaction manager.

As you can see from the selection panel shown in Figure 11-15 you may also select the order in which the report is sorted. The default is by program termination time but you may request the order to be any of the fields shown. For instance if you were having a locking problem you might choose to sort the report by Time Waiting for LOCKS. A sample of the output in the default order of program termination is shown in Example 11-12. You may also notice that where some values exceed the length of the report field a > sign will precede the value.


== K.B.L.A. DBCTL Transaction Analysis == COMMAND ===>	
Input IMS Log DSN <u>'IMSPSA.IM1B.SAVEOLDS'</u> IMS Log Version <u>9</u>	_ Cataloged? <u>Y</u>
TransactionSummary ReportSorted by:DLI I/O TimeNNNBA BuffersUsedNPSBNAMEN(A/D/N)SchedulingElapsedNSYNC FailureN(A/D/N)SYNC FailureN(A/D/N)TimeWaiting for DEDBBUFFERM(A/D/N)NTimeWaiting for INTENTNTimeWaiting for POOLSPACESyncFailureNA/D/N)TimeTimeWaiting for CILOCKSN(A/D/N)TimeWaiting for CILOCKN(A/D/N)TimeWaiting for UOWLOCKN(A/D/N)	
Output DSN Keyword <u>IMSV9</u> The Output DSN VIGUERS.keyword	
Log DSNs were extracted from RECON PDS member containing logs	

Figure 11-15 KBLA DBCTL Transaction Analysis

Example 11-12 DBCTL Transaction Analysis output

								- 0.19																	
PSBNAME				SCHED_TIME				DLI		IOT		DEC		DEP	0VF	BWT	NBA	UPD	SDP	CLK		VRD	VDR	VWR	-
	ID	T NBR	SS.T	HH:MM:SS.T	MS	MS	MS	#	#	MS	MS	#	#	#	#	#	#	#	#	#	#	#	#	#	F
DVPOSO	CICSAOR3	D 22	.0	08:02:15.2	1	0	0	2	3	2	0	14	4	0	0	0	9	0	0	0	0	6	0	0	
DVPOSO	CICSAOR3	D 22	.0	08:02:15.2	1	0	0	0	0	0	0	12	2	0	0	0	7	1	0	0	0	5	0	0	
DVPOSO	CICSAOR1	D 12	.0	08:02:15.2	1	0	0	0	0	0	0	24	12	0	0	0	21	7	0	0	0	11	0	1	
DVPOSO	CICSAOR3	D 22	.1	08:02:15.2	0	0	0	0	0	0	0	12	2	0	0	0	7	0	0	0	0	5	0	0	
DVLOSO	CICSAOR3	D 35	.0	08:02:15.3	0	0	0	1	0	0	0	11	3	0	0	0	10	0	0	0	0	8	0	0	
DVPOSO	CICSAOR1	D 12	.1	08:02:15.2	1	0	0	2	1	1	0	30	4	0	0	0	11	2	0	0	0	8	0	0	
DVROSO	CICSAOR2	D 63	.0	08:02:15.3	1	0	0	12	11	9	0	84	21	0	0	0	17	13	0	0	0	22	0	0	
DVAOSO	CICSAOR1	D 12	.1	08:02:15.3	1	0	0	0	0	0	0	22	8	0	0	0	15	3	0	0	0	8	0	0	
DVPOSO	CICSAOR3	D 22	.1	08:02:15.3	1	0	0	2	1	0	0	28	4	0	0	0	9	2	0	0	0	6	0	0	
DVLOSO	CICSAOR2	D 63	.1	08:02:15.3	0	0	0	8	0	0	0	14	4	0	0	0	12	2	0	0	0	8	0	0	
DVPOSO	CICSAOR2	D 63	.0	08:02:15.4	1	0	0	0	0	0	0	12	2	0	0	0	8	1	0	0	0	5	0	0	
DVGOSO	CICSAOR1	D 21	.1	08:02:15.3	1	0	0	16	34	30	0	34	15	0	0	0	23	7	0	0	0	10	0	0	
DVAOSO	CICSAOR3	D 22	.0	08:02:15.4	1	0	0	2	3	2	0	12	3	0	0	0	12	0	0	0	0	10	0	0	U
DVAOSO	CICSAOR3	D 22	.0	08:02:15.4	1	0	0	0	0	0	0	4	1	0	0	0	1	1	0	0	0	0	0	0	
DVEOSO	CICSAOR3	D 35	.2	08:02:15.3	1	0	0	23	66	64	0	61	26	0	0	0	22	11	0	0	0	18	0	1	
DVPOSO	CICSAOR2	D 63	.0	08:02:15.5	1	0	0	0	0	0	0	12	2	0	0	0	8	0	0	0	0	6	0	0	
DVLOSO	CICSAOR1	D 12	.0	08:02:15.5	0	0	0	8	0	0	0	14	4	0	0	0	12	2	0	0	0	8	0	0	
DVAOSO	CICSAOR1	D 21	.1	08:02:15.4	1	0	0	4	3	3	0	47	14	0	0	0	29	8	0	0	0	17	0	0	
DVLOSO	CICSAOR3	D 35	.1	08:02:15.5	0	0	0	8	0	0	0	14	4	0	0	0	12	2	0	0	0	8	0	0	
DVLOSO	CICSAOR2	D 75	1.8	08:02:13.8	1	0	0	935>	999	1376	0	15	3	0	0	0	8	1	0	0	0	6	0	0	
DVROSO	CICSAOR1	D 21	.0	08:02:15.6	1	0	0	0	0	0	0	28	6	0	0	0	17	0	0	0	0	11	0	0	
DVAOSO	CICSAOR3			08:02:15.6	1	0	0	0	0	0	0	22	10	0	0	0	18	3	0	0	0	8	0	0	
DVPOSO	CICSAOR2	D 74	.1	08:02:27.0	1	0	0	0	0	0	0	12	2	0	0	0	7	0	0	0	0	5	0	0	
DVLOSO	CICSAOR2	D 75	.0	08:02:27.1	0	0	0	6	12	8	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
DVPOSO	CICSAOR3	D 22	.0	08:02:27.1	1	0	0	2	2	1	0	32	6	0	0	0	12	2	0	0	0	6	0	0	
DVLOSO	CICSAOR2	D 75	.0	08:02:27.1	1	0	0	2	0	0	0	15	2	0	0	0	10	0	0	0	0	8	0	0	U
DVGOSO	CICSAOR1	D 21	.7	08:02:26.4	1	0	0	20	32	27	659	34	12	0	0	0	20	8	0	0	0	10	0	0	
DVPOSO	CICSAOR1	D 21	.0	08:02:27.2	1	0	0	0	0	0	0	12	2	0	0	0	8	1	0	0	0	6	0	0	
DVEOSO	CICSAOR2			08:02:27.2	1	0	0	0	0	0	0	14	4	0	0	0	13	0	0	0	0	9	0	0	
	END OF FIL	E ON 3	INPUT																						
	F SYNC REC		(593)	7) 132	871																				
	F SYNC FAI		•		425																				
	F SCHD REC		(08)	134																					
	F TERM REC		(07)	134																					
	OPTION COM		()	101	-																				
	END OF JOB																								





12

Miscellaneous enhancements in IMS Version 9

IMS Version 9 contains over 50 enhancements, all of them responding to specific customer requirements. In this chapter we have gathered together the miscellaneous enhancements that haven't been described in their own chapters previously in this book:

- Database Manager enhancements:
 - 12.1.1, "Parallel full function database open option" on page 200
 - 12.1.2, "Miscellaneous HALDB enhancements" on page 200
 - 12.1.3, "Improved message with DB abends" on page 202
 - 12.1.4, "Greater than 32K tape block size for image copies" on page 202
- Transaction Manager enhancements:
 - 12.2.1, "OTMA and APPC /EXIT command support" on page 203
 - 12.2.2, "Message level ACEE aging value for OTMA" on page 204
 - 12.2.3, "OTMA trace table enhancement" on page 206
 - 12.2.4, "DFSYPRX0 pre-routing exit" on page 206
 - 12.2.5, "Input message ZZ protection for OTMA" on page 207
 - 12.2.6, "APPCIOT= in DFSDCxxx for IMS/APPC application time-out" on page 208
 - 12.2.7, "LU type 3 logon option as ETO SLUTYPE1 or 3270P" on page 208
 - 12.2.8, "Notify CQS outage to terminal users" on page 209
 - 12.2.9, "Greater than 255 transaction classes" on page 209
- System manageability enhancements:
 - 12.3.1, "Operational enhancement for FDBR message DFS4172" on page 211
 - 12.3.2, "FDBR virtual storage constraint relief" on page 212
 - 12.3.3, "Independent ARM restart for FDBR" on page 212
 - 12.3.4, "External subsystem resolve-in-doubt notification" on page 213
 - 12.3.5, "Virtual storage constraint relief (VSCR)" on page 215
 - 12.3.6, "Command recognition character (CRC) enhancement" on page 215
 - 12.3.7, "/DIAGNOSE command" on page 217
 - 12.3.8, "IPCS enhancement" on page 219
 - 12.3.9, "Online change copy utility enhancements" on page 220
 - 12.3.10, "Disabling of z/OS DFSMS V1R5 PS EDI" on page 221

12.1 Miscellaneous Database Manager enhancements

In this section we describe the following Database Manager enhancements:

- 12.1.1, "Parallel full function database open option" on page 200
- ► 12.1.2, "Miscellaneous HALDB enhancements" on page 200
- ► 12.1.3, "Improved message with DB abends" on page 202
- ▶ 12.1.4, "Greater than 32K tape block size for image copies" on page 202

12.1.1 Parallel full function database open option

IMS Version 8 introduced the use of parallel DB open. This function is invoked by IMS restarts, /NRE and /ERE. Databases which were open when IMS was last terminated are opened during restart instead of waiting for the first use of the databases.

IMS Version 9 makes the use of this function optional. The NOPDBO control statement in the DFSVSMxx member is used to turn it off. When a NOPDBO statement is used, databases are not authorized, allocated and opened as part of restart processing.

12.1.2 Miscellaneous HALDB enhancements

IMS Version 9 provides also the following HALDB enhancements:

- HALDB specific partition initialization
- DBRC option enhancement for HALDB
- HALDB processing control statement enhancement
- HALDB partition selection exit DSECT enhancement
- HALDB partition selection exit customization enhancement
- HD Unload and Reload utilities (DFSURGU0 and DFSURGL0) are enhanced to generate statistics for each HALDB partition

HALDB specific partition initialization

Originally HALDB partition initialization utilities initialized all of the partitions in a database for which the *partition initialization needed flag* (PINIT) in RECON was set. These utilities are the HALDB partition data set initialization utility (DFSUPNT0) and the database pre reorganization utility (DFSURPR0).

There is one exception. DFSUPNT0 has a capability to initialize all of the partitions in a database without regard to the PINIT flag. This was added to IMS Version 8 by APAR PQ55002 and to IMS Version 7 by APAR PQ49638. It allows a user to initialize all of the partitions in a database without having to issue any DBRC CHANGE.DB commands to change the PINIT flags. This unconditional partition initialization is invoked by including a DFSOVRDS DD statement with an INITALL control statement. When a partition is initialized, the *partition initialization needed* flag is turned off.

IMS Version 9 adds a capability to initialize specific partitions. This is done by specifying the partition name in the control statement for the HALDB Partition Initialization utility (DFSUPNT0).

The control statements for DSFSUPNT0 may include both databases and partitions. For the databases on control statements, the utility initializes only the partitions which have the *partition initialization needed* flag on in the RECONs. For the partitions on control statements, the utility initializes them no matter what the setting is for the PINIT flag.

Example 12-1 is an example of the use of the HALDB partition data set initialization utility (DFSUPNT0) to invoke both specific partition initialization and the former function.

Example 12-1 HALDB partition data set initialization utility (DFSUPNT0)

//PINIT EXE	EC PGM=DFSUPNTO,REGION=2048K
//STEPLIB	DD DSN=IMS.SDFSRESL,DISP=SHR
//DFSRESLB	DD DSN=IMS.SDFSRESL,DISP=SHR
//IMS	DD DSN=IMS.DBDLIB,DISP=SHR
//DFSVSAMP	DD DSN=IMS.DFSVSAMP(PINIT),DISP=SHR
//SYSUDUMP	DD SYSOUT=A
//SYSPRINT	DD SYSOUT=A
//SYSIN	DD *
DBABC011	
DBEFG022	
PAROOAB	
PAR78CD	
/*	

In this example, DBABC011 and DBEFG022 are databases. The utility will initialize only their partitions which have the *partition initialization needed* flag set. PAR00AB and PAR78CD are partitions. The utility will initialize these partitions without regard to their PINIT flags, on or off. In any case, all partitions which are initialized will have their PINIT flags turned off.

There are two ways to execute the HALDB partition data set initialization utility (DFSUPNT0). The example shows the execution as a stand-alone program. That is, the utility is executed with PGM=DFSUPNT0 on the EXEC statement. The utility also may be executed in a ULU utility region. In this case, the EXEC statement has PGM=DFSRRC00 and the PARM list begins with PARM=(ULU,DFSUPNT0,dbname,...) where 'dbname' is the name of a HALDB. This form of execution does not allow one to specify a partition name. It operates on only one database.

DBRC option enhancement for HALDB

DBRC option enhancement for HALDB allows a batch program that references a HALDB to run without DBRC so long as no database calls refer to the HALDB during execution. This provides more flexibility in running a single program in different environments, thus reducing application developer and operations efforts that might be needed to convert programs and ensure their running only in specific environments. This enhancement is also being provided through the IMS Version 7 and IMS Version 8 service process.

HALDB processing control statement enhancement

HALDB processing control statement enhancement increases the number of HALDB single partition processing control statements from 10 to 20 for usability. This allows a customer's application to specify up to 20 DB PCBs that are allowed to perform single partition processing in a HALDB. This enhancement is also being provided through the IMS Version 7 and IMS Version 8 service process.

HALDB partition selection exit DSECT enhancement

HALDB partition selection exit DSECT enhancement allows customers to use the DFSPSEIB macro to get the partition selection exit DSECTs. This makes HALDB with a user-written partition selection exit easier to use. Customers no longer have to create their own DSECTs for the partition selection exit parameters. This enhancement is also being provided through the IMS Version 7 and IMS Version 8 service process.

HALDB partition selection exit customization enhancement

HALDB partition selection exit customization enhancement makes HALDB with a user-written partition selection exit more customizable and easier to use. This allows a partition selection exit to run differently, depending on IMS and the application running. This enhancement is being provided through the IMS Version 9 service process.

HD Unload and Reload utilities statistics

HD Unload and Reload utilities (DFSURGU0 and DFSURGL0) are enhanced to generate statistics for each HALDB partition, previously they had statistics for the entire HALDB database. HD Reload has been enhanced to read partition statistics in the unload file and to support concatenated unload files. This enhancement is also available through the IMS Version 7 and Version 8 service process.

12.1.3 Improved message with DB abends

In previous releases message DFS0832I is issued for HALDB abends, U0880, U3303 and U3498. It is issued prior to abends to indicate which database or partition is affected.

IMS Version 9 also issues this message for some non-HALDB abends, such as U085x. The advantage is that it identifies the database in error. The other error messages associated with these abends, such as DFS554A, do not identify the database. Example 12-2 shows DFS0832I format.

Example 12-2 DFS08321

DFS0832I ABEND UXXXX REASON CODE yyyy <PARTITION DATABASE> zzzzzzzz

The field xxxx shows abend code, yyyy reason code, PARTITION for HALDB, or DATABASE for non-HALDB, zzzzzzz DBD name. If this message is issued for non-HALDB, reason code, which is shown as yyyy, is not applicable. If DBD name is not available, zzzzzzz field is shown as NOTAPPLI which is default value of zzzzzz.

12.1.4 Greater than 32K tape block size for image copies

Large tape block sizes, a capability introduced in OS/390 V2R10 and known as the large block interface (LBI), is supported with IMS Version 9.

When a block size is not specified and a device supporting large tape block sizes is used, or when a block size larger than 32K is specified, the Image Copy utility (DFSUDMP0) will use the large (>32K) block size. This is also supported by the utilities that read the image copies produced by the Image Copy utility. These are the database recovery utility (DFSURDB0) and the Database Recovery Facility product (program number 5655-I44) with PQ79327. It is not supported by Online Image Copy utility or Image Copy 2.

When large tape block sizes are used, image copy issues the following message:

Example 12-3 DFS31851

DFS31851 LARGE BLOCK INTERFACE DETECTED, IT WILL BE USED FOR DDNAME....

This message explains that the image copy utility has determined that the image copy output data set is on a device that supports the large block interface and no explicit block size was specified. 32K tape blocksize support requires the large block interface on 3480 magnetic tape, 3490 and 3490E magnetic tape subsystems, or 3590 devices.

12.2 Miscellaneous Transaction Manager enhancements

In this section we describe the following Transaction manager enhancements:

- ▶ 12.2.1, "OTMA and APPC /EXIT command support" on page 203
- ▶ 12.2.2, "Message level ACEE aging value for OTMA" on page 204
- ▶ 12.2.3, "OTMA trace table enhancement" on page 206
- ► 12.2.4, "DFSYPRX0 pre-routing exit" on page 206
- ▶ 12.2.5, "Input message ZZ protection for OTMA" on page 207
- ► 12.2.6, "APPCIOT= in DFSDCxxx for IMS/APPC application time-out" on page 208
- ▶ 12.2.7, "LU type 3 logon option as ETO SLUTYPE1 or 3270P" on page 208
- 12.2.8, "Notify CQS outage to terminal users" on page 209
- ▶ 12.2.9, "Greater than 255 transaction classes" on page 209

12.2.1 OTMA and APPC /EXIT command support

IMS Version 9 provides /EXIT command support to APPC and OTMA conversational processing.

Releases prior to IMS Version 9 have had an outstanding issue in APPC and OTMA environments for IMS conversational processing. There was no method to end an APPC or OTMA conversation externally. This affected, for example, online change related to that conversational transaction and its related storage. For online change, all conversations need to be terminated beforehand. For the storage, all the related control blocks remain in the storage if the client does not terminate the conversation. If a remote client does not cleanly terminate the IMS conversation such that IMS considers it still active, then all the related control blocks of this "hung" interaction remain in storage. Every time IMS takes a system checkpoint, the control blocks are written to the log. A large number of these types of conversations that hang around indefinitely could potentially impact system checkpoint performance.

The support relied on either the IMS application or the remote APPC or OTMA program to cleanly terminate the conversation. For IMS applications this meant placing a blank transaction code in the SPA. For APPC this meant issuing a DEALLOCATE verb which cleaned up both the APPC conversation and the IMS conversation. For OTMA this meant that the remote program sent a message with the commit-confirmation flag set in the message-control information section of the message prefix (indicating a deallocate flow). If none of the above were done, or if the remote program took a long time in sending the reply then IMS processes such as online change could not complete.

IMS Version 9 introduces new parameters in the /EXIT command that affect active IMS Conversational programming flows in the APPC and OTMA environments:

- /EXIT CONVERSATION conv# LUNAME luname
- /EXIT CONVERSATION conv# TMEMBER tmembername TPIPE tpipename

LUNAME, TMEMBER, and TPIPE are new parameters for the /EXIT command. /EXIT with LUNAME terminates both the APPC conversation and the IMS conversation on the luname specified. /EXIT with TMEMBER and TPIPE terminates the IMS conversation on the tmembername and tpipename combination specified.

Output from the /DISPLAY CONVERSATION command in prior releases did not display information about the OTMA. IMS Version 9 supports an enhancement to the command to display the OTMA information, TMEMBER and TPIPE. The APPC information was supported in the prior releases. This information is necessary for identifying the conversations when issuing the /EXIT command for this environment. Example 12-4 on page 204 shows /EXIT command output.

Example 12-4 /EXIT command output

IEE600I	REPLY TO	597	IS;/DIS	CONV			
DFS000I	TERM	INAL		USER	ID	STATUS	IMSG
DFS000I	HWS9	10G.	7003	JOUK01	0001	ACTIVE	IMSG
DFS000I	*042	11/14	40031*	IMSG			

TMEMBER and TPIPE are displayed on TERMINAL column as HWS910G and 7003.

Note that the /EXIT command enhancements in IMS Version 9 apply to issuing the command from an IMS terminal. Remote programs are not allowed to pass in /EXIT as a target name. This has been true for all previous releases and continues to be true in IMS Version 9. The MQSeries® externalization of a /EXIT is actually trapped by MQ and converted into a commit-confirmation flag to indicate a deallocate flow in the accepted protocol - the /EXIT does not actually flow as a command into IMS.

In an IMSplex environment where there are multiple IMS systems, care should be taken to ensure that the /EXIT command is issued on the correct IMS system that owns the conversation. Additionally, note that for APPC and OTMA, a conversation id is only unique within an IMS system and not necessarily across all the systems in an IMSplex even with sysplex terminal management.

12.2.2 Message level ACEE aging value for OTMA

IMS Version 9 allows the OTMA client to specify an override for the ACEE aging value for any user ID.

When an input message from an OTMA client arrives in IMS, a call to RACF or equivalent security product is issued to build an ACEE control block for the user ID associated with the message. OTMA uses a hash table to maintain pointers to ACEEs so that if the same user ID enters another transaction from the OTMA client, the previously created ACEE is reused. Use of the existing ACEE eliminates a call to RACF. The ACEEs are kept in storage based on a defined aging value that is established at client-bid process in which OTMA client sends client-bid message toward OTMA to connect IMS. The ability to reuse an ACEE rather than create it for every request, is a performance benefit particularly if the same user ID sends in multiple transaction requests.

In prior releases, the aging value was established globally for all user IDs as part of the client-bid process. For more details of client-bid process, see *IMS Version 9: Open Transaction Manager Access Guide and Reference,* SC18-7829. This is still the way to specify the default value in IMS Version 9.

Sometimes, however, it may be necessary to refresh the cached ACEEs during the lifetime of the ACEE aging value, for example, the user ID has been revoked and the ACEE has not yet expired. There are two ways to do this:

- Stop OTMA by /STOP OTMA and restart OTMA by /START OTMA
- ▶ Invoke the enhanced format of the /SECURE OTMA command:

/SECURE OTMA REFRESH [TMEMBER tmembername]

With APARs PQ68350 (IMS Version 7) and PQ66549 (IMS Version 8), the /SECURE OTMA command can request a REFRESH of the cached ACEEs. Issuing the /SEC OTMA REFRESH command without the TMEMBER results in a refresh of all the user IDs for all the OTMA clients. The addition of the TMEMBER parameter with an associated tmembername requests a refresh of the ACEEs associate with just that tmembername.

In both cases, however, the actual ACEE refresh occurs when the next OTMA message for a user ID is received. This is designed to prevent all the RACF ACEE refresh from happening at one time.

IMS Version 9 has enhanced the support in this area to allow for greater granularity on a user ID level. OTMA clients are now able to set an override security ACEE aging value in the OTMA message prefix. For more details of OTMA message prefix, see *IMS Version 9: Open Transaction Manager Access Guide and Reference*, SC18-7829.

There are two fields that support this capability:

- TMAMAGNG in the message-control information section of the OTMA message prefix
 - This is a 4 byte field in byte 20 of the message-control information. The value that can be specified in this field defines an override ACEE aging value for the user ID in seconds. The offset is the same as the existing TMAMCSNS field which stores the sense code and reason code if an OTMA message error is detected.
 - The minimum value for caching support is 300 seconds (5 minutes). If the aging value specified is less than the minimum, IMS always creates a non-cached ACEE.
- TMAMSAGN in the state data section of the OTMA message prefix
 - This is a bit in the TMAMHCFL in byte 5 of the state data, which signifies to OTMA that the aging value in TMAMAGNG is to be used to override the default value.

Both indicators, TMAMAGNG and TMAMSAGN, are reset before the message is enqueued.

Although the ACEE aging value is set, if OTMA does not have security turned on with either a value of CHECK or FULL then the ACEEs are not created or cached in IMS. A refresh of the ACEE is requested in one of the following circumstances:

- Message level aging value specified in the message expires
- New aging value is specified in the message
- Client-bid aging value expires
- /SECURE OTMA REFRESH command is issued
- /STOP and subsequent /START OTMA
- OTMA client disconnect followed by reconnect (client bid)

As documented earlier, the actual ACEE refresh occurs when the next OTMA message for the user ID is received.

When determining a value to specify for the ACEE aging value, a primary consideration involves understanding that it is meant to cache information about the user for the purpose of minimizing I/O to the RACF (or underlying security product) data sets. If a value of zero is used, then ACEE caching is turned off and every message that carries the user ID results in accessing RACF for the information to build the ACEE (this assumes that OTMA security is enabled).

Although OTMA provides the capability for a message level override of the ACEE aging value, it is actually up to the OTMA client to decide whether or not this should be implemented in their environments and, if so, how it should be implemented. For example, IMS Connect already provides access to the OTMA message prefix through its message exits. For an IMS Version 9 environment, a user message exit could easily be modified to set the appropriate flags and fields for the ACEE override. Additionally, the exits could enhance the client interface to optionally allow the client headers to also specify an override value.

12.2.3 OTMA trace table enhancement

New OTMA trace table entries for trace activity in and out of the exits as X'5A05'-X'5A0A' are supported in IMS Version 9.

OTMA supports the creation of new OTMT trace table entries in the effort to standardize OTMA traces and conform to the tracing that is done for other OTMA modules. The existing exit entries do not follow the OTMA table entry standard that is documented in the Diagnosis Guide and Reference manual. This enhancement provides customers and IBM service support personnel with an easier way to check the return code set by the user exits.

Whenever an OTMA user exit is called, an OTMT table trace record is cut to trace the input parameters associated with the exit. After the call to the exit, another OTMT table trace entry is cut to trace the return code set by the exit. This enhancement applies to all the OTMA exit routines, DFSYIOE0, DFSYPRX0, and DFSYDRU0.

- DFSYIOE0 OTMA input output edit exit routine
 - x'5A05' when entering the exit
 - x'5A06' when leaving the exit, word 3 contains the exit RC
- DFSYPRX0 OTMA pre routing exit routine
 - x'5A07' when entering the exit
 - x'5A08' when leaving the exit, word 3 contains the exit RC
- DFSYDRU0 OTMA destination resolution exit routine
 - x'5A09' when entering the exit
 - x'5A0A' when leaving the exit, word 3 contains the exit RC

This now conforms to the way other OTMA modules cut trace entries which are: OTMA module entry (x'5A01') and OTMA module exit (x'5A02').

12.2.4 DFSYPRX0 pre-routing exit

When ALTPCB output destination is created in an OTMA environment, the processing of the message is controlled by whether or not any OTMA exits exist. The OTMA pre-routing exit (DFSYPRX0) routing provides a mechanism to control whether OTMA or IMS TM is called to handle the message. See Figure 12-4 on page 204 for this process.




Figure 12-1 DFSYPRX0 and DFSYDRU0

A second exit routine, the OTMA destination resolution exit (DFSYDRU0) can be further invoked when the destination is an OTMA client. DFSYDRU0 can be coded to specify the target OTMA TMEMBER name, the TPIPE name to be used, and whether a synchronized or non-synchronized TPIPE is to be created.

Over several releases, IMS has provided the capability to define the target TMEMBER and type of TPIPE outside DFSYDRU0. The TMEMBER can be specified as a client override name in DFSYPRX0. The TPIPE type can be specified in an IMS execution parameter OTMASP.

IMS Version 9 adds the ability to specify the target TPIPE name in DFSYPRX0. Prior to Version 9, DFSYPRX0 determines whether ALTPCB message are to be processed by OTMA or non-OTMA destinations, and for OTMA destinations, TMEMBER can be specified by this exit routine. In IMS Version 9, the specification for TPIPE override name in DFSYPRX0 has been added to the end of the input parameter list at offset 84. With this enhancement, the exit routine can specify both the TMEMBER and TPIPE names.

12.2.5 Input message ZZ protection for OTMA

In prior releases, OTMA always zeroed out the values in the ZZ field of the input LLZZ application data. In IMS Version 9, the bit settings are untouched and sent in to IMS. If necessary, OTMA exit DFSYIOE0 which has access to all messages inbound and outbound, can set or modify the value.

This could be important to IMS applications that were originally coded for sensitivity to MFS options. The ZZ field in (non-OTMA) MFS messages contains the MFS formatting option being used to format the messages to and from the IMS application program. Although OTMA

does not invoke MFS, the existing IMS application program may be sensitive to this information and expect to see a value in the field. Remote clients, understanding that they are communicating with a program that looks for this field, can set the bit prior to transmission to IMS.

12.2.6 APPCIOT= in DFSDCxxx for IMS/APPC application time-out

IMS Version 9 adds a second time-out value for APPC to the existing APPCIOT parameter in DFSDCxxx. This new value limits the amount of time an IMS application is inactive and can be used to terminate conversations that appear to be hung. The parameter can be described as follows:

APPCIOT=(xxxx,yyyy)

The first parameter of APPCIOT specifies the APPC time-out value expressed in minutes. This refers to an IMS wait for a requested APPC/MVS service to complete. IMS takes advantage of the ATBSTO5 service to enforce the time-out. Valid values are between 0 and 1440. If APPCIOT is specified as 0, time-out detection is deactivated.

The second parameter is new. This is the APPC/IMS time-out. This refers to an APPC/MVS wait for an IMS process to complete. For example, the timer would begin when IMS receives a message from APPC/MVS and would be reset when another APPC verb is issued, for example, send of a reply, error message or deallocate. This would be similar to putting a time-out value on a queue to queue response. Like the first parameter, valid values are between 0 and 1440. A specification of 0 causes deactivation of the time-out detection capability.

12.2.7 LU type 3 logon option as ETO SLUTYPE1 or 3270P

ETO now allows devices that are defined to VTAM as SLU type 3 (SLU3) to logon to IMS. IMS is not adding a SLU3 device driver, rather, the connection to IMS will be established as either a SLU type 1 (SLU1) or a 3270 Printer (3270P). This action extends what has been used in a static environment for years. The capability eases migration towards the use of ETO for networks that have SLU3 devices.

Specification of how a SLU3 device should connect to IMS is done in the initialization exit routine (DFSINTXO). During IMS initialization, this exit provides a set of flags to define whether SLU3 devices should connect to IMS as either SLUTYPE1 or 3270P. Sample routine is located in IMS.ADFSSMPL. You can specify the flags as follows:

- Parmlist input/output flag byte (+16)
 - X'08'
 - 0: SLU3 not allowed for ETO SLU1 (default)
 - 1: SLU3 allowed to logon as SLU1
 - X'04'
 - 0: SLU3 not allowed for ETO 3270P (default)
 - 1: SLU3 allowed to logon as

The exit should specify one or the other. If, by mistake, both flags are set then this is treated as an error condition and SLU3 devices will not be allowed to logon.

DFSINTXP is a new mapping macro that maps the options for DFSINTX0. It is used by DFSINITX0 and DFSAINB0. IMS ensures that this is only done for ETO environments. Sample is located in IMS.ADFSMAC.

12.2.8 Notify CQS outage to terminal users

In previous releases, if the CQS address space abended, users who tried to connect to IMS would get disconnected immediately after the DFS3649A message was sent. The terminal user was not told what caused the problem.

IMS Version 9 has enhanced the DFS3649A sign-on message for two sets of users. For ETO terminals, the user is signed off and the DFS3649A message includes RC=436. For static non-STSN terminals, the session persists, the user is signed off if already signed on, and RC=436 is included in the DFS3649A message. Other terminal users (static STSN terminals) are not affected by this change. The documentation of RC=436 indicates that CQS is unavailable. You can modify their greeting messages exit routine (DFSGMSG0) to react to the RC=436.

12.2.9 Greater than 255 transaction classes

IMS Version 9 lifts the restriction on the number of transaction scheduling classes that can be specified, from 255 to 999. A maximum specification of 999 was chosen so that command output and output messages in general would not adversely affect existing automation capabilities. It could be affected by a value greater than 3 digits. The following areas are affected:

- System definition
- Dependent region initialization
- Transaction scheduling
- Command processing
- Log records
- IMS control blocks

System definition

In the system definition, the APPLCTN, TRANSACT and IMSCTRL macros have been changed to allow a maximum transaction scheduling class specification of 999. You can specify as follows:

- ► APPLCTN macro, PGMTYPE= (,,999)
- TRANSACT macro, MSGTYPE= (,,999)
- IMSCTRL macro, MAXCLAS= 999

Dependent region initialization

It is also true for the CL1 through CL4 parameters in the DFSMPR and DFSJMP procedures.

Transaction scheduling

Since CPI-C driven transactions are not defined to IMS, the class specification is provided in the associated APPC/MVS TP_Profile entry. The value can now also be specified as 999. An example of this specification in MVS System Data Manager Utility (ATBSDFMU) is shown in Example 12-5. For more information about TP_Profile and ATBSDFMU, see *IMS Version 9: Administration Guide: Transaction Manager*, SC18-7808.

Example 12-5 The specification of TP_Profile in MVS System Data Manager Utility

```
TPADD TPSCHED_EXIT(DFSTPPE0)
TPNAME(INQUIRY_PART)
SYSTEM
ACTIVE(YES)
TPSCHED_DELIMITER(##)
TRANCODE=PART
CLASS=999
```

MAXRGN=1 CPUTIME=0 ##

Command processing

The commands that are affected by the new maximum value are:

- /ASSIGN CLASS
- /ASSIGN TRANSACTION
- /DISPLAY ACTIVE (REGION)
- /DISPLAY STATUS CLASS
- /DISPLAY Q (CLASS)
- ► /DISPLAY TRANSACTION
- ► /PSTOP TRANSACTION CLASS
- ► /PURGE TRANSACTION CLASS
- ► /START CLASS
- ► /STOP CLASS
- ► /START TRANSACTION CLASS
- ► /STOP TRANSACTION CLASS
- QUERY TRAN
- UPDATE TRAN

The /ASSIGN command can be used to specify a new transaction scheduling class value. The /DISPLAY commands display the current transaction scheduling class value. The /PSTOP, /PURGE, QUERY, /START, /STOP, and UPDATE commands can also specify a transaction scheduling class value.

Log records

Two of the log records associated with scheduling have changed. This may affect user programs that are looking at these specific records.

- X'08' log record (Scheduling)
 - LINTSY2 changed to contain new 8-byte PSTCLASS field
 - LINTCLAS (new field) used available storage, class value was previously stored at LINTSY2+4
 - LINTPRTY (new field) used available storage, priority value was previously stored at LINTSY2+5
- X'0A08' log record (CPIC program Scheduling) changed the size of L0ACLASS field to 8 bytes

IMS control blocks

Regarding 999 transaction classes support, 4 IMS control blocks are changed.

SMB (scheduler message block) - IAPS mapping macro

SMBCLASS is moved (offset changed) to reserved field after SMBGUCNT, and changed size to half word.

The size is increased by adding 2 new reserved words before suffix:

- ► Old length of SMB = X'80' (EQU SMBLGTH)
- Old length of SMB plus suffix = X'88' (EQU SMBTOTSZ)
- ► New length of SMB = X'88' (EQU SMBLGTH)
- ► New length of SMB plus suffix = X'90' (EQU SMBTOTSZ)

And, offset changed for field SMBHELM in the suffix.

PST (partition specification table) - IPST mapping macro

PSTCLASS is moved (offset changed) to reserved fields at end of PST, and changed size to double word. No size increases.

TAB (transaction anchor block) - DFSTAB mapping macro

TCTCLAS is moved (offset changed) to reserved field within TCT block, and changed size to half word.

TABPSTQE field is deleted, and made as a reserved field.

The size is increased:

- Old size = X'B7F0' (EQU TABLGTH)
- New size = X'2CEB8' (EQU TABLGTH)

TABCLASS_JAVA_EYECATCHER field is added. Offset of field TABCLASS_JAVA and all TCTs are changed. And TCTN EQU is changed to 999 from 255.

SSOB (subsystem options block) - DFSSSOB mapping macro

SSCTNBA and SSCTOBA are moved to prior location of SSCTCLAS at offset X'58'.

SSCTCLAS is moved (offset changed) to reserved word at offset X'74'. And increased size to 8-bytes, that other 4-bytes are used at prior location of SSCTNBA and SSCTOBA starting at offset X'78'. No size increases.

12.3 Miscellaneous system manageability enhancements

In this section we describe the following system manageability enhancements:

- ▶ 12.3.1, "Operational enhancement for FDBR message DFS4172" on page 211
- 12.3.2, "FDBR virtual storage constraint relief" on page 212
- 12.3.3, "Independent ARM restart for FDBR" on page 212
- ▶ 12.3.4, "External subsystem resolve-in-doubt notification" on page 213
- ▶ 12.3.5, "Virtual storage constraint relief (VSCR)" on page 215
- ▶ 12.3.6, "Command recognition character (CRC) enhancement" on page 215
- ► 12.3.7, "/DIAGNOSE command" on page 217
- 12.3.8, "IPCS enhancement" on page 219
- 12.3.9, "Online change copy utility enhancements" on page 220
- 12.3.10, "Disabling of z/OS DFSMS V1R5 PS EDI" on page 221

12.3.1 Operational enhancement for FDBR message DFS4172

An operational usability enhancement changes the DFS4172 WTOR message to a WTO message so that a reply is not necessary. This message notifies operations when the FDBR tracker is started before the active IMS

Message DFS4172 is issued in the event that FDBR is started but IMS has not yet been started or has not reached the point of joining the FDBR XCF group. Prior to IMS Version 9 this message was issued as a WTOR meaning that action must be taken to reply to this message once the active IMS subsystem has been initialized.

In IMS Version 9 this message is now just a WTO to inform the operator that there is no active IMS to track. Once the active IMS has been started it will join the XCF group already

established by FDBR. This will cause FDBR to be notified that the active IMS is up and it may now start tracking. Operator intervention to allow FDBR to begin tracking is no longer required.

The FDBR system waits for the cross-system coupling facility (XCF) group exit routine to indicate a change in status of a member of the group. That is, the FDBR system waits for the active IMS system to rejoin the group. Use the IRLM MODIFY command (F irImproc,STATUS) to display the status of the identified IMS system. To ensure that the IMS system is active, check that the IMSID specified in the IMSID parameter of the EXEC statement is identical to the IMSID of the active system. Correct any errors and restart, or let ARM restart, the IMS active system. If the IMS system is XRF capable, RSENAME is used for the identifier instead of IMSID, which causes this message and an abend.

12.3.2 FDBR virtual storage constraint relief

For IMS Version 9, IMS can obtain storage for DEDB buffer pools from the IMS private region rather than from ECSA. For the ACTIVE IMSID control statement of the DFSFDRxx member of IMS.PROCLIB, you can specify an optional parameter *FPBUFF=LOCAL* that specifies that the control blocks for Fast Path DEDB processing should be obtained from the FDBR control region private storage instead of from ECSA. This includes the DEDB common buffer pool as well as the SVSO buffer pools.

FDBR in previous releases of IMS built Fast Path module DBFCONT0 in ECSA. DBFCONT0 includes the Fast Path data base buffer pool, SVSO buffer pools, DMACs, DMHRs, OTHRs, and other control blocks. FPBUFF=LOCAL statement in the DFSFDRxx member causes Fast Path to place DBFCONT0 in extended private. Since FDBR typically runs in an LPAR with other IMS subsystems or FDBR instances, this option may allow users to build configurations that ECSA limitations would otherwise prevent. This can mean significant ECSA relief for systems with large Fast Path buffer pools since FDBR must have the same size pool as the active IMS it is tracking. It may also prove very valuable where multiple FDBR subsystems are started on the same LPAR.

If the FPBUFF=LOCAL statement is not included in the DFSFDRxx member, the Fast Path DBFCONT0 module is built in ECSA as with previous releases of IMS.

This enhancement is also available for IMS Version 8 with APAR PQ80264.

Other VSCR for FDBR

Included in IMS Version 9 but also made available in Version 8 (PQ66531) and Version 7 (PQ66507) is additional VSCR for other pools previously obtained in ECSA. The following pools have been moved to EPVT:

- PSBW The PSB work pool
- CSAPSB The CSA portion of the PSB pool
- DMBP The data management block pool
- DBWP The database work pool

Note that this is a change for FDBR only; it has been true for IMS online systems previously.

12.3.3 Independent ARM restart for FDBR

With IMS Version 9, FDBR allows the active IMS and FDBR to be totally independent with respect to the Automatic Restart Manager. Prior to this change either IMS or FDBR could use ARM restart. If ARMRST was specified for FDBR it would disable ARMRST for the active IMS by using an associate function to prevent IMS from possibly restarting before FDBR could

finish its processing causing an integrity exposure. Unfortunately this did not eliminate this possibility since IMS could be restarted by automation.

The code to close this potential exposure also allowed for the independent ARM restart possibility. Now if you specify ARM restart for FDBR the associate will no longer be done and ARM restart will work for both FDBR and IMS if specified at startup.

This change is also available in IMS Version 8 with APAR PQ88094, and in IMS Version 7 with APAR PQ86024.

12.3.4 External subsystem resolve-in-doubt notification

A new external subsystem attach facility (ESAF) indoubt notification exit routine (DFSFIDN0), is provided in IMS Version 9 that allows customers to resolve in-doubt work without waiting for IMS restart to complete. In-doubt work is work that has completed sync point phase 1 (prepare) but has not completed sync point phase 2. This enhancement provides the identity of in-doubt IMS ESAF UOWs to a user notification exit during the recovery phase, thus enabling you to resolve the in-doubt UOW between IMS and external subsystems before IMS and the external subsystem have been reconnected.

The new exit is called for each unresolved unit of work (UOW) during /ERE, XRF takeover and FDBR processing. The action of the exit routine is determined by the user. IMS does not take any action to resolve unresolved units of work. This is the responsibility of the user. The user exit is not called during /ERE COLDBASE or if RRS is the sync point coordinator. IMS retains information necessary to do resolve-in-doubt processing. When IMS again connects to the subsystem, it will do resolve-in-doubt processing for all work that was unresolved when IMS last terminated, regardless of any action taken by the user exit

This capability is especially important for IMS and DB2 data sharing environments using FDBR. When an IMS system fails, FDBR backs out its uncommitted IMS database updates and releases its IMS locks. It does not resolve any in-doubt UOWs with DB2. Normally, this has been done after IMS is restarted and reconnects to DB2. The new exit routine capability allows users to resolve these in-doubts much more quickly.

The FDBR region is a separate address space that monitors an IMS, detects failure, and recovers any IMS-owned database resources that are locked by the failed IMS, making them available for other IMS systems without having to wait for the next full restart. As they scan their collections of IMS units of work for recovery, FDBR and IMS systems determine whether external-subsystem data was also changed as part of each unit of work. If so, they provide all of the following information to a user exit routine:

- Recovery token
- ► The name of the external subsystem that was connected to the failed IMS
- The final resolution of the data

The exit parameter list is mapped by DFSRNID macro in IMS.SDFSMAC. This exit is optional and no sample code is provided by IBM. The name of the exit routine must be DFSFIDN0. The FDBR or IMS system attempts to load the user exit routine from the concatenation of the IMS.SDFSRESL libraries. IMS calls the exit routine once for each in doubt ESAF unit of work. This is a synchronous call to the exit routine, so you should ensure that the exit routine does not impact the performance of the FDBR or the IMS system. For more details about ESAF indoubt notification exit routine (DFSFIDN0), refer to *IMS Version 9: Customization Guide*, SC18-7817.

DB2 has a facility which provides services somewhat similar to FDBR. However, it is implemented differently. The facility is DB2 Restart Light. Unlike FDBR, DB2 Restart Light does not track another subsystem. Instead, it is a special form of DB2 restart. As the name

implies, it uses less resources, including less ECSA, than a normal DB2 restart. It backs out in-flight DB2 updates and releases the associated locks. In DB2 Version 7 it terminated, after this processing. It did not address in-doubt updates. An enhancement in DB2 Version 8 addresses this. DB2 Version 8 Restart Light remains active if there are any in-doubts.

These can be resolved by restarting the partner IMS on the same LPAR. Alternatively, the new IMS exit routine may be used with FDBR or IMS emergency restart. The exit routine may be used to identify whether the in-doubt UOWs should be committed or aborted. This information may be used to issue the -RECOVER INDOUBT command on the DB2 Restart Light instance.

Figure 12-2 is an illustration of a possible interaction of IMS FDBR and DB2 with Restart Light.

At the top of Figure 12-2, there are two systems in the Parallel Sysplex. Both systems have an active IMS and an active DB2. Both IMS systems have a tracking FDBR on the other system.




Figure 12-2 FDBR DB2 in-doubt UOW

In the middle of Figure 12-2, system A fails. This invokes FDBR A which was tracking IMS A. FDBR A releases IMS locks held by IMS A. This makes this data available to IMS A. FDBR A completes before DB2 Restart Light for DB2 A can be started. FDBR A externalizes information about the in-doubt DB2 UOWs. This could be writing records to a file, sending messages via MQ, or some other method. One should be careful that the release of IMS locks by FDBR is not delayed. The exit routine is called for each unresolved UOW before any back outs are done or any locks are released.

At the bottom of Figure 12-2, DB2 Restart Light is invoked for DB2 A. The -RECOVER INDOUBT commands are issued using the saved information from the FDBR exit routine. This releases the DB2 locks and makes this data available to DB2 B.

12.3.5 Virtual storage constraint relief (VSCR)

The VSCR enhancement ensures that the data set association blocks (DSABs) generated are allocated in above-the-line private storage, thereby providing enhanced virtual storage constraint relief. For example, if you have 20,000 full function and/or Fast Path data sets dynamically allocated, you could have over one megabyte of storage allocated above the line. Approximately 20 online change modules moved from below-the-line private to above-the-line private. Also the online change modules are removed from the nucleus and become standalone modules.

IMS systems moving from IMS Version 7 to IMS Version 9 will see a savings in CSA of 48K or 112K depending on whether the environment includes Fast Path. An additional amount of savings can be calculated based on the number of log buffers and whether single or dual logging is used. This is further documented in the redbook *IMS Version 8 Implementation Guide - A Technical Introduction of the New Features,* SG24-6594, which can be downloaded from the following URL:

http://www.ibm.com/redbooks/

IMS systems moving from IMS Version 8 to IMS Version 9 will see a decrease in CSA usage below the line. This is due primarily to several modules being moved from 24-bit to 31-bit addressing.

CSA to ECSA

Load modules moved from 24-bit to 31-bit addressing

► PVT to EPVT

Control blocks associated with dynamically allocated data sets

ECSA to EPVT

DEDB storage in an FDBR environment

The size of the control blocks associated with dynamically allocated databases is 96 bytes per dataset. For full function datasets the storage is moved from DLISAS PVT to EPVT, and for Fast Path, from IMS control region PVT to EPVT. Databases allocated via JCL maintain their DSABs in the PVT storage of the appropriate address space.

12.3.6 Command recognition character (CRC) enhancement

If all subsystems executing in a sysplex have a unique command recognition character, then an operator can enter a command from any system in a sysplex, and route that command to the appropriate subsystem for execution. For this to be operational, all subsystems must register their characters. The z/OS group requested that all subsystems cooperate in this endeavor.

During control region initialization, after all input parameters have been processed, the z/OS command prefix facility (CPF) macro is issued to register the IMS command recognition character (or command prefix) within the system.

The intention is to have all the IMSs on a system register a unique CRC. This gives the console operator the capability to issue a command from any system in the sysplex and direct it to the appropriate system for execution. If the character is not unique, IMS issues the following message but continues on through its initialization process:

DFS1946W IMS CRC OF 'x' ALREADY EXISTS WITHIN SYSTEM OR SYSPLEX

However, note that IMS checks this only to see if it is unique within a system, not across the sysplex, in spite of what the text of the DFS1946W might imply and the explanation in the *IMS*

Version 9: Messages and Codes Volume 2, GC18-7828 explicitly states. This is done intentionally since you may want to have the same CRC on different LPARs in the same sysplex, because it allows a single command to be processed by all the subsystems having the same CRC.

A DISPLAY OPDATA -command on the z/OS console shows you all recognition commands used on your environment, refer to Example 12-6.

Example I	2-0 2/03 D	ISFLAT OFL	ATA COMINA	anu anu ns	response	
SDSF OPERI	LOG DATE 08	3/02/2004	14 WTORS		66 RES	
COMMAND IN	NPUT ===> /[) OPDATA			S	
RESPONSE=S	SC42					
IEE603I 🗄	13.58.03 OPE	DATA DISPLAY	861			
PREFIX	OWNER	SYSTEM	SCOPE	REMOVE	FAILDSP	
\$	JES2	SC47	SYSTEM	NO	SYSPURGE	
-MQFI	MQFI					
-MQFN	MQFN					
-MQJ1	MQJ1					
-MQJ2	MQJ2					
-MQ4B	MQ4B					
-MQ4D	MQ4D					
-DBD8	DBD8MSTR	SC54	SYSPLEX	NO	SYSPURGE	
-DB4B	DB4BMSTR	SC48	SYSPLEX	NO	SYSPURGE	
-DB4C	DB4CMSTR	SC50	SYSPLEX	NO	SYSPURGE	
-DB4D	DB4DMSTR	SC52	SYSPLEX	NO	SYSPURGE	
-DB7A	DB7AMSTR	SC53	SYSPLEX	NO	SYSPURGE	
-DB7C	DB7CMSTR	SC47	SYSPLEX	NO	SYSPURGE	
/	IMSG	SC53	SYSTEM	NO	PURGE	
?	IM2B	SC47	SYSTEM	NO	PURGE	
?	IM1B	SC42	SYSTEM	NO	PURGE	

Example 12-6 z/OS DISPLAY OPDATA command and its' response

The CRC can be used on the SDFS screen for example /?DIS A which returns the status of the IM1B if you are on SC42 console without using the reply number. In our case, if we had used ROUTE *ALL with the command, we would have gotten the response also from IM2B system on SC47.

Example 12-7 /?DIS A example

SDSF OPERLOG DATE O	8/02/20	04 14 W	TORS	COMM	AND ISSUED	
COMMAND INPUT ===> /	DIS A?				SCROLL ===> CS	SR
RESPONSE=SC42						
DFS4444I DISPLAY FR	DM ID=I	M1B				
REGID JOBNAME	ТҮРЕ	TRAN/STEP	PROGRAM	STATUS	CLASS	
2 MPP1BSL	ТР	TPCCS	PSBSL	WAIT-INPUT	5	
4 MPP1BDE	TP	TPCCD	PSBDE	WAIT-INPUT	4	
3 MPP1BOS	TP			WAITING	3	
JMPRGN	JMP	NONE				
JBPRGN	JBP	NONE				
BATCHREG	BMP	NONE				
1 IFP1BPA	FPM	NO MSG.	PSBPA			
5 IFP1BNO	FPM	NO MSG.	PSBNO			
DBTRGN	DBT	NONE				
IM1BDBRC	DBRC					
IM1BDLS	DLS					
VTAM ACB OPEN		-LOGONS	ENABLED			

12.3.7 /DIAGNOSE command

Customers want the ability to obtain IMS diagnostic information without impacting operations. Currently, a console dump is required to gather the basic information necessary to analyze many types of ordinary problems, such as hung terminals or transactions. Even the simple verification of configuration, system generation, or startup information in key control blocks may require a dump. Taking a console dump in an IMS production environment, especially during peak hours, is a disruptive process, and many customers are forced to schedule dumps during an off-peak period or are prevented from taking dumps at all in their production environment.

This enhancement answers a long-standing requirement in the problem determination area. For prior releases, when the IBM support center, needed information to analyze a problem, oftentimes a console dump was requested. Unfortunately, taking a console dump in an IMS production environment, especially during peak hours, was considered a disruptive process that could potentially have a negative impact on operations, service level agreements, and financial goals.

The new **/DIAGNOSE** command in IMS Version 9 provides customers with a built-in, nondisruptive alternative to the console dump for gathering the required information. Additionally, the information produced is in a much more compact form than a console dump which will allow for easier transmission to the IBM support center, when necessary, and will allow IBM service to respond more quickly to problems.

The new **/DIAGNOSE** command operates like a standard type-1 command. An operational consideration is that the OLDS needs to be switched to extract logged data. The command output can also be directed to the external trace data se by using the OPTION(TRACE) keyword with the command. OPTION(OLDS) is the default and it directs the output to the online log data set.

IMS Version 9 supports the following control blocks: ALL, CMDE, ESCD, LSCD, MWA, QSCD, SCD, SQM, TSCD. /DIAG is a new type-1 command, and it logs IMS resource data to the OLDS as type X'6701' records. It uses existing log record mapping and facilities, and allows users to take a snap shot of IMS resources. The command itself is also logged as a X'02' record

This command can be issued from an IMS terminal, a console WTOR, APPC and OTMA clients, an AOI program, MCS/EMCS consoles, and any OM command clients including SPOC.

The SNAP function of the command captures storage, both addresses and raw data, for the requested IMS control blocks, NODEs and transactions. The information in the blocks is copied to a copy storage area to avoid holding enqueues, locks, latches, etc. The environment is further protected by a separate ESTAE that both protects the copy process and prevents an IMS failure. The information is written to the OLDS. A successful completion of the command returns a DFS058I message.

When requesting the SNAP function against the BLOCK resource, at least one control block name is required. The Example 12-8 lists all the valid names that can be requested. Specifying "ALL" results in capturing the information associated with one control block of each type mentioned in the list.

When requesting a SNAP of a specific transaction, the Scheduler Message Block (SMB) is captured. The SMB is the control block that contains information relative to a transaction.

Example 12-8 /Diagnose keywords

•

ALL	Capture all control blocks
CMDE	IMS Commands SCD Extension
ESCD	Extended System Contents Directory
LSCD	LU 6.2(APPC) SCD Extension
MWA	Modify Command Work Area (between
	/MOD prepare and /MOD commit)
QSCD	Queue Manager SCD Extension
SCD	System Contents Directory
SQM	Shared Queue Master Control Block
TSCD	OTMA SCD Extension
NODE(nodename)	
TRAN (tranname)	
LTERM(ltermname)	
USER(username)	
ADDRESS(address)	
LENGTH(length) Key(0	7)

Since this is a new command, the implementation has some potential considerations. If command security is desired, then changes may need to be made to both the RACF definitions as well as the DFSCCMD0 command authorization user exit.

Note: The command is invalid in an XRF alternate environment. It cannot be entered on the alternate nor is it processed by the alternate if the command is entered on the active system.

Command security is achieved by using on or more of the following:

- RACF CIMS definitions
 - Add DIAGNOSE command to RDEFINE for CIMS
- DFSCCMD0 command authorization user exit
- OM security user exit
- RACF OPERCMDS class for OM

It is supported on a RSR environment on RLT and DLT remote trackers.

In an IMSplex environment that uses the Resource Manager, the status recovery mode for USER and NODE resources can be defined as local, global or none. This is specified in the SRMDEF parameter of DFSDCxxx.

If specified as GLOBAL, the significant status of a resource is saved globally in the Coupling Facility resource structure every time the significant status changes, along with all other recoverable status for that resource. The resource status is restored at the next logon or sign on and is available from any IMS system in the IMSplex. The resource status is copied to the local system when that resource becomes active, but is deleted from the local system when it becomes inactive.

The use of the **/DIAGNOSE** command in this environment can therefore result in capturing the terminal control blocks from another system.

Use of the command is documented in the bullets below. Note that since the x'6701' log record is used with no change to the mapping of the record, the existing DFSERA10 batch job can be used to extract the information. The extracted information is what should be sent to the IBM support center when requested.

1. Issue command

- 2. Switch the OLDS
- 3. Extract the information using DFSERA10 (batch job)
- 4. Transmit to IBM support center:
 - a. Cut and paste in PMR
 - b. FAX
 - c. E-mail

12.3.8 IPCS enhancement

In IMS Version 9 the Interactive Problem Control System (IPCS) is enhanced with the Enhanced Dump Analysis (EDA). The EDA tool provides an alternative way to assist you in reducing the time spent on dump analysis.

OPTION ===> _	IMS ENHANCED DUMP FORMATTING MEN	J						
1 BROWSE	- Browse dump dataset (IPCS norm)	*****						
2 DB	- Full Function Data Base	*USERID - JOUKO3						
3 FP	- Fast Path Data Base	*DATE - 04/08/18						
4 TM	- Transaction Management and DC *JULIAN - 04.231							
5 SYS	- Systems	*TIME - 20:14						
T TUTORIAL	- IMS Dump Formatter Tutorial	*PREFIX - JOUKO3						
X EXIT	- Exit EDA dump formatting menu	*TERMINAL- 3278						
		*PF KEYS -						

Enter END or	RETURN command to terminate IMS compone	ent formatting.						

Figure 12-3 IPCS EDA select panel

In the EDA primary menu you can select the different parts of IMS like DB, FP, TM, and SYS as shown in Figure 12-3. Each one shows you the possible sub selection list like PST for DB. This is not really new since we have been able to select PSTs from the previous IMS versions as well, but the filter option is new. If you select this option and press enter the panel as shown in Figure 12-4 appears.

		GENERIC	FILTERING PANEL
Length (def Cond (def Bit (def Type (def	uired) ault = 1) ault = EQ) ault = N) ault = X) uired)	- Offset - Length - Type of - Should - Is the - Value of - Qualifi - How to only th	of the field in the block. (hex) of field in the control block. (decimal) f compare to be done. (EQ,NE,GT,GE,LT,LE) comparison be a bit mask? (Y or N) value type decimal, hex, or char (D,X,A)? of the field to be compared at given offset. y filter to search in sub-blocks. combine multiple conditions. If blank, he first condition will be executed. 4 conditions allowed)
Offset Length	Cond Bit	Type	Value
0064 1 1 1 1	EQ Y EQ N EQ N EQ N EQ N	X X X X	10

Figure 12-4 Filter option

Place an S to the left of the desired low level formatting option(s) and fill in the associated argument. If you omit the argument for an option marked *P* you will be given a sub-list of selectable items for the option. Enter UP/DOWN to scroll or END to cancel the request.

Filtering provides a powerful method of finding only the blocks that you are interested in. Instead of manually searching through many blocks for the few blocks that you might be interested in, you can create a simple boolean expression (with the help of the filtering panel) to search for those blocks for you. Multiple boolean expressions are supported, as well as something called a qualifier. Qualifiers allow the user to filter with fields in a sub-block. For example, if block A has a sub-block B, you can use the qualifier to filter through fields in block B. The result will show all blocks A with the corresponding B blocks, that match the filter criteria for block B.

Let's start from the top and move our way down. The first two fields (AND/OR and QUAL) are global parameters. The AND/OR option is an optional parameter, but is required when defining more than one boolean statement. If this field is left blank, only the top boolean statement will be executed. Furthermore, in combining these statements, they are either all ANDed or all ORed. The QUAL field is the qualifier. For EPSTs, if the DMHR or XCRB was not selected from the previous panel, they may be typed in here.

Now to making the actual boolean statements. As shown above, the default values are already filled in for you. OFFSET is a required field that is the location in the block of the field you want to filter on. LENGTH is how long from that offset you want to compare values. COND is how you want to compare the value at the offset. BIT can be set to enable bit comparisons. TYPE is the type of the VALUE field. VALUE is a required field containing the value to compare to. Example: OFFSET=2F, LENGTH=1, COND=NE, BIT=N, TYPE=X, VALUE=00. This would mean you are searching for all blocks, that at offset 2F have a non-zero value.

12.3.9 Online change copy utility enhancements

The online change copy utility (DFSUOCU0) calls IEBCOPY to perform the copying of members between online change data sets. There have been times, especially when copying a large number of members, that the utility has failed because of inadequate default execution values.

The online change utility is enhanced to override IEBCOPY parameter values. This is a means to ensure that the utility runs to successful completion.

The IEBCOPY utility override parameters that can be specified in the online change utility include: WORK=, SIZE=, LIST=. These parameters are optional and positional and added as the 4th - 6th parameter in the OLCUTL procedure. If one or more are specified, the following combinations are valid:

- WORK=
- ► WORK=, SIZE=
- ▶ WORK=, SIZE=, LIST=

WORK=(n | nK | nM | 1M) specifies the number of bytes of virtual storage to request for a work area to hold directory entries, internal tables, and I/O buffers. The default request will be for 1M. The actual amount obtained will not exceed the space available in the REGION.

SIZE=(n | nK | nM) specifies the maximum number of bytes of virtual storage that IEBCOPY may use as a buffer. It is best to let IEBCOPY choose buffer sizes by not using this parameter. The minimum buffer size is approximately 4 times the largest track size of the devices being used, plus about 3%. There is no maximum for this value, but IEBCOPY cannot use more than the quantity available in the work area.

LIST=(NOIYES) is optional parameter that passes the list parameter to the IEBCOPY utility. LIST=NO suppresses IEBCOPY IEB154I messages that are issued for each member that is successfully copied. The default value is YES. This parameter can only be specified if the work and size parameters are also specified.

The IEBCOPY options list may not exceed 64 bytes. This count includes: the IEBCOPY keywords, equal signs, parameter values, and commas. If exceeded, the following error message is issued:

DFS3486 IEBCOPY PARAMETER ERROR

This error is occurred, for example, when length of the IEBCOPY options list exceeds 64 bytes, or one or more IEBCOPY parameters are specified on the PROC and EXEC statements but not specified as input parameters. The IEBCOPY parameters are passed to IEBCOPY when it is called.

12.3.10 Disabling of z/OS DFSMS V1R5 PS EDI


Physical Sequential Enhanced Data Integrity (PS EDI) is a data integrity function which is introduced newly in z/OS DFSMS V1R5. PS EDI prevents two programs from writing to the same physical sequential data set at the same time. It does this by preventing two programs from opening the data set concurrently if the data set is DSORG=PS, allocated with DISP=SHR, and opened for output or update. This check is for all programs in the same LPAR and in different LPARs in the same sysplex.

PS EDI is optional in z/OS DFSMS V1R5. PS EDI is invoked by the IFGPSEDI member of SYS1.PARMLIB. An installation may set it to a warning level (WARN mode). With this level, opens are not prevented but warning messages are issued. An installation may set it to an enforcement level (ENFORCE mode). With this level, opens are prevented.

IMS OSAM data sets are DSORG=PS, but IMS does not need this protection for database data sets, because DBRC authorization processing prevents concurrent up daters of these data sets unless data sharing is being used with IRLMs. If data sharing is used, IRLM lock processing provides the required integrity.

In addition to OSAM data sets, there are other data sets that must be opened for update by multiple IMS systems. When XRF is used both the active and the alternate must have the OLDS, WADS, RDS, and MSDB dump data sets open for update concurrently. When takeover occurs, the alternate must have write capabilities for these data sets. So, IMS also disables PS EDI for these data sets when XRF is used.

DFSMS allows authorized programs running in keys 0-7 to disable PS EDI. IMS disables PS EDI for OSAM database data sets and the mentioned system data sets, by setting a bit in the DCBE (DCBEEXPS) for the data set. The APARs supplying this function are PQ83940 for IMS Version 9, PQ83941 for IMS Version 8, and PQ83942 for IMS Version 7. There is no user specification. PS EDI is invoked and is an excellent facility for other IMS data sets, such as logs.



13

Migration and coexistence considerations

This chapter provides information about migration and coexistence steps you need to consider if migrating from a supported IMS release to IMS Version 9. Migration tasks such as applying the RECON coexistence code to the previous version is discussed.

- Supported migration paths
- Supported connections and required maintenance
- Migration tasks and coexistence considerations
- RECON upgrade

13.1 Supported migration paths

I

Minimum software level prerequisites for z/OS are z/OS V1R4 (5694-A01) with the IBM High-Level Assembler Toolkit (program number 5696-234).

If you use RACF for security, z/OS V1.6 is needed for new RACF security classes IIMS, JIMS, LIMS, MIMS as default classes. These classes can be defined manually with z/OS V1.4 and higher. See 6.2, "Resource access security (RAS)" on page 86 describing the new security classes.

When IMS recognizes it is running on a z/OS 1.5 or later system, it will ensure that DSAB blocks created as part of the allocations for FF or FP databases, will be above the line.

13.2 Supported connections and required maintenance

Here we provide the list of the minimum requirements for coexisting systems. Check the PSP bucket for the latest maintenance information.

- ISC is supported with
 - IMS Version 9, Version 8 and Version 7
 - CICS Transaction Server for z/OS Version 2 (program number 5697-E93)
 - CICS Transaction Server for OS/390 Version 1 (program number 5655-147)
 - CICS/ESA®(R) Version 4 (program number 5655-018)
 - User-written software
- DB2 connections are supported with
 - DB2 Universal Database for OS/390 Version 6 (program number 5645-DB2)
 - DB2 for z/OS and OS/390 Version 7 (program number 5675-DB2)
 - DB2 UDB for z/OS Version 8 (program number 5625-DB2)
- DBCTL connections are supported with
 - CICS Transaction Server for z/OS Version 2 (program number 5697-E93)
 - CICS Transaction Server for OS/390 Version 1 (program number 5655-147)
 - CICS/ESA Version 4 (program number 5655-018)
- MSC is supported with
 - IMS Version 8
 - IMS Version 7 (PQ32932, PQ58631)
- Shared queues is supported with
 - IMS Version 8
 - IMS Version 7 (PQ32932, PQ54585, PQ58631)

Compatibility APARs are required for IMS Version 7 users during the migration to IMS Version 9. These are required for MSC support between the two versions, or the use of shared message queues, or the Queue Control Facility.

- Control Center support for IMS Version 9
 - DB2 Universal Database Version 8, with fix pack 5 or later
 - IMS Connect Version 1.2 or later, you must have APARs PQ62379 and PQ70216 installed.
 - IMS Version 9 provides an integrated IMS Connect function; make sure that the Connect function is installed and configured on your system.
- IMS Java RDS

- Client
 - Distributed WebSphere Application Server V5.0.2
- z/OS
 - IMS Version 9
 - z/OS V1.4 or later
 - WebSphere Application Server for z/OS Version 5.0.2.3 or later. If you have WebSphere Application Server for z/OS V5.0.2, you must install either V5.0.2.1 or apply APAR PQ81944.
 - WebSphere Application Server V5.0.2.2 with cumulative fixes that include PQ79485, or WebSphere Application Server V5.0.2.3 or later.
 - IBM SDK for z/OS Java 2 Technology Edition V.3 IBM SDK for z/OS Java 2 Technology Edition, Version 1.3.1 or later
- The following protocols and z/OS components are required:
 - RRS (resource recovery services) for z/OS
 - RACF or equivalent product
- The following IMS components are required:
 - ODBA
 - DRA

To use IMS Java remote database services to access IMS databases from applications that run on WebSphere Application Server on a non-z/OS platform, you must download IMS Java files from the IMS Java Web site. These files are required in addition to the files that are installed as part of the SMP/E installation of the IMS Java FMID.

To download the required IMS Java files, go to the IMS Web site at:

http://www.ibm.com/ims

and link to the IMS Java Web page for more information. The download page contains the required files for remote database services as well as the installation verification program and two sample applications for remote database services.

- JDBC access to IMS DB
 - DB2 stored procedures
 - Minimum of DB2 for z/OS and OS/390 Version 7 (APARs PQ46673 and PQ50443)
 - DB2 SQLJ/JDBC driver with APAR PQ48383
 - CICS applications
 - Minimum of CICS Transaction Server for z/OS Version 2
 - WebSphere applications
 - WebSphere Application Server (WAS) z/OS V4.0.1, and additional WAS z/OS Connection Management support
- DB2 access from an IMS JMP or JBP region
 - Part of base IMS Version 9
 - IMS Version 8
 - PQ73326 (UQ80615)
 - Prerequisite PQ73897 (latest level of IMS Java)
 - Prerequisite PQ75284 (IMS code using DB2's attachment facility)
 - DB2
 - DB2 Version 8 (PQ74629)

- DB2 Version 7 (PQ69861)
- Uses DB2 RRS attach facility
 - Requires SSM= and RRS=Y in the IMS startup definitions
- IMS Java and the DLIModel utility require Xalan-Java Version 2.6.0 or later from the Apache Software Foundation:

http://www.apache.org

XML Project, or equivalent code function. XSLT 4.3.1, which is equivalent to Xalan-Java Version 2.6.1, is included in SDK 1.4.2. If you are using SDK 1.4.2 or later, do not download and install the Apache XML files.

The Apache XML Project is a collaborative software development project that licenses open source software at no charge. The following open source files (or equivalent code function) are required by IMS Java and the DLIModel utility: xercesImpl.jar, xalan.jar, xml-apis.jar.

Integrated IMS Connect function

The IMS Connector for Java 9.1.0.1 runtime component for z/OS is delivered with the base of IMS. The IMS Connector for Java 9.1.0.1 development component which ships with WebSphere Studio Application Developer Integration Edition (WSADIE) will be delivered as an update to WSADIE 5.1.1.

IMS Version 9 adds the XPLINK= dependent region parameter for Java Message Processing (JMP) regions and Java Batch Processing (JBP) regions. This parameter allows IMS Java dependent regions to use the IBM Language Environment® Extra Performance Linkage (XPLINK) runtime option. If you use IBM SDK for z/OS, Java Technology Edition, Version 1.4.1 or later, you must specify XPLINK=Y for a JMP region or a JBP region. However, if you use Version 1.3.1 of the SDK, you should specify XPLINK=N or allow IMS to use XPLINK=N as the default.

Related reading

Specific information about product enhancements that were made for earlier releases of IMS might not be included in this book. When migrating to a more recent release of IMS, be sure to review the release planning guides that span your specific migration path. The release guides that are currently available are:

- ► IMS Version 8: Release Planning Guide, GC27-1305
- IMS Version 7: Release Planning Guide, GC26-9437
- ► IMS/ESA Version 6: Release Planning Guide, GC26-8744

13.3 Migration tasks and coexistence considerations

The following is a high level list of migration tasks. It is not supposed to be complete, rather vice versa, this list is an absolute minimum for all the installations. You should prepare your own migration and fallback plan, which should have a detailed list of all the tasks appropriate to your environment. The manual, *IMS Version 9: Release Planning Guide*, GC17-7831 provides a more detailed migration check list, and can be of help when compiling your own list. On very high level, you need to perform the following tasks:

- Check PSP bucket for latest maintenance information
- Apply coexistence maintenance to other IMS systems
- Install IMS Version 9
- Check the required software levels of IMS related products such as IMS Tools or OEM vendor products; upgrade to the appropriate levels and maintenance

- Check and test any changes needed to the user exits and usermods
- Upgrade RECONs
- Do system definition
- Do ACBGEN

13.3.1 CQS coexistence considerations

The following coexistence considerations exist for CQS:

- An IMS Version 9 CQS supports only IMS Version 9. Earlier versions of IMS cannot register with an IMS Version 9 CQS.
- User or vendor-written CQS clients that want to register with an IMS Version 9 CQS must be recompiled with the IMS Version 9 CQS macros.
- IMS Version 7 system can register only with IMS Version 7 CQS.
- IMS Version 7 CQS, IMS Version 8 CQS, and IMS Version 9 CQS can connect to the same Coupling Facility structure.
- IMS Version 7 CQS, IMS Version 8 CQS, and IMS Version 9 CQS can run on the same central processing complex (CPC).

13.3.2 Database utilities coexistence

The database recovery utilities take three types of input; log, image copy, and change accumulation data sets. The method of processing for coexistence in the utility programs is to translate the records as they are read into the format of the current release for that record type. For the pre-version 8 change accumulation records, there is not sufficient information to translate the records in IMS Version 8 or IMS Version 9. For this reason, it is necessary to apply the following coexistence APAR to the utilities in IMS Versions 7 to provide the necessary information to enable the translation:

APAR PQ54585 for IMS Version 7

Only those CA records from IMS Version 7 that were created after installing the appropriate APAR are usable by IMS Version 8 or IMS Version 9. The installation of IMS Version 9 as an upgrade from IMS Version 7 requires a sequence of operations to achieve coexistence for the recovery and change accumulation utilities:

- 1. The coexistence APAR must be installed on the existing IMS Version 7 system.
- 2. The change accumulation files must be conditioned to allow them to be used by IMS Version 9. This is done in one of this ways:
 - Make an image copy of the database subsequent to the installation of the APAR. This will invalidate all of the old CA data sets.
 - Run the change accumulation utility on IMS Version 7 with the appropriate APAR installed. If the APAR is installed before IMS Version 9 is used, most or all of the CA data sets might be processed and made valid for coexistence with IMS Version 9.

The batch back out, log archive, and log recovery utilities read only one input. This is a log data set. The IMS Version 9 version of these utilities accepts only input produced by IMS Version 9. Logs produced by earlier releases must be processed by the utility from the same release.

The IMS Version 9 database recovery utility (DFSURDB0) accepts all types of image copies, including batch image copy, image copy with the CIC option, online image copy, and partial

image copies produced by HSSP. A HISAM unload data set may be used in place of an image copy. These data sets, change accumulation data sets, and logs (RLDS and SLDS) may come from prior releases.

The IMS Version 9 change accumulation utility accepts logs and change accumulation input data sets produced by prior releases.

IMS Database Recovery Facility (DRF) V2R1 support requires the following APARs:

- PQ80052 to support recovery of HALDB database data sets which have undergone online reorganization
- PQ77559 to allow specification of sort parm overrides in SYSIN
- PQ79162 to enable secondary source support
- PQ80051 for IMS Version 9 coexistence and support for IMS Version 9 input
- PQ79326 to add the image copy cached function for the Virtual Tape Server (VTS)
- PQ79327 to support large block image copies

13.3.3 Remote Site Recovery (RSR) coexistence

For coordinated disaster recovery for IMS and DB2, an IMS Version 9 RSR tracking subsystem with XRC tracking enabled can track logs from supported pre-Version 9 active systems that have the usual and customary DBRC coexistence SPEs applied. For regular RSR, IMS Version 9 RSR coexistence supports configurations in which:

- The tracking site Transport Manager Subsystem (TMS) is at the IMS Version 9 level and the active site is at IMS Version 6, Version 7, or Version 8 level.
- The active site RECON data sets are at the IMS Version 6, Version 7, or Version 8 level (with the Version 9 DBRC coexistence SPE applied)
- The active TMS that is running ILS is at the IMS Version 6, Version 7, or Version 8 level.
- One or more active IMSs are at the IMS Version 6, Version 7, or Version 8 level.

Table 13-1 on page 229 contains all the supported configurations of a simple set of subsystems in an RSR Global Service Group (GSG). Some unsupported configurations are not included because a prerequisite configuration also is not supported. Some unsupported configurations are included even though a pre-requisite configuration is supported so that the reason for non-support can be explained.

The simple set of configurations in Table 7 on page 49 assumes:

- A single active IMS
- A single Transport Manager Subsystem (TMS) that is running the Isolated Log Transport
- A single set of active site RECON data sets
- A single tracking IMS v A single remote site TMS
- A single set of remote site RECON data sets

Table 13-1 on page 229 also describes valid and invalid RSR coexistence configurations. The following notation is used to denote the state of the subsystems and RECON data sets in this table:

- pre-V9 = IMS Version 7, or Version 8
- pre-V9 + SPE = IMS Version 7, or Version 8 with the DBRC coexistence SPE applied
- ► V9 = IMS Version 9

Active Sit	e State		Remote S	e Site State			
IMS	TMS ILS	RECON	IMS	тмѕ	RECON	NOTES	
pre-V9	pre-V9	pre-V9	pre-V9	pre-V9	pre-V9	Supported	
pre-V9 + SPE	pre-V9	pre-V9	pre-V9	pre-V9	pre-V9	Supported	
pre-V9 + SPE	V9	V9	pre-V9	pre-V9	pre-V9	Supported	
pre-V9	V9	pre-V9	pre-V9	pre-V9	pre-V9	Not Supported. The local TMS/ILS connot be migrated to IMS Version 9 if the RECON data set have not been upgraded to IMS Version 9.	
pre-V9 + SPE	pre-V9 + SPE	pre-V9	pre-V9	pre-V9	pre-V9	Supported	
V9	pre-V9 + SPE	pre-V9	pre-V9	pre-V9	pre-V9	Not supported. The RECON data sets must be upgraded prior to running any IMS at the IMS Version 9 level. The active IMS cannot be at the IMS Version 9 level if the local site TMS that is running ILS is not at the same level. The local site IMS cannot be at a later level than the remote IMS.	
pre-V9 + SPE	pre-V9 + SPE	V9	pre-V9	pre-V9	pre-V9	Supported	
pre-V9	V9	V9	pre-V9	pre-V9	pre-V9	Not supported. The local site TMS that is running ILS cannot be at the IMS Version 9 level if the tracking IMS is at the pre-Version 9 level. The active IMS also cannot be at the IMS Version 9 level.	
V9	V9	V9	pre-V9	pre-V9	pre-V9	Not supported. The local site TMS that is running ILS and the active IMS cannot be at the IMS Version 9 level if the tracking IMS is at the pre-Version 9 level. The active IMS also cannot be at the IMS Version 9 level.	
pre-V9	pre-V9	pre-V9	pre-V9 + SPE	pre-V9	pre-V9	Supported	
pre-V9 + SPE	pre-V9	pre-V9	pre-V9 + SPE	pre-V9	pre-V9	Supported	

Table 13-1 Valid RSR coexistence subsystem configurations

Active Site State			Remote S	ite State		
IMS	TMS ILS	RECON	IMS	NOTES		
pre-V9 + SPE	pre-V9 + SPE	pre-V9	pre-V9 + SPE	pre-V9	pre-V9	Supported

13.3.4 Additional coexistence considerations

The OLCSTAT data set (used for global online change) is not compatible with Version 7 IMSs.

Extended checkpoint restriction

You cannot use extended checkpoint to restart applications across different releases of IMS.

13.3.5 Using IRLM 2.2

You can run IRLM 2.2 with the same procedure that you use for IRLM 2.1 by changing the procedure to use the IRLM 2.2 SDXRRESL.

The following execution parameters have changed for IRLM 2.2:

- PC=NO is ignored, IRLM 2.2 uses always PC=YES
- ► The MAXCSA value is ignored because it applies only to the PC=NO environment.
- The MVS EXEC parameter MEMLIMIT has been added to the IRLM 2.2 startup procedure. The value for MEMLIMIT is set to 2 GB by default. IRLM 2.2 only accepts values of 2 GB or higher.
- The default for DEADLOK is (1,1).

You can use IRLM 2.2 with IRLM 2.1 in an IMS Version 9 environment, including a data-sharing environment. IRLM 2.2 can use storage above the 2 GB bar for 64-bit processors, but IRLM 2.2 can also run on 32-bit processors. You can also use IRLM 2.2 with IMS Version 8 or IMS Version 7 using either 64-bit or 32-bit processors.

13.4 RECON upgrade

IMS Version 7 RECONs may be upgraded directly to IMS Version 9. Similarly, IMS Version 8 RECONs may be upgraded to IMS Version 9. There is no support to upgrade RECONs from previous IMS releases to IMS Version 9. The following APARs should be applied to IMS Version 7 or IMS Version 8 before its RECONs are upgraded to IMS Version 9:

- PQ72838 is an IMS Version 7 APAR which allows IMS Version 7 to use RECONs which have been upgraded to IMS Version 9.
- PQ72840 is an IMS Version 8 APAR which allows IMS Version 8 to use RECONs which have been upgraded to IMS Version 9.

RECONs are upgraded to IMS Version 9 by using the DBRC CHANGE.RECON UPGRADE command with the IMS Version 9 DBRC utility (DSPURX00).

The upgrade may be run while the RECONs are allocated to and being used by IMS Version 7 or IMS Version 8, Of course, these systems must be able to use IMS Version 9 RECONs. The upgrade checks the RECONs to ensure that any subsystems using the RECONs are capable of using IMS Version 9 RECONs. It does this by examining the SUBSYS records in

the RECONs. Some IMS utilities do not create SUBSYS records. Thus, the upgrade cannot determine if they are running. Users must ensure that any IMS utility which is running at the time of the upgrade has the appropriate maintenance which allows it to read IMS Version 9 RECONs.

Upgrade from IMS Version 7 to IMS Version 9 reads SSYS records to check for DBRC SPE, updates every record from IMS Version 7 to IMS Version 8 format due to segmented record support which was added in IMS Version 8 and updates RECON header from IMS Version 7 to IMS Version 9.

Upgrade from IMS Version 8 to IMS Version 9 reads SSYS records to check for DBRC SPE, and updates the RECON header from IMS Version 8 to IMS Version 9. This should be very quick.

When RECONs are upgraded, any HALDB databases in the RECONs are marked as incapable of running integrated online reorganization. Users can issue CHANGE.DB commands to make them capable of using online reorganization.

When a HALDB master or partition database record from the RECONs is listed, IMS Version 9 includes a field which shows if online reorganization has been enabled for it. Existing HALDBs are upgraded to reflect that they are not capable of running integrated online reorganization and listing the RECON shows it as follows:

- New field for master database listing:
 - ONLINE REORG CAPABLE =YES NO
- New fields for partition listing:
 ONLINE REORG CAPABLE =YES | NO
- ► RSR fields:

OLR ACTIVE HARD COUNT =n OLR INACTIVE HARD COUNT =n

If a HALDB is made capable of online reorganization, it cannot be used by IMS Version 7. There is a small programming enhancement (SPE) for IMS Version 8 which allows it to tolerate online reorganization. It allows IMS Version 8 subsystems to use the database while an IMS Version 9 system is doing online reorganization for the database. Of course, IMS Version 8 cannot invoke online reorganization. If the SPE is not applied to the IMS Version 8 system, it has the same restrictions which IMS Version 7 has and which are explained above. The SPE is provided through four APARs. They are PQ78493, PQ78758, PQ78916, and PQ78917.

For more details on RECON and DBRC, see 5.5, "DBRC migration and coexistence" on page 82.

Note: The batch RECON upgrade utility, DSPURU00, is no longer supported

You must issue the **CHANGE.RECON UPGRADE** command using the DBRC utility (DSPURX00). You cannot issue the command from an online IMS.

The MINVERS keyword of the **INIT.RECON** and **CHANGE.RECON** commands specifies the minimum version of IMS that can sign on to DBRC. When a RECON data set is migrated to an IMS Version 9 level, DBRC sets a default of MINVERS('7.1'). The value that is set for the minimum version is displayed in the **LIST.RECON** command output.

When all systems that access the RECON data set are at an IMS Version 9 level, you can reset the minimum version value by using the MINVERS keyword on the IMS Version 9

CHANGE.RECON command. After you set the MINVERS level for an IMS system, system sign on fails for earlier versions of IMS.

13.5 Fallback considerations

IMS does not generally support downward compatibility in any major function between releases. However, consider the following list when preparing your migration fallback plan. This information is intended as a guide to understanding fallback inhibitors, and should not be considered complete:

The ACB maintenance utility, ACBGEN, is required.

For each IMS that you are migrating to a pre-Version 9 level, perform the following steps:

- Shut down that IMS
- Install the version of IMS that you want
- Run INITMOD to initialize the MODSTAT data set
- Cold start the IMS

You can use the IMS Queue Control Facility (QCF) to convert IMS Version 9 messages to IMS Version 8 or IMS Version 7 messages.

For IMS Version 8 subsystems with the OLR coexistence SPE applied, full data sharing is allowed and no immediate action is necessary. For IMS Version 8 subsystems without the OLR coexistence SPE applied, and for IMS Version 7 subsystems, databases that are defined as not capable of being reorganized online are available and no action is required.

However, if any M-V (and Y) DBDSs are active or online reorganization is active for any partitions, then you must perform the following actions whenever processing those partitions before falling back to use the IMS Version 8 utilities:

 Reorganize all partitions with the M-V (and Y) data sets active or online reorganization active using the IMS Version 9 OLR or the offline reorganization utility.

This leaves only the A-J (and X) data sets active.

Change DBRC for the databases to reflect that they are not capable of being reorganized online using the IMS Version 9 command:

CHANGE.DB DBD(HALDB master) OLRNOCAP

If you must fall back to an earlier version of IMS, you must set DBRC for all HALDBs to OLRNOCAP. Take a listing of the RECON and verify that there is no entry with an ACTIVE DBDS=M-V (and Y) data sets or an ACTIVE DBDS=A-J (and X) and M-V (and Y).

Α

DBRC API control blocks

In this appendix, we show the layout of DBRC API control blocks:

- ► DSPAPI FUNC=HEAD, "Constants and equates needed by the DBRC API" on page 234
- "DSPAPQHD header" on page 236
- "DSPAPQAL allocation block" on page 237
- "DSPAPQAR Fast Path area block" on page 238
- "DSPAPQBO backout block" on page 241
- "DSPAPQCA change accumulation execution block" on page 244
- "DSPAPQCG change accumulation group block" on page 246
- "DSPAPQDB full function database block" on page 248
- "DSPAPQDG DBDS, database, and recovery group block" on page 250
- "DSPAPQDS database data set block" on page 252
- "DSPAPQEL EEQE list" on page 254
- "DSPAPQFD DEDB database block" on page 256
- "DSPAPQGG global service group block" on page 258
- ► "DSPAPQHB HALDB block" on page 260
- "DSPAPQHP HALDB Partition block" on page 261
- "DSPAPQIC image copy block" on page 264
- "DSPAPQLA log allocation block" on page 267
- "DSPAPQLG RLDS/SLDS block" on page 269
- "DSPAPQLI log information block" on page 272
- "DSPAPQNF not found block" on page 273
- "DSPAPQOL online log data set block" on page 275
- "DSPAPQRC RECON status block" on page 277
- "DSPAPQRI DBDS/area recovery information block" on page 280
- "DSPAPQRR DBDS reorganization block" on page 281
- "DSPAPQRV recovery block" on page 282
- "DSPAPQSL DB/area authorized subsystem list block" on page 284
- "DSPAPQSS subsystem block" on page 285

Constants and equates needed by the DBRC API

Example: A-1 DSPAPI FUNC=DSECT - constants and equates needed by the API

	DOIAITION		01 - 0011314	nis and equales in	eeded by life Al	1
+DSPAPI Plist	Func	EQU	0	Function		01-DSPAP
+DSPAPI Plist		EQU	1	Туре		01-DSPAP
+DSPAPI_Plist		EQU	4	Version		01-DSPAP
+DSPAPI Plist		EQU	8	Token		01-DSPAP
+DSPAPI Plist		EQU	12	Output		01-DSPAP
+DSPAPI Plist	Retcode	EQU	16	Return Code		01-DSPAP
+DSPAPI Plist	Rsncode	EQU	20	Reason Code		01-DSPAP
+DSPAPI Plist		EQU	24	SYSPRINT		01-DSPAP
+DSPAPI_Plist	Buffer	EQU	24	Buffer		01-DSPAP
+DSPAPI_Plist	Name	EQU	28	DBname/DBlist/Na	ime	01-DSPAP
+DSPAPI_Plist	DDN	EQU	32	DDN		01-DSPAP
+DSPAPI_Plist	SSID	EQU	36	SSID		01-DSPAP
+DSPAPI_Plist	Startime	EQU	40	Start time		01-DSPAP
+DSPAPI_Plist	Flag1	EQU	44	Flags 1		01-DSPAP
+DSPAPI_Plist	_Flag2	EQU	45	Flags 2		01-DSPAP
+DSPAPI_Plist	_Flag3	EQU	46	Flags 3		01-DSPAP
+DSPAPI_Plist	_Flag4	EQU	47	Flags 4		01-DSPAP
+DSPAPI_Plist	_SaveR15	EQU	48	Reg 15 Save area	l i	01-DSPAP
+DSPAPI_Plist	_SaveR0	EQU	52	Reg O Save area		01-DSPAP
+DSPAPI_Plist	_Reserve1	EQU	56	Reserved		01-DSPAP
+DSPAPI_Plist	_Reserve2	EQU	60	Reserved		01-DSPAP
+DSPAPI_Plist		EQU	64	End of Plist		01-DSPAP
+* These Equa		e vario	ous API Fur	nctions		
+DSPAPI_Func_		EQU	01	STARTDBRC		01-DSPAP
+DSPAPI_Func_		EQU	02	STOPDBRC		01-DSPAP
+DSPAPI_Func_		EQU	03	QUERY		01-DSPAP
+DSPAPI_Func_		EQU	04	RELBUF		01-DSPAP
+DSPAPI_Func_		EQU	05	DSECT		01-DSPAP
+* These Equa						
+DSPAPI_Type_			01	Type=DB		01-DSPAP
+DSPAPI_Type_		EQU	02	Type=RECON		01-DSPAP
+DSPAPI_Type_		EQU	03	Type=DBDSGROUP		01-DSPAP
+DSPAPI_Type_		EQU	04	Type=DBGROUP		01-DSPAP
+DSPAPI_Type_		EQU	05	Type=RECOVGROUP		01-DSPAP
+DSPAPI_Type_		EQU	06	Type=CAGROUP		01-DSPAP
+DSPAPI_Type_		EQU	07	Type=GSGROUP		01-DSPAP
+DSPAPI_Type_		EQU	08	Type=BACKOUT		01-DSPAP
+DSPAPI_Type_		EQU	09	Type=LOG		01-DSPAP
+DSPAPI_Type_		EQU	10	Type=OLDS		01-DSPAP
+DSPAPI_Type_		EQU	11	Type=SUBSY		01-DSPAP
+* These Equa					I	
+DSPAPI_Name1			X'80'	NAMELIST specifi	ea	01-DSPAP
+DSPAPI_CAINF			X'40'	CAINFO = YES	(Turne-1.00)	01-DSPAP
+DSPAPI_TRACK			X'20'	TRACKER = YES	(Type=LOG)	01-DSPAP
+DSPAPI_SSTYP			X'10' X'08'	SSTYPE=ONLINE SSTYPE=BATCH	(TYPE=SUBSYS) (TYPE=SUBSYS)	
+DSPAPI_SSTYP			X'04'	SSITPE-DATCH	(11PE-SUDS15)	
+DSPAPI_Reser				DDN=*		01-DSPAP
+DSPAPI_DDN_A +DSPAPI Reser			X'02' X'01'	-אוסס		01-DSPAP 01-DSPAP
+DSPAPI_Reser +DSPAPI First	_	-	X'80'	LOC FIRST		01-DSPAP 01-DSPAP
_			X'80' X'40'	LUC FIRSI		
+DSPAPI_Reser	veu_J		X'40 X'20'	LOC NEXT		01-DSPAP 01-DSPAP
+DSPAPI_Next +DSPAPI Prev			X'10'	LOC PREV		01-DSPAP 01-DSPAP
+DSPAPI_Prev +DSPAPI Reser	ved 4	EQU	X'08'	LUG FNLV		01-DSPAP 01-DSPAP
+DSPAPI_Reser	_	EQU	X'04'			01-DSPAP 01-DSPAP
+DSPAPI_Reser			X'04 X'02'			01-DSPAP 01-DSPAP
. DOL WIT VESSEL	·cu_o	LQU	N VL			

	EQU	X'01'		/ ×	01-DSPAP
	EQU	X'80'	LIST=ALLOC	(TYPE=DB)	01-DSPAP
	EQU	X'40'	LIST=IC	(TYPE=DB)	01-DSPAP
	EQU	X'20'	LIST=RECOV	(TYPE=DB)	01-DSPAP
	EQU	X'10'	LIST-REORG	(TYPE=DB)	01-DSPAP
	EQU	X'08'			01-DSPAP
	EQU	X'04'			01-DSPAP
	EQU	X'02'			01-DSPAP
	EQU	X'01'			01-DSPAP
	EQU	X'80'			01-DSPAP
	EQU	X'40'			01-DSPAP
	EQU	X'20'			01-DSPAP
	EQU	X'10'			01-DSPAP
	EQU	X'08'			01-DSPAP
+DSPAPI_Reserved_17	EQU	X'04'			01-DSPAP
	EQU	X'02'			01-DSPAP
+DSPAPI_Reserved_19	EQU	X'01'			01-DSPAP
+* These Equates define the	Quer	y Output B	lock Types		
	EQU	X'0100'	RECON Status		01-DSPAP
+DSPAPI_B1kType_PRILOG	EQU	X'0500'	PRIMARY LOG		01-DSPAP
+DSPAPI_B1kType_LOGINFO	EQU	X'0501'	Log Information		01-DSPAP
+DSPAPI_B1kType_LOGALL	EQU	X'0700'	LOG ALLOCATION		01-DSPAP
	EQU	X'0900'	SECONDARY LOG		01-DSPAP
+DSPAPI B1kType CAGROUP	EQU	X'0F00'	CA GROUP		01-DSPAP
+DSPAPI_B1kType_CA	EQU	X'1100'	CA EXECUTION		01-DSPAP
	EQU	X'1600'	DBDS GROUP		01-DSPAP
+DSPAPI B1kType DBGRP	EQU	X'1601'	DB GROUP		01-DSPAP
+DSPAPI_B1kType_RECOVGRP	EQU	X'1602'	RECOVERY GROUP		01-DSPAP
	EQU	X'1800'	IMS DB		01-DSPAP
	EQU	X'1801'	HALDB		01-DSPAP
	EQU	X'1802'	Fast Path DEDB		01-DSPAP
+DSPAPI_B1kType_DBNotFound		X'18FF'	DB Not Found		01-DSPAP
	EQU	X'1900'	PARTition		01-DSPAP
	EQU	X'2000'	DBDS HEADER		01-DSPAP
	EQU	X'2100'	Area		01-DSPAP
	EQU	X'2800'	ALLOCATION		01-DSPAP
	EQU	X'2801'	Recovery Informa	tion	01-DSPAP
	EQU	X'2D00'	IMAGE COPY		01-DSPAP
	EQU	X'3200'	REORGANIZATION		01-DSPAP
	EQU	X'3500'	BACKOUT		01-DSPAP
	EQU	X'3700'	RECOVERY		01-DSPAP
	EQU	X'3A00'	GSG		01-DSPAP
	EQU	X'3F00'	SUBSYSTEM		01-DSPAP
	EQU	X'4300'	PRIM SYS LOG		01-DSPAP
	EQU	X'4400'	TRACKING PSLDS		01-DSPAP
	EQU	X'4700'	SEC SYS LOG		01-DSPAP
	EQU	X'4800'	TRACKING SSLDS		01-DSPAP
	EQU	X'4000'	PRIMARY ONLINE		01-DSPAP
	EQU	X'5700'	SEC ONLINE		01-DSPAP
+* Block version constants	LQU	X 3700	SEC ONLINE	@PQ83837	01-031 AI
	EQU	X 10000010	0' Version=1.0	61 (05057	01-DSPAP
	EQU		1' Version=1.01		01-DSPAP
	LQU	V 0000010	T ACI21011-1.01		
+ print off + print on					01-DSPAP 01-DSPAP

DSPAPQHD header

```
Example: A-2 DSPAPQHD - API query output header
```

```
+*
+*
             DSPAPQHD - DBRC API Query output header
   Name:
+*
+*
   Function:
+*
+*
    Describes the header of all output areas returned by the DBRC
+*
    FUNC=QUERY calls.
+*
+*
    This macro can be included or invoked multiple times without
+*
    problem - both in assembler and PL/X form.
+*
+*
    The header described by this macro is included in several DBRC
+*
    API control blocks. Changing the block's length will require
+*
    finding both the direct and indirect users of the block.
+*
+*
+*
    Arguments: (assembler only)
+*
       DSECT - YES NO
                      Determines whether a DSECT statement line is
+*
                      included in the expansion. Use NO if the
+*
                      block is to be imbedded in a larger block.
+*
+*
       PREFIX-
                      Determines what prefix is to be added to the
+*
                      assembler DSECT symbolic names for fields.
+*
                      Default is APQHD. Don't include the char.
+*
                      All requested prefixes must be reflected in
+*
                      the macro code to ensure that xref searches
+*
                      can be done when needed.
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
               Ver PTM/APAR Init Description
     Date
+*
            -- ----- ------
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
+DSPAPQHD
              DSECT
                                OUTPUT HEADER
                                                                  01-DSPAP
+
              DS OF
                                                                  01-DSPAP
+APQHD EYECATCHER DS CL8
                               Output area eyecatcher
                                                                  01-DSPAP
+APQHD LENGTH DS F
                               Block length, hdr + data
                                                                  01-DSPAP
+APQHD_BLKTYPE DS XL2
                               Block type
                                                                  01-DSPAP
             DS H
+
                               Reserved
                                                                  01-DSPAP
+APQHD DEPPTR DS A
                               Ptr to block dependent
                                                                  01-DSPAP
+APQHD NEXTPTR DS A
                               Ptr to next block of the same type
                                                                  01-DSPAP
```

DSPAPQAL - allocation block

Example: A-3 DSPAPQAL - allocation block

+**	**************************************	*T*
+*	Licensed Materials - Property of IBM	*
+* +*	5655-J38	*
+*		*
+* +*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	* *
+*	US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule contract with	*
+*	IBM Corp.	*
+*	**************************************	*
+**		*
+* +*	Name: DSPAPQAL - Allocation block	*
+*	Product: DBRC Application Programming Interface	*
+*		*
+*	Function:	*
+*		*
+* +*	This macro maps the Allocation output block returned on the DSPAPI FUNC=QUERY TYPE=DB call.	*
+*		*
+* +*	The header of this block is mapped by DSPAPQHD which contains the following information:	*
+*	the forfowing information:	*
+*	apqhd_eyecatcher = 'DSPAPQAL'	*
+*	apqhd_length = block length	*
+*	<pre>apqhd_blktype = X'2800' (DSPAPI_BlkType_ALLOC)</pre>	*
+*	apqhd_depptr = 0, no dependent blocks	*
+*	<pre>apqhd_nextptr = pointer to next ALLOC block for the DBDS apqhd blkoffset = offset from DSPAPQHD to DSPAPQAL</pre>	*
+*	apqua_bikoliset - oliset itom bsfarqhb to bsfarqal	*
+*	Notes:	*
+*		*
+*	Dependencies: None.	*
+*	Destroisting News	*
+* +*	Restrictions: None.	*
+*	Parameters: None.	*
+*		*
+*	External References:	*
+*	Macros: None	*
+*		*
+* +*	Modules: None	*
+*	Change Activity:	*
+*		*
+*	Date Ver PTM/APAR Init Description	*
+*		*
+*	2003-10-02 1.0 KZ30219 pas Prolog update	*
+*		~

+**************************************						
+DSPAPQAL DSECT Allocation block	01-DSPAP					
+apqal_DBname DS CL8 Database name (01-DSPAP					
+apqal_DDname DS OCL8 DD name or (01-DSPAP					
+apqal_Areaname DS CL8 Area name	01-DSPAP					
+apqal_alloctm DS XL12 Allocation time	01-DSPAP					
+apqal_daltm DS XL12 Deallocation time	01-DSPAP					
+apqal_strtm DS XL12 Log start time (01-DSPAP					
+apqal_dssn DS F Field for DSSN value (01-DSPAP					
+apqal_usid DS F Update set identifier (01-DSPAP					
+apqal_alrid DS XL8 LRID of begin-upd rec (01-DSPAP					
+apqal_dlrid DS XL8 LRID of end-upd rec	01-DSPAP					
+apqal_slrid DS XL8 Last LRID applied if suspended (01-DSPAP					
+apqal_flags DS XL1 Flags	01-DSPAP					
+apqal_tsusp EQU X'80' Tracking is suspended (01-DSPAP					
+apqal_napp1 EQU X'40' No records applied (01-DSPAP					
+apqal_cicpt EQU X'20' Fuzzy ic purge time	01-DSPAP					
+ DS CL3 Reserved	01-DSPAP					
+**************************************						
+* END OF DSPAPQAL *						
+**************************************						

DSPAPQAR - Fast Path area block

Example: A-4 DSPAPQAR - Fast Path area block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
+*
                                                       *****@ECPYRT
+*
              DSPAPQAR - Fast Path Area block
+*
   Name:
+*
+*
   Product:
              DBRC Application Programming Interface
+*
+*
   Function:
+*
+*
    This macro maps the Fast Path Area output block returned on
+*
    the DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQAR'
+*
      apqhd length
                     = block length
+*
      apqhd_blktype
                      = X'2100' (DSPAPI_BlkType_AREA)
      apqhd_depptr
+*
                      = pointer to Recovery Information
+*
                        block (DSPAPQRI)
                                                                   *
+*
      apqhd_nextptr
                      = pointer to next Area block
```

```
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQAR
+*
+*
    Within DSPAPQAR are the following fields which are used to
+*
    access the Area Data Set, EEQE, and authorized subsystem
+*
    information for the area:
+*
+*
      apqar ADSlist
                       = offset from DSPAPQAR to ADS data
+*
                        (apqar_adslt)
+*
      apqar ADSLength = length of each ADS entry
+*
      apqar NOADS
                       = number of ADSs
+*
+*
      apqar_EEQElist
                      = offset from DSPAPQAR to EEQE
+*
                        data (DSPAPQEL)
+*
      apqar_EEQELength = length of each EEQE entry
+*
      apqar_EEQECount = number of EEQEs
+*
+*
                      = offset from DSPAPQAR to SS
      apqar_SSlist
+*
                        data (DSPAPQSL)
+*
      apqar SSEntLen = length of each SS entry
+*
      apqar_SSNUM
                      = number of authorized subsystems
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
                Ver
                     PTM/APAR Init Description
+*
     ----- -----
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
     2004-03-04 1.01 PQ83837 pas Add user-recoverable flag
+*
DSECT
+DSPAPQAR
                                    Fast Path Area block
                                                                     01-DSPAP
                       DS CL8
                                                                     01-DSPAP
+apqar_DBname
                                    Database name
+apgar Areaname
                       DS
                             CL8
                                    Area name
                                                                     01-DSPAP
+apqar EEQElist
                       DS
                             F
                                    Offset to EEQE list (DSPAPQEL),
                                                                     01-DSPAP
+*
                                    zero if no EEQEs
+apqar_SSlist
                       DS
                             F
                                    Offset to SS list (DSPAPQSL),
                                                                     01-DSPAP
+*
                                   zero if no SS auth'd
+apqar_ADSlist
                       DS
                             F
                                    Offset to ADS list,
                                                                     01-DSPAP
+*
                                    zero if none registered
+
                       DS
                             F
                                    Reserved
                                                                     01-DSPAP
+apgar SHRLVL
                       DS
                             FL1
                                    Share level of DB
                                                                     01-DSPAP
                                    Held auth state
+apqar_HELDAU
                       DS
                             FI1
                                                                     01-DSPAP
                             X'80' High order bit flag
+apqar HAUBIT
                       EQU
                                                                     01-DSPAP
+apqar_DMBNUM
                       DS
                             Н
                                    Global DMB number
                                                                     01-DSPAP
+apqar_SSNUM
                       DS
                             Н
                                    # subsytems authd to Area
                                                                     01-DSPAP
+apqar_SSEntLen
                       DS
                             Н
                                    Length of each SS entry
                                                                     01-DSPAP
                       DS
                                    Access state for CHG AUTH
+apqar_CACCSS
                             FL1
                                                                     01-DSPAP
+apqar_CANCDD
                       DS
                             FL1
                                    Encoded state for CHG AUTH
                                                                     01-DSPAP
```

+apqar_CAHELD	DS	FL1 Held state for CHG AUTH 01-DSPAP
+apqar_IRLMAU	DS	CL5 IRLMID of auth SS 01-DSPAP
+apqar_FLAGS	DS	XL2 01-DSPAP
+apqar_RECYC	EQU	X'8000' REUSE image copies 01-DSPAP
+apgar ICREC	EQU	X'4000' Image Copy Recommended 01-DSPAP
+apqar IC	EQU	X'2000' Image Copy Needed 01-DSPAP
+apqar ICNDIS	EQU	X'1000' IC needed disabled option 01-DSPAP
+*	EQU	1 = IC Needed Disabled
+apqar RECOV	EQU	X'0800' Recovery needed 01-DSPAP
· · · -		
+apqar_INPRO	EQU	
+apqar_GT240	EQU	X'0200' M/C FP GT240 area DEDB 01-DSPAP
+apqar_VS0	EQU	X'0100' VSO flag 01-DSPAP
+apqar_PREOP	EQU	X'0080' PREOPEN flag 01-DSPAP
+apqar_PRELD	EQU	X'0040' PRELOAD flag 01-DSPAP
+apqar_LKASD	EQU	X'0020' VSO CF buffer lookaside 01-DSPAP
+apqar_MAS	EQU	X'0010' VSO area resides in multi-area 01-DSPAP
+*		CF structure
+apqar RRGAL	EQU	X'0008' REORG since last ALLOC, 01-DSPAP
+*	N ²	only set if RSR-covered
+apqar TSRAL	EQU	X'0004' TS recov since last ALLOC, 01-DSPAP
+*	LQU	only set if RSR-covered
	DC	
+apqar_RSRflags	DS	XL1 Remote Site Recovery flags 01-DSPAP
+apqar_RCVTRK	EQU	X'80' Recovery Level Tracking 01-DSPAP
+apqar_TRKSPN	EQU	X'40' Tracking was suspended 01-DSPAP
+apqar_PURBIT	EQU	X'20' Suspended by time 01-DSPAP
+apqar_RCVRQ	EQU	X'10' Receive Required 01-DSPAP
+apqar_AUFLAG	DS	XL1 Authorization flags 01-DSPAP
+apqar PAFLG	EQU	X'80' Prohibit authorization 01-DSPAP
+apqar NONRV	EQU	X'40' Non-recoverable 01-DSPAP
+apqar USRRV	EQU	X'20' User-recoverable (VERSION=1.01) 01-DSPAP
+*		@PQ83837
+apqar DSORG	DS	XL1 Data set organization 01-DSPAP
+apqar VSAM	EQU	X'80' 1 = VSAM, 0 = NON-VSAM 01-DSPAP
+apqar_INDEX +*	EQU	X'40' 0 = Non-indexed (OSAM or ESDS), 01-DSPAP
		1 = Indexed(ISAM or KSDS)
+apqar_DBORG	DS	XL1 IMS DB organization 01-DSPAP
+apqar_GSGname	DS	CL8 GSG Name 01-DSPAP
+	DS	CL2 Reserved 01-DSPAP
+apqar_USID	DS	F Last ALLOC USID 01-DSPAP
+apqar AUSID	DS	F Last authorized USID 01-DSPAP
+apqar_RUSID	DS	F Last received USID 01-DSPAP
+apqar HUSID	DS	F Hardened USID 01-DSPAP
+apgar RNUSID	DS	F Receive needed USID 01-DSPAP
+apqar RecovGrp	DS	CL8 Recovery Group name 01-DSPAP
+apgar CAGrpName	DS	CL8 Change Accum group name 01-DSPAP
+apgar GENMX	DS	H Max number of ICs that may be 01-DSPAP
+*	03	-
	DC	predefined for this area
+apqar_GENNO	DS	H Number of available ICs for 01-DSPAP
+*		this area
+apqar_USDIC	DS	H Number of ICs used 01-DSPAP
+apqar_EEQECount	DS	H EEQE count 01-DSPAP
+apqar_EEQELength	DS	H EEQE entry length 01-DSPAP
+apqar_NOADS	DS	FL1 # of ADS in the area 01-DSPAP
+apgar AVADS	DS	FL1 # of available ADS 01-DSPAP
+apgar ADSLength	DS	H ADS entry length 01-DSPAP
+	DS	CL2 Reserved 01-DSPAP
+apqar JCL	DS	OCL40 GENJCL members 01-DSPAP
+apqar ICJCL	DS	CL8 Image copy member 01-DSPAP
+apqar OIJCL	DS	CL8 Online IC member 01-DSPAP
+apqar_013CL +apqar RCJCL	DS	
·apyar_KCUCL	03	CL8 Recovery member 01-DSPAP

+apqar DFJCL	DS	CL8	DEFLTJCL member	01-DSPAP		
+apqar_RVJCL	DS	CL8	Receive JCL member	01-DSPAP		
+apqar_RTPRD	DS	Н	IC retention period	01-DSPAP		
+apqar_DSID	DS	Н	IMS data set ID	01-DSPAP		
+apqar_DSSN	DS	F	Data set sequence number	01-DSPAP		
+apqar_CFST1	DS	CL16	VSO CF Structure 1	01-DSPAP		
+apqar_CFST2	DS	CL16	VSO CF Structure 2	01-DSPAP		
+apqar_adslt	DSECT		Area Data Set List	01-DSPAP		
+apqar_ADSDD	DS	CL8	DDNAME of the ADS	01-DSPAP		
+apqar_ADSDN	DS	CL44	DSN of the ADS	01-DSPAP		
+apqar_ADSBT	DS	XL1	ADS flags	01-DSPAP		
+apqar_ADSAV	EQU	X'80'	Avail status of ADS	01-DSPAP		
+apqar_ADSFM	EQU	X'40'	Format status of create util	01-DSPAP		
+apqar_ADSCP	EQU	X'20'	Copy status of create util	01-DSPAP		
+	DS	CL3	Reserved	01-DSPAP		
+**************************************						
+* END OF DSPAPQAR			*			
+****	*****	******	***************************************			

DSPAPQBO - backout block




Figure A-1 Backout output

Example: A-5 DSPAPQBO - backout block

DSPAPQB0 +************************************	31479703 YRT**@SCPYRT*
+*	*
+* Licensed Materials - Property of IBM	*
+*	*
+* 5655-J38	*
+*	*
+* (C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*	*
+* US Government Users Restricted Rights - Use, duplicatio	n or *

```
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
+*
+*
   Name:
              DSPAPQBO - Backout block
+*
+*
   Product:
              DBRC Application Programming Interface
+*
+*
    Function:
+*
+*
    This macro maps the Backout output block returned on the
+*
    DSPAPI FUNC=QUERY TYPE=BACKOUT call.
+*
+*
     The header of this block is mapped by DSPAPQHD which contains
+*
     the following information:
+*
+*
      apqhd_eyecatcher = 'DSPAPQB0'
+*
      apqhd length = block length
      apqhd blktype = X'3500' (DSPAPI_BlkType_BACKOUT)
+*
+*
      apqhd depptr
                       = 0, no dependent block
      apqhd_nextptr
+*
                       = pointer to next Backout block
+*
       apphd blkoffset = offset from DSPAPQHD to DSPAPQBO
+*
+*
    Within DSPAPQBO are the following fields which are used to
+*
     access the first and the last UOR entries:
+*
+*
      apgbo FirstUOR
                        = offset from DSPAPQBO to the first UOR
+*
                          entry (apqbo_UOREntry)
+*
+*
      apqbo_LastUOR
                        = offset from DSPAPQBO to the last UOR
+*
                          entry
+*
+*
     Within each UOR entry (apqbo UOREntry) are the following
+*
     fields which are used to access the previous and next UOR
+*
     entries as well as the databases associated with the UOR:
+*
+*
       apqbo_NextUOR
                        = offset from DSPAPQBO to the next UOR
+*
                          entry
+*
      apqbo PrevUOR
                        = offset from DSPAPQBO to the previous
+*
                          UOR entry
+*
+*
       apqbo DS DBOffset = offset from apqbo UOREntry to DB entries
+*
                          (apqbo_DBent)
+*
       apqbo DBCount
                        = number of DB entries
+*
      apgbo DBLength
                      = Length of each DB entry
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
```

+* Change Activity: +* +* Date Ver PTM/APAR Init Description +* ----- -----+* 2003-10-02 1.0 KZ30219 pas Prolog update +* DSECT +DSPAPQB0 Backout block 01-DSPAP +apqbo SSID DS CL8 Subsystem identifier 01-DSPAP DS +apgbo FirstUOR F Offset of first UOR entry 01-DSPAP F DS 01-DSPAP +apqbo LastUOR Offset of last UOR entry +apqbo_TimeFirst DS XL12 Earliest UOR time 01-DSPAP DS +apqbo TimeLast XL12 Latest UOR time 01-DSPAP DS +apqbo FLAGS XL1 Backout flags 01-DSPAP +apqbo SAVER EQU X'80' SAVUOR call during restart 01-DSPAP + DS CL3 Reserved 01-DSPAP +apgbo UORcount DS F Number of UORs 01-DSPAP ************* +* +* The following structure maps the unit of recovery entries. +* There is one such entry for each unit of recovery (i.e. there +* are appbo UORcount entries). Each unit of recovery entry contains the offset within the backout block to the previous +* +* and following entries. Field apqbo_PrevUOR is the offset of +* the previous entry and apqbo NextUOR is the offset of the +* following entry. For the first unit of recovery (UOR) entry, +* apqbo PrevUOR will be zero. Similarly, apqbo NextUOR will be +* zero for the last entry. +* DSECT Unit of Recovery entry +apqbo_UORentry 01-DSPAP DS OCL64 Prefix section +apqbo_prefix 01-DSPAP +apqbo NextUOR DS F Offset of next UOR entry 01-DSPAP DS DS +apgbo PrevUOR F Offset of previous UOR entry 01-DSPAP +apqbo DBoffset F Offset to DB entries 01-DSPAP +apqbo UORTime DS XL12 Time stamp for this UOR 01-DSPAP DS CL8 +apqbo UORPSB PSB name 01-DSPAP +apqbo UORflags DS XL2 01-DSPAP +apqbo DEFBO EQU X'8000' Deferred backout - dynamic 01-DSPAP +* backout failure EQU X'4000' Inflight UOR +apqbo INFLT 01-DSPAP +apqbo INDOU EQU X'2000' Indoubt UOR 01-DSPAP X'1000' BMP UOR +apqbo BMP EQU 01-DSPAP X'0800' BBO identified candidate +apqbo BOCAN EQU 01-DSPAP +apgbo COLDN EQU X'0400' Cold start ended for UOR 01-DSPAP +apgbo BBOK EQU X'0200' Backed out OK by BBO 01-DSPAP +apqbo CMD EQU X'0100' UOR modified by command 01-DSPAP +apqbo BATCH EOU X'0080' Batch IMS UOR 01-DSPAP + DS CI 6 Reserved 01-DSPAP +apqbo RTOKN DS OCL16 Recovery token 01-DSPAP +apqbo RTSSID DS CL8 SSID for this token 01-DSPAP +apgbo UORID DS CL8 Unique UOR ID 01-DSPAP +apqbo DBcount DS F Number of DBs for this UOR 01-DSPAP +apqbo_DBLength DS Н Length of each DB entry 01-DSPAP DS CL2 Reserved 01-DSPAP +apqbo DBent DSECT Database entry 01-DSPAP +apqbo DBname DS CL8 ! Database name 01-DSPAP +apgbo DBflags DS XL1 ! Flags 01-DSPAP EQU X'80' ! UOR backed out for this DB +apgbo DBOUT 01-DSPAP X'40' ! Dyn backout failure this DB +apqbo_DBDEF EQU 01-DSPAP

DSPAPQCA - change accumulation execution block

Example: A-6 DSPAPQCA - change accumulation execution block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
    *****
+**
                                                      ******@ECPYRT*
+*
+*
              DSPAPQCA - CA Execution block
   Name:
+*
+*
   Product:
             DBRC Application Programming Interface
+*
+*
   Function:
+*
+*
    This macro maps the Change Accum block returned on the
    DSPAPI FUNC=QUERY TYPE=CAGROUP call.
+*
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apqhd_eyecatcher = 'DSPAPQCA'
+*
      apqhd length = block length
+*
      apqhd_blktype = X'1100' (DSPAPI_BlkType_CA)
+*
      apghd depptr
                      = 0, no dependent block
      apqhd nextptr = pointer to next CA block
+*
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQCA
+*
+*
    Within DSPAPQCA are the following fields which are used to
+*
    access CA member data and the volume information:
+*
+*
      apqca MemberInfo = offset from DSPAPQCA to member list
+*
                         (apqca Member)
+*
      apqca MemberLen = length of each member entry
+*
      apqca MemberCount = number of group members
+*
+*
                       = offset from DSPAPQCA to volume data
      apqca_Volinfo
+*
                          (apqca Vol Data)
+*
+*
    Within the volume data are the following fields which are
+*
    used to access the list of VOLSERs:
+*
+*
      apgca Vol Offset = offset from apgca Vol Data to the list
+*
                         of VOLSERs (apqca VOLSER)
+*
      apqca Vol Length = length of each VOLSER entry
+*
      apqca_Vol_Count = number of VOLSERs
+*
```

+* Notes:			,	*
+*			ŕ	*
+* Dependencies: None	е.		ډ	ł
+*			د	*
+* Restrictions: None	e.		د	k
+*			ł	*
+* Parameters: None.			ډ	
+*			t de la constante de	*
+* External References	5:		*	*
+* Macros: None			د	
+*			*	
+* Modules: None			7	
+* 				
+* Change Activity: +*			- -	
+* Date Ver		D Init		
+*			Description	
+* 2003-10-02 1.0	K730219	nas	Prolog update	k
+*	KZJUZIJ	pus	Horog update	+
+****	*******	******	*******	ł
+DSPAPQCA	DSECT		CA Execution block	01-DSPAP
+apgca GroupName	DS	CL8	Group name	01-DSPAP
+apqca Memberinfo	DS	F	Offset to group member list	01-DSPAP
+apqca MemberLen	DS	Н	Length of each member entry	01-DSPAP
+apqca_MemberCount	DS	Н	Number of group members	01-DSPAP
+apqca_Volinfo	DS	F	Offset to volume information	01-DSPAP
+	DS	F	Reserved	01-DSPAP
+apqca_DSN	DS	CL44	Data set name	01-DSPAP
+apqca_StopTime	DS	XL12	Packed decimal date/time - for	01-DSPAP
+*			predefined datasets, represents	
+*			record creation time. Otherwise,	
+*			it is the stoptime of the last	
+*			logtape volume used as input to	
+*			the Change Accumulation utility	
+*			that produced this CA as output.	
+* +*			If the CA run included an	
+*			'incomplete log subset' it is the start time of the first	
+*			truncated log volume.	
' +apqca RunTime	DS	XL12	CA run time	01-DSPAP
+apqca_Flags	DS	XL1	Flags	01-DSPAP
+apqca Error	EQU	X'80'	Error on data set	01-DSPAP
+apqca Subset	EQU	X'40'	Subset of logs used for CA	01-DSPAP
+apqca Command	EQU	X'20'	SUBSET/COMP has been set or	01-DSPAP
+*			reset with an external cmd	
+	DS	CL3	Reserved	01-DSPAP
+apqca_Member	DSECT		List of group members	01-DSPAP
+apqca_Mem_DBname	DS	CL8	Database name	01-DSPAP
+apqca_Mem_DDname	DS	0CL8	DD name or	01-DSPAP
+apqca_Mem_Areaname	DS	CL8	AREA name	01-DSPAP
+apqca_Mem_DSSN	DS	F	Data Set sequence number	01-DSPAP
+apqca_Mem_USID	DS	F	USID of last change	01-DSPAP
+*			accumulated	
+apqca_Mem_LRID	DS	XL8	LRID of last change	01-DSPAP
+*	DC.	VI 10	accumulated	01 00040
+apqca_Mem_PurgeTime	DS	XL12	Purge time	01-DSPAP
+apqca_Mem_LSN	DS	XL6	Lock sequence number	01-DSPAP
+apqca_Mem_Flags	DS	XL1	Member flags	01-DSPAP
+apqca_Mem_NoChg	EQU	X'80'	No changes accumulated	01-DSPAP
+apqca_Mem_Indoubt	EQU	X'40'	Indoubt EEQEs accumulated	01-DSPAP

+apgca Mem Incomp	EQU	X'20'	Incomplete CA	01-DSPAP
+	DS	CL5	Reserved	01-DSPAP
+apqca_Vol_Data	DSECT		Volume data	01-DSPAP
+apqca_Vol_FileSeq	DS	Н	File sequence number	01-DSPAP
+apqca_Vol_Unit	DS	CL8	Unit type	01-DSPAP
+apqca_Vol_Count	DS	Н	Number of VOLSERs defined	01-DSPAP
+apqca_Vol_Used	DS	Н	Number of VOLSERs used	01-DSPAP
+apqca_Vol_Length	DS	Н	Length of each VOLSER	01-DSPAP
+apqca_Vol_Offset	DS	F	Offset to VOLSER information	01-DSPAP
+	DS	CL4	Reserved	01-DSPAP
+	DSECT			01-DSPAP
+apqca VOLSER	DS	CL6	List of VOLSERs	01-DSPAP
+****	*****	******	*******	
+* END OF DSPAPQCA			*	

DSPAPQCG - change accumulation group block




Figure A-2 CAGROUP output

Example: A-7 DSPAPQCG - change accumulation group block

+~~	**************************************	I *
+*		*
+*	Licensed Materials - Property of IBM	*
+*		*
+*	5655-J38	*
+*		*
+*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*		*
+*	US Government Users Restricted Rights - Use, duplication or	*

```
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
+*
+*
   Name:
              DSPAPQCG - CA Group block
+*
+*
   Product:
             DBRC Application Programming Interface
+*
+*
   Function:
+*
+*
    This macro maps the CA Group block returned on the
+*
    DSPAPI FUNC=QUERY TYPE=CAGROUP call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apqhd_eyecatcher = 'DSPAPQCG'
+*
      apqhd length = block length
      apqhd_blktype = X'OFOO' (DSPAPI_BlkType_CAGROUP)
apqhd_depptr = pointer to CA Execution block (DSPAPQCA)
apqhd_nextptr = pointer to next CA Group block
+*
+*
+*
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQCG
+*
+*
    Within DSPAPQCG are the following fields which are used to
+*
    access CA Group member data:
+*
      apqcg MemberInfo = offset from DSPAPQCG to member list
+*
+*
                         (apqcg Member)
+*
      apqcg_MemberLen = length of each member entry
+*
      apqcg MemberCount = number of group members
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
   External References:
+*
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
             Ver PTM/APAR Init Description
+*
     ------
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+****
+DSPAPQCG
                      DSECT
                                   CA Group block
                                                                    01-DSPAP
+apqcg_GroupName
                     DS CL8
                                   Group name
                                                                    01-DSPAP
                     DS F
+apqcg Memberinfo
                                   Offset to group member list
                                                                    01-DSPAP
                      DS H
+apqcg_MemberLen
                                   Length of group member entry
                                                                    01-DSPAP
                          Н
+apqcg_MemberCount
                      DS
                                   Number of group members
                                                                    01-DSPAP
+
                       DS
                            2F
                                   Reserved
                                                                    01-DSPAP
                       DS
                            Н
                                   Maximum number of CAs that may
                                                                    01-DSPAP
+apqcg_GrpMax
                                   be predefined for this CA group
```

+apqcg_AvailCA# +*	DS	Н	Number of available CA data sets for this group	01-DSPAP
+apqcg_UsedCA#	DS	Н	Number of used CA data sets	01-DSPAP
+apqcg_Flags	DS	XL1	Flags	01-DSPAP
+apqcg_Reuse	EQU	X'80'	Reuse CA data sets	01-DSPAP
+	DS	CL1	Reserved	01-DSPAP
+apqcg_CAJCL	DS	CL8	GENJCL CAJCL member name	01-DSPAP
+apqcg_DFJCL	DS	CL8	DEFLTJCL member name	01-DSPAP
+apqcg_Member	DSECT		List of group members	01-DSPAP
+apqcg_DBname	DS	CL8	Database name	01-DSPAP
+apqcg_DDname	DS	0CL8	DD name or	01-DSPAP
+apqcg_Areaname	DS	CL8	AREA name	01-DSPAP
+*****	*****	******	*****	
+* END OF DSPAPQCG			*	

DSPAPQDB - full function database block




Figure A-3 Non-HALDB full function output

Example: A-8 DSPAPQDB - full function database block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
         **********************************
                                                   *****@ECPYRT*
+*
+*
+*
   Name:
             DSPAPQDB - Full Function DB block
+*
+*
   Product:
            DBRC Application Programming Interface
+*
+*
   Function:
```

```
+*
+*
    This macro maps the Full Function DB output block returned
+*
    on the DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQDB'
+*
      apphd length = block length
      apqhd_blktype = X'1800' (DSPAPI_BlkType_IMSDB)
+*
      apqhd_depptr = pointer to DBDS block (DSPAPQDS
apqhd_nextptr = pointer to next database block
+*
                     = pointer to DBDS block (DSPAPQDS)
+*
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQDB
+*
+*
    Within DSPAPQDB are the following fields which are used to
+*
    access the authorized subsystem information for the DB:
+*
+*
      apqdb_SS1ist
                      = offset from DSPAPQDB to SS
+*
                        data (DSPAPQSL)
+*
      apqdb SSEntLen
                      = length of each SS entry
+*
      apqdb SSNUM
                      = number of authorized subsystems
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
               Ver
                     PTM/APAR Init Description
+*
     _____
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
DSECT
                                   Full Function DB block
+DSPAPODB
                                                                    01-DSPAP
                       DS CL8
+apqdb DBname
                                   Database name
                                                                    01-DSPAP
+apqdb SSlist
                       DS
                             F
                                   Offset to SS list (DSPAPQSL),
                                                                    01-DSPAP
+*
                                   zero is no SS auth'd
                       DS
                             3F
                                   Reserved
                                                                    01-DSPAP
+
+apqdb_IRCNT
                       DS
                             Н
                                   IC receive needed counter
                                                                    01-DSPAP
+apqdb AUFLAG
                       DS
                             XL1
                                   Authorization flags
                                                                    01-DSPAP
+apqdb BKFLG
                       EQU X'80'
                                   Backout needed flag
                                                                    01-DSPAP
+apqdb PAFLG
                       EQU
                             X'40'
                                   Prohibit authorization
                                                                    01-DSPAP
+apgdb RDFLG
                       EQU
                             X'20'
                                   Read only SS auth
                                                                    01-DSPAP
+apqdb NONRV
                             X'10'
                                   Non-recoverable
                       EQU
                                                                    01-DSPAP
+apqdb IRLMAU
                       DS
                             CL5
                                   IRLMID of auth SS
                                                                    01-DSPAP
                                   Recovery needed count
+apqdb RCVCTR
                       DS
                            Н
                                                                    01-DSPAP
                      DS H
+apqdb_ICCTR
                                   IC needed count
                                                                    01-DSPAP
                            Н
                                   IC recommended counter
+apqdb ICRecCtr
                      DS
                                                                    01-DSPAP
+apqdb SHRLVL
                       DS
                            FL1
                                   Share level of DB
                                                                    01-DSPAP
+apqdb HELDAU
                       DS
                             FL1
                                   Held auth state
                                                                    01-DSPAP
                       EQU X'80' High order bit flag
+apqdb_HAUBIT
                                                                    01-DSPAP
```

+apqdb_DMBNUM	DS	Н	Global DMB number	01-DSPAP
+apqdb_SSNUM	DS	Н	# of SS auth DB	01-DSPAP
+apqdb_SSEntLen	DS	Н	Length of each SS entry	01-DSPAP
+apqdb_CACCSS	DS	FL1	Access state for chg auth	01-DSPAP
+apqdb_CANCDD	DS	FL1	Encode state for chg auth	01-DSPAP
+apqdb_CAHELD	DS	FL1	Held state for chg auth	01-DSPAP
+	DS	CL3	Reserved	01-DSPAP
+apqdb_EQECNT	DS	Н	Total EQE count	01-DSPAP
+apqdb_RSRFLG	DS	XL2	Flags	01-DSPAP
+apqdb_RCVTRK	EQU	X'8000	' Recovery level tracking	01-DSPAP
+apqdb_TRKSPN	EQU	X'4000	' Tracking is suspended	01-DSPAP
+apqdb_PURBIT	EQU	X'2000	' Suspended by time	01-DSPAP
+apqdb_ICNDIS	EQU	X'1000	' IC needed disabled option	01-DSPAP
+apqdb_GSGname	DS	CL8	Global Service Group name	01-DSPAP
+apqdb_USID	DS	F	Last alloc USID	01-DSPAP
+apqdb_AUSID	DS	F	Last authorized USID	01-DSPAP
+apqdb_RUSID	DS	F	Last received USID	01-DSPAP
+apqdb_HUSID	DS	F	Hardened by tracker USID	01-DSPAP
+apqdb_RNUSID	DS	F	Receive needed USID	01-DSPAP
+apqdb_RecovGrp	DS	CL8	Recovery Group name	01-DSPAP
+	DS	CL4	Reserved	01-DSPAP
+****	******	******	*******	
+* END OF DSPAPQDB			*	
+*****	*****	******	****	

DSPAPQDG - DBDS, database, and recovery group block




Figure A-4 DBDS, DB, and recovery group output

Example: A-9 DSPAPQDG - DBDS, database, and recovery group block	Example: A-9	DSPAPQDG - I	DBDS, database,	and recovery	group block
--	--------------	--------------	-----------------	--------------	-------------

+**	**************************************	*
+*		*
+*	Licensed Materials - Property of IBM	*
+*		*
+*	5655-J38	*
+*		*
+*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*		*
+*	US Government Users Restricted Rights - Use, duplication or	*
+*	disclosure restricted by GSA ADP Schedule contract with	*

```
IBM Corp.
+*
+*
+*
+*
    Name:
              DSPAPQDG - DBDS, Database, and Recovery Group block
+*
+*
    Product:
             DBRC Application Programming Interface
+*
+*
    Function:
+*
+*
     This macro maps the DBDS, Database, and Recovery Group output
+*
     blocks returned on the DSPAPI FUNC=QUERY TYPE=DBDSGROUP
+*
     DBGROUP | RECOVGROUP call.
+*
+*
     The header of this block is mapped by DSPAPQHD which contains
+*
     the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQDG'
+*
      apqhd length = block length
                      = X'1600' (DSPAPI_B1kType_DBDSGRP)
+*
      apqhd_blktype
+*
                        X'1601' (DSPAPI_B1kType_DBGRP)
                        X'1602' (DSPAPI_B1kType_RECOVGRP)
+*
+*
      apghd depptr
                      = 0, no dependent block
+*
      apqhd nextptr
                      = pointer to next group block
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQDG
+*
+*
     Within DSPAPQDG are the following fields which are used to
+*
     access group member data:
+*
+*
      apqdg_MemberInfo = offset from DSPAPQDG to member list
+*
                         (apqdg Member)
+*
      apqdg_MemberLen = length of each member entry
+*
      apqdg MemberCount = number of group members
+*
+*
    Notes:
+*
+*
     Dependencies: None.
+*
+*
     Restrictions: None.
+*
    Parameters: None.
+*
+*
+*
    External References:
+*
      Macros: None
+*
+*
     Modules: None
+*
+*
    Change Activity:
+*
+*
      Date
                Ver PTM/APAR Init Description
+*
      +*
      2003-10-02 1.0 KZ30219 pas Prolog update
+*
+DSPAPQDG
+apqdg_GroupName DS CL8
+apqdg_Memberinfo DS F
+apqdg_MemberLen DS H
______ MomberCount DS H
_____ 2F
                     DSECT
                                   DBDS, DB, and Recov Group block 01-DSPAP
                     DS CL8
                                   Group name
                                                                   01-DSPAP
                                   Offset to group member list
                                                                   01-DSPAP
                                   Length of group member entry
                                                                   01-DSPAP
                                   Number of group members
                                                                   01-DSPAP
+
                       DS
                             3F
                                   Reserved
                                                                   01-DSPAP
```

+	DS	CL4	Reserved		01-DSPAP
+apqdg_Member	DSECT		List of group members		01-DSPAP
+apqdg_DBDSG	DS	0CL16	DBDS group		01-DSPAP
+apqdg_DBDSG_DBname	DS	CL8	Database name		01-DSPAP
+apqdg_DBDSG_DDname	DS	0CL8	DD name or		01-DSPAP
+apqdg_DBDSG_Areaname	DS	CL8	AREA name		01-DSPAP
+	ORG	apqdg_	DBDSG		01-DSPAP
+apqdg_DBG	DS	0CL16	DB group		01-DSPAP
+apqdg_DBG_DBname	DS	0CL8	Database name or		01-DSPAP
+apqdg_DBG_Areaname	DS	CL8	AREA name		01-DSPAP
+	DS	CL8	Not used		01-DSPAP
+	ORG	apqdg_	DBDSG		01-DSPAP
+apqdg_RecovG	DS	0CL16	Recovery group		01-DSPAP
+apqdg_RecovG_DBname	DS	CL8	Database name		01-DSPAP
+apqdg_RecovG_Areaname	DS	CL8	AREA name, null if not	Fast Path	01-DSPAP
+****	*****	******	*******	******	
+* END OF DSPAPQDG				*	

DSPAPQDS - database data set block




Figure A-5 DSPAPQDS database data set block

Example: A-10 DSPAPQDS - database data set block

+*************************************	SCPYRT*
+*	*
+* Licensed Materials - Property of IBM	*
+*	*
+* 5655-J38	*
+*	*
+* (C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*	*
+* US Government Users Restricted Rights - Use, duplication or	*
+* disclosure restricted by GSA ADP Schedule contract with	*
+* IBM Corp.	*
+*	*
+**************************************	ECPYRT*
+*	*

```
+*
   Name:
             DSPAPQDS - Database Data Set (DBDS) block
+*
+*
   Product:
             DBRC Application Programming Interface
+*
+*
   Function:
+*
+*
    This macro maps the DBDS output block returned on the
+*
    DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apqhd eyecatcher = 'DSPAPQDS'
+*
      apphd length = block length
+*
      apqhd blktype = X'2000' (DSPAPI BlkType DBDS)
+*
      apqhd depptr
                     = pointer to Recovery Information
+*
                       block (DSPAPQRI)
+*
      apqhd_nextptr
                     = pointer to next DBDS block
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQDS
+*
+*
    Within DSPAPQDS are the following fields which are used to
+*
    access EEQE information for the DBDS:
+*
      apqds_EEQElist = offset from DSPAPQDS to EEQE
+*
+*
                       data (DSPAPQEL)
+*
      apqds EEQELength = length of each EEQE entry
+*
      apqds EEQECount = number of EEQEs
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
               Ver PTM/APAR Init Description
     Date
+*
     ----- -----
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
DSECT
+DSPAPODS
                                  Database Data Set (DBDS) block
                                                                  01-DSPAP
                    DS CL8
+apqds_DBname
                                  Database name
                                                                  01-DSPAP
+apqds DDname
                    DS CL8
                                  DD name
                                                                  01-DSPAP
+apqds EEQElist
                    DS F
                                  Offset to EEQE list (DSPAPQEL),
                                                                  01-DSPAP
+*
                                  zero if no EEQEs
+
                      DS
                            3F
                                  Reserved
                                                                  01-DSPAP
                                  Data set name
                                                                  01-DSPAP
+apqds DSN
                      DS CL44
+apqds_RTPRD
                          Н
                     DS
                                  IC retention period
                                                                  01-DSPAP
+apqds DSID
                      DS
                            Н
                                  Data set ID number
                                                                  01-DSPAP
+apqds DSSN
                      DS
                            F
                                  Data set sequence number
                                                                  01-DSPAP
+apqds_RUSID
                      DS
                            F
                                  Recovered-to USID(trkr)
                                                                  01-DSPAP
+apqds_FLAGS
                      DS
                            XL1
                                                                  01-DSPAP
```

+apqds RECYC	EQU	X'80'	REUSE image copies	01-DSPAP
+apqds ICREC	EQU	X'40'	Image Copy Recommended	01-DSPAP
+apqds_RCVRQ	EQU	X'20'	Receive required	01-DSPAP
+apqds IC	EQU	X'10'	Image Copy Needed	01-DSPAP
+apqds RECOV	EQU	X'08'	Recovery Needed	01-DSPAP
+apqds_NONRV	EQU	X'00'	Non-recoverable	01-DSPAP
+apqds_DSORG	DS	X 04 XL1	Data set organization	01-DSPAP
+apqds_VSAM	EQU	X'80'	1 = VSAM, 0 = NON-VSAM	01-DSPAP
+apqds INDEX	EQU	X'40'	0 = Non-indexed (OSAM or ESDS),	01-DSPAP
+*	LŲŪ	X 40	1 = Indexed (ISAM or KSDS)	01-D3FAF
+apqds_DBORG	DS	XL1	IMS DB organization	01-DSPAP
+	DS	FL1	Reserved	01-DSPAP
+apqds_GENMX	DS	Н	Max number of ICs that may be	01-DSPAP
+*			predefined for this DBDS	
+apqds_AvailIC#	DS	Н	Number of available ICs for	01-DSPAP
+*			this DBDS	
+apqds_UsedIC#	DS	Н	Number of ICs used	01-DSPAP
+apqds_EEQECount	DS	Н	EEQE count	01-DSPAP
+apqds_EEQELength	DS	Н	EEQE entry length	01-DSPAP
+apqds_FLG1	DS	XL1	Flags	01-DSPAP
+apqds_RRGAL	EQU	X'80'	REORG since last ALLOC,	01-DSPAP
+*			only set if RSR-covered	
+apqds_TSRAL	EQU	X'40'	TS recov since last ALLOC,	01-DSPAP
+*			only set if RSR-covered	
+apqds_FLG2	DS	XL1	DBDS type flags	01-DSPAP
+apqds_Part	EQU	X'80'	TYPEPART record	01-DSPAP
+apqds_PData	EQU	X'40'	TYPEPART subtype DATA	01-DSPAP
+apqds_PILE	EQU	X'20'	TYPEPART subtype ILE	01-DSPAP
+apqds_PIndx	EQU	X'10'	TYPEPART subtype Index	01-DSPAP
+apqds_CAGrpName	DS	CL8	Change Accum group name	01-DSPAP
+apqds_JCL	DS	0CL40	GENJCL members	01-DSPAP
+apqds_ICJCL	DS	CL8	Image copy member	01-DSPAP
+apqds_0IJCL	DS	CL8	Online IC member	01-DSPAP
+apqds_RCJCL	DS	CL8	Recovery member	01-DSPAP
+apqds_DFJCL	DS	CL8	DEFLTJCL member	01-DSPAP
+apqds_RVJCL	DS	CL8	Receive JCL member	01-DSPAP
+apqds_ODDN	DS	CL8	OLR partner DBDS	01-DSPAP
+****	*****	******	****	
+* END OF DSPAPQDS			*	
+****	*****	******	***************************************	

DSPAPQEL - EEQE list

Example: A-11 DSPAPQEL - EEQE list

+*************************************	CPYRT*
+*	*
+* Licensed Materials - Property of IBM	*
+*	*
+* 5655-J38	*
+*	*
+* (C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*	*
+* US Government Users Restricted Rights - Use, duplication or	*
+* disclosure restricted by GSA ADP Schedule contract with	*
+* IBM Corp.	*
+*	*
+*************************************	CPYRT*
+*	*

```
+*
            DSPAPQEL - EEQE List
   Name:
+*
+*
   Product:
            DBRC Application Programming Interface
+*
+*
   Function:
+*
+*
    This macro maps the EEQE List portion of the DBDS or Area
+*
    blocks returned on the DSPAPI FUNC=QUERY TYPE=DB call. Refer
+*
    to the DBDS or Area blocks - DSPAPQDS or DSPAPQAR - for more
+*
    information on accessing the EEQE list.
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
    Macros: None
+*
+*
    Modules: None
+*
+*
   Change Activity:
+*
+*
    Date
              Ver PTM/APAR Init Description
+*
     -----
            +*
    2003-10-02 1.0 KZ30219 pas Prolog update
+*
DSECT EEQE List block
+DSPAPQEL
                                                            01-DSPAP
+apqel_EEQEentryDSOCL13EEQEDS control+apqel_eqefgDSXL1EEQE flags+apqel_ertlEQUX'80'Toleration error
                                                            01-DSPAP
                                                            01-DSPAP
                                                            01-DSPAP
+apgel_errd
                  EQU X'40'
                               Read error
                                                            01-DSPAP
+apqel_erwt
                   EQU X'20' Write error
                                                            01-DSPAP
                    EQU X'10' DBRC user modified
+apgel_erus
                                                            01-DSPAP
+apgel erpm
                    EQU
                        X'08'
                               DBRC permanent error
                                                            01-DSPAP
+apgel indt
                   EQU X'04'
                               Indoubt EEQE
                                                            01-DSPAP
                   EQU X'02' Index CI indicator
+apgel ciind
                                                            01-DSPAP
+apqel_EQE
                   DS XL4
                               EEQE
                                                            01-DSPAP
+apgel SSID
                    DS CL8
                               SSID which owns the EEQE
                                                            01-DSPAP
+* END OF DSPAPQEL
```

DSPAPQFD - DEDB database block




Figure A-6 Fast Path (DEDB) output

Example: A-12 DSPAPQFD - Fast Path DEDB block

+**************@SCPYRT**@SC	PYRT*
+*	*
+* Licensed Materials - Property of IBM	*
+*	*
+* 5655-J38	*
+*	*
+* (C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*	*
+* US Government Users Restricted Rights - Use, duplication or	*
+* disclosure restricted by GSA ADP Schedule contract with	*
+* IBM Corp.	*
+*	*
+*************************************	PYRT*
+*	*
+* Name: DSPAPQFD - Fast Path DEDB block	*
+*	*
+* Product: DBRC Application Programming Interface	*
+*	*
+* Function:	*
+*	*
+* This macro maps the Fast Path DEDB output block returned on	*
+* the DSPAPI FUNC=QUERY TYPE=DB call.	*
+*	*
+* The header of this block is mapped by DSPAPQHD which contains	*
+* the following information:	*
+*	*
+* apqhd_eyecatcher = 'DSPAPQFD'	*
+* apqhd_length = block length	*
+* apqhd_blktype = X'1802' (DSPAPI_BlkType_FPDEDB)	*

```
+*
      apqhd depptr
                     = pointer to Fast Path Area block
+*
                       (DSPAPQAR)
+*
      apghd nextptr
                     = pointer to next database block
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQFD
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
               Ver
                    PTM/APAR Init Description
+*
                    -----
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
     2004-03-04 1.01 PQ83837 pas Add user-recoverable flag
+*
+DSPAPQFD
                      DSECT
                                  Fast Path DEDB block
                                                                 01-DSPAP
+apqfd DBname
                      DS
                           CL8
                                  Database name
                                                                 01-DSPAP
                           4F
                                  Reserved
                                                                 01-DSPAP
+
                      DS
+apqfd_RCVCTR
                      DS
                           Н
                                  Recovery Needed Counter
                                                                 01-DSPAP
+apqfd ICCTR
                      DS
                                  IC Needed Counter
                           Н
                                                                 01-DSPAP
+apqfd_ICRecCtr
                      DS
                                  IC Recommended Counter
                           Н
                                                                 01-DSPAP
+apqfd DMBNUM
                      DS
                           Н
                                  Global DMB number
                                                                 01-DSPAP
+apqfd EQECNT
                      DS
                           Н
                                  Total EEQE count
                                                                 01-DSPAP
+apqfd_AuthdAreas
                      DS
                           Н
                                  Number of Areas authorized
                                                                 01-DSPAP
                           FL1
+apqfd_SHRLVL
                      DS
                                  Share Level
                                                                 01-DSPAP
+apqfd Flags
                      DS
                           XL1
                                  Flags
                                                                 01-DSPAP
                      EQU
                          X'80' Prohibit authorization
+apqfd_PAFLG
                                                                 01-DSPAP
+apqfd NONRV
                      EQU
                           X'40'
                                  Non-recoverable
                                                                 01-DSPAP
+apqfd ICNDIS
                      EQU
                           X'20'
                                  IC needed disabled option
                                                                 01-DSPAP
+apqfd USRRV
                      EQU
                           X'10'
                                  User-recoverable (VERSION=1.01)
                                                                 01-DSPAP
+*
                                                         @P083837
     *****
+**
                                                          *******
   END OF DSPAPQFD
+*
```

DSPAPQGG - global service group block





Figure A-7 Global service group


```
Example: A-13 DSPAPQGG - global service group block
```

```
+*
+*
   Licensed Materials - Property of IBM
+*
   5655-J38
+*
+*
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
   disclosure restricted by GSA ADP Schedule contract with
+*
+*
   IBM Corp.
+*
              +**
+*
             DSPAPQGG - Global Service Group block
+*
   Name:
+*
+*
   Product:
            DBRC Application Programming Interface
+*
+*
   Function:
+*
    This macro maps the Global Service Group output block
+*
+*
    returned on the DSPAPI FUNC=QUERY TYPE=GSGROUP call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQGG'
+*
      apqhd_length = block length
+*
      apqhd blktype = X'3A00' (DSPAPI BlkType GSG)
+*
      apqhd depptr = 0, no dependent block
+*
      apqhd nextptr
                     = pointer to next group block
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQGG
+*
+*
    Within DSPAPQGG are the following fields which are used to
+*
    access group member data:
+*
```

```
+*
      apqgg MemberInfo = offset from DSPAPQGG to member list
+*
                         (apqgg_Member)
+*
      apqgg MemberLen = length of each member entry
+*
      apgg MemberCount = number of group members
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
               Ver PTM/APAR Init Description
+*
     ----- -----
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
+DSPAPQGG
                                   Global Service Group block
                                                                    01-DSPAP
                       DSECT
+apqgg GroupName
                       DS CL8
                                   Group name
                                                                    01-DSPAP
+apqgg Memberinfo
                       DS
                            F
                                   Offset to group member list
                                                                    01-DSPAP
                       DS
                            Н
                                   Length of group member entry
+apqgg_MemberLen
                                                                    01-DSPAP
+apqgg_MemberCount
                      DS
                            Н
                                   Number of group members
                                                                    01-DSPAP
                       DS
+
                            2F
                                   Reserved
                                                                    01-DSPAP
                       DS
                            F
                                   SLDS DSN sequence number
+apqgg_SDSN#
                                                                    01-DSPAP
+apqgg_PToken
                       DS
                            F
                                   Current PRILOG token
                                                                    01-DSPAP
+apqgg_MPTOK
                       DS
                            F
                                   Min required PRILOG token
                                                                    01-DSPAP
+apqgg_TTOKN
                       DS
                            F
                                   Planned takeover token
                                                                    01-DSPAP
                            XL12
+apqgg_LOGTime
                       DS
                                   Current log start time
                                                                    01-DSPAP
+apqgg_HiTime
                       DS
                            XL12
                                   Highest time ever received
                                                                    01-DSPAP
+*
                                   from the active site
+apqgg TSname
                       DS
                             CL8
                                   Tracking subsystem ID
                                                                    01-DSPAP
+apqgg Flags
                       DS
                             XL1
                                                                    01-DSPAP
+apqgg_ActTKO
                       EQU
                            X'80'
                                                                    01-DSPAP
                                   Active takeover in progress
+apqgg_1stSignon
                       EQU
                            X'40'
                                   Indicates the first signon of
                                                                    01-DSPAP
+*
                                   an active subsystem after an
+*
                                   RSR takeover
+apqgg_TrkTKO
                       EQU
                            X'20'
                                   Tracker takeover in progress
                                                                    01-DSPAP
+apqgg RESET
                       EQU
                            X'10'
                                   RESET.GSG issued
                                                                    01-DSPAP
                       DS
                             CL7
                                   Reserved
                                                                    01-DSPAP
+apqgg_Member
                       DSECT
                                   List of group members
                                                                    01-DSPAP
+apqgg SGname
                       DS
                            CL8
                                   Service group name
                                                                    01-DSPAP
+apqgg_SGrole
                       DS
                            CL1
                                   Role 'A' OR 'T'
                                                                    01-DSPAP
+apqgg SGflags
                       DS
                            XL1
                                   Flags
                                                                    01-DSPAP
+apqgg_SGlocal
                       EQU
                            X'80'
                                   1 = local SG
                                                                    01-DSPAP
                                                                    01-DSPAP
+
                       DS
                             CL6
                                   Reserved
+****
                      *****
                            *******
+* END OF DSPAPQGG
```

DSPAPQHB - HALDB block





Example: A-14 DSPAPQHB - HALDB block

	· ·	
+**	**************************************	(RT*
+*		*
+*	Licensed Materials - Property of IBM	*
+*		*
+*	5655-J38	*
+*		*
+*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*		*
+*	US Government Users Restricted Rights - Use, duplication or	*
+*	disclosure restricted by GSA ADP Schedule contract with	*
+*	IBM Corp.	*
+*		*
+**	**************************************	(RT*
+*		*
+*	Name: DSPAPQHB - HALDB block	*
+*		*
+*	Product: DBRC Application Programming Interface	*
+*		*
+*	Function:	*
+*		*
+*	This macro maps the HALDB output block returned on the	*
+*	DSPAPI FUNC=QUERY TYPE=DB call.	*
+*		*
+*	The header of this block is mapped by DSPAPQHD which contains	*
+*	the following information:	*
+*	angle averately - IDSDADOUDI	*
+* +*	apqhd_eyecatcher = 'DSPAPQHB'	*
+^ +*	apqhd_length = block length	*
+^ +*	apqhd_blktype = X'1801' (DSPAPI_BlkType_HALDB)	*
т"	apqhd_depptr = pointer to HALDB Partition block	

+* (DSPAPQHP) +* apqhd nextptr = pointer to next database block +* apphd blkoffset = offset from DSPAPQHD to DSPAPQHB +* +* Notes: +* +* Dependencies: None. +* +* Restrictions: None. +* Parameters: None. +* +* +* External References: +* Macros: None +* +* Modules: None +* +* Change Activity: +* +* Date Ver PTM/APAR Init Description +* ----- -----+* 2003-10-02 1.0 KZ30219 pas Prolog update +* DSECT +DSPAPOHB HALDB block 01-DSPAP DS CL8 HALDB name +apqhb_DBname 01-DSPAP DS 4F + Reserved 01-DSPAP +apghb flags DS XL1 Flags 01-DSPAP +apghb NONRV EQU X'80' Non-recoverable 01-DSPAP +apqhb ICNDIS EQU X'40' IC needed disabled 01-DSPAP +apqhb_OLRcap X'20' HALDB is OLR capable EQU 01-DSPAP DB organization +apqhb_Org DS XL1 01-DSPAP +apghb PSINDEX EQU X'80' PSINDEX DB 01-DSPAP +apqhb PHIDAM EQU X'40' PHIDAM DB 01-DSPAP +apqhb_PHDAM EQU X'20' PHDAM DB 01-DSPAP +apqhb_OSAM EQU X'10' OSAM DB 01-DSPAP +apqhb SHRLVL FL1 Share level DS 01-DSPAP +apqhb_DSGCNT DS FL1 # DS Group members 01-DSPAP +apghb DMBNUM DS Н Global DMB number 01-DSPAP +apghb PartID DS Н Current Partition ID 01-DSPAP H H +apghb PART# DS Number of parts in HALDB 01-DSPAP +apqhb_Version# DS Version number 01-DSPAP +apqhb_PSname CL8 Name of Part Sel Routine DS 01-DSPAP DS CL8 +apqhb_GSGname GSG name 01-DSPAP CL8 +apghb RecovGrp DS Recovery Group name 01-DSPAP +* END OF DSPAPOHB +****

DSPAPQHP - HALDB Partition block

Example: A-15 DSPAPQHP - HALDB Partition block

+***	+*************************************						
+*		*					
+*	Licensed Materials - Property of IBM	*					
+*		*					
+*	5655-J38	*					
+*		*					
+*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*					

```
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
+**
         **********@FCPYRT
+*
+*
    Name:
               DSPAPQHP - HALDB Partition block
+*
+*
    Product:
               DBRC Application Programming Interface
+*
+*
    Function:
+*
+*
     This macro maps the HALDB Partition output block returned
+*
     on the DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
     The header of this block is mapped by DSPAPQHD which contains
+*
     the following information:
+*
+*
       apphd eyecatcher = 'DSPAPQHP'
+*
       apphd length = block length
+*
       apqhd blktype
                       = X'1900' (DSPAPI BlkType PART)
+*
                       = pointer to DBDS block (DSPAPQDS)
       apqhd depptr
+*
       apqhd nextptr
                       = pointer to next partition block
+*
       apphd blkoffset = offset from DSPAPQHD to DSPAPQHP
+*
+*
     Within DSPAPQHP are the following fields which are used to
+*
     access the partition high key or string, OSAM data set group
+*
     information, and authorized subsystem information for the
+*
     partition:
+*
+*
       apqhp_keystring
                           = offset from DSPAPQHP to key/string
+*
                             (apqhp_PString)
+*
       apqhp PStLn
                           = length of key/string
+*
       apqhp_DSGInfoOffset = offset from DSPAPQHP to DSG info
+*
+*
                             (apqhp_DSGinfo)
+*
       apghp DSGInfoLen
                           = length of each DSG entry
+*
       apqhp_DSGcnt
                           = number of DSG entries
+*
+*
                           = offset from DSPAPQHP to SS
       apqhp_SSlist
+*
                             data (DSPAPQSL)
+*
       apqhp SSEntLen
                           = length of each SS entry
+*
       apqhp_SSNUM
                           = number of authorized subsystems
+*
    Notes:
+*
+*
+*
     Dependencies: None.
+*
+*
     Restrictions: None.
+*
+*
    Parameters: None.
+*
+*
    External References:
+*
      Macros: None
+*
+*
      Modules: None
+*
+*
    Change Activity:
+*
```

+* +*	Date	Ver I	PTM/APAF	R Init	Deseription	*
	2003-10-02	1.0 H	KZ30219	pas	iiolog upuale	*
+****	*********	******	******	******	*******	*
+DSPAP	QHP		DSECT		HALDB Partition block	01-DSPAP
	_HALDBname		DS	CL8	HALDB name	01-DSPAP
	_Partname		DS	CL8	Partition name	01-DSPAP
+apqhp +*	_SSlist		DS	F	Offset to SS list (DSPAPQSL), zero is no SS auth'd	01-DSPAP
+apqhp +* +*	_keystring		DS	F	Offset to KEYSTRING, apqhp_PString, zero if no key/string	01-DSPAP
+apqhp +*	_DSGInfoOff	set	DS	F	Offset to data set group information	01-DSPAP
+			DS	F	Reserved	01-DSPAP
+apqhp	DSNbase			0CL37	Base Partition DSN	01-DSPAP
+	_		DS	CL44		01-DSPAP
+apqhp	_HDAM		DS	0CL18	PHDAM fields	01-DSPAP
+apqhp	RMName		DS	CL8	Randomizing module name	01-DSPAP
+apqhp	RBN		DS	F	Max relative block number	01-DSPAP
+apqhp	bytes		DS	F	Max # of bytes	01-DSPAP
+apqhp	_anchr		DS	Н	<pre># of root anchor points</pre>	01-DSPAP
+apqhp	_fbff		DS	FL1	Free block frequency factor	01-DSPAP
+apqhp	_fspf		DS	FL1	Free space percentage factor	01-DSPAP
+apqhp	_PartID		DS	H	Partition ID	01-DSPAP
+apqhp +*	_PStLn		DS	Н	Length of Part Key/String, apqhp PString	01-DSPAP
+apqhp +*	_DSGInfoLer	1	DS	Н	Length of each apqhp_DSGinfo entry	01-DSPAP
+apqhp	_DSGcnt		DS	FL1	DSG count	01-DSPAP
+apqhp	_flags		DS	XL1	Flags	01-DSPAP
+apqhp			EQU	X'80'	Partition must be initialized	01-DSPAP
+apqhp	_Ordbds		EQU	X'40'	O=A-J/1=M-V DBDS active	01-DSPAP
+apqhp	_01ron		EQU	X'20'	OLR active	01-DSPAP
+apqhp	_Disab		EQU	X'10'	Partition Disabled	01-DSPAP
+apqhp	_MVdbds		EQU	X'08'	1 = M-V DBDS exist	01-DSPAP
+apqhp +*	_OLRcap		EQU	X'04'	Partition is OLR capable	01-DSPAP
					eys, i.e. no Partition	
					elds are used to sort	
+* the +*	partitions	; in key	/ sequer	nce.		
+apqhp	_prev		DS	CL8	DDN of previous partition	01-DSPAP
+apqhp			DS	CL8	DDN of next partition	01-DSPAP
+apqhp	_OLRIMS		DS	CL8	Owning IMS for OLR	01-DSPAP
	_IRCNT		DS	Н	IC receive needed counter	01-DSPAP
+apqhp	_AUFLAG		DS	XL1	Authorization flags	01-DSPAP
	_BKFLG		EQU	X'80'	Backout needed	01-DSPAP
	_PAFLG		EQU	X'40'	Prohibit authorization	01-DSPAP
+apqhp	_RDFLG		EQU	X'20'	Read only SS auth	01-DSPAP
+apqhp	-		EQU	X'10'	Non-recoverable	01-DSPAP
	_IRLMAU		DS	CL5	IRLM ID of auth SS	01-DSPAP
	_RCVCTR		DS	Н	Recovery needed count	01-DSPAP
	_ICCTR		DS	Н	IC needed count	01-DSPAP
+apqhp	_SHRLVL		DS	FL1	Share level of DB	01-DSPAP
+apqhp	_HELDAU		DS	FL1	Held auth state	01-DSPAP
+apqhp	_HAUBIT		EQU	X'80'	High order bit flag	01-DSPAP
	_DMBNUM		DS	Η	Global DMB number	01-DSPAP
+apqhp	_SSNUM		DS	Н	# of SS auth DB	01-DSPAP

+apqhp_SSEntLen	DS	Н	Length of each SS entry	01-DSPAP
+apghp CACCSS	DS	FL1	Access state for chg auth	01-DSPAP
+apqhp CANCDD	DS	FL1	Encode state for chg auth	01-DSPAP
+apqhp CAHELD	DS	FL1	Held state for chg auth	01-DSPAP
+	DS	CL1	Reserved	01-DSPAP
+apqhp EQECNT	DS	Н	Total EQE count	01-DSPAP
+apqhp_RSRFLG	DS	XL2	Flags	01-DSPAP
+apqhp_RCVTRK	EQU	X'8000	' Only recov level trackng	01-DSPAP
+apghp TRKSPN	EQU	X'4000	' Tracking is suspended	01-DSPAP
+apghp_PURBIT	EQU		' Suspended by time	01-DSPAP
+apqhp ICNDIS	EQU	X'1000	' IC needed disabled option	01-DSPAP
+apghp NoHKey	EQU	X'0800	' High key required	01-DSPAP
+apqhp_GSGname	DS	CL8	GSG name	01-DSPAP
+apqhp_USID	DS	F	Last alloc USID	01-DSPAP
+apqhp AUSID	DS	F	Last authorized USID	01-DSPAP
+apqhp_RUSID	DS	F	Last received USID	01-DSPAP
+apqhp_HUSID	DS	F	Hardened by tracker USID	01-DSPAP
+apqhp_RNUSID	DS	F	Receive needed USID	01-DSPAP
+apqhp ICRecCtr	DS	Н	IC Recommended Counter	01-DSPAP
+apqhp_Version#	DS	Н	Version number	01-DSPAP
+apqhp_OLRActHardCtr	DS	FL1	OLR curs active count	01-DSPAP
+apqhp_OLRInactHardCtr	DS	FL1	OLR curs inact count	01-DSPAP
+apqhp_Reorg#	DS	Н	Partition reorg #	01-DSPAP
+apqhp_DSGinfo	DSECT		Data set group information	01-DSPAP
+apqhp_BLKSZ	DS	Н	DS block size, OSAM only	01-DSPAP
+	DSECT			01-DSPAP
+apqhp_PString	DS	00	Partition Key/String	01-DSPAP
	******	*******	***************************************	
+* END OF DSPAPQHP			*	
+****	******	******	********	

DSPAPQIC - image copy block

Example: A-16 DSPAPQIC - image copy block

+**	**************************************	YRT*
+*		*
+*	Licensed Materials - Property of IBM	*
+*		*
+*	5655-J38	*
+*		*
+*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*		*
+*	US Government Users Restricted Rights - Use, duplication or	*
+*	disclosure restricted by GSA ADP Schedule contract with	*
+*	IBM Corp.	*
+*		*
	**************************************	YRT*
+*		*
+*	Name: DSPAPQIC - Image Copy block	*
+*		*
+*	Product: DBRC Application Programming Interface	*
+*		*
+*	Function:	*
+*		*
+*	This macro maps the Image Copy (IC) output block returned on	*
+*	the DSPAPI FUNC=QUERY TYPE=DB call.	*
+*		*
+*	The header of this block is mapped by DSPAPQHD which contains	*

```
+*
     the following information:
+*
+*
       apqhd_eyecatcher = 'DSPAPQIC'
+*
       apphd length = block length
+*
       apqhd blktype = X'2D00' (DSPAPI BlkType IC)
+*
       apphd depptr = 0, no dependent blocks
       apqhd nextptr = pointer to next IC block
+*
+*
       apqhd blkoffset = offset from DSPAPQHD to DSPAPQIC
+*
+*
     Within DSPAPQIC are the following fields which are used to
+*
     access the primary/secondary IC data or the User IC data.
+*
+*
     For non-User ICs (Batch, SMS, etc.):
+*
+*
       appic OFF1 = offset from DSPAPQIC to IC1 data (appic IC12)
+*
       appic OFF2 = offset from DSPAPQIC to IC2 data (appic IC12),
+*
                     if applicable
+*
       apqic_Len12 = length of IC1/IC2 data
+*
+*
       Within the IC1/IC2 data block (apqic_IC12) are the
+*
       following fields which are used to access the volume
+*
       information for the IC data set:
+*
+*
         apqic_VolListOffset = offset from apqic_IC12 to volume
+*
                              list data (apqic VOLS)
+*
                             = length of each volume list entry
         apqic VolListLen
+*
         apqic VOLCT
                            = number of volumes
+*
+*
     For User ICs (apqic_UserIC):
+*
+*
       appic OFFU = offset from DSPAPQIC to User IC data
+*
                    (apqic User)
+*
       appic LenU = length of User IC data
+*
+*
    Notes:
+*
+*
     Dependencies: None.
+*
+*
     Restrictions: None.
+*
+*
    Parameters: None.
+*
+*
    External References:
      Macros: None
+*
+*
+*
      Modules: None
+*
+*
    Change Activity:
+*
+*
      Date
                 Ver PTM/APAR Init Description
+*
      +*
      2003-10-02 1.0 KZ30219 pas Prolog update
+*
+apqic_DBnameDSCL8Database name+apqic_DDnameDSOCL8DD name or+apqic_AreanameDSCL8Area name+apqic_startimeDSXL12IC start time, packed decimal+apqic_stoptimeDSXL12IC stop time_packed docimal
                                                                         01-DSPAP
                                                                         01-DSPAP
                                                                         01-DSPAP
                                                                         01-DSPAP
                                                                         01-DSPAP
                                                                         01-DSPAP
```

Langia TVDE	DC	VI 1	Image Conv. tune	
+apqic_TYPE +apqic BATCH	DS EQU	XL1 X'80'	Image Copy type Batch	01-DSPAP 01-DSPAP
· · · -	EQU	x ou X'40'	Concurrent	01-DSPAP
+apqic_CIC +apqic UserIC	EQU	x 40 X'20'		01-DSPAP
		X'20' X'10'	User Image Copy	
+apqic_online	EQU		Online	01-DSPAP
+apqic_SMSIC	EQU	X'08'	SMS IC w/ DB exclusive	01-DSPAP
+apqic_SMSCC	EQU	X'04'	SMS IC w/ DB shared	01-DSPAP
+apqic_status	DS	XL1	IC status flags	01-DSPAP
+apqic_AVAIL	EQU	X'80'	Available IC	01-DSPAP
+apqic_IC1	EQU	X'40'	Image Copy 1 exists	01-DSPAP
+apqic_IC2	EQU	X'20'	Image Copy 2 exists	01-DSPAP
+apqic_ERR1	EQU	X'10'	Error on image 1	01-DSPAP
+apqic_ERR2	EQU	X'08'	Error on image 2	01-DSPAP
+apqic_EMP2	EQU	X'04'	Image 2 defined and unused	01-DSPAP
+apqic_FLAGS	DS	XL1		01-DSPAP
+apqic_HSINP	EQU	X'80'	HSSP CIC in progress	01-DSPAP
+apqic_CAT	EQU	X'40'	Catalogued IC (HSSP)	01-DSPAP
+	DS	CL1	Reserved	01-DSPAP
+apqic OFF1	DS	OH	Offset to image 1 data	01-DSPAP
+apqic OFFU	DS	Н	Offset to user IC data	01-DSPAP
+apgic OFF2	DS	Н	Offset to image 2 data	01-DSPAP
+apgic CNT12	DS	F	Record count	01-DSPAP
+apqic USID	DS	F	Update set ID	01-DSPAP
+apqic Len12	DS	OH	Length of image 1/2 data	01-DSPAP
+apqic LenU	DS	Н	Length of user IC data	01-DSPAP
+	DS	CL6	Reserved	01-DSPAP
+apqic IC12	DSECT		Data for image 1 or 2	01-DSPAP
+apqic DSN12	DS	CL44	Data set name	01-DSPAP
+apqic FILE	DS	H	File sequence number	01-DSPAP
+apqic RUT12	DS	CL8	Unit device type	01-DSPAP
+apqic VOLCT	DS	H	# of volumes predefined	01-DSPAP
+apqic_VOLUS	DS	Н	# of volumes used	01-DSPAP
+apqic VolListLen	DS	Н	Length of each volume list	01-DSPAP
+*	03		entry in appic VOLS	01-DJFAF
' +apqic_VolListOffset	DS	F	Offset to volume list	01-DSPAP
+	DSECT		offset to volume fist	01-DSPAP
	DSECT	CL6	List of VOLSERs	01-DSPAP 01-DSPAP
+apqic_VOLS	DSECT			
+apqic_User			Data for user IC	01-DSPAP
+apqic_UData	DS	CL80	User supplied data	01-DSPAP
+*************************************				
+* END OF DSPAPQIC * +***********************************				
+ * * * * * * * * * * * * * * * * * * *				

DSPAPQLA - log allocation block




Figure A-9 LOGALL output

Example: A-17 DSPAPQLA - log allocation block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
        +**
+*
+*
             DSPAPQLA - Log Allocation block
   Name:
+*
   Product:
             DBRC Application Programming Interface
+*
   Function:
+*
+*
    This macro maps the Log Allocation output block returned on
+*
    the DSPAPI FUNC=QUERY TYPE=LOG call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apqhd_eyecatcher = 'DSPAPQLA'
+*
      apqhd_length = block length
      apqhd_blktype = X'0700' (DSPAPI_BlkType_LOGALL)
+*
+*
      apghd depptr
                    = 0, no dependent blocks
      apqhd_nextptr
+*
                     = 0, no next block
+*
      apqhd_blkoffset = offset from DSPAPQHD to DSPAPQLA
+*
+*
    Within DSPAPQLA are the following fields which are used to
+*
    access the list of DBDSs allocated on this log:
+*
+*
      apqla_DBDSAreaInfo = offset from DSPAPQLA to list of
```

```
+*
                         allocated DBDSs and Areas
+*
                         (apqla_DBDSArea)
+*
      apgla DBDSAreaCount = number of DBDS/Area entries
+*
      apqla DBDSAreaLen = length of each DBDS/Area entry
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
              Ver PTM/APAR Init Description
+*
     ----- -----
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
DSECT
DS F
+DSPAPQLA
                                 Log Allocation block
                                                                01-DSPAP
+apqla DBDSAreainfo
                  DS F
                                 Offset to allocated DBDS/Area list O1-DSPAP
+
                     DS
                           3F
                                 Reserved
                                                                01-DSPAP
+apgla PRILOGtime
                     DS
                                 PRILOG time
                           XL12
                                                                01-DSPAP
+apqla_Flags
                     DS
                           XL1
                                 Flags
                                                                01-DSPAP
                     EQU X'80'
+apqla NonRegd
                                 Non-registered DB updated
                                                                01-DSPAP
                                 Number of DBDS/Areas
+apqla_DBDSAreaCount
                     DS
                           XL3
                                                                01-DSPAP
+*
                                 allocated on this log
                           E
+apgla DBDSAreaLen
                     DS
                                 Length of DBDS/Area entry
                                                                01-DSPAP
+apgla EarliestALLOC
                     DS
                           XL12
                                 Earliest ALLOC time for this log
                                                                01-DSPAP
+apqla_DBDSArea
                     DSECT
                                 List of allocated DBDSs and Areas 01-DSPAP
                                 Database name
+apqla DBname
                     DS
                           CL8
                                                                01-DSPAP
                           0CL8
                                DD name or
+apqla_DDname
                     DS
                                                                01-DSPAP
+apgla Areaname
                     DS
                           CL8
                                 AREA name
                                                                01-DSPAP
+apqla FirstALLOC
                     DS
                           XL12
                                 Earliest ALLOC time for this
                                                                01-DSPAP
                                 DBDS/Area on this log
+*
+apqla_ALLNO
                     DS
                           Н
                                 Number of ALLOCs for this
                                                                01-DSPAP
                                 DBDS/Area on this log
+*
+
                      DS
                           CL2
                                 Reserved
                                                                01-DSPAP
+* END OF DSPAPQLA
                                                              *
```

DSPAPQLG - RLDS/SLDS block




Figure A-10 Output block for the log entries

Example: A-18 DSPAPQLG - RLDS/SLDS block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
                                            ******************@ECPYRT
+*
+*
+*
              DSPAPQLG - RLDS/SLDS block
   Name:
+*
+*
              DBRC Application Programming Interface
   Product:
+*
+*
   Function:
+*
+*
    This macro maps the RLDS/SLDS output block returned on the
+*
    DSPAPI FUNC=QUERY TYPE=LOG call.
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
+*
    the following information:
+*
+*
      apqhd eyecatcher = 'DSPAPQLG'
+*
      apqhd_length = block length
+*
      apqhd blktype
                      = X'0500'
                                 (DSPAPI BlkType PRILOG)
+*
                        X'0900'
                                 (DSPAPI BlkType SECLOG)
+*
                        X'4300'
                                 (DSPAPI BlkType PRISLDS)
+*
                        X'4700'
                                 (DSPAPI BlkType SECSLDS)
                                                                   *
+*
                                 (DSPAPI B1kType PRITSLDS)
                        X'4400'
```

+* X'4800' (DSPAPI BlkType SECTSLDS) +* apghd depptr = 0, no dependent block +* apqhd nextptr = 0, no next block +* apphd blkoffset = offset from DSPAPQHD to DSPAPQLG +* Within DSPAPQLG are the following fields which are used to +* +* access the first and the last data set entries: +* +* apqlg FirstLogDS = offset from DSPAPQLG to first log data set entry (apqlg_DS_Entry) +* +* +* apqlg_LastLogDS = offset from DSPAPQLG to last log data +* set entry +* +* Within each DS entry (apglg DS Entry) are the following +* fields which are used to access the previous and next DS +* entries as well as the volumes associated with the DS: +* +* apqlg DS Next = offset from DSPAPQLG to next DS entry +* apqlg_DS_Prev = offset from DSPAPQLG to previous DS entry +* +* apqlg DS Volinfo = offset from apqlg DS Entry to volume +* info (apqlg_DSVolume) of the first DS +* volume +* +* Within apqlg_DSVolume: +* +* apqlg DSVol Next = offset from apqlg DS Entry to the +* next DS volume +* +* Notes: +* +* Dependencies: None. +* +* Restrictions: None. +* +* Parameters: None. +* +* External References: +* Macros: None +* +* Modules: None +* +* Change Activity: +* +* Date Ver PTM/APAR Init Description +* +* 2003-10-02 1.0 KZ30219 pas Prolog update +* +DSPAPQLG DSECT RLDS/SLDS block 01-DSPAP DS F Offset to first log DS entry DS F Offset to last log DS entry +apqlg FirstLogDS 01-DSPAP +apqlg_LastLogDS 01-DSPAP + DS 2F Reserved 01-DSPAP DS CL8 +apqlg SSID Subsystem ID 01-DSPAP +apqlg_StartTime DS XL12 Log start time 01-DSPAP DS XL12 DS XL12 DS F DS FL1 +apqlg EndTime Log end time 01-DSPAP +apqlg DSNcount Number of data sets 01-DSPAP +apqlg_RELVL Log Release Level 01-DSPAP Flags +apqlg_Flags1 DS XL1 01-DSPAP

```
+apqlg Online
                        EOU
                             X'80'
                                    Online log
                                                                      01-DSPAP
+apqlg LSTAR
                        EQU
                             X'40'
                                    Last OLDS has been archived
                                                                      01-DSPAP
+apqlg LSTNA
                        EQU
                             X'20'
                                    Last OLDS has not been archived
                                                                      01-DSPAP
+apglg GAP
                        EQU
                             X'10'
                                    There is a gap in this log
                                                                      01-DSPAP
+apqlg PRGAP
                        EQU
                             X'08'
                                    There is a gap in a prev log
                                                                      01-DSPAP
+apqlg_Flags2
                        DS
                              XL1
                                     Flags
                                                                      01-DSPAP
                             X'80'
                                    Tracking log data set
+apqlg TRKNG
                        EQU
                                                                      01-DSPAP
+apqlg_NTERM
                        EQU
                              X'40'
                                     IMS subsystem has terminated
                                                                      01-DSPAP
+*
                                     normally
+apqlg BKLOG
                        EQU
                              X'20'
                                    Batch backout log
                                                                      01-DSPAP
+
                        DS
                              CL1
                                    Reserved
                                                                      01-DSPAP
+apqlg_FirstLRID
                        DS
                              XL8
                                     Id of first log record
                                                                      01-DSPAP
+apqlg PToken
                        DS
                             F
                                    PRILOG token
                                                                      01-DSPAP
+apqlg GSGname
                        DS
                             CL8
                                    GSG name
                                                                      01-DSPAP
+apqlg CHKPT0
                        DS
                             XL12
                                    Checkpoint 0 time
                                                                      01-DSPAP
+
                        DS
                              CL8
                                     Reserved
                                                                      01-DSPAP
+*
   The following structure maps the data set entries. There is
+*
   one such entry for each data set.
                                       Each data set entry
+*
   contains the offset to the preceeding and succeeding entries
+*
   as well as the offset to the first of a chain of DS volume
+*
   entries. Field apglg DS Next is the offset of the succeeding
   entry and apqlg_DS_Prev is the offset of the preceeding entry.
+*
+*
   Field applg DS VolInfo is the offset of the first volume entry.
+* For the first data set entry applg DS Prev will be zero.
   Similarly, applg DS Next will be zero for the the last data
+*
+*
   set entry.
+*
DSECT
                                                                      01-DSPAP
+apqlg DS entry
                                    Data set entry
+apqlg DS Next
                       DS
                             F
                                    Offset to next log DS entry
                                                                      01-DSPAP
+apqlg DS Prev
                             F
                       DS
                                    Offset to prev log DS entry
                                                                      01-DSPAP
+apqlg DS VolInfo
                        DS
                             F
                                    Offset to DS volume info
                                                                      01-DSPAP
+apglg DS DSname
                        DS
                             CL44
                                    Data set name
                                                                      01-DSPAP
+apqlg_DS_StartTime
                       DS
                             XL12
                                    DS start time
                                                                      01-DSPAP
                             XL12
+apq1g_DS_EndTime
                        DS
                                    DS end time
                                                                      01-DSPAP
                                    Flags
+apqlg DS Flags1
                        DS
                             XL1
                                                                      01-DSPAP
+apqlg_DS_ERR
                        EQU
                            X'80' I/O Error
                                                                      01-DSPAP
+apq1g DS DUMMY
                        EQU
                             X'40'
                                    Log compressed, 1st DS dummy
                                                                      01-DSPAP
+*
+* The next six bits apply only to SLDSs.
+*
+apqlg DS RSTBG
                        EQU
                             X'20'
                                    Restart begin
                                                                      01-DSPAP
+apqlg DS RSTEN
                        EQU
                             X'10'
                                    Restart end
                                                                      01-DSPAP
+apqlg DS COLD
                        EQU
                             X'08'
                                    Cold start
                                                                      01-DSPAP
+apglg DS NOBMP
                        EQU
                             X'04'
                                    ERE NOBMP
                                                                      01-DSPAP
+apqlg_DS_SAVER
                        EQU
                             X'02'
                                    Backout UORs saved
                                                                      01-DSPAP
+apqlg_DS_NOID
                        EQU
                             X'01'
                                    Backouts not identified
                                                                      01-DSPAP
+apqlg DS Flags2
                        DS
                              XI 1
                                     Flags
                                                                      01-DSPAP
+apqlg DS TrkArch
                        EQU
                             X'80'
                                    Tracking log DS archived
                                                                      01-DSPAP
+apqlg DS TrkFEOV
                        EQU
                             X'40'
                                    Tracking log closed FEOV
                                                                      01-DSPAP
+apglg DS DFLG3
                        DS
                              CL2
                                     Reserved
                                                                      01-DSPAP
+apqlg DS FLRID
                        DS
                              XL8
                                     First log record ID
                                                                      01-DSPAP
+apq1g DS LLRID
                        DS
                              XL8
                                    Last log record ID
                                                                      01-DSPAP
+apqlg DS LastBlkSeqNo
                        DS
                              F
                                    Last block seq number
                                                                      01-DSPAP
                             CL8
+apqlg DS UnitType
                        DS
                                    Unit type name
                                                                      01-DSPAP
+apqlg DS FileSeq
                        DS
                             Н
                                    File sequence no
                                                                      01-DSPAP
+apqlg_DS_VolCount
                        DS
                              Н
                                    Number of volumes
                                                                      01-DSPAP
+apqlg_DS_CkptCount
                        DS
                              FL1
                                    Number of chkpts on DSN
                                                                      01-DSPAP
+apqlg_DS_ChkptTypes
                        DS
                              XL1
                                    CHKPT types.
                                                                      01-DSPAP
```

	FOU	VIOOI	CIMPLE chackmaint	
+apqlg_DS_SIMPL	EQU	X'80'	SIMPLE checkpoint	01-DSPAP
+apqlg_DS_SNAPQ	EQU	X'40'	SNAPQ checkpoint	01-DSPAP
+apqlg_DS_DUMPQ	EQU	X'20'	DUMPQ checkpoint	01-DSPAP
+apqlg_DS_PURGE	EQU	X'10'	PURGE checkpoint	01-DSPAP
+apqlg_DS_FREEZ	EQU	X'08'	FREEZE checkpoint	01-DSPAP
+	DS	Н	Reserved	01-DSPAP
+apqlg_DSVolume	DSECT		Volume information	01-DSPAP
+apqlg_DSVol_Next	DS	F	Offset to next volume	01-DSPAP
+apqlg_DSVol_SER	DS	CL6	VOLSER	01-DSPAP
+apqlg_DSVol_CkptCt	DS	FL1	Volume chkpt count	01-DSPAP
+	DS	CL1	Reserved	01-DSPAP
+apqlg_DSVol_EndTime	DS	XL12	Volume end time	01-DSPAP
+apqlg_DSVol_CPTID	DS	XL12	Checkpoint ID	01-DSPAP
+apqlg_DSVol_LockSN	DS	XL6	Lock Sequence Number	01-DSPAP
+	DS	CL6	Reserved	01-DSPAP
+****	*****	******	*******	
+* END OF DSPAPQLG			*	
+****	*****	******	***********	

DSPAPQLI - log information block

0-	DSPAPQLI length LOGINFO dep ptr next ptr	
	block offset version PRILOG LOGALL	► PRILOG block
	SECLOG	
	SECSLDS	SECSLDS block
	PRITSLDS SECTSLDS	PRITSLDS block SECTSLDS block

Figure A-11 DSPAPQLI log information block

Example: A-19 DSPAPQLI - log information block

+**	+*************************************						
+*			*				
+*	Licensed M	laterials - Property of IBM	*				
+*			*				
+*	5655-J38		*				
+*			*				
+*	(C) Copyri	ght IBM Corp. 1974,2003 All Rights Reserved	*				
+*			*				
+*	US Governm	ment Users Restricted Rights - Use, duplication or	*				
+*	disclosure	e restricted by GSA ADP Schedule contract with	*				
+*	IBM Corp.		*				
+*			*				
+**	*******	:*************************************	CPYRT*				
+*			*				
+*	Name:	DSPAPQLI - Log Information block	*				
+*			*				
+*	Product:	DBRC Application Programming Interface	*				

```
+*
+*
   Function:
+*
+*
     This macro maps the Log Information output block returned on
+*
    the DSPAPI FUNC=QUERY TYPE=LOG call.
+*
+*
     The header of this block is mapped by DSPAPQHD which contains
+*
     the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQLI'
+*
      apqhd_length = block length
      apqhd_blktype = X'0501' (DSPAPI_BlkType_LOGINFO)
+*
+*
      apqhd depptr
                      = 0, no dependent blocks
+*
      apqhd_nextptr
                       = pointer to the LOGINFO block for the
+*
                         next group of log blocks
+*
       apphd blkoffset = offset from DSPAPQHD to DSPAPQLI
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
     Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
              Ver
                      PTM/APAR Init Description
+*
                       -----
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+***
                   ***********
                                                  *****
                     DSECT
+DSPAPQLI
                                    Log Information block
                                                                       01-DSPAP
                     DS CL8 Log SSID
DS XL12 Log start time
DS A ptr to PRILOG block
DS A ptr to LOGALL block
ntr to SECLOG block
+apqli SSID
                                                                       01-DSPAP
+apgli StartTime
                                                                       01-DSPAP
+apqli PRILOGptr
                                                                       01-DSPAP
+apqli_LOGALLptr
                                                                       01-DSPAP
+apqli_SECLOGptr
                      US A
DS A
DS A
DS A
DS A
                                                                       01-DSPAP
+apqli_PRISLDSptr
                                     ptr to PRISLDS block
                                                                       01-DSPAP
+apgli SECSLDSptr
                                     ptr to SECSLDS block
                                                                       01-DSPAP
+apqli PRITSLDSptr
                                     ptr to PRITSLDS block
                                                                       01-DSPAP
+apqli SECTSLDSptr
                                     ptr to SECTSLDS block
                                                                       01-DSPAP
+* END OF DSPAPQLI
```


DSPAPQNF - not found block

Example: A-20 DSPAPQNF - not found block

+**	**************************************	*
+*		*
+*	Licensed Materials - Property of IBM	*
+*		*
+*	5655-J38	*
+*		*

```
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
    +**
+*
+*
   Name:
             DSPAPQNF - Not Found block
+*
   Product:
             DBRC Application Programming Interface
+*
+*
+*
   Function:
+*
+*
    This macro maps the Not Found output block returned on the
+*
    DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apghd eyecatcher = 'DSPAPQNF'
     apqhd_length = block length
apqhd_blktype = X'18FF' (DSPAPI_BlkType_DBNotFound)
apqhd_depptr = 0, no dependent blocks
apqhd_nextptr = pointer to the next DB output block
+*
+*
+*
+*
+*
      apqhd_blkoffset = offset from DSPAPQHD to DSPAPQNF
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
          Ver PTM/APAR Init Description
     Date
+*
     _____
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
DSECT Not Found block @KZ30205 01-DSPAP
DS CL8 Database name 01-DSPAP
+DSPAPQNF
+apgnf DBname
+* END OF DSPAPQNF
```

DSPAPQOL - online log data set block





Example: A-21 DSPAPQOL - online log data set block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
               +*
+*
+*
   Name:
            DSPAPQOL - Online Log Data Set block
+*
            DBRC Application Programming Interface
+*
   Product:
+*
+*
   Function:
+*
+*
    This macro maps the Online Log Data Set output block returned
+*
    on the DSPAPI FUNC=QUERY TYPE=OLDS call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
      apphd eyecatcher = 'DSPAPQOL'
+*
                                                             *
+*
      apqhd_length
                 = block length
                                                             *
```

```
+*
      apqhd blktype
                      = X'5300' (DSPAPI BlkType PRIOLDS)
+*
                       X'5700' (DSPAPI_B1kType_SECOLDS)
+*
      apqhd depptr
                      = If PRIOLDS block, this is the pointer to
+*
                       the SECOLDS block, if one exists. If
+*
                       SECOLDS block, this is zero.
+*
      apqhd_nextptr
                      = pointer to next OLDS block
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQOL
+*
+*
    Within DSPAPQOL are the following fields which are used to
+*
    access online log data set information:
+*
+*
      apqol_OLDSInfo
                     = offset from DSPAPQOL to OLDS entries
+*
                       (apqla OLDSentry)
+*
      apqol_OLDSCount = number of OLDS entries
+*
      apqol OLDSLen
                     = length of each OLDS entry
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date
               Ver
                    PTM/APAR Init Description
+*
     _____
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
DSECT
                                  Online Log Dataset block
+DSPAPOOL
                                                                  01-DSPAP
                    DS F
                                  ! Offset to OLDS list
+apqol_OLDSinfo
                                                                  01-DSPAP
                     DS 3F
+
                                  ! Reserved
                                                                01-DSPAP
+apgol SSID
                     DS CL8 ! Subsystem ID
                                                                 01-DSPAP
                     DS H ! Length of OLDS entry
DS H ! Number of OLDS entries
+apqol OLDSlen
                                                                  01-DSPAP
                                 ! Number of OLDS entries
+apqo1_OLDScount
                                                                  01-DSPAP
                      DS XL12 ! Checkpoint O time
+apqol CHKPT0
                                                                  01-DSPAP
                      DS
                            CL8
                                  ! Reserved
                                                                  01-DSPAP
+apgol OLDSentry
                      DSECT
                                  OLDS entry
                                                                  01-DSPAP
                            CL8
+apqol DDname
                      DS
                                  OLDS DD name
                                                                  01-DSPAP
+apqol_DSNAM
                      DS
                            CL44 OLDS data set name
                                                                  01-DSPAP
                      DS
+apqol_OpenTime
                            XL12
                                  OLDS open time
                                                                  01-DSPAP
                      DS
+apqol CloseTime
                            XL12
                                  Close time
                                                                  01-DSPAP
+apqol_PRILOGtime
                      DS XL12
                                  Start time of associated PRILOG
                                                                  01-DSPAP
+apqol FLSN
                      DS
                            XL8
                                  LSN of first record in OLDS
                                                                  01-DSPAP
+apgol LLSN
                      DS
                            XL8
                                  LSN of last record in OLDS
                                                                  01-DSPAP
+apgol Flag1
                      DS
                            XL1
                                                                  01-DSPAP
+apqo1_RSTBG
                     EQU
                            X'80'
                                  Restart begin
                                                                  01-DSPAP
                     EQU X'40'
+apqol RSTEN
                                  Restart end
                                                                  01-DSPAP
+apqol_COLD
                           X'20'
                      EQU
                                  Cold start
                                                                  01-DSPAP
+apqol NOBMP
                      EQU
                            X'10'
                                  ERE NOBMP
                                                                  01-DSPAP
+apqol SAVER
                      EQU
                            X'08'
                                  Backout UORs saved
                                                                  01-DSPAP
                                  Backouts not identified
                      EQU
                           X'04'
+apqol NOID
                                                                  01-DSPAP
+apqo1_TRKNG
                      EQU X'02' OLDS created by tracking SS
                                                                  01-DSPAP
```

+apqol Flag2	DS	XL1	OLDS flags	01-DSPAP
+apqo1_STAT	EQU	X'F0'	OLDS status	01-DSPAP
+apqol_INUSE	EQU	X'80'	OLDS is in use	01-DSPAP
+apqol_ARNED	EQU	X'40'	Archive needed	01-DSPAP
+apqo1_ARSCH	EQU	X'20'	Archive scheduled (GENJCL)	01-DSPAP
+apqol_ARSTD	EQU	X'10'	Archive job started	01-DSPAP
+apqo1_CLERR	EQU	X'08'	Close error on OLDS	01-DSPAP
+apqol_FEOV	EQU	X'04'	Force EOV at archive	01-DSPAP
+apqo1_DUMMY	EQU	X'02'	OLDS not used due to I/O err	01-DSPAP
+apqo1_PRVCE	EQU	X'01'	Close error on previous OLDS	01-DSPAP
+apqol_RELVL	DS	FL1	Log release level	01-DSPAP
+apqo1_GAVER	DS	FL1	GENJCL.ARCHIVE version	01-DSPAP
+apqol_BlockSeqNo	DS	XL4	Block sequence number	01-DSPAP
+apqol_ARJOB	DS	CL8	Name of the archive job	01-DSPAP
+*			Generated by GENJCL.ARCHIVE	
+apqol_LockSeqNo	DS	XL6	Lock sequence number	01-DSPAP
+	DS	CL2	Reserved	01-DSPAP
+***********************	******	******	***********	
+* END OF DSPAPQOL			*	

DSPAPQRC - RECON status block

Example: A-22 DSPAPQRC - RECON status block

```
+*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
+**
       *****
                                             **************@ECPYRT
+*
             DSPAPQRC - RECON Status block
+*
   Name:
+*
   Product: DBRC Application Programming Interface
+*
+*
+*
   Function:
+*
+*
    This macro maps the output area returned on the DSPAPI
+*
    FUNC=QUERY TYPE=RECON call. This block describes the overall
+*
    status of the RECON as well as the status of each RECON data
+*
    set.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQRC'
+*
      apqhd length = block length
+*
      apqhd_blktype = X'0100' (DSPAPI_BlkType_RECON)
+*
      apqhd depptr
                      = 0, no dependent blocks
+*
      apqhd nextptr
                      = 0, no next blocks
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQRC
+*
+*
    DSPAPQRC maps the information describing the overall status
```

+* of the RECON. Within this block are the following fields +* * which are used to access the information for the individual +* RECON data sets (mapped by apprc RECONDS info): * +* * * +* apgrc RECONcount = number of RECON data set elements +* apqrc_RECONinfo = offset from DSPAPQRC to information +* about the first RECON in the list, +* apqrc_RECONDS_info. +* apprc RECONinfolen = length of each RECON data set element +* +* Notes: +* +* Dependencies: None. +* +* Restrictions: None. +* +* Parameters: None. +* +* External References: +* Macros: None +* +* Modules: None +* +* Change Activity: +* +* Date Ver PTM/APAR Init Description +* _____ +* 2003-10-02 1.0 KZ30219 pas Prolog update +* +DSPAPORC DSECT RECON status header 01-DSPAP +apqrc_DATA DS CL44 Initialized with "RECOVERY 01-DSPAP +* CONTROL DATASET" +apqrc_RECONinfo DS F Offset to RECON data set info 01-DSPAP + DS 2F Reserved 01-DSPAP Length of each RECON dataset +apqrc_RECONinfolen DS н 01-DSPAP +* info element +apqrc_RECONcount DS XL1 # of RECON dataset elements 01-DSPAP + DS CL1 Reserved 01-DSPAP +apgrc flags DS XL1 Process flags... 01-DSPAP +apgrc NOCHK EQU X'80' 1= NOCHECK log tape dsn check 01-DSPAP +apgrc CHK17 EQU X'40' 1= CHECK17 log tape dsn check 01-DSPAP +apqrc CHK44 EQU X'20' 1= CHECK44 log tape dsn check 01-DSPAP +apqrc_LSTLG EQU X'10' 1= list log DSN 01-DSPAP +apgrc INUPG EQU X'08' Upgrade in progress. 01-DSPAP +apqrc flag2 DS XL1 More flags... 01-DSPAP +apgrc FORCE EQU 1 = FORCER, 0 = NOFORCERX'80' 01-DSPAP 1=CA|IC|LOGS cataloged +apgrc CATDS EQU X'40' 01-DSPAP +apqrc TRACE EQU X'20' 1 = ext. GTF trace on 01-DSPAP +apgrc CmdSAF EQU X'10' SAF enabled 01-DSPAP +apgrc CmdExit EQU X'08' Cmd auth exit enabled 01-DSPAP + DS CL2 Reserved 01-DSPAP +apgrc CLEAN DS OCL136 Fields needed for cleanup 01-DSPAP +apqrc_CSET DS F 0 = updates not in progress, 01-DSPAP >0 = update in progress +* DS F Type of update +apqrc_TYPE 01-DSPAP +apgrc OKEY DS XL32 Key of original record 01-DSPAP +apqrc BKEY DS XL32 Key of base record that is in 01-DSPAP +* the process of being changed Key of new record DS XL32 01-DSPAP +apqrc_NKEY

	DC	00116	DDID of DDDC	
+apqrc_DBID +apqrc_DBD	DS DS	CL8	DBID of DBDS DBD name	01-DSPAP 01-DSPAP
+apqrc_DBD +apqrc_DDN	DS DS	CL8 CL8	DD name	01-DSPAP 01-DSPAP
+apqrc_CAGRP	DS	CL8	CA group name	01-DSPAP
+apqrc_DDNEW	DS	CL8	New DBDS DD name	01-DSPAP
+apqrc_DMBN0	DS	Н	DMB sequence number	01-DSPAP
<pre>+apqrc_LastReusedDMB#</pre>	DS	Н	Last reused DMB number, valid	01-DSPAP
+*			only when apqrc_DMBNO	
+*			is 32767	
+apqrc_InitToken	DS	XL7	Recon init. token	01-DSPAP
+apqrc_CmdHLQ	DS	CL8	Cmd auth high lvl qual	01-DSPAP
+apqrc_MVERS	DS	FL1	Minimum IMS version	01-DSPAP
+apqrc_NWFLG	DS	XL1	Fields needed for RECON I/O	01-DSPAP
+*			error(s)	
+apqrc_NEW	EQU	X'80'	1=STARTNEW, O=NONEW	01-DSPAP
+	DS	CL3	Reserved	01-DSPAP
+apqrc_SSIDN	DS	CL8	SSID for DASD	01-DSPAP
+apqrc_DASDU	DS	CL8	Unit type for DASD	01-DSPAP
+apqrc_TAPEU	DS	CL8	Unit type for tape	01-DSPAP
+* +apqrc_TIME	DS	0CL24	*	01-DSPAF
+apgrc TZDEF	DS	XL2	Input offset default	01-DSPAP
· · =		XL5	Time format options	01-DSPAP
+apgrc IMFMI	05	ALD		
+apqrc_TMFMT +	DS DS		·	
+	DS	CL1	Reserved	01-DSPAP
+ +apqrc_TPREC	DS DS	CL1 H	Reserved Time stamp precision	01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT	DS DS DS	CL1 H XL12	Reserved Time stamp precision Minimum log retention period	01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM	DS DS	CL1 H	Reserved Time stamp precision Minimum log retention period Number of entries in time	01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +*	DS DS DS DS	CL1 H XL12 H	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL	DS DS DS DS DS	CL1 H XL12 H 32CL8	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT	DS DS DS DS DS DS	CL1 H XL12 H 32CL8 XL2	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex	DS DS DS DS DS DS DS	CL1 H XL12 H 32CL8 XL2 CL5	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex +	DS DS DS DS DS DS	CL1 H XL12 H 32CL8 XL2	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + + +* 	DS DS DS DS DS DS DS DS CRT par	CL1 H XL12 H 32CL8 XL2 CL5 CL5	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved	01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* 	DS DS DS DS DS DS DS DS RT par	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 ameter	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved values * SIZEALERT dsnum	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
<pre>+ + +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +*</pre>	DS DS DS DS DS DS DS CRT par DS DS	CL1 H XL12 H 32CL8 XL2 CL5 CL5 ameter F F	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * values * SIZEALERT dsnum SIZEALERT volnum	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + + ** SIZEALERT and LOGALE ** +apqrc_SIZW_DSNUM +apqrc_SIZW_VOLNUM +apqrc_SIZW_PERCENT	DS DS DS DS DS DS DS DS RT par DS DS DS	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 ameter F F F	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT percent	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + + ** SIZEALERT and LOGALE ** +apqrc_SIZW_DSNUM +apqrc_SIZW_PERCENT +apqrc_LOGW_DSNUM	DS DS DS DS DS DS DS DS CS DS DS DS DS DS DS	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 ameter F F F	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT percent LOGALERT dsnum	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** SIZEALERT and LOGALE +*	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT percent	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
<pre>+ + +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** sIZEALERT and LOGALE +*</pre>	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT percent LOGALERT volnum	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** SIZEALERT and LOGALE ** +apqrc_SIZW_DSNUM +apqrc_SIZW_VOLNUM +apqrc_SIZW_PERCENT +apqrc_LOGW_VOLNUM +apqrc_LOGW_VOLNUM +apqrc_RECONDS_info +apqrc_RECONDS_DDname	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F CL8	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT percent LOGALERT dsnum LOGALERT volnum RECON DD name	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
<pre>+ + +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** sIZEALERT and LOGALE +*</pre>	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT percent LOGALERT volnum	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** SIZEALERT and LOGALE ** +apqrc_SIZW_DSNUM +apqrc_SIZW_VOLNUM +apqrc_SIZW_PERCENT +apqrc_LOGW_VOLNUM +apqrc_LOGW_VOLNUM +apqrc_RECONDS_info +apqrc_RECONDS_DDname	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F CL8	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT percent LOGALERT dsnum LOGALERT volnum RECON DD name	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** SIZEALERT and LOGALE **	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F F CL8 CL44 XL1 X'80'	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * Values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT volnum RECON DD name RECON DD name	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
+ +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** SIZEALERT and LOGALE **	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F CL8 CL44 XL1	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT volnum RECON DD name RECON DS name RECON DS status	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
<pre>+ + +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** ** SIZEALERT and LOGALE **</pre>	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F F CL8 CL44 XL1 X'80'	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT volnum RECON DD name RECON DS name RECON DS status COPY 1	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP
<pre>+ + +apqrc_TPREC +apqrc_LOGRT +apqrc_TZNUM +* +apqrc_TZTBL +apqrc_TROPT +apqrc_IMSplex + +* ** ** ** ** ** ** ** ** ** ** ** *</pre>	DS DS DS DS DS DS DS DS DS DS DS DS DS D	CL1 H XL12 H 32CL8 XL2 CL5 CL5 CL5 F F F F F F CL8 CL44 XL1 X'80' X'40'	Reserved Time stamp precision Minimum log retention period Number of entries in time zone label table Time zone label table DBRC trace options IMSplex name Reserved * values * SIZEALERT dsnum SIZEALERT volnum SIZEALERT volnum RECON DD name RECON DS name RECON DS status COPY 1 COPY 2	01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP 01-DSPAP

DSPAPQRI - DBDS/area recovery information block




Figure A-13 RCVInfo output

Example: A-23 DSPAPQRI - DBDS/area recovery information block

+**	**************************************	*
+*		*
+*	Licensed Materials - Property of IBM	*
+*		*
+*	5655-J38	*
+*		*
+*	(C) Copyright IBM Corp. 1974,2003 All Rights Reserved	*
+*		*
+*	US Government Users Restricted Rights - Use, duplication or	*
+*	disclosure restricted by GSA ADP Schedule contract with	*
+*	IBM Corp.	*
+*		*

+*		*
+*	Name: DSPAPQRI - DBDS/Area Recovery Information block	*
+*		*
+*	Product: DBRC Application Programming Interface	*
+* +*	Function.	*
+^ +*	Function:	*
+* +*	This mappe maps the DDDS/Amer Decovery Information output	*
+*	This macro maps the DBDS/Area Recovery Information output block returned on the DSPAPI FUNC=QUERY TYPE=DB call.	*
+*	DIOCK TECUTIEN ON THE DEFAFT FUNC-QUERT TIFE-DB CATT.	*
+*	The header of this block is mapped by DSPAPOHD which contains	*
' +*	the following information:	*
+*	the forfowing information.	*
+*	apghd eyecatcher = 'DSPAPQRI'	*
+*	apqhd_cyccuccher born qn1 apqhd_length = block_length	*
+*	apqhd_leftype = X'2801' (DSPAPI B1kType RCVINFO)	*

```
+*
    apqhd depptr = 0, no dependent block
+*
    apphd nextptr = 0, no next block
+*
    apphd blkoffset = offset from DSPAPQHD to DSPAPQRI
+*
+*
  Notes:
+*
+*
   Dependencies: None.
+*
+*
   Restrictions: None.
+*
+*
  Parameters: None.
+*
+*
  External References:
+*
    Macros: None
+*
+*
    Modules: None
+*
+*
  Change Activity:
+*
+*
    Date
           Ver PTM/APAR Init Description
+*
    _____
    2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
Recovery Information block
                                                 01-DSPAP
                                                 01-DSPAP
                                                 01-DSPAP
                                                 01-DSPAP
                                                 01-DSPAP
                                                 01-DSPAP
                                                 01-DSPAP
+apqri_REORGptr
              DS A
                                                 01-DSPAP
+* END OF DSPAPQRI
                                                *
```

DSPAPQRR - DBDS reorganization block

Example: A-24 DSPAPQRR - DBDS reorganization block

+**	*******	**************************************	PYRT*
+*			*
+*	Licensed M	Materials - Property of IBM	*
+*			*
+*	5655-J38		*
+*			*
+*	(C) Copyri	ght IBM Corp. 1974,2003 All Rights Reserved	*
+*			*
+*	US Governm	ment Users Restricted Rights - Use, duplication or	*
+*	disclosure	e restricted by GSA ADP Schedule contract with	*
+*	IBM Corp.		*
+*			*
+**	*********	**************************************	PYRT*
+*			*
+*	Name:	DSPAPQRR - DBDS Reorganization block	*
+*			*
+*	Product:	DBRC Application Programming Interface	*
+*			*
+*	Function:		*
+*			*
+*	This macr	ro maps the DBDS Reorganization output block	*

```
+*
    returned on the DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apqhd_eyecatcher = 'DSPAPQRR'
+*
      apqhd length = block length
      apqhd_blktype = X'3200' (DSPAPI_BlkType_REORG)
+*
     apqhd_depptr = 0, no dependent blocks
apqhd_nextptr = pointer to next REORG block for the DBDS
+*
+*
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQRR
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
   Change Activity:
+*
+*
     Date Ver PTM/APAR Init Description
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*
DSECT
+DSPAPQRR
                                DBDS Reorganization block
                                                              01-DSPAP
                  DS CL8 Database na
DS OCL8 DD name or
+apqrr DBname
                                Database name
                                                              01-DSPAP
+apqrr_DDname
                                                              01-DSPAP
+apqrr_Areaname
                   DS CL8
                                Area name
                                                              01-DSPAP
                    DS XL12 The time at which the DBDS was
+apqrr_RunTime
                                                              01-DSPAP
+*
                                reorganized.
+apgrr Stoptime
                     DS
                          XL12
                                Stoptime of online reorg
                                                              01-DSPAP
+apgrr flags
                     DS
                          XL1
                                                              01-DSPAP
+apgrr ONL
                    EQU X'80' 1=ONLINE/0=OFFLINE reorg
                                                              01-DSPAP
                     EQU X'40' 1=May be used for recovery
+apqrr_RECOV
                                                              01-DSPAP
                          CL3
+
                     DS
                                Reserved
                                                              01-DSPAP
                     DS
+apqrr_USID
                          F
                                Associated USID
                                                              01-DSPAP
                          XL12
+apgrr PITR
                     DS
                                Stoptime moved - PITR
                                                              01-DSPAP
+* END OF DSPAPORR
```

DSPAPQRV - recovery block

Example: A-25 DSPAPQRV - recovery Block

+************@SCPYRT*@SCPYRT					
+*		*			
+*	Licensed Materials - Property of IBM	*			
+*		*			
+*	5655-J38	*			
+*		*			
+"		~			

```
+*
    (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
    US Government Users Restricted Rights - Use, duplication or
+*
    disclosure restricted by GSA ADP Schedule contract with
+*
    IBM Corp.
+*
    +**
+*
+*
    Name:
                DSPAPQRV - DBDS Recovery block
+*
    Product: DBRC Application Programming Interface
+*
+*
+*
    Function:
+*
+*
     This macro maps the DBDS Recovery output block returned on
+*
     the DSPAPI FUNC=QUERY TYPE=DB call.
+*
+*
     The header of this block is mapped by DSPAPQHD which contains
+*
     the following information:
+*
+*
       apphd eyecatcher = 'DSPAPQRV'
       apqhd_length = block length
apqhd_blktype = X'3700' (DSPAPI_BlkType_RECOV)
apqhd_depptr = 0, no dependent blocks
apqhd_nextptr = pointer to next RECOV block for the DBDS
+*
+*
+*
+*
+*
       apqhd_blkoffset = offset from DSPAPQHD to DSPAPQRV
+*
+*
    Notes:
+*
+*
     Dependencies: None.
+*
+*
     Restrictions: None.
+*
+*
    Parameters: None.
+*
+*
    External References:
+*
      Macros: None
+*
+*
      Modules: None
+*
    Change Activity:
+*
+*
      Date Ver PTM/APAR Init Description
+*
+*
      _____
      2003-10-02 1.0 KZ30219 pas Prolog update
+*
+*

      +DSPAPQRV
      DSECT
      DBDS Recovery block

      +apqrv_DBname
      DS
      CL8
      Database name

      +apqrv_DDname
      DS
      OCL8
      DD name or

      +apqrv_Areaname
      DS
      CL8
      Area name

      +apqrv_RunTime
      DS
      XL12
      The time at which the DBDS was

      +*
      recovered.
      **

                                                                            01-DSPAP
                                                                            01-DSPAP
                                                                            01-DSPAP
                                                                            01-DSPAP
                                                                            01-DSPAP
+*
                                        recovered.
+apqrv_EndTime DS
                                XL12 Partial recovery only, the time
                                                                            01-DSPAP
+*
                                       to which the DBDS was restored
+* Update set IDs that were 'undone' by timestamp recovery.
DS F
+apqrv_FUSID
                                       First undone USID
                                                                            01-DSPAP
+apqrv_LUSID
                        DS F
                                       Last undone USID
                                                                            01-DSPAP
```

+apqrv_FLAGS	DS	XL1	Flags	01-DSPAP
+apqrv_PITR	EQU	X'80'	Point In Time Recovery	01-DSPAP
+*****	*****	******	***************************************	
+* END OF DSPAPQRV			*	
+****	*****	******	*************************************	

DSPAPQSL - DB/area authorized subsystem list block

Example: A-26 DSPAPQSL - DB/area authorized subsystem list block

```
DSPAPQSL
                                                     31469001
+****
                                   +*
+*
   Licensed Materials - Property of IBM
+*
+*
   5655-J38
+*
+*
   (C) Copyright IBM Corp. 1974,2003 All Rights Reserved
+*
+*
   US Government Users Restricted Rights - Use, duplication or
+*
   disclosure restricted by GSA ADP Schedule contract with
+*
   IBM Corp.
+*
  +**
+*
+*
            DSPAPQSL - DB/Area Authorized Subsystem List block
   Name:
+*
+*
   Product:
            DBRC Application Programming Interface
+*
+*
   Function:
+*
+*
    This macro maps the authorized subsystem list portion of the
+*
    Database, Area, and HALDB Partition output blocks returned on
+*
    the DSPAPI FUNC=QUERY TYPE=DB call. Refer to the DB, Area,
    or Partition blocks - DSPAPQDB, DSPAPQAR, or DSPAPQHP - for
+*
+*
   more information on accessing the authorized subsystem list.
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
    Macros: None
+*
+*
    Modules: None
+*
+*
   Change Activity:
+*
+*
                 PTM/APAR Init Description
    Date
              Ver
+*
     +*
    2003-10-02 1.0 KZ30219 pas Prolog update
+*
+DSPAPQSL
                    DSECT
                                DB/Area Auth SS List block
                                                             01-DSPAP
+apqs1_SSINF0
                    DS
                          OCL16 Subsystem list entry
                                                             01-DSPAP
+apqs1 SSNAME
                    DS
                          CL8
                                Subsystem ID
                                                             01-DSPAP
```

+apgs1 ACCESS	DS	FL1	Access intent	01-DSPAP				
· · _								
+apqs1_NCDDST	DS	FL1	Encoded state	01-DSPAP				
+apqs1_SSFLGS	DS	XL1	Flags	01-DSPAP				
+apqs1_SSROLE	EQU	X'80'	0 - Active SS, 1 - Tracking SS	01-DSPAP				
+apqs1_SSXRFC	EQU	X'40'	1 - XRF Capable	01-DSPAP				
+	DS	XL1	Reserved	01-DSPAP				
+apqsl BKINFO	DS	0XL4	Backout information	01-DSPAP				
+apqs1_BKCTR	DS	Н	Backout needed count	01-DSPAP				
+apqs1_BKNUM	DS	Н	Backout done count	01-DSPAP				
+*****	******	******	*******************************					
+* Possible access inten	t value	es (apq	s1 ACCESS) *					

+apgs1 ACCR0	EQU	X'01'	READ-GO	01-DSPAP				
+apqs1_ACCRD	EQU	X'02'	READ	01-DSPAP				
+apqs1 ACCUP	EQU	X'03'	UPDATE	01-DSPAP				
+apqs1_ACCEX	EQU	X'04'	EXCLUSIVE	01-DSPAP				
+*****	+**************************************							
+* END OF DSPAPQSL			*					
+****	*****	******	***********					

DSPAPQSS - subsystem block





Figure A-14 Subsystem output

Example: A-27 DSPAPQSS - subsystem block

+**	*******	**************************************	YRT*
+*			*
+*	Licensed M	aterials - Property of IBM	*
+*			*
+*	5655-J38		*
+*			*
+*	(C) Copyri	ght IBM Corp. 1974,2003 All Rights Reserved	*
+*			*
+*	US Governm	ent Users Restricted Rights - Use, duplication or	*
+*	disclosure	restricted by GSA ADP Schedule contract with	*
+*	IBM Corp.		*
+*			*
	*********	**************************************	
+*			*
+*	Name:	DSPAPQSS – Subsystem block	*
+*			*
+*	Product:	DBRC Application Programming Interface	*
+*			*

```
+*
   Function:
+*
+*
    This macro maps the Subsystem output block returned on the
+*
    DSPAPI FUNC=QUERY TYPE=SUBSYS call.
+*
+*
    The header of this block is mapped by DSPAPQHD which contains
+*
    the following information:
+*
+*
      apphd eyecatcher = 'DSPAPQSS'
      apqhd_length = block length
apqhd_blktype = X'3FOO' (DSPAPI_BlkType_SUBSYS)
+*
+*
+*
      apqhd_depptr = 0, no dependent block
apqhd_nextptr = pointer to next SUBSYS block
+*
+*
      apphd blkoffset = offset from DSPAPQHD to DSPAPQSS
+*
+*
    Within DSPAPQSS are the following fields which are used to
+*
    access authorized database/area information:
+*
+*
      apqss AuthList = offset from DSPAPQSS to list of authorized
+*
                        DBs/Areas (apqss_AuthName)
+*
      apgss AuthCount = number of authorized DB/Areas
+*
      apgss AuthLen = length of each entry
+*
+*
   Notes:
+*
+*
    Dependencies: None.
+*
+*
    Restrictions: None.
+*
+*
   Parameters: None.
+*
+*
   External References:
+*
     Macros: None
+*
+*
     Modules: None
+*
+*
    Change Activity:
+*
+*
     Date
                Ver
                      PTM/APAR Init Description
+*
     ----- -----
+*
     2003-10-02 1.0 KZ30219 pas Prolog update
+*
     2004-03-04 1.01 PQ83837 pas Add user-recoverable flag
+*
DSECT
+DSPAPQSS
                                    Subsystem block
                                                                      01-DSPAP
                      DS CL8
+apqss SSID
                                    Subsystem identifier
                                                                      01-DSPAP
+apqss_Authlist
                       DS
                           F
                                    Offset to authd DB/Area list
                                                                      01-DSPAP
+apqss_AuthCount
                      DS F
                                    Number of authorized DB/Areas
                                                                      01-DSPAP
                       DS H
+apqss_AuthLen
                                    Length of auth entry
                                                                      01-DSPAP
+
                       DS CL6
                                    Reserved
                                                                      01-DSPAP
+apgss LOGtime
                        DS
                             XL12
                                    Start time of log
                                                                      01-DSPAP
+apqss RELLVL
                        DS
                             FL1
                                    Subsystem release level
                                                                      01-DSPAP
+*
                                    '71'X=V7R1,'81'X=V8R1
+*
                                    '91'X=V9R1, etc.
                                                                      01-DSPAP
+apqss CoexLvl
                       DS
                             FL1
                                    Coexistence level
                                    IRLM status count
+apqss_IRLMCT
                       DS
                             FL1
                                                                      01-DSPAP
                        DS
                             CL1
                                    Reserved
                                                                      01-DSPAP
+apqss GSGname
                       DS
                             CL8
                                    Global Service Group name
                                                                      01-DSPAP
                       DS
                             CL5
+apqss_IRLMID
                                    IRLM ID of SS
                                                                      01-DSPAP
+apqss_IRLMBK
                        DS
                             CL5
                                    IRLM ID of backup SS
                                                                      01-DSPAP
```

+apgss FLAGS	DS	XL1	Flags	01-DSPAP
+apqss TYPE	EOU	X'80'	1=Online 0=batch	01-DSPAP
+apqss ABTERM	EQU	X'40'	Abnormal termination	01-DSPAP
+apqss RCVPRC	EQU	X'20'	Recovery processing started	01-DSPAP
+apqss BKSIGN	EQU	X'10'	Backup SS signed on	01-DSPAP
+apqss IRLMFL	EQU	X'08'	IRLM failure	01-DSPAP
+apqss COMMFL	EQU	X'04'	COMM failure	01-DSPAP
+apqss SYSFL	EQU	X'02'	SYS failure	01-DSPAP
+apqss ACTVST	EQU	X'01'	Status of active SS when	01-DSPAP
+*	-40	. • -	backup exists, 1=abterm	01 00110
+apqss FLAGS2	DS	XL1	FLAGS 2	01-DSPAP
+apqss SHRING	EQU	X'80'	Sharing covered DBs	01-DSPAP
+apqss TRKER	EQU	X'40'	Subsystem is a Tracker	01-DSPAP
+apqss TRKTRM	EQU	X'20'	TRACKER has terminated	01-DSPAP
+apqss TRCKED	EQU	X'10'	SSID is tracked	01-DSPAP
+apqss FRSTS0	EQU	X'08'	1ST signon after RSR takeover	01-DSPAP
+*	240		is in progress	01 001/1
+apgss XRFCAP	EQU	X'04'	SS is XRF capable	01-DSPAP
+apqss BCKTKN	DS	Н	Backup recovery token	01-DSPAP
+	DS	CL2	Reserved	01-DSPAP
+apgss Authname	DSECT	-	Names of authd DB/Areas	01-DSPAP
+apqss DBNAME	DSLOT	CL8	DB name	01-DSPAP
+apqss AREANM	DS	CL8	If FP, Area name	01-DSPAP
+apqss SHRLVL	DS	FL1	Share level	01-DSPAP
+apqss DBACCS	DS	FL1	Access intent	01-DSPAP
+apqss DBNCOD	DS	FL1	Encoded state	01-DSPAP
+apqss DBSTAT	DS	FL1	DB status flags	01-DSPAP
+apqss DBEQCT	DS	Н	DB EQE count	01-DSPAP
+apqss GLBDMB	DS	Н	Global DMB number	01-DSPAP
+apgss AuthFlags	DS	XL1	Flags	01-DSPAP
+apqss NRDBUP	EQU	X'80'	Nonrecov DB/Area updated	01-DSPAP
+apqss COVRD	EQU	X'40'	DB covered by GSG	01-DSPAP
+apgss NRECV	EQU	X'20'	Non-recoverable DB/Area	01-DSPAP
+apgss ORDBDS	EQU	X'10'	O=A-J/1=M-V ACTIVE	01-DSPAP
+apqss_OLRON	EQU	X'08'	0 = no OLR active	01-DSPAP
+apgss OLROWR	EQU	X'04'	0 = no OLR owner	01-DSPAP
+apgss OLROWD	EQU	X'02'	0 OLR not owned by SS	01-DSPAP
+apgss URECV	EQU	X'01'	User-recoverable Area	01-DSPAP
+*			(VERSION=1.01) @PQ83837	
+	DS	CL7	Reserved	01-DSPAP
+****	*****		****	
+* END OF DSPAPQSS				*



Β

Database Recovery Facility support

IMS Database Recovery Facility for z/OS (product number 5655-I44) is Version 2 of IMS Online Recovery Services for z/OS (product number 5655-E50). DRF includes the capabilities of ORS and has significant enhancements. Some of the capabilities and characteristics of DRF are the ones that were included in ORS. DRF supports IMS Version 7 with PQ73997, IMS Version 8 with PQ73990, and IMS Version 9 with PQ80051 and PQ80052.

We describe DRF here to summarize the available functions depending on IMS Version through 7 to 9.

DRF functions inherited from ORS

DRF recovers multiple database data sets in parallel. One invocation of DRF is used for these multiple recoveries. DRF may be used to invoke IMS database recoveries from an IMS online system by using /RECOVER commands. Users do not code JCL for these recoveries. DRF allocates the database data sets and recovery input data sets (image copies, change accumulations, and logs) from information in the RECONS.

DRF may be used to do two types of time stamp recoveries. A normal time stamp recovery is to a "recovery point". This is a time which is not spanned by a RECON ALLOC record. It is a time when the database is not allocated to any IMS subsystem. The second type of time stamp recovery is a point-in-time recovery (PITR). A PITR may be done to any time, including a time at which the database was being updated by an IMS subsystem. This includes a time at which updates were in-flight. PITR recovers only updates that were committed before the PITR time.

DRF reads input data sets in parallel, which are image copies, change accumulations, and logs. These input data sets are read only once. Typically, a log or a change accumulation data set is used as input to the recovery of multiple database data sets. The user determines the number of parallel read processes.

DRF enhancements

DRF can be invoked by a batch job since IMS Version 7. DRF uses a different process for recovery. ORS used the facilities of the online system for recovering data sets. For full function databases it used the online system's database buffer pools. For Fast Path databases it used its own Fast Path buffer pool in the online system. DRF does not use online facilities for the recovery except for the processing of /RECOVER commands. These commands are used to invoke DRF in its own address spaces, since IMS Version 8.

DRF has several performance improvements over ORS. DRF allows users to specify separate limits for the number of parallel read processes used for tape and DASD devices.

DRF includes an option to create a list of inputs required for a recovery without actually doing the recovery, with VERIFY option This is useful to determine if the inputs are available and to determine if a recovery is possible.

DRF includes new reports on its processing. This includes a list of all of the inputs used in its recoveries.

Figure 13-1 on page 291 illustrates DRF process. DRF is invoked either by /RECOVER commands from an IMS online system or by a batch job step. In either case, the DRF master address space is executed. The online system and batch job may use the same catalogued procedure for this address space.




Figure 13-1 Database Recovery Facility (DRF) process

The master address space reads the RECONs and determines the inputs needed for recovery. It also reads the logs and change accumulation data sets for the recoveries. The required records from these data sets are passed to DRF subordinate address spaces. Each data set to be recovered is assigned to a subordinate address space. The number of address spaces is controlled by the NUM(nn) sub parameter of the SORT parameter in the FRXDRFxx PROCLIB member. The subordinate address spaces read the image copies, sort the log and change accumulation records, and apply all of these to recover the database data sets. The data sets are written sequentially.

Online invocation

DRF can be invoked with IMS online command, /RECOVERY, since IMS Version 8. This online command is compatible with ORS. This command is used as follows;

- /RECOVER ADD: used to build a list of elements to be recovered
- /RECOVER REMOVE: used to delete elements in the list
 - The list may contain data sets, areas, databases, HALDB partitions, and groups. Groups include CA groups, DBDS groups, and recovery groups. These groups are defined in the RECONs. Database groups cannot be used with DRF commands.
- /RECOVER START: used to start a recovery of all of the elements in the list
- /RECOVER STOP: used to stop the recovery of all of the database data sets whose recovery is in process
- /RECOVER TERMINATE: used to stop the DRF master address space
 - Without this command, the master address space remains after a recovery is completed.

See IMS Command Reference for more information about /RECOVERY command.

DFSORSxx PROCLIB member is used for online execution of DRF. This member is specified by IMS ORSMBR= execution parameter, and contains only one parameter for DRF, DRFNAME(nnnnnn). DRFNAME is the name of procedure that executes DRF. The default name for DRFNAME is FRXJCLDF. This member was also used by ORS. ORS parameters in this member are ignored by DRF.

Batch invocation

The batch execution of DRF is the execution of the DRF master address space. The batch invocations is available since IMS Version 7. This is the same address space which is invoked by the online execution of DRF. DRF supplies a sample cataloged procedure, FRXJCLDF, which may be used for this address space. If you use the procedure instead of the JCL shown on this page, you only need to specify the //SYSIN DD statement and the control statements. See Example 13-1.

Example 13-1 DRF batch invocation; FRXJCLDF

```
//MYJOB JOB
              <acctng data etc.>
//DRFSTEP EXEC PGM=FRXSDR00,PARM='DRFMBR=AA,BPECFG=BPEDRFCG'
//STEPLIB DD DSN=DRF.SFRXRESL,DISP=SHR
11
           DD
               DSN=IMS.SDFSRESL,DISP=SHR
//PROCLIB DD
               DSN=IMS.PROCLIB,DISP=SHR
//DBDLIB DD
               DSN=IMS.DBDLIB,DISP=SHR
//SYSPRINT DD
               SYSOUT=*
//REPORT
          DD SYSOUT=*
//SYSUDUMP DD SYSOUT=*
//SYSIN DD *
ADD DB (ABC1 ABC2 ABC3)
ADD RECOVGRP (XYZ1 XYZ2)
START RCVTIME('20033611330000', PITR)
/*
```

The batch control statements are similar to online commands. Only ADD, REMOVE, and START are used.


- ADD: used to build a list of elements to be recovered
- REMOVE: used to delete elements in the list
 - The list may contain data sets, areas, databases, HALDB partitions, and groups. Groups include CA groups, DBDS groups, and recovery groups. These groups are defined in the RECONs. Database groups cannot be used with DRF commands. When an area is specified in a batch control statement the database must also be specified.
- START: used to start a recovery of all of the elements in the list

Execution enhancements

ORS could limit the number of parallel read processes. This was done with the READNUM parameter. DRF enhances this capability to limit both the total number of parallel read processes and the number used for tape inputs. The limits are set by the READNUM specifications in the FRXDRFxx PROCLIB member. The total number of processes may be overridden on the START command (batch or online). The number of tape drives may be overridden on the batch START command.

The new VERIFY option on the START command may be used to produce a report of the inputs required for a recovery without recovering the database data sets. The VERIFY option may be specified on either the batch or online version of the START command. Some

installations find it useful to verify that the required inputs are available before they start a recovery.



С

IMS Tools support for IMS Version 9

This appendix provides the *minimum* software level requirements for the IMS Tools products to be used with IMS Version 9. There is a comment after each product that tells the level of support; it is either not supported, tolerate or exploit.

- ► Not supported means that the product does not function properly on IMS Version 9.
- Tolerate allows the product to execute as it did on a previous release of IMS, but does not utilize any of the new IMS Version 9 functions.
- Exploit means that the product utilizes the new functions and features available in IMS Version 9.


IMS Tools and IMS Version 9 compatibility

This list provides the *minimum* maintenance required for IMS[™] Tools to support IMS for z/OS Version 9.1. You can find the table and the latest updates to it from the following Web site:

http://www-1.ibm.com/support/docview.wss?rs=434&cntext=sszjxp&uid=swg21167251&loc=en_US& cs=utf-8&lang=en+en

- Application Recovery Tool 1.2.0 Exploit with APAR PQ84689
- Data Encryption 1.1.0 Exploit, no change required
- Data Refresher 1.1.0 Exploit, no change required
- DB/DC Data Dictionary 1.6.0 Tolerate, no change required
- IMS ADF II 2.2.0 X Tolerate, no change required
- IMS Advanced ACB Generator 1.1.0 Not supported, replaced by IMS Library Integrity Utilities
- IMS Batch Backout Manager 1.1.0 Exploit with APAR PQ79075
- IMS Batch Terminal Simulator 3.1.0 Exploit with APAR PQ80182
- IMS Buffer Pool Analyzer 1.1.0 Exploit with APAR PQ80183
- IMS Checkpoint Wrapper 1.1.0 Exploit with APAR PQ80214
- IMS Command Control Facility 1.1.0 Exploit with APAR PQ79840
- IMS Connect 1.2.0 Tolerate, no change required
- IMS Database Control Suite 3.1.0 Exploit with APAR PQ80215
- IMS Database Recovery Facility 2.1.0 Exploit with APARs PQ80051, PQ80052
- IMS Database Repair Facility 1.1.0 and 1.2.0 Exploit, no change required
- ► IMS DataPropagator[™] 3.1.0 Exploit, no change required
- IMS DEDB Fast Recovery 2.2.0 Exploit with APAR PQ80193
- IMS ETO Support 3.1.0 Tolerate with APAR PQ79849
- IMS Fast Path Basic Tools 1.2.0 Exploit with APAR PQ80197
- IMS Fast Path Online Tools 2.1.0 Exploit with APAR PQ80200
- IBM Fault Analyzer V4 Exploit with APAR PQ94701
- IBM Fault Analyzer V5 Exploit with APAR PQ95289
- IMS HD Compression Extended 2.2.0 Exploit with APAR PQ79146
- IMS HP Change Accumulation 1.2.0 Exploit with APAR PQ80221
- IMS HP Fast Path Utilities 2.1.0 Exploit, no change required
- IMS HP Image Copy 3.1.0 Exploit with APARs PQ83801, PQ80186, PQ83453, PQ86664, PQ80197, PQ89630
- IMS HP Image Copy 3.2.0 Exploit, no change required
- IMS HP Load 1.1.0 Exploit with APARs PQ80198, PQ85616
- IMS HP Load 2.1.0 Exploit, no change required
- IMS HP Pointer Checker 2.1.0 Exploit with APARs PQ80186, PQ83453, PQ86664
- IMS HP Prefix Resolution 2.1.0 and 3.1.0 Exploit, no change required
- IMS HP Sysgen Tools 1.1.0 Exploit with APAR PQ79845
- IMS HP Unload 1.1.0 Exploit with APARs PQ80191, PQ83387

- IMS Image Copy Extensions 2.1.0 Tolerate with APAR PQ80187
- ► IMS Index Builder 2.2.0 Exploit with APAR PQ80216
- ▶ IMS Index Builder 2.3.0 Exploit with APARs PQ80216, PQ88453
- IMS Library Integrity Utilities 1.1.0 Exploit with APARs PQ80199, PQ83869
- IMS Library Management Utilities 1.1.0 Not supported, replaced by IMS Library Integrity Utilities
- IMS MFS Reversal Utilities 1.1.0 Tolerate, no change required
- IMS Multi-Dialog Manager 1.1.0 Tolerate with APAR PQ80331
- IMS Network Compression Facility 1.1.0 Tolerate with APAR PQ79842
- IMS Online Recovery Services 1.1.0 Not supported, replaced by IMS Database Recovery Facility
- IMS Online Reorganization Facility 1.1.0 Exploit, no change required
- IMS Parameter Manager 1.1.0 Exploit, no change required
- ► IMS Parallel Reorganization 2.1.0 Exploit with APARs PQ80190, PQ83386, PQ80191, PQ83387, PQ80198, PQ85616
- ► IMS Parallel Reorganization 3.1.0 Exploit, no change required
- IMS Performance Analyzer 3.2.0 Exploit with APARs PQ79473, PQ83568, PQ85111, PQ85681
- IMS Performance Monitor 1.1.0 Exploit with APAR PQ85342
- IMS Problem Investigator 1.1.0 Exploit with APAR PQ79474
- ▶ IMS Program Restart Facility 2.1.0 Exploit with APARs PQ79074, PQ84911, PQ86995
- IMS Queue Control Facility 1.2.0 Exploit with APAR PQ69897
- IMS Queue Control Facility 2.1.0, Exploit, no change required
- IMS Sequential Randomizer Generator 1.1.0 Exploit, no change required
- IMS Workload Router 2.4.0 Tolerate, no change required



D

IMS Control Center

This appendix provides information about how to download and connect the command center to IMS Version 9. This appendix covers the following topics:

- Workstation software
- Host requirements
- What set up steps you have to do
- ► Using the IMS Control Center

IMS Control Center steps you need to know

You can manage your IMS systems using a graphical interface from a workstation using the IMS Control Center. The IMS Control Center uses the IMS single point of control (SPOC) functions. The IMS Control Center is part of the IBM DB2 Universal Database Version 8 Control Center. The DB2 Control Center is available with the IBM DB2 Universal Database (DB2 UDB) Administration Client, Version 8.2.

Using the IMS Control Center, you can view the members of the IMSplex and define groups of members. The Control Center supports both IMS Version 8 and later versions. From the Control Center you can issue IMS type-2 commands using command windows or wizards, depending on how much assurance you want. Wizards help you build and issue the commands. The results are displayed in the IMS Results window. In addition, using the Command Editor, you can issue both type-1 and type-2 IMS commands.

Workstation software

From the IMS home page click the IMS Control Center. This will take you into the DB2 Information Center, and the information needed to setup the IMS Control Center, and also where to download the software.

From the DB2 download site you need to choose your workstation platform and download the related DB2 administration client.

If you have DB2 UDB:

At a minimum, install the administration client on your workstation. For information about installing DB2 UDB, refer to the *Getting Started* information for DB2 UDB. To install the administration client, select the Custom installation when asked. Then choose to install these features under Administration tools:

- Control Center
- Command Editor
- Configuration Assistant

You can choose to install any other features you want. Be sure that the features you do not want to install are marked with a red X.

If you do not have DB2 UDB:

You can download the IBM DB2 UDB administration client from the DB2 UDB support Web site: DB2 UDB support downloads

Migration

If you have installed an earlier version of the IMS Control Center, you can install DB2 UDB Administration Client Version 8.2 without uninstalling the earlier version. However, installing the latest version of the IMS Control Center will remove your IMS Control Center IMSplex system definitions, tools settings, and command history from an earlier version.

Host requirements

First, check that your system has the required software at the correct levels.

IMS Version 8

► You must have APAR PQ69527 installed to enable IMS Control Center support.

- The Common Service Layer must be configured.
- IMS Connect Version 1.2 or later with APARs PQ62379 and PQ70216 installed.

IMS Version 9

- IMS Version 9 provides an integrated IMS Connect function; make sure that the Connect function is installed and configured on your system.
- You must have APARs PQ92398 installed.
- The Common Service Layer must be configured (this can be an Enhanced Command Environment).

You must have APAR PQ69527 installed to enable IMS Control Center support.

What set up steps you have to do

Follow these steps to complete the set up for the IMS Control Center:

1. Configure the IMS Operations Manager (OM).

Check your OM configuration to ensure the following:

- a. In the OM initialization parameters member (CSLOIxxx), the IMSplex name specified in the IMSPLEX parameter must be the same as that specified in both IMS member DFSCGxxx and in your IMS Connect configuration member (HWSCFxxx).
- b. Also in the OM initialization parameters member (CSLOIxxx), CMDTEXTDSN must point to the data set containing the command syntax translatable text that was placed in the SDFSDATA library when IMS was installed.

For more information about configuring OM, refer to *IMS Version 9: Common Service Layer Guide and Reference*, SC18-7816.

2. Configure IMS Connect.

Modify the configuration member you use to define the environment for IMS Connect or create a new IMS Connect configuration member. The IMS Connect configuration member is the PROCLIB member you specify in the HWSCFG= parameter of your IMS Connect startup JCL. For more information about IMS Connect configuration, see Chapter 4, "IMS Connect Definition and Tailoring", in the *IMS Connect Guide and Reference*, SC27-0946.

In your configuration member, specify the following settings:

- c. The user message exits for IMSplex support (HWSCSLO0 and HWSCSLO1) in the EXIT keyword statement
- d. Each IMSplex you want to manage in the IMSPLEX keyword statement

Example D-1 is a sample IMS Connect configuration member with the updates for the IMS Control Center.

Example: D-1 HWSCFGxx sample

```
HWS (ID=IMSGCONN,RACF=N,XIBAREA=20)
TCPIP (HOSTNAME=TCPIP,PORTID=(7003,LOCAL),MAXSOC=2000,TIMEOUT=8800,
EXIT=(HWSSMPL0,HWSCSL00,HWSCSL01),IPV6=Y)
DATASTORE (ID=IMSG,GROUP=IMS9EXCF,MEMBER=HWS910G,TMEMBER=SCSIM9G)
IMSPLEX (MEMBER=IMSPLEXG,TMEMBER=PLEXG)
```

Note the port number for the IMSplex in the PORTID parameter in the TCPIP keyword statement. You will use this later when you add the IMSplex to the Control Center. You also need to know the IP address of your system.

- 3. If you created a new IMS Connect configuration member, update the HWSCFG= parameter in your IMS Connect startup JCL to point to the new member.
- 4. Stop IMS Connect and restart it with your updated configuration.
- 5. On your workstation with DB2 UDB installed, open the Control Center by selecting Start->Programs->IBM DB2->General Administration Tools-->Control Center.

The Control Center is displayed see Figure D-1:

an info-pop will ask you to choose "basic", "advanced" or "customized", you need to mark **advanced**.

Control Center Control Center Selected Edit View Tools Help Control Center Selected Edit View Tools Help Control Center Selected Edit View	
Control Center	Control Center ↓ ^A Z Name → All Databases
	1 of 1 items displayed 1 2 3 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

Figure D-1 DB2 Control Center

 Add the IMSplex that you want to manage by right-clicking on the All Cataloged Systems folder (your Control Center folder may just be named Systems). Then select Add... from the pop-up menu.

The Add System window is displayed in Figure D-2 on page 303:

🏪 Add System	×
System Type	O DB2 O IMS
System name	PLEXB
Host name	
Port Number	7002
Operating system	OS/390 or z/OS
Comment	
ок с	ancel Apply Reset Show Command Help

Figure D-2 ADD system

You need the saved information from the HWSCFGxx file.

- 7. Select IMS as the System Type and enter the information for your IMSplex.
 - Enter your IMSplex name in the System name field.
 - Enter host name or the IP address of the host system for the IMSplex in the Host name field. You might have to overwrite the IMSplex name that the system places in this field.
 - Enter the port number as specified in your IMS Connect configuration member in the Port number field.

Click OK.

- To log in to the IMSplex, right-click the IMS system folder in the object tree in the left frame of the Control Center and select Login... from the pop-up menu. A Login window is displayed.
- 9. Enter the User ID you use to issue IMS commands and its password.

Click OK.

You can now use the IMS Control Center and you can also use the Command Editor to issue IMS commands. For more information about using the IMS Control Center see the DB2 Information Management Software Information Center for z/OS Solutions on page:

http://publib.boulder.ibm.com/infocenter/dzichelp/index.jsp

Using the IMS Control Center

After the IMS Control Center is successfully installed and connected to the IMS Connect you are able to use the Command Editor as seen on Figure D-3 on page 304

Command Editor 1	
Command Editor Selected Edit	
	😰 🐕 🖵 🕇 🗃 🦂 🕐
Commands	
Target	Specify Target
	Target type IMS Route
	Available targets
	FI PLEXB
	Available mt K Cancel Help

Figure D-3 IMS Control Center command editor

After entering the target in our case PLEXB a security pop-up asks for user ID and password. As soon as you've entered it you'll find the screen Figure D-4 on page 305 where you may be able to specify a single member of your sysplex IMS or all members.

Target type MS Route	×
Available targets	
Available members M2B IM1B IM1BRM IM2BRM	Selected members All_Members <
	OK Cancel Help

Figure D-4 Specify target

Now you are able to use the new commands as introduced in "Type-2 database commands" on page 119. We provided a sample of the QRY DB command and its results in Figure D-5.

> "아 않 📼 mmands Detailed F	Se 🧾 🥵	7	80 🖵 < 🖻	■ { ?								
esults history												
UERY DB NAME(*)	SHOW(ALL)											
ISplex Con	n mand master		Route									
LEXB IMI	В		All_Members	5								
1 1	_											
Results Errors Ti	ime											
	1							TYPE	⇔	LAcc :	≑ LclStat	
DBName ≙	I AreaName	_ ⇔	PartName ≙ i	i MbrName		CC	=					
	AreaName	÷ I	PartName ⇔		\$	CC	<u> </u>		<u> </u>			≑ ▲
CUSTDB	AreaName			IM1B	\$	CC	. (PHDAM		UPD		
	Areaname		CUSTD1	IM1B IM1B	\$	cc) PHDAM) PART		UPD UPD	NOTOPEN	
CUSTDB CUSTDB CUSTDB	AreaName		CUSTD1 CUSTD2	IM1B IM1B IM1B	\$	CC	(() PHDAM) PART) PART		UPD	NOTOPEN NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTDB	Areaname		CUSTD1 CUSTD2 CUSTD3	M1B M1B M1B M1B) PHDAM) PART) PART) PART		UPD UPD UPD UPD	NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI	Areaname		CUSTD1 CUSTD2 CUSTD3	M1B M1B M1B M1B M1B M1B	\$			PHDAM DPART DPART DPART DPSINDEX		UPD UPD UPD UPD UPD	NOTOPEN NOTOPEN NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI	Areaname		CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B	\$			DPHDAM DPART DPART DPART DPSINDEX DPART		UPD UPD UPD UPD UPD READ	NOTOPEN NOTOPEN NOTOPEN NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI CUSTSI DBFSAMD1			CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B	\$			D PHDAM D PART D PART D PART D PSINDEX D PART D		UPD UPD UPD UPD UPD READ EXCL	NOTOPEN NOTOPEN NOTOPEN ALLOCS,NOTOPE NOTINIT,STOSCHI	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI DBFSAMD1 DBFSAMD2			CUSTD1 CUSTD2 CUSTD3 CUSTS1	IM1B IM1B IM1B IM1B IM1B IM1B IM1B IM1B	*			D PHDAM D PART D PART D PART D PSINDEX D PART D		UPD UPD UPD UPD UPD READ	NOTOPEN NOTOPEN NOTOPEN NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI DBFSAMD1 DBFSAMD2 DBFSAMD3	CUSDB		CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B	*) PHDAM) PART) PART) PART D PSINDEX) PART)		UPD UPD UPD UPD UPD READ EXCL EXCL	ALLOCS,NOTOPEN NOTOPEN ALLOCS,NOTOPE NOTINIT,STOSCHI	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI DBFSAMD1 DBFSAMD2 DBFSAMD3 DBFSAMD3			CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B M1B M1B M1B	*) PHDAM) PART) PART) PART) PART) PSINDEX) PART)) DEDB		UPD UPD UPD UPD UPD READ EXCL EXCL	NOTOPEN NOTOPEN NOTOPEN ALLOCS,NOTOPE NOTINIT,STOSCHI NOTINIT,STOSCHI	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI CUSTSI CUSTSI DBFSAMD2 DBFSAMD3 DBFSAMD3 DBFSAMD3			CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B M1B M1B M1B				0 PHDAM 0 PART 0 PART 0 PART 0 PART 0 PART 0 PART 0 0 0 0 0 DEDB 0 AREA		UPD UPD UPD UPD READ EXCL EXCL UPD	NOTOPEN NOTOPEN NOTOPEN ALLOCS,NOTOPE NOTINIT,STOSCHI NOTOPEN NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI CUSTSI DBFSAMD1 DBFSAMD2 DBFSAMD3 DBFSAMD3 DBFSAMD4 DISTDB			CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B M1B M1B M1B	*			PHDAM PART PART PART PART PART PART PART PART DEDB DAREA DLA		UPD UPD UPD UPD READ EXCL EXCL UPD UPD	NOTOPEN NOTOPEN NOTOPEN ALLOCS,NOTOPE NOTINIT,STOSCHI NOTOPEN NOTOPEN	
CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI CUSTSI DBFSAMD1 DBFSAMD2 DBFSAMD3 DBFSAMD3 DBFSAMD4 DBFSAMD4 DISTDB DISTDB	CUSDB		CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B M1B M1B M1B	*			PHDAM PART PART PSINDEX PART DART DEDB DART DART		UPD UPD UPD UPD READ EXCL EXCL UPD UPD	NOTOPEN NOTOPEN ALLOCS,NOTOPEN NOTINIT,STOSCHI NOTINIT,STOSCHI NOTOPEN NOTOPEN NOTOPEN OPEN	
DBName ♀ CUSTDB CUSTDB CUSTDB CUSTDB CUSTDB CUSTDB CUSTDB CUSTSI DBFSAMD1 DBFSAMD2 DBFSAMD3 DBFSAMD4 DISTDB DI21PART HISTDB	CUSDB		CUSTD1 CUSTD2 CUSTD3 CUSTS1	M1B M1B M1B M1B M1B M1B M1B M1B M1B M1B	*			PHDAM PART PART		UPD UPD UPD UPD UPD EXCL EXCL UPD UPD UPD UPD	NOTOPEN NOTOPEN ALLOCS,NOTOPEN ALLOCS,NOTOPEN NOTINIT,STOSCHI NOTOPEN NOTOPEN NOTOPEN OPEN OPEN	

Figure D-5 QRY DB SHOW(ALL) sample

Also the new UPDATE data base command can be used via the Command Editor see Figure D-6 on page 306. Here in the "Detailed Results" tab, you find folders for results, errors, if any, returning the condition and reason codes, as well as a time folder showing you the duration and access time.

Co F Co		r Selec 5 🗔 etailed Ri	ted Edit To 음우 💽 🌘			₽ {	φ®	1 { 0	?									_ — ×
ſ	UPD DB NAM	E(CUSTE	B CUSTSI) ST.	ART(A	CCESS)		_				_	_	_		_			-
	MSplex	Com	mand master			Route												_
	PLEXB					All_Mem	here											
	Results En										-							 1
	DBName	≑	AreaName	\$	MbrNan	ne	\$	cc			_	orText	:	Ş				
	CUSTDB CUSTSI				IM1B IM1B						0							
	CUSTSI				IM11B IM2B						0							
	CUSTSI				IM2B						0							
		4 oʻ	f 4 items displa	ayed			↓AZ		₫ <u></u> >	θĐ	\searrow^{\oplus}	₽"	•		■	8:8	Default View	 View

Figure D-6 UPD DB NAME(CUSTDB CUSTSI) START(ACCESS)

An error would result if for example you tried to update an unknown database. You will see the return and reason codes as well as the CSLN054I message as seen in Figure D-7.

Command Editor 1
┡_ ヤ} ☆ 쯔 ☞ ■ ☆ ☆ ₽ < < <
Commands Detailed Results
Results history
UPD DB NAME(HUGO*) START(ACCESS)
IMSplex Command master Route
PLEXB IM1B All_Members
Results Errors Time
IMSplex Error
Message Message ID Return Code Reason Code
CSLN054I 0200000C 00003008
IMS Member Error(s)
Member Message Type Subtype Message ID Return Code Reason Code
IM1B IMS 000000C 00003004
IM2B IMS 0000000C 00003004

Figure D-7 CSLN054I message sample

If you were using the TSO SPOC, you will find the return and reason codes for the same command by simply pressing PF4 on the return panel it shows you the same as shown in Figure D-8.




Figure D-8 TSO SPOC sample of return and reason codes

The explanation of this return and reason code is mentioned in the CSLN054I message: "No clients returned return code 0. Check return code(s) Explanation: The command was routed to multiple clients. None of the clients that processed the command returned a return code 0 and reason code 0 to the Operations Manager. For information on the CSLOMCMD return and reason code, refer to *IMS Version 9: Common Service Layer Guide and Reference*, SC18-7816."

Using the IMS Control Center and Command Editor with IMS Version 9

You are able to update the resources that are new to IMS Version9, that is, database, online reorganization, area, and datagroup.

Using the IMS Control Center with the latest version of DB2 UDB Administration Client Version 8.2 has the following enhancements (available whether you are using IMS V8 or V9):

Command Editor (previous versions referred to this as the "Command Center")

The Command Editor has a "syntax assist" capability. In the command area of the Command Editor you can start typing the command, or press the spacebar to display a list of the type-2 IMS commands, if syntax assist is on. Select the command you want using the arrow keys and use the spacebar to add it to the editor. Press the spacebar again to continue.

Command Shortcuts

You can set up short names for commands that you use often; then you can use the short names in the Command Editor. For example, if you routinely want to query the same series of transactions, those that start with TSP, LMH, and SRG, you can create a short name &MYQRY and specify the command QUERY TRAN NAME(TSP* LMH* SRG*). To define a short name and its command, click the Command Editor. The icon is only available when you have selected an IMS target.

When you enter &MYQRY in the Command Editor, you will run the QUERY TRAN command you specified. You can also define the defaults to use for parameters for commonly used commands in the IMS Command Shortcuts.

• Compare Two Sets of command outputs from the Results panel.


You can compare results from running a type-2 command at different times. You can compare results to view changes after updating members, to check status, to find differences in attributes. The comparison must be between results from the same command. A message informs you if the results sets you chose are different. The results from the second results set you selected are shown with a gray background. The individual results that are different are highlighted in the second set, when a value appears in both sets but are different. You can choose to show only the differences between the results or show the full results. To open the IMS Compare Results window: Click in the IMS Results window.

Abbreviations and acronyms

ACB	application control block	DBRC	data base recovery control
ACEE	access control environment	DBWP	database work pool
	element	DEDB	data entry database
AGN	application group name	 DL/I	Data Language/I
ΑΟΙ	automated operator interface	DLI/SAS	DL/I separate address space
APAR	authorized program analysis report	DLT	database level tracking (RSR)
APF	authorized program facility	DMB	database management block
API	application programming interface	DMBP	data management block pool
APPC	advanced program to program communication	DRA	database resource adapter
ARLN	automatic RECON loss notification	DRF	IMS Database Recovery Facility
ARM	Automatic Restart Manager	DSAB	data set association block
ATM	automatic teller machine	EBCDIC	extended binary coded decimal
AWE	Asynchronous Work Element		interchange code
BMP	batch message program	ECSA	extended common system area
BPE	Base Primitive Environment	EEQE	extended error queue element
BSDS	boot strap data set	EIS	Enterprise Information System
CBPDO		EJB	Enterprise Java Bean
CBPDO	custom built product delivery offering	EMCS	extended multiple consoles support
CDT	class descriptor table	EMEA	Europe, Middle East and Africa
CF	Coupling Facility	ЕМН	expedited message handler
CFRM	Coupling Facility Resource	EMHQ	expedited message handler queue
	Manager	ESAF	external subsystem attach facility
CI	control interval	ESCON®	Enterprise System Connection
CICS	Customer Information Control	ESO	Extended Service Offering
	System	ΕΤΟ	Extended Terminal Option
COBOL	common business oriented	EX	execution (IVP)
CPF	language command prefix facility	FDBR	Fast Database Recovery
CQS	Common Queue Server	FICON	Fiber Connection
CSA	common system area	FMID	function modification identifier
CSI	consolidated software inventory	FT	file tailoring (IVP)
CSL		FTP	File Transfer Protocol
CSL	Common Service Layer Consolidated Service Test	GSAM	generalized sequential access method
СТС	channel-to-channel	HALDB	High Availability Large Database
DASD	direct access storage device	HDAM	hierarchic direct access method
DB/DC	database/data communications	HFS	hierarchical file system
DB2	DATABASE 2	HIDAM	hierarchic indexed direct access
DBA	database administrator		method
DBCTL	database control	HLQ	high-level qualifier
DBD	database description	HTML	Hyper Text Markup Language
DBDS	database data set	HTTP	Hyper Text Transfer Protocol

IBM	International Business Machines	MOD	message output descriptor (MFS)
	Corporation	MOD	module (SMP/E)
IFP	IMS Fast Path program	MPP	message processing program
IIOP	Internet inter-ORB protocol	MPR	message processing region
ILDS	indirect list data set	MSC	multiple systems coupling
ILE	indirect list data set list entry	MSDB	Main Storage Data Base
ILS	Isolated Log Sender	MVS	Multiple Virtual System
IMS	Information Management System	NCCF	network communication control
IPCS	Interactive Problem Control System		facility
IPL	initial program load	NCP	network control program
IRLM	Integrated Resource Lock Manager	NMD BMP	non-message driven BMP
ISC	intersystem communication	ODBA	open database access
ISD	independent software delivery	OLDS	online log data set
ISPF	Interactive Systems Productivity Facility	OLR	integrated HALDB online reorganization
ITSO	International Technical Support	ОМ	Operations Manager
	Organization	ORS	Online Recovery Service
IVP	installation verification program	OSAM	overflow sequential access method
J2C	J2EE Connector Architecture	ΟΤΜΑ	open transaction manager access
J2C	J2EE Connector Architecture	ОТМА СЛ	OTMA callable interface
J2EE	Java 2 Platform, Enterprise Edition	PCB	program communication block
JBP	Java batch processing region	PDS	partitioned data set
JCL	job control language	PDSE	partitioned data set extended
JDBC	Java database connectivity	PDU	partition definition utility
JDK	Java Development Kit	PHDAM	partitioned HDAM
JES	job entry subsystem (JES2 or JES3)	PHIDAM	partitioned HIDAM
JMP	Java message processing region	PIA	package input adapter
JNDI	Java Naming and Directory	PIC	Product Introduction Centre
	Interface	PITR	point in time recovery
JVM	Java Virtual Machine	PMR	problem management record
KBLA	Knowledge Based Log Analysis	PPT	program properties table
KSDS	key sequenced data set	PS EDI	physical sequential enhanced data integrity (DFSMS)
LE	Language Environment	PSB	program specification block
LMOD	load module	PSBW	PSB work pool
LPA	link pack area	PSINDEX	partitioned secondary index
LPAR	logical partition	PSP	preventive service planning
LTERM	logical terminal	PST	program specification table
LU	logical unit	PST	partition specification table
LU2	Logical Unit 2	PTF	program temporary fix
MCS	multiple consoles support	QCF	IMS Queue Control Facility
MD BMP	message driven BMP	QPP	Quality Partnership Program
MFS	message format services	RACF	Resource Access Control Facility
MLPA	modifiable link pack area	RAP	root anchor point
MNPS	Multi-Node Persistent Sessions	RAS	resource access security
			. cooling accord booting

RBA	relative byte address	TCP/IP	Transmission Control Protocol/Internet Protocol
RDS	restart data set	TMS	Transport Manager System
RDS	remote database services	TPNS	Teleprocessing Network Simulator
RIM	related installation material	TSO	Time Sharing Option
RLDS	recovery log data set	UDB	Universal Database (DB2)
RLT	recovery level tracking (RSR)	UOR	unit of recovery
RM	Resource Manager	UOW	unit of work
RMF™ DM///OD	Resource Measurement Facility remote method invocation/Internet	USS	Unix System Services
RMI/IIOP	inter-ORB protocol	USS	unformatted system services (SNA)
RNR	Rapid Network Recovery	WADS	write ahead data set
RRS	Resource Recovery Service	WAS	WebSphere Application Server
RRSAF	resource recovery service	VG	variable gathering (IVP)
	attachment facility	VLF	virtual lookaside facility
RSR	Remote Site Recovery	VOLSER	volume serial (number)
RSU	recommended service upgrade	WSADIE	WebSphere Application Developer
RYO	roll your own		Integration Edition
SAF	Security Authorization Facility	VSAM	virtual storage access method
SCI	structured call interface	VSCR	Virtual Storage Constraint Relief
SDM	System Data Mover	WSDL	Web Service Description Language
SDSF	spool display and search facility	WSIF	Web Service Invocation Framework
SLDS	system log data set	VSO	Virtual Storage Option (DEDB
SMB	scheduler message block	VTAM	VSO) virtual telecommunication access
SMP/E	System Modification Program/Extended		method
SMQ	shared message queues	WTO	write-to-operator
SMS	system managed storage	WTOR	write-to-operator-reply
SMU	security maintenance utility	WWW	World Wide Web
SOAP	simple object access protocol	XML	eXtensible Markup Language
SPE	small programming enhancement	XRC	eXtended Remote Copy
SPOC	single point of control	XRF	eXtended Recovery Facility
SQL	structured query language		
SRDS	structure recovery data set		
SSA	sub-system alias		
SSID	subsystem ID		
SSL	secure sockets layer		
SSOB	subsystem options block		
STM	sysplex terminal management		
SVC	supervisor call		
SVL	Silicon Valley Laboratories		
SVSO	shared VSO		
ΤΑΒ	transaction anchor block		
ТВ	twin backward (pointer)		
ТСВ	task control block		
тсо	time controlled operations		



Related publications

The publications listed in this section are considered particularly suitable for a more detailed discussion of the topics covered in this redbook.

IBM Redbooks

For information on ordering these publications, see "How to get IBM Redbooks" on page 314. Note that some of the documents referenced here may be available in softcopy only.

- IMS e-business Connectors: A Guide to IMS Connectivity, SG24-6514
- Ensuring IMS Data Integrity Using IMS Tools, SG24-6533
- ► IMS Installation and Maintenance Processes, SG24-6574
- IMS Version 8 Implementation Guide A Technical Introduction of the New Features, SG24-6594
- IMS DataPropagator Implementation Guide, SG24-6838
- Using IMS Data Management Tools for Fast Path Databases, SG24-6866
- IMS in the Parallel Sysplex, Volume I: Reviewing the IMSplex Technology, SG24-6908
- IMS in the Parallel Sysplex, Volume II: Planning the IMSplex, SG24-6928
- IMS in the Parallel Sysplex, Volume III: IMSplex Implementation and Operations, SG24-6929
- The Complete IMS HALDB Guide, All You Need to Know to Manage HALDBs, SG24-6945
- Reorganizing Databases Using IMS Tools A Detailed Look at the IBM IMS High Performance Tools, SG24-6074
- IMS Version 9 Implementation Guide A Technical Overview, SG24-6398

Other publications

These publications are also relevant as further information sources:

- IMS Version 9: Administration Guide: Database Manager, SC18-7806
- IMS Version 9: Administration Guide: System, SC18-7807
- IMS Version 9: Administration Guide: Transaction Manager, SC18-7808
- IMS Version 9: Application Programming: Database Manager, SC18-7809
- IMS Version 9: Application Programming: Design Guide, SC18-7810
- IMS Version 9: Application Programming: EXEC DLI Commands for CICS and IMS, SC18-7811
- ► IMS Version 9: Application Programming: Transaction Manager, SC18-7812
- IMS Version 9: Base Primitive Environment Guide and Reference, SC18-7813
- IMS Version 9: Command Reference, SC18-7814
- IMS Version 9: Common Queue Server Guide and Reference, SC18-7815
- IMS Version 9: Common Service Layer Guide and Reference, SC18-7816

- ► IMS Version 9: Customization Guide, SC18-7817
- IMS Version 9: Database Recovery Control (DBRC) Guide and Reference, SC18-7818
- IMS Version 9: Diagnosis Guide and Reference, LY37-3203
- IMS Version 9: Failure Analysis Structure Tables (FAST) for Dump Analysis, LY37-3204
- IMS Version 9: IMS Connect Guide and Reference, SC18-9287
- ► IMS Version 9: IMS Java Guide and Reference, SC18-7821
- IMS Version 9: Installation Volume 1: Installation Verification, GC18-7822
- IMS Version 9: Installation Volume 2: System Definition and Tailoring, GC18-7823
- IMS Version 9: Master Index and Glossary, SC18-7826
- IMS Version 9: Messages and Codes Volume 1, GC18-7827
- IMS Version 9: Messages and Codes Volume 2, GC18-7828
- IMS Version 9: Open Transaction Manager Access Guide and Reference, SC18-7829
- IMS Version 9: Operations Guide, SC18-7830
- IMS Version 9: Release Planning Guide, GC17-7831
- IMS Version 9: Summary of Commands, SC18-7832
- IMS Version 9: Utilities Reference: Database Manager and Transaction Manager, SC18-7833
- IMS Version 9: Utilities Reference: System, SC18-7834
- IMS Connector for Java 2.2.2 and 9.1.0.1 Online Documentation for WebSphere Studio Application Developer Integration Edition 5.1.1, SC09-7869
- z/OS V1R5 Communications Server: SNA Network Implementation, SC31-8777
- z/OS V1R5.0 Security Server RACF System Programmer's Guide, SA22-7681

Online resources

These Web sites and URLs are also relevant as further information sources:

IMS home page:

http://www.ibm.com/ims

- DB2 Information Management Software Information Center for z/OS Solutions http://publib.boulder.ibm.com/infocenter/dzichelp/index.jsp
- IBM Redbooks:

http://www.ibm.com/redbooks

How to get IBM Redbooks

You can search for, view, or download Redbooks, Redpapers, Hints and Tips, draft publications and Additional materials, as well as order hardcopy Redbooks or CD-ROMs, at this Web site:

ibm.com/redbooks

Help from IBM

IBM Support and downloads

ibm.com/support

IBM Global Services

ibm.com/services



Index

Symbols

/ASSIGN 210 /ASSIGN CLASS 210 /CHE FREEZE 21 /CHE STATISTICS 191 /CHECKPOINT DUMPQ 44 /CHECKPOINT FREEZE 44 /CHECKPOINT PURGE 44 /DBD DB 43 /DBR DB 43 /DIAGNOSE command 8, 217-218 /DIS AREA 68 /DIS DB 120 /DIS DB OLR 42 /DIS FPV 62-63 /DISPLAY 39, 41 /DISPLAY CONVERSATION 203 /ERE 67, 92-93, 100-101, 104-105, 200, 213 /ERE COLDBASE 213 /ERE COLDCOMM 67 /ERE COLDSYS 67 /ERE COLDSYS PASSWORD 98 /EXIT 203 /EXIT CONVERSATION 203 /INIT 36, 39, 42, 44 /LOCK 97-98 /NRE 44, 65, 67, 92-93, 98, 100-101, 104-105, 200 /NRE CHECKPOINT 0 67 /PSTOP 210 /PURGE 210 /RECOVER ADD 291 /RECOVER REMOVE 291 /RECOVER START 291 /RECOVER STOP 291 /RECOVER TERMINATE 291 /RECOVERY 291 /RMGENJCL 80 /RMxxxx command 4, 6, 79-80 /SECURE OTMA 204 /SECURE OTMA REFRESH 204-205 /SET 97-98 /SIGN ON 99 /START 127, 210 /START AREA 62-64, 66, 69 /START DB 43, 69, 124 /START OTMA 204-205 /STOP 127, 205, 210 /STOP DB 43, 120, 124 /STOP OTMA 204 /TERMINATE 39-40 /UNLOCK 97-98 /UPDATE 39-40 /VUNLOAD 62

Α

access control environment element (ACEE) 5, 177 ACEE 92, 94, 97, 109, 177, 204-205 ADFSMAC 74, 208 ADFSSMP 74 ADFSSMPL 14, 208 AGN 86-90, 112-113 AIMS RACF security class 86, 88-89 APPC 89, 203-204, 208, 217 APPC/MVS TP_Profile entry 209 APPCIOT 208 application group name (AGN) security 86 Application Recovery Tool 296 APSB call 89 APSB security 88-89 ARM restart 212-213 ARMRST 212 ASSIGN TRANSACTION 210 automatic RECON loss notification 130-131 autonomic computing 3

С

CBPDO 10 CFRM policy 20, 58-61, 67 CFSTR1 58-59, 61, 83 CFSTR2 58-59,83 change accumulation utility (DFSUCUM0) 46 CHANGE.DB 35, 49-50 CHANGE.DB ALL OLRCAP 35 CHANGE.DBDS 49 CHANGE.RECON 83, 231-232, 279 CHANGE.RECON CMDAUTH 80 CHANGE.RECON MINVERS 83 CHANGE.RECON UPGRADE 230-231 CIMS RACF security class 91, 95, 105, 218 COBOL 6, 139-140, 142, 147, 153, 155, 159, 162, 167-168 coexistence 9, 35, 48, 51, 73, 82, 223, 226-228, 232 command authorization exit (DFSCCMD0) 94, 109 command recognition character 8, 215 Common Client Interface (CCI) application 139 Common Queue Server (CQS) 7, 19, 116 Common Service Layer (CSL) 7, 116, 128-130, 134 Coupling Facility 5, 62-63, 116, 129, 218, 227 CQS 20-21, 24, 67, 116, 209, 227 CQSIP000 20 CQSSG000 20 CQSSGxxx 67 CQSSL000 20 CQSSLxxx 67 cross-system coupling facility (XCF) 136, 212 CSL 19-20, 116-117, 129, 131, 134 CSLG= 133 CSLOIxxx 133, 301

CSLOSCX mapping macro 132 CSLRIxxx 134 CSLSIxxx 133 cursor 30–35, 37–38, 41, 44–48, 52, 168

D

Data Encryption 296 Data Refresher 296 database level tracking (DLT) 53 database pre reorganization utility (DFSURPR0) 200 Database Recovery Control (DBRC) 4, 6 database recovery utility (DFSURDB0) 46, 202 data-centric approach 146 DB/DC 11, 19-21, 23, 88, 192 DB/DC Data Dictionary 296 DB2 Information Management Software Information Center 27, 303 DB2 stored procedures 160, 225 DB2 Universal JDBC driver 161 DBCTL 11, 19-20, 23-24, 30, 88-89, 128, 161, 195, 224 DBFUHDR0 68 DBFULTA0 195 DBFUMDL0 68 DBFUMMH0 68 DBFUMRIO 68 DBFUMSC0 68 DBRC xv, 3-8, 11-17, 19-20, 26, 30-31, 35-36, 46-50, 52, 59, 61, 73-76, 78-81, 200, 221, 228, 230-232, 234, 236-238, 242, 244, 247-248, 251, 253, 255-256, 258, 260, 262, 264, 267, 269, 272, 274-275, 277, 279-281, 283-285 DBRC API 4, 6, 74, 76-79, 233-234, 236 DBRC application programming interface (API) 4, 6, 73–74 DBRC=FORCE 15 DBRC=NO 15 DBRC=YES 14-15 DCCTL 11, 19-20, 23, 88, 166 decomposed storage 146-148, 152, 157 DEDB 5, 58, 60-62, 64, 66, 69, 76, 83, 116, 120-122, 126, 146, 166, 212, 215, 235, 240, 256-257 DEDB Compare utility (DBFUMMH0) 68 DEDB Create utility (DBFUMRI0) 68 DEDB statement 58 DEDBMAS statement 59, 62 DEFINE LOGSTREAM statement 67 DELETE 116 DESC 11-13 DFS0488I 43 DFS0540I 165 DFS058I 217 DFS066 111 DFS067 111 DFS0832I 202 DFS1946W 215 DFS2634I 70 DFS26351 70 DFS2636I 70 DFS28221 63 DFS28511 63

DFS28531 63 DFS3210I 66 DFS3486 221 DFS3649A 209 DFS3676I 16 DFS3689W 98 DFS3715I 66 DFS3719I 66 DFS4172 211 DFS554A 202 DFSAINB0 208 DFSAOE00 91,93 DFSAPPL application 17 DFSCCMD0 91-94, 106-109, 112, 218 DFSCGxxx 111, 131-134, 301 DFSCNTE0 93 DFSCSGN0 104 DFSCTRN0 95-97, 108-109, 111 DFSCTSE0 108 DFSDCxxx 24, 96–99, 102–103, 113, 208, 218 DFSERA10 218-219 DFSERA30 186 DFSERA60 186 DFSFDRxx 212 DFSFIDN0 213 DFSIDEF0 14-15, 19-20 DFSILTA0 195 DFSINTX0 208 DFSISIS0 86, 88, 112 DFSISSOx 102-103 DFSIVPEX 22 DFSJBP 162 DFSJMP 162, 209 DFSJVMEV member 162 DFSJVMMS member 161 DFSLOG10 112 DFSLOG22 macro 128 DFSMPR 209 DFSMRC00 17 DFSMRC20 17 DFSMRCL0 11, 17 DFSMS 221 DFSMSCE0 95, 97, 111-112 DFSORSxx 292 DFSOVRDS DD statement 200 DFSPBxxx 11, 13-14, 24, 101-102, 104, 133 DFSPIRP0 186 DFSPREC0 53 DFSPSEIB macro 201 DFSRAS00 88-89, 112 DFSRRC00 201 DFSSGNX0 104 DFSSQ000 20 DFSSQxxx 24,67 DFSTCF 93 DFSTCFI 94 DFSTCNT0 93 DFSTRAxx 192 DFSUDUMP DD statement 46 DFSUOCU0 220

DFSUOLC0 132 DFSUPNT0 200-201 DFSURGL0 200, 202 DFSURGU0 200, 202 DFSUSVC0 16-17 DFSVC000 12-13 DFSVSAMP 54 DFSVSMxx 53-54, 58-59, 61, 200 DFSYDRU0 5, 206-207 DFSYIOE0 5, 206-207 DFSYPRX0 5, 206 DIMS RACF security class 105 **DISPLAY ACTIVE 210** DISPLAY Q 210 DISPLAY STATUS CLASS 210 **DISPLAY TRANSACTION 210** DLIModel xv, 4, 26, 146-147, 153-155, 176 DLIModel Utility xv, 4, 26, 147, 153-155, 176 DLT 10-11, 218 document-centric approach 146 DRF 47, 51, 289-292 DSP1100I 81 DSP1102I 81 DSPAPI FUNC=DSECT 75 DSPAPI FUNC=QUERY 75 DSPAPI FUNC=RELBUF 76 DSPAPI FUNC=STARTDBRC 75 DSPAPI FUNC=STOPDBRC 76 **DSPAPQAR** 76, 238 DSPAPQBO 76, 241 **DSPAPQCA** 76, 244 DSPAPQCG 76, 246 DSPAPQDB 76, 79, 248 DSPAPQDG 76, 250 DSPAPQDS 76, 249, 252 DSPAPQEL 76, 239, 253-254 DSPAPQFD 76, 256 **DSPAPQGG** 76, 258 **DSPAPQHB** 76, 260 DSPAPQHD 76-77, 79, 236 **DSPAPQHP** 77, 261 DSPAPQIC 77 **DSPAPQLA** 77, 267 **DSPAPQLG** 77, 269 **DSPAPQLI** 77, 272 DSPAPQNF 77, 273 **DSPAPQOL** 77, 275 DSPAPQRC 77, 277 **DSPAPQRI** 77, 280 **DSPAPQRR** 77, 281 DSPAPQRV 77, 282 **DSPAPQSL** 77, 284 **DSPAPQSS** 77, 285 DSPAPQxx macros 75-76, 78-79 DSPAPSMP sample program 74 DSPURX00 80, 82, 230-231 dynamic allocation 5, 45, 48, 51, 55, 75, 81 dynamic SVC update utility (DFSUSVC0) 16

Ε

Eclipse plug-in 4 EJB 139, 141–142, 169–170, 172, 174–177 enhanced command environment 7, 19, 21, 115–116 Enterprise Java Bean (EJB) 4, 6, 160 Enterprise Service application 139 ESAF 213 ESAF indoubt notification exit routine (DFSFIDN0) 213 ETO 11, 16, 20, 104, 106, 108–109, 208–209 ETO descriptor 16 ETOFEAT parameter 16 expedited message handler (EMH) 2, 6, 67 Extended Recovery Facility (XRF) 30, 52 Extended Terminal Option (ETO) 6–7, 10, 15 external subsystem attach facility (ESAF) 161, 213

F

Fast Database Recovery (FDBR) 8, 45, 52 Fast Path 2–3, 5–6, 11, 20, 57, 67–71, 76, 87, 93, 116, 212, 215, 235, 238, 252, 256, 290 FDBR 8, 24, 45, 52, 211–214 FMID 10, 225 FPOPN= 64–66 FPRLM= 66 FRXDRFxx 291–292 Function Modification Identifier (FMID) 10, 135 FunctionPac 10

G

GENJCL 51, 80, 240, 248, 254, 277 GENJCL.ARCHIVE 277 GENJCL.CA 46, 49, 51 GENJCL.IC 46, 51, 79, 81 GENJCL.RECOV 47, 49, 51, 80 GENJCL.UIC 51 GIMS RACF security class 88, 105 global online change 11, 128–130, 132 greeting messages exit routine (DFSGMSG0) 209 GSAM 4, 159, 166–167

Η

HALDB xv, 2-4, 8, 18, 29-36, 45, 50-51, 53-54, 76-77, 79, 81-83, 116, 120-121, 130, 134, 146, 200-202, 228, 231-232, 235, 248, 260-263, 284, 291-292 HALDB block 76, 260-261 HALDB Partition block 77, 260-263 HD Reload (DFSURGL0) 48 HD Unload (DFSURGU0) 48 High Availability Large Database 3, 8, 18 High Speed Reorganization utility (DBFUHDR0) 68 High Speed Sequential Processing utility (HSSP) 68 HIR2101 10 HIR2102 10 HMK9900 10, 135 HSRE 68 HSSP 68 HWSCFxxx 301

IBM Fault Analyzer 296 ICH408I message 111 ICHERCDE macro 87, 110 IEBCOPY 8, 220-221 IIMS RACF security class 87, 89, 98, 110, 224 ILDS 33, 35, 53 ILOGREC 68 Image Copy 2 202 Image Copy utility (DFSUDMP0) 202 IMS ADF II 296 IMS Advanced ACB Generator 296 IMS Application Menu 9, 17-19, 22, 180 IMS Batch Backout Manager 296 IMS Batch Terminal Simulator 296 IMS Buffer Pool Analyzer 296 IMS Checkpoint Wrapper 296 IMS Command Control Facility 296 IMS Connect xv, 5, 118, 135-140, 142, 224, 296, 301-303 IMS Connector for Java 10, 136-140, 142 IMS Database Control Suite 296 IMS Database Recovery Facility (DRF) 31, 46-47, 228, 289, 296-297 IMS Database Repair Facility 296 IMS DataPropagator 296 IMS DEDB Fast Recovery 296 IMS Dump Formatter 19 IMS ETO Support 296 IMS Fast Path Basic Tools 296 IMS Fast Path Online Tools 296 IMS HD Compression Extended 296 IMS HP Change Accumulation 296 IMS HP Fast Path Utilities 296 IMS HP Image Copy 296 IMS HP Load 296 IMS HP Pointer Checker 296 IMS HP Prefix Resolution 296 IMS HP Sysgen Tools 296 IMS HP Unload 296 IMS Image Copy Extensions 297 IMS Index Builder 297 IMS Java xv, 3-4, 10, 19, 26, 145-147, 153-154, 159-161, 163, 165-170, 172, 174, 176-178, 224-225 IMS Java remote database services 225 IMS Library Integrity Utilities 296-297 IMS Library Management Utilities 297 IMS MFS Reversal Utilities 297 IMS Multi-Dialog Manager 297 IMS Network Compression Facility 297 IMS Online Recovery Services 289, 297 IMS Online Reorganization Facility 297 IMS Parallel Reorganization 297 IMS Parameter Manager 297 IMS Performance Analyzer 297 IMS Performance Monitor 297 IMS Problem Investigator 297 IMS Program Restart Facility 297 IMS Queue Control Facility 297 IMS Records User Data Scrub 183

IMS Sequential Randomizer Generator 297 IMS Version 5 DEDB CI format 70 IMS Workload Router 297 IMSCTF macro 11, 16 IMSCTRL macro 11, 16 IMSGROUP 11-13 IMSID 11-13, 37, 68, 161, 192, 212 IMSplex 21, 45, 74, 111, 115–118, 128, 130–134, 204, 218, 279, 301-303 Indirect list data set (ILDS) 31, 33, 35, 53 INIT.DB 35, 49 INIT.DBDS 59 INIT.PART 49-50 INIT.RECON 83, 231 initialization exit routine (DFSINTXO) 208 INITIATE 116 INITIATE OLR command 39 INITIATE OLREORG command 39 INSTALIB 14, 24 installation verification program (IVP) 7, 9, 18-19 **INSTATBL 22** intact storage 4, 146-147, 151-152, 157 Integrated HALDB online reorganization (OLR) 4, 26, 29-30, 115 Integrated IMS Connect function 3, 10, 118, 136-137 Interactive Problem Control System (IPCS) 219 IPCS 19, 23, 69 IRLM 10, 19, 54, 64, 66-67, 191, 193, 221, 230, 240, 249, 263, 286-287 IRLM MODIFY command 212 IRLM reconnect options 66 IRLM= 13 IRM header 138 IV_D216T 23 IV_D217T_23 IV_D301T 24 IV_E207J 14, 20 IV_E304J 20 IV E307J 20 IV_G309T 23 IV H311T 23 IV J309T 23 IV_0102J 21 IV_0203J 21 IV 0205T 21 IV_0215J 21 IV_P001T 21 IV P101J 21 IV_P102J 21 IV_P103J 21 IV P104J 21 IV_P215J 21 IV_P217T 21 IV_P218T 21 IV_P221T 21 IV_P230T 21 IV P232T 21 IV_P401J 21 IVP 7, 11, 14-15, 18-24 IVP Export Utility 19

J

J2EE 4, 136, 138, 172, 175–176 J2EE Connector Architecture (J2C) 138–139 J2EE server 174, 176 JCICS 160 JDBC xv, 3, 161–162, 168, 170, 172, 174–178, 225 JDBC/SQLJ driver 161 JIMS RACF security class 88, 110, 224 JMK9901 10 JMK9902 10 JMK9903 10 JMK9904 10 JMK9905 10 JMK9906 10

Κ

KBLA 18, 179–182, 184–185, 188–191 Knowledge Based Log Analysis (KBLA) 18, 179

L

LIMS RACF security class 88, 98, 109–110, 224 LIST.RECON 74, 81, 231 LKASID 58, 61–62 LOGR policy 67

Μ

management class 23 MAS 59, 83 MCS 11–13 MDL0 68 migration 9, 17, 19, 24, 70, 73, 82, 86–87, 102–103, 108, 112, 208, 223–224, 226, 232 MIMS RACF security class 88, 110, 224 MINVERS 83, 231 MMH0 68 MRI0 68 MSC0 68 MSCSEC= 97 multi-area structure support 5

Ν

NODEL 38–41, 45 NOLKASID 58, 62 NOPDBO statement 200 NOTIFY.IC 49 NOTIFY.REORG 49 NOTIFY.UIC 49

0

OLDS 54, 75, 124, 126, 193, 217, 219, 221, 234, 271, 275–277 OLR 4, 29–56, 81–83, 120, 232, 254, 263–264, 287 OLR log records 43 OLRCAP 35, 49–50 OLRNOCAP 35, 49–50, 232 OM 7, 21, 39, 115–118, 127–134, 217–218, 301 OM API 116–117, 119 OM security user exit 128, 132, 218 OMPROC= 131, 133 on demand 1 on demand business xv, 1–3, 136 online change 7–8, 15, 130–132, 134, 203, 215 online log data set (OLDS) 5–6, 75 open transaction manager access (OTMA) 5 Operations Manager 7, 21, 133, 301, 307 Operations Manager (OM) API 7, 115–116 OTMA 5–6, 137–139, 142, 203–205 OTMA destination resolution exit (DFSYDRU0) 207

Ρ

partition data set initialization utility (DFSUPNT0) 200-201 Partition Definition Utility (PDU) 18, 80, 82 partition initialization needed flag (PINIT) 200-201 PDU 18 PHDAM 30-31, 34, 37, 41, 44, 48, 54, 261 PHIDAM 30-31, 34-37, 41, 44, 48, 53-54, 261 PQ32932 224 PQ46673 225 PQ48383 225 PQ49638 200 PQ50443 225 PQ54585 224, 227 PQ55002 200 PQ57320 174 PQ58631 224 PQ62379 224 PQ66507 212 PQ66531 212 PQ66549 204 PQ68350 204 PQ69527 301 PQ69861 226 PQ69897 297 PQ70216 224 PQ72838 82, 230 PQ72840 82, 230 PQ73326 225 PQ73630 71 PQ73631 71 PQ73897 225 PQ74606 64 PQ74629 225 PQ75284 225 PQ77559 228 PQ78493 51, 82, 231 PQ78758 51, 82, 231 PQ78916 51, 82, 231 PQ78917 51, 82, 231 PQ79074 297 PQ79075 296 PQ79146 296 PQ79162 228 PQ79326 228 PQ79327 202, 228

PQ79473 297

PQ79474 297

PQ79485 225 PQ79840 296 PQ79842 297 PQ79845 296 PQ79849 296 PQ80051 228, 296 PQ80052 228, 296 PQ80182 296 PQ80183 296 PQ80186 296 PQ80187 297 PQ80190 297 PQ80191 296-297 PQ80193 296 PQ80197 296 PQ80198 296-297 PQ80199 297 PQ80200 296 PQ80214 296 PQ80215 296 PQ80216 297 PQ80221 296 PQ80264 212 PQ80331 297 PQ81944 225 PQ83386 297 PQ83387 296-297 PQ83453 296 PQ83568 297 PQ83801 296 PQ83869 297 PQ83940 221 PQ83941 221 PQ83942 221 PQ84689 296 PQ84911 297 PQ85111 297 PQ85342 297 PQ85616 296-297 PQ85681 297 PQ86024 213 PQ86664 296 PQ86995 297 PQ88094 213 PQ88453 297 PQ89630 296 PQ90051 137 PQ94701 296 PQ95289 296 PROCLIB 7, 13–14, 20–21, 24–25, 53, 61, 67, 96–99, 101-104, 111, 131-134, 161-162, 212, 291-292, 301 product integration openness 3 product packaging 9 ProductPac 10 **PSINDEX 31, 261** PSTOP TRANSACTION CLASS 210 PURGE TRANSACTION CLASS 210

Q

QUERY 116, 119, 210

QUERY AREA 122 QUERY DB 120 QUERY MEMBER 133 QUERY OLC 133 QUERY OLR command 39 QUERY OLREORG command 41 QUERY TRAN 133, 210, 307

R

RACF 6, 80, 86-89, 91-95, 97-98, 100-113, 127-128, 132, 177, 204-205, 218, 224-225 RACROUTE macro 86 RATE 30, 39-42, 44-45, 55 RECON xv, 21, 32, 35, 37-38, 41, 45, 47-48, 50, 52-53, 62, 64, 73-77, 79-83, 130, 200, 223, 227-232, 234-235, 277-279, 290-292 RECONs 230 recovery-level-tracking (RLT) 53 Redbooks Web site 314 Contact us xvii remote database services 4, 10, 19, 169-170, 172, 176, 225 Remote Site Recovery (RSR) 30, 52 resource access security exit routine (DFSRAS00) 88 Resource Manager 7, 11, 21, 116, 128, 134, 218 resource recovery service attach facility (RRSAF) 161 Resource Recovery Services (RRS) 138, 161–162, 174 resource structure 116, 128-130, 218 RGSUF 11, 13 RLT 10-11, 218 RM 116, 128-130, 132, 134 RMENV= 131-134 RMI/IIOP 140-141 RRS 138, 161-162, 213, 225 RRSAF 161 RSR 10-11, 52-53, 69, 192, 218, 228, 240, 250, 254, 259, 264, 287

S

SAF 80, 85-87, 89, 91-95, 97-98, 101-111, 113, 127 SBONLINE parameter 53 SCI 21, 117 SCIPROC= 131, 133 SDEP Delete utility (DBFUMDL0) 68 SDEP Scan utility (DBFUMSC0) 68 SDFSDATA 301 SDFSEXEC 17 SDFSMAC 74, 213 SDFSRESL 11-12, 15-16, 22, 74, 201, 213, 292 SDXRRESL 230 SECURITY macro 88, 91-92, 98, 100-101, 104-105, 113 security maintenance utility (SMU) 6, 85-86 ServerPac 10 shared virtual storage option (SVSO) 5 shared VSO 58-59, 62 sign on exit routine (DFSSGNX0) 102 sign on/off security exit routine (DFSCSGN0) 102 SIGNON= 99

SIGNON=ALL 99, 102-103, 113 SIGNON=SPECIFIC 99, 102-104, 113 single point of control (SPOC) 7, 300 small programming enhancement (SPE) 231 SMP/E 10-11, 15-16 SMS management class 19 SMS storage class 19, 23, 36 SMS-managed 35 SMU 6, 85-89, 91-95, 98-105, 108-109, 111-112, 124 SOAP 6, 139-141 SPE 35, 51, 82-83, 228-229, 231-232 SPOC 18, 21, 117-118, 128, 217, 307 SQL xv, 4, 156, 159, 161-162, 167-169 START CLASS 210 START TRANSACTION CLASS 210 STOP CLASS 210 STOP TRANSACTION CLASS 210 storage class 35 STRUCTURE statement 67 Structured Call Interface 21, 117 SVC 99 75 SVC number 12, 16 SVC2 11-13 SVSO 5, 57, 59-62, 212 symbolic checkpoint and restart support 4, 159, 163, 166 Syntax Checker 7, 9, 11, 18, 24-26 sysplex terminal management (STM) 129 System Authorization Facility (SAF) 85-86 system definition 11, 14–16, 19, 55, 88, 91–92, 98–100, 103-105, 209, 227 system generation 3, 7, 11-12, 15-16, 217 SystemPac 10

Т

takeover 52-53, 213, 221 TERMINAL macro 100, 103-104 TERMINATE 46, 116 TERMINATE OLREORG command 39-40, 46 TIMS RACF security class 87-88, 98, 105 TMAMAGNG 205 TMAMSAGN 205 TPIPE 5, 203-204, 207 transaction authorization exit (DFSCTRN0) 98, 108-109 TSO single point of control (TSO SPOC) 18, 116 TSO SPOC 18, 39, 117-118, 121, 123, 125, 128 TYPE macro 100, 103 type-1 command 7, 36, 39-40, 42, 115, 118-120, 123–125, 127, 217 type-2 command 7, 21, 30, 36, 39-40, 115-119, 128-131, 134

U

U085x user abends 202 U0880 user abends 202 U3303 user abends 202 U3476 user abends 16 U3498 user abends 202 unit of reorganization (UOR) 30, 37 UOR 34, 37, 40–41, 44–45, 52, 54 UPDATE 116, 119, 210 UPDATE AREA 126 UPDATE DATAGRP 126 UPDATE DB 123–124 UPDATE OLREORG command 39–40 UPDATE TRAN 210 UQ74475 167 UQ74520 167 UQ75641 167 UQ80615 161, 225

V


virtual storage constraint relief (VSCR) 3, 212, 215 VSO 69, 122, 240–241 VSO keyword 58 VSO PRELOAD option 64 VSO structure 62–63

W

WADS 190, 221
WebSphere Application Server 10, 136, 138, 146, 159, 169–170, 172, 174–177, 225
WebSphere Studio 10, 137, 142, 147, 155, 226
write ahead data set (WADS) 5–6
write-to-operator (WTO) 8
WSADIE 10, 137, 139, 147, 155, 226
WTO 8, 211
WTOR 8, 80, 211, 217

X

XML 3-4, 6, 117-118, 128, 139, 145-157 XML schema 4, 141-142, 147-148, 153-154, 157 XML storage 3-4, 145, 159 XRF 19-20, 23, 212, 218, 221, 285, 287 XRF takeover 213





IMS Version 9 Implementation Guide: A Technical Overview





IMS Version 9 Implementation Guide A Technical Overview



Get familiar with the HALDB online reorganization feature

See the possibilities of these new technologies - IMS Java and XML

Explore all the new features of IMS Version 9 This IBM Redbook provides an overview of the new functions and enhancements in IBM Information Management System (IMS) Version 9. IMS Version 9 contains over 50 enhancements, in all areas of the product. that address availability, scalability, capacity, usability, manageability, operations, on demand business, and application development requirements from its huge customer base. All of the enhancements in this new version resulted from specific customer requirements. The major enhancements include:

- Improved database availability for HALDB databases is provided by the long-awaited online reorganization (OLR) enhancement.
- The functionality of the IMS Connect product is included as an integrated function of IMS.
- DBRC provides a new API that allows assembler programs to query the RECON.
- IMS Java users will have new JDBC SQL calls and DLI Model Utility support for retrieving existing IMS data in XML format as well as storing, indexing, searching, and retrieving valid XML documents into new or existing IMS databases.

We describe these enhancements and all other major changes in IMS Version 9. This redbook gives you the essential information that you need when you are migrating your IMS systems to IMS Version 9.

INTERNATIONAL TECHNICAL SUPPORT ORGANIZATION

BUILDING TECHNICAL INFORMATION BASED ON PRACTICAL EXPERIENCE

IBM Redbooks are developed by the IBM International Technical Support Organization. Experts from IBM, Customers and Partners from around the world create timely technical information based on realistic scenarios. Specific recommendations are provided to help you implement IT solutions more effectively in your environment.

For more information: ibm.com/redbooks

SG24-6398-00

ISBN 0738491578