



vImpact

Dytran 5800SL

- ***Automatic Modal Hammer***
- ***Dytran 5800SL Impulse Hammer***
- ***Adjustable Impact Rate***
- ***Timer Operation***
- ***External Controllable***
- ***Frequency Range up to 20kHz***
- ***Highest Impact Reproducibility***



Automatic Modal Hammer

A manual excitation with a small Modal hammer without a „Double Hit“ is nearly impossible – a well-known and very inconvenient issue.

As solution for this issue MAUL-THEET developed the automatic Modal hammer *vImpact*. This enables you to precisely and reproducibly excite structures and measure the excitation forces. The frequency ranges up to 20 kHz make the small Modal hammer very interesting for acoustic or laser measurements.

The *vImpact* system is divided into two components:

- Hammer head
- Control unit

The hammer head includes a small Modal hammer who has an integrated force cell and the electro dynamic actor that moves the hammer.

The control unit sends the impulse that moves the Modal hammer to the actor inside the hammer head. The measured force signal is at the output of the control unit available.



The hammer can be triggered by several methods:

- Manually with the trigger button at the control unit.
- By closing the external input with a switch through an extension wire or by any device with a closing contact.
- By TTL-Signal
- With the internal timer in the range of 3 hits per second up to 1 hit per 1000 second.



Technical Specifications:

Frequency range	0-20kHz, depending on object
Sensitivity	25 mV/N
Measuring range	222 N pk
Resonance Frequency	$\geq 300\text{kHz}$
Nonlinearity	$\leq 1\%$
Output impedance	$< 100\Omega$
Coupling	2-20mA, IEPE
Trigger	Button, Timer External switch (Closers) TTL-Signal 40....200 ms Timer
Power supply	12-15V DC

Information:

For further information, please contact us under the address given below!

MAUL-THEET GmbH
Bülowstrasse 66
D-10783 Berlin
tel: 0049 (0) 30 8620 7775
fax: 0049 (0) 30 8620 7568
info@maul-theet.com