NEW Calibrated Xenon Light Source L7810



is a logo mark for an accreditation system based on Japanese Measurement Law. Our Planning & Engineering Division is accredited in accordance with ISO/IEC Guide 25: 1990 in the field of photometry calibration.

(Our accreditation number is 0081.) [JCSS: Japan Calibration Service System (The Japanese Goverment accreditation scheme for calibration laboratories and a signatory of APLAC Mutual Recognition Arrangement)]

▲LEFT: LAMP HOUSING, RIGHT: POWER SUPPLY

FEATURES

■High Stability

Stability is one of the important characteristics of calibrated light sources. Hamamatsu's excellent cathode technology and optimized lamp housing realize high stability and good repeatability.

•Light Intensity Drift (Typ.)



■High Power

IAMAMATSU

A Xenon lamp emits high intense UV, visible and IR light so that a reliable measurement can be possible even in the range of 300 nm to 400 nm, where either a deuterium lamp or a tungsten lamp doesn't deliver enough light.



•Comparison of Spectral Irradiance (Reference data) : 50 cm away from light source

WAVELENGTH (nm)

SPECIFICATIONS

Lamp		Xenon Lamp	Input Voltage		100 Vac/115 Vac/200 Vac/230 Vac
Input Wattage		150 W	(switched manually)		(±10 %), 50/60 Hz
Spectral Distribution		185 nm to 2000 nm	Power Consumption		500 VA
Calibrated Range [®]		250 nm to 800 nm	Cooling (Lamp Housing,		Forces Air Cooling
Type of Calibration		Spectral Irradiance	Power Supply)		(cooling fan is included)
Calibration Unit		µW⋅cm ⁻² ⋅nm ⁻¹	Ambient Temperature		0 °C to 40 °C
Stability	Fluctuation (p-p)	1.0 % Max.	Humidity		30 % to 90 %
	Drift	±0.5 %/h Max.	Dimensions	Lamp Housing	100 mm $ imes$ 280 mm $ imes$ 100 mm
Window Material		Synthetic Silica	$(W \times H \times D)$	Power Supply	144 mm $ imes$ 176 mm $ imes$ 280 mm
(Lamp Housing)				Case ^D	595 mm \times 425 mm \times 345 mm
Warm-up Time		10 min		Lamp Housing	Approx. 3.5 kg
Recommended Calibration		100 hours or 1 year whichever	Weight	Power Supply	Approx. 10 kg
Period [®]		comes first		Case ^D	Approx. 7.8 kg
Guaranteed Life [©]		500 hours			

NOTE: AThe calibrated value is the light power at 50 cm away from front surface of lamp housing.

BThis is the recommended calibration period when high reliability is required. Please contact to our sales office for re-calibration fee.

©This is the guaranteed time the unit satisfies requirements as calibrated light source.

DThis is an accessory coming with the unit.

DIMENSIONAL OUTLINES (Unit: mm)



Subject to local technical requirements and regulations, availability of products included in this promotional material may vary. Please consult with our sales office. Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2000 Hamamatsu Photonics K.K



HOMEPAGE URL http://www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Electron Tube Center

314-5, Shimokanzo, Toyooka-village, Iwata-gun, Shizuoka-ken, 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P. O. Box 6910, Bridgewater. N.J. 08807-0910, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658 E-mail: info@hamamatsu.de France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, Ofedex, France, Telephone: (49)6159 53 71 00. Fax: (33)169 53 71 10. E-mail: france@hamamatsu.com United Kingdom: Hamamatsu Photonics VK Limited: Lough Point, 2 Gladbeck Way, Windmill Hill, Enfield, Middlesex EN2 7JA, United Kingdom, Telephone: 44(20)8-367-3560, Fax: 44(20)8-367-6384 E-mail: info@hamamatsu.co.uk North Europe: Hamamatsu Photonics Italia: S.R.L.: Strada della Moia, 172, 20020 Arses (Milano), Italy, Telephone: (46)9-509-031-00, Fax: (46)8-509-031-01 E-mail: info@hamamatsu.et TLSO1039E01

TLSO1039E01 JUN. 2000 SI Printed in Japan(1000)