



SOT-23



Pin Definition:

TS803	TS803R
1. Ground	1. <u>Reset</u>
2. <u>Reset</u>	2. Ground
3. Vcc	3. Vcc

TS803

Microprocessor Reset Circuit

General Description

The TS803/TS803R are microprocessor (μ P) supervisory circuit used to monitor the power supplies in μ P and digital systems. They provide excellent circuit reliability and low cost by eliminating external components and adjustments when used with +5V, +3.3V, +3.0V powered circuits. These circuits perform a single function: they assert a reset signal whenever the VCC supply voltage declines below a preset threshold, keeping it asserted for at least 140ms after VCC has risen above the reset threshold. Reset thresholds suitable for operation with a variety of supply voltages are available. The TS803/TS803R are open-drain outputs. The TS803/TS803R have an active low RESET output, while the TS803/TS803R has an active high RESET output. The reset comparator is designed to ignore fast transients on VCC, and the output guaranteed to be in the correct logic state for VCC down to 1V. Low supply current makes the TS803/TS803R ideal for use in portable equipment.

Features

- Precision monitoring of +3V, +3.3V & +5V power supply voltage
- Fully specified over temperature
- Available in three output configurations
- Open-Drain RESET low output
- 3uA supply current
- Guaranteed reset valid to Vcc = +1V
- Power supply transient immunity
- No external components

Applications

- Computers
- Controllers
- Intelligent Instruments
- Critical uP and uC power monitoring
- Portable / Battery Power Equipment
- Automotive

Ordering Information

Part No.	Package	Packing
TS803CX \underline{x} RF	SOT-23	3Kpcs / 7" Reel
TS803RCX \underline{x} RF	SOT-23	3Kpcs / 7" Reel

Note: \underline{x} is the threshold voltage type, option as

TS803 Threshold Voltage

A : 4.63V	B : 4.38V	C : 4.00V	D : 3.08V
E : 2.93V	F : 2.63V	G : 2.32V	H : 2.1V
I : 2.0V	J : 1.8V	K : 1.6V	

TS803R Threshold Voltage

B : 4.20V	E : 2.93V	F : 2.70V
------------------	------------------	------------------

Contact factory for additional voltage options.

Absolute Maximum Rating

Parameter	Symbol	Value	Unit
Supply Voltage	V _{CC}	7	V
<u>RESET</u> & (RESET) Open Drain	V _{RESET}	- 0.3 ~ (V _{CC} +0.3)	V
Input Current, V _{CC}	I _{CC}	20	mA
Output Current, <u>RESET</u>	I _O	20	mA
Rate of Rise, V _{CC}	V _R	100	V/uS
ESD Classification		B	

Note: Stress above the listed absolute maximum rating may cause permanent damage to the device
HBM B: 2000V~3999V

Recommended Operating Conditions

Parameter	Symbol	Value	Unit
Supply Voltage	V_{CC}	<5	V
Operating Ambient Temperature Range	T_A	-40 ~ +85	°C
Operating Junction Temperature Range	T_J	-40 ~ +125	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	°C
Thermal Resistance	Θ_{JC}	325	°C/W
Power Dissipation	P_D	350	mW
Lead Soldering Temperature (260°C)	T_{LEAD}	10	S


Electrical Characteristics $T_A=25^\circ\text{C}$, unless otherwise specified.

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Input Supply Voltage	$T_A=-40^\circ\text{C}\sim+85^\circ\text{C}$	V_{CC}	1.0	--	5.5	V
Supply Current	$V_{CC} \leq V_{TH} * 1.1$	I_{CC}	--	--	3	uA
	$V_{IN} = 3V, T_A=-40^\circ\text{C}\sim+85^\circ\text{C}$		--	--	5	
Reset Threshold		V_{TH}	0.985 $ V_{TH} $	--	1.015 $ V_{TH} $	V
Reset Threshold (Full temperature range)		V_{TH}	0.97 $ V_{TH} $	--	1.02 $ V_{TH} $	V
Reset Threshold Temperature Coefficient		V_{TH}	3-0	50	160	ppm/°C
V_{CC} to Reset Delay	$V_{CC} = V_{TH}$ to $(V_{TH} - 100\text{mV})$	T_{DELAY}	--	40	--	uS
Reset Active Timeout Period	$T_A=-40^\circ\text{C}\sim+85^\circ\text{C}$		0.5	1.5	5	mS
<u>RESET</u> Output Voltage Low	$V_{CC} < V_{TH(MIN)}, I_{SINK} = 1.2\text{mA}$,	V_{OL}	--	--	0.5	V
<u>RESET</u> Output Voltage High	$V_{CC} > V_{TH(MAX)}, I_{SOURCE} = 500\text{uA}$ $V_{CC} > 1.8V$	V_{OH}	0.8 V_{CC}	--	--	V
	$V_{CC} > V_{TH(MAX)}, I_{SOURCE} = 150\text{uA}$, $1.8V \geq V_{CC} > 1V$					

Note 1: The data based on $V_{TH} = 2.7V$ part type.


Note 2: Guaranteed by Design

Function Block




Function Description

Typical Application Circuit



Timing Diagram



Electrical Characteristics Curve




Figure 1. Glitch Rejection




Figure 2. Reset Time vs. Temperature

Electrical Characteristics Curve (Continue)




Figure 3. I_{IN} vs. Temperature




Figure 4. Reset V_{th} vs. Temperature




Figure 5. I_{IN} vs. V_{IN}




Figure 6. Threshold Hysteresis vs. Temperature





Figure 7. Reset V_{OL} vs. Temperature

SOT-23 Mechanical Drawing



SOT-23 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX.
A	0.95 BSC		0.037 BSC	
A1	1.9 BSC		0.074 BSC	
B	2.60	3.00	0.102	0.118
C	1.40	1.70	0.055	0.067
D	2.80	3.10	0.110	0.122
E	1.00	1.30	0.039	0.051
F	0.00	0.10	0.000	0.004
G	0.35	0.50	0.014	0.020
H	0.10	0.20	0.004	0.008
I	0.30	0.60	0.012	0.024
J	5°	10°	5°	10°

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.