C2G

Discontinued - Mobile Device USB Micro-B to HDMI™ Display MHL Adapter Cable

Part No. CG-29351



The Mobile Device USB Micro-B to HDMI Display MHL 1 Adapter Cable is the perfect solution for connecting the USB Micro-B port of a MHL enabled tablet, smartphone or other mobile device to the HDMI port on a display. This adapter will support up to a 1080p resolution with up to 7.1 channel digital audio depending upon the capabilities of the mobile device and the display. This adapter will allow high definition movies, photos, games, the Internet browser and other content from the mobile device to be shown on the connected display.

Connecting a separate USB-A to Micro-B cable, such as the charging cable or adapter for the mobile device, to the USB Micro-B female port on the adapter is recommended during operation. This cable (sold separately) will provide supplemental power to the adapter and charge the mobile device while content is being shown on the display.. MHL technology makes this connection easy and does not require a driver, software or lengthy setup time. Simply connect the adapter to the Micro-B port on a MHL enabled mobile device, then use a standard HDMI cable (not included) to connect from the HDMI port of the adapter to the HDMI port of a display and the content on the mobile device can be shown on the connected display.

Note: The smartphone, tablet or other mobile device used with this adapter must support MHL 1 technology. Consult the manual of the mobile device to ensure support for MHL 1 technology. This adapter is designed to support devices that use the 5-pin Micro-B and will not support devices that require an 11-pin connection, such as the Samsung Galaxy S3 and Samsung Galaxy S4.

Features & Benefits

Connects the USB Micro-B port of a MHL enabled device to the HDMI port on a display

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120293514	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Adapter, Cable

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Bend Radius	40 mm
Cable Type	Adapter, USB, Video	Data Transfer Rate	480 Mbps
Connector 2	USB Micro-B Female, USB Micro-B Male	Connector 1	HDMI Female
Video Output Support	HDMI		