Product Data Sheet

QB100 Degreaser

Description

Castrol QB 100 is a solvent based, water emulsifiable multi purpose degreaser. The advanced quick break formulation allows for rapid separation of oil and grease from waste water as required but many effluent disposal systems. The quick break properties of Castrol QB 100 permit recovery of the oil and grease for correct disposal when collected in an effluent pit or sump.

Application

Castrol QB 100 may be used in a wide variety of degreasing applications on all metals, wood, glass, ceramics and concrete. It is ideal for cleaning engines, machinery, automotive components and workshop floors. Castrol QB 100 can be applied by brush, swab, spray or in an immersion tank. Apply to the surface to be cleaned and allow time to penetrate the dirt deposits (5-10 mins), then rinse with fresh water. After rinsing the cleaning solution should be collected in an effluent pit or sump where oil and grease residues will quickly separate to allow safe disposal of the contaminants.

Advantages

PRODUCT FEATURES & BENEFITS

Convenient to use, just brush, swab or spray on and wash off
Washes off easily with water then separates so that grease and oil can be recovered for proper disposal
High flash point above 60C (Closed), reduces the risk of fire when using
Suitable for a wide range of degreasing applications
Quick break properties allow more rapid and cost effective downstream treatment of the waste water

Removal

Bare Metal Surfaces: Remove with Castrol solvent cleaners or water based degreasers.
Hand Cleaning: Use any of the Castrol range of hand cleaners, e.g. CareClean Plus.
Other Surfaces: Contact the Castrol Technical Advice Line on 0800 10 40 60.

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ , BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz