pe.eaton.com



Eaton Series C complete molded case circuit breaker

FD2225L

UPC:786679015285

Dimensions:

- **Height:** 2.75 IN
- **Length:** 3.38 IN
- **Width:** 2.75 IN

Weight:4.5 LB

Warranties: No Data

Specifications:

- **Amperage Rating:** 225A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 35 kAIC at 480 Vac
- **Number Of Poles:** Two-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** FD
- **Circuit Breaker Frame Type:** Complete breaker
- **Series:** Series C
- **Terminals:** Line and load
- **Frame:** F-frame
- **Frequency Rating:** 50-60 Hz

Supporting documents:

- Application of Multi-Wire Terminals for Molded Case Circuit Breakers
- UL listed 100%-rated molded case circuit breakers
- Application of Tap Rules to Molded Case Breaker Terminals
- StrandAble terminals product aid
- Plug-in adapters for molded case circuit breakers product aid
- Multi-wire lugs product aid

- MOEM MCCB Product Selection Guide
- Circuit breaker motor operators product aid
- Motor protection circuit breakers product aid
- Power metering and monitoring with Modbus RTU product aid
- Current limiting Series C molded case circuit breakers product aid
- Molded case circuit breakers
- FD2 2D PDF
- FD2 3D Model Xchange
- Time Current Curves for Series C® F-Frame Circuit Breakers
- FD2 AutoCAD 2D Footprint (mm)
- FD2 3D Inventor
- Installation Instructions for EHD, EDB, EDS, ED, EDH, EDC, FDB, FD, HFD, FDC, HFDDC Circuit Breakers and Molded Case Switches
- Breaker service centers
- Counterfeit and Gray Market Awareness Guide
- MOEM MCCB product selection guide
- Series C J-Frame molded case circuit breakers time current curves
- Series C G-Frame molded case circuit breakers time current curves
- Eaton Specification Sheet - FD2225L
- Series C F-Frame molded case circuit breakers

Certifications:

- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.