Product Data Sheet

Castrol Transmax Dex/Merc

Automatic Transmission Fluid

Description

Castrol Transmax™ DEX/MERC Domestic Multi-Vehicle Transmission Fluid is for use in older Ford and General Motors vehicles.

Advantages

- Enhanced friction durability for smooth transmission performance
- Meets DEXRON®-IIIH requirements. Also satisfies requirements of DEXRON®, DEXRON®-III, IIE and II. Do not use this ATF in applications calling for DEXRON®-VI. Use Castrol Transmax™ Type F ATF in applications calling for Type F.
- Meets MERCON® requirements. May also be used in power steering applications where MERCON® is required. Do not use this ATF in applications calling for MERCON® V or MERCON® SP.

Warranty and Protection Requirements

Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-IIIH or MERCON® type ATF is specified

Industry Specifications and OEM Approvals

Meets or Exceeds General Motors DEXRON®-IIIH Requirements

- Meets or Exceeds Ford MERCON® Requirements

Typical Characteristics

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	32
Viscosity at 100°C, cSt	ASTM D-445	7.2
Viscosity Index	ASTM D-2270	200
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	17,000
Pour Point, ºC (ºF)	ASTM D-97	-43(-45)
Flash Point, °C (°F)	ASTM D-92	177(350)
Specific Gravity, 60°F	ASTM D-1298	0.863
Pounds per Gallon	ASTM D-287	7.19

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

Meets Ford Mercon
GM - Dexron IIIH

User Advice

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDSs are available upon request through your sales contact office, or via the internet at www.castrol.com/ar. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1.800.462.0835
www.castrol.com/ar