Product Data

Ford - Castrol Magnatec Professional D 0W-30

Instant protection from the moment you turn the key

Description

Ford-Castrol MAGNATEC PROFESSIONAL D 0W-30's intelligent molecules protect from the moment you turn the key. They cling to the engine like a magnet providing an extra layer of protection, dramatically reducing* engine wear.

Ford-Castrol MAGNATEC PROFESSIONAL D 0W-30's unique formulation delivers protection you can see, hear and feel. It is now certified CO_2 neutral according to the highest global standards. Engineered with Micro-Filtration in order to meet Castrol PROFESSIONAL's new quality standard and verified using Castrol's new Optical Particle Measurement System (OPMS) to guarantee product quality.

**As tested in the industry Sequence IVA wear test*

Application

Ford-Castrol MAGNATEC Professional D 0W-30 is tailor made with Ford for use in their latest diesel engines that require a 0W-30 lubricant that meets Ford WSS-M2C950-A specification.

Advantages

Ford-Castrol MAGNATEC PROFESSIONAL. Instant Protection From The Moment You Turn The Key.

Ford-Castrol MAGNATEC PROFESSIONAL D 0W-30 delivers superior performance under extreme cold start up conditions.
.
Ford-Castrol MAGNATEC PROFESSIONAL D 0W-30 is a fully synthetic lubricant**.** It's specially developed for use in Ford vehicles.

Typical Characteristics

Name	Method	Units	Ford-Castrol Magnatec Professional D 0W-30
Density @ 15°C, Relative	ASTM D4052	g/ml	0.847
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	9.6
Viscosity, CCS -35°C (0W)	ASTM D5293	mPa.s (cP)	5800
Viscosity, Kinematic 40°C	ASTM D445	mm²/s	45
Viscosity Index	ASTM D2270	None	203
Pour Point	ASTM D97	°C	-50
Flash Point, PMCC	ASTM D93	°C	206
Ash, Sulphated	ASTM D874	% wt	0.78

Product Performance Claims

Meets Ford WSS-M2C950-A

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk