

I'm not robot!

Auma sar 10.2 manual

Requirements for safe handling of product5 Department distribution for review of DasHatu17 185.3.2.1 connection types. Install the rotary gear using the 195.3.2.2 plugin. Threaded connection from the Finishing21 forms connection forms b/c/d and e225.3.3.1. Rote Drive with type B connection.
Installation 23 protective pipes of the mixer embankment erecting 24 assembly positions on the controller mounting site 25 Mounting position 25 SD electrical connection (AUMA cover connection) 28 connection room) 3 Object connection 34 Accessories for electrical connections 35 ACCO For mounting on the ICLIO35 wall. Equipment equipment activation of installation 36 in manual mode 37 Settlement of payments in ORT38 Menu management using remote control 39 using the keys (for settings and screens) 39 Structure and password. input 40 correct starting password41 45 When starting the drive for the actuator and valve 49 - recommendations 50 City registration 51 messages (outputs) 53 messages about the state using detectors (digital outputs) 53 Similar reports (analog outputs) Connections 5 / control 55 connections (items) 55 Basic connection (zero setting) Installation 5 5 (mounting sticker) Installation / control 56 Go to the position above the 57 local control unit. Go to the remote control position 5810.1.10.
Game level 5910.1.11. Specify/verify reporting behavior in accordance with Regulation 5910.1.12. Justification of the intermediate position hysteresis 60 Setting the torque switch 60 checks the direction of rolling of the roller shaft/wave errors 62 when starting, 64 error messages and warning 64 fuses in the shield regulatorRequirements for the safe processing of the Incorporation5 product in Valve17 \ XC3 \ X9C Presentation of the types of compounds 185.3.2.1. Turn the reader with the TAGE connection type 195.3.2.2. The connection of the wind wind ends 21 of the form of the connection b / c / d and E225.3.3.1. Apply the rotation reader using the assembly reading of the connection 23 of the protection pipe from the contacts for the provisions of the rope valve 24 in the suburban installation provisions of 25 \ xc3 \ x84 modify the Electric connection SD (round plugin Auma) 28 Space Connection (for \ xc3 \ xbcr (for network connection).) Connection) Schl IE \ XC3 \ X9FEN32 Connection to the field tire \ X96 Open 33 Closing Field Tire Closure \ XC3 \ X9 Open Connection Accessories35 Connection on the wall 35erd external connection \ xc3 \ x4 Site 38 39 menu \ xc3 \ xb Operation \ xc3 \ xbüb on keys (f \ xc3 \ xbcr Parameters and display) 39 Structural structure and navigation of level D 'User40, Password password41 if password input 43 is inserted.
Display in accordance with AUMA category 49 state displays in accordance with the NAMUR recommendations on ADS Control ADS (output signals) 53 american Reports \ XBC via Detectorelais (digital output \ XC3 \ XA4NGE) Message (analogue output \ XC3 \ XA4ng E) 53 antis. Main parameters) 54 ArchwearDfestil Funcation54 type of reader parameter / PR \ XC3 \ XBCFEN54 PARTIONS OF STATION / PR \ XC3 \ XBCFEN55. Install üsse (positions) 55homeport (zero position) 55 positions (valves Pak \ XC3 \ XBCSSE) SAFT / PRCFENC5MOVE \ X to the position \ XC3 \ XBCVIA Local controller button 57 von of a dote color in the position of 5810.1.10. Compensation for the game 5910.1.11. Set of position ratio / PR \ XC3 \ XBCFEN5910.1.12. Hysteresis for the message of intermediate positions installation 60 switching switchesInstall the reader with connection form ADD195.3.2.2. Basic threaded connection. Connection forms B/C/D and E225.3.3.1. Mold production process in form 21. Replace reader with connection B form B ADS23 pin leading from Spinel 24 Sno anspection Spection to create local tax position25 'Connection Ndern25-Electro SD (AUMA circuit bandage) 28 Connection (for mains connection) ã FFNEN29 Place for connection (main connection) Last room closed room for control control control 35 control control 35 on the handle 35erdung connection 36 INDITION Active, drive control Place38 Fern39menüt used on the action drive 38. Print button (for parameters and displays) structural structure and navigation40 user level, user level, user level, user level. Password 41 password. Category AUMA 49SDADUS AD According to NAMUR 50 registration sites recommendations for the tax inspector 51 (output signals) 53 Sensor status reports (digital output) 53 Analog reports (analog output) 53 Input (basic parameters) 54 Functional Kit multiport Valuve Drive / Pruefent 54 Settings / PreeenS55 Ports disconnected (elements) 55Homeport (zero position) Add) button to print local tax element 57 trip to element from Fern5810.1.10. Compensation JEU5910.1.11. Define element reporting behavior / PRISPEN5910.1.12. Hysteresis determination for intermediate position transfer 60 steam switching 60 direct directions on empty shaft/spindle. Replace fuse F1/F2 6811.3.2.2. Protect the fused F3/F4/ExchangeFor the controller, please refer to the appropriate Drive manual. However, the brake unit must be maintained no later than reaching the number of gravity levers after: 10.2: Maximum 250 gravity triggers its 16.2: Maximum 500 Trigity Trangger Gravity Transport: ¢ Demassemble Motor. The appropriate controller can be found in the installation instructions "Motor replacement". • SA.2 series: Place the motor connection by removing the rings. SA.1 series: Place the motor connection as well as two wooden sealing washers. ¢ Place the centrifugal brake and remove the centrifugal brake from the wood.



Example: Remove the centrifugal brake. Damage to health by inhalation or contact with large amounts of brake dust. “Wear a fine dust mask when working on the brake block. (We recommend at least FFP2 protective masks below 149: 2001+A1: 2009) Wear protective gloves and goggles with side safety goggles. SA.2 .1 = SA series. 1 page 1/2 1/2