
# Intermediate plate
# MUHX2-ZP-D-3-24G

Part number: 34935



## Data sheet

| Feature | Value |
|---|---|
| Nominal width | 14.5 mm |
| Width dimension | 72 mm |
| Type code | MUHX2 |
| Actuation type | Electrical |
| Mounting position | Any |
| Manual override | Non-detenting |
| Reset method | Mechanical spring |
| Type of control | Direct |
| Flow direction | Non-reversible |
| Operating pressure | -0.9 bar ... 10 bar |
| Pilot pressure | 2 bar ... 10 bar |
| Nominal operating voltage DC | 24 V |
| Permissible voltage fluctuations | +/- 10 % |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| CE marking (see declaration of conformity) | As per EU EMC directive |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Storage temperature | -20 °C ... 40 °C |
| Temperature of medium | -5 °C ... 50 °C |
| Degree of protection | IP65 |
| Pilot medium | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Ambient temperature | -5 °C ... 50 °C |
| Certification | c UL us - Recognized (OL) |
| Product weight | 500 g |
| Type of mounting | With through-hole |
| Note on materials | RoHS-compliant |
| Seals material | NBR |



IAS COMPONENTS industrial components supplier. Interested in products or technical support? www.ias-components.com | +442038082761 | info@ias-components.com