Portable Projector

Vivitek-DH2660Z

1080p projector with a brilliant image, multiple I/O ports and long-life light source.



Features

- Up to 4,000 lumens with a strong contrast ratio
- Native 1080p resolution with a maximum 4K UHD resolution
- DLP® DarkChip3™ and BrilliantColor™ technologies or optimal black levels and vibrant colorful images
- Low cost of ownership and maintenance with an environmentally、friendly lamp-less design for up to 30,000 hours of usage
- Distorted and trapezoid image issues are easily corrected with HV keystone, and 4-corner adjustment
- High Dynamic Range (HDR10) delivers enriched brightness and vibrancy for precise natural colors
- Full suite of display connectivity inputs and outputs including: HDMI v2.0, VGA-In
- Manual zoom and focus for easy adjustment and positioning flexibility
- Full suite of display connectivity inputs and outputs
- Built-in 10W audio speaker with multiple audio-in and audio-out ports
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Quick on/off for immediate power on or shut down
- Portable and lightweight at only 4.8kg (10.5lbs)
- Anti-theft security features include: Kensington® security slot, and security bar

Photos









Specifications

Display Type	Single Chip 0.65" DLP Technology by TI	
Brightness	4,000 Lumens*	
Native Resolution	1080p (1920 x 1080)	
Maximum Resolution	4K UHD (3840 x 2160)	
Contrast Ratio	3,000,000:1(Dynamic Contrast Ratio)	
Laser Life/Type	20,000 / 30,000 hours (Normal / Eco) (Laser Phosphor Light Engine)	
Throw Ratio*	1.475-1.753	
Image Size (Diagonal)*	40" - 300"	
Projection Distance*	1.32 – 9.9m (4.33ft to 32.48ft)	
Projection Lens*	F = 2.5 – 2.66, f = 22 – 25.42mm	
Zoom Ratio*	1.2x	
Aspect Ratio	16:9	
Offset	107%±5% (Full Height)	
Keystone Correction	Horizontal ±30°, Vertical ±30°	
Horizontal Frequency	15K~102KHz	
Vertical Scan Rate	23~120KHz	
3D Functionality	Yes (DLP® Link™, HDMI Blu-ray, Top-Bottom / Frame-Sequential / Frame Packing / Side By Side)	
Speaker	10W (Mono)	
Video Compatibility	NA NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Computer Compatibility	VGA (640 x 480) to 4K UHD(3840 x 2160)	
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
I/O Connection Ports	HDMI v2.0 (x2) (HDCP v2.2 Compliant), VGA-In (x1), Audio-In (Mini-Jack)(x1), Audio-Out (Mini-Jack)(x1) ,USB 2.0(5V/1.5A)(x1) , RS232(x1), USB Mini B (Service) (x1)	
Projection Method	Table Top, Ceiling Mount (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar	
Dimensions (WxDxH)	353 x 290 x 144mm (13.9” x 11.4" x 5.67")	
Weight	4.8kg (10.5lbs)	
Available Colors	White	
Noise Level	33dB/31dB (Normal/Eco Mode)	
Power Supply	AC 100-240V, 50/60Hz	
Power Consumption	Normal	230W/220W(Max/Typ)
	Eco	180W
	Eco Standby	Less than 0.5W
Environmental Conditions	Operating	At temperature 0 to 40◦C, relative humidity 10% to 85%,non-condensation
	Storage	At temperature -10 to 60◦C, relative humidity 5% to 95%,non-condensation
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit	
Optional Accessories	VWD-01 **	

* Note: Brightness specifications are compliance with ISO 21118 standards
**Note: VWD-01 is a wireless display dongle module.

© 2023 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.