Wilhelmsen Ships Service

Foam Ext. 9 l W/O B

Product Group: 290 **Product number: 766984**



EDP_766984_Foam 9L Extinguisher

General description

Our 9 L foam extinguisher gives you a specially blended high performance AFFF additive enabling you to fight fires quicker and efficiently.

Unitor's range of fire extinguishers offers you higher fire ratings, easier fire fighting capability and increased levels of user safety.

Features

- Higher fire ratings
- Easier fire fighting capability
- Safer fire fighting
- High quality material and finish

Benefits

- Specially blended high performance AFFF additive enables you to fight fires quickly and efficiently ensuring damage costs are reduced to a minimum.
- Integrated flow control valve at the hose end equips you with a direct and better control to fight fire
- Our higher than normal industry standard burst pressure for the cylinder and hose safeguards you when fire fighting
- A long life and low maintenance costs are assured as our extinguishers are manufactured from 2 mm thick steel, shot blasted, and polyester coated. A non rusting safety pin in included.

Technical Data

Capacity	9 Ltr
Min discharge range	4 Mtr
Test Pressure	26 Bar
Working Pressure	11.2 Bar
Weight Empty	6 Kg
Weight Full	15Kg
Height	640 mm
Diameter	180 mm
Fire Rating	27A-233B
Operating temp range	+5 C to +60 C

Properties

the extinguisher can be used in the presence of an electrical source. There is no danger as the water is thrown in a fine droplet

spray prevents it and its additive from conducting electricity at voltages less than 1000 V.

Spare Charges Regulations

- Spare charges shall be provided for 100% of the first ten extinguishers and 50% of the remaining fire extinguishers capable of being recharged on board. Not more than sixty total spare charges are required. Instructions for recharging shall be carried on board

Ordering information

Product Number	Product name
766984	EXTINGUISHER FOAM 9L
711416	UNIVERSAL BRACKET F/P6/P6P/P9P/
766983	EXTINGUISHER FOAM 9L

Accessories

Product Number	Product name
Recommended to conform to regulations	
668178	CO2 CARTRID.60G F/E9/E9A1
736579	AFFF FOAM CHARGE 90ML FOR E9A1EV
667584	VALVE SEAL FOR EXTINGUISHER
If Required	
669655	STRAP F/MARINE BRACKET

Approvals

The extinguisher holds MED, RMRS, CCS, PED and NF EN 3 -7 approvals. The extinguishers are completely compliant with the MED and SOLAS standards.

Type	Document	Size
766984 PED certificate	PDF	1011 KB
766984 NF EN3-7 certificate	PDF	509 KB
RMRS certificate	PDF	2428 KB
China Class Society Certificate	PDF	2142 KB
MED MODULE B FOR POWDER PORTABLE EXTINGUISHERS	PDF	288 KB
MED MODULE D FOR EXTINGUISHERS PART 1	PDF	274 KB
MED MODULE D FOR EXTINGUISHERS PART2	PDF	274 KB

Directions for use

Easy to Use Operation Once the safety pin has been removed, the device is pressurized by pressing on the striking handle. The flow rate is controlled by the final control valve. The fact that it is so simple to use means that risks of incorrect use are greatly reduced.

Pressurization during use Striking the internal cartridge releases the propellant (CO2), pressurizes the body and thus causes the water and additive to be discharged. The cartridge is interchangeable and its level can be checked accurately by weighing, so the extinguisher can be refilled on site, without having to send it back to the factory. Both preventive and corrective maintenance can therefore be carried out in optimum conditions.

1. Pull out the safety pin
2. Strike by pressing handle
3. Control the flow rate by squeezing the final control valve and direct the spray at base of fire

Documentation

Type	Document	Size
766984 Technical data sheet	PDF	221 KB