

touch pen system for capacitive or resistive touch screen Pen incl. holder for 22.5 mm, screw on or glue for capacitive and resistive touch screens Further information, Quantity and content: see technical data



Figure similar

| General information                  |                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------|
| Product type designation             | Touch pen system capacitive technology                                                |
| Control elements                     |                                                                                       |
| Frame size/design                    |                                                                                       |
| • Standard                           | Yes; For industrial applications                                                      |
| • Ergonomic                          | Yes; With holder                                                                      |
| Installation type/mounting           |                                                                                       |
| Mounting type                        | Wall-mounting bracket can be mounted with mounting disk, 2x M3 screw or adhesive pads |
| Mounting position                    | Horizontal                                                                            |
| Wall mounting/direct mounting        | Yes                                                                                   |
| Degree and class of protection       |                                                                                       |
| IP (at the front)                    | IP65 (depending on mounting)                                                          |
| Ambient conditions                   |                                                                                       |
| Ambient temperature during operation |                                                                                       |

|                                                   |                                                                                                                              |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| • min.                                            | -40 °C; At temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended.                              |
| • max.                                            | 80 °C                                                                                                                        |
| Ambient temperature during storage/transportation |                                                                                                                              |
| • min.                                            | -40 °C                                                                                                                       |
| • max.                                            | 80 °C                                                                                                                        |
| Relative humidity                                 |                                                                                                                              |
| • Operation, max.                                 | 90 %                                                                                                                         |
| Mechanics/material                                |                                                                                                                              |
| Material                                          |                                                                                                                              |
| • Plastic                                         | Yes; Attachment cord                                                                                                         |
| • Aluminum                                        | Yes; Touch pen, wall-mounting bracket                                                                                        |
| Dimensions                                        |                                                                                                                              |
| Height                                            | 150 mm; Length                                                                                                               |
| Thickness                                         | 14 mm; Diameter                                                                                                              |
| Enclosure diameter                                | 37 mm; Diameter wall-mounting bracket                                                                                        |
| Mounting cutout, height                           | 39 mm; Height wall-mounting bracket                                                                                          |
| Weights                                           |                                                                                                                              |
| Weight without packaging                          | 0.13 kg                                                                                                                      |
| Weight incl. packaging                            | 0.14 kg                                                                                                                      |
| Scope of supply                                   |                                                                                                                              |
| Delivery quantity in pieces                       | 1; 1x touch pen with string, wall-mounting bracket, M6 screw, mounting disk, O-ring, adhesive pads, spare caps for touch pen |
| Other                                             |                                                                                                                              |
| Merchandise                                       | Yes; Function depending on touch sensitivity, not suitable for Ceran cooktops, MP377 Daylight, possibly others               |
| Manufacturer name                                 | SIEMENS AG                                                                                                                   |
| Manufacturer's address                            | Gleiwitzerstraße 555, 90475 Nuremberg, Germany                                                                               |
| Target devices                                    | For common capacitive and resistive touch systems                                                                            |
| Note:                                             | Length of the interconnecting lead 53 cm to 100 cm                                                                           |
| Usable in the following products                  |                                                                                                                              |
| • Product 1                                       | <a href="#">6AV2124-0GC13-0AX0</a>                                                                                           |
| • Product 2                                       | <a href="#">6AV2124-0QC13-0AX0</a>                                                                                           |
| last modified:                                    | 05/17/2018                                |