

Osprey Plus S Pedestal (OB)

SKU: V4171-0002

Fully Steerable, 2-Stage pedestal with perfectly balanced stage for 'on shot' movement in field applications. Payload up to 70kg / 155lb.





PRODUCT DESCRIPTION

The Osprey Plus S (OB) is a fully steerable version of the Osprey Plus and is capable of payloads up to 70kg / 155lb. It has 2 stages for achieving very high and low shots, and the upper stage is perfectly balanced for on shot tracking of talent. It has an integral manual pump and an inlet valve for use with an external supply, making Perfect Balance easy to achieve. There is a storage area for the camera operator. In addition, the Osprey Plus pedestal includes a pressure gauge for clear and reliable set-up and the detachable skid allows the pedestal to be simply broken down into two sections for easy storage and transportation. It has a selector for both single wheel and all wheel crab steering for working in tight spaces and on shot direction changes. It comes with 16cm / 6.3 inch wheels for greater ground clearance in outside broadcast applications.

Key features

- Upper stage perfect balance for on-shot performance
- Balance assisted second stage for easy elevation and extended height range
- Full crab and steer facilities controlled from a central steering ring for enhanced manoeuvrability and on-shot steering
- Built in pressure gauge and manual pump for easy counter balance set-up
- Detachable skid for easy transport and storage
- Wheel rim braking mechanism eliminates tyre flat spots for super smooth rolling shots
- Pedestal supplied with Quickfix quick release system & operator storage area
- Column can be adapted to work on dolly track

TECHNICAL SPECIFICATIONS

Range	Osprey
Payload	70 kg | 154.32 lb
Weight	45.8 kg | 100.97 lb
Application	Multicam, Live on Location, Live Studio
Tracking Width	94 cm | 37.01 in
Transit Width	80 cm | 31.5 in
Trim Weights	3500
Color	Black
Wheel Locks	Single-point
Pedestal Base	Open
Stages	2
Perfect Balance Stages	1
On Shot Stroke	41 cm to | 16.14 in to
Height	69.5 cm to 150.5 cm | 27.36 in to 59.25 in
Narrow Transit Width	70 cm | 27.56 in
Wheel Diameter	16 cm | 6.3 in
Steering Ring Diameter	53.5 cm | 21.06 in

IN THE BOX

- Osprey Plus S (OB) Pedestal
- Quickfix
- Accessory holder
- Manual Pump
- Kick ring
- User Guide

YOU MAY ALSO LIKE...



[Nitrogen Charging Adaptor]



[Steering ring, large]



[150 mm Levelling Bowl Adaptor]



[100 mm Levelling Bowl Adaptor]



[OB Wheel Cable Guard For Osprey Elite]



[200 mm Hi-Hat]



[Mitchell Adaptor to 4-Bolt Flat Base]



[Tracking Dolly]



[Vector 750 Pan and Tilt Head]



[Vector 430 Pan and Tilt Head]



[Vision 250F Pan and Tilt Head, Flat Base]



[Vector 75 Pan and Tilt Head]