平衡臂

符合人体工程学，节省空间，死角处也能充分吸除



为了尽量彻底清洁每个角落，平衡抽排臂内置有两个用烟气挡板保持稳定的部分。吸尘器有三个旋转点，一个在底部，一个在中间，一个在喷嘴连接处。因此可将喷嘴移至平衡臂可及范围内的任何位置。平衡臂可配备尼的曼高真空吸尘器计划范围内的所有吸嘴。侧向移动的摩擦是可调的。平衡臂有三种不同的安装方式:安装至墙上、工作台或延伸臂。

安装支架、喷嘴(CWN-S或FWN)、手柄和软管(FS或WH软管)须单独订购。安装支架、喷嘴、手柄和软管须单独订购。

经济、安全
平衡性佳、灵活
易操作
通用性佳

品名	平衡臂





This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

平衡臂

臂长（米）	重量（公斤）	产品编号
1,5	9,7	40180000
2,5	16,5	40180010
3,5	19,2	40180020

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

平衡臂

附件		产品编号
	工作台支架，BA	40180040
	墙面安装支架，BA	40180030
	墙面安装支架，BA 500mm	40180070
	Hose WH−38 L=10m m.spiral	40160292
	Hose WH−51 L=10m m.spiral	40160272
	EA250 延伸臂（2.5m）	40180050
	EA450 延伸臂（4.5m）	40180060
	Nozzle FWN 200/50, connection D=50 mm, airflow 250 m3/h, width 200 mm	40290110*
	Nozzle FWN 400/50, connection D=50 mm, airflow 250 m3/h, width 400 mm	40290120*
	CWN−S 105/50 nozzle silencer, connection D=50 mm, airflow 250 m3/h, suction diameter 105 mm	40290230**
	CWN−S 105/63 nozzle silencer, connection D=63 mm, airflow 400 m3/h suction diameter 105 mm	40290240**
	Nozzle CWN−S 105/50L silencer, connection D=50 mm, airflow 250 m3/h	40290270***
	Nozzle CWN−S 105/40, connection D=40 mm,, airflow 200 m3/h	40290330**
	SOV 50, Manual shut off valve (D=50)	40140030
	SOV 40, Manual shut off valve (D=40)	40142510
	吸嘴延伸	40290200

**Fish tail nozzle. For mounting on balance arms, magnet or suction base. Must be combined with nozzle extension when used with balance arms.*
***Noise reducing nozzle. For mounting on balance arms, magnet or suction base.*
****Noise reducing nozzle with flexible steel tube extension. For mounting on balance arms, magnet or suction base.*

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB