CIRRUS® Second Look®

Scored Tegular
medium texture

TOTAL ACOUSTICS®
Sound Absorption (NRC)
+ Sound Blocking (CAC)

SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Cirrus® Second Look® III panels with Suprafine® XL® 9/16" suspension system



See more photos at:
armstrongceilings.com/photogallery
SEARCH: cirrus

Medium texture panels with a scored plank visual: Offer both Sustain® and Total Acoustics® panel performance.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent sustainability compliance standards today
- Classic Cirrus texture
- Excellent score line painting for a clean visual
- Mold- and mildew-resistant surface
- USDA-Certified Biobased Product – 91%

COLOR

White
(WH)

FACE VIEW



Cirrus® Second Look® I panel –
Scoring creates nominal 12" x 12" squares

Cirrus® Second Look® II panel –
Scoring creates nominal 24" x 24" squares



Cirrus® Second Look® III panel –
Scoring creates nominal 6" x 48" linear planks

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)





1. Cirrus® Second Look® III
2. Cirrus® Second Look® III with Suprafine® 9/16" suspension system

CIRRUS® Second Look®

Scored Tegular
medium texture

USDA CERTIFIED BIOBASED PRODUCT PRODUCT 91%

SUSTAIN® High Performance Sustainable Ceiling Systems

Declare.

GREENGUARD Gold Certified (details below)

LEED® | WELL™ | LBC

UP TO 67% RECYCLED CONTENT

Calculate sustainability with GreenGenie™ armstrongceilings.com/greengenie

energy management · construction waste mgmt · regional materials · design for flexibility · EPD · recyclable/ extended producer resp. · biobased materials · recycled content · sourcing of raw materials · material ingredient reporting · low emitting/ materials · lighting quality · acoustics

▲ LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance. $$$$

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)		UL Classified Acoustics NRC + CAC =	Total Acoustics[1]	Fire Performance	Light Reflect	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
CIRRUS® Second Look® I 15/16" Beveled Tegular	14	**512**	24 x 48 x 3/4"		0.65	35 •	GOOD	Class A	0.85 •	•	Std	•	Std	•	•	10-Yr
CIRRUS® Second Look® II 9/16" Beveled Tegular	28	**510**	24 x 48 x 3/4"		0.65	35 •	GOOD	Class A	0.85 •	•	Std	•	Std	•	•	10-Yr
15/16" Beveled Tegular	14	**513**	24 x 48 x 3/4"		0.65	35 •	GOOD	Class A	0.85 •	•	Std	•	Std	•	•	10-Yr
CIRRUS® Second Look® III 9/16" Beveled Tegular	28	**511**	24 x 48 x 3/4"		0.65	35 •	GOOD	Class A	0.85 •	•	Std	•	Std	•	•	10-Yr
15/16" Beveled Tegular	14	**514**	24 x 48 x 3/4"		0.65	35 •	GOOD	Class A	0.85 •	•	Std	•	Std	•	•	10-Yr

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

15/16" Prelude®

9/16" Suprafine®

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 1, Pattern E I K
Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 1.9 (BTU units)
R Factor – 0.33 (Watts units)

Design Consideration
Do not mix Cirrus® Second Look® with standard Cirrus items in the same room.

Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1.09 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
512M, 510M, 513M, 511M, 514M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

MINERAL FIBER – Standard

TechLine / 1 877 276-7876
armstrongceilings.com/cirrussecondlook

BPCS-3013-1020

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute®; WELL™ and Well Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2020 AWI Licensing LLC

Armstrong® CEILING & WALL SOLUTIONS