Heat-shrink crimp connector, HIGH-END butt connector

Connection sleeve with inspection holes, Crystal Clear™ heat-shrink tubing (except art. no. 05556100) for optimum visual monitoring of the connection.

- Time saved thanks to 40 % faster shrinking process
- Low risk of damage to connector and cable insulation thanks to low shrinking temperature of +300°C



Illustration only

Dielectric strength	30 kV/mm
IP protection class	IP 67
Min./max. temperature conditions	-55 to 125 °C
Min. shrinkage temperature	300 °C

Min./max. wire cross section	Colour	Length	Art. no.	P. Qty.
0.5-1.5 mm^2	Red	38 mm	**0555 610 1**	25
1.5-2.5 mm^2	Blue	38 mm	**0555 610 2**	25/50
4-6 mm^2	Yellow	41 mm	**0555 610 4**	25

Can be stored in ORSY

Details/Application

Dust-proof and damp-proof connections. Good to excellent resistance against petrol, battery acid, diesel, engine oil, anti-freeze, brake fluid, 5% saline solution, isopropyl alcohol.



Proof of performance

RoHS-compliant

Notice

Avoid localised overheating of the heat-shrink tubing.

Related products	Art. no.
WGLG 100 self-igniting gas soldering device	**0984 990 100**

CL01_6501061901, Rev: 0.288, State: 14. 05. 2024