

BEFORE YOU BEGIN

- Please read these instructions carefully to familiarize yourself with the required tools, materials, and installation sequences. Follow the sections that pertain to your particular installation. This will help you avoid costly mistakes. In addition to proper installation, read all operating and safety instructions.
- All information in these instructions is based upon the latest product information available at the time of publication. Kohler China reserves the right to make changes in product characteristics, packaging, or availability at any time without notice.
- These instructions contain important care, cleaning, and warranty information—**please leave instructions for the consumer.**
- VEIL Bathroom Furniture adopts E1 grade wood-based panel of high quality, and with further processing, its harmful emissions will be less than 1.5mg/L.
- Turn off the water supply.
- The plumbing installation must comply with Water Supply Regulations/Bye-laws, Building Regulations or any particular regulations and practices, specified by the local water company or water undertakers. The installation should be carried out by a plumber.
- Before installation carefully inspect the new fixture for any signs of damage.
- This product complies with GB24977-2010、GB/T 17743-2007、GB7000.1-2015 and GB7000.201-2008.

安装之前

- 请仔细阅读本指引，以便熟悉所需工具、材料及安装程序。请遵照适用的章节来安装本产品，以免安装失当导致不必要的损失。除了有关正确的安装方法之外，还务请详阅所有操作及安全指引。
- 本指引所载之一切资料，均以印刷时所有之最新产品情况为基础，科勒中国保留权利随时更改产品特性、包装或供应情况，恕不另行通知。安装家具之前，请先确认所有必需的电气工作均已完成。
- 说明书包括重要的安装、清洁及保养方面的内容，**请把这些资料交给用户阅读，保管。**
- 维亚浴室家具选用 E1 级优质饰面人造板精心加工而成，其有害气体释放量少于 1.5mg/L。
- 关闭供水。
- 管道安装必需遵循当地所有给排水、建筑或者其他的特别规定。管道安装人员必需具备相应资格。
- 安装之前，仔细检查新产品是否有损伤。
- 本产品符合 GB24977-2010、GB/T 17743-2007、GB7000.1-2015 和 GB7000.201-2008。

ORDERING INFORMATION

This installation covers the following products in the VEIL range:

VEIL Bathroom Furniture..... K-21800T-X

订购信息

此安装说明书适用于以下维亚系列家具的安装：

维亚浴室家具..... K-21800T-X

SAFETY WARNINGS

Kohler products are precision-engineered and should give continued superior and safe performance, provided:

1. They are installed, commissioned, operated and maintained in accordance with the recommendations given in this Manual.
2. Periodic attention is given, as necessary, to maintain the product in good functional order. Recommended guidelines are given in the **MAINTENANCE** section.

Carefully inspect the new fixture for any signs of damage.

When installing Kohler Products, manufacturers guidelines for power tool safety should be followed.

安全警告

科勒产品经过精确制造，性能卓越，经久耐用。为保证产品品质，您必须：

1. 按照此手册中推荐的方法进行安装、起动、操作及维护。
2. 如有需要，定期检查，令产品保持良好性能状态。日常维护章节中列有推荐方法。

仔细检查新产品是否有损伤。


在安装科勒产品时，必须遵循制造商相关电动工具的安全的指令。

ROUGHING-IN

尺寸图

Reference Value
参考值

UNIT: mm
单位: 毫米



Kohler reserves the right to change marked dimensions without prior notice.
科勒公司保留随时变更图中标示尺寸的权利, 无需另行通知。

INSTALLATION

安装

A. Before Installation

Before cabinet installation, please reserve 0.5m, 220V power line on the wall for background light connection (see Fig. 1).

A. 安装之前

请在安装浴室柜的墙面上预留 0.5m 长的 220V 电源线, 用于连接浴室柜上的背景灯 (见图 1)。




Fig. 1 图 1

B. Install Washbasin Cabinet

Install the services.
Hot (H) and Cold (C) inlets must be connected to the correct inlet pipes.
Install the drain in accordance with the manufacturer's instructions.
We suggest using P-trap drain. Connect P-trap pipe with washbasin drain.

CAUTION! Make sure a watertight seal exists on all washbasin drain connections.

CAUTION! Provide access to the plumbing connections for future plumbing maintenance.

NOTE: The hot and cold water supplies must be installed with isolating valves.

B. 安装脸盆柜

安装管道。
热水 (H) 及冷水 (C) 入口必须连接至正确的进水管。
根据制造商说明书安装排水。
我们建议采用墙排水方式，使用 P 弯管连接脸盆去水。

小心! 请确保所有脸盆排水的连接处都装有防水密封胶。

小心! 管道连接处需留有检修空间，以备日后管道维护之用。

注意: 安装冷热供水管时必须使用隔离阀。




Fig. 2 图 2

1. Mark the position of hanged bracket and wall bolt according to dimensions as illustrated, and loosen the suspension hook of washbasin cabinet.

CAUTION! Avoid the cables and pipes inner set when drilling in the wall.

NOTE: Different types of bolts are required for different decoration boards.
Please apply suitable bolts and plugs.

1. 根据图示尺寸在墙壁上标示出挂墙托片和配套台盆悬挂螺栓的位置，并将脸盆柜吊码的挂钩伸长。

小心! 在墙壁上钻孔时请务必小心避开内设的缆线和管道。

注意: 不同的装饰墙面需要不同型号的螺钉。请使用合适的螺钉和入墙胶塞。

UNIT: mm
单位: 毫米




Fig. 3 图 3

2. Install stand.

- a. Fix the four feet to the stand with the attached screws and a socket head wrench as shown in the figure below.

2. 安装脚架。

- a. 如下图将四只支脚用配套的螺杆和内六角扳手固定在脚架上。




Fig. 4 图 4

- b. Lay the VEIL cabinet on its back. Fix the stand onto the bottom plate with tapping screws as shown in the figure below.

- b. 将维亚浴柜放倒背部着地，将脚架按下图所示用自攻螺丝固定在底板上。




Fig. 5 图 5

3. Install counter top and washbasin.

- a. Install the counter top: As shown in the figure below, apply silica gel onto the area on the cabinet panel indicated by the dotted lines to fix the counter top (the back of the counter top shall be aligned with that of the cabinet, while the left and the right sides of the counter top shall be both 1.5 mm away from the cabinet). Find the connectors A1 and B1 on the stone counter top and the connector B2 on the cabinet according to the figure below.

3. 安装台面、台盆。

- a. 安装台面：如下图所示，在浴柜面板处虚线位置打硅胶，用于固定住台面（注意台面的后部与浴柜的后部齐平，台面左右两边各凸出浴柜约 1.5mm）。并按下图所示找到对应的电路接口，其中石材台面上有 A1 和 B1 接口，浴柜上有 B2 接口。




Fig. 6 图 6

- b. Connect the connector on the counter top with that on the cabinet. After the counter top is fixed and the silica gel is completely dried, find the connector A1 on the counter top and the connector B2 on the cabinet and connect them together by inserting one into the other. (Make sure the connectors are securely connected. Attempt to pull them apart. If they cannot be separated, the connection is secure.)

b. 台面和浴柜线路接口连接。固定好台面后，待胶干透后，找到台面上的 A1 和浴柜上的 B2 接口将他们插入连接起来。（确保插头连接到位，可以试着反方向用力拔开两个接口，无法拔出则连接到位）
- c. Install the washbasin and the counter top: Take out the attached washbasin. Place it into the hole in the counter top in the direction shown in the figure below (find the washbasin connector A3 shown in the figure below prior to placing the washbasin). Slightly turn the washbasin until it cannot be turned anymore with uniform gap from the counter top.
- c. 台盆与台面安装：将配套的台盆取出，按下图所示方向放入浴柜台面上的台盆孔中（安放台盆前找到图示中所示的台盆接口 A3），放入台盆后轻轻转动台盆确保台盆稳定不会转动，且与台面的缝隙均匀。




Fig. 7 图 7

- d. Connect the connector on the washbasin and that on the counter top. After fixing the washbasin, find the connector A3 on the washbasin and the connector B1 on the counter top. Connect them together by inserting one into the other. (Make sure the connectors are securely connected. Attempt to pull them apart. If they cannot be separated, the connection is secure.)
- d. 台盆和台面线路接口连接。固定好台盆后，找到台盆上的 A3 接口和台面上的 B1 接口，将他们插入连接起来。（确保插头连接到位，可以试着反方向用力拔开两个接口，无法拔出则连接到位）

e. Fix the washbasin: After verifying the washbasin is properly placed, apply silica gel into the gap between the washbasin and the counter top (see the figure below). Check that the connector on the washbasin is securely connected with that on the counter top.

e. 固定台盆：确认台盆放置好后，沿台盆与台面一圈接缝处打透明硅胶（见下图）；并确认台盆与台面的电线接口是否连接好。




Fig. 8 图 8

4. Install the faucet and the washbasin drain respectively onto the cabinet and the washbasin by following the attached installation instructions. Connect the faucet pull bar with the drain.
5. Fix onto the wall.
- a. Have the cabinet and washbasin slightly lifted with two person. Hook the two hooks on the back of the cabinet onto the pre-installed wall bracket.
- b. Turn the two wooden stoppers at the bottom of the cabinet by 90°, so that the backboard falls down to the floor. See the figure below.

4. 按照配套龙头和落水的安装说明将龙头和落水安装在浴柜和台盆上，并将龙头提拉杆与落水连接起来。
5. 与墙面固定。
- a. 由两人稍稍抬起浴柜和台盆，将柜体后部的 2 个挂钩挂在墙面预先安装好的托墙挂片上。
- b. 将浴柜底部的 2 个木质的挡块旋转 90 度，使后背板落在地板上。见下图。




Fig. 9 图 9

- c. Adjust the the cabinet to be level and properly away from the wall by adjusting the wall clips. See the figure below.

- c. 通过调节吊码调节浴室柜的水平及与墙面的距离。见下图。




Fig. 10 图 10

- d. After the adjustment is correctly completed, fix the cabinet onto the wall with the attached screws in the hardware package. (The holes and the embedded parts have been prepared in the first step. See Figure 3.)

- d. 确认调整无误后，用五金包中的配套的螺丝将浴柜与墙面再次连接起来。（墙面上的孔和预埋件在第一步中已完成，见图 3）




Fig. 11 图 11

C. Install The Water And Electricity System

- 1. Have the water system connected and installed by a professional plumber to avoid any leakage.
- 2. Have the power bus at the back of the cabinet connected with the reserved line on the wall by a professional technician (see figure 9) to avoid electric leakage.
- 3. After the procedures stated in 1 and 2 above are completed, lift the backboard to the location shown in Figure 9. Turn the stopper by 90° to fix the backboard.
- 4. Open the cabinet door. Place the laminate glass onto the support.

D. Adjust

- 1. Adjust the cabinet door (see the figure below).




Fig. 12 图 12

- 2. Adjust the adjustable feet. Check whether the bottom of each of the four metal feet closely contacts the floor. If not, turn the adjustable feet counterclockwise so that the bottom closely contacts the floor.

E. Introduction Of The Lights

- 1. Configure the lights. (See the figure below.)




Fig. 13 图 13

- 2. Function Of The Lights
The background lightings are centrally controlled by the suite controller.
Status of the task lighting: When the door is closed, the light gradually turns off; when the door is opened, the light gradually turns on.
Transparency control of the glass door: Wave your hand in front of the sensor (see the figure above), the glass becomes transparent; wave your hand again in front of the sensor, the glass becomes murky.
- 3. For detailed control of the background lightings, see the light introductions of the VEIL Suite.

C. 水电安装

- 1. 由专业人员连接并安装上下水，确保无渗漏。
- 2. 由专业电工将浴柜后部的电源总线与墙面预留的电线（图 9）连接起来，确保安全无漏电。
- 3. 安装好后，参考上述图 9 中，将后背板升起，并转动背板挡块 90 度，固定住后背板。
- 4. 最后打开柜门，将层板玻璃放入层板拖上。

D. 调节

- 1. 柜门调节（见下图）

- 2. 调节脚调节。检查四个金属脚底部是否与地面紧密接触，如未接触请逆时针旋转调节脚，使其与地面紧密接触。

E. 灯光功能介绍

- 1. 灯光配置。（见下图）

- 2. 灯光功能
氛围灯由套件控制器统一控制。
工作灯光状态：门关闭 灯渐灭；门打开，灯渐亮。
玻璃门板透明控制：扫一下控制器部位（见上图）玻璃透明，再扫一下玻璃变磨砂状态。
- 3. 氛围灯详细的控制说明请参加维亚套件的灯光说明。

USER MAINTENANCE



Warning! Risk of product damage.

1. Many cleansers contain abrasive and chemical substance which is not suitable for cleaning stainless steel, enamel, plating or plastic products. You may use mild cleansers or soaps to clean the surfaces. Wipe any splashes of cleaner solutions from the surface with clean soft cloth.
2. Maintain ventilation in the bathroom, and separate the dry area from the damp one if conditions permit. Try to open the door and windows of the bathroom and maintain good ventilation.
3. Kohler bathroom cabinet are dealt with strict procedures for damp-proof, whose good damp-proof function ensures good performance even in bathroom of huge humidity. Yet do not splash and pour water directly on the bathroom cabinet. Make sure that the bathroom is not over damp and wipe any splashes from surfaces immediately.
4. Maintenance of door board: Clean and wipe door board regularly, and wipe the condensation vapor with dry and soft cloth.
5. Ensure that electrical connections for appliances such as head lamp is insulated wipe mirror surface with chamois regularly to guarantee the persistent excellent performance.
6. Please do not sit, lean or step on the basin cabinet.
7. If any fixtures caused by abnormal reasons, Kohler China can supply paid replacement for service parts caused by abnormal reasons as shown in the Service Parts Page in the limited duration of warranty.
8. In case that any light or the glass door cannot operate normally, do not disassemble it by yourself. Instead, promptly contact the after-sales department of Kohler. We will help you solve the problem as soon as possible.

日常维护



警告! 小心产品受损。

1. 许多清洁剂都含有研磨剂及化学物质，不可用于清洁不锈钢、搪瓷、镀层或塑料制品。这些表面须使用温和的清洁剂或皂液进行清洁，将残余洗涤剂洗干净，然后用干净的软布擦干。
2. 卫生间请保持良好的通风状态，有条件的可以干、湿分离，平常尽量保持浴室空气畅通，养成开窗开门的习惯。
3. 科勒浴柜都经过严格的防潮处理，但防潮并不是防水，使用时不可随意任浴柜被水浇、溅。良好的防潮性能可以保证在高相对湿度时仍有良好使用性，所以请避免卫生间过于潮湿，遇有水迹要及时擦干。
4. 门板的保养：经常用软布定期清洁、擦拭，洗浴后的冷凝水蒸气应用干布擦净，保持门板的干爽。
5. 照明灯等电器连接要确保绝缘、防潮镜面最好用麂皮经常擦拭，可以保障使用质量经久如一。
6. 日常使用时，请勿坐、倚、靠、踩踏在脸盆柜上。
7. 科勒公司确保在担保期内，可以提供因非正常原因造成的如维修零件图中零件的有偿更换。
8. 如出现灯光和透明玻璃门板无法正常工作时，请勿擅自拆卸，及时联系科勒售后服务，我们将尽快为您解决。