Shenzhen Newsmy Technology Co., Ltd

Hunan Head Quaters: Newman Park, No.2 Lixiaang Road East,Changsha, China
Shenzhen Factory: Building 2, 1st Floor,Longbi Industrial Park, Bantian, Shenzhen
Email: sindy@newsmy-car.com Skype: sindyliu111 Wechat:mshk6937






Model	N150	N150P	N200	N300(Pure Sine Wave)
Dimensions	168*132*130MM	168*202*130MM	168*202*130MM	168*262*130MM
Material	Aluminum alloy + fireproof ABS	Aluminum alloy + fireproof ABS	Aluminum alloy + fireproof ABS	Aluminum alloy + fireproof ABS
Battery	Rated voltage: 12.8V	Rated voltage: 12.8V	Rated voltage: 12.8V	Rated voltage: 12.8V
	Battery power: 12Ah, 153.6Wh	Battery power: 18Ah, 230.4Wh	Battery power: 18Ah, 230.4Wh	Battery power: 307.2Wh, 24Ah
	Battery type: LiFePO4	Battery type: LiFePO4	Battery type: LiFePO4	Battery type: LiFePO4
Charging input	DC in: DC3.5*1.25 16V 2A 32W	DC in: DC3.5*1.25 16V 2A 48W	DC in: DC3.5*1.25 16V 3A 48W	DC in: DC3.5*1.25 16V 2A 48W
	Solar panel charging: DC15-20V 32W(supported, optional)	Solar panel charging: DC15-20V 48W(supported, optional)	Solar panel charging: DC15-20V 48W(supported, optional)	Solar panel charging: DC15-30V 48W(supported, optional)
	Car charger: 16V 2A 32W(Optional)	Car charger: 16V 2A 32W(Optional)	Car charger: 16V 2A 32W(Optional)	Car charger: 16V 4A 48W(Optional)
	Charging time: AC about 6 hours Car charger about 10 hours(Optional)	Charging time: AC about 6 hours Car charger about 10 hours(Optional)	Charging time: AC about 6 hours Car charger about 10 hours(Optional)	Charging time: AC about 6 hours Car charger about 10 hours(Optional)
USB output	USB1：QC3.0 / BC1.2 /5V2.4A 9V2A 12V 1.5A	USB1：QC3.0 / BC1.2 /5V2.4A 9V2A 12V 1.5A	USB1：QC3.0 / BC1.2 /5V2.4A 9V2A 12V 1.5A	USB1：QC3.0 / BC1.2 /5V2.4A 9V2A 12V 1.5A
	USB2：BC1.2 / 5V 2.4A(Max)	USB2：BC1.2 / 5V 2.4A	USB2：BC1.2 / 5V 2.4A	USB2：BC1.2 / 5V 2.4A
	USB3：BC1.2 / 5V 2.4A(Max)	Type-C：PD60W 5V3A 9V3A 12V3A 15V3A 20V3A	Type-C：PD60W 5V3A 9V3A 12V3A 15V3A 20V3A	Type-C：PD65W 5V3A 9V3A 12V3A 15V3A 20V3.25A
DC output	DC5.5*2.1 12V 10A (MAX) DC+AC out at same time: DC 6A max DC out power: 150W	DC5.5*2.1 12V 10A (MAX) DC+AC out at same time: DC 6A max DC out power: 210W	DC5.5*2.1 12V 10A (MAX) DC+AC out at same time: DC 6A max DC out power: 210W	DC5.5*2.1 12V 10A (MAX) DC+AC out at same time: DC 6A max DC out power: 210W
AC output	Voltage:110V+-10V AC / 220V+-10V AC corrected sine wave	Voltage:110V+-10V AC / 220V+-10V AC corrected sine wave	Voltage:110V+-10V AC / 220V+-10V AC corrected sine wave	Voltage:110V+-10V AC / 220V+-10V AC Pure sine wave
	Frequency: 60HZ+- 3hz / 50HZ +- 3hz	Frequency: 60HZ+- 3hz / 50HZ +- 3hz	Frequency: 60HZ+- 3hz / 50HZ +- 3hz	Frequency: 60HZ+- 3hz / 50HZ +- 3hz
	Rated power: 150W	Rated power: 150W	Rated power: 200W	Rated power: 300W
	Peak power: 300W	Peak power: 300W	Peak power: 400W	Peak power: 600W
	AC port type: Japan/America/Europe/ UK	AC port type: Japan/America/Europe/ UK	AC port type: Japan/America/Europe/ UK	AC port type: Japan/America/Europe/ UK
Display Screen	white nixie tube display	white nixie tube display	white nixie tube display	white nixie tube display
	Display content: 5 level battery, charging output state,temperature	Display content: 5stages battery, temperature, charging output state	Display content: 5stages battery, temperature, charging output state	Display content: 5stages battery, temperature, charging output state
LED light	6W LED light	6W LED light	6W LED light	6W LED light
	Red-yellow warning light	Red-yellow warning light	Red-yellow warning light	Red-blue warning light
Button	Power on/off	Power on/off	Power on/off	Power on/off
	AC on/off	AC on/off	AC on/off	AC on/off
	Lighting：turn on/off the light, adjust brightness, light mode	Lighting：turn on/off the light, adjust brightness, light mode	Lighting：turn on/off the light, adjust brightness, light mode	Lighting：turn on/off the light, adjust brightness, light mode
Sales area	Online & Offline	Only Offline	Only Offline	Online & Offline
Accessories supply	Box, user manual, AC charging in adaptor	Box, user manual, AC charging in adaptor	Box, user manual, AC charging in adaptor	Box, user manual, AC charging in adaptor
Optional Accessories	Car charger/Solar panel/DC transfering car light port	Car charger/Solar panel/DC transfering car light port	Car charger/Solar panel/DC transfering car light port	Car charger/Solar panel/DC transfering car light port
Package	4 pcs/ctn, 12.6kg	2 pcs/ carton, 9.2kg	/	/
Price	**74USD**	**94USD**	**121USD**	**134USD(Estimated price)**
Remark	1. All Prices are FOB Shenzhen prices based on MOQ = 500pcs. Please reconfirm price before placing order. 2. All models are CE, FCC, Rohs, PSE circle, METI,UN38.3,MSDS certificated, and with UL report. 3. OEM is supported.			