CAMERA

TRISTAR HD - HIGH DEFENITION CAMERA 3-CCD

- Full HD resolution
- High speed shutter
- Multilingual menu
- Remote camera head



CAMERA

TRISTAR HD - HIGH DEFENITION CAMERA 3-CCD

Technical Data

Camera head:	· Aspect ratio: 16:9 · Image sensor: 3x 1/3'' CCD · Immersible (using the attached cap)
System	· Power supply: 100/240 VAC, 50-60 Hz · Fuses: 2 Fine fuses, 5x20 mm, delay acting 3,15 AH (I=1500A) · Power consumption: 20 AV · Image resolution: full HD 1920 x 1080 · TV resolution: > 1000 lines · Sensitivity: < 3 lux (1/1.4) · White balance automatically, with data hold shutter speed: 1/50 (1/60) to 1/100.000 sec
Video out terminal	· 2x HD SDI · 1x HDMI / DVI · 1x Y-Pb-Pr (Component) · 1x Video (PAL / NTSC) · 1x S-Video (PAL / NTSC)
Standard	· Protection class: I · Application part: Type BF · classification acc. 93/42/EEC: I · EN ISO 13485 | 93/42/EEC | IEC 601-1, EN 60601-1C
Features	· White balance, boost function · On-screen-menu · 3 user settings storable · 2.5 digital zoom · Freeze function · Character generator
Dimensions	· Control unit: 355 x 103 x 253 mm (WxHxD); 4,5 kg
Delivery contains	· CCU, camera head with 4m cable, mains cable, Y/C cable, BNC cable, HDMI - DVI cabel, HDMI cable, User manual · Optional: waterproof keyboard, footswitch

Options

Optional accessories	· Waterproof keyboard · Footswitch

TRIstar HD 3-CCD camera head



Weight: 160 g
Size: 82 x 53 x 39 mm

With push buttons

03/16 Specifications subject to change without notice. Reproduction in whole or in part prohibited. All rights reserved. © 2016 ILO electronic GmbH, Carl-Zeiss-Strasse 3, 25451 Quickborn