GL0200C1UL

THREE-POLE SWITCH DISCONNECTOR, UL98, 200A




Product designation				Switch disconnector
Product type designation				GL UL
Number of poles			Nr.	3
Operating voltage type				AC
Contact characteristics				
IEC Conventional free air thermal current Ith			A	200
Rated insulation voltage Ui IEC/EN			V	1000
Rated impulse withstand voltage Uimp			kV	12
Operating current Ie				
	AC21A			
		400V	A	200
		500V	A	200
		690V	A	200
	AC22A			
		400V	A	200
		500V	A	200
		690V	A	200
	AC23A			
		400V	A	200
		500V	A	200
		690V	A	200
Power dissipation per pole max			W	4
Rated operational power AC23A				
		400V	kW	110
		690V	kW	200
Reactive power for control of capacitors at				
		400V	kvar	100
Rated short time current (1s) Icw (rms)			kA	6
Rated short time current (0.3s) Icw (rms)			kA	12
Conditional short-circuit current (rms)			kA	100
Short-circuit protection with fuse			Class/A	J/200
Making capacity AC23A 400V			A	2000
Breaking capacity AC23A 400V			A	1600
Mechanical life			cycles	20000
Mechanical features				
Operating position				
		normal		Vertical plan
		allowable		Any
Fixing				Screw / DIN rail 35mm
Terminals				
		type		M8 x 25
Tightening torque for terminals				
		min	Nm	15


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	max	Nm	22
	min	lbin	132
	max	lbin	194
Conductor section			
	IEC min	mm²	70
	IEC max	mm²	185
	AWG/kcmil min		00
	AWG/kcmil max	kcmil	400
UL technical data			
UL Standard			UL98
General purpose current rating		A	200
Operating voltage max		V	600
Horsepower/FLA current three phase motor			
	240V	HP/A	75/192
	480V	HP/A	150/180
	600V	HP/A	200/192
Short circuit rating		kA rms	200
Short circuit rating with fuse		Class/A	J/200
UL Terminal kit lugs			GLX500 - GLX501
Minimum enclosure dimensions at rated current			
	mm	mm	400 x 250 x 150
	in	in	15,8 x 9,9 x 5,9
Ambient conditions			
Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Max altitude		m	3000
Dimensions			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Wiring diagrams



Certifications and compliance

Compliance

	IEC/EN 60947-1
	IEC/EN 60947-3

Certifications

	cULus

ETIM classification

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

ETIM 8.0

EC000216 - Switch disconnector

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding