

Clairex CLD156 Photodiode Datasheet

<http://www.manuallib.com/clairex/cld156-photodiode-datasheet.html>

The CLD156 and CLD156R are 0.122" x 0.222" active area silicon photodiodes featuring high linearity and low dark current. The TO-5 header provides thermal environment for reliable operation over a wide temperature range. Wide acceptance angle permits use in IR air communications, ambient light detection, safety and monitoring, security systems, etc. For additional information, call Clairex.

ManualLib.com collects and classifies the global product instruction manuals to help users access anytime and anywhere, helping users make better use of products.

<http://www.manuallib.com>



CLD156

Large Active Area Silicon Planar photodiode

This product is tested to satisfy the conditions of both the CLD156 and the CLD156R.



May, 2001



features

- 100° acceptance angle
- 860nm peak response
- TO-5 hermetic package
- usable for visible through near-IR
- RoHS compliant

absolute maximum ratings ($T_A = 25^\circ\text{C}$ unless otherwise stated)

storage temperature.....	-65°C to +150°C
operating temperature.....	-65°C to +150°C
lead soldering temperature ⁽¹⁾	260°
reverse voltage	30V
continuous power dissipation ⁽²⁾	200mW

description

The CLD156 and CLD156R are 0.122" x 0.222" active area silicon photodiodes featuring high linearity and low dark current. The TO-5 header provides thermal environment for reliable operation over a wide temperature range. Wide acceptance angle permits use in IR air communications, ambient light detection, safety and monitoring, security systems, etc. For additional information, call Clairex.

notes:

1. 0.06" (1.5mm) from the header for 5 seconds maximum.
2. Derate linearly 1.28mW/°C free air temperature to $T_A = +150^\circ\text{C}$.

electrical characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
symbol	parameter	min	typ	max	units	test conditions
I_{SC}	Short-circuit current ⁽³⁾	-	100	-	μA	$V_{BIAS} = 0\text{V}$, $E_e = 5\text{mW}/\text{cm}^2$
I_D	Dark current	-	-	50	nA	$V_F = 100\text{mV}$, $E_e = 0$
		-	-	50	nA	$V_R = 15\text{V}$, $E_e = 0$
V_O	Open circuit voltage ⁽³⁾	-	0.35	-	V	$E_e = 5\text{mW}/\text{cm}^2$
V_{BR}	Reverse breakdown	25	-	-	V	$I_R = 100\mu\text{A}$
C_J	Junction capacitance	-	-	400	pF	$V_{BIAS} = 0\text{V}$, $f = 1\text{MHz}$
t_r, t_f	Output rise and fall time ⁽⁴⁾	-	-	10	μs	$R_L = 1\text{k}\Omega$
Θ_{HP}	Total angle at half sensitivity points	-	100	-	deg.	

notes: 3. Radiation source is a frosted tungsten lamp at a color temperature of 2854K or equivalent.

4. Radiation source is an AlGaAs IRED operating at a peak emission wavelength of 880nm and $E_e = 20\text{mW}/\text{cm}^2$.

Clairex reserves the right to make changes at any time to improve design and to provide the best possible product.

Revised 3/15/06

Clairex Technologies, Inc.
Phone: 972-265-4900

1301 East Plano Parkway
Fax: 972-265-4949

Plano, Texas 75074-8524
www.clairex.com