

CTC B320-B3200 RECTIFIER Datasheet

<http://www.manuallib.com/ctc/b320-b3200-rectifier-datasheet.html>

FEATURES

Metal-Semiconductor junction with guard ring

Low forward voltage drop

High current capability

The plastic material carries UL recognition 94V-0

For use in low voltage,high frequency inverters,free wheeling,and polarity protection applications

ManualLib.com collects and classifies the global product instruction manuals to help users access anytime and anywhere, helping users make better use of products.

<http://www.manuallib.com>

SCHOTTKY BARRIER RECTIFIERS

REVERSE VOLTAGE - **20** to **200** Volts
FORWARD CURRENT - **3.0** Amperes


FEATURES

- Metal-Semiconductor junction with guard ring
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low voltage,high frequency inverters,free wheeling,and polarity protection applications

MECHANICAL DATA

- Case : JEDEC SMA molded plastic
- Polarity : Color band denotes cathode
- Weight : 0.231 grams
- Mounting position : Any

SMC



SMC		
DIM.	MIN.	MAX.
A	6.60	7.11
B	5.59	6.22
C	2.75	3.15
D	0.15	0.31
E	7.75	8.13
F	0.05	0.20
G	2.00	2.62
H	0.76	1.52
All Dimensions in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

PARAMETER	SYMBOL	B320	B330	B340	B350	B360	B380	B3100	B3150	B3200	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	150	200	V
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	105	140	V
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	150	200	V
Maximum average forward redified current	I _F	3.0									A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	80.0									A
Maximum Instantaneous Forward Voltage @ 3.0A	V _F	0.50			0.70		0.85		0.87	0.90	V
Maximum DC Reverse Current @ TA=25 °C at Rated DC Blocking Voltage @ TA=100 °C	I _R	0.5					0.2				mA
		10.0					5.0				
Typical Junction Capacitance	C _J	180			150		110		100		pF
Typical Thermal Resistance	R _{BJA}	70									°C/W
Operating Temperature Range	T _J	-55 to +125									°C
Storage Temperature Range	T _{STG}	-55 to +150									°C

FIG. 1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2-TYPICAL FORWARD CHARACTERISTICS




FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE

