

MP770 DLP Projector

Features

Texas Instruments DLP™
Projection System
Native XGA (1024 x 768)
resolution
3200 ANSI Lumens
2000:1 contrast ratio
31" to 300" image size
5 segment colour wheel
Brilliant Colour™ Technology
3kg net weight
Less than 31dB audible noise
9 preset modes
Remote control

The BenQ MP770 is a portable digital projector with the power of fixed-installation projectors, and is the ideal unit for open environments such as classrooms and conference rooms.

This portable projector features a brightness of 3200 ANSI lumens, a 2000:1 contrast ratio, XGA native resolution of 1024 x 768 and versatile connectivity via an optional wireless feature.

Weighing only 3kg, the MP770 comes equipped with BenQ's proprietary Colour Wheel technology and Texas Instruments' Brilliant Colour™ technology to ensure great colour performance.



Specifications[#]

Projection System

Digital Micromirror Device (DMD)

Native Resolution

Resolutions Supported

Brightness

Contrast Ratio

Colour Reproduction

Image Size

Throw Ratio

Aspect Ratio

Zoom Ratio

Lens

Horizontal Frequency

Vertical Scan Rate

Projection Position

Lamp

Lamp Life

Audible Noise

Input Terminals

Output Terminals

Control Terminals

Audio Terminals

Video Compatible

Dimensions (mm) (W x H x D)

Weight (kg)

Power Supply

Power Consumption

Features

Standard Accessories

Optional Accessories

DLP™ Technology by Texas Instruments®

XGA DDR DMD™ x 1

XGA (1024 x 768)

640 x 350 to 1280 x 1024

3200 ANSI Lumens

2000:1

Full 16.7 million colour palette

31" to 300"

60" @ 2m (60" @ 6.6 feet)

4:3 native / 16:9 selectable

01:01.2

Manual Zoom, F=2.6 to 2.77, f=20.4-23.5 mm

31 ~ 82 kHz

45 ~ 85 Hz

Front / Rear / Table / Ceiling

220W NSH

Up to 3000/4000 hours (Normal / Economic Mode)

<31dB/28dB (Normal/Economic Mode)

DVI-I (shared with wireless module) / Analog-D-sub 15

pin x 1 (shared with Component Video) / S-Video: Mini

DIN 4 pin x 1 / Composite Video x 1

Speaker 2W, Analog-D-sub 15 pin x 1

USB

PC Audio Jack

NTSC / PAL / SECAM / NTSC 4.43

230 x 94 x 298mm

3.0

100 to 240 VAC, 50 to 60 Hz

320W (Max.)

2D Keystone / Auto Off / Freeze / Blank / 8 Application

Modes / Security Password / Digital Zoom / PIP / Off & Go

User's Manual / Remote Control / Battery / Manual CD /

PC Audio Cable / Warranty Information Booklet / Power

Cable / VGA Cable / Soft Carry Case / USB Cable

Wireless Module (QLink Pro) / Ceiling Mounting Kit /

Mac Adapter / Component Video Cable- Dsub /

Presentation Plus

