

XC6203

Series

(Large Current) Positive Voltage Regulators



- ◆ CMOS Low Power Consumption (16 μ A max)
- ◆ Dropout Voltage : 150mV @ 100mA,
300mV @ 200mA
- ◆ Maximum Output Current
: more than 400mA (3.3V)
- ◆ Highly Accurate : \pm 2%
- ◆ SOT-89 / SOT-223 / TO-92 Package

■ General Description

The XC6203E series are highly precise, low power consumption, positive voltage regulators manufactured using CMOS and laser trimming technologies.

The series provides large currents with a significantly small dropout voltage.

The XC6203E consists of a driver transistor, a precision reference voltage and an error amplifier. Output voltage is selectable in 0.1V steps between a voltage of 1.8V and 6.0V.

SOT-89 (500mW), SOT-223 (1200mW) and TO-92 (300mW) package.

■ Applications


- Battery Powered Equipment
- Reference Voltage Sources
- Cameras, Video Cameras
- CD-ROMs, DVDs
- Palmtops
- Portable Audio Video Equipment

3


■ Features

Maximum Output Current	: 400mA
Maximum Operating Voltage	: 8V
Output Voltage Range	: 1.8V ~ 6.0V (selectable in 0.1V steps)
Highly Accurate	: \pm 2%
Low Power Consumption	: TYP 8.0 μ A
Output Voltage Temperature Characteristics	: TYP \pm 100ppm/ $^{\circ}$ C
Operational Temperature Range	: -40 $^{\circ}$ C ~ 85 $^{\circ}$ C
Ultra Small Packages	: SOT-89, SOT223, TO-92


■ Typical Application Circuit



■ Typical Performance Characteristic



■ Pin Configuration



3

■ Pin Assignment

PIN NUMBER		PIN NAME	FUNCTION
SOT-89/SOT223/TO-92 (T)	TO-92 (L)		
1	2	Vss	Ground
2	1	Vin	Power Input
3	3	Vout	Output

■ Product Classification

● Ordering Information

XC6203 ①②③④⑤⑥


DESIGNATOR	SYMBOL	DESCRIPTION	DESIGNATOR	SYMBOL	DESCRIPTION	
①	Type of Regulator		⑤	Package Type		
	P	Current limiter circuit built-in		P	SOT-89	
	E	No current limiter circuit built-in		F	SOT-223	
②③④	18~ 60 & A	e.g. 252 : 2.5V, Accuracy $\pm 2\%$ 28A : 2.85V, Accuracy $\pm 2\%^*$ "A" indicates voltage of 50mV steps	⑥	TO-92 (Standard)		
				T	TO-92 (Standard)	
				L	TO-92 (Custom pin configuration)	
				Device Orientation		
				R	Embossed Tape (Standard Feed)	
				L	Embossed Tape (Reverse Feed)	
				H	Paper Type (TO-92)	
				B	Bag (TO-92)	

Note*: Output Voltage in 50mV steps is applied only for 2.85V type.

Accuracy of $\pm 1\%$ is available as custom-designed products.


■Packaging Information

●SOT-89





3

●SOT-223




●TO-92



■Marking

- SOT-89, SOT-223



- ① Represents the product name

DESIGNATOR	PRODUCT NAME
3	XC6203* * * * *

- ② Represents the type of regulator

DESIGNATOR			PRODUCT NAME
VOLTAGE=0.1~3.0V	VOLTAGE=3.1~6.0V	VOLTAGE=2.85V	
5	6	7	XC6203P* * * * *
2	3	4	XC6203E* * * * *

- ③ Represents the output voltage



DESIGNATOR	OUTPUT VOLTAGE (V)		DESIGNATOR	OUTPUT VOLTAGE (V)	
0	—	3.1	—	F	—
1	—	3.2	—	H	—
2	—	3.3	—	K	1.8
3	—	3.4	—	L	1.9
4	—	3.5	—	M	2.0
5	—	3.6	—	N	2.1
6	—	3.7	—	P	2.2
7	—	3.8	—	R	2.3
8	—	3.9	—	S	2.4
9	—	4.0	—	T	2.5
A	—	4.1	—	U	2.6
B	—	4.2	—	V	2.7
C	—	4.3	—	X	2.8
D	—	4.4	—	Y	2.9
E	—	4.5	—	Z	3.0
					4.6
					4.7
					4.8
					4.9
					5.0
					5.1
					5.2
					5.3
					5.4
					5.5
					5.6
					5.7
					5.8
					2.85
					6.0
					—

- ④ Denotes the production lot number

0 to 9, A to Z repeated(G,I,J,O,Q,W excepted)

●TO-92

3



① Represents the type of regulator

DESIGNATOR	PRODUCT NAME
P	XC6203P*****
E	XC6203E*****

②③④ Represents the output voltage

DESIGNATOR			VOLTAGE (V)	VOLTAGE ACCURACY(%)	PRODUCT NAME
②	③	④			
3	3	2	3.3	±2	XC6203*33***
5	0	2	5.0	±2	XC6203*50***
2	8	A	2.85	±2	XC6203*28A**

⑤ Represents a least significant digit of the produced year


DESIGNATOR	PRODUCED YEAR
0	2000
1	2001

⑥ Denotes the production lot number


0 to 9, A to Z repeated(G.I.J.O.Q.W excepted)

Note: Character inversion is not used

Block Diagram



XC6203E



XC6203P

Absolute Maximum Ratings

Ta=25°C

PARAMETER	SYMBOL	RATINGS	UNITS
Input Voltage	VIN	12	V
Output Current	IOUT	500	mA
Output Voltage	VOUT	VSS-0.3~VIN+0.3	V
Power Dissipation	SOT-89	500	mW
	SOT-223	1,200 (NOTE)	
	TO-92	300	
Operating Ambient Temperature	Topr	-40~+85	°C
Storage Temperature	Tstg	-40~+125	°C

Note: Circuits board mounting : Double-sided board

■ Electrical Characteristics

XC6203X182 V_{OUT(T)}=1.8V (Note 1)

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT(E)} (Note2)	V _{IN} =2.8V I _{OUT} =40mA	1.764	1.800	1.836	V
Maximum Output Current	I _{OUTmax}	V _{IN} =2.8V V _{OUT} ≥V _{OUT(E)} × 0.90	400			mA
Load Regulation	ΔV _{OUT}	V _{IN} =2.8V 1mA≤I _{OUT} ≤200mA		40	100	mV
Dropout Voltage (Note3)	V _{dif1}	I _{OUT} =100mA		200	300	mV
	V _{dif2}	I _{OUT} =200mA		400	600	
Supply Current	I _{SS}	V _{IN} =2.8V		8.0	16.0	μA
Line Regulation	ΔV _{OUT} ΔV _{IN} • ΔV _{OUT}	I _{OUT} =40mA 2.8V≤V _{IN} ≤8.0V		0.2	0.3	%/V
Input Voltage	V _{IN}				8	V
Output Voltage Temperature Characteristics	ΔV _{OUT} ΔT _{opr} • V _{OUT}	I _{OUT} =40mA -40°C≤T _{opr} ≤85°C		±100		ppm /°C
Short Circuit Current (XC6203P Series Only)	I _{lim}	V _{IN} =2.8V V _{OUT} =0V		60		mA

XC6203X252 V_{OUT(T)}=2.5V (Note 1)

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT(E)} (Note2)	V _{IN} =3.5V I _{OUT} =40mA	2.450	2.500	2.550	V
Maximum Output Current	I _{OUTmax}	V _{IN} =3.5V V _{OUT} >V _{OUT(E)} × 0.93	400			mA
Load Regulation	ΔV _{OUT}	V _{IN} =3.5V 1mA≤I _{OUT} ≤200mA		40	100	mV
Dropout Voltage (Note3)	V _{dif1}	I _{OUT} =100mA		170	250	mV
	V _{dif2}	I _{OUT} =200mA		320	500	
Supply Current	I _{SS}	V _{IN} =3.5V		8.0	16.0	μA
Line Regulation	ΔV _{OUT} ΔV _{IN} • ΔV _{OUT}	I _{OUT} =40mA 3.5V≤V _{IN} ≤8.0V		0.2	0.3	%/V
Input Voltage	V _{IN}				8	V
Output Voltage Temperature Characteristics	ΔV _{OUT} ΔT _{opr} • V _{OUT}	I _{OUT} =40mA -40°C≤T _{opr} ≤85°C		±100		ppm /°C
Short Circuit Current (XC6203P Series Only)	I _{lim}	V _{IN} =3.5V V _{OUT} =0V		60		mA

XC6203X302 V_{OUT(T)}=3.0V ^(Note 1)

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT(E)} ^(Note2)	V _{IN} =4V I _{OUT} =40mA	2.940	3.000	3.060	V
Maximum Output Current	I _{OUTmax}	V _{IN} =4V V _{OUT} ≥V _{OUT(E)} × 0.96	400			mA
Load Regulation	Δ V _{OUT}	V _{IN} =4V 1mA≤I _{OUT} ≤200mA		40	100	mV
Dropout Voltage ^(Note3)	V _{dif1}	I _{OUT} =100mA		150	220	mV
	V _{dif2}	I _{OUT} =200mA		300	420	
Supply Current	I _{SS}	V _{IN} =4V		8.0	16.0	μA
Line Regulation	Δ V _{OUT} Δ V _{IN} • Δ V _{OUT}	I _{OUT} =40mA 4V≤V _{IN} ≤8.0V		0.2	0.3	%/V
Input Voltage	V _{IN}				8	V
Output Voltage	Δ V _{OUT} Δ T _{opr} • V _{OUT}	I _{OUT} =40mA -40°C≤T _{opr} ≤85°C		±100		ppm /°C
Short Circuit Current (XC6203P Series Only)	I _{lim}	V _{IN} =4V V _{OUT} =0V		60		mA

XC6203X332 V_{OUT(T)}=3.3V ^(Note 1)

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT(E)} ^(Note2)	V _{IN} =4.3V I _{OUT} =40mA	3.234	3.300	3.366	V
Maximum Output Current	I _{OUTmax}	V _{IN} =4.3V V _{OUT} ≥V _{OUT(E)} × 0.96	400			mA
Load Regulation	Δ V _{OUT}	V _{IN} =4.3V 1mA≤I _{OUT} ≤200mA		40	100	mV
Dropout Voltage ^(Note3)	V _{dif1}	I _{OUT} =100mA		150	220	mV
	V _{dif2}	I _{OUT} =200mA		300	420	
Supply Current	I _{SS}	V _{IN} =4.3V		8.0	16.0	μA
Line Regulation	Δ V _{OUT} Δ V _{IN} • Δ V _{OUT}	I _{OUT} =40mA 4.3V≤V _{IN} ≤8.0V		0.2	0.3	%/V
Input Voltage	V _{IN}				8	V
Output Voltage	Δ V _{OUT} Δ T _{opr} • V _{OUT}	I _{OUT} =40mA -40°C≤T _{opr} ≤85°C		±100		ppm /°C
Short Circuit Current (XC6203P Series Only)	I _{lim}	V _{IN} =4.3V V _{OUT} =0V		60		mA

XC6203X502 VOUT(T)=5.0V (Note 1)

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	VOUT(E) (Note2)	VIN=6.0V IOUT=40mA	4.900	5.000	5.100	V
Maximum Output Current	IOUTmax	VIN=6.0V VOUT≥VOUT(E) × 0.96	400			mA
Load Regulation	Δ VOUT	VIN=6.0V 1mA≤IOUT≤200mA		40	100	mV
Dropout Voltage (Note3)	Vdif1	IOUT=100mA		100	180	mV
	Vdif2	IOUT=200mA		200	320	
Supply Current	I _{SS}	VIN=6.0V		10.0	20.0	μA
Line Regulation	$\frac{\Delta \text{VOUT}}{\Delta \text{VIN} \cdot \Delta \text{VOUT}}$	IOUT=40mA 6.0V≤VIN≤8.0V		0.2	0.3	%/V
Input Voltage	VIN				8	V
Output Voltage	$\frac{\Delta \text{VOUT}}{\Delta \text{Topr} \cdot \text{VOUT}}$	IOUT=40mA -40°C≤Topr≤85°C		±100		ppm /°C
Short Circuit Current (XC6203P Series Only)	I _{lim}	VIN=6.0V VOUT=0V		60		mA

Note : 1. Vout(T) = Specified Output Voltage.


2. Vout(E) = Effective Output Voltage (i.e. the output voltage when "Vout(T)+1.0V" is provided at the VIN pin while maintaining a certain Iout value).

3. Vdif = VIN1 - VOUT1

4. VOUT1 = A voltage equal to 98% of the output voltage when "Vout(T)+1.0V" is input.e

5. VIN1 = The input voltage when VOUT1 is output following a gradual decrease in the input voltage.


■ Typical Application Circuit




■Typical Performance Characteristics

●XC6203E182PR


(1) OUTPUT VOLTAGE vs. OUTPUT CURRENT




(2) OUTPUT VOLTAGE vs. INPUT VOLTAGE




(3) DROPOUT VOLTAGE vs. OUTPUT CURRENT




(4) SUPPLY CURRENT vs. INPUT VOLTAGE




(5) OUTPUT VOLTAGE vs. AMBIENT TEMPERATURE




(6) SUPPLY CURRENT vs. AMBIENT TEMPERATURE




(7) INPUT TRANSIENT RESPONSE




(8) LOAD TRANSIENT RESPONSE




XC6203E182PR (1.8V)



(9) RIPPLE REJECTION RATE




XC6203E182PR (1.8V)




● XC6203E252PR


(1) OUTPUT VOLTAGE vs. OUTPUT CURRENT




(2) OUTPUT VOLTAGE vs. INPUT VOLTAGE




(3) DROPOUT VOLTAGE vs. OUTPUT CURRENT




(4) SUPPLY CURRENT vs. INPUT VOLTAGE





(5) OUTPUT VOLTAGE vs. AMBIENT TEMPERATURE





(6) SUPPLY CURRENT vs. AMBIENT TEMPERATURE





(7) INPUT TRANSIENT RESPONSE



(8) LOAD TRANSIENT RESPONSE




(9) RIPPLE REJECTION RATE



●XC6203E332PR


(1) OUTPUT VOLTAGE vs. OUTPUT CURRENT

XC6203E332PR (3.3V)




(2) OUTPUT VOLTAGE vs. INPUT VOLTAGE

XC6203E332PR (3.3V)




(3) DROPOUT VOLTAGE vs. OUTPUT CURRENT

XC6203E332PR (3.3V)




(4) SUPPLY CURRENT vs. INPUT VOLTAGE

XC6203E332PR (3.3V)




(5) OUTPUT VOLTAGE vs. AMBIENT TEMPERATURE

XC6203E332PR (3.3V)





(6) SUPPLY CURRENT vs. AMBIENT TEMPERATURE



XC6203E332PR (3.3V)





(7) INPUT TRANSIENT RESPONSE



(8) LOAD TRANSIENT RESPONSE




(9) RIPPLE REJECTION RATE



●XC6203E502PR


(1) OUTPUT VOLTAGE vs. OUTPUT CURRENT

XC6203E502PR (5.0V)




(2) OUTPUT VOLTAGE vs. INPUT VOLTAGE

XC6203E502PR (5.0V)




(3) DROPOUT VOLTAGE vs. OUTPUT CURRENT

XC6203E502PR (5.0V)




(4) SUPPLY CURRENT vs. INPUT VOLTAGE

XC6203E502PR (5.0V)




(5) OUTPUT VOLTAGE vs. AMBIENT TEMPERATURE

XC6203E502PR (5.0V)





(6) SUPPLY CURRENT vs. AMBIENT TEMPERATURE

XC6203E502PR (5.0V)





(7) INPUT TRANSIENT RESPONSE





3

(8) LOAD TRANSIENT RESPONSE




(9) RIPPLE REJECTION RATE




(10) OUTPUT VOLTAGE vs. OUTPUT CURRENT


XC6203P182 (1.8V)



XC6203P252 (2.5V)



XC6203P332 (3.3V)



XC6203P502 (5.0V)

