

UT2102C

Digital Storage Oscilloscope Product

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

| Feature | UT2102C |
|---------------------------------|-----------------------------------------------------------------------------------|
| Bandwidth | 100 MHz |
| Rise Time | ≤3.5 ns |
| Sample Range | 500MS/s ~ 1GS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 1M |
| Sample Rate | Real time 500MS/s ~ 1GS/s, Equivalent: 25GS/s |
| Scan Time Base | 5ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host and RS-232C, Optional: LAN |
| Mathematics | Add, Subtract, Divide, Reverse and FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---------------------------------------------------------------|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey, White and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm (wide) x 150mm (high) x 130mm (deep) |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 455 x 430 x 280mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 11kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)